



CHARLOTTE DEP CON 134.75 257.2 AWOS-3 119.675	RNAV 1 - DME/DME/IRU or GPS.	TOP ALTITUDE: 3000
	RADAR required.	

TAKEOFF MINIMUMS

Rwy 5: Standard.
Rwy 23: 300-1½ or standard with minimum climb of 308'/NM to 1200.



- NOTE: Turbojet only.
- NOTE: If unable to accept climb rates, advise ATC on initial contact.
- NOTE: Transponder code will be issued via PDC or CLT CLNC DEL.
- NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.



NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 5: Climb on heading 063° to 2000 before proceeding on course for vectors to GINNN, thence. . .
TAKEOFF RUNWAY 23: Climb on heading 243° to 2800 before turning left for vectors to GINNN, thence. . .
. . .on track 255° to ESTRR, then on IPTAY Transition. Maintain 3000, expect filed altitude 10 minutes after departure.
IPTAY TRANSITION (ESTRR8.IPTAY)

SE-2, 29 OCT 2026 to 26 NOV 2026

SE-2, 29 OCT 2026 to 26 NOV 2026