


APP CRS	Rwy Ldg	5002
093°	TDZE	790
	Apt Elev	790

RNAV (GPS) RWY 9

BULT FLD (C56)

NA DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. Use Lansing Muni altimeter setting; when not received, use Chicago Midway Intl altimeter setting and increase all MDA 40 feet. Procedure NA at night.	MISSED APPROACH: Climbing right turn to 2600 direct EON VORTAC and hold.
---	--

AWOS-AV 119.125	IGQ AWOS-3PT 124.925	CHICAGO CENTER 132.5 284.7	UNICOM 123.0 (CTAF)
--------------------	-------------------------	-------------------------------	------------------------



4 NM Holding Pattern				2600	EON
HOSIX				5002 X 75 → 0.4% UP 0	
AGREE				RW09	
3.04° TCH 40				1620	
SEFOB 2.5 NM to RW09				RW09	
6.1 NM				2.1 NM	
2.5 NM					
CATEGORY	A	B	C	D	
LNAV MDA	1220-1	430 (500-1)	1220-1¼ 430 (500-1¼)	NA	
CIRCLING	1260-1 470 (500-1)	1400-1½ 610 (700-1½)	1400-1¾ 610 (700-1¾)	NA	

URL Rwy 9-27