

LOC/DME I-PGV	APP CRS	Rwy Ldg
110.7	197°	6505
Chan 44		TDZE 25
		Apt Elev 26

ILS Y or LOC Y RWY 20

PITT-GREENVILLE (PGV)



ADF required. VDP NA with Washington altimeter setting. When local altimeter setting not received use Washington altimeter setting and increase S-ILS 20 DA to 298 feet; increase all MDAs 60 feet and S-LOC 20 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. For inop ALS when using Washington altimeter setting, increase S-ILS 20 all Cats visibility ¾ SM, and S-LOC 20 visibility Cat A/B ¼ SM. Inop table does not apply to S-ILS all Cats. Rwy 20 helicopter visibility reduction below ¾ SM NA. For inop ALS, increase S-LOC 20 visibility Cat A/B ¼ SM, Cat C/D ¾ SM.

NA


MALSR
AS

MISSED APPROACH: Climb to 800 then climbing right turn to 1600 direct AQE NDB and hold.

AWOS-3PT 128.425	WASHINGTON CENTER 123.85 279.65	UNICOM 122.8 (CTAF) 1
----------------------------	---	---------------------------------



CATEGORY	A	B	C	D
S-ILS 20		257-¾ 231 (300-¾)		
S-LOC 20		420-¾ 394 (400-¾)		
CIRCLING	600-1 574 (600-1)	620-1 594 (600-1)	700-2 674 (700-2)	800-2½ 774 (800-2½)



SE-2, 29 OCT 2026 to 26 NOV 2026

SE-2, 29 OCT 2026 to 26 NOV 2026