

MILCOM 2016

SECURE COMMUNICATIONS AT THE SPEED OF CYBER

Decompiled Loop Recovery

Suresh C. Kothari
Richardson Professor
Department of Electrical and Computer Engineering

Ben Holland, Iowa State University

Acknowledgement: Team members at Iowa State University and EnSoft, DARPA contracts FA8750-12-2-0126 & FA8750-15-2-0080

BALTIMORE, MD • NOVEMBER 1–3, 2016

Motivation for Recovering Loops

- Most of the execution time is spent in loops
- 90/10 law
 - 90% of the time is spent in 10% of the code
 - 10% of the time is spent in the remaining 90% of the code

Challenge

- In compiled code high-level source constructs such as *for loops* and *while loops* do not exist.
 - Low-level code consists of goto's and labels

Goal: Identify loops in Control Flow Graphs (CFGs)

Loop Definition

A loop in the CFG:

- Has a set of child nodes (basic blocks)
- A loop has a *loop header* such that
 - Control to all child nodes in the loop always goes through the loop header
 - Has a back edge from one of its child nodes to the loop header

Remember

- Node X *dominates* node Y if all paths from the entry node to Y go through X
- A *depth-first search* of a graph starts at the root (CFG entry node) and explores as far as possible along each branch before backtracking.

Loop Recovery Intuitions

- Header of a loop dominates all child nodes in loop body
- Back edges are edges whose heads dominate their tails
 - An edge $X \rightarrow Y$ such that Y dominates X
- Loop identification is essentially back edge identification

Loop Recovery Algorithm

foreach node H in dominator tree

 foreach node N such that \exists an edge $N \rightarrow H$

 define loop:

 header = H

 back edge = $N \rightarrow H$


 loop body = nodes found in a backwards
 DFS traversal from N to H

Loop Recovery Algorithm

- DLI algorithm described in [1] presents an efficient algorithm for identifying loops in irreducible graphs.

[1] Wei, Tao, et al. "A new algorithm for identifying loops in decompilation." International Static Analysis Symposium. Springer Berlin Heidelberg, 2007.

Loop Call Graph



Nodes:


- Methods containing loops (blue)
- Methods reaching methods containing loops (white)

Edges:

- Call relationships
- Color attributes to show placement of call site in loop



Called Inside Loop



Called Outside Loop

