

Mongoose Schema Definition for Test Scripts Database

| SCHEMA NAME | FIELD NAME | CONTENT | TYPE/SUB-PROPERTIES | DOMAIN / RANGE | FORMAT | REQUIRED | UNIQUE |
|--------------------|--------------------|--|---|--|--|----------|--------|
| testScript | _id | Test script ID | ObjectId | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| | name | Test script name (as entered) | String | Any string ≤ 100 characters | xxxxxxxxxxx... "01. Sales Process" | Y | Y |
| | name_lowercase | Test script name (lowercase) | String | "name" but without caps Note that test script names are <i>not</i> considered case sensitive. Therefore, "Test" and "test" will be considered the equivalent, and only one may be used to create a test script. | xxxxxxxxxxx... "01. sales process" | Y | Y |
| | createdAt | Timestamp recording when test script was created | Date | Automatically generated | Date 2022-05-03T01:51:49.873+00:d00 | Y (auto) | N |
| | updatedAt | Timestamp recording when test script was last updated | Date | Automatically generated | Date 2022-05-03T01:51:49.873+00:00 | Y (auto) | N |
| | owner | Test script owner | { firstName: String, lastName: String } | NA | Object { firstName: "Benjie", lastName: "Friedman" } | Y | N |
| | description | Test script description | String | Any string ≤ 1000 characters | xxxxxxxxxxx... "This string covers the following units..." | Y | N |
| | primaryWorkstream | Test script primary workstream | String | Any string ≤ 100 characters | xxxxxxxxxxx... "Sales and PM" | N | N |
| step | _id | Step ID | ObjectId | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| | testScriptID | ID of test script to which this step belongs | ObjectId | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| | number | Step number | Number | 1 to number of steps (incremental) | ## 12 | Y | Y |
| | description | Step description | String | Any string ≤ 1000 characters | xxxxxxxxxxxxxxxxxxxxx... "Log in to Epicor" | Y | N |
| | dataInputtedByUser | Data to be input by user for the step | String | Any string ≤ 1000 characters | xxxxxxxxxxxxxxxxxxxxx... "username, password" | N | N |
| stepResponse | _id | Step response ID | ObjectID | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| | sessionID | ID of session to which this step response belongs | ObjectId | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | N |
| | stepID | ID of step to which this response belongs | ObjectID | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| stepResponseSchema | comments | The tester"s comments about the step | String | Any string ≤ 1000 characters | xxxxxxxxxxxxxxxxxxxxx... "Page would not load properly..." | N | N |
| | pass | Whether the step has passed, passed with minor issues, or failed | String | "P" (passed), "I" (passed with minor issues), "F" (failed) | X "P" | Y | N |

| SCHEMA NAME | FIELD NAME | CONTENT | TYPE/SUB-PROPERTIES | DOMAIN / RANGE | FORMAT | REQUIRED | UNIQUE |
|---------------------------------------|----------------------|---|---|---|---|----------|--------|
| stepResponseSchema (cont'd) | uploadedImage | Information pertaining to an uploaded image for the step, if it exists | { imageName: String, imageURL: String } | NA | { imageName: "someImage.jpeg", imageURL: "https://firebasestorage.googleapis.com/v0/b/luni-ko-test-scripts-app.appspot.com/o/..." } | | |
| testingSession | _id | Testing session ID | ObjectId | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| | testScriptID | ID of test script for which this testing session was conducted | ObjectId | Automatically generated | ObjectId("xxxxxxxxxxx...") ObjectId("626c53d5911a2a499cf90b64") | Y (auto) | Y |
| | tester | The tester performing the testing session | { firstName: String, lastName: String } | NA | Object { firstName: "Lindsey", lastName: "Van der Lee" } | Y | N |
| | createdAt | Timestamp recording when testing session was submitted | Date | Automatically generated | Date 2022-05-03T01:51:49.873+00:d00 | Y (auto) | N |
| | updatedAt | Timestamp recording when testing session was last updated | Date | Automatically generated | Date 2022-05-03T01:51:49.873+00:00 | Y (auto) | N |
| | pass | Whether or not the testing session has passed. If any individual step has failed, then the session must be marked as a fail | Boolean | 0/1 (true/false) | true/false true | Y | N |
| | complete | Whether or not the testing session is complete. If a tester has not responded to all steps before submitting the session, said session is marked as <i>not</i> complete | Boolean | 0/1 (true/false) default = false | true/false true | Y | N |
| | stoppedTestingAtStep | If a testing session is submitted before all steps have been completed, this attribute records the step at which the session was prematurely terminated | Number | 0-Number.MAX_SAFE_INTEGER | # 5 | N | N |
| | failedSteps | An array of numbers representing the steps that have been marked as "failed" by the tester | Array | NA | [#, #, #,...] [1, 6, 10] | N | N |
| | stepsWithMinorIssues | An array of numbers representing the steps that have been marked as "passed with minor issues" by the tester | Array | Na | [#, #, #,...] [1, 6, 10] | N | N |