

Master Thesis Presentation

Comparison of Disparity Algorithms for Stereoscopic Videos

Ben John

May 25, 2016

University of Mannheim, Department of Praktische Informatik IV

Table of contents

1. Motivation
2. Foundations
3. Implementation
4. Evaluation
5. Conclusion

Motivation

- Depth-estimation via camera settings
- Kinect (sunlight)
- 3DTV (remapping)

Foundations

Epipolar geometry




Figure 1: Epipolar geometry¹

¹Source (accessed 02/2016): <https://en.wikipedia.org>.

Epipolar geometry




Figure 2: Epipolar geometry after image rectification²

²Source (accessed 02/2016): <https://en.wikipedia.org>.

Constraints

- Epipolar
- Uniqueness
- Continuity
- Ordering
- Limit
- Lambertian

Classification

- Local methods
 - Area matching
 - Feature matching
- Global methods
 - Dynamic programming
 - Graph cuts
 - Belief propagation

- Local methods
 - Area matching
 - Feature matching
- Global methods
 - Dynamic programming
 - Graph cuts
 - Belief propagation

Energy function

$$E(d) = E_{data}(d) + \lambda E_{smooth}(d)$$

1. Computing of matching cost
2. Save values in disparity space image
3. Aggregation of cost values
4. Disparity refinement

Matching cost


- Penalty
- Cost for having dissimilarities
- Optimum = 0

- Penalty
- Cost for having dissimilarities
- Optimum = 0

Sum of absolute differences

$$\text{SAD} = \sum_{i,j \in U} |I_1(x_L + i, y_L + j) - I_2(x_R + i, y_R + j)|$$

Disparity space image



Simple block-matching






Figure 4: Illustration of block matching along a scanline.


Example for stereo image pair



(a) left input image



(b) right input image




(c) ground-truth data

Figure 5: Tsukuba benchmark stereo image pair of the University of Tsukuba [1].

Implementation

Overview



Spatiotemporal stereo matcher

Algorithm 1: CREATEDISPARITYSPACEIMAGE

Input: I_L , I_R , d_{max} , $wSize$

Output: C

```
1  $step \leftarrow (wSize - 1)/2$ 
2  $C \leftarrow \text{CREATEMATRIX}(\text{COLS}(I_L), \text{ROWS}(I_L), d_{max})$ 
3 for  $t \leftarrow 0$  to  $\text{IMAGES}(I_L)$  do
4    $leftImage \leftarrow I_L(t)$ 
5    $rightImage \leftarrow I_L(t)$ 
6   for  $y \leftarrow 0 + step$  to  $\text{ROWS}(I_L(0)) - step$  do
7     for  $x \leftarrow 0 + step$  to  $\text{COLS}(I_L(0)) - step - d_{max}$  do
8       for  $d \leftarrow 0$  to  $d_{max}$  do
9          $rect_L \leftarrow \text{RECT}\{x - step, y - step, wSize, wSize\}$ 
10         $rect_R \leftarrow \text{RECT}\{x + d - step, y - step, wSize, wSize\}$ 
11         $window_L \leftarrow leftImage(rect_L)$ 
12         $window_R \leftarrow rightImage(rect_R)$ 
13         $C(x, y, t, d) \leftarrow \text{MATCHINGCOST}(window_L, window_R)$ 
14 return  $C$ 
```

Algorithm 2: GETDISPARITYMAP

Input: C, t

Output: *DisparityMap*

```
1 DisparityMap  $\leftarrow$  CREATEMATRIX(COLS( $C$ ), ROWS( $C$ ))
2 for  $t \leftarrow 0$  to FRAMES( $C$ ) do
3   for  $y \leftarrow 0$  to ROWS( $C$ ) do
4     for  $x \leftarrow 0$  to COLS( $C$ ) do
5        $Cost \leftarrow \frac{1}{4} C(x, y, f_0) + \frac{2}{4} C(x, y, f_1) + \frac{1}{4} C(x, y, f_2)$ 
6        $DisparityMap(x, y) \leftarrow$  BESTMATCH( $Cost$ )
7 return DisparityMap
```

Masking modes

- Non-occluded mask
- Depth-discontinuity mask
- Textureless mask
- Saliency mask




Figure 7: Frame of book sequence

Masking modes

- Non-occluded mask
- Depth-discontinuity mask
- Textureless mask
- Saliency mask




Figure 7: Ground-truth companion

- Non-occluded mask
- Depth-discontinuity mask
- Textureless mask
- Saliency mask




Figure 7: Depth-discontinuity at object borders

Masking modes

- Non-occluded mask
- Depth-discontinuity mask
- Textureless mask
- Saliency mask



Figure 7: Non-occluded mask

Masking modes

- Non-occluded mask
- Depth-discontinuity mask
- Textureless mask
- Saliency mask




Figure 7: Textureless regions

Masking modes

- Non-occluded mask
- Depth-discontinuity mask
- Textureless mask
- Saliency mask



Figure 7: Salient pixels



Figure 8: Flow of the image diminisher.

Image diminisher




Figure 9: Flow of FFmpeg as image diminisher.

- Visualization of evaluation engine
- Written in Node.js
- Displaying some statistics

Demo

Evaluation

- Targeting videos (mean)
- Looking for outliers
- Masking modes
- Video compression

- Cambridge
- SVDDD (high-resolution)

- **Percentage of bad matching pixels**

$$\frac{1}{n} \sum_{x,y=0} (|d_a(x, y) - d_e(x, y)| > \delta_t)$$

- **RMS-Error**

$$\sqrt{\frac{1}{n} \sum_{x,y=0} (d_a(x, y) - d_e(x, y))^2}$$

	10 CVSM	11 SNSM	12 SNTU	13 SNTW
S1	32.61%	8.72%	10.07%	9.65%
S2	25.64%	11.79%	8.76%	8.90%
S3	13.26%	6.08%	8.71%	7.29%
S4	38.96%	12.98%	11.15%	11.26%
S5	8.60%	0.93%	4.54%	2.15%
Ø	23,81%	8,10%	8,66%	7,85%

Table 1: Result table for comparison of own implementation

Results




Figure 10: Depth-discontinuity mask applied on the book sequence.

Results




Figure 11: Chart of textureless region mask applied on the tunnel sequence.




Figure 12: Chart of general outliers in a sequence.




Figure 13: Examples for general outliers in the book sequence. The disparity maps are computed with the (3) ELAS algorithm.

Results







Figure 14: Chart of the impact of different σ^2 values for additive Gaussian noise on the result of disparity algorithms focusing on $P_{noc,1px}$.



(a) (3) ELAS outliers



(b) (5) MRF GC Swap
outliers



(c) (13) SNSM STW

Figure 15: Example of computed disparity maps with video compression. CRF is set to 40. Frame 23 of the tanks scene.

Results




Figure 16: Chart of the impact of different CRF values for H.265 video compression on the result of disparity algorithms focusing on $PBMP_{noc,1px}$.

Results






Figure 17: Comparison of the runtime of different disparity algorithms with both datasets, Cambridge and SVDDD



(a) Negative disparity



(b) Only positive disparity

Figure 18: Comparison of computed disparity maps regarding negative disparity.




Figure 19: Performance of SVDDD rabbit scene

	1	2	3	4	5	6
02-rabbit-neg	58.62%	61.51%	59.99%	60.58%	57.12%	57.13%
02-rabbit	1.68%	4.31%	2.98%	3.82%	0.65%	0.68%
03-apple	1.69%	4.10%	3.11%	3.44%	0.63%	0.65%
\emptyset (w/o neg)	1.69%	4.21%	3.05%	3.63%	0.64%	0.67%

Table 2: Result table for general performance of SVDDD (PBMP_{noc,1px})

Conclusion

- surprise candidate ELAS
- camera noise model
- SVDDD dataset
- Salient mask varies a bit
- Immense runtime differences
- Possible outliers in a scene

Contributions

- PFM file reader
- Generic Disparity Interface
- Disparity Executioner
- Evaluation Engine
- Mask creator
- Image diminisher
- Python scripts
- Web result viewer
- Benchmark results
- Skeleton for stereo matcher with separated dsi
- Spatiotemporal stereo matcher

- Motion saliency
- Enhancement of spatiotemporal matcher
- Holistic evaluation suite for modern disparity algorithm comparison

- Multi-view datasets
- High-resolution datasets
- Optical flow regarding spatiotemporal consistency
- Humans depth experience with neuronal networks

Questions?



S. Martull, M. Peris, and K. Fukui.

Realistic CG stereo image dataset with ground truth disparity maps.

In *ICPR workshop TrakMark2012*, volume 111, pages 117–118, 2012.