

SERA FREQUENCY UTILIZATION PLAN for 50 - 54 MHz	
52 MHz Standard FM Repeater Pairs (39) 1 MHz Split	Page1
51 MHz Standard FM Repeater Pairs (15) 500 Khz Split	Page 1
51 MHz Standard FM Repeater Pairs (4) 500 Khz Split	Page 2
52 MHz Duplex Digital & Packet Repeaters (5) 1 MHz Split	Page 2
Voice FM Simplex Frequencies	Page 2
Digital & Packet FM Simplex Frequencies	Page 2
Frequency Spectrum Plan for 50 MHz	Page 2

DUPLEX VOICE FM REPEATERS: (Standard Pairs)

39 Repeater Pairs, 20 KHz channels, 20 kHz spacing, 1 MHz split – in/out

52.010 – 53.010	52.030 – 53.030	52.050 – 53.050	52.070 – 53.070	52.090 – 53.090
52.110 – 53.110	52.130 – 53.130	52.150 – 53.150	52.170 – 53.170	52.190 – 53.190
52.210 – 53.210	52.230 – 53.230	52.250 – 53.250	52.270 – 53.270	52.290 – 53.290
52.310 – 53.310	52.330 – 53.330	52.350 – 53.350	52.370 – 53.370	52.390 – 53.390
52.410 – 53.410	52.430 – 53.430	52.450 – 53.450	52.470 – 53.470	52.710 – 53.710
52.730 – 53.730	52.750 – 53.750	52.770 – 53.770	52.790 – 53.790	52.810 – 53.810
52.830 – 53.830	52.850 – 53.850	52.870 – 53.870	52.890 – 53.890	52.910 – 53.910
52.930 – 53.930	52.950 – 53.950	52.970 – 53.970	52.990 – 53.990	

15 Repeater Pairs: 20 Khz channels, 20 kHz spacing, 500 Khz split – in/out

51.200 – 51.700	51.220 – 51.720	51.240 – 51.740	51.260 – 51.760	51.280 – 51.780
51.300 – 51.800	51.320 – 51.820	51.340 – 51.840	51.360 – 51.860	51.380 – 51.880
51.400 – 51.900	51.420 – 51.920	51.440 – 51.940	51.460 – 51.960	51.480 – 51.980

4 Repeater Pairs: 20 Khz Channels, 20 KHz spacing, 500 KHz split – in/out

51.120 – 51.620	51.140 – 51.640	51.160 – 51.660	51.180 – 51.680
-----------------	-----------------	-----------------	-----------------

DUPLEX FM PACKET/DIGITAL REPEATERS:

5 Repeater Pairs, 20 Khz channels, 20 KHz spacing, 1 MHz split – in/out

52.610 – 53.610	52.630 – 53.630	52.650 – 53.650	52.670 – 53.670	52.690 – 53.690
-----------------	-----------------	-----------------	-----------------	-----------------

VOICE FM SIMPLEX FREQUENCIES: 12 Simplex Channels

51.500	51.520	51.540	51.560	51.580	51.600
52.490	52.510	52.525*	52.550	52.570	52.590

* 52.525 is the National FM Voice Simplex Calling Frequency

PACKET/DIGITAL FM SIMPLEX FREQUENCIES:

53.490	53.510	53.530	53.550	53.570	53.590
--------	--------	--------	--------	--------	--------

Frequency Spectrum Plan for 50-54 MHz

50.000 – 50.100 CW and Beacons (100 KHz)
50.060 – 50.080 Automatic Control Beacons (20 KHz)
50.100 – 50.600 SSB & AM (500 KHz)
50.125 SSB DX Calling Frequency
50.200 SSB National Calling Frequency
50.400 AM Calling Frequency
50.600 – 51.000 Experimental/Special Modes (400 KHz)
50.700 TTY Calling Frequency
50.800 – 50.980 Remote Control Model Radio Control (180 KHz)
51.000 – 51.100 Pacific DX Window (100 KHz)
51.100 – 52.000 FM Repeaters & Simplex, Voice & Packet/Digital
52.000 – 52.050 Pacific DX Window (50 KHz)
52.000 – 54.000 FM Repeaters & Simplex Voice & Packet/Digital

DOCUMENT MODIFICATION HISTORY:

The SERA Board of Directors revised the 6-Meter frequency utilization plan in February, 1996, in order to utilize the 51 MHz repeater sub-band and provide more spectrum for packet/digital operation. If there are any questions, contact your local Frequency Coordinator.

The SERA Board of Directors voted August 17, 2002, to eliminate the allocation for 2.51 MHz repeater pairs.

Approved version 08/02 HAHjr

