

SERA FREQUENCY UTILIZATION PLAN for 902 - 928 MHz	
902 – 927 MHz Itinerant (1) and Repeater Pairs (18)	Page1
902 – 927 MHz Alternate Repeater Pairs (6) for Part 15 Mitigation	Page 1
907/909 – 919/921 MHz Itinerant (2) and Repeater Pairs (27)	Page 2
Auxiliary Simplex Link Frequencies	Page 2
Auxiliary Duplex Link Frequency Pairs	Page 2
FM Voice Simplex Channels	Page 3
Digital Packet Simplex Channels	Page 3
Frequency Spectrum Plan for 902-928 MHz	Page 3

Itinerant Repeater Pair, 12.5 KHz channel / frequency spacing, 25 MHz Duplex in/out Reserved for itinerant and short term use during a special event or emergency with no formal coordination required. Trustees/Owners are encouraged to notify their local coordinator to inform them of system parameters and expected duration of use.

902.4875 - 927.4875

Standard FM Repeater Service: 18 pairs, 12.5 KHz channels / frequency spacing, 25 MHz split in/out

902.5125 - 927.5125	902.5250 - 927.5250	902.5375 - 927.5375
902.5500 - 927.5500	902.5625 - 927.5625	902.5750 - 927.5750
902.5875 - 927.5875	902.6000 - 927.6000	902.6125 - 927.6125
902.6250 - 927.6250	902.6375 - 927.6375	902.6500 - 927.6500
902.6625 - 927.6625	902.6750 - 927.6750	902.6875 - 927.6875
902.7000 - 927.7000	902.7125 - 927.7125	902.7250 – 927.7250

Additional Regular FM Repeater Service:

These additional pairs will normally be assigned *only when it has been determined that the pairs between 927.5125 and 927.7250 (shown above) are unusable due to local Part 15 device interference.*

902.0125 Rx 927.0125 Tx	902.0250 Rx 927.0250 Tx	902.0375 Rx 927.0375 Tx
902.0500 Rx 927.0500 Tx	902.0625 Rx 927.0625 Tx	902.0750 Rx 927.0750 Tx

Itinerant Repeater Pairs: 2 Repeater Pairs, 100 KHz spacing between channels, 12 MHz Duplex in/out. Reserved for *itinerant and short term use* during a special event or emergency with no formal coordination required. Trustees/Owners are encouraged to notify their local coordinator to inform them of system parameters and expected duration of use.

907.100 – 919.100 907.200 - 919.200

Standard FM Repeater Service: 27 Pairs, 100 KHz spacing between channels, 12 MHz split in/out

907.300 - 919.300	907.400 - 919.400	907.500 - 919.500
907.600 - 919.600	907.700 - 919.700	907.800 - 919.800
907.900 - 919.900	908.000 - 920.000	908.100 - 920.100
908.200 - 920.200	908.300 - 920.300	908.400 - 920.400
908.500 - 920.500	908.600 - 920.600	908.700 - 920.700
908.800 - 920.800	908.900 - 920.900	909.000 - 921.000
909.100 - 921.100	909.200 - 921.200	909.300 - 921.300
909.400 - 921.400	909.500 - 921.500	909.600 - 921.600
909.700 - 921.700	909.800 - 921.800	909.900 - 921.900

Auxiliary Simplex Link Frequencies: Specific *Vertical or Horizontal Antenna Polarization* Required
12.5 KHz spacing between channels

vertical 927.0125	horizontal 927.0250	vertical 927.0375	horizontal 927.0500
vertical 927.0625	horizontal 927.0750	vertical 927.0875	horizontal 927.1000
vertical 927.1125	horizontal 927.1250	vertical 927.1375	horizontal 927.1500
vertical 927.1625	horizontal 927.1750	vertical 927.1875	horizontal 927.2000
vertical 927.8000	horizontal 927.8125	vertical 927.8250	horizontal 927.8375
vertical 927.8500	horizontal 927.8625	vertical 927.8750	horizontal 927.8875
vertical 927.9000	horizontal 927.9125	vertical 927.9250	horizontal 927.9375
vertical 927.9500	horizontal 927.9625	vertical 927.9750	horizontal 927.9875

Auxiliary Duplex Link Frequency Pairs: 22 pairs, Specific *Vertical or Horizontal Antenna Polarization* Required, 12.5 KHz spacing between channels with 25 MHz Duplex in/out

vertical 902.2125 - 927.2125	horizontal 902.2250 - 927.2250	vertical 902.2375 - 927.2375
vertical 902.2500 - 927.2500	horizontal 902.2625 - 927.2625	vertical 902.2750 - 927.2750
vertical 902.2875 - 927.2875	horizontal 902.3000 - 927.3000	vertical 902.3125 - 927.3125
vertical 902.3250 - 927.3250	horizontal 902.3375 - 927.3375	vertical 902.3500 - 927.3500
vertical 902.3625 - 927.3625	horizontal 902.3750 - 927.3750	vertical 902.3875 - 927.3875
vertical 902.4000 - 927.4000	horizontal 902.4125 - 927.4125	vertical 902.4250 - 927.4250
vertical 902.4375 - 927.4375	horizontal 902.4500 - 927.4500	vertical 902.4625 - 927.4625
vertical 902.4750 - 927.4750		

FM Voice Simplex Channels

902.5000 927.5000

906.5000 (old national – retained under grandfather clause)

927.7500 (old SERA – retained under grandfather clause)

Digital Packet Simplex Channels

904.000 to 906.000 MHz - channel every 25 KHz

916.000 to 918.000 MHz - channel every 25 KHz

Frequency Spectrum Plan for 902-928 MHz

902.0000 – 902.2875 SSTV, FAX, ACSSB, Experimental

902.2125 – 902.4625 Auxiliary FM Duplex Link Input Frequency Pairs

902.4875 – 902.7250 FM Repeater Inputs & designated simplex (25 MHz split - 12.5 KHz spacing)

902.5000 - FM Simplex Calling Channel (1 of 2)

902.7375 – 903.0500 EME Exclusive

903.0700 – 903.0800 CW Beacons

903.1000 - CW, SSB Calling Frequency

903.4000 – 903.6000 Cross Band Linear Translator Inputs

903.6000 – 903.8000 Cross Band Linear Translator Outputs

903.8000 – 904.0000 Experimental Beacons Exclusive

904.0000 – 906.0000 Digital Communications

906.0000 – 907.0000 Narrow Band FM Simplex (grandfathered system - 25 KHz channels)

906.5000 - Old National Calling Frequency (grandfathered)

907.0000 – 910.0000 FM Repeater Inputs (12 MHz split - 100 KHz spacing)

910.0000 – 916.0000 ATV

916.0000 – 918.0000 Digital Communications

918.0000 – 919.0000 Narrow Band FM Control Links/Remote Bases

919.0000 – 922.0000 FM Repeater Outputs (12 MHz split - 100 KHz spacing)

927.0125 – 927.9875 Auxiliary Simplex & Link Frequencies

927.2125 – 927.4625 Auxiliary FM Duplex Link Input Frequency Pairs

927.4875 – 927.7250 FM Repeater Outputs & designated simplex (25 MHz split - 12.5 KHz spacing)

927.5000 - FM Simplex Calling Channel (2 of 2)

927.7375 – 927.7875 Old SERA FM Voice Simplex Channels (grandfathered)

922.0000 – 928.0000 Wideband Experimental, ATV, Simplex, Spread Spectrum

Previous edition as adopted by the SERA Board of Directors on 02/10/02 HAHjr
Official Amended Copy as adopted by the SERA Board of Directors on 08/16/03 HAHjr
Official Amended Copy as adopted by the SERA Board of Directors on 06/19/10 HAHjr

