

FIT2004

Algorithms and Data Structures

Ian Wern Han Lim
lim.wern.han@monash.edu

Referencing materials by
Nathan Compane, Aamir Cheema, Arun Konagurthu and Lloyd Allison



Faculty of Information Technology, Monash University

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act. Do not remove this notice

Ready?

Agenda

- Sorting Algorithms
 - Comparison based
 - Selection
 - Insertion
 - Non-comparison based (the IMBA ones)
 - Counting
 - Radix

Let us begin...

- We are back to sorting!
 - Bubble
 - Insertion
 - Selection
 - Merge
 - Quick

■ We are back to sorting!

- Bubble
- Insertion
- Selection
- Merge
- Quick



Janelle Shane @JanelleCShane · 14 Apr ✓

For example, there was an algorithm that was supposed to sort a list of numbers. Instead, it learned to delete the list, so that it was no longer technically unsorted.

💬 10

↻ 143

❤️ 635



- We are back to sorting!
 - Bubble
 - Insertion
 - Selection
 - Merge
 - Quick

- All of these are known as comparison based sorting.
Why?

- We are back to sorting!
 - Bubble
 - Insertion
 - Selection
 - Merge
 - Quick

- All of these are known as comparison based sorting.
Why? Because we compare between items to know if $a < b$ or $b > a$

- We are back to sorting!
 - Bubble
 - Insertion
 - Selection
 - Merge
 - Quick
- All of these are known as comparison based sorting.
Why? Because we compare between items to know if $a < b$ or $b > a$
- Now let us analyze them based on what we have learnt!

Questions?

Sorting

Selection Sort

- Correctness
- Complexity

Sorting

Selection Sort

- **Correctness**
 - Loop invariant
 - Termination
- **Complexity**
 - Time
 - Space

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - Termination
- Complexity
 - Time
 - Space

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - Termination

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - Termination

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```


Sorting

Selection Sort

- Correctness
 - Loop invariant
 - $\text{my_list}[0 \dots i-1]$ is sorted
 - $\text{my_list}[0 \dots i-1] \leq \text{my_list}[i \dots N]$
 - Termination

```
def selection_sort(my_list):
    for i in range(len(my_list)):
        minimum = i
        # find the minimum
        for j in range(i+1, len(my_list)):
            if my_list[minimum] > my_list[j]:
                minimum = j
        # swap
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - $\text{my_list}[0 \dots i-1]$ is sorted
 - $\text{my_list}[0 \dots i-1] \leq \text{my_list}[i \dots N]$
 - Termination

```
def selection_sort(my_list):
    for i in range(len(my_list)):
        minimum = i
        # find the minimum
        for j in range(i+1, len(my_list)):
            if my_list[minimum] > my_list[j]:
                minimum = j
        # swap
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - `my_list[0...i-1]` is sorted
 - `my_list[0...i-1] ≤ my_list[i...N]`
 - Termination
 - `i` and `j` always increment and both reach the end of the list

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - `my_list[0...i-1]` is sorted
 - `my_list[0...i-1] ≤ my_list[i...N]`
 - Termination
 - `i` and `j` always increment and both reach the end of the list
 - So why is it working then?

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
 - Loop invariant
 - `my_list[0...i-1]` is sorted
 - `my_list[0...i-1] ≤ my_list[i...N]`
 - Termination
 - `i` and `j` always increment and both reach the end of the list
 - So why is it working then?
 - `i` keep increment till `n` and we know from invariant `0...i-1` is sorted, thus we will sort the entire list!

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Space

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Space

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$
 - Worst = $O(N^2)$
 - Space

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```


Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - Space

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - Space

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - Space
 - $O(N)$ for the input list
 - Auxiliary?

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - Space
 - $O(N)$ for the input list
 - Auxiliary? $O(1)$

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - Space
 - $O(N)$ for the input list
 - Auxiliary? $O(1)$ **in place**

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - But what if I tell you comparing the items have a cost of $O(k)$
 - Like comparing between words, you need to compare the alphabets

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - But what if I tell you comparing the items have a cost of $O(k)$
 - Like comparing between words, you need to compare the alphabets
 - We know complexity is based on comparison $O(N^2)$ comparisons...

```
def selection_sort(my_list):  
    for i in range(len(my_list)):  
        minimum = i  
        # find the minimum  
        for j in range(i+1, len(my_list)):  
            if my_list[minimum] > my_list[j]:  
                minimum = j  
        # swap  
        my_list[i], my_list[minimum] = my_list[minimum], my_list[i]
```

Sorting

Selection Sort

- Correctness
- Complexity
 - Time
 - Best = $O(N^2)$ because no matter what we have to find the minimum and can't terminate earlier!
 - Worst = $O(N^2)$
 - But what if I tell you comparing the items have a cost of $O(k)$
 - Like comparing between words, you need to compare the alphabets
 - We know complexity is based on comparison $O(N^2)$ comparisons...
 - So our final complexity is $O(kN^2)$

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change
 - Is it stable?

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change
 - Is it stable? **No!** but **why?**

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change
 - Is it stable? **No!** but **why?**
 - [4a, 2, 3, 4b, 1]

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change
 - Is it stable? **No!** but **why?**
 - [4a, 2, 3, 4b, 1]
 - Minimum is 1, so we swap

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change
 - Is it stable? **No!** but **why?**
 - [4a, 2, 3, 4b, 1]
 - Minimum is 1, so we swap
 - [1, 2, 3, 4b, 4a]

Sorting

Selection Sort

- Correctness
- Complexity
- Stable?
 - Relative ordering doesn't change
 - Is it stable? **No!** but **why?**
 - [4a, 2, 3, 4b, 1]
 - Minimum is 1, so we swap
 - [1, 2, 3, 4b, 4a]
 - Now we see that 4a is behind 4b!

Questions?

Sorting

Insertion Sort

- Correctness
- Complexity

- Correctness
- Complexity

Problem 1. Write pseudocode for insertion sort, except instead of sorting the elements into non-decreasing order, sort them into non-increasing order. Identify a useful invariant of this algorithm.

- Correctness
- Complexity

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
 - Loop invariant
 - Termination
- Complexity

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
 - Loop invariant
 - Termination
 - Simple, I skip this
- Complexity

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

Sorting

Insertion Sort

- Correctness
 - Loop invariant
 - `my_list[0...i-1]` sorted
 - Termination
 - Simple, I skip this
- Complexity

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
- Complexity
 - Best
 - Worst

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```


- Correctness
- Complexity
 - Best $O(N)$ comparison
 - Each loop only look and compare with left item once
 - Worst

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
- Complexity
 - Best $O(N)$ comparison
 - Each loop only look and compare with left item once
 - Worst $O(N^2)$
 - Each loop keep look left, compare and swap till beginning of list

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

Sorting

Insertion Sort

- Correctness

- Complexity

- Best $O(N)$ comparison

- Each loop only look and compare with left item once

- Worst $O(N^2)$

- Each loop keep look left, compare and swap till beginning of list

- So if $O(k)$ is the comparison cost, when we have $O(kN^2)$ worst case!

```
def insertion_sort(my_list):
    for i in range(1, len(my_list)):
        key = my_list[i]
        j = i - 1
        # keep shifting to left if left is greater
        while j >= 0 and key < my_list[j]:
            my_list[j+1] = my_list[j]
            j = j - 1
        my_list[j+1] = key
```

Sorting

Insertion Sort

- Correctness

- Complexity

- Best $O(N)$ comparison

- Each loop only look and compare with left item once

- Worst $O(N^2)$

- Each loop keep look left, compare and swap till beginning of list

- So if $O(k)$ is the comparison cost, when we have $O(kN^2)$ worst case!
 - What about space?

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness

- Complexity

- Best $O(N)$ comparison

- Each loop only look and compare with left item once

- Worst $O(N^2)$

- Each loop keep look left, compare and swap till beginning of list

- So if $O(k)$ is the comparison cost, when we have $O(kN^2)$ worst case!

- What about space?

- $O(N)$ for the input list
 - $O(1)$ auxiliary cause it is in-place

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
- Complexity
- Stability

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
- Complexity
- Stability
 - Yes

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

- Correctness
- Complexity
- Stability
 - Yes
 - Don't swap if value is the same

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```


- Correctness
- Complexity
- Stability
 - Yes
 - Don't swap if value is the same
 - Most **shifting** will ensure stability

```
def insertion_sort(my_list):  
    for i in range(1, len(my_list)):  
        key = my_list[i]  
        j = i - 1  
        # keep shifting to left if left is greater  
        while j >= 0 and key < my_list[j]:  
            my_list[j+1] = my_list[j]  
            j = j - 1  
        my_list[j+1] = key
```

Questions?


Summary

Sorting

| | Best | Worst | Average | Stable? | In-place? |
|-----------------------|---------------|--------------------------------------|---------------|---------|-----------|
| Selection Sort | $O(N^2)$ | $O(N^2)$ | $O(N^2)$ | No | Yes |
| Insertion Sort | $O(N)$ | $O(N^2)$ | $O(N^2)$ | Yes | Yes |
| Heap Sort | $O(N \log N)$ | $O(N \log N)$ | $O(N \log N)$ | No | Yes |
| Merge Sort | $O(N \log N)$ | $O(N \log N)$ | $O(N \log N)$ | Yes | No |
| Quick Sort | $O(N \log N)$ | $O(N^2)$ – can be made $O(N \log N)$ | $O(N \log N)$ | Depends | No |

Summary

Sorting

| | Best | Worst | Average |  | |
|-----------------------|---------------|--------------------------------------|---------------|---|----|
| Selection Sort | $O(N^2)$ | $O(N^2)$ | $O(N^2)$ | | |
| Insertion Sort | $O(N)$ | $O(N^2)$ | $O(N^2)$ | | |
| Heap Sort | $O(N \log N)$ | $O(N \log N)$ | $O(N \log N)$ | | |
| Merge Sort | $O(N \log N)$ | $O(N \log N)$ | $O(N \log N)$ | Yes | No |
| Quick Sort | $O(N \log N)$ | $O(N^2)$ – can be made $O(N \log N)$ | $O(N \log N)$ | Depends | No |

Summary

Auxiliary for Recursion

- The recursion stack takes up memory!!!

Summary

Auxiliary for Recursion

- The recursion stack takes up memory!!!
 - So that is why it isn't in place!

- The recursion stack takes up memory!!!
 - So that is why it isn't in place!
 - If I have recursion $\log N$ times, then I take $O(\log N)$ space for the recursion alone!
 - If each recursion is k , then my total space is $O(k \log N)$!!!

- The recursion stack takes up memory!!!
 - So that is why it isn't in-place!
 - Iterative is easier to get in-place
 - If I have recursion $\log N$ times, then I take $O(\log N)$ space for the recursion alone!
 - If each recursion is k , then my total space is $O(k \log N)$!!!

Summary

Sorting

| | Best | Worst | Average | Stable? | In-place? |
|-----------------------|---------------|--------------------------------------|---------------|---------|-----------|
| Selection Sort | $O(N^2)$ | $O(N^2)$ | $O(N^2)$ | No | Yes |
| Insertion Sort | $O(N)$ | $O(N^2)$ | $O(N^2)$ | Yes | Yes |
| Heap Sort | $O(N \log N)$ | $O(N \log N)$ | $O(N \log N)$ | No | Yes |
| Merge Sort | $O(N \log N)$ | $O(N \log N)$ | $O(N \log N)$ | Yes | No |
| Quick Sort | $O(N \log N)$ | $O(N^2)$ – can be made $O(N \log N)$ | $O(N \log N)$ | Depends | No |

- So... what is the lower bound for the sorting algorithms that we have learnt?
 - Bubble
 - Insertion
 - Selection
 - Quick
 - Merge
- These are all comparison based
- $\Omega(N \log N)$
- We will see more of this **later**

Questions?

Thank you