






PANEL THICKNESS	X dimension
0.75-1.25 [0.030-.049]	19.2- <i>a</i> 1 [0.756]
1.25-2.0 [0.049-.079]	19.4- <i>a</i> 1 [0.764]
2.0-3.0 [0.079-.118]	19.8- <i>a</i> 1 [0.780]



SWITCH FUNCTION	
POS. 1	POS. 2
ON	OFF
1-1a	OPEN



NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERMINAL NUMBERS FOR REF ONLY
- RATING: 15A @ 125VAC OR
6A @ 250VAC
- APPROVALS:
(UL, CSA, VDE, NEMKO, SEMKO, FIMKO, DEMKO)
- MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
- ELECTRICAL LIFE: 10,000 cycles
- CONTACT RESISTANCE: <20 Mega Ω
- INSULATION RESISTANCE: >1000 Mega Ω
- DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles

①

E-SWITCH®

TITLE

R1966A BLK BLK FR

SCALE

1.5:1

DATE

1/23/96

DR

MM

DWG

M301212

REV

D

D	11664	REVISED PART DESCRIPTION	9/19/01	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSFERRED