



The Unix Shell

Advanced Shell Tricks




Copyright © The University of Southampton 2011

This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.



"How should I do this?"



Some technical problem...



“How should I do this?”

With smartphones, you’ll often hear people say something like

“There’s an app for that... check this out!”





“How should I do this?”

With smartphones, you’ll often hear people say something like

“There’s an app for that... check this out!”



Whereas Unix shell programmers will say

“There’s a shell trick for that... check this out!”



In previous episodes, we've seen how to:

- Combine existing programs using pipes & filters

```
$ wc -l *.pdb | sort | head -1
```

In previous episodes, we've seen how to:

- Combine existing programs using pipes & filters
- Redirect output from programs to files

```
$ wc -l *.pdb > lengths
```

In previous episodes, we've seen how to:

- Combine existing programs using pipes & filters
- Redirect output from programs to files
- Use variables to control program operation

```
$ SECRET_IDENTITY=Dracula
```

```
$ echo $SECRET_IDENTITY
```

```
Dracula
```

In previous episodes, we've seen how to:

- Combine existing programs using pipes & filters
- Redirect output from programs to files
- Use variables to control program operation

Very powerful when used together

In previous episodes, we've seen how to:

- Combine existing programs using pipes & filters
- Redirect output from programs to files
- Use variables to control program operation

Very powerful when used together

But there are other useful things we can do with these – let's take a look...

First, let's revisit redirection...



data

cubane.pdb

ethane.pdb

methane.pdb


octane.pdb

pentane.pdb

propane.pdb

First, let's revisit redirection...


`$ ls *.pdb > files` ← list all pdb files
redirect to a file



First, let's revisit redirection...

\$ `ls *.pdb > files` ← list all pdb files
redirect to a file


*The 'redirection'
operator*



First, let's revisit redirection...

`$ ls *.pdb > files` ← list all pdb files
redirect to a file

But what about adding this together with other results generated later?




First, let's revisit redirection...

`$ ls *.pdb > files` ← list all pdb files
redirect to a file

But what about adding this together with other results generated later?

`$ ls *.ent > more-files`



First, let's revisit redirection...


```
$ ls *.pdb > files
```

← list all pdb files
redirect to a file

But what about adding this together with other results generated later?

```
$ ls *.ent > more-files
```

*We just want
the ent files*




First, let's revisit redirection...

`$ ls *.pdb > files` ← list all pdb files
redirect to a file

But what about adding this together with other results generated later?

`$ ls *.ent > more-files`
`$ cat files more-files > all-files` ← append
files into a
single new
file



First, let's revisit redirection...


`$ ls *.pdb > files` ← list all pdb files
redirect to a file

But what about adding this together with other results generated later?

`$ ls *.ent > more-files`
`$ cat files more-files > all-files` ← append
files into a
single new
file

Instead, we can do...

`$ ls *.ent >> files`



First, let's revisit redirection...

`$ ls *.pdb > files` ← list all pdb files
redirect to a file


But what about adding this together with other results generated later?

`$ ls *.ent > more-files`
`$ cat files more-files > all-files` ← append
files into a
single new
file

Instead, we can do...

`$ ls *.ent >> files`

*Note the double >'s – the
append' operator*




We know that...

Normally, standard output is directed to a display:

We know that...


Normally, standard output is directed to a display:



We know that...

Normally, standard output is directed to a display:

But we have redirected it to a file instead:



But what happens with error messages?

But what happens with error messages?

For example...

```
$ ls /some/nonexistent/path > files
```

```
ls: /some/nonexistent/path: No such file or directory
```

But what happens with error messages?

For example...

```
$ ls /some/nonexistent/path > files
```

```
ls: /some/nonexistent/path: No such file or directory
```

No files are listed in *files*, as you might expect.

But what happens with error messages?

For example...

```
$ ls /some/nonexistent/path > files
```

```
ls: /some/nonexistent/path: No such file or directory
```


No files are listed in *files*, as you might expect.

But why isn't the error message in *files*?

This is because error messages are sent to the *standard error* (stderr), separate to stdout


This is because error messages are sent to the *standard error* (stderr), separate to stdout

So what was happening with the previous example?




This is because error messages are sent to the *standard error* (stderr), separate to stdout

So what was happening with the previous example?



This is because error messages are sent to the *standard error* (stderr), separate to stdout

So what was happening with the previous example?



We can capture standard error as well as standard output

We can capture standard error as well as standard output

To redirect the standard error to a file, we can do:

```
$ ls /some/nonexistent/path 2> error-log
```

*Redirect as before,
but with a slightly
different operator*

We can capture standard error as well as standard output

To redirect the standard error to a file, we can do:

```
$ ls /some/nonexistent/path 2> error-log
```

Now we have any error messages stored in *error-log*

We can capture standard error as well as standard output

To redirect the standard error to a file, we can do:

```
$ ls /some/nonexistent/path 2> error-log
```

Now we have any error messages stored in *error-log*

To redirect both stdout and stderr, we can then do:

```
$ ls /usr /some/nonexistent/path > files 2> error-log
```

We can capture standard error as well as standard output

To redirect the standard error to a file, we can do:

```
$ ls /some/nonexistent/path 2> error-log
```

Now we have any error messages stored in *error-log*

To redirect both stdout and stderr, we can then do:

```
$ ls /usr /some/nonexistent/path >files 2>error-log
```



We can use both stdout and stderr redirection – at the same time

We can capture standard error as well as standard output

To redirect the standard error to a file, we can do:

```
$ ls /some/nonexistent/path 2> error-log
```

Now we have any error messages stored in *error-log*

To redirect both stdout and stderr, we can then do:

```
$ ls /usr /some/nonexistent/path > files 2> error-log
```

Which would give us contents of */usr* in *files* as well.

So why a '2' before the '>' ?

So why a '2' before the '>' ?

Both stdout and stderr can be referenced by numbers:

```
$ ls /usr /some/nonexistent/path 1> files 2> error-log
```

So why a '2' before the '>' ?

Both stdout and stderr can be referenced by numbers:

\$ ls /usr /some/nonexistent/path **1>**files **2>**error-log

*Refers to
stdout*

*Refers
to stderr*

So why a '2' before the '>' ?

Both stdout and stderr can be referenced by numbers:

```
$ ls /usr /some/nonexistent/path 1> files 2> error-log
```

To just redirect both to the same file we can also do:

```
$ ls /usr /some/nonexistent/path &> everything
```

With '&' denoting both stdout and stderr

So why a '2' before the '>' ?

Both stdout and stderr can be referenced by numbers:

```
$ ls /usr /some/nonexistent/path 1> files 2> error-log
```

To just redirect both to the same file we can also do:

```
$ ls /usr /some/nonexistent/path &> everything
```

With '&' denoting both stdout and stderr

We can also use append for each of these too:


```
$ ls /usr /some/nonexistent/path 1>> files 2>> error-log
```


- > 1> Redirect stdout to a file
- 2> Redirect stderr to a file
- &> Redirect both stdout and stderr to the same file

- > 1> Redirect stdout to a file
- 2> Redirect stderr to a file
- &> Redirect both stdout and stderr to the same file
- >> 1>> Redirect and append stdout to a file
- 2>> Redirect and append stderr to a file
- &>> Redirect and append both stdout and stderr to a file

We've seen how pipes and filters work with using a single program on some input data...

We've seen how pipes and filters work with using a single program on some input data...




We've seen how pipes and filters work with using a single program on some input data...

But what about running the same program *separately*, for each input?


We've seen how pipes and filters work with using a single program on some input data...

But what about running the same program *separately*, for each input?



We've seen how pipes and filters work with using a single program on some input data...

But what about running the same program *separately*, for each input?




We can use *loops* for this...

So what can we do with loops?

So what can we do with loops?

Let's go back to our first set of pdb files,
and assume we want to compress each
of them




So what can we do with loops?

Let's go back to our first set of pdb files, and assume we want to compress each of them

We could do the following for each:

```
$ zip cubane.pdb.zip cubane.pdb  
adding: cubane.pdb (deflated 73%)
```




So what can we do with loops?

Let's go back to our first set of pdb files, and assume we want to compress each of them

We could do the following for each:

```
$ zip cubane.pdb.zip cubane.pdb  
adding: cubane.pdb (deflated 73%)
```


typical output
from the zip
command



So what can we do with loops?

Let's go back to our first set of pdb files, and assume we want to compress each of them

We could do the following for each:



```
$ zip cubane.pdb.zip cubane.pdb
adding: cubane.pdb (deflated 73%)
```


typical output
from the zip
command

*The zip file
we wish to
create*

So what can we do with loops?

Let's go back to our first set of pdb files, and assume we want to compress each of them

We could do the following for each:



```
$ zip cubane.pdb.zip cubane.pdb
adding: cubane.pdb (deflated 73%)
```

typical output
from the zip
command

*The zip file
we wish to
create*

*The file(s)
we wish to
add to the
zip file*


So what can we do with loops?

Let's go back to our first set of pdb files,
and assume we want to compress each
of them

We could do the following for each:

```
$ zip cubane.pdb.zip cubane.pdb  
  adding: cubane.pdb (deflated 73%)
```

Not efficient for many files



Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

*For each pdb
file in this
directory...*

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

Run this command

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

*This is the end of
the loop*

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```



*The semicolons
separate each part
of the loop
construct*

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb do zip $file.zip $file; done
```

*This expands to a
list of every pdb
file*

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

*This variable holds
the next pdb file in
the list*

Using a loop, we can iterate over each file, and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

*We reference the
'file' variable, and
use '.' to add the
zip extension to
the filename*

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done
```

*We reference the
'file' variable again*

Using a loop, we can iterate over each file, and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done  
adding: cubane.pdb (deflated 73%)  
adding: ethane.pdb (deflated 70%)  
adding: methane.pdb (deflated 66%)  
adding: octane.pdb (deflated 75%)  
adding: pentane.pdb (deflated 74%)  
adding: propane.pdb (deflated 71%)
```


Using a loop, we can iterate over each file, and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done  
  adding: cubane.pdb (deflated 73%)  
  adding: ethane.pdb (deflated 70%)  
...
```

In one line, we've ended up with all files zipped

Using a loop, we can iterate over each file,
and run *zip* on each of them:

```
$ for file in *.pdb; do zip $file.zip $file; done  
  adding: cubane.pdb (deflated 73%)  
  adding: ethane.pdb (deflated 70%)  
...
```

In one line, we've ended up with all files zipped

```
$ ls *.zip  
cubane.pdb.zip    methane.pdb.zip  pentane.pdb.zip  
ethane.pdb.zip    octane.pdb.zip   propane.pdb.zip
```

Now instead, what if we wanted to output the first line of each pdb file?

Now instead, what if we wanted to output the first line of each pdb file?

We could use `head -1 *.pdb` for that, but it would produce:

```
==> cubane.pdb <==  
COMPND    CUBANE
```

```
==> ethane.pdb <==  
COMPND    ETHANE
```

```
==> methane.pdb <==  
COMPND    METHANE
```

```
...
```

Now instead, what if we wanted to output the first line of each pdb file?

We could use `head -1 *.pdb` for that, but it would produce:

head produces this
(it's not in the file)

```
==> cubane.pdb <==  
COMPND    CUBANE
```

```
==> ethane.pdb <==  
COMPND    ETHANE
```

```
==> methane.pdb <==  
COMPND    METHANE
```

...

Now instead, what if we wanted to output the first line of each pdb file?

We could use `head -1 *.pdb` for that, but it would produce:

head produces this
(it's not in the file)

```
==> cubane.pdb <==
COMPND    CUBANE
```

this is actually the first
line in this file!

```
==> ethane.pdb <==
COMPND    ETHANE

==> methane.pdb <==
COMPND    METHANE
...
```

Now instead, what if we wanted to output the first line of each pdb file?

We could use `head -1 *.pdb` for that, but it would produce:

head produces this
(it's not in the file)

```
==> cubane.pdb <== ←
COMPND    CUBANE ← this is actually the first
                   line in this file!

==> ethane.pdb <==
COMPND    ETHANE

==> methane.pdb <==
COMPND    METHANE
...
```

Perhaps we only want the actual first lines...

However, using a loop:

However, using a loop:

```
$ for file in *.pdb; do head -1 $file; done
```

However, using a loop:

```
$ for file in *.pdb; do head -1 $file; done
```

We use \$file as we did before, but this time with the head command

However, using a loop:

```
$ for file in *.pdb; do head -1 $file; done
```

```
COMPND    CUBANE  
COMPND    ETHANE  
COMPND    METHANE  
COMPND    OCTANE  
COMPND    PENTANE  
COMPND    PROPANE
```

What if we wanted this list sorted in reverse afterwards?

What if we wanted this list sorted in reverse afterwards?

Simple!

```
$ (for file in $(ls *.pdb); do head -1 $file; done) | sort -r
```

What if we wanted this list sorted in reverse afterwards?

Simple!

```
$ (for file in ls *.pdb; do head -1 $file; done) | sort -r
```

*Using a pipe, we
can just add this
on the end*

What if we wanted this list sorted in reverse afterwards?

Simple!

```
$ (for file in ls *.pdb; do head -1 $file; done) | sort -r
```

```
COMPND    PROPANE  
COMPND    PENTANE  
COMPND    OCTANE  
COMPND    METHANE  
COMPND    ETHANE  
COMPND    CUBANE
```

zip

Create a compressed zip file
with other files in it

for ...; do ... done;

Loop over a list of data and run
a command once for each
element in the list



created by

Steve Crouch

July 2011



Copyright © Software Carpentry and The University of Southampton 2010-2011

This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.