

```

library(caTools)
library(tidyverse)
library(miscTools)
library(Metrics)
library(plotly)
library(glmnet)
library(PRROC)
library(ROCit)
library(rpart)
library(rpart.plot)
library(randomForest)
library(caret)
library(caTools)
library(dplyr)

data = read.csv("/Users/bennetthellman/Desktop/OneDrive - Massachusetts
Institute of Technology/AE/HWs/HW3/readmission.csv")
data<-data%>%mutate(readmission = as.factor(readmission))
set.seed(144)
split = createDataPartition(data$readmission, p = 0.75, list = FALSE)
readm.train <- data[split,]
readm.test <- data[-split,]

#a
#this is actually the lost matrix, I will redefine the cost matrix later
cm <- matrix(c(0,1200,7550,0), nrow=2, ncol=2, byrow=TRUE)

#b
tree1 = rpart(readmission ~ .,
               data=readm.train, parms=list(loss=cm), method =
               'class')
tree2 = rpart(readmission ~ .,
               data=readm.train, parms=list(loss=cm),
               cp=0.0016)
tree3 = rpart(readmission ~ .,
               data=readm.train, parms=list(loss=cm),
               cp=0.0012)
rpart.plot(tree1, extra = 101)
rpart.plot(tree2, extra =101)
rpart.plot(tree3, extra =101)

#c
pred_t1 = predict(tree1, newdata = readm.test, type = 'class')
pred_t2 = predict(tree2, newdata = readm.test, type = 'class')
pred_t3 = predict(tree3, newdata = readm.test, type = 'class')

#ci
table_mat1 <- table(readm.test$readmission, pred_t1)
table_mat1[1,2]+table_mat1[2,2]
table_mat2 <- table(readm.test$readmission, pred_t2)
table_mat2[1,2]+table_mat2[2,2]
table_mat3 <- table(readm.test$readmission, pred_t3)
table_mat3[1,2]+table_mat3[2,2]

```

```

#cii
#simply .75 * bottom true positives
.75*table_mat1[2,2]
.75*table_mat2[2,2]
.75*table_mat3[2,2]
#ciii
accuracy_Test1 <- sum(diag(table_mat1)) / sum(table_mat1)
accuracy_Test1
accuracy_Test2 <- sum(diag(table_mat2)) / sum(table_mat2)
accuracy_Test2
accuracy_Test3 <- sum(diag(table_mat3)) / sum(table_mat3)
accuracy_Test3

#civ
tpr1 = table_mat1[2,2]/(table_mat1[2,1]+table_mat1[2,2])
tpr1
tpr2 = table_mat2[2,2]/(table_mat2[2,1]+table_mat2[2,2])
tpr2
tpr3 = table_mat3[2,2]/(table_mat3[2,1]+table_mat3[2,2])
tpr3

#cv
fpr1 = table_mat1[1,2]/(table_mat1[1,1]+table_mat1[1,2])
fpr1
fpr2 = table_mat2[1,2]/(table_mat2[1,1]+table_mat2[1,2])
fpr2
fpr3 = table_mat3[1,2]/(table_mat3[1,1]+table_mat3[1,2])
fpr3

#cvi
cm <- matrix(c(0,1200,35000,27450), nrow=2, ncol=2, byrow=TRUE)
sum(cm*table_mat1)
sum(cm*table_mat2)
sum(cm*table_mat3)

#di
bl_cost = sum(readm.test$readmission==1)*35000 #absolute cost reduction
bl_cost-sum(cm*table_mat1) #relative cost reduction
(bl_cost-sum(cm*table_mat1))/bl_cost*100
bl_cost-sum(cm*table_mat2)
(bl_cost-sum(cm*table_mat2))/bl_cost*100
bl_cost-sum(cm*table_mat3)
(bl_cost-sum(cm*table_mat3))/bl_cost*100

#eii
cm <- matrix(c(0,1200,7550,0), nrow=2, ncol=2, byrow=TRUE)

bud <- matrix(c(0,1200*1.25,7550,0), nrow=2, ncol=2, byrow=TRUE)
treebud = rpart(readmission ~ ., data=readm.train,
parms=list(loss=bud),cp=0.001)
pred_bud = predict(treebud, newdata = readm.test, type = 'class')
table_bud <- table(readm.test$readmission, pred_bud)
((table_bud[1,2]+table_bud[2,2])/sum(table_bud))

```

```

bud <- matrix(c(0,1200*1.5,7550,0), nrow=2, ncol=2, byrow=TRUE)
treebud = rpart(readmission ~ ., data=readm.train,
parms=list(loss=bud),cp=0.001)
pred_bud = predict(treebud, newdata = readm.test, type = 'class')
table_bud <- table(readm.test$readmission, pred_bud)
((table_bud[1,2]+table_bud[2,2])/sum(table_bud))

bud <- matrix(c(0,1200*1.75,7550,0), nrow=2, ncol=2, byrow=TRUE)
treebud = rpart(readmission ~ ., data=readm.train,
parms=list(loss=bud),cp=0.001)
pred_bud = predict(treebud, newdata = readm.test, type = 'class')
table_bud <- table(readm.test$readmission, pred_bud)
((table_bud[1,2]+table_bud[2,2])/sum(table_bud))

bud <- matrix(c(0,1200*1.6,7550,0), nrow=2, ncol=2, byrow=TRUE)
treebud = rpart(readmission ~ ., data=readm.train,
parms=list(loss=bud),cp=0.001)
pred_bud = predict(treebud, newdata = readm.test, type = 'class')
table_bud <- table(readm.test$readmission, pred_bud)
((table_bud[1,2]+table_bud[2,2])/sum(table_bud))

bud <- matrix(c(0,1200*1.5,7550,0), nrow=2, ncol=2, byrow=TRUE)
treebud = rpart(readmission ~ ., data=readm.train,
parms=list(loss=bud),cp=0.001)
pred_bud = predict(treebud, newdata = readm.test, type = 'class')
table_bud <- table(readm.test$readmission, pred_bud)
((table_bud[1,2]+table_bud[2,2])/sum(table_bud))

bud <- matrix(c(0,1200*1.75,7550,0), nrow=2, ncol=2, byrow=TRUE)
treebud = rpart(readmission ~ ., data=readm.train,
parms=list(loss=bud),cp=0.001)
pred_bud = predict(treebud, newdata = readm.test, type = 'class')
table_bud <- table(readm.test$readmission, pred_bud)
((table_bud[1,2]+table_bud[2,2])/sum(table_bud))

#eiii
(table_bud[1,2]+table_bud[2,2])
.25*table_bud[2,2]
.25*table_bud[2,2]*(35000-1200)

#eiv
bl_cost=sum(cm*table_bud)
(bl_cost-sum(cm*table_bud))/bl_cost*100
sum(cm*table_mat2)-sum(cm*table_bud)
(sum(cm*table_mat2)-sum(cm*table_bud))/sum(cm*table_mat2)*100

```