



用户入门手册

User Manual

ZenMux 驱动的本地 AI 办公工作台

ZenMux-powered local AI office workspace



关于本手册

About this manual

本手册面向第一次使用 GenOffice 的用户，以当前仓库 **v0.6.50** 源码与真实运行态为依据，说明安装、ZenMux 设置、Word、Excel、PowerPoint、Markdown、PDF 以及跨编辑器 AI 工作流。界面截图于 2026-08-16 在隔离的临时用户目录中从当前应用运行态取得；截图没有包含用户文件、真实 API Key 或个人数据。

This manual is based on the current **v0.6.50** source tree and real runtime UI. It covers installation, ZenMux configuration, Word, Excel, PowerPoint, Markdown, PDF, and cross-editor AI workflows. Screenshots were captured on 16 August 2026 in an isolated temporary profile and contain no user documents, real API Key, or personal data.

AI 适配与修改 / AI adaptation and modifications

由复旦大学计算与智能创新学院徐志平完成 AI 适配与修改工作。

AI adaptation and modifications by Zhiping Xu, College of Computer Science and Artificial Intelligence, Fudan University.

GenOffice 是 [genspark-ai/genoffice](#) 的衍生版本，保留 Apache-2.0 开源基础，并完成 ZenMux AI 通道、本地凭据、学术工作流、跨编辑器连接及多平台发行等适配。项目源码与发行包见 [bennix/GenZenMuxAIOffice](#)。

GenOffice is derived from [genspark-ai/genoffice](#). It retains the Apache-2.0 foundation and adds ZenMux routing, local credential storage, academic workflows, cross-editor connections, and multi-platform distribution. Source and releases are available at [bennix/GenZenMuxAIOffice](#).

注意 • Notice AI 功能依赖网络、代理状态和模型服务可用性。AI 输出、联网结果、公式识别、审稿意见与图像生成均应由用户核对。AI features depend on network, proxy, and provider availability; always verify generated content, sources, formulas, reviews, and images.

手册 LaTeX 源文件与生成的 PDF 同步发布。文档中的产品名称、第三方项目及商标归各自权利人所有。

The LaTeX source and compiled PDF are published together. Product names, third-party projects, and trademarks belong to their respective owners.

一分钟找到需要的章节

Find the right section in one minute

每个主题由相邻的中文页和英文页组成。截图来自中文界面；英文页会给出对应英文控制名称和操作路径。 / Every topic is presented as a Chinese page followed by its English counterpart. Screenshots use the Chinese UI; English pages provide matching control names and paths.

目标 · Goal	中文入口	English route
尽快开始	第 I 部分：安装、首次启动、主页、设置	Part I: install, first launch, home, settings
使用 AI	第 II 部分：上下文、附件、复制、@Connect	Part II: context, attachments, copy, @Connect
编辑文件	第 III-VI 部分：Word、Excel、PPT、Mark-down、PDF	Parts III-VI: Word, Excel, PPT, Mark-down, PDF
学术工作	文献、引用、公式、审稿、联网查证	Literature, citations, equations, review, web verification
排查问题	第 VII 部分：超时、权限、保存、安全	Part VII: timeout, permissions, saving, security



- 路径中的“设置 > AI 模型”表示先打开设置，再选择“AI 模型”。
- macOS 的 **Command** 与 Windows/Linux 的 **Ctrl** 在本手册中写作 **Cmd/Ctrl**。
- 所有 AI 工作流都以用户自己的 ZenMux API Key 为前提；纯本地编辑不需要 API Key。
- PDF 模块以查看、页面处理、水印、安全与 AI 问答为主；当前功能区不提供文字、图片或公式编辑入口。

提示 · Tip 建议先完成“首次启动”和“ZenMux 设置”，再直接跳到你正在使用的文件类型。 / Complete First launch and ZenMux setup, then jump directly to the file type you need.

目录 • Contents

I 安装与设置 / Install & configure	6
01 安装并验证应用 / Install and verify	7
02 首次启动与欢迎页 / First launch and welcome	9
03 主页、项目与最近文件 / Home, projects, and recent files	11
04 设置 ZenMux API Key / Configure the ZenMux API Key	13
05 增加、选择与删除模型 / Add, select, and remove models	15
06 本地凭据、版本与网络提示 / Local credentials, version, and network notices	17
II 统一 AI 工作流 / Shared AI workflow	19
07 选择内容作为 AI 上下文 / Use selected content as AI context	20
08 附件、图片与剪贴板 / Attachments, images, and clipboard	22
09 复制提示词与 AI 回复 / Copy prompts and AI replies	24
10 用 @Connect 打通编辑器 / Connect editors with @Connect	26
III Word 文档工作台 / Word document workspace	28
11 创建、打开与保存 DOCX / Create, open, and save DOCX	29
12 文字、段落、样式与 AI 修改 / Text, paragraphs, styles, and AI edits	31
13 插入图片与文字环绕 / Insert images and wrap text	33
14 插入、识别与编辑 LaTeX 公式 / Insert, recognize, and edit LaTeX	35
15 科研文献检索、/cite 与 BIB / Literature search, /cite, and BIB	37
16 严格 AI 审稿委员会 / Strict AI review committee	39
17 AI 配图与扫描件处理 / AI imagery and scanned-page processing	41
IV Excel 数据工作台 / Excel data workspace	43
18 工作簿、工作表与基础编辑 / Workbooks, sheets, and basic editing	44
19 主流数据分析流程 / Mainstream data analysis	46
20 字段驱动的数据可视化 / Field-driven data visualization	48
21 AI 选区修改、公式与回填 / AI range edits, formulas, and write-back	50
V PowerPoint 演示工作台 / PowerPoint presentation workspace	52
22 打开、编辑与生成可编辑幻灯片 / Open, edit, and generate editable slides	53
23 形状、艺术字、表格与图表 / Shapes, WordArt, tables, and charts	55
24 插入并播放视频、音频和图片 / Insert and play video, audio, and images	57
25 录制旁白并合成 MP4 / Record narration and export MP4	59
26 PPT 公式、文献与 ZenMux 配图 / Equations, citations, and imagery	61
VI Markdown 与 PDF / Markdown & PDF	63
27 Markdown 基础编辑与图片 / Markdown basics and images	64
28 Markdown 中的行内与多行 LaTeX / Inline and multiline math in Markdown	66

29 Mermaid 插入、编辑与 AI 生成 / Insert, edit, and generate Mermaid	68
30 Markdown 与 Word 互转 / Convert between Markdown and Word	70
31 Markdown 审稿、翻译与文献 / Markdown review, translation, and literature	72
32 PDF 预览与页面处理 / PDF viewing and page operations	74
33 PDF 水印、批注与安全 / PDF watermarks, annotation, and security	76
34 PDF 框选提问、附件与 @Connect / PDF region questions, attachments, and @Connect	78
VII 联网、可靠性与安全 / Web, reliability & safety	80
35 以当前系统时间为参考 / Use current system time as the reference	81
36 科研检索入口与合法全文 / Scholarly sources and lawful full text	83
37 AI 超时、流式中断与重试 / AI timeout, interrupted streaming, and retry	85
38 麦克风、屏幕录制与文件权限 / Microphone, screen recording, and file permissions	87
39 常用快捷键与可恢复操作 / Common shortcuts and recoverable actions	89
40 保存、导出与跨应用复核 / Save, export, and verify in another app	91
41 隐私、安全与更新 / Privacy, security, and updates	93
42 首次使用与交付检查单 / First-use and delivery checklists	95

安装与设置

Install & configure

从可信发行包开始，完成首次启动，并把 ZenMux API Key 安全地保存在本机。 / Start from a trusted build, complete first launch, and store the ZenMux API Key securely on this device.

安装并验证应用

Install and verify

GenOffice 提供 macOS DMG、Windows x64 安装程序、Ubuntu DEB 与通用 RPM。请只从项目 Landing Page 或 GitHub Releases 下载。

1. 在 [官方 Landing Page](#) 选择操作系统；检查页面显示的当前版本与文件名一致。
2. macOS: 打开 DMG, 将 GenOffice 拖入 “应用程序”。Apple Silicon 版本使用 Developer ID 签名并经过 Apple 公证。
3. Windows: 运行 x64 安装程序。当前安装包未做 Authenticode 签名, SmartScreen 可能显示 “未知发布者”; 请核对下载域名与 Release 文件。
4. Ubuntu: 执行 `sudo apt install ./genoffice_0.6.50_amd64.deb`。Fedora/RHEL 系使用 `sudo dnf install ./genoffice-0.6.50.x86_64.rpm`。

平台	文件	说明
macOS	.dmg	Apple Silicon, macOS 11+
Windows	.exe	Windows 10/11 x64
Ubuntu	.deb	Ubuntu 22.04/24.04 amd64
RPM	.rpm	Fedora/RHEL/Rocky/Alma/openSUSE x86_64

提示 · Tip 安装包版本、Landing Page 版本与下载链接应一致。若浏览器下载失败, 进入 [GitHub Releases](#) 后手动选择同名资源。

Install and verify

安装并验证应用

GenOffice ships as a macOS DMG, Windows x64 installer, Ubuntu DEB, and RPM. Download only from the project Landing Page or GitHub Releases.

1. Open the [official Landing Page](#), choose your platform, and confirm that the displayed version matches the filename.
2. macOS: open the DMG and drag GenOffice to Applications. The Apple Silicon build is Developer ID signed and Apple notarized.
3. Windows: run the x64 installer. The current build is not Authenticode-signed, so SmartScreen may report an unknown publisher; verify the domain and Release asset first.
4. Ubuntu: run `sudo apt install ./genoffice_0.6.50_amd64.deb`. Fedora/RHEL-family users can run `sudo dnf install ./genoffice-0.6.50.x86_64.rpm`.


Platform	File	Requirement
macOS	.dmg	Apple Silicon, macOS 11+
Windows	.exe	Windows 10/11 x64
Ubuntu	.deb	Ubuntu 22.04/24.04 amd64
RPM	.rpm	Fedora/RHEL/Rocky/Alma/openSUSE x86_64

提示 • Tip The installer version, Landing Page label, and download target should agree. If a direct link fails, open [GitHub Releases](#) and choose the matching asset manually.

首次启动与欢迎页

First launch and welcome

欢迎页直接连接 ZenMux：可以立即填写 API Key，也可以先跳过，在设置页稍后完成。纯本地文件编辑不要求登录。



当前源码真实运行态：ZenMux 首次启动欢迎页（未填写任何真实凭据）。


1. 没有 API Key 时，点击邀请链接 <https://zenmux.ai/invite/GBQMC5> 申请或注册。
2. 把 Key 粘贴到输入框，选择默认文本模型，然后继续。Key 会在界面中以遮罩形式显示。
3. 暂时只想编辑本地文件时，可选择“跳过”；Word、Excel、PPT、Markdown 和 PDF 的非 AI 功能仍可使用。

注意 · Notice 不要把 API Key 写入文档正文、截图、聊天附件或公开仓库。应用设置页是唯一推荐的录入位置。

First launch and welcome

首次启动与欢迎页

The welcome screen connects directly to ZenMux. Enter an API Key now or skip and configure it later in Settings. Local file editing does not require sign-in.



Real runtime UI from the current source: ZenMux welcome screen with no real credential entered.


1. If you do not have a key, use <https://zenmux.ai/invite/GBQMC5> to register or request one.
2. Paste the key, choose the default text model, and continue. The value is masked in the interface.
3. To work locally first, choose Skip. Non-AI features in Word, Excel, PowerPoint, Markdown, and PDF remain available.

注意 • Notice Never place an API Key in document text, screenshots, chat attachments, or a public repository. Settings is the recommended entry point.

主页、项目与最近文件

Home, projects, and recent files

主页集中提供五类编辑器、打开本地文件、项目列表、收藏和最近文件。一个窗口可以用标签页并行处理多种格式。



当前源码真实运行态：主页快速新建卡片、项目栏、最近文件筛选与设置入口。


- 点击 AI Docs、AI Sheets、AI Slides、AI Markdown 或 AI PDF 新建对应内容；“打开本地文件”用于选择已有文件。
- 左侧“项目”用于组织文件；“最近”和“收藏”可快速返回经常使用的内容。
- 右侧筛选条按文档、表格、演示、PDF 或 Markdown 缩小最近文件范围。

提示 · Tip 同一个文件已经在标签页中打开时，优先切回现有标签，避免产生两个编辑会话。

Home, projects, and recent files

主页、项目与最近文件

The home screen brings together five editors, local-file opening, projects, favorites, and recents. Tabs let one window host several file types.



Real runtime UI: quick-create cards, project navigation, recent-file filters, and Settings.

- Choose AI Docs, AI Sheets, AI Slides, AI Markdown, or AI PDF to create content; Open local file selects an existing file.
- Projects organize work. Recent and Favorites provide quick return paths.
- The filter strip narrows recents to documents, spreadsheets, presentations, PDF, or Markdown.

提示 • Tip If a file is already open in a tab, switch to that tab instead of creating a second editing session.

设置 ZenMux API Key

Configure the ZenMux API Key

所有 AI 通道使用统一的 OpenAI 兼容地址 <https://zenmux.ai/api/v1>。API Key 保存后会持久保存在当前设备。



当前源码真实运行态：设置 > AI 模型；API Key 为空且界面不暴露任何秘密。

1. 在主页左下角点击“设置”，选择“AI 模型”。
2. 粘贴 ZenMux API Key。Base URL 已锁定为 <https://zenmux.ai/api/v1>，通常不需要修改。
3. 选择一个文本模型和一个配图模型，关闭设置。新配置会供 Word、Excel、PPT、Markdown 和 PDF 共用。
4. 发送一条不含隐私内容的短问题验证连接；若失败，先检查网络、代理、额度和模型可用性。

提示 · Tip 设置页面遮罩 Key；保存使用操作系统安全存储。更换 Key 时直接在同一位置覆盖即可。

Configure the ZenMux API Key

设置 ZenMux API Key

Every AI path uses the OpenAI-compatible endpoint <https://zenmux.ai/api/v1>. Once saved, the API Key persists on this device.



Real runtime UI: Settings > AI models, with an empty API Key field and no secret exposed.

1. Select Settings at the lower left of Home, then open AI models.
2. Paste the ZenMux API Key. The Base URL is fixed to <https://zenmux.ai/api/v1> and normally needs no change.
3. Choose one text model and one illustration model, then close Settings. Word, Excel, PowerPoint, Markdown, and PDF share the configuration.
4. Send a short, non-sensitive test question. If it fails, check network, proxy, quota, and model availability.

提示 • Tip The UI masks the key and saves it through operating-system secure storage. Enter a replacement in the same field to rotate credentials.

增加、选择与删除模型

Add, select, and remove models

设置页既可选择预置模型，也可按 ZenMux 的 provider/model-name 格式增加模型；文本模型和配图模型都支持删除。



模型区真实运行态：当前模型、增加模型名称、配图模型与删除按钮。

- 本版预置文本模型：anthropic/claude-sonnet-4.6、z-ai/glm-5v-turbo、openai/gpt-5.4。
- 公式图片识别默认视觉模型：z-ai/glm-5v-turbo。
- 配图默认可使用：openai/gpt-image-2。
- 新增时输入 ZenMux 模型页给出的完整名称，不要省略提供商前缀。加入后从下拉列表设为当前模型。
- 删除只会移除本地模型列表，不会删除 ZenMux 平台上的模型或账户数据。至少保留一个可用文本模型。

提示 · Tip 不同图像模型的请求格式可能不同；优先使用应用已适配的模型。新模型若报参数错误，可先切回预置模型验证。

Add, select, and remove models

增加、选择与删除模型

Settings offers built-in models and accepts additional names in ZenMux provider/model-name form. Text and illustration models can both be removed locally.



Real runtime model area: current model, add-model field, illustration model, and delete controls.

- Built-in text models in this release: anthropic/claude-sonnet-4.6, z-ai/glm-5v-turbo, and openai/gpt-5.4.
- Formula image recognition model: z-ai/glm-5v-turbo.
- Illustration model: openai/gpt-image-2.
- Add the complete name shown by ZenMux, including the provider prefix, then select it from the current-model list.
- Delete removes only the local list entry; it does not delete a ZenMux model or account data. Keep at least one working text model.

提示 • Tip Image models may require different request formats. Prefer models already adapted by the app; if a new model rejects parameters, switch back to a built-in model to isolate the issue.

本地凭据、版本与网络提示

Local credentials, version, and network notices

API Key 在界面中加密遮罩，并由系统凭据服务安全保存。应用版本、适配署名和更新通道可在“设置 > 关于”查看。



当前源码真实运行态：版本 0.6.50、AI 适配与修改署名、稳定版更新通道。

- macOS 使用系统安全存储/钥匙串能力；Windows 使用系统凭据加密机制。应用不会把 Key 写进安装包或手册。
- 文档打开、编辑和保存以本地为主；调用 ZenMux、联网搜索、文献检索、公式 OCR 或配图时才需要网络。
- 网络、代理、服务负载、额度或某个模型的临时状态都可能影响速度和结果；超时不等于供应方一定没有生成结果。
- “关于”页用于核对实际安装版本。报告问题时附上版本、平台、操作路径和无敏感信息的截图。

注意 • Notice 若怀疑 Key 泄露，应立即在 ZenMux 平台撤销或轮换，并在设置中替换；不要把 Key 发给支持人员。

Local credentials, version, and network notices

本地凭据、版本与网络提示

The API Key is masked in the UI and protected by the operating-system credential service. Version, adaptation credit, and update channel appear under Settings > About.



Real runtime UI: version 0.6.50, AI adaptation credit, and the stable update channel.

- macOS uses operating-system secure storage/Keychain capabilities; Windows uses system credential encryption. The key is not embedded in installers or this manual.
- Opening, editing, and saving files are local-first. ZenMux calls, web search, literature search, formula OCR, and image generation require a network.
- Network, proxy, provider load, quota, or model status can affect speed and output. A client timeout does not prove that the provider produced no result.
- Use About to confirm the installed version. A useful issue report includes version, platform, action path, and a screenshot without secrets.

注意 • Notice If a key may be exposed, revoke or rotate it at ZenMux and replace it in Settings. Never send the key to support staff.

统一 AI 工作流

Shared AI workflow

五类编辑器共享上下文、附件、剪贴板、公式渲染、消息复制和 @Connect 信息通路。 / Five editors share context, attachments, clipboard input, equation rendering, message copy, and @Connect.

选择内容作为 AI 上下文

Use selected content as AI context

先选择，再提问，是最可靠的精确修改方式。Word 选择段落，Excel 选择单元格，PPT 选择对象，Markdown 选择文字；PDF 使用矩形框选页面区域。




1. 在编辑器中完成选择，确认界面出现选区、对象、单元格范围或 PDF 区域缩略图。
2. 提问时说明动作和边界，例如“只润色选中段落，不改变公式和引用键”。
3. 先阅读 AI 回复或差异，再执行替换、插入或应用；不满意时撤销并缩小任务范围。
4. Markdown 会冻结发送时的锚点；若用户随后修改原文，过期锚点会阻止错误回填。

提示 · Tip 没有选择时，AI 可能读取全文或当前页面。处理长文档时，显式选择能减少歧义、延迟和不必要的上下文。

Use selected content as AI context

选择内容作为 AI 上下文

Select first, then ask. Word selects paragraphs, Excel selects cells, PowerPoint selects objects, Markdown selects text, and PDF captures a rectangular page region.




1. Make the selection and confirm that the UI shows a range, object, text card, or PDF region thumbnail.
2. State both action and boundary, for example: “Polish only the selected paragraph; preserve equations and citation keys.”
3. Read the response or diff before replacing, inserting, or applying. Undo and narrow the task if the result is not acceptable.
4. Markdown freezes the anchor at send time. If the source is edited later, a stale anchor is rejected to prevent misplaced write-back.

提示 • Tip With no explicit selection, AI may use the full document or current page. Explicit context reduces ambiguity, latency, and unnecessary input on long files.

附件、图片与剪贴板

Attachments, images, and clipboard

AI 输入每次最多支持 5 个附件。文件可通过选择器或拖放添加；剪贴板图片会显示为可删除缩略图，并发送给视觉模型。




- 普通文件会先在本机解析可读取内容；图片作为视觉输入。大型、加密或不受支持的文件可能无法解析。
- 用 Cmd/Ctrl+V 粘贴剪贴板图片；发送前检查缩略图，点击删除可移除不需要的附件。
- 附件总数超过 5 个时，先删除或分批提问。不要把 API Key、密码、未脱敏个人信息作为附件。
- 网络失败重试时，应用尽量保留原附件和框选内容；仍建议在重新发送前确认缩略图列表。

注意 · Notice 发送附件会把相关内容交给所选 ZenMux 模型处理。涉及保密、伦理审查或受限数据时，先遵守所在机构政策。

Attachments, images, and clipboard

附件、图片与剪贴板

Each AI request accepts up to five attachments. Add files with the picker or drag-and-drop; pasted images appear as removable thumbnails and are sent as visual input.



- Ordinary files are parsed locally before relevant content is supplied; images are visual input. Large, encrypted, or unsupported files may not parse.
- Paste a clipboard image with Cmd/Ctrl+V. Check thumbnails before sending and remove any item that is not needed.
- If the total exceeds five, remove items or split the task. Never attach API Keys, passwords, or unredacted personal information.
- The app attempts to retain attachments and PDF regions after network failure. Confirm the thumbnail list again before retrying.

注意 • Notice Relevant attachment content is processed by the selected ZenMux model. Follow institutional rules before sending confidential, ethics-controlled, or otherwise restricted data.

复制提示词与 AI 回复

Copy prompts and AI replies

用户发出的提示词和 AI 回复都可以复制。复制保留 Markdown、LaTeX、Mermaid 与代码源文；界面同时把合法公式实时渲染成可读形式。

- 在消息旁使用复制按钮；粘贴到纯文本编辑器时得到源文，粘贴到支持富文本的目标时可保留适合的结构。
- 行内公式使用 $\$...\$$ ，独立公式使用 $\$...\$$ ；多行公式可使用 aligned、gathered 等 LaTeX 环境。
- AI 回复中的 GFM 表格、列表、粗体和公式会统一解析；流式传输尚未闭合的定界符会暂时按可读文本显示，完成后再渲染。
- 若某段公式仍未渲染，先复制源文，检查反斜杠、成对定界符和下划线是否被意外转义。

行内： $E = mc^2$ 多行：
$$\begin{aligned} F &= ma \\ E_k &= \frac{1}{2}mv^2 \end{aligned}$$

源文可复制，渲染结果可阅读，插入文档后仍可继续编辑。

提示 · Tip 表格不适合表达长段推理。可要求 AI 使用“短表格 + 表格后解释”，提高 Word 与 Markdown 中的可读性。

Copy prompts and AI replies

复制提示词与 AI 回复

Both user prompts and AI replies can be copied. Copy preserves Markdown, LaTeX, Mermaid, and code source while the UI renders valid equations for reading.

- Use the copy control beside a message. A plain-text destination receives source; a rich destination can preserve suitable structure.
- Use `$...$` for inline math and `$$...$$` for display math. Multiline equations can use LaTeX environments such as `aligned` or `gathered`.
- GFM tables, lists, emphasis, and equations share the same reply parser. An unclosed delimiter remains readable during streaming and renders when complete.
- If a formula does not render, copy the source and check backslashes, paired delimiters, and accidentally escaped underscores.

Inline: $E = mc^2$ Multiline:
$$\begin{aligned} F &= ma \\ E_k &= \frac{1}{2}mv^2 \end{aligned}$$

Source remains copyable, rendering remains readable, and inserted equations remain editable.

提示 • Tip A wide table is a poor container for long reasoning. Ask for a concise table followed by prose to improve readability in Word and Markdown.

用 @Connect 打通编辑器

Connect editors with @Connect

在 AI 输入中键入 @Connect，可把最近一条 AI 回复送到另一个已经打开的 Word、Excel、PPT 或 Markdown 标签页。源可以来自五类编辑器，包括 PDF。



1. 先打开目标文件，确保目标标签页已经出现在 GenOffice 窗口中。
2. 在当前 AI 输入框键入 @Connect，从正确的开放标签列表中选择目标；不要仅凭相似文件名判断。
3. 发送后检查目标：Word/Markdown 接收可编辑文本，Excel 接收适合单元格的内容，PPT 接收可编辑文本框，而不是扁平截图。
4. 连接只在本机应用内部传递回复；目标文件仍需用户保存。若目标关闭或改名，重新打开后再选择。

提示 · Tip 推荐 workflow：PDF 框选提问 → @Connect 到 Word 整理；Excel 分析 → @Connect 到 PPT 形成汇报提纲。

Connect editors with @Connect

用 @Connect 打通编辑器

Type @Connect in an AI input to send the latest reply to another open Word, Excel, PowerPoint, or Markdown tab. The source can be any of the five editors, including PDF.



1. Open the destination first and confirm that its tab is visible in GenOffice.
2. Type @Connect, then choose the correct item from the list of open targets. Do not rely only on similar filenames.
3. Verify the destination: Word/Markdown receives editable text, Excel receives cell-suitable content, and PowerPoint receives an editable text box rather than a flattened screenshot.
4. Transfer is local to the app, but the destination file still needs to be saved. If a target is closed or renamed, reopen it before selecting again.

提示 • Tip Useful flows: PDF region question → @Connect to Word for synthesis; Excel analysis → @Connect to PowerPoint for a briefing outline.

Word 文档工作台


Word document workspace

编辑真实 DOCX，处理分页、样式、图片环绕、公式、文献、审稿与 AI 配图。 / Edit real DOCX files with pagination, styles, image wrapping, equations, citations, review, and AI imagery.

创建、打开与保存 DOCX

Create, open, and save DOCX

Word 工作台直接处理 DOCX。未修改的文档部分尽量保持原始结构；保存前仍应检查页面、字体、图片和复杂对象。



当前源码真实运行态：Word 编辑器、分页画布、功能区与左侧 ZenMux AI 面板。


- 从主页点击 AI Docs 新建，或用“打开本地文件”选择.docx。标题栏显示当前文件名与保存状态。
- 使用 Cmd/Ctrl+S 保存，Cmd/Ctrl+Shift+S 另存。首次保存的新文档需要选择位置与文件名。
- 自动保存可减少意外损失，但在大幅修改前仍建议另存版本；关闭时留意未保存提示。
- 在 Microsoft Word 或其他兼容应用中复核交付文件，尤其是特殊字体、域、目录、浮动对象和跨页表格。

提示 · Tip 处理重要文件时，保留“原始文件、编辑副本、最终交付”三份，避免覆盖唯一来源。

Create, open, and save DOCX

创建、打开与保存 DOCX

The Word workspace edits real DOCX files. Unchanged areas are preserved as narrowly as possible, but page layout, fonts, images, and complex objects still deserve a final check.



Real runtime UI: Word editor, paginated canvas, ribbon, and the ZenMux AI panel on the left.


- Choose AI Docs to create a file or Open local file to select a .docx. The title area shows filename and save state.
- Use Cmd/Ctrl+S to save and Cmd/Ctrl+Shift+S for Save As. A new document asks for location and name on first save.
- Auto-save reduces accidental loss, but create a new version before major edits and respond to unsaved-close prompts.
- Review deliverables in Microsoft Word or another compatible app, especially custom fonts, fields, contents, floating objects, and multipage tables.

提示 • Tip For important work, keep an untouched original, an editing copy, and a final delivery file instead of overwriting the only source.

文字、段落、样式与 AI 修改

Text, paragraphs, styles, and AI edits

功能区用于字体、字号、粗斜体、颜色、对齐、列表和样式。选择一段文字后，AI 可以只针对选区润色、翻译、总结或改写。



Word 真实运行态：文字编辑区和 ZenMux AI 面板并排，便于先选中再提问。


1. 先选择文字，再调整字体或字号；若字号输入不顺畅，可点击字号框、全选数值、输入目标大小并按 Enter。
2. 用样式而不是逐段手工放大来建立标题层级；列表、缩进和段前段后距应通过段落工具统一设置。
3. AI 修改时写清楚语言、语气、长度和禁止改变项，例如“保持数字、LaTeX 公式、引用键和专有名词不变”。
4. 应用前查看差异；应用后用撤销检查可恢复性。跨多个段落时分批处理，减少格式被连带改变。

提示 • Tip 长文档先统一样式，再让 AI 润色正文。这样内容修改和版式修改更容易分别审阅。

Text, paragraphs, styles, and AI edits

文字、段落、样式与 AI 修改

The ribbon controls font, size, emphasis, color, alignment, lists, and styles. After selecting text, AI can polish, translate, summarize, or rewrite only that range.



Real Word runtime: editing surface beside the ZenMux panel, designed for select-then-ask work.


1. Select text before changing font or size. If the size control feels awkward, focus it, select the current value, type the target, and press Enter.
2. Build hierarchy with styles rather than manually enlarging every heading. Use paragraph controls for lists, indents, and spacing.
3. State language, tone, length, and protected items: “Preserve numbers, LaTeX equations, citation keys, and proper nouns.”
4. Review the diff before applying and test Undo afterward. Split a large multi-paragraph change into smaller batches to limit format side effects.

提示 • Tip Normalize styles before polishing a long manuscript. Content and layout changes then remain easier to review separately.

插入图片与文字环绕

Insert images and wrap text

图片可从文件、剪贴板或拖放进入 Word，并支持嵌入、四周、紧密、穿越、上下、衬于文字下方及浮于文字上方等布局。



当前源码真实运行态：Word “插入” 功能区中的图片、表格、公式与绘图入口。


1. 在“插入”中选择图片，或把本地图片拖到文档目标位置。插入后先确认图片仍在页面边界内。
2. 选择环绕方式：正文中的内容优先用“嵌入”；需要自由布局时使用四周/紧密；背景图或水印式素材才使用衬于文字下方。
3. 通过角点等比缩放；宽高可输入并实时更新。自由浮动图片要检查锚点、层级和跨页位置。
4. 导出 PDF 前使用分页预览检查图像尺寸、页面纸张、边距和是否出现边框；导出结果应与页面画布 1:1 对应。

注意 · Notice 浮于文字上方或下方时若图片看似消失，先检查层级、锚点所在页、页面边界和缩放比例，再撤销最近一次布局操作。

Insert images and wrap text

插入图片与文字环绕

Images can enter Word from a file, clipboard, or drag-and-drop. Layout modes include inline, square, tight, through, top and bottom, behind text, and in front of text.



Real runtime UI: Word Insert ribbon with image, table, equation, and drawing entry points.


1. Choose Picture under Insert or drop a local image at the intended location. Confirm that the object remains inside the page boundary.
2. Prefer Inline for body content. Use square/tight for controlled floating layout; reserve Behind text for background-like material.
3. Resize proportionally from a corner. Width and height fields update the object; for floating images, verify anchor, z-order, and page position.
4. Before PDF export, compare paginated preview, paper size, margins, image dimensions, and borders. The exported page should match the canvas one-to-one.

注意 • Notice If an image appears to vanish in front-of-text or behind-text mode, check z-order, anchor page, page bounds, and zoom, then undo the most recent layout change.

插入、识别与编辑 LaTeX 公式

Insert, recognize, and edit LaTeX

Word 支持行内和独立公式、多行环境，以及从剪贴板截图或图片文件识别公式。识别结果先以 LaTeX 文本确认，再按文档公式形式插入。



Word “插入” 功能区包含公式入口；截图来自当前源码运行态。

- 行内公式适合句中变量，如 $F = ma$ ；独立公式适合推导与编号。多行可使用 `aligned`：

$$F = ma,$$

$$E_k = \frac{1}{2}mv^2.$$


1. 从“插入 > 公式”输入 LaTeX，预览后插入。需要修改时选择公式对象，再进入编辑。
2. 识别图片公式时，可粘贴截图或选择图片文件；裁剪应只保留公式和必要编号，避免背景文字干扰。
3. 核对上下标、希腊字母、分式、矩阵、对齐点和多行换行；AI OCR 对低清晰度或手写公式可能误判。
4. 保存并在 Word 中复核公式是否仍为可编辑对象，而不是普通截图。

提示 • Tip 复杂公式建议同时保留一份 LaTeX 源文，便于在 Word、PPT、Excel 与 Markdown 之间复用。

Insert, recognize, and edit LaTeX

插入、识别与编辑 LaTeX 公式

Word supports inline and display equations, multiline environments, and formula recognition from clipboard screenshots or image files. Confirm the recognized LaTeX before insertion.



The Word Insert ribbon contains the equation entry point; this is current runtime UI.

- Inline math suits variables in a sentence, such as $F = ma$; display math suits derivations and numbered results. Use `a`ligned for multiple lines:

$$F = ma,$$

$$E_k = \frac{1}{2}mv^2.$$


1. Enter LaTeX under Insert > Equation, preview, and insert. To revise, select the equation object before opening the editor.
2. For image recognition, paste a screenshot or choose a file. Crop to the formula and necessary number so background prose does not interfere.
3. Verify subscripts, superscripts, Greek letters, fractions, matrices, alignment points, and line breaks. Low-resolution or handwritten math may be misread.
4. Save and verify in Word that the result remains an editable equation rather than a screenshot.

提示 • Tip Keep a LaTeX source copy for complex formulas so the same math can be reused in Word, PowerPoint, Excel, and Markdown.

科研文献检索、/cite 与 BIB

Literature search, /cite, and BIB

Word 的“引用”入口可检索公开学术元数据、导入本地文献库、插入正文引用，并在文末生成参考文献表与 BibTeX 文件。



当前源码真实运行态：Word “引用” 功能区与科研文献入口。


1. 在“引用 > 科研文献”检索 OpenAlex、Crossref、Semantic Scholar、Europe PMC/PubMed 与 arXiv；受限平台会在浏览器打开官方搜索，不做不合规抓取。
2. 将结果加入本地文献库，或导入 BibTeX、RIS、CSL-JSON。用 DOI、PMID、arXiv ID 检查重复，并区分预印本与正式发表版本。
3. 在正文输入 /cite，从本地文献条目列表选择；也可从引用管理器插入。选择 GB/T 7714、APA 7、IEEE、Nature 或 Vancouver 样式。
4. 完成后执行“插入参考文献表”，把条目写到文末；同时导出.bib，即使只是临时交换文件也应保留到确认交付后。

注意 · Notice 元数据来自公开索引并不等于全文可合法下载。优先使用 OA 版本，并人工核对作者、题名、年份、期刊、卷期页和 DOI。

Literature search, /cite, and BIB

科研文献检索、/cite 与 BIB

Word References can search public scholarly metadata, import a local library, insert in-text citations, and generate both a bibliography at the end and a BibTeX file.



Real runtime UI: Word References ribbon and the scholarly-literature entry point.


1. Search OpenAlex, Crossref, Semantic Scholar, Europe PMC/PubMed, and arXiv. Restricted services open official browser searches instead of being scraped.
2. Add results to the local library or import BibTeX, RIS, or CSL-JSON. Deduplicate by DOI, PMID, or arXiv ID and distinguish preprints from published versions.
3. Type /cite and choose from the local entry list, or insert through the manager. Select GB/T 7714, APA 7, IEEE, Nature, or Vancouver style.
4. Insert Bibliography when drafting is complete so entries appear at the end, then export .bib and keep even a temporary exchange file until delivery is verified.

注意 • Notice Public metadata does not imply that every full text can be downloaded lawfully. Prefer open-access copies and verify authors, title, year, journal, volume, pages, and DOI.

严格 AI 审稿委员会

Strict AI review committee

审阅功能按文档类型建立至少 3 名委员和 1 名主席的委员会；模型从当前可用文本模型中分配，并可输出中文或英文审稿意见。



当前源码真实运行态：Word “审阅” 功能区和严格 AI 审稿入口。


- 可选标准包括 Science、Nature、Cell、Elsevier、IEEE 顶刊、IEEE 顶级会议、IEEE 一般会议，以及国家自然科学基金、863、科技和商业标书等。
- 委员分别检查新颖性、方法、证据、统计、可复现性、表达和合规性；主席综合冲突意见、主要问题、次要问题与建议结论。
- 审阅范围包括正文、公式、表格、图片、图表和图形。视觉内容应清晰，且图注、编号和正文引用要完整。
- 选择报告语言后再开始；长文档可能耗时并受网络影响。保存审稿报告，同时把每条意见映射到具体页、段落、公式或图号。

注意 • Notice AI 审稿不是正式同行评议、基金评审或法律意见。随机模型分配不能替代领域专家，关键结论必须人工复核。

Strict AI review committee

严格 AI 审稿委员会

Review creates a committee of at least three members plus a chair. Models are assigned from the available text-model list, and the report can be Chinese or English.



Real runtime UI: Word Review ribbon and the strict AI review entry point.


- Standards include Science, Nature, Cell, Elsevier, top IEEE journals, top IEEE conferences, general IEEE conferences, and several Chinese grant, 863, technology, and commercial proposal types.
- Members assess novelty, methods, evidence, statistics, reproducibility, writing, and compliance. The chair reconciles conflicts and separates major issues, minor issues, and recommendation.
- Scope includes prose, equations, tables, images, charts, and shapes. Visuals need adequate resolution plus complete captions, numbering, and textual references.
- Choose report language before starting. Long documents take time and depend on network conditions. Save the report and map every comment to a page, paragraph, equation, or figure.

注意 • Notice AI review is not formal peer review, grant adjudication, or legal advice. Random model assignment does not replace domain experts; verify every consequential conclusion.

AI 配图与扫描件处理

AI imagery and scanned-page processing

Word 配图通过 ZenMux 图像模型生成，默认适配文档比例。扫描件工具可保守增强黑白材料，或去除覆盖在印刷内容上的手写痕迹。



Word “插入” 运行态：本地图片与 AI 配图从同一文档工作流进入。


1. 生成配图时描述主题、构图、受众、比例、是否需要文字以及禁止出现的元素。Word 默认适合约 3:2 的文档配图。
2. 去手写时选择包含原始扫描图的对象，使用 openai/gpt-image-2 处理；提示应要求保留印刷体、公式、表格、线条和纸张结构。
3. 手写可能覆盖印刷字时，工具只应依据邻近笔画保守修复，不应臆造无法判断的内容。增强模式不等于去手写模式。
4. 对比处理前后预览，放大核对数字、符号、签章和边缘；确认后才替换原图，并保留原始文件。

注意 • Notice 图像生成与修复具有不确定性，也可能受网络影响。涉及证据、档案、签字或科研原始记录时，不要用 AI 结果替代原件。

AI imagery and scanned-page processing

AI 配图与扫描件处理

Word illustrations are generated through ZenMux and use a document-friendly aspect ratio. Scan tools can conservatively enhance monochrome material or remove handwriting over printed content.



Real Word Insert runtime: local images and AI illustrations enter the same document workflow.

1. Describe subject, composition, audience, aspect ratio, desired text, and prohibited elements. Word defaults to an illustration near a 3:2 document ratio.
2. For handwriting removal, select the scanned image and use `openai/gpt-image-2`. Instruct it to preserve print, equations, tables, lines, and paper structure.
3. Where handwriting overlaps print, reconstruction should be conservative and based only on nearby strokes. Enhancement mode is distinct from handwriting-removal mode.
4. Compare before and after at high zoom, checking digits, symbols, stamps, and edges. Replace only after confirmation and retain the untouched original.

注意 • Notice Image generation and restoration are uncertain and network-dependent. Never replace evidentiary, archival, signed, or original research records with an AI-processed image.

Excel 数据工作台


Excel data workspace

在真实 XLSX 中完成公式、清洗、统计分析、字段驱动可视化和选区 AI 操作。 / Work in real XLSX files with formulas, cleaning, statistics, field-driven visualization, and selection-aware AI.

工作簿、工作表与基础编辑

Workbooks, sheets, and basic editing

Excel 工作台用于真实 XLSX 的打开、编辑和保存，支持公式重算、排序筛选、数据验证、条件格式、透视表及常见工作簿结构。



当前源码真实运行态：Excel 工作台、网格、公式栏、功能区与 ZenMux AI 面板。


- 点击 AI Sheets 新建，或打开.xlsx/.xls/.csv。导入 CSV 时先确认编码、分隔符、日期与小数点格式。
- 通过名称框或鼠标选择范围；公式以等号开始。粘贴前确认目标范围大小，避免覆盖邻近数据。
- 排序和筛选前确保表头唯一且没有不必要的合并单元格；数据验证适合限制类别、日期或数值范围。
- 保存后在 Excel 或兼容应用中复核公式结果、图表、透视表、打印区域和冻结窗格。

提示 • Tip 分析前复制原始数据工作表，只在副本上清洗。保留一个“数据字典”工作表说明字段、单位、缺失值和来源。

Workbooks, sheets, and basic editing

工作簿、工作表与基础编辑

The Excel workspace opens, edits, and saves real XLSX files with formula recalculation, sorting, filtering, validation, conditional formatting, pivots, and common workbook structure.



Real runtime UI: Excel grid, formula bar, ribbon, and ZenMux AI panel.


- Choose AI Sheets or open .xlsx/.xls/.csv. For CSV, verify encoding, delimiter, date conventions, and decimal separators.
- Select a range by mouse or name box; formulas begin with an equals sign. Confirm destination dimensions before pasting so adjacent data is not overwritten.
- Before sort/filter, use unique headers and avoid unnecessary merged cells. Validation is useful for categories, dates, and numeric limits.
- After saving, verify results in Excel or a compatible app, including formulas, charts, pivots, print area, and frozen panes.

提示 • Tip Duplicate the raw-data sheet and clean only the copy. Keep a data-dictionary sheet describing fields, units, missing values, and sources.

主流数据分析流程

Mainstream data analysis

选中已有字段后，可从描述统计、数据质量、相关与回归、时间序列、分组汇总、异常值和情景分析等入口开始。



Excel 真实运行态：先在网格选择字段，再从数据/AI 工具发起分析。




1. 明确问题与分析单位；确认每行代表什么、每列类型、样本范围、时间频率和缺失值编码。
2. 先做数据质量检查与描述统计，再决定相关、协方差、回归、分组比较、时间趋势、预测或异常检测。
3. 把结果输出到新区域或新工作表，不覆盖原数据；记录筛选条件、参数与随机性。
4. 检查模型假设、样本量、离群点和数据泄漏。相关不等于因果，预测区间比单点预测更重要。

注意 · Notice AI 可以建议方法和生成步骤，但不能替代研究设计、统计诊断或领域判断。重要结论应由专业人员复核。


Mainstream data analysis

主流数据分析流程

After selecting existing fields, start with descriptive statistics, data quality, correlation/regression, time series, grouped summaries, outliers, or scenario analysis.



Real Excel runtime: select fields in the grid before launching data or AI analysis.




1. Define the question and unit of analysis. Confirm what each row represents, column types, sample scope, time frequency, and missing-value codes.
2. Run quality checks and descriptive statistics before choosing correlation, covariance, regression, group comparison, trends, forecasting, or anomaly detection.
3. Place output in a new range or sheet. Preserve raw data and record filters, parameters, and any randomness.
4. Test assumptions, sample size, outliers, and leakage. Correlation is not causation; intervals are more informative than a single forecast point.

注意 • Notice AI can suggest methods and generate steps, but it does not replace research design, statistical diagnostics, or domain judgment. Obtain expert review for consequential conclusions.

字段驱动的数据可视化

Field-driven data visualization

Excel 可根据当前列或字段推荐并创建可编辑原生图表，重点支持中文标题、坐标轴、图例、标签与悬停数值。



Excel 真实运行态：数据、图表与 AI 位于同一工作簿上下文。

目的	推荐图形
类别比较	柱形、条形、组合图
时间趋势	折线、面积、组合图
构成比例	饼图、环形图（类别不宜过多）
变量关系	散点图；必要时加趋势线
多维轮廓	雷达图（变量量纲需谨慎）


- 选择含表头的数据范围，再创建图表；确认类别列与数值列没有错位。
- 编辑标题、轴、图例、颜色、标签和数据源。中文字体应在目标系统存在，避免导出后回退。
- 悬停提示提供简单交互；交付静态文档时仍需让标题、单位、注释和来源在不悬停时可读。

提示 • Tip 一种图只回答一个主要问题。与其把所有字段放进同一张图，不如制作几张结构清晰的小图。

Field-driven data visualization

字段驱动的数据可视化

Excel can recommend and create editable native charts from selected columns, with Chinese-friendly titles, axes, legends, labels, and hover values.



Real Excel runtime: data, charts, and AI share the same workbook context.

Question	Suitable chart
Category comparison	Column, bar, or combo
Trend over time	Line, area, or combo
Part-to-whole	Pie or doughnut, with few categories
Relationship	Scatter, optionally with a trend line
Multivariate profile	Radar, with careful scaling


- Select a range with headers and verify that category and numeric columns are aligned.
- Edit title, axes, legend, color, labels, and data source. Ensure chosen Chinese fonts exist on the delivery system.
- Hover provides lightweight interaction, but static exports still need visible titles, units, annotations, and source notes.

提示 • Tip Let one chart answer one primary question. Several focused charts are usually clearer than one overloaded figure.

AI 选区修改、公式与回填

AI range edits, formulas, and write-back

选择单元格范围后，AI 可解释数据、生成公式、清洗或格式化并回填。任何批量应用都应先在小范围验证。



Excel 真实运行态：网格选区可作为 ZenMux AI 的精确上下文。


1. 选择目标范围，说明是否包含表头、允许新增的列、公式起始行和空值处理方式。
2. 要求 AI 先给出“计划 + 预览”，再应用写回；复杂公式先在一列少量行中验证相对/绝对引用。
3. 图片公式可通过剪贴板或文件识别为 LaTeX，再按用途转成表格公式或作为说明性公式插入。
4. 应用后检查数值格式、百分比、日期、对齐、条件格式和公式填充范围。右对齐等中性格式应能安全映射，不应中断整批操作。

提示 • Tip 让 AI 在旁边新建结果列，比直接覆盖原列更安全；确认无误后再决定是否替换。

AI range edits, formulas, and write-back

AI 选区修改、公式与回填

After selecting a cell range, AI can explain data, generate formulas, clean or format, and write back. Validate every batch operation on a small range first.



Real Excel runtime: a grid selection can become precise ZenMux AI context.

1. Select the target and state whether headers are included, which columns may be added, the first formula row, and how blanks should be treated.
2. Ask for a plan and preview before applying. Test complex formulas on a few rows and verify relative versus absolute references.
3. Recognize an image formula from clipboard or file as LaTeX, then convert it to a spreadsheet formula where appropriate or insert it as explanatory math.
4. Check number formats, percentages, dates, alignment, conditional formatting, and fill range. Neutral alignment such as right-align should map safely without aborting the batch.

提示 • Tip Creating a new result column beside the source is safer than overwriting it. Replace only after verification.

PowerPoint 演示工作台


PowerPoint presentation workspace

生成并编辑真实 PPTX 对象，处理形状、公式、配图、媒体、放映录制和可编辑输出。 / Generate and edit real PPTX objects with shapes, equations, imagery, media, recording, and editable output.

打开、编辑与生成可编辑幻灯片

Open, edit, and generate editable slides

PPT 工作台直接处理 PPTX。AI 生成内容应落为可编辑文字框、形状、表格和图表，而不是每页一张不可编辑图片。



当前源码真实运行态：PPT 编辑画布、缩略图、功能区与 ZenMux AI 面板。


- 打开现有.pptx 或从 AI Slides 新建；先确定页面比例、主题、母版和受众，再生成内容。
- 双击文字框编辑文字；选择对象后调整位置、尺寸、填充、描边、字体和层级。智能参考线帮助对齐。
- AI 任务应明确“每页使用可编辑对象，不要把整页扁平化为图片”，并限制单页要点数量。
- 保存后用 PowerPoint 或兼容应用检查母版、字体、图表、动画、媒体和对象边界。

提示 · Tip 先让 AI 生成 5-8 页结构提纲，再逐页完善，比一次生成整套长演示更容易保持逻辑和版式一致。

Open, edit, and generate editable slides

打开、编辑与生成可编辑幻灯片

The presentation workspace edits PPTX directly. AI output should become editable text boxes, shapes, tables, and charts rather than one flattened image per slide.



Real runtime UI: slide canvas, thumbnails, ribbon, and ZenMux AI panel.


- Open a .pptx or create one with AI Slides. Define aspect ratio, theme, master, and audience before generating content.
- Double-click a text box to edit. Select an object to change position, size, fill, outline, font, and z-order; smart guides assist alignment.
- Explicitly request editable objects and prohibit full-slide flattening. Limit the number of ideas on each slide.
- After saving, review in PowerPoint or a compatible app, including masters, fonts, charts, animations, media, and object bounds.

提示 • Tip Generate a five-to-eight-slide outline first, then refine each page. This is easier to control than producing a long deck in one request.

形状、艺术字、表格与图表

Shapes, WordArt, tables, and charts

“绘图”页签提供覆盖 Visio 常用基本形状的 104 种可编辑形状；艺术字、表格和图表也应在画布、编辑与导出之间保持一致。



PPT 当前运行态：对象画布与功能区，适合选择后对齐、分组和调整层级。


1. 从绘图形状库插入矩形、圆、箭头、流程、标注、星形、连接线等；按住修饰键可约束比例或复制。
2. 统一填充、描边、圆角与字体；用对齐、等距分布、组合和层级减少手工误差。
3. 艺术字需要同时检查文字内容、字体、字号、填充、真实描边、旋转和缩放；避免只在屏幕上看似正确。
4. 表格单元格保持可编辑；图表的数据源、图例、轴和标签应可更新。导出前放映检查对象是否超出页面。

提示 · Tip 流程图优先使用形状和连接线，而不是一张截图；这样 AI 或用户后续仍能修改节点和文字。

Shapes, WordArt, tables, and charts

形状、艺术字、表格与图表

The Drawing tab includes 104 editable shapes covering common Visio-style basics. WordArt, tables, and charts should remain consistent across canvas, editing, and export.



Current presentation runtime: object canvas and ribbon for selection, alignment, grouping, and z-order.


1. Insert rectangles, circles, arrows, flowchart symbols, callouts, stars, and connectors from the shape library; use modifier keys to constrain or duplicate.
2. Normalize fill, outline, corners, and typography. Use align, distribute, group, and z-order rather than estimating by eye.
3. For WordArt, verify text, font, size, fill, true outline, rotation, and scaling—not only the on-screen appearance.
4. Table cells remain editable; chart data, legends, axes, and labels should remain updateable. Run a slide show to find objects outside the page.

提示 • Tip Build a process diagram from shapes and connectors instead of a screenshot so users and AI can revise nodes and labels later.

插入并播放视频、音频和图片

Insert and play video, audio, and images

PPT 支持把视频、音频和图片拖到目标幻灯片，也可从“插入”选择文件。媒体在编辑预览和放映时按插入框比例播放。



当前源码真实运行态：PPT “插入” 功能区，包含图片、媒体、公式与其他对象入口。


- 支持常见视频容器如 MP4、M4V、MOV、WebM；最终可播放性仍取决于系统解码器和媒体编码。
- 拖放时把指针放在目标位置；插入后用角点等比缩放。播放画面应适配插入框并保持原始宽高比，不应被纵向或横向压扁。
- 编辑预览和幻灯片放映都要测试开始、暂停、结束、音量以及跨页切换；不要只看静态封面帧。
- 图片同样支持拖放，插入后仍可移动、裁剪和缩放。大媒体会显著增加 PPTX 与导出视频体积。

提示 · Tip 交付前把演示复制到另一台目标平台机器测试，确认媒体路径没有断裂且声音、画面和比例都正确。

Insert and play video, audio, and images

插入并播放视频、音频和图片

Drop video, audio, or images directly onto a target slide, or choose a file under Insert. Media plays inside its inserted frame in both edit preview and slide show.



Real runtime UI: PowerPoint Insert ribbon with image, media, equation, and object entry points.

- Common video containers include MP4, M4V, MOV, and WebM. Actual playback still depends on system codecs and the media encoding.
- Drop at the intended location and resize from a corner. Playback should fit the inserted frame while preserving aspect ratio, without horizontal or vertical distortion.
- Test start, pause, end, volume, and slide transitions in both edit preview and slide show; a static poster frame is not enough.
- Images can also be dropped and remain movable, croppable, and resizable. Large media increases both PPTX and exported-video size.

提示 • Tip Test a delivery copy on another target-platform machine to catch broken media references, missing audio, or aspect-ratio differences.

录制旁白并合成 MP4

Record narration and export MP4

录制入口位于“幻灯片放映”和“插入”。应用可采集麦克风并把演示画面合成为 H.264/AAC MP4，支持暂停和继续。

1. 首次录制前在系统设置授权麦克风；macOS 还可能需屏幕录制权限。授权后完全退出并重新打开应用。
2. 选择麦克风并观察音量活动；做 10 秒测试，播放确认人声清晰、没有静音或削波。
3. macOS 会混合麦克风与 GenOffice 演示中播放的媒体声音；Windows 可使用系统回环采集系统声音。系统级音频能力受平台和权限限制。
4. 开始全屏放映，按需要暂停/继续；结束后等待编码完成，选择本地 MP4 路径，再检查画面、音画同步、比例和总时长。

注意 · Notice 若麦克风已采集但系统音频缺失，先区分“幻灯片内媒体音频”和“其他应用的系统音频”，再检查平台支持、屏幕录制/音频权限及输出设备。

Record narration and export MP4

录制旁白并合成 MP4

Recording is available from Slide Show and Insert. GenOffice captures microphone narration and composes the presentation into a local H.264/AAC MP4 with pause and resume.


1. Before the first recording, grant microphone access. macOS may also require Screen Recording permission; quit and relaunch the app after changing permissions.
2. Choose the microphone and watch input activity. Record a ten-second test and check for silence, clipping, and intelligibility.
3. macOS mixes the microphone with media played inside the GenOffice presentation. Windows can use system loopback. System-wide audio availability depends on platform and permission support.
4. Start the full-screen show, pause/resume as needed, wait for encoding, choose a local MP4 destination, then verify image, sync, aspect ratio, and duration.

注意 • Notice If narration works but system audio is missing, distinguish slide-embedded media from audio in other apps, then check platform capability, screen/audio permissions, and output device.

PPT 公式、文献与 ZenMux 配图

Equations, citations, and imagery

PPT 支持 LaTeX 公式、图片公式识别、科研文献检索与引用，并可用 ZenMux 图像模型生成适合 16:9 幻灯片的配图。



PPT “插入” 运行态：公式、图片和媒体均作为可编辑/可布局对象进入当前页。


- 从“插入 > 公式”输入或粘贴 LaTeX；多行推导先预览再放入独立公式框。识别截图时核对所有符号。
- 文献管理与 Word 共享检索和本地库；正文引用应是可编辑文字，参考文献可放在末页或备注中，并导出.bib。
- 配图提示词应包含视觉重点、留白方向、品牌颜色和 16:9 横向构图。生成后裁剪不破坏原始比例。
- 引用图像、数据或论文时在页脚给出来源；联网搜索结果需核对时间、作者和原始链接。

提示 • Tip 科学演示中，优先用可编辑图表和形状表达数据；生成式配图只承担解释或氛围，不替代真实证据。

Equations, citations, and imagery

PPT 公式、文献与 ZenMux 配图

PowerPoint supports LaTeX equations, image-to-formula recognition, scholarly search and citations, plus ZenMux imagery composed for 16:9 slides.



Real Insert runtime: equations, images, and media enter the current slide as layout-aware objects.

- Enter or paste LaTeX under Insert > Equation. Preview multiline derivations before placing them in a display box; verify every recognized symbol.
- Literature search and the local library are shared with Word. Use editable in-slide citations, place references on final slides or in notes, and export .bib.
- An illustration prompt should state visual focus, desired empty space, brand colors, and 16:9 landscape composition. Crop without distorting aspect ratio.
- Credit external images, data, and papers in the footer. Verify dates, authors, and original URLs for web-derived claims.

提示 • Tip In scientific presentations, use editable charts and shapes for evidence. Generated imagery should support explanation or mood, not substitute for real data.

Markdown 与 PDF


Markdown & PDF

用纯 Markdown 管理可编辑文本、公式与图形；用 PDF 工作台完成阅读、页面处理、水印、安全和视觉提问。 / Manage editable Markdown, equations, and diagrams; use PDF for reading, page operations, watermarks, security, and visual questions.

Markdown 基础编辑与图片

Markdown basics and images

Markdown 工作台往返保存纯.md/.markdown 文件，支持标题、列表、任务、引用、GFM 表格、链接、代码块和本地图片。




- 从主页新建 AI Markdown 或打开.md；保存会回写纯 Markdown，而不是专有二进制格式。
- 使用功能区或 Markdown 习惯插入标题、列表、任务、引用、链接、表格与 fenced code block。
- 图片可从文件选择、粘贴或拖放；优先使用相对于.md 文件的资源路径，移动文档时连同资源目录一起移动。
- 选中一段文字后，可提问、精确改写或在锚点前后插入 AI 回复；应用前确认选区卡仍对应当前内容。

提示 · Tip 交付一个 Markdown 项目时，把.md、图片目录和.bib 放在同一父目录，并用相对路径，最容易跨平台移动。

Markdown basics and images

Markdown 基础编辑与图片

The Markdown workspace round-trips plain .md/.markdown files with headings, lists, tasks, quotations, GFM tables, links, code blocks, and local images.



- Create AI Markdown or open .md. Saving writes plain Markdown rather than a proprietary binary format.
- Use the ribbon or familiar syntax for headings, lists, tasks, quotes, links, tables, and fenced code blocks.
- Insert images by picker, paste, or drop. Prefer paths relative to the .md file and move the asset folder with the document.
- Select text to ask, rewrite precisely, or insert AI output before/after the anchor. Confirm that the context card still matches before applying.

提示 • Tip For a portable Markdown project, keep the .md, image folder, and .bib under one parent directory and use relative paths.

Markdown 中的行内与多行 LaTeX

Inline and multiline math in Markdown

Markdown 支持行内公式、独立公式、多行对齐环境，以及从剪贴板或图片文件识别公式后插入。正确的定界符和反斜杠是渲染关键。

行内源文: `$F_1 = G \sin\theta$` 渲染: $F_1 = G \sin \theta$

独立多行渲染:
$$F = ma$$
$$E_k = \frac{1}{2}mv^2$$

- 使用 ASCII 美元符作为定界符，不要混用全角符号；独立公式的开闭 `$$` 各自单独成对。
- LaTeX 命令的反斜杠必须保留。下标用 `F_1`，正文中不要把命令写成被额外转义的普通文本。
- 多行环境的换行使用 `\\`；矩阵、`cases`、`aligned` 等环境必须完整闭合。
- 从图片识别后先检查 LaTeX 源文，再插入并保存；重新打开文件验证源文和渲染均正常。

提示 · Tip 如果粘贴一大段含公式的文字后没有渲染，先在纯文本视图查找不成对的美元符、丢失的反斜杠和错误的下划线转义。

Inline and multiline math in Markdown

Markdown 中的行内与多行 LaTeX

Markdown supports inline, display, and aligned multiline math plus recognition from clipboard or image files. Correct delimiters and backslashes are essential.

Inline source: `$F_1 = G \sin\theta$` Rendered: $F_1 = G \sin \theta$

Rendered multiline:
$$F = ma$$
$$E_k = \frac{1}{2}mv^2$$


- Use ASCII dollar signs, not full-width variants. Opening and closing `$$` for display math must be paired.
- Preserve command backslashes. Write a subscript as `F1`; avoid turning commands into over-escaped plain text.
- Use `\\` for line breaks and close every matrix, cases, aligned, or other environment.
- After image recognition, inspect LaTeX source before insertion. Save and reopen to verify both source and rendering.

提示 • Tip If a large pasted passage fails to render, inspect plain source for unmatched dollar signs, missing backslashes, and incorrectly escaped underscores.

Mermaid 插入、编辑与 AI 生成

Insert, edit, and generate Mermaid

Markdown 支持标准 fenced Mermaid 源码、实时渲染、源码修改，以及通过 ZenMux 自然语言生成或修改图形。




- 1. 插入 Mermaid 代码块,选择正确图类型:flowchart、sequenceDiagram、stateDiagram、classDiagram 等。
- 2. 节点文字含 @、括号、冒号或其他特殊字符时，用引号包住标签，例如 A[" 标签"]。
- 3. AI 生成后先检查语法，再检查逻辑方向、节点缺失、循环和敏感信息；修改时让 AI 返回完整 fenced block。
- 4. 保存.md 后重新打开确认渲染；导出或转 Word 时检查图形是否以合适形式保留。

注意 · Notice Mermaid “能解析”不等于逻辑正确。流程、状态和时序关系必须由熟悉业务的人核对。

Insert, edit, and generate Mermaid

Mermaid 插入、编辑与 AI 生成

Markdown supports standard fenced Mermaid source, live rendering, source edits, and ZenMux generation or modification from natural-language instructions.



1. Insert a Mermaid fence and choose the right diagram family: flowchart, sequenceDiagram, stateDiagram, classDiagram, and so on.
2. Quote node labels that contain @, parentheses, colons, or other special characters, for example A["Label"].
3. Check syntax and then logic—direction, missing nodes, cycles, and sensitive information. Ask AI to return the complete fenced block when modifying.
4. Save and reopen the .md to verify rendering. During export or Word conversion, confirm that the diagram is preserved appropriately.

注意 • Notice A Mermaid diagram that parses can still be logically wrong. A domain owner must validate process, state, and sequence relationships.

Markdown 与 Word 互转

Convert between Markdown and Word

Markdown 可导出 Word，Word 内容也可转为 Markdown。转换目标是保留结构和可编辑性，不保证两个排版模型逐像素一致。



- 转 Word 前使用规范标题层级、真实列表、GFM 表格、相对图片路径和闭合公式定界符。
- LaTeX 转为 Word 公式时检查多行结构；Mermaid 在目标格式中的表现可能是图形或可替代表示，应在导出后核对。
- Word 转 Markdown 时，复杂分页、浮动图片、艺术字、页眉页脚和某些样式无法一一映射，需要人工简化。
- 转换后同时保留源文件和目标文件；后续确定一个主版本，避免在两边交替编辑造成内容分叉。

提示 · Tip Markdown 适合版本控制与轻量协作，Word 适合复杂分页和正式交付。根据最终用途选择主格式。

Convert between Markdown and Word

Markdown 与 Word 互转

Markdown can export to Word, and Word content can be converted to Markdown. The goal is editable structure, not pixel-identical layout between two different models.



- Before Word export, use proper heading levels, real lists, GFM tables, relative image paths, and closed math delimiters.
- Verify multiline math after conversion to Word equations. Mermaid may become a graphic or alternate representation; check the exported result.
- Word-to-Markdown cannot map every pagination feature, floating image, WordArt object, header/footer, or style. Simplify manually where necessary.
- Keep both source and result. Choose one as the new master instead of alternating edits and creating divergent versions.

提示 • Tip Markdown suits version control and lightweight collaboration; Word suits complex pagination and formal delivery. Choose the master according to the final use.

Markdown 审稿、翻译与文献

Markdown review, translation, and literature

Markdown 使用与 Word 相同的严格审稿通路、选区/全文翻译和科研文献库，并支持正文引用、文末参考文献与.bib。

- 1. 审稿时选择目标标准与中英文报告；委员会检查正文、公式、表格、图片和 Mermaid 等图形。
- 2. 翻译时保护代码块、链接、引用键、LaTeX 和 Mermaid 源码；长文档按章节处理并统一术语表。
- 3. 通过科研文献入口检索或导入，使用本地库插入 Pandoc 兼容引用键；输入 /cite 从条目列表选择。
- 4. 在文末生成参考文献，并导出 BibTeX。打开纯源文确认引用键、参考文献块和图片路径都已实际写入。

提示 · Tip 翻译前把关键术语、缩写和不翻译名称整理成提示词；翻译后用原文逐段对照，而不是只检查流畅度。

Markdown review, translation, and literature

Markdown 审稿、翻译与文献

Markdown shares Word's strict review path, selection/full-document translation, and scholarly library, including in-text citations, end bibliography, and .bib export.


1. Choose a target standard and Chinese or English report. The committee reviews prose, equations, tables, images, and Mermaid diagrams.
2. During translation, protect code fences, links, citation keys, LaTeX, and Mermaid source. Process long files by section and maintain a glossary.
3. Search or import literature, then insert Pandoc-compatible keys from the local library. Type /cite to choose an entry.
4. Generate references at the end and export BibTeX. Inspect plain source to confirm that keys, bibliography block, and image paths were actually saved.

提示 • Tip Before translating, define terminology, abbreviations, and names that must remain unchanged. Compare against the source paragraph by paragraph afterward.

PDF 预览与页面处理

PDF viewing and page operations

PDF 工作台支持连续滚动、逐页和双页查看、缩放、适合页面/宽度、手形平移，以及页面提取、插入、旋转、重排和删除。



- 从主页 AI PDF、打开本地文件、系统文件关联或 PDF 专用入口打开；加密文件会要求输入打开密码。
- 阅读时根据任务切换连续、单页或双页；缩放后用手形工具平移，避免误选批注对象。
- 页面操作前另存副本。提取、插入、旋转、重排或删除后检查页码、书签、表单、签名和总页数。
- 当前 PDF 功能区不提供编辑文字、编辑图片或公式插入入口；需要内容级修改时优先回到源文件再重新导出 PDF。

注意 · Notice 页面删除和重排会改变引用页码及签名有效性。对合同、档案或签名 PDF 操作前先确认合规要求。

PDF viewing and page operations

PDF 预览与页面处理

The PDF workspace offers continuous, single-page, and two-page views; zoom, fit page/width, hand pan; and page extraction, insertion, rotation, reorder, and deletion.



- Open through AI PDF, Open local file, an operating-system association, or the dedicated PDF entry point. Encrypted files request an open password.
- Switch between continuous, single, and spread views. After zooming, use the hand tool to pan without selecting annotations accidentally.
- Save a copy before page operations. After extract, insert, rotate, reorder, or delete, check page numbers, bookmarks, forms, signatures, and total count.
- The current PDF ribbon does not expose text editing, image editing, or equation insertion. For content-level changes, edit the source document and export PDF again.

注意 · Notice Deleting or reordering pages changes cited page numbers and may invalidate signatures. Check compliance before modifying contracts, archives, or signed PDFs.

PDF 水印、批注与安全

PDF watermarks, annotation, and security

水印文字支持剪贴板粘贴、颜色、角度、不透明度和字号设置；确认并保存后写入全部 PDF 页面，而不是只显示在预览层。

1. 打开水印工具，把文字粘贴到输入框；选中文字后再粘贴可替换选区，多行内容会整理为适合水印的单行。
2. 预览颜色、角度、不透明度和字号，确认不遮挡关键正文、签名、二维码或页码。
3. 点击确定并保存副本，关闭后用另一款 PDF 阅读器重新打开，逐页确认水印已经实际写入。
4. 可使用批注、表单、签名、印章、页眉页脚和自动页码。加密时另存 AES-128 密码保护副本，避免覆盖原文件。

注意 · Notice 应用不会持久保存 PDF 密码。遗失密码可能导致副本无法打开；请通过合规的密码管理方式单独保存。

PDF watermarks, annotation, and security

PDF 水印、批注与安全

Watermark text accepts clipboard paste and configurable color, angle, opacity, and size. After confirmation and save, it is embedded on every PDF page rather than left as preview-only UI.

1. Open Watermark and paste text. Pasting over selected text replaces the selection; multiline input is normalized into a suitable single-line watermark.
2. Preview color, angle, opacity, and size, ensuring that key text, signatures, QR codes, and page numbers remain readable.
3. Confirm and save a copy, then close and reopen it in another PDF reader to verify every page contains the watermark.
4. Annotations, forms, signatures, stamps, headers/footers, and automatic page numbers are available. Save encryption as a new AES-128 protected copy rather than overwriting the source.

注意 · Notice The application does not persist PDF passwords. A lost password can make the protected copy inaccessible; store it separately with an approved password manager.

PDF 框选提问、附件与 @Connect

PDF region questions, attachments, and @Connect

在页面上拖出矩形区域，可把该区域截图作为当前问题的首要视觉上下文；PDF AI 也支持最多 5 个附件、图片粘贴与 @Connect。



1. 启用框选工具，在当前 PDF 页面拖出矩形。缩略图出现后放大确认文字、表格、图或公式完整可见；按 Esc 取消。
2. 还可添加文件、拖放或粘贴图片，总数最多 5 个。普通附件在本机解析，图片作为视觉输入。
3. 提问要指出需要识别、解释、核对或转写的对象；对于表格和公式，要求保留单位、脚注、符号和上下标。
4. AI 回复可复制，或通过 @Connect 送到已打开的 Word、Excel、PPT 或 Markdown；在目标中检查可编辑内容后保存。

提示 · Tip 网络失败后重试前，确认区域缩略图和附件仍在。对于多栏 PDF，一次只框选一个逻辑区域可显著提高识别质量。

PDF region questions, attachments, and @Connect

PDF 框选提问、附件与 @Connect

Drag a rectangle over a page to make that capture the primary visual context. PDF AI also supports up to five attachments, pasted images, and @Connect.



1. Activate region capture and drag on the current page. Inspect the thumbnail at high zoom so text, table, figure, or equation is complete; press Escape to cancel.
2. Add files by picker/drop or paste images, up to five total. Ordinary files are parsed locally; images are visual input.
3. State whether to recognize, explain, verify, or transcribe. For tables and equations, require units, footnotes, symbols, superscripts, and subscripts to be preserved.
4. Copy the reply or use @Connect to send it to an open Word, Excel, PowerPoint, or Markdown tab. Verify editability at the destination and save.

提示 • Tip Before retrying a failed network call, confirm that the region thumbnail and attachments remain. On a multicolumn page, capture one logical region at a time.

联网、可靠性与安全

Web, reliability & safety

让 AI 参考当前日期和可信来源，同时掌握超时重试、系统权限、保存恢复、隐私和交付检查。
/ Ground AI in the current date and credible sources while mastering retries, permissions, recovery, privacy, and delivery checks.

以当前系统时间为参考

Use current system time as the reference

本手册生成时系统日期为 2026-08-16。涉及“最新”“今天”“当前政策”或市场与科研进展的问题，应显式要求 AI 参考当前系统时间并联网查证。

1. 在提示词中写明时间边界，例如“以当前系统日期为截止时间，只使用 2025-01-01 之后可验证的资料”。
2. 要求回答区分“模型已有知识”“联网检索事实”“推断/预测”，并给出来源标题、机构、日期和原始链接。
3. 新闻可交叉查证 Reuters/AP、BBC、CNN、Times 等；社交平台 X 适合发现线索，不应作为唯一证据。
4. 科学问题优先核对期刊原文、Science、Nature、PubMed/PMC、学会、大学和政府数据库；预印本要明确标注未正式同行评议。

注意 · Notice 网页内容会变化，搜索摘要也可能截断语境。对高风险结论，打开原文、记录访问日期，并至少使用两个独立可信来源。

Use current system time as the reference

以当前系统时间为参考

The system date when this manual was generated is 16 August 2026. Questions about “latest,” “today,” current policy, markets, or recent science should explicitly request current-date web verification.

1. Define a time boundary: “Use the current system date as the cutoff and rely only on verifiable material after 1 January 2025.”
2. Ask the response to distinguish model knowledge, retrieved facts, and inference/forecast, with source title, institution, date, and original URL.
3. Cross-check news with sources such as Reuters/AP, BBC, CNN, or Times. Use X to discover leads, not as the sole evidence.
4. For science, prefer original papers, Science, Nature, PubMed/PMC, societies, universities, and government databases. Label preprints as not formally peer reviewed.

注意 • Notice Web pages change and search snippets omit context. For high-stakes claims, open the original, record access date, and use at least two independent credible sources.

科研检索入口与合法全文

Scholarly sources and lawful full text

科研文献功能整合开放 API 与本地文献库；其他平台通过官方搜索入口打开。优先合法 OA，避免绕过访问控制或自动抓取受限服务。

用途	推荐入口
综合元数据	OpenAlex、Crossref、Semantic Scholar
生物医学	PubMed、PMC、Europe PMC
预印本	arXiv、bioRxiv、medRxiv、SSRN、OSF
开放全文	CORE、DOAJ、BASE、机构仓储、Unpaywall
国内入口	百度学术、PubScholar、NSSD、NSTL（按官方访问规则）

- 用 DOI、题名、作者和年份组合查询；Google Scholar 适合综合发现，但应用应打开官方搜索而不是自动抓取。
- 下载前确认许可证、OA 状态和版本。作者接受稿、预印本与版本记录的内容和同行评议状态可能不同。
- 导入本地库后去重，补齐文献类型、页码与 DOI；引用时以正式版本为主，并在必要时标注预印本。

提示 · Tip Unpaywall 与 Open Access Button 可帮助寻找合法开放版本；机构订阅和文献传递也应遵守授权范围。

Scholarly sources and lawful full text

科研检索入口与合法全文

Scholarly search combines open APIs with a local library; other services open their official search pages. Prefer lawful open access and never bypass controls or scrape restricted services.

Need	Recommended entry points
General metadata	OpenAlex, Crossref, Semantic Scholar
Biomedicine	PubMed, PMC, Europe PMC
Preprints	arXiv, bioRxiv, medRxiv, SSRN, OSF
Open full text	CORE, DOAJ, BASE, repositories, Unpaywall
Chinese discovery	Baidu Scholar, PubScholar, NSSD, NSTL under official access rules

- Search with DOI or a combination of title, author, and year. Google Scholar is useful for discovery, but the app should open official search rather than scrape it.
- Check license, OA status, and version before download. Accepted manuscripts, preprints, and versions of record can differ in content and review status.
- Deduplicate the local library and complete type, pages, and DOI. Cite the formal version where possible and label a preprint when used.

提示 · Tip Unpaywall and Open Access Button help locate lawful versions. Institutional subscriptions and document delivery remain subject to their license terms.

AI 超时、流式中断与重试

AI timeout, interrupted streaming, and retry

客户端显示超时，并不一定代表供应方没有生成结果。不要立刻连续重发相同长任务；先判断请求状态并保留上下文。




1. 记录发送时间、所用模型、提示词长度和附件数量。等待短暂时间，检查当前会话是否继续出现流式内容。
2. 检查 ZenMux 状态、账户额度、网络与代理；切换到短提示词或预置模型做健康测试。
3. 若供应方控制台显示已完成但应用未回填，复制可获得的结果或在原会话重试，并保留原始提示词以便报告。
4. 重试前确认选区、PDF 区域和最多 5 个附件仍存在。长任务拆为“计划、分段生成、合并”三个阶段。

注意 • Notice 连续重复提交可能产生重复计费、多个结果或错误写回。任何自动重试都应有次数上限，并让用户看到状态。

AI timeout, interrupted streaming, and retry

AI 超时、流式中断与重试

A client timeout does not necessarily mean the provider produced no result. Do not immediately resubmit the same long task repeatedly; determine request state and preserve context first.



1. Record send time, model, prompt length, and attachment count. Wait briefly and see whether streaming resumes in the current conversation.
2. Check ZenMux status, quota, network, and proxy. Use a short prompt or built-in model as a health test.
3. If the provider console shows completion but the app did not write back, copy any available result or retry in the original conversation and retain the prompt for diagnosis.
4. Confirm that the selection, PDF region, and up to five attachments remain. Split long work into plan, sectional generation, and merge phases.

注意 · Notice Repeated submissions can cause duplicate cost, multiple results, or incorrect write-back. Any automatic retry needs a visible state and a bounded attempt count.

麦克风、屏幕录制与文件权限

Microphone, screen recording, and file permissions

桌面系统会分别控制麦克风、屏幕录制、文件夹访问和通知。权限未授权时，应用可能没有收到系统弹窗或采集到静音。

- macOS：打开“系统设置 > 隐私与安全性”，检查麦克风与屏幕录制中的 GenOffice；更改后退出应用并重新打开。
- 若列表没有 GenOffice，先从应用执行一次录制动作触发请求；仍没有时确认应用位于“应用程序”且不是从临时挂载卷运行。
- Windows：在“设置 > 隐私和安全性 > 麦克风”允许桌面应用访问；系统音频回环还取决于音频设备和驱动。
- 文件无法打开或保存时，检查目标文件夹权限、磁盘空间、只读属性、云盘同步锁和文件是否被另一应用占用。

提示 • Tip 权限排查采用最小测试：新建空白演示、录制 10 秒、保存到本地桌面，再逐项加入系统音频、媒体和复杂文件。

Microphone, screen recording, and file permissions

麦克风、屏幕录制与文件权限

Desktop systems govern microphone, screen recording, folders, and notifications separately. Without permission, no prompt may appear or recording may be silent.

- macOS: open System Settings > Privacy & Security and inspect Microphone and Screen Recording for GenOffice. Quit and relaunch after a change.
- If GenOffice is absent, start one recording action to trigger the request. If still absent, place the app in Applications and do not run it from a temporary mounted volume.
- Windows: allow desktop apps under Settings > Privacy & security > Microphone. System loopback also depends on the audio device and driver.
- If open/save fails, check folder permission, free space, read-only state, cloud-sync locks, and whether another application holds the file.

提示 • Tip Use a minimal permission test: blank presentation, ten-second recording, local Desktop save, then add system audio, media, and complex files one variable at a time.

常用快捷键与可恢复操作

Common shortcuts and recoverable actions

键盘操作在 macOS 使用 Command，在 Windows/Linux 使用 Ctrl。编辑复杂对象前先保存，应用 AI 写回后立即检查撤销。

快捷键	操作
Cmd/Ctrl+N	新建
Cmd/Ctrl+O	打开本地文件
Cmd/Ctrl+S	保存
Cmd/Ctrl+Shift+S	另存为
Cmd/Ctrl+Z	撤销
Cmd/Ctrl+Shift+Z 或 Ctrl+Y	重做
Cmd/Ctrl+C / V	复制 / 粘贴（含支持的图片粘贴）
Cmd/Ctrl+W	关闭当前标签/窗口

- PPT 还支持常见的复制格式、粘贴格式、组合、取消组合、复制对象和缩放快捷操作；具体以菜单显示为准。
- Markdown 的块级移动、复制与删除快捷键适合结构化编辑，但第一次使用时先在副本测试。
- 撤销栈只覆盖当前编辑会话；关闭、崩溃或跨应用修改后不能替代版本备份。

提示 · Tip 执行批量 AI 修改、页面删除、媒体替换或大范围格式调整前，先保存一个命名清晰的版本。

Common shortcuts and recoverable actions

常用快捷键与可恢复操作

Use Command on macOS and Ctrl on Windows/Linux. Save before editing complex objects and test Undo immediately after an AI write-back.

Shortcut	Action
Cmd/Ctrl+N	New
Cmd/Ctrl+O	Open local file
Cmd/Ctrl+S	Save
Cmd/Ctrl+Shift+S	Save As
Cmd/Ctrl+Z	Undo
Cmd/Ctrl+Shift+Z or Ctrl+Y	Redo
Cmd/Ctrl+C / V	Copy / Paste, including supported image paste
Cmd/Ctrl+W	Close current tab/window

- PowerPoint also provides common shortcuts for copy/paste formatting, group/ungroup, duplicate, and zoom; follow the menu display for the current platform.
- Markdown block move, duplicate, and delete shortcuts suit structured editing, but test them on a copy first.
- Undo covers the active editing session; it is not a substitute for versions after close, crash, or external modification.

提示 • Tip Before batch AI edits, page deletion, media replacement, or large format changes, save a clearly named version.

保存、导出与跨应用复核

Save, export, and verify in another app

“界面里看起来正确”只是第一步。DOCX、XLSX、PPTX、PDF 与 Markdown 都应在另一个兼容应用中打开，确认保存内容真正写入。

1. 保存后关闭当前文件，重新打开一次；确认图片修改、公式、表格、引用和水印不是仅存在于临时预览层。
2. DOCX 在 Word/LibreOffice，XLSX 在 Excel/LibreOffice，PPTX 在 PowerPoint/LibreOffice，PDF 在系统预览或 Acrobat，Markdown 在纯文本编辑器中复核。
3. 导出 PDF 时对比纸张大小、方向、边距、页面满幅、图像宽高、边框和浮动层级；选择几页叠加或并排核对。
4. 交付前计算文件大小和页数，检查损坏、密码、外链、媒体、字体与隐私元数据，并保留源文件。

提示 · Tip 最小验收集：第一页、包含图片的一页、包含公式/表格的一页、最后一页；复杂文档再做全页检查。

Save, export, and verify in another app

保存、导出与跨应用复核

Correct appearance inside the editor is only the first step. Open DOCX, XLSX, PPTX, PDF, and Markdown in another compatible application to confirm changes were truly written.

1. Save, close, and reopen. Confirm that image edits, equations, tables, citations, and watermarks are not merely temporary preview layers.
2. Verify DOCX in Word/LibreOffice, XLSX in Excel/LibreOffice, PPTX in PowerPoint/LibreOffice, PDF in Preview or Acrobat, and Markdown in a plain-text editor.
3. For PDF export, compare paper size, orientation, margins, full-page position, image width/height, borders, and floating z-order across representative pages.
4. Before delivery, check file size, page count, corruption, passwords, external links, media, fonts, and privacy metadata; retain the source file.

提示 • Tip A minimum acceptance sample includes the first page, an image page, an equation/table page, and the final page. Inspect every page for complex documents.

隐私、安全与更新

Privacy, security, and updates

GenOffice 本地打开、编辑和保存文件；使用 ZenMux、网络搜索或外部链接时会发生网络访问。用户负责判断哪些内容可以发送。

- API Key 使用系统安全存储并在 UI 遮罩；不要写入环境截图、日志、文档或仓库。定期轮换并使用最小额度/权限策略。
- AI 附件、选区、PDF 截图和提示词可能包含敏感信息。发送前脱敏，并遵守学校、公司、伦理、合同与数据跨境规则。
- 只从项目 Releases 下载更新；核对版本、文件名和平台。macOS 核对签名/公证，Windows 对未签名包要额外核对来源。
- 发现安全问题时，不要在公开 issue 粘贴秘密或个人数据；使用仓库 SECURITY.md 指定的渠道和最小复现文件。

注意 · Notice 本地优先不等于所有 AI 数据都留在本机。只要调用云端模型或联网工具，相关请求内容就会离开设备。

Privacy, security, and updates

隐私、安全与更新

GenOffice opens, edits, and saves files locally. ZenMux, web search, and external links create network access. The user decides what content is permitted to leave the device.

- The API Key uses operating-system secure storage and is masked in the UI. Keep it out of screenshots, logs, documents, and repositories; rotate it and limit quota/permissions.
- AI attachments, selections, PDF captures, and prompts may contain sensitive data. Redact first and follow institutional, ethics, contract, and data-transfer rules.
- Download updates only from project Releases. Verify version, filename, and platform; check macOS signing/notarization and scrutinize the source of unsigned Windows builds.
- Do not paste secrets or personal data into a public issue. Follow SECURITY.md and provide the smallest sanitized reproduction.

注意 · Notice Local-first does not mean every AI datum remains on-device. Content relevant to a cloud-model or web-tool request leaves the device.

首次使用与交付检查单

First-use and delivery checklists

最后用两个短检查单收束工作：第一次配置关注连接与权限，交付前关注可编辑性、兼容性、来源和可恢复性。

第一次使用	交付前
☐ 从官方页面安装正确平台包 ☐ 在欢迎页或设置录入 ZenMux Key ☐ 选择可用文本/配图模型 ☐ 用无隐私短问题测试连接 ☐ 测试保存与另存为 ☐ 测试麦克风/屏幕权限	☐ 保存、关闭、重新打开 ☐ 用另一兼容应用复核 ☐ 公式、表格、图片、引用逐项检查 ☐ PDF 页面、比例、水印与密码复核 ☐ 媒体和字体在目标设备测试 ☐ 保留源文件、BIB 和版本备份

- 若 AI 不工作：检查 Key、模型、网络、代理、额度、附件数量与超时状态。
- 若文件显示不一致：检查字体、页面尺寸、对象边界、图片比例和另一应用的兼容性。
- 若不知道从哪里开始：先选择一小段内容，用一句具体动作请求测试完整闭环。

提示 · Tip 官方页面: <https://bennix.github.io/GenZenMuxAI0ffice/> 源码与问题: <https://github.com/bennix/GenZenMuxAI0ffice>

First-use and delivery checklists

首次使用与交付检查单

Close with two compact checklists: first-use setup focuses on connection and permissions; delivery focuses on editability, compatibility, provenance, and recovery.

First use	Before delivery
☐ Install the right official platform build ☐ Enter the ZenMux key in welcome/settings ☐ Select working text/image models ☐ Test with a short non-private question ☐ Test Save and Save As ☐ Test microphone/screen permissions	☐ Save, close, and reopen ☐ Verify in another compatible app ☐ Check equations, tables, images, citations ☐ Verify PDF pages, ratio, watermark, password ☐ Test media and fonts on target hardware ☐ Keep source, BIB, and version backup

- If AI fails: check key, model, network, proxy, quota, attachment count, and timeout state.
- If a file differs elsewhere: check fonts, page size, object bounds, image ratio, and compatibility of the other app.
- If unsure where to start: select a small passage and test one precise action through the complete loop.

提示 · Tip Official page: <https://bennix.github.io/GenZenMuxAI0ffice/> Source and issues: <https://github.com/bennix/GenZenMuxAI0ffice>

从一个真实文件开始。

Start with a real file.

选择内容，提出明确问题，审阅结果，再写回可编辑对象。

Select context, ask precisely, review the result, then write back to editable objects.

