

# Elements of Language Processing and Learning

## Lab assignment report

### Stage 2: Adding support of Unary Rules in the CKY ALgorithm

Benno Kruit, 10576223  
Sara Veldhoen, 10545298

December 4, 2013

The CKY algorithm was originally implemented for binary rules only. We extended the code to support unary rules.

## 1 Implementation

### Grammar

- We created a general class **Rule** to replace the **BinaryRule** and **UnaryRule** classes. Occurrences of **Rule** can be either binary or unary rules. The method **getChildren()** returns an array of Strings. This enables other functions to iterate over the children in a more general way.
- We extended the class **Grammar** with **UnaryClosedGrammar**, which is a grammar that computes and stores the unary closure of all unary rules after instantiation. The methods **getUnaryRulesByParent(String)** and **getUnaryRulesByChild** are guaranteed to return the unary closure of unary rules.

### Parsing

- The Parsing algorithm itself is run with the function **getBestParse(List<String>)**. The pseudocode of the algorithm is as follows:

```
match preterminal productions
for  $max = 1 : 1 : n$ 
  for  $min = max - 1 : -1 : 0$ 
    foreach  $C \in syntacticCategories$ 
      foreach  $R \in binaryrules$ 
        for  $mid = min + 1 : 1 : max - 1$ 
          match binary rule, keep the best scoring rule and its midpoint
        end
      end
      store the best rule and midpoint in the chart
    end
    foreach  $C \in syntacticCategories$ 
      foreach  $R \in unaryclosure$ 
        match unary rule, keep the best scoring rule
      end
      if ( $bestScoringUnary > bestStoredInChart$ )
        replace this position in the chart with the unary rule
      end
    end
  end
end
end
```

- Traverse backpointers

## 2 Results