

Namespace NetAF.Adapters

Classes

Filter by title

SystemConsoleAdapter (NetAF.Adapters.SystemConsoleAdapter.html)

Provides an adapter for the System.Console.
[\(NetAF.Adapters.html\)](#)

IIOAdapter

Interfaces

[\(NetAF.Adapters.IIOAdapter.html\)](#)

SystemConsoleAdapter

[\(NetAF.Adapters.SystemConsoleAdap](#)

IIOAdapter (NetAF.Adapters.IIOAdapter.html)

+ **NetAF.Assets**

Represents any object that provides an adapter for input.
[\(NetAF.Assets.html\)](#)

+ **NetAF.Assets.Attributes**

[\(NetAF.Assets.Attributes.html\)](#)

+ **NetAF.Assets.Characters**

[\(NetAF.Assets.Characters.html\)](#)

+ **NetAF.Assets.Locations**

[\(NetAF.Assets.Locations.html\)](#)

+ **NetAF.Commands**

[\(NetAF.Commands.html\)](#)

+ **NetAF.Commands.**

Conversation

[\(NetAF.Commands.Conversation.html\)](#)

+ **NetAF.Commands.Frame**

[\(NetAF.Commands.Frame.html\)](#)

+ **NetAF.Commands.Global**

[\(NetAF.Commands.Global.html\)](#)

+ **NetAF.Commands.**

Persistence

[\(NetAF.Commands.Persistence.html\)](#)

+ **NetAF.Commands.Region**

Map

[\(NetAF.Commands.RegionMap.html\)](#)

Interface IIOAdapter

Represents any object that provides an adapter for input.

Filter by title

Namespace: NetAF (NetAF.html).Adapters (NetAF.Adapters.html)

Assemblies

(NetAF.Adapters.html)

```
IIOAdapter  
public interface IIOAdapter  
(NetAF.Adapters.IIOAdapter.html)  
SystemConsoleAdapter  
(NetAF.Adapters.SystemConsoleAd
```

+ NetAF.Assets

Methods

+ NetAF.Assets.Attributes

RenderFrame (Attributes.html)

+ NetAF.Assets.Characters

Declaration
(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

RenderFrame (Locations.html)

+ NetAF.Commands

Parameters
(NetAF.Commands.html)

Type

+ NetAF.Commands.

IFrame (NetAF.Rendering.Frames.IFrame.html)

Name

Description

frame

The frame to render.

Conversation

(NetAF.Commands.Conversation.html)

+ NetAF.Commands.Frame

Setup(Game)

(NetAF.Commands.Frame.html)

Setup for a game.

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

void Setup(Game game)

Persistence

(NetAF.Commands.Persistence.html)

Parameters

+ NetAF.Commands.Region

Type

Map

GameRegion (GameRegion.html)

Name

Description

game

The game to set up for.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

WaitForAcknowledge()

+ NetAF.Conversations

Wait for acknowledgment.

Declaration

```
bool WaitForAcknowledge()
```

>Returns

Type	Description
bool (NetAF.Adapters.html) (https://learn.microsoft.com/dotnet/api/system.boolean) n) (NetAF.Adapters.IIOAdapter.html) SystemConsoleAdapter (NetAF.Adapters.SystemConsoleA	True if the acknowledgment was received correctly, else false.

+ [WaitForInput\(\)](#) [NetAF.Assets](#)

[\(NetAF.Assets.html\)](#)
Wait for input.

+ [NetAF.Assets.Attributes](#)

Declaration
[\(NetAF.Assets.Attributes.html\)](#)

+ [NetAF.Assets.Characters](#)

[\(NetAF.Assets.Characters.html\)](#)

Returns

+ [NetAF.Assets.Locations](#)

Type
[\(NetAF.Assets.Locations.html\)](#)

+ [NetAF.Commands](#)
[\(NetAF.Commands.html\)](#)

+ [NetAF.Commands.](#)

[Conversation](#)

[\(NetAF.Commands.Conversation.html\)](#)

+ [NetAF.Commands.Frame](#)

[\(NetAF.Commands.Frame.html\)](#)

+ [NetAF.Commands.Global](#)

[\(NetAF.Commands.Global.html\)](#)

+ [NetAF.Commands.](#)

[Persistence](#)

[\(NetAF.Commands.Persistence.html\)](#)

+ [NetAF.Commands.Region](#)

[Map](#)

[\(NetAF.Commands.RegionMap.html\)](#)

+ [NetAF.Commands.Scene](#)

[\(NetAF.Commands.Scene.html\)](#)

+ [NetAF.Conversations](#)

Class SystemConsoleAdapter

Provides an adapter for the System.Console.

Filter by title

Inheritance

+ NetAF.Adapters

↳ [Object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Adapters.html\)](#)

Implements

[IIOAdapter](#)
[\(NetAF.Adapters.IIOAdapter.html\)](#)
[IIOAdapter](#) ([NetAF.Adapters.IIOAdapter.html](#))

Inherited Members
[\(NetAF.Adapters.SystemConsoleAdapter\)](#)

[object.Equals\(object\)](#) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

[\(NetAF.Assets.html\)](#)

[object.Equals\(object, object\)](#) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object-object)))

[\(NetAF.Assets.Attributes.html\)](#)

[object.GetHashCode\(\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

[object.GetType\(\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

[+ NetAF.Assets.Characters](#)

[object.ReferenceEquals\(object, object\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

[\(NetAF.Assets.Characters.html\)](#)

Namespace: NetAF ([NetAF.html](#)).Adapters ([NetAF.Adapters.html](#))

+ NetAF.Assets.Locations

Assembly: [NetAF.dll](#)

[\(NetAF.Assets.Locations.html\)](#)

Syntax

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

public sealed class SystemConsoleAdapter : IIIOAdapter

+ NetAF.Commands.

Conversation

[\(NetAF.Commands.Conversation.html\)](#)

Methods

+ NetAF.Commands.Frame

[\(NetAF.Commands.Frame.html\)](#)

RenderFrame(IFrame)

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

Delegates

Persistence

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.Region

Parameters

Map

[\(NetAF.Commands.RegionMap.html\)](#)

Name

Description

+ NetAF.Commands.Scene

frame

The frame to render.

[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

Setup(Game)

Setup for a game.

Declaration

```
public void Setup(Game game)
```

Part: NetAFAdapters

Type	Name	Description
IIOAdapter Game (NetAF.Logic.Game.html) (NetAF.Adapters.IIOAdapter.html)	game	The game to set up for.

SystemConsoleAdapter
(NetAF.Adapters.SystemConsoleA

+ NetAFAssets

WaitForAcknowledge()

Declarative

(NetAFAssets.Attributes.html)

```
public bool WaitForAcknowledge()
```

+ NetAFAssets.Characters

(NetAFAssets.Characters.htm

Returns

+ NetAFAssets.Locations

Type
(NetAFAssets.Locations.html)

bool

+ NetAFCommands

(https://learn.microsoft.com/dotnet/api/system.boolean)(NetAFCommands.html)

+ NetAFCommands.

Conversation

WaitForInput()

(NetAFCommands.Conversati

WaitForInput

+ NetAFCommands.Frame

(NetAFCommands.Frame.html)

Declaration

+ NetAFCommands.Global

```
public string WaitForInput()
```

+ NetAFCommands.

Returns

Persistence

Type
(NetAFCommands.Persistence)

string (https://learn.microsoft.com/dotnet/api/system.string)

+ NetAFCommands.Region

Map

(NetAFCommands.RegionMap)

Implements

+ NetAFCommands.Scene

IIOAdapter (NetAF.Adapters.IIOAdapter.html)

(NetAFCommands.Scene.html)

+ NetAF Conversations



- **NetAF.Adapters**
[\(NetAF.Adapters.html\)](#)
 - IIOAdapter
[\(NetAF.Adapters.IIOAdapter.html\)](#)
 - SystemConsoleAdapter
[\(NetAF.Adapters.SystemConsoleAd](#)
- + **NetAF.Assets**
[\(NetAF.Assets.html\)](#)
- + **NetAF.Assets.Attributes**
[\(NetAF.Assets.Attributes.html\)](#)
- + **NetAF.Assets.Characters**
[\(NetAF.Assets.Characters.htm](#)
- + **NetAF.Assets.Locations**
[\(NetAF.Assets.Locations.html\)](#)
- + **NetAF.Commands**
[\(NetAF.Commands.html\)](#)
- + **NetAF.Commands.**
Conversation
[\(NetAF.Commands.Conversati](#)
- + **NetAF.Commands.Frame**
[\(NetAF.Commands.Frame.html\)](#)
- + **NetAF.Commands.Global**
[\(NetAF.Commands.Global.htm](#)
- + **NetAF.Commands.**
Persistence
[\(NetAF.Commands.Persistence](#)
- + **NetAF.Commands.Region**
Map
[\(NetAF.Commands.RegionMap](#)
- + **NetAF.Commands.Scene**
[\(NetAF.Commands.Scene.html\)](#)
- + **NetAF Conversations**

Structs

Point2D (NetAF.Assets.Point2D.html)

Represents a two-dimensional point.



Point3D (NetAF.Assets.Point3D.html)

+ NetAF.Adapters

Represents a three-dimensional point.
(NetAF.Adapters.html)

Size (NetAF.Assets.Size.html)

(NetAF.Assets.html)

Represents a size.

Condition

(NetAF.Assets.Condition.html)

Interfaces

ConditionalDescription

(NetAF.Assets.ConditionalDescriptor)

Description

IExaminable (NetAF.Assets.IIExaminable.html)

(NetAF.Assets.Description.html)

Represents any object that is examinable.

ExaminableObject

(NetAF.Assets.ExaminableObject.h)

ExaminationCallback

IIInteractWithItem (NetAF.Assets.IIInteractWithItem.html)

(NetAF.Assets.ExaminationCallback)

Represents any object that can interact with an item.

ExaminationRequest

(NetAF.Assets.ExaminationRequest)

ExaminationResult

IIItemContainer (NetAF.Assets.IIItemContainer.html)

(NetAF.Assets.ExaminationResult.h)

Represents any object that is a container of items.

ExaminationScene

(NetAF.Assets.ExaminationScene.h)

IExaminable

IPlayerVisible (NetAF.Assets.IPlayerVisible.html)

(NetAF.Assets.Examinable.html)

Represents any object that is visible to a player.

(NetAF.Assets.IIInteractWithItem.h)

Enums

ItemContainer

(NetAF.Assets.IIItemContainer.html)

IPlayerVisible

(NetAF.Assets.IPlayerVisible.html)

Identifier

Enumeration of interaction results.

(NetAF.Assets.Identifier.html)

Interaction

Delegates

(NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.h)

Condition (NetAF.Assets.Condition.html)

InteractionResult

(NetAF.Assets.InteractionResult.h)

Represents a callback for interactions.

Item (NetAF.Assets.Item.html)

Point2D

ExaminationCallback (NetAF.Assets.ExaminationCallback.html)

(NetAF.Assets.ExaminationCallback.h)

Represents the callback for examinations.

Point3D

InteractionCallback (NetAF.Assets.InteractionCallback.html)

Represents the callback for interacting with objects.



- + **NetAF.Adapters**
(NetAF.Adapters.html)
 - **NetAF.Assets**
(NetAF.Assets.html)
 - Condition
(NetAF.Assets.Condition.html)
 - ConditionalDescription
(NetAF.Assets.ConditionalDescription.html)
 - Description
(NetAF.Assets.Description.html)
 - ExaminableObject
(NetAF.Assets.ExaminableObject.html)
 - ExaminationCallback
(NetAF.Assets.ExaminationCallback.html)
 - ExaminationRequest
(NetAF.Assets.ExaminationRequest.html)
 - ExaminationResult
(NetAF.Assets.ExaminationResult.html)
 - ExaminationScene
(NetAF.Assets.ExaminationScene.html)
 - IExaminable
(NetAF.Assets.IExaminable.html)
 - IInteractWithItem
(NetAF.Assets.IInteractWithItem.html)
 - IItemContainer
(NetAF.Assets.IItemContainer.html)
 - IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)
 - Identifier
(NetAF.Assets.Identifier.html)
 - Interaction
(NetAF.Assets.Interaction.html)
 - InteractionCallback
(NetAF.Assets.InteractionCallback.html)
 - InteractionResult
(NetAF.Assets.InteractionResult.html)
 - Item (NetAF.Assets.Item.html)
 - Point2D
(NetAF.Assets.Point2D.html)
 - Point3D
(NetAF.Assets.Point3D.html)

Delegate Condition

Represents a callback for conditions.

 Filter by title

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html)

+ NetAF.Adapters
Assembly: NetAF.dll

Assembly: NetAF.dll

(NetAF.Adapters.html)

- NetAEAssets

(Net) Assets, Net Assets, and Condition

Condition

Returns [NetAF.Assets.Condition.html](#)

Type	ConditionalDescription (NetAF.Assets.ConditionalDescriptor.html) boolean (Learn.microsoft.com/dotnet/api/system.boolean) Description (NetAF.Assets.Description.html) ExaminableObject (NetAF.Assets.ExaminableObject.html) ExaminationCallback (NetAF.Assets.ExaminationCallback.html) ExaminationRequest (NetAF.Assets.ExaminationRequest.html) ExaminationResult (NetAF.Assets.ExaminationResult.html) ExaminationScene (NetAF.Assets.ExaminationScene.html) IExaminable (NetAF.Assets.IExaminable.html) IInteractWithItem (NetAF.Assets.IInteractWithItem.html) IItemContainer (NetAF.Assets.IItemContainer.html) IPlayerVisible (NetAF.Assets.IPlayerVisible.html) Identifier (NetAF.Assets.Identifier.html) Interaction (NetAF.Assets.Interaction.html) InteractionCallback (NetAF.Assets.InteractionCallback.html) InteractionResult (NetAF.Assets.InteractionResult.html) Item (NetAF.Assets.Item.html)	Description
	The result of the condition.	

Class ConditionalDescription

Represents a conditional description of an object.

Filter by title

Inheritance

([NetAF.Adapters.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

- [NetAF.Assets](#) ([NetAF.Assets.Description.html](#))

([NetAF.Assets.html](#))

Inherited Members

([NetAF.Assets.Condition.html](#))

Description.Empty ([NetAF.Assets.Description.html#NetAF_Assets_Description_Empty](#))

ConditionalDescription

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

Description

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

ExaminableObject

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

([NetAF.Assets.ExaminableObject.html](#))

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

ExaminationCallback

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

([NetAF.Assets.ExaminationCallback.html](#))

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

ExaminationRequest

Namespace: [NetAF](#) ([NetAF.html](#)), [Assets](#) ([NetAF.Assets.html](#))

([NetAF.Assets.ExaminationRequest.html](#))

Assembly: [NetAF](#)

ExaminationResult

Syntax: [NetAF.Assets.ExaminationResult.I](#)

ExaminationScene

([NetAF.Assets.ExaminationScene.html](#))

public sealed class ConditionalDescription : Description

IExaminable

([NetAF.Assets.IExaminable.html](#))

IInteractWithItem

([NetAF.Assets.IInteractWithItem.html](#))

IItemContainer

([NetAF.Assets.IItemContainer.html](#))

IPlayerVisible

([NetAF.Assets.IPlayerVisible.html](#))

Represents a conditional description of an object.

Identifier

Declaration: [NetAF.Assets.Identifier.html](#)

Interaction

([NetAF.Assets.Interaction.html](#))

public ConditionalDescription(string trueDescription, string falseDescription, Condition interactionCallback)

([NetAF.Assets.InteractionCallback.html](#))

InteractionResult

Parameters

([NetAF.Assets.InteractionResult.html](#))

Type: [Item](#) ([NetAF.Assets.Item.html](#))

Point2D

string (<https://learn.microsoft.com/dotnet/api/system.string>)

([NetAF.Assets.Point2D.html](#))

Type: [Point3D](#) string (<https://learn.microsoft.com/dotnet/api/system.string>)

([NetAF.Assets.Point3D.html](#))

Result

Type	Name	Description
Item (NetAF.Assets.Item.html)	trueDescription	The true description.
Point2D string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Assets.Point2D.html)	falseDescription	The false description.

Type	Name	Description
Condition (NetAF.Assets.Condition.html)	<i>condition</i>	The condition.

Properties

(NetAF.Adapters.html)

Condition

(NetAF.Assets.html)

Get or Set the condition

Condition

Declaration

(NetAF.Assets.Condition.html)

ConditionalDescription

```
public Condition ConditionalDescription { get; set; }
```

Description

(NetAF.Assets.Description.html)

Property Value

ExaminableObject

Type (NetAF.Assets.ExaminableObject.h)

Description

ExaminationCallback

Condition (NetAF.Assets.Condition.html)

(NetAF.Assets.ExaminationCallback)

ExaminationRequest

(NetAF.Assets.ExaminationRequest)

ExaminationResult

(NetAF.Assets.ExaminationResult.I)

ExaminationScene

(NetAF.Assets.ExaminationScene.I)

GetDescription()

IExaminable

(NetAF.Assets.IExaminable.html)

Get the description.

IInteractWithItem

Declaration (NetAF.Assets.IInteractWithItem.html)

ItemContainer

(NetAF.Assets.ItemContainer.html)

Description

(NetAF.Assets.ItemContainer.html)

Description

(NetAF.Assets.ItemContainer.html)

Returns Identifier

Type (NetAF.Assets.Identifier.html)

Description

Interaction

string (<https://learn.microsoft.com/dotnet/api/system.string>)

The description.

(NetAF.Assets.Interaction.html)

InteractionCallback

OVERRIDES (NetAF.Assets.InteractionCallback)

Description GetDescription() (NetAF.Assets.Description.html#NetAF_Assets_Description_GetDescription)

(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Result

Class Description

Represents a description of an object.

Filter by title

Inheritance

↳ [NetAF.Assets](#)([arn.microsoft.com/dotnet/api/system.object](https://learn.microsoft.com/dotnet/api/system.object))

([NetAF.Assets.html](#))

↳ [ConditionalDescription](#) ([NetAF.Assets.ConditionalDescription.html](#))
Condition

Inherited Members

([NetAF.Assets.Condition.html](#))

ConditionalDescription

[object.Equals\(object\)](#) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

Description

[object.Equals\(object, object\)](#) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

ExaminableObject

[object.GetHashCode\(\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

([NetAF.Assets.ExaminableObject.html](#))

ExaminationCallback

[object.MemberwiseClone\(\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

([NetAF.Assets.ExaminationCallback.html](#))

[object.ReferenceEquals\(object, object\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

ExaminationRequest

[object.ToString\(\)](#) (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Assets.ExaminationRequests.html](#))

Namespace

([NetAF.html](#)).Assets ([NetAF.Assets.html](#))

ExaminationResult

Assembly

([NetAF.html](#)).Assets.ExaminationResult.I

Syntax

([NetAF.Assets.ExaminationScene.html](#))

IExaminable

public class Description

([NetAF.Assets.IExaminable.html](#))

IInteractWithItem

([NetAF.Assets.IInteractWithItem.html](#))

ItemContainer

([NetAF.Assets.IItemContainer.html](#))

IPlayerVisible

([NetAF.Assets.IPlayerVisible.html](#))

Identifier

Represents a description of an object.

([NetAF.Assets.Identifier.html](#))

Declaration

([NetAF.Assets.Interaction.html](#))

public class Description(string description)

([NetAF.Assets.InteractionCallback.html](#))

InteractionResult

Parameters

([NetAF.Assets.InteractionResult.html](#))

Type Item ([NetAF.Assets.Item.html](#))

Name

Description

Point2D

string (<https://learn.microsoft.com/dotnet/api/system.string>)

([NetAF.Assets.Point2D.html](#))

description

The description

Point3D

([NetAF.Assets.Point3D.html](#))

Result

([NetAF.Assets.Result.html](#))

Properties

DefaultDescription

Get or set the description.

Declaration

- NetAF.Assets

```
protected String DefaultDescription { get; set; }
```

(NetAF.Assets.html)

Property Value

(NetAF.Assets.Condition.html)

Type ConditionalDescription

Description

(NetAF.Assets.ConditionalDescriptor.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Description

(NetAF.Assets.Description.html)

ExaminableObject

Empty

NetAF.Assets.ExaminableObject.html

ExaminationCallback

Get an empty description.

(NetAF.Assets.ExaminationCallback.html)

Declaration

ExaminationRequest

(NetAF.Assets.ExaminationRequest.html)

ExaminationResult

```
public static Description Empty { get; }
```

(NetAF.Assets.ExaminationResult.html)

ExaminationScene

Property Value

(NetAF.Assets.ExaminationScene.html)

Type

IExaminable

(NetAF.Assets.IExaminable.html)

Description

Description (NetAF.Assets.Description.html)

(NetAF.Assets.IInteractWithItem.html)

IItemContainer

(NetAF.Assets.IItemContainer.html)

Methods

GetDescription()

Interaction

Get the description.

(NetAF.Assets.Interaction.html)

InteractionCallback

Declaration

(NetAF.Assets.InteractionCallback.html)

InteractionResult

```
public virtual string GetDescription()
```

(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Return

Point2D (NetAF.Assets.Point2D.html)

Description

Type

Point3D

(NetAF.Assets.Point3D.html)

The description.

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Result

(NetAF.Assets.Result.html)



- **NetAF.Assets**

(NetAF.Assets.html)

Condition
(NetAF.Assets.Condition.html)

ConditionalDescription
(NetAF.Assets.ConditionalDescription.html)

Description
(NetAF.Assets.Description.html)

ExaminableObject
(NetAF.Assets.ExaminableObject.html)

ExaminationCallback
(NetAF.Assets.ExaminationCallback.html)

ExaminationRequest
(NetAF.Assets.ExaminationRequest.html)

ExaminationResult
(NetAF.Assets.ExaminationResult.html)

ExaminationScene
(NetAF.Assets.ExaminationScene.html)

IExaminable
(NetAF.Assets.IExaminable.html)

IInteractWithItem
(NetAF.Assets.IInteractWithItem.html)

ItemContainer
(NetAF.Assets.IItemContainer.html)

IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)

Identifier
(NetAF.Assets.Identifier.html)

Interaction
(NetAF.Assets.Interaction.html)

InteractionCallback
(NetAF.Assets.InteractionCallback.html)

InteractionResult
(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Point2D
(NetAF.Assets.Point2D.html)

Point3D
(NetAF.Assets.Point3D.html)

Result
(NetAF.Assets.Result.html)

Class ExaminableObject

Represents an object that can be examined.

Filter by title

Inheritance

- NetAF.Assets

↳ [https://learn.microsoft.com/dotnet/api/system.object\)](https://learn.microsoft.com/dotnet/api/system.object)
↳ ExaminableObject
Condition
↳ Character (NetAF.Assets.Characters.Character.html)
(NetAF.Assets.Condition.html)
↳ Item (NetAF.Assets.Item.html)
ConditionalDescription
↳ Exit (NetAF.Assets.Locations.Exit.html)
(NetAF.Assets.ConditionalDescript
↳ Overworld (NetAF.Assets.Locations.Overworld.html)
Description
↳ Region (NetAF.Assets.Locations.Region.html)
(NetAF.Assets.Description.html)
↳ Room (NetAF.Assets.Locations.Room.html)
ExaminableObject

Implements

IExaminable (NetAF.Assets.IExaminable.html)

IPlayable (NetAF.Assets.IPlayable.html)

IRestoreFromObjectSerialization (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)<Examinable

Serializable (NetAF.Serialization.Serializable.html)

ExaminationResult

Inherited Members

(NetAF.Assets.ExaminationResult.I

object.Equals (object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))
NetAF.Assets.ExaminationScene.I

object.Equals (object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object))

object.GetHashCode () (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType () (https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.MemberwiseClone () (https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone)

object.ReferenceEquals (object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

object.ToString () (https://learn.microsoft.com/dotnet/api/system.object.tostring)

(NetAF.Assets.PlayerVisible.html)

Namespace

NetAF (NetAF.html)

Assets (NetAF.Assets.html)

Identifier

Assembly

NetAF.dll

(NetAF.Assets.Identifier.html)

Syntax

Interaction

(NetAF.Assets.Interaction.html)

public class ExaminableObject : IExaminable, IPlayerVisible, IRestoreFromObjectSerializa
tion<ExaminableSerialization>
(NetAF.Assets.InteractionCallback.
InteractionResult

(NetAF.Assets.InteractionDateResult.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Attributes

Result

Get the examination result for this object.

Size (NetAF.Assets.Size.html)

Get the size of this object.

Declaration

```
public AttributeManager Attributes { get; }
```

Property Value

Type	Description
- NetAF.Assets AttributeManager (NetAF.Assets.Attributes.AttributeManager.html) (NetAF.Assets.html)	

Condition

(NetAF.Assets.Condition.html)

ConditionalDescription

Get the conditional description.

Description

Declaration
(NetAF.Assets.Description.html)

ExaminableObject

```
public CustomCommand[] Commands { get; protected set; }
```

ExaminationCallback

(NetAF.Assets.ExaminationCallback.html)

ExaminationRequest

Type
(NetAF.Assets.ExaminationRequest.html)

ExaminationResult

CustomCommand (NetAF.Commands.CustomCommand.html)[]
(NetAF.Assets.ExaminationResult.html)

ExaminationScene

(NetAF.Assets.ExaminationScene.html)

Examinable

(NetAF.Assets.IExaminable.html)

Get a description of this object.

InteractWithItem

Declaration
(NetAF.Assets.IInteractWithItem.html)

ItemContainer

(NetAF.Assets.ItemContainer.html)

```
public Description Description { get; protected set; }
```

IPlayerVisible

(NetAF.Assets.IPlayerVisible.html)

Identifier

Type
(NetAF.Assets.Identifier.html)

Interaction

Description (NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

(NetAF.Assets.InteractionDate.html)

Item

(NetAF.Assets.Item.html)

Get the callback handling an examination of this object.

Point2D

Declaration
(NetAF.Assets.Point2D.html)

Point3D

public ExaminationCallback Examination { get; protected set; }

Result

(NetAF.Assets.Result.html)

Size

(NetAF.Assets.Size.html)

Property Value

Size (NetAF.Assets.Size.html)

Type	Description
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	

Identifier

Get this object's identifier.

NetAF.Assets

(NetAF.Assets.html)

Declaration

```
public NetAF.Assets.Identifier Identifier { get; protected set; }
```

ConditionalDescription

```
(NetAF.Assets.ConditionalDescription)
```

Property Value

Description

Type	Description
NetAF.Assets.Identifier.html	

ExaminableObject

```
Identifier (NetAF.Assets.Identifier.html)
```

```
(NetAF.Assets.ExaminableObject.html)
```

ExaminationCallback

```
(NetAF.Assets.ExaminationCallback.html)
```

ExaminationRequest

```
(NetAF.Assets.ExaminationRequest.html)
```

Get if this is visible to the player.

IsPlayerVisible

Declaration

ExaminationScene

```
(NetAF.Assets.ExaminationScene.html)
```

```
public bool IsPlayerVisible { get; set; }
```

IExaminable

```
(NetAF.Assets.IExaminable.html)
```

InteractWithItem

```
(NetAF.Assets.IInteractWithItem.html)
```

Type

ItemContainer

Type	Description
NetAF.Assets.ItemContainer.html	

bool	(https://learn.microsoft.com/dotnet/api/system.boolean)
------	---

IPlayerVisible

```
(NetAF.Assets.IPlayerVisible.html)
```

Identifier

```
(NetAF.Assets.Identifier.html)
```

Interaction

```
(NetAF.Assets.Interaction.html)
```

InteractionCallback

```
(NetAF.Assets.InteractionCallback.html)
```

Examine this object.

Declaration

```
Item (NetAF.Assets.Item.html)
```

Point2D

```
(NetAF.Assets.Point2D.html)
```

Point3D

```
(NetAF.Assets.Point3D.html)
```

Parameters

Result

```
(NetAF.Assets.Result.html)
```

Size (NetAF.Assets.Size.html)

Methods

Examine(ExaminationScene)

Declaration

```
Item (NetAF.Assets.Item.html)
```

Point2D

```
(NetAF.Assets.Point2D.html)
```

Point3D

```
(NetAF.Assets.Point3D.html)
```

Parameters

Result

```
(NetAF.Assets.Result.html)
```

Size (NetAF.Assets.Size.html)

Type	Name	Description
ExaminationScene (NetAF.Assets.ExaminationScene.html)	scene	The scene this object is being examined from.

Returns

Type	Description
- NetAF.Assets.ExaminationResult (NetAF.Assets.html) (NetAF.Assets.ExaminationResult.html)	A ExaminationResult detailing the examination of this object.

Condition
(NetAF.Assets.Condition.html)

ConditionalDescription
(NetAF.Assets.ConditionalDescription.html)

RestoreFrom(ExaminableSerialization)

Description
Restore this object from a serialization.
(NetAF.Assets.Description.html)

Declaration

ExaminableObject
(NetAF.Assets.ExaminableObject.html)

ExaminationCallback
public void RestoreFrom(ExaminableSerialization serialization)
(NetAF.Assets.ExaminationCallback.html)

ExaminationRequest

Parameters
(NetAF.Assets.ExaminationRequest.html)

Type	Name	Description
ExaminationResult (NetAF.Assets.ExaminationResult.html)	serialization	The serialization to restore from.

IExaminable

(NetAF.Assets.IExaminable.html)

Implementations

(NetAF.Assets.IInteractWithItem.html)

IExaminable
(NetAF.Assets.IExaminable.html)

ItemContainer
(NetAF.Assets.ItemContainer.html)

IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)

IRestoreFromObjectSerialization<T>
(NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)

Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

(NetAF.Assets.InteractionDateResult.html)

Item
(NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Result

(NetAF.Assets.Result.html)

Size
(NetAF.Assets.Size.html)

Delegate ExaminationCallback

Represents the callback for examinations.

 Filter by title

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html)

(NetAF.Assets.html)

Assembly: NetAF.dll

Condition

(NetAF.Assets.Condition.html)

ConditionalDescription

public delegate ExaminationResult ExaminationCallback(ExaminationRequest request)
(NetAF.Assets.ConditionalDescriptor)

Description

(NetAF.Assets.Description.html)

ExaminableObject

(NetAF.Assets.ExaminableObject.html)

ExaminationCallback

(NetAF.Assets.ExaminationCallback.html)

Name

Description

request

The examination request.

ExaminationRequest

(NetAF.Assets.ExaminationRequest.html)

Returns

(NetAF.Assets.ExaminationResult.html)

Type

Description

(NetAF.Assets.ExaminationResult.html)

A string representing the result of the examination.

ExaminationScene

(NetAF.Assets.ExaminationScene.html)

IExaminable

(NetAF.Assets.IExaminable.html)

IIInteractWithItem

(NetAF.Assets.IIInteractWithItem.html)

IItemContainer

(NetAF.Assets.IItemContainer.html)

IPlayerVisible

(NetAF.Assets.IPlayerVisible.html)

Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Class ExaminationRequest

Represents a request to examine an IExaminable.

Filter by title

Inheritance

Condition	
↳ object	(https://learn.microsoft.com/dotnet/api/system.object) (NetAF.Assets.Condition.html)
↳ ExaminationRequest	
↳ ConditionalDescription	
Inherited Members	(NetAF.Assets.ConditionalDescriptor)
Description	
object.Equals(object)	(https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)) (NetAF.Assets.Description.html)
ExaminableObject	
object.Equals(object, object)	(https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)) (NetAF.Assets.ExaminableObject.html)
ExaminationCallback	
object.GetHashCode()	(https://learn.microsoft.com/dotnet/api/system.object.gethashcode) (NetAF.Assets.ExaminationCallback.html)
object.GetType()	(https://learn.microsoft.com/dotnet/api/system.object.gettype) (NetAF.Assets.ExaminationRequest.html)
object.MemberwiseClone()	(https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone) (NetAF.Assets.ExaminationRequest.html)
object.ReferenceEquals(object, object)	(https://learn.microsoft.com/dotnet/api/system.object.referenceequals) (NetAF.Assets.ExaminationResult.html)
object.ToString()	(https://learn.microsoft.com/dotnet/api/system.object.tostring) (NetAF.Assets.ExaminationResult.html)
Namespace	NetAF (NetAF.html).Assets (NetAF.Assets.html)
ExaminationScene	
Assembly	NetAF
Assembly	(NetAF.Assets.ExaminationScene.html)

Syntax

IExaminable	
	(NetAF.Assets.IExaminable.html)
IIteractWithItem	
public class ExaminationRequest	(NetAF.Assets.IIInteractWithItem.html)
ItemContainer	

Constructors

IPlayerVisible	
	(NetAF.Assets.IPlayerVisible.html)
Identifier	

ExaminationRequest(IExaminable, ExaminationScene)

Interaction
Represents a request to examine an IExaminable.
(NetAF.Assets.Interaction.html)

Declaration

InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

public ExaminationRequest(IExaminable examinable, ExaminationScene scene)

(NetAF.Assets.InteractionDate.html)

Item

(NetAF.Assets.Item.html)

Parameters

Point2D

Type	Name	Description
Point2D		
IExaminable (NetAF.Assets.IExaminable.html) (NetAF.Assets.Point3D.html)	examinable	The object being examined.
Result		
ExaminationScene (NetAF.Assets.Result.html) (NetAF.Assets.ExaminationScene.html)	scene	The scene the object is being examined from.
Size (NetAF.Assets.Size.html)		

+ NetAF.Assets.Attributes

ExaminationRequest(IExaminable, Game)

Initializes a new instance of the ExaminationRequest class.

Declaration

```
public ExaminationRequest(IExaminable examinable, Game game)
```

Parameters

Type	Name	Description
(NetAF.Assets.Condition.html) ConditionalDescription		
IExaminable (NetAF.Assets.IExaminable.html) Description	examinable	The object being examined.
Game (NetAF.Logic.Game.html) (NetAF.Assets.Description.html)	game	The executing game.

Condition

ExaminableObject
(NetAF.Assets.ExaminableObject.html)

ExaminationCallback

Properties
.ExaminationCallback

ExaminationRequest

(NetAF.Assets.ExaminationRequest.html)

ExaminableResult

(NetAF.Assets.ExaminationResult.html)

Get the examinable object.

ExaminationScene

(NetAF.Assets.ExaminationScene.html)

Declaration

IExaminable

(NetAF.Assets.IExaminable.html)

public IExaminable Examinable { get; }

IInteractWithItem

(NetAF.Assets.IInteractWithItem.html)

Property Value Container

Type	Description
(NetAF.Assets.IItemContainer.html) IPlayerVisible	
IExaminable (NetAF.Assets.IPlayerVisibleExaminable.html)	

Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)

InteractionCallback

Get the examination scene.

(NetAF.Assets.InteractionCallback.html)

Declaration

InteractionResult

(NetAF.Assets.InteractionResult.html)

Point (NetAF.Assets.Point.html)

Point2D

(NetAF.Assets.Point2D.html)

Property Value

Point3D

Type	Description
(NetAF.Assets.Point3D.html)	
Result ExaminationScene (NetAF.Assets.ExaminationScene.html) (NetAF.Assets.Result.html)	

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes



Condition
(NetAF.Assets.Condition.html)
ConditionalDescription
(NetAF.Assets.ConditionalDescription.html)
Description
(NetAF.Assets.Description.html)
ExaminableObject
(NetAF.Assets.ExaminableObject.html)
ExaminationCallback
(NetAF.Assets.ExaminationCallback.html)
ExaminationRequest
(NetAF.Assets.ExaminationRequest.html)
ExaminationResult
(NetAF.Assets.ExaminationResult.html)
ExaminationScene
(NetAF.Assets.ExaminationScene.html)
IExaminable
(NetAF.Assets.IExaminable.html)
IInteractWithItem
(NetAF.Assets.IInteractWithItem.html)
IItemContainer
(NetAF.Assets.IItemContainer.html)
IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)
Identifier
(NetAF.Assets.Identifier.html)
Interaction
(NetAF.Assets.Interaction.html)
InteractionCallback
(NetAF.Assets.InteractionCallback.html)
InteractionResult
(NetAF.Assets.InteractionResult.html)
Item (NetAF.Assets.Item.html)
Point2D
(NetAF.Assets.Point2D.html)
Point3D
(NetAF.Assets.Point3D.html)
Result
(NetAF.Assets.Result.html)
Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

Class ExaminationResult

Represents the result of an examination.

Filter by title

Inheritance...

(NetAF.Assets.Condition.html)
↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
 ConditionalDescription
 ↳ Result (NetAF.Assets.Result.html)
 (NetAF.Assets.ConditionalDescriptor)
 ↳ ExaminationResult
 Description
Inherited Members
(NetAF.Assets.Description.html)
ExaminableObject
Result.Description ([NetAF.Assets.Result.html#NetAF_Assets_Result_Description](#))
(NetAF.Assets.ExaminableObject)
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
 (NetAF.Assets.ExaminationCallback)
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
 (NetAF.Assets.ExaminationRequest)
equals(SYSTEM-OBJECT-SYSTEM-OBJECT)
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
ExaminationResult
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
 (NetAF.Assets.ExaminationResult)
object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)
ExaminationScene
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
 (NetAF.Assets.ExaminationScene)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)
 IExaminable
Namespace
NetAF (NetAF.html) Assets (NetAF.Assets.html)
 (NetAF.Assets.IExaminable.html)
Assembly
NetAF

Syntax
NetAF.Assets.IInteractWithItem.htm

IItemContainer
public class EXAMINATIONRESULT : Result
 IPlayerVisible
 (NetAF.Assets.IPlayerVisible.html)

Identifier
(NetAF.Assets.Identifier.html)

Interaction
(NetAF.Assets.Interaction.html)
ExaminationResult(string)
InteractionCallback

(NetAF.Assets.InteractionCallback)
Initializes a new instance of the ExaminationResult class.
InteractionResult

Declaration
NetAF.Assets.InteractionDate.htm

Item (NetAF.Assets.Item.html)
Point2D
public ExaminationResult(string description)
 (NetAF.Assets.Point2D.html)

Point3D
Parameters
(NetAF.Assets.Point3D.html)

Type	Name	Description
Result (NetAF.Assets.Result.html) string (https://learn.microsoft.com/dotnet/api/system.string) Size (NetAF.Assets.Size.html)	description	A description of the result.

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)



Condition
(NetAF.Assets.Condition.html)
ConditionalDescription
(NetAF.Assets.ConditionalDescripti
Description
(NetAF.Assets.Description.html)
ExaminableObject
(NetAF.Assets.ExaminableObject.h
ExaminationCallback
(NetAF.Assets.ExaminationCallbac
ExaminationRequest
(NetAF.Assets.ExaminationReques
ExaminationResult
(NetAF.Assets.ExaminationResult.I
ExaminationScene
(NetAF.Assets.ExaminationScene.I
IExaminable
(NetAF.Assets.IExaminable.html)
IInteractWithItem
(NetAF.Assets.IInteractWithItem.ht
IItemContainer
(NetAF.Assets.IItemContainer.html)
IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)
Identifier
(NetAF.Assets.Identifier.html)
Interaction
(NetAF.Assets.Interaction.html)
InteractionCallback
(NetAF.Assets.InteractionCallback.
InteractionResult
(NetAF.Assets.InteractionResult.ht
Item (NetAF.Assets.Item.html)
Point2D
(NetAF.Assets.Point2D.html)
Point3D
(NetAF.Assets.Point3D.html)
Result
(NetAF.Assets.Result.html)
Size (NetAF.Assets.Size.html)

+ **NetAF.Assets.Attributes**
(NetAF.Assets.Attributes.html)

Class ExaminationScene

Represents a scene that an examination occurs in.

Filter by title

Inheritance .. [System.Object](#)

ConditionalDescription

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

(NetAF.Assets.ConditionalDescriptor)

↳ ExaminationScene

Description

Inherited Members

[\(NetAF.Assets.Description.html\)](#)

ExaminableObject

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

ExaminationCallback

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

ExaminationRequest

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

(NetAF.Assets.ExaminationRequest)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

ExaminationResult

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

(NetAF.Assets.ExaminationResult)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

ExaminationScene

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF.Assets.ExaminationScene)

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html)

IExaminable

Assembly: NetAF

(NetAF.Assets.IExaminable.html)

Syntax

[IInteractWithItem](#)

(NetAF.Assets.IInteractWithItem.html)

ItemContainer [ExaminationScene](#)

(NetAF.Assets.IItemContainer.html)

IPlayerVisible

(NetAF.Assets.IPlayerVisible.html)

Constructors

Identifier

(NetAF.Assets.Identifier.html)

Interaction

[ExaminationScene\(Character, Room\)](#)

(NetAF.Assets.Interaction.html)

InteractionCallback

Represents a scene that an examination occurs in.

(NetAF.Assets.InteractionCallback)

InteractionResult

(NetAF.Assets.InteractionResult.html)

Item [ExaminationScene](#)

(NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Parameters

Point3D

Type	Name	Description
Result		
Character	examiner	The character who is examining the object.
Size	room	The room the examinable is being examined from.

+ [NetAF.Assets.Attributes](#)

(NetAF.Assets.Attributes.html)

↳ [NetAF.Assets.Characters](#)

(NetAF.Assets.Characters.html)

ExaminationScene(Game)

Initializes a new instance of the ExaminationScene class.

Declaration

```
public ExaminationScene(Game game)
```

Parameters

Type	Name	Description
(NetAF.Assets.ConditionalDescription.html)	game	The executing game.

Properties

Examiner

Get the Examiner.

```
(NetAF.Assets.ExaminationScene.IExaminable)
```

Declaration

```
public Character Examiner { get; }
```

```
(NetAF.Assets.IInteractWithItem.html)
```

Property value

```
(NetAF.Assets.IItemContainer.html)
```

Type

Description

PlayerVisible	
(NetAF.Assets.IPlayerVisible.html)	
Character (NetAF.Assets.Characters.Character.html)	
Identifier	

```
(NetAF.Assets.Identifier.html)
```

Interaction

NoScene

Get a default value for when there is no scene.

```
(NetAF.Assets.InteractionCallback)
```

Declaration

```
(NetAF.Assets.InteractionResult.html)
```

```
Item (NetAF.Assets.Item.html)
```

```
public static ExaminationScene NoScene { get; }
```

```
Point2D
```

```
(NetAF.Assets.Point2D.html)
```

Property value

```
(NetAF.Assets.Point3D.html)
```

Description

Type

Result

ExaminationScene (NetAF.Assets.ExaminationScene.html)	
---	--

```
Size (NetAF.Assets.Size.html)
```

+ NetAF.Assets.Attributes

Root (NetAF.Assets.Attributes.html)

↳ NetAF.Assets.Characters

Get the room the examinable is being examined from.

Declaration

```
public Room Room { get; }
```

Property Value

Type	Description
ConditionalDescription Room (NetAF.Assets.Locations.Room.html) Description	

(NetAF.Assets.Description.html)
ExaminableObject
(NetAF.Assets.ExaminableObject.html)
ExaminationCallback
(NetAF.Assets.ExaminationCallback.html)
ExaminationRequest
(NetAF.Assets.ExaminationRequest.html)
ExaminationResult
(NetAF.Assets.ExaminationResult.html)
ExaminationScene
(NetAF.Assets.ExaminationScene.html)
IExaminable
(NetAF.Assets.IExaminable.html)
IInteractWithItem
(NetAF.Assets.IInteractWithItem.html)
IItemContainer
(NetAF.Assets.IItemContainer.html)
IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)
Identifier
(NetAF.Assets.Identifier.html)
Interaction
(NetAF.Assets.Interaction.html)
InteractionCallback
(NetAF.Assets.InteractionCallback.html)
InteractionResult
(NetAF.Assets.InteractionResult.html)
Item ([NetAF.Assets.Item.html](#))
Point2D
(NetAF.Assets.Point2D.html)
Point3D
(NetAF.Assets.Point3D.html)
Result
(NetAF.Assets.Result.html)
Size ([NetAF.Assets.Size.html](#))

+ NetAF.Assets.Attributes

[\(NetAF.Assets.Attributes.html\)](#)

↳ NetAF.Assets.Characters

Interface IExaminable

Represents any object that is examinable.

Filter by title

Inherited Members

(NetAF.Assets.ConditionalDescriptor)
IPlayerVisible.IsPlayerVisible (NetAF.Assets.IPlayerVisible.html#NetAF_Assets_IPlayerVisible_IsPlayerVisible)
Description
IRestoreFromObjectSerialization<ExaminableSerialization>.RestoreFrom(ExaminableSerialization)
(NetAF.Assets.Description.html)
(NetAF.Serialization.IRestoreFromObjectSerialization-
ExaminableObject
1.html#NetAF_Serialization_IRestoreFromObjectSerialization_1_RestoreFrom__0_)
(NetAF.Assets.ExaminableObject.html)

Namespace: NetAF.NET.Engine.Assets (NetAF.Assets.html)

Assembly: NetAF.NET.Engine

Syntax

(NetAF.Assets.ExaminationRequest)

ExaminationResult

```
public interface IExaminable : IPlayerVisible, IRestoreFromObjectSerialization<Exami  
nablesSerialization>  
    ExaminationScene  
        (NetAF.Assets.ExaminationScene.I  
        IExaminable  
            (NetAF.Assets.IExaminable.html)
```

Properties

IInteractWithItem

(NetAF.Assets.IInteractWithItem.html)

IItemContainer

Attributes

(NetAF.Assets.IItemContainer.html)

IPlayerVisible

Get the attribute manager for this object.

(NetAF.Assets.IPlayerVisible.html)

Identifier

(NetAF.Assets.Identifier.html)

Interaction

```
AttributeManager Attributes { get; }
```

(NetAF.Assets.Interaction.html)

InteractionCallback

Property: (NetAF.Assets.InteractionCallback).

InteractionResult

(NetAF.Assets.InteractionDate.html)

AttributeManager (NetAF.Assets.Attributes.AttributeManager.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Result

Get this objects commands.

(NetAF.Assets.Result.html)

Declaration

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

```
CustomCommand[] Commands { get; }
```

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

Property: Value

NetAF.Assets.Characters.html

Type	Description
CustomCommand (NetAF.Commands.CustomCommand.html)	

Description

Get a description of this object.
[\(NetAF.Assets.ConditionalDescription.html\)](#)

Declaration

[\(NetAF.Assets.Description.html\)](#)

ExaminableObject { get; }

[\(NetAF.Assets.ExaminableObject.html\)](#)

ExaminationCallback

Property Value
[\(NetAF.Assets.ExaminationCallback.html\)](#)

Type ExaminationRequest

Description

[\(NetAF.Assets.ExaminationRequest.html\)](#)

Description [\(NetAF.Assets.Description.html\)](#)

ExaminationResult

[\(NetAF.Assets.ExaminationResult.html\)](#)

ExaminationScene

[\(NetAF.Assets.ExaminationScene.html\)](#)

Identifier

IExaminable

Get the object's identifier
[\(NetAF.Assets.IExaminable.html\)](#)

IInteractWithItem

Declaration
[\(NetAF.Assets.IInteractWithItem.html\)](#)

ItemContainer

Identifier Identifier { get; }

[\(NetAF.Assets.ItemContainer.html\)](#)

IPlayerVisible

Property Value
[\(NetAF.Assets.IPlayerVisible.html\)](#)

Identifier

Type [\(NetAF.Assets.Identifier.html\)](#)

Description

Interaction

[\(NetAF.Assets.Identifier.html\)](#)

[\(NetAF.Assets.Interaction.html\)](#)

InteractionCallback

[\(NetAF.Assets.InteractionCallback.html\)](#)

InteractionResult

[\(NetAF.Assets.InteractionResult.html\)](#)

Item [\(NetAF.Assets.Item.html\)](#)

Point2D

[\(NetAF.Assets.Point2D.html\)](#)

Examine(ExaminationScene)

[\(NetAF.Assets.Result.html\)](#)

Point3D

[\(NetAF.Assets.Point3D.html\)](#)

Declaration

Result

[\(NetAF.Assets.Result.html\)](#)

Examine(ExaminationResult, ExaminationScene scene)

Size [\(NetAF.Assets.Size.html\)](#)

+ NetAF.Assets.Attributes

Parameters

[\(NetAF.Assets.Attributes.html\)](#)

+ NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

Type	Name	Description
ExaminationScene (NetAF.Assets.ExaminationScene.html)	scene	The scene this object is being examined from.

Returns

Type	Description
(NetAF.Assets.ExaminationResultConditionalDescriptor.html)	A ExaminationResult detailing the examination of this object.
(NetAF.Assets.ExaminationResult.html)	
(NetAF.Assets.Description.html)	
ExaminableObject	
(NetAF.Assets.ExaminableObject.html)	
ExaminationCallback	
(NetAF.Assets.ExaminationCallback.html)	
ExaminationRequest	
(NetAF.Assets.ExaminationRequest.html)	
ExaminationResult	
(NetAF.Assets.ExaminationResult.html)	
ExaminationScene	
(NetAF.Assets.ExaminationScene.html)	
IExaminable	
(NetAF.Assets.IExaminable.html)	
IIInteractWithItem	
(NetAF.Assets.IIInteractWithItem.html)	
IIItemContainer	
(NetAF.Assets.IIItemContainer.html)	
IPlayerVisible	
(NetAF.Assets.IPlayerVisible.html)	
Identifier	
(NetAF.Assets.Identifier.html)	
Interaction	
(NetAF.Assets.Interaction.html)	
InteractionCallback	
(NetAF.Assets.InteractionCallback.html)	
InteractionResult	
(NetAF.Assets.InteractionResult.html)	
Item (NetAF.Assets.Item.html)	
Point2D	
(NetAF.Assets.Point2D.html)	
Point3D	
(NetAF.Assets.Point3D.html)	
Result	
(NetAF.Assets.Result.html)	
Size (NetAF.Assets.Size.html)	

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

Interface IInteractWithItem

Represents any object that can interact with an item.

Filter by title

Namespace: NetAF.(NetAF.html).Assets.(NetAF.Assets.html)

Assembly: NetAF.dll

(NetAF.Assets.Description.html)

Syntax

```
ExaminableObject  
(NetAF.Assets.ExaminableObject.h)  
public interface IInteractWithItem  
ExaminationCallback
```

```
(NetAF.Assets.ExaminationCallbac
```

```
ExaminationRequest
```

```
(NetAF.Assets.ExaminationReques
```

```
ExaminationResult
```

```
(NetAF.Assets.ExaminationResult.I
```

```
ExaminationScene
```

```
(NetAF.Assets.ExaminationScene.I
```

IExaminable

Interaction (NetAF.Assets.IExaminable.html)

IInteractWithItem

Declaration (NetAF.Assets.IInteractWithItem.ht

```
ItemContainer
```

```
Interaction Interact(Item item)
```

```
(NetAF.Assets.ItemContainer.html)
```

IPlayerVisible

```
(NetAF.Assets.IPlayerVisible.html)
```

Parameters

Identifier

Type (NetAF.Assets.Identifier.html)

Interaction
(NetAF.Assets.Item.html)
(NetAF.Assets.Interaction.html)

Returns InteractionCallback

```
(NetAF.Assets.InteractionCallback.
```

Type InteractionResult

(NetAF.Assets.InteractionResult.ht
Interaction (NetAF.Assets.Interaction.html)
Item (NetAF.Assets.Item.html)

Point2D

```
(NetAF.Assets.Point2D.html)
```

Point3D

```
(NetAF.Assets.Point3D.html)
```

Result

```
(NetAF.Assets.Result.html)
```

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.htm

Interface IItemContainer

Represents any object that is a container of items.

▼ Filter by title

Inherited Members

(NetAF.Assets.Description.html)
IExaminable.Identifier (NetAF.Assets.IExaminable.html#NetAF_Assets_IExaminable_Identifier)
ExaminableObject
IExaminable.Description (NetAF.Assets.IExaminable.html#NetAF_Assets_IExaminable_Description)
(NetAF.Assets.ExaminableObject.r)
IExaminable.Commands (NetAF.Assets.IExaminable.html#NetAF_Assets_IExaminable_Commands)
ExaminationCallback
IExaminable.Attributes (NetAF.Assets.IExaminable.html#NetAF_Assets_IExaminable_Attributes)
(NetAF.Assets.ExaminationCallback)
IExaminable.Examine (ExaminationScene)
ExaminationRequest
(NetAF.Assets.IExaminable.html#NetAF_Assets_IExaminable_Examine_NetAF_Assets_ExaminationScene_)
(NetAF.Assets.ExaminationRequest)
IPlayerVisible.IsPlayerVisible (NetAF.Assets.IPlayerVisible.html#NetAF_Assets_IPlayerVisible_IsPlayerVisible)
ExaminationResult
IRestoreFromObjectSerialization<ExaminableSerialization>.RestoreFrom(ExaminableSerialization)
(NetAF.Assets.ExaminationResult.)
(NetAF.Serialization.IRestoreFromObjectSerialization-
ExaminationScene
1.html#NetAF_Serialization_IRestoreFromObjectSerialization_1_RestoreFrom__0_)
(NetAF.Assets.ExaminationScene.)
Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html)

Assets (NetAF.html).Assets (NetAF.Assets.html)

InteractWithItem

(NetAF.Assets.IInteractWithItem.html)

IItemContainer

```
public interface IItemContainer : IExaminable, IPlayerVisible, IRestoreFromObjectSerialization<ExaminableSerialization>
{
    IPlayerVisible
    (NetAF.Assets.IPlayerVisible.html)
    Identifier
    (NetAF.Assets.Identifier.html)
```

Properties

(NetAF.Assets.Interaction.html)

InteractionCallback

Items (NetAF.Assets.InteractionCallback.html)

InteractionResult

Get the items (NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Declaration

Point2D

(NetAF.Assets.Point2D.html)

Item[] Items { get; }

Point3D

(NetAF.Assets.Point3D.html)

Properties

CurrentValue

Type	Description
Size (NetAF.Assets.Size.html)	

Item (NetAF.Assets.Item.html)[]

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

AddItem(Item)

Add an item.

Declaration

```
void AddItem(Item item)
```

 Description

Parameters
Type
(NetAF.Assets.Description.html)

Type	Name	Description
ExaminableObject (NetAF.Assets.ExaminableObject.html)	item	The item to add.

RemoveItem(Item)

Remove an item.
ExaminationScene

Declaration
NetAF.Assets.ExaminationScene.I

IExaminable

(NetAF.Assets.IExaminable.html)

IIInteractWithItem

(NetAF.Assets.IIInteractWithItem.html)

Parameters

ItemContainer

Type	Name	Description
ItemContainer (NetAF.Assets.IItemContainer.html)	item	The item to remove.

Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

(NetAF.Assets.InteractionDate.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Result

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

Interface IPlayerVisible

Represents any object that is visible to a player.

Filter by title

Namespace: NetAF.(NetAF.html).Assets.(NetAF.Assets.html)

Assembly: NetAF.dll

Syntax (NetAF.Assets.ExaminableObject.h)

ExaminationCallback

(NetAF.Assets.ExaminationCallback.h)
public interface IPlayerVisible
ExaminationRequest

(NetAF.Assets.ExaminationRequest.h)

ExaminationResult

(NetAF.Assets.ExaminationResult.h)

ExaminationScene

(NetAF.Assets.ExaminationScene.h)

IExaminable

(NetAF.Assets.IExaminable.html)

IInteractWithItem

Get (NetAF.Assets.IInteractWithItem.html)

IItemContainer

Declaration (NetAF.Assets.IItemContainer.html)

IPlayerVisible

bool IsPlayerVisible { get; set; }
(NetAF.Assets.IPlayerVisible.html)

Identifier

Property Value (NetAF.Assets.Identifier.html)

Interaction

Type (NetAF.Assets.Interaction.html)

Description

InteractionCallback (https://learn.microsoft.com/dotnet/api/system.boolean)

(NetAF.Assets.InteractionCallback.h)

InteractionResult

(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Result

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Class Identifier

Provides a class that can be used as an identifier.

Filter by title

Inheritance

(NetAF.Assets.ExaminableObject.h)
↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ ExaminationCallback
↳ Identifier
(NetAF.Assets.ExaminationCallback)

Implementation

ExaminationRequest
IEquatable<Identifier> (<https://learn.microsoft.com/dotnet/api/system.iequatable-1<string>)
(<https://learn.microsoft.com/dotnet/api/system.string>)>
IEquatable<ExaminationResult> (<https://learn.microsoft.com/dotnet/api/system.iequatable-1<Identifier> (NetAF.Assets.Identifier.html))>

Inherited Members

(NetAF.Assets.ExaminationScene.I
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
(NetAF.Assets.IExaminable.html)
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object, system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object)))
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

Namespace: NetAF (NetAF/Assets (NetAF.Assets.html))

Identifier

Assembly: NetAF.dll

(NetAF.Assets.Identifier.html)

Syntax

Interaction
(NetAF.Assets.Interaction.html)
public sealed class Identifier : IEquatable<string>, IEquatable<Identifier>
InteractionCallback
(NetAF.Assets.InteractionCallback.
InteractionResult

Constructors

Identifier(string) ([https://learn.microsoft.com/dotnet/api/NetAF.Assets.Identifier\(string\).html](https://learn.microsoft.com/dotnet/api/NetAF.Assets.Identifier(string).html))

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

Provides a class for Point3D defined as an identifier.

Result

Declaration
(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

public Identifier(string name)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

Parameters

+ NetAF.Assets.Characters

Type
(NetAF.Assets.Characters.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	name	The name.

Properties

Empty

Get an empty identifier.

Declaration

```
(NetAF.Assets.ExaminableObject.h
public static Identifier Empty { get; }
```

ExaminationCallback

(NetAF.Assets.ExaminationCallback

ExaminationRequest

(NetAF.Assets.ExaminationReques

Type ExaminationResult

Description

(NetAF.Assets.ExaminationResult)

Identifier (NetAF.Assets.Identifier.html)

ExaminationScene

(NetAF.Assets.ExaminationScene.I

IExaminable

IdentifiableName

(NetAF.Assets.IExaminable.html)

IInteractWithItem

Get the name as a case insensitive identifier.

(NetAF.Assets.IInteractWithItem.ht

Declaration

ItemContainer

(NetAF.Assets.IItemContainer.html)

IPlayerVisible

```
public string IdentifiableName { get; }
```

(NetAF.Assets.IPlayerVisible.html)

Identifier

Property Value

(NetAF.Assets.Identifier.html)

Type Interaction

Description

(NetAF.Assets.Interaction.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Assets.InteractionCallback.

InteractionResult

Name

(NetAF.Assets.InteractionDate.html)

Item (NetAF.Assets.Item.html)

Get the Name.

(NetAF.Assets.Point2D.html)

Declaration

Point3D

(NetAF.Assets.Point3D.html)

```
public string Name { get; }
```

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

Property Value

+ NetAF.Assets.Attributes

Type

Description

(NetAF.Assets.Attributes.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.htm

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Methods

Equals(Identifier)

Indicates whether the current object is equal to another object of the same type.

Declaration

```
public bool Equals(Identifier other)
```

Parameters

Type	Name	Description
Identifier (NetAF.Assets.ExaminationRequest.html) (NetAF.Assets.ExaminationRequest.html)	other	An object to compare with this object.

Returns

ExaminationResult
(NetAF.Assets.ExaminationResult.html)

Type	Description
bool (NetAF.Assets.ExaminationScene.html)	true (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool) if the current object is equal to the other parameter; otherwise, false (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool). IExaminable (https://learn.microsoft.com/dotnet/api/system.item) IInteractWithItem (https://learn.microsoft.com/dotnet/api/system.itemcontainer) IItemContainer (NetAF.Assets.IItemContainer.html)

IPlayerVisible

Equals(string)

Identifier

Indicates whether the current object is equal to another object of the same type.
(NetAF.Assets.Identifier.html)

Declaration

```
public bool Equals(string other)
```

InteractionCallback
(NetAF.Assets.InteractionCallback.html)

InteractionResult

Parameters

Type	Description
Item (NetAF.Assets.Item.html) Point2D string (https://learn.microsoft.com/dotnet/api/system.string)	other

Point3D
(NetAF.Assets.Point3D.html)

Result
(NetAF.Assets.Result.html)

booSize (NetAF.Assets.Size.html)
(<https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool>) if the current object is equal to the other parameter; otherwise,

+ NetAF.Assets.Attributes
(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

Tostring()
(NetAF.Assets.Locations.html)

Returns a string that represents the current object.

Declaration

```
public override string ToString()
```

>Returns

Type	Description
NetAF.Assets.ExaminableObject.h ExaminationCallback string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Assets.ExaminationCallback)	A string that represents the current object.

Overrides

ExaminationRequest
(NetAF.Assets.ExaminationRequest.html)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

ExaminationResult
(NetAF.Assets.ExaminationResult.html)

Implements

ExaminationScene
(NetAF.Assets.ExaminationScene.html)
IEquatable<T> (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)
IEquatable<T> (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)

IInteractWithItem

(NetAF.Assets.IInteractWithItem.html)

IItemContainer

(NetAF.Assets.IItemContainer.html)

IPlayerVisible

(NetAF.Assets.IPlayerVisible.html)

Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

(NetAF.Assets.InteractionDate.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Result

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Class Interaction

Represents an interaction.

Filter by title

Inheritance: [System.Object](#)

↳ [ExaminationCallback](#)
↳ [object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ [\(NetAF.Assets.ExaminationCallback.html\)](#)
↳ [Result](#) ([NetAF.Assets.Result.html](#))
↳ [ExaminationRequest](#)
↳ [Interaction](#)
↳ [\(NetAF.Assets.ExaminationRequest.html\)](#)
↳ [Identifier](#)
↳ [\(NetAF.Assets.ExaminationResult.html\)](#)
Result.Description ([NetAF.Assets.Result.html#NetAF_Assets_Result_Description](#))
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
object.Equals(object, object) ([\(NetAF.Assets.IExaminable.html\)](#)
equals(system-object-system-object))
InteractWithItem
object.GetHashCode() ([\(NetAF.Assets.InteractWithItem.html\)](#)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
ItemContainer
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() ([\(NetAF.Assets.ItemContainer.html\)](#)
IPlayerVisible
Namespace: [NetAF](#) ([NetAF.html](#)) Assets ([NetAF.Assets.html](#))
Namespace: [\(NetAF.Assets.IPlayerVisible.html\)](#)
Assembly: [NetAF.dll](#)

Syntax: [\(NetAF.Assets.Identifier.html\)](#)

Interaction
↳ [\(NetAF.Assets.Interaction.html\)](#)
public sealed class Interaction : Result
InteractionCallback
↳ [\(NetAF.Assets.InteractionCallback.html\)](#)

Constructors

[\(NetAF.Assets.InteractionResult.html\)](#)

Item ([NetAF.Assets.Item.html](#))

Point2D

[\(NetAF.Assets.Point2D.html\)](#)

Point3D

Initializes a new instance of the Interaction class.
[\(NetAF.Assets.Point3D.html\)](#)

Declaration

[\(NetAF.Assets.Result.html\)](#)

Size ([NetAF.Assets.Size.html](#))

public Interaction(InteractionResult result, Item item)

+ NetAF.Assets.Attributes

[\(NetAF.Assets.Attributes.html\)](#)

+ Type: NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

InteractionResult ([NetAF.Assets.InteractionResult.html](#))

Name

Description

result The result of the interaction.

+ Type: NetAF.Assets.Locations

[\(NetAF.Assets.Locations.html\)](#)

item

The item used in the interaction.

+ NetAF.Commands

Interaction(InteractionResult, Item, string)

Initializes a new instance of the Interaction class.

Declaration

```
public Interaction(InteractionResult result, Item item, string descriptionOfEffect)
```

Parameters

Type	Name	Description
(NetAF.Assets.ExaminationCallback)(NetAF.Assets.ExaminationRequest)		
InteractionResult (NetAF.Assets.InteractionResult.html)	result	The result of the interaction.
Item (NetAF.Assets.Item.html)	item	The item used in the interaction.
string (https://learn.microsoft.com/dotnet/api/system.string)	descriptionOfEffect	A description of the effect.

Properties

Item

Identifier
(NetAF.Assets.Identifier.html)
Get the item used in the interaction.
Interaction
Declaration
(NetAF.Assets.Interaction.html)

InteractionCallback

(NetAF.Assets.InteractionCallback.html)
InteractionResult
(NetAF.Assets.InteractionDate.html)

Property Value
Item (NetAF.Assets.Item.html)

Type	Description
Point2D (NetAF.Assets.Point2D.html)	

Item (NetAF.Assets.Item.html)

Point3D
(NetAF.Assets.Point3D.html)

Result
(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

Get the result.

+ NetAF.Assets.Attributes

Declaration
(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

Result
(NetAF.Assets.Characters.html)

NetAF/Assets/Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

Type	Description
InteractionResult (NetAF.Assets.InteractionResult.html)	



[ExaminationCallback](#)
 (NetAF.Assets.ExaminationCallback.html)
[ExaminationRequest](#)
 (NetAF.Assets.ExaminationRequest.html)
[ExaminationResult](#)
 (NetAF.Assets.ExaminationResult.html)
[ExaminationScene](#)
 (NetAF.Assets.ExaminationScene.html)
[IExaminable](#)
 (NetAF.Assets.IExaminable.html)
[IInteractWithItem](#)
 (NetAF.Assets.IInteractWithItem.html)
[IItemContainer](#)
 (NetAF.Assets.IItemContainer.html)
[IPlayerVisible](#)
 (NetAF.Assets.IPlayerVisible.html)
[Identifier](#)
 (NetAF.Assets.Identifier.html)
[Interaction](#)
 (NetAF.Assets.Interaction.html)
[InteractionCallback](#)
 (NetAF.Assets.InteractionCallback.html)
[InteractionResult](#)
 (NetAF.Assets.InteractionResult.html)
[Item](#)
 (NetAF.Assets.Item.html)
[Point2D](#)
 (NetAF.Assets.Point2D.html)
[Point3D](#)
 (NetAF.Assets.Point3D.html)
[Result](#)
 (NetAF.Assets.Result.html)
[Size](#)
 (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

Delegate InteractionCallback

Represents the callback for interacting with objects.

Filter by title

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html)

Assembly: NetAF.dll

Syntax

```
public delegate InteractionCallback(InteractionResult item)
(NetAF.Assets.ExaminationResult)
```

ExaminationScene

Parameters

IExaminable
Type

(NetAF.Assets.IExaminable.html)

Item
Type

(NetAF.Assets.Item.html)

IInteractWithItem
Type

(NetAF.Assets.IInteractWithItem.html)

ItemContainer
Type

(NetAF.Assets.IItemContainer.html)

PlayerVisible
Type

(NetAF.Assets.IPlayerVisible.html)

Interaction
Type

(NetAF.Assets.Interaction.html)

Identifier
Type

(NetAF.Assets.Identifier.html)

Interaction
Type

(NetAF.Assets.Interaction.html)

InteractionCallback
Type

(NetAF.Assets.InteractionCallback.html)

InteractionResult
Type

(NetAF.Assets.InteractionResult.html)

Item
Type

(NetAF.Assets.Item.html)

Point2D
Type

(NetAF.Assets.Point2D.html)

Point3D
Type

(NetAF.Assets.Point3D.html)

Result
Type

(NetAF.Assets.Result.html)

Size
Type

(NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

[\(NetAF.Assets.Attributes.html\)](#)

+ NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

+ NetAF.Assets.Locations

Enum InteractionResult

Enumeration of interaction results.

Filter by title

Namespace: NetAF.(NetAF.html).Assets.(NetAF.Assets.html)

Assembly: NetAF

Syntax

```
ExaminationResult
  (NetAF.Assets.ExaminationRequest.html)
  ExaminationScene
    (NetAF.Assets.ExaminationScene.html)
    IExaminable
      (NetAF.Assets.IExaminable.html)
    InteractWithItem
      (NetAF.Assets.IInteractWithItem.html)
```

Fields

(NetAF.Assets.IInteractWithItem.html)

Name	Description
ItemContainer (NetAF.Assets.IItemContainer.html)	
ItemAndTargetExpired IPlayerVisible (NetAF.Assets.IPlayerVisible.html)	The item and the target expired.
ItemExpired Identifier (NetAF.Assets.IItemExpired.html)	The item expired.
NeitherItemOrTargetExpired (NetAF.Assets.INeitherItemOrTargetExpired.html)	Neither the item or the target expired.
Interaction TargetExpired (NetAF.Assets.Interaction.html)	The target expired.

InteractionCallback
(NetAF.Assets.InteractionCallback.html)

InteractionResult
(NetAF.Assets.InteractionDate.html)

Item (NetAF.Assets.Item.html)

Point2D
(NetAF.Assets.Point2D.html)

Point3D
(NetAF.Assets.Point3D.html)

Result
(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

(NetAF.Commands.html)

Class Item

Represents an item that can be used within the game.

Filter by title

Inheritance

(NetAF.Assets.ExaminationRequest
↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ ExaminationResult
↳ ExaminableObject (NetAF.Assets.ExaminableObject.html)
↳ NetAF.Assets.ExaminationResult.
↳ Item
↳ ExaminationScene

Implements

- NetAF.Assets.ExaminationScene.IExaminableObject (NetAF.Assets.IExaminable.html)
- NetAF.Assets.IPlayerVisible (NetAF.Assets.IPlayerVisible.html)
- IRestoreFromObjectSerialization (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)<Examinable>
- NetAF.Assets.ISerializableWithAssets (NetAF.Assets.ExaminableSerialization.html)>
- IInteractableItem (NetAF.Assets.IInteractWithItem.html)
- IRestoreFromObjectSerialization (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)<ItemSerialization>
- NetAF.Serialization.Items.ItemSerialization (NetAF.Serialization.Items.ItemSerialization.html)>
- (NetAF.Assets.IPlayerVisible.html)

Inherited Members

- Identifier
- ExaminableObject.Examination (NetAF_Assets_ExaminableObject_Examination.html)
- ExaminableObject.ExaminableObject (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_Examination)
- ExaminableObject.Identifier (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_Identifier)
- ExaminableObject.Description (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_Description)
- ExaminableObject.Commands (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_Commands)
- Item (NetAF_Assets_Items.html)
- NetAF_Assets_ExaminableObject.Attributes (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_Attributes)
- Point3D (NetAF_Assets_Point3D.html)
- ExaminableObject.IsPlayerVisible (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_IsPlayerVisible)
- ExaminableObject.RestoreFrom (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_RestoreFrom)
- ExaminableObject.RestoreFrom (NetAF_Assets_ExaminableObject.html#NetAF_Assets_ExaminableObject_RestoreFrom_NetAF_Serialization_Assets_ExaminableSerialization_)
- + NetAF.Assets.Attributes
[\(NetAF.Assets.Attributes.html\)](#)
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))
- + NetAF.Assets.Characters
[\(NetAF.Assets.Characters.html\)](#)
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
- + NetAF.Assets.Locations
[\(NetAF.Assets.Locations.html\)](#)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
- + NetAF.Commands
[\(NetAF.Commands.html\)](#)
Namespace: NetAF (NetAF.dll).Assets (NetAF.Assets.html)
- Assembly: NetAF.dll
+ NetAF.Commands.

Syntax

```
public sealed class Item : ExaminableObject, IExaminable, IPlayerVisible, IRotateFor  
omObjectSerialization<ExaminableSerialization>, IInteractWithItem, IRotateFromObjec  
tSerialization<ItemSerialization>
```

▼

Constructors

(NetAF.Assets.ExaminationRequest.html)

ExaminationResult

(NetAF.Assets.ExaminationResult.html)

Item(Identifier, Description, bool, CustomCommand[], InteractionCallback, ExaminationCallback)

(NetAF.Assets.ExaminationScene.html)

IExaminable

Initializes a new instance of the Item class.

(NetAF.Assets.IExaminable.html)

Declaration

IInteractWithItem

(NetAF.Assets.IInteractWithItem.html)

```
public Item(Identifier identifier, Description description, bool isTakeable = false,  
CustomCommand[] commands, InteractionCallback interaction = null, ExaminationCallback examination = null)
```

(NetAF.Assets.IPlayerVisible.html)

Identifier

Parameters

(NetAF.Assets.Identifier.html)

Type	Name	Description
Identifier (NetAF.Assets.Identifier.html)	identifier	This Items identifier.
Description (NetAF.Assets.Description.html)	description	A description of this Item.
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	isTakeable	Specify if this item is takeable.
CustomCommand[] (NetAF.Assets.Commands.CustomCommand.html)	commands	This objects commands.
Point2D (NetAF.Assets.Point2D.html)	interaction	The interaction.
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	examination	The examination.

Result

(NetAF.Assets.Result.html)

Item(string, string, bool, CustomCommand[], InteractionCallback, ExaminationCallback)

+ NetAF.Assets.Attributes

Initializes a new instance of the Item class.

(NetAF.Assets.Attributes.html)

Declaration

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

```
public Item(string identifier, string description, bool isTakeable = false, CustomCo
```

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

Parameters

(NetAF.Commands.html)

+ NetAF.Commands.

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>identifier</i>	This Items identifier.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i>	A description of this Item.
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	<i>isTakeable</i>	Specify if this item is takeable.
CustomCommand (NetAF.Commands.CustomCommand.html)	<i>commands</i>	This objects commands.
InteractionCallback (NetAF.Assets.InteractionCallback.html)	<i>interaction</i>	The interaction.
ExaminationResult (NetAF.Assets.ExaminationResult.html)	<i>examination</i>	The examination.

ExaminationScene
 (<NetAF.Assets.ExaminationScene.html>)
 IExaminable
 (<NetAF.Assets.IExaminable.html>)
 IIInteractWithItem
 (<NetAF.Assets.IIInteractWithItem.html>)

Interaction
 IItemContainer
 (<NetAF.Assets.IItemContainer.html>)
 Get the interaction.
 IPlayerVisible
 (<NetAF.Assets.IPlayerVisible.html>)
 Declaration
 Identifier
 (<NetAF.Assets.Identifier.html>)
 public InteractionCallback Interaction { get; }
 Interaction
 (<NetAF.Assets.Interaction.html>)
 Property InteractionCallback

Type	Description
InteractionResult	

InteractionResult (<NetAF.Assets.InteractionResult.html>)
 Item (<NetAF.Assets.Item.html>)

Point2D
 (<NetAF.Assets.Point2D.html>)
 Point3D

(<NetAF.Assets.Point3D.html>)
 Get or set if this is takeable.
 Result

Declaration
 (<NetAF.Assets.Result.html>)
 Size (<NetAF.Assets.Size.html>)

+ NetAF.Assets.Attributes
 (<NetAF.Assets.Attributes.html>)

Property Value

+ NetAF.Assets.Characters

Type	Description
NetAF.Assets.Characters.html	

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)
 + NetAF.Assets.Locations

(<NetAF.Assets.Locations.html>)

+ NetAF.Commands

Method
 (<NetAF.Commands.Commands.html>)

+ NetAF.Commands.

Interact(Item)

Interact with an item.

Declaration

```
public Interaction Interact(Item item)
```

Parameters

Type	Name	Description
ExaminationResult (NetAF.Assets.ExaminationResult.html)	item	The item to interact with.

Returns

Type	Description
InteractWithItem (NetAF.Assets.IInteractWithItem.html)	The interaction.

Identifier

Restore this object from a serialization.
(NetAF.Assets.Identifier.html)

Declaration

```
Interaction
```

```
public void RestoreFrom(ItemSerialization serialization)
```

(NetAF.Assets.InteractionCallback.html)

InteractionResult

Parameters

Type	Name	Description
Item (NetAF.Assets.Item.html) Point2D (NetAF.Assets.Point2D.html)	serialization	The serialization to restore from.

(NetAF.Serialization.Assets.ItemSerialization.html)

(NetAF.Assets.Point3D.html)

Result

Implements

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

IExaminable (NetAF.Assets.IExaminable.html)

IPlayerVisible (NetAF.Assets.IPlayerVisible.html)

(NetAF.Assets.Attributes.html) NetAF.Serialization.IRestoreFromObjectSerialization-1.html

IInteractWithItem (NetAF.Assets.IInteractWithItem.html)

+ NetAF.Assets.Attributes

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Struct Point2D

Represents a two-dimensional point.

Filter by title

Implements: [IEquatable<Point2D>](#)

[IEquatable](#) (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)<Point2D (NetAF.Assets.Point2D.html)>
(NetAF.Assets.ExaminationResult.html)

Inherited Members

[ExaminationScene](#)

[Value](#) ([NetAF.Assets.Object](#)) (<https://learn.microsoft.com/dotnet/api/system.valuetype.equals>)

[Value](#) ([System](#)) (<https://learn.microsoft.com/dotnet/api/system.valuetype.gethashcode>)

[Value](#) ([NetAF.Assets.ExaminationResult](#)) (<https://learn.microsoft.com/dotnet/api/system.valuetype.tostring>)

[object](#) ([EqualWithObject](#)) (<https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals>)
(NetAF.Assets.ObjectWithObject.html)

[object](#) ([GetObjectType](#)) (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

[object](#) ([ReferenceEquals](#)) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

[IPlayerVisible](#)

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html)
(NetAF.Assets.IPlayerVisible.html)

Assembly: NetAF.dll

Identifier

Syntax

[\(NetAF.Assets.Identifier.html\)](#)

Interaction

[Point2D](#) ([NetAF.Assets.InteractionPoint](#)) : IEquatable<Point2D>

InteractionCallback

[\(NetAF.Assets.InteractionCallback.html\)](#)

InteractionResult

[Point2D](#) ([NetAF.Assets.InteractionResult](#))

Item

[\(NetAF.Assets.Item.html\)](#)

[Point2D](#) ([Point2D](#), int)

[\(NetAF.Assets.Point2D.html\)](#)

Represents a two-dimensional point.

[\(NetAF.Assets.Point3D.html\)](#)

Declaration

[Result](#)

[\(NetAF.Assets.Result.html\)](#)

[public Point2D \(int x, int y\)](#)

+ NetAF.Assets.Attributes

Parameters

[\(NetAF.Assets.Attributes.html\)](#)

Type

[+ NetAF.Assets.Characters](#)

[int](#) ([NetAF.Assets.Characters.html](#)) (<https://learn.microsoft.com/dotnet/api/system.int32>)

Name

Description

x

The x position.

[+ NetAF.Assets.Locations](#)

[\(NetAF.Assets.Locations.html\)](#)

y

The y position.

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

Properties

+ NetAF.Commands.

Conversation

X

Get the X position.

Declaration

```
public int X { get; }
```

Property Value

Type	Description
(NetAF.Assets.ExaminationResult.html)	

Y
ExaminationScene
int (https://learn.microsoft.com/dotnet/api/system.int32)
IExaminable
(NetAF.Assets.IExaminable.html)

IInteractWithItem

Y
(NetAF.Assets.IInteractWithItem.html)

ItemContainer

Get the Y position.
(NetAF.Assets.IItemContainer.html)

Declaration

PlayerVisible
(NetAF.Assets.IPlayerVisible.html)

Identifier
public int Y { get; }

(NetAF.Assets.Identifier.html)

Interaction

Property Value
(NetAF.Assets.Interaction.html)

Type	Description
InteractionCallback (NetAF.Assets.InteractionCallback.html)	

int (https://learn.microsoft.com/dotnet/api/system.int32)

InteractionResult
(NetAF.Assets.InteractionDate.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

(NetAF.Assets.Point3D.html)

Methods

Equals(Point2D)

(NetAF.Assets.Result.html)

Indicates whether the current object is equal to another object of the same type.

Size (NetAF.Assets.Size.html)

Declaration

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

public bool Equals(Point2D other)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

Parameters

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Point2D (NetAF.Assets.Point2D.html)

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Conversation

Type	Name	Description
	other	An object to compare with this object.

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	true (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool) if the current object is equal to the other parameter; otherwise, false (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool).

[View All Documentation Requests](#)

ExaminationResult

Implements

[NetAF.Assets.ExaminationResult.IExaminationScene](#)

[IEquatable<T>](#) (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)

IExaminable

([NetAF.Assets.IExaminable.html](#))

IInteractWithItem

([NetAF.Assets.IInteractWithItem.html](#))

IItemContainer

([NetAF.Assets.IItemContainer.html](#))

IPlayerVisible

([NetAF.Assets.IPlayerVisible.html](#))

Identifier

([NetAF.Assets.Identifier.html](#))

Interaction

([NetAF.Assets.Interaction.html](#))

InteractionCallback

([NetAF.Assets.InteractionCallback.html](#))

InteractionResult

([NetAF.Assets.InteractionDate.html](#))

Item ([NetAF.Assets.Item.html](#))

Point2D

([NetAF.Assets.Point2D.html](#))

Point3D

([NetAF.Assets.Point3D.html](#))

Result

([NetAF.Assets.Result.html](#))

Size ([NetAF.Assets.Size.html](#))

+ NetAF.Assets.Attributes

([NetAF.Assets.Attributes.html](#))

+ NetAF.Assets.Characters

([NetAF.Assets.Characters.html](#))

+ NetAF.Assets.Locations

([NetAF.Assets.Locations.html](#))

+ NetAF.Commands

([NetAF.Commands.html](#))

+ NetAF.Commands.

Conversation

Struct Point3D

Represents a three-dimensional point.

Filter by title

Implements

IEquatable<Point3D> (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)<Point3D (NetAF.Assets.Point3D.html)>

ExaminationScene

Inherited Members

(NetAF.Assets.ExaminationScene.)

ValueEquals(object) (<https://learn.microsoft.com/dotnet/api/system.valuetype.equals>)

ValueGetHashCode() (<https://learn.microsoft.com/dotnet/api/system.valuetype.gethashcode>)

ValueToString() (<https://learn.microsoft.com/dotnet/api/system.valuetype.tostring>)

object.Equals(object) (<https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals>)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

(NetAF.Assets.IPlayerVisible.html)

Namespace

NetAF (NetAF.html).Assets (NetAF.Assets.html)

Identifier

Assembly

(NetAF.dll)

Syntax

Interaction

(NetAF.Assets.Interaction.html)

public struct Point3D : IEquatable<Point3D>

(NetAF.Assets.InteractionCallback.

InteractionResult

(NetAF.Assets.InteractionDate.html)

Item (NetAF.Assets.Item.html)

Point2D

(NetAF.Assets.Point2D.html)

Point3D

Represents a three-dimensional point.

Result

Declaration

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

public Point3D(int x, int y, int z)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

Parameters

+ NetAF.Assets.Characters

Type

(NetAF.Assets.Characters.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

+ NetAF.Assets.Locations

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

(NetAF.Assets.Locations.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Properties

(NetAF.Commands.Conversati

	Name	Description
int x	x	The x position.
int y	y	The y position.
int z	z	The z position.

X

Get the X position.

Declaration

```
public int X { get; }
```

Property Value

Type	Description
(NetAF.Assets.ExaminationResult.IExaminable.html)	

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

(NetAF.Assets.IExaminable.html)

IInteractWithItem

(NetAF.Assets.IInteractWithItem.html)

Y ItemContainer

(NetAF.Assets.IItemContainer.html)

Get the Y position.

IPlayerVisible

Declaration

(NetAF.Assets.IPlayerVisible.html)

Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)

Property Value

InteractionCallback

Type	Description
(NetAF.Assets.InteractionCallback.html)	

InteractionResult

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Point2D

Z (NetAF.Assets.Point2D.html)

Point3D

Get the Z position.

(NetAF.Assets.Point3D.html)

Result

Declaration

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)

public int Z { get; }

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

Property Value

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

Methods

(NetAF.Commands.html)

+ NetAF.Commands

Equals(Point3D)

Conversation

(NetAF.Commands.Conversati

Indicates whether the current object is equal to another object of the same type.

Declaration

```
public bool Equals(Point3D other)
```

Parameters

Type	Description
NetAF.Assets.ExaminationResult.IPoint3D (NetAF.Assets.Point3D.html)	<code>other</code> An object to compare with this object.

IExaminable

Returns [\(NetAF.Assets.IExaminable.html\)](#)

Type	Description
IInteractWithItem (NetAF.Assets.IInteractWithItem.html)	<code>bool ItemContainer</code> true (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool) if the current object is equal to the <code>other</code> parameter; otherwise, false (NetAF.Assets.IPlayerVisible.html)

Interaction

[\(NetAF.Assets.Interaction.html\)](#)

InteractionCallback

[IEquatable<T>](#) (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)

([NetAF.Assets.InteractionCallback.html](#))

InteractionResult

([NetAF.Assets.InteractionResult.html](#))

Item

([NetAF.Assets.Item.html](#))

Point2D

([NetAF.Assets.Point2D.html](#))

Point3D

([NetAF.Assets.Point3D.html](#))

Result

([NetAF.Assets.Result.html](#))

Size

([NetAF.Assets.Size.html](#))

+ NetAF.Assets.Attributes

([NetAF.Assets.Attributes.html](#))

+ NetAF.Assets.Characters

([NetAF.Assets.Characters.html](#))

+ NetAF.Assets.Locations

([NetAF.Assets.Locations.html](#))

+ NetAF.Commands

([NetAF.Commands.html](#))

+ NetAF.Commands.

Conversation

([NetAF.Commands.Conversation.html](#))

Class Result

Represents a result.

Filter by title

Inheritance ↳ System.Object

↳ ExaminationScene
↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
(NetAF.Assets.ExaminationScene.)
↳ Result
IExaminable
↳ ExaminationResult ([NetAF.Assets.ExaminationResult.html](#))
(NetAF.Assets.IExaminable.html)
↳ Interaction ([NetAF.Assets.Interaction.html](#))
IInteractWithItem

Inherited Members (NetAF.Assets.IInteractWithItem.html)

IItemContainer
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object)))
(NetAF.Assets.IItemContainer.html)
IPlayerVisible
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-system-object)))
(NetAF.Assets.IPlayerVisible.html)
Identifier
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
(NetAF.Assets.Identifier.html)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
Interaction
object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)
(NetAF.Assets.Interaction.html)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
InteractionCallback
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)
(NetAF.Assets.InteractionCallback)

Namespace: NetAF ([NetAF.html](#)).Assets ([NetAF.Assets.html](#))

InteractionResult

Assembly: NetAF.dll

([NetAF.Assets.InteractionResult.html](#))

Syntax (NetAF.Assets.Item.html)

Point2D
(NetAF.Assets.Point2D.html)
public abstract class Result

Point3D

(NetAF.Assets.Point3D.html)

Result

Constructors

(NetAF.Assets.Result.html)

Size ([NetAF.Assets.Size.html](#))

NetAF.Assets.Attributes

Result ([NetAF.Assets.Attributes.html](#))

Initializes a new instance of the Result class.

+ NetAF.Assets.Characters

Declaration
Result ([NetAF.Assets.Characters.html](#))

+ NetAF.Assets.Locations

Locations ([NetAF.Assets.Locations.html](#))

+ NetAF.Commands

Commands ([NetAF.Commands.html](#))

Properties

+ NetAF.Commands.

Conversation

Description

Conversation ([NetAF.Commands.Conversation.html](#))

Get the description.

Declaration

```
public string Description { get; protected set; }
```



Property Value

Type	Description
ExaminationScene (NetAF.Assets.ExaminationScene.html) string (https://learn.microsoft.com/dotnet/api/system.string) IExaminable	

(NetAF.Assets.IExaminable.html)
IInteractWithItem
(NetAF.Assets.IInteractWithItem.html)
IItemContainer
(NetAF.Assets.IItemContainer.html)
IPlayerVisible
(NetAF.Assets.IPlayerVisible.html)
Identifier
(NetAF.Assets.Identifier.html)
Interaction
(NetAF.Assets.Interaction.html)
InteractionCallback
(NetAF.Assets.InteractionCallback.html)
InteractionResult
(NetAF.Assets.InteractionResult.html)
Item (NetAF.Assets.Item.html)
Point2D
(NetAF.Assets.Point2D.html)
Point3D
(NetAF.Assets.Point3D.html)
Result
(NetAF.Assets.Result.html)
Size (NetAF.Assets.Size.html)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversation.html)

Struct Size

Represents a size.

Filter by title

Inherited Members

(NetAF.Assets.ExaminationScene.IValueType.Equals(object) (https://learn.microsoft.com/dotnet/api/system.valuetype.equals)
IExaminable
ValueType GetHashCode() (https://learn.microsoft.com/dotnet/api/system.valuetype.gethashcode)
(NetAF.Assets.IExamnable.html)
ValueType.ToString() (https://learn.microsoft.com/dotnet/api/system.valuetype.tostring)
InteractWithItem
object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object))
(NetAF.Assets.IInteractWithItem.html)
ItemContainer
object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)
(NetAF.Assets.ItemContainer.html)
object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)
IPlayerVisible
Namespace: NetAF (NetAF.html) Assets (NetAF.Assets.html)

Assembly Identifier

(NetAF.Assets.Identifier.html)

Interaction

(NetAF.Assets.Interaction.html)
public readonly struct Size
InteractionCallback

(NetAF.Assets.InteractionCallback.html)

InteractionResult

Constructors

(NetAF.Assets.InteractionResult.html)

Item (NetAF.Assets.Item.html)

Point2D

Size(int, int)

(NetAF.Assets.Point2D.html)

Point3D

Represents a size.

(NetAF.Assets.Point3D.html)

Declaration

(NetAF.Assets.Result.html)

Size (NetAF.Assets.Size.html)
public Size(int width, int height)

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

int (https://learn.microsoft.com/dotnet/api/system.int32)

Name

Description

width The width.

+ NetAF.Assets.Locations

int (https://learn.microsoft.com/dotnet/api/system.int32)

height

The height.

+ NetAF.Commands

(NetAF.Commands.html)

Properties

+ NetAF.Commands.

Conversation

Height (NetAF.Commands.Conversation.html)

Get the height.

NETAF.Commands.Frame

Declaration

```
public int Height { get; }
```

Property Value

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Assets.ExaminationScene.html)	

IExaminable
([NetAF.Assets.IExaminable.html](#))

IIteractWithItem
([NetAF.Assets.IIInteractWithItem.html](#))

IItemContainer
([NetAF.Assets.IItemContainer.html](#))

IPlayerVisible
([NetAF.Assets.IPlayerVisible.html](#))

```
public int width { get; }
```

Identifier
([NetAF.Assets.Identifier.html](#))

Interaction
([NetAF.Assets.Interaction.html](#))

InteractionCallback
([NetAF.Assets.InteractionCallback.html](#))

int (<https://learn.microsoft.com/dotnet/api/system.int32>)
[InteractionResult](#)

([NetAF.Assets.InteractionResult.html](#))

Item ([NetAF.Assets.Item.html](#))

Point2D
([NetAF.Assets.Point2D.html](#))

Point3D
([NetAF.Assets.Point3D.html](#))

Result
([NetAF.Assets.Result.html](#))

Size ([NetAF.Assets.Size.html](#))

+ NetAF.Assets.Attributes

[\(NetAF.Assets.Attributes.html\)](#)

+ NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

+ NetAF.Assets.Locations

[\(NetAF.Assets.Locations.html\)](#)

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

+ NetAF.Commands.

Conversation

[\(NetAF.Commands.Conversation.html\)](#)

+ NetAF.Commands.Frame

Namespace NetAF.Assets.Attributes

Classes

Filter by title

+ NetAF.Adapters

Attribute ([NetAF.Assets.Attributes.Attribute.html](#))

([NetAF.Adapters.html](#))

Provides a description of an attribute.

+ NetAF.Assets

([NetAF.Assets.html](#))

AttributeManager ([NetAF.Assets.Attributes.AttributeManager.html](#))

- NetAF.Assets.Attributes

Provides a class for managing attributes.

([NetAF.Assets.Attributes.html](#))

Attribute

([NetAF.Assets.Attributes.Attribute.html](#))

AttributeManager

([NetAF.Assets.Attributes.AttributeManager.html](#))

+ NetAF.Assets.Characters

([NetAF.Assets.Characters.html](#))

+ NetAF.Assets.Locations

([NetAF.Assets.Locations.html](#))

+ NetAF.Commands

([NetAF.Commands.html](#))

+ NetAF.Commands.

Conversation

([NetAF.Commands.Conversation.html](#))

+ NetAF.Commands.Frame

([NetAF.Commands.Frame.html](#))

+ NetAF.Commands.Global

([NetAF.Commands.Global.html](#))

+ NetAF.Commands.

Persistence

([NetAF.Commands.Persistence.html](#))

+ NetAF.Commands.Region

Map

([NetAF.Commands.RegionMap.html](#))

+ NetAF.Commands.Scene

Class Attribute

Provides a description of an attribute.

Filter by title

Inheritance

([NetAF.Attributes.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAFAssets**

↳ Attribute

([NetAFAssets.html](#))

Implements

- **NetAFAssets.Attributes**

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Attribute

([NetAFAssets.Attributes.html](#))

Serialization ([NetAF.Serialization.Assets.AttributeSerialization.html](#))>

↳ Attribute

Inherited Members

([NetAFAssets.Attributes.Attribute.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

([NetAFAssets.Attributes.AttributeN.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAFAssets.Characters**

([NetAFAssets.Characters.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAFAssets.Locations**

([NetAFAssets.Locations.html](#))

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Commands**

([NetAF.Commands.html](#))

Namespace: NetAF (NetAF.html) Assets (NetAF.Assets.html).Attributes (NetAF.Assets.Attributes.html)

Assembly: NetAF.dll

+ **NetAF.Commands.**

Syntax

Conversation

([NetAFCommands.Conversation.html](#))

public class Attribute : IRestoreFromObjectSerialization<AttributeSerialization>

+ **NetAF.Commands.Frame**

([NetAFCommands.Frame.html](#))

Constructors

([NetAFCommands.Global.html](#))

([NetAFCommands.Global.html](#))

Attribute(string, string, int, int)

Persistence

Provides a description of an attribute.

([NetAFCommands.Persistence.html](#))

Declaration

+ **NetAF.Commands.Region**

Maplic Attribute(string name, string description, int minimum, int maximum)

([NetAFCommands.RegionMap.html](#))

Parameters

([NetAFCommands.Scene.html](#))

+ **NetAF.Conversations**

([NetAFConversations.html](#))

(<https://learn.microsoft.com/dotnet/api/system.string>)

Type	Name	Description
String	name	Specify the name of the attribute.

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i>	Specify the description of the attribute.
int (https://learn.microsoft.com/dotnet/api/system.int32) ▼	<i>minimum</i>	Specify the minimum limit of the attribute.
int (https://learn.microsoft.com/dotnet/api/system.int32) ▼	<i>maximum</i>	Specify the maximum limit of the attribute.

+ **NetAF.Assets**

[\(NetAF.Assets.html\)](#)

- **NetAF.Assets.Attributes**

[Properties](#)
[\(NetAF.Assets.Attributes.html\)](#)

Attribute

[Description](#)
[\(NetAF.Assets.Attributes.Attribute.html\)](#)

AttributeManager

Get the attribute manager.
[\(NetAF.Assets.Attributes.AttributeManager.html\)](#)

NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

public string Description { get; }

+ **NetAF.Assets.Locations**

[\(NetAF.Assets.Locations.html\)](#)

Property Value

+ **NetAF.Commands**

Type
[\(NetAF.Commands.html\)](#)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ **NetAF.Commands.**

Conversation

[\(NetAF.Commands.Conversation.html\)](#)

Maximum

+ **NetAF.Commands.Frame**

Get the maximum limit of the attribute.
[\(NetAF.Commands.Frame.html\)](#)

Declaration

+ **NetAF.Commands.Global**

[\(NetAF.Commands.Global.html\)](#)

public int Maximum { get; }

+ **NetAF.Commands.**

Persistence

Property Value

[\(NetAF.Commands.Persistence.html\)](#)

Type

+ **NetAF.Commands.Region**

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Map

[\(NetAF.Commands.RegionMap.html\)](#)

NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Get the minimum limit of the attribute.

+ **NetAF.Conversations**

Declaration

[\(NetAF.Conversations.html\)](#)

```
public int Minimum { get; }
```

Property Value

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Adapters.html)	

+ NetAF.Assets

[\(NetAF.Assets.html\)](#)

- NetAF.Assets.Attributes

Get the name of the attribute.

[\(NetAF.Assets.Attributes.html\)](#)

Declaration
Attribute

```
(NetAF.Assets.Attributes.Attribute)  
public string Name { get; }
```

AttributeManager

(NetAF.Assets.Attributes.AttributeM

Property Value

+ NetAF.Assets.Characters

Type [\(NetAF.Assets.Characters.html\)](#)

Description

+ NetAF.Assets.Locations

[\(NetAF.Assets.Locations.html\)](#)

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

Methods

+ NetAF.Commands.

Conversation

FromSerialization(AttributeSerialization)

[\(NetAF.Commands.Conversati](#)

Create a new Attribute from a serialization.

+ NetAF.Commands.Frame

Declaration

[\(NetAF.Commands.Frame.html\)](#)

+ NetAF.Commands.Global

```
public static Attribute FromSerialization(AttributeSerialization serialization)
```

[\(NetAF.Commands.Global.htm](#)

Properties

Persistence

Type [\(NetAF.Commands.Persistence.html\)](#)

Name

Description

AttributeSerialization

serialization

The serialization to create the Attribute from.

+ NetAF.Commands.Region

[\(NetAF.Commands.Region.html\)](#)

Map

[\(NetAF.Commands.RegionMap.html\)](#)

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Attribute ([NetAF.Assets.Attributes.Attribute.html](#))

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

RestoreFrom(AttributeSerialization)

Restore this object from a serialization.

Declaration

```
public void RestoreFrom(AttributeSerialization serialization)
```

(NetAF.Adapters.html)

Parameters

+ **NetAF.Assets**

Type
(NetAF.Assets.html)

AttributeSerialization

- **NetAF.Assets.Attributes**

(NetAF.Serialization.Assets.AttributeSerialization.html)

(NetAF.Assets.Attributes.html)

Name

Description

serialization

The serialization to restore from.

Attribute

Implements

NetAF.Assets.Attributes.Attribute.h

AttributeManager

IRestoreFromObjectSerialization (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

+ **NetAF.Assets.Characters**

(NetAF.Assets.Characters.html)

+ **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

+ **NetAF.Commands**

(NetAF.Commands.html)

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversation)

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

Class AttributeManager

Provides a class for managing attributes.

Filter by title

Inheritance

+ **NetAF.Assets**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
(NetAF.Assets.html)
↳ AttributeManager

NetAF.Assets.Attributes

Implements

(NetAF.Assets.Attributes.html)

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<AttributeManager

Serialization ([NetAF.Serialization.Assets.AttributeManagerSerialization.html](#))>

(NetAF.Assets.Attributes.Attribute.html)

Inherited Members

AttributeManager

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ **NetAF.Assets.Characters**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

(NetAF.Assets.Characters.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

+ **NetAF.Assets.Locations**

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

(NetAF.Assets.Locations.html)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Commands**

(NetAF.Commands.html)

Namespace: NetAF ([NetAF.html](#)) Assets ([NetAF.Assets.html](#)).Attributes ([NetAF.Assets.Attributes.html](#))

Assembly: NetAF.dll

+ **NetAF.Commands.**

Syntax

Conversation

(NetAF.Commands.Conversation.html)

public sealed class AttributeManager : IRestoreFromObjectSerialization<AttributeManager>

 [Serializable]

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

Properties

+ **NetAF.Commands.**

Persistence

Count

(NetAF.Commands.PersistenceCount.html)

Get the number of attributes this manager has.

+ **NetAF.Commands.Region**

RegionMap

(NetAF.Commands.RegionMap.html)

 public int Count { get; }

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

Property Value

+ **NetAF.Conversations**

Type

(NetAF.Conversations.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

+ **NetAF.Conversations.**

Description

Methods

Add(Attribute, int)

Add a value to an attribute.



Declaration

+ NetAF.Assets

```
public void Add(Attribute attribute, int value)
```

(NetAF.Assets.html)

- NetAF.Assets.Attributes

Parameters

(NetAF.Assets.Attributes.html)

Type	Name	Description
Attribute		
Attribute (NetAF.Assets.Attributes.Attribute.html)	attribute	The attribute.
AttributeManager int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Assets.Attributes.AttributeV	value	The value.

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

Add(String, int)

+ NetAF.Assets.Locations

Add a value to an attribute.

(NetAF.Assets.Locations.html)

Declaration

+ NetAF.Commands

(NetAF.Commands.html)

```
public void Add(string attributeName, int value)
```

+ NetAF.Commands.

Conversation

Parameters

(NetAF.Commands.Conversation.html)

Type

Name

Description

+ NetAF.Commands.Frame

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Commands.Frame.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

value

The value.

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

GetAsDictionary()

Persistence

Get all attributes as a dictionary.

(NetAF.Commands.Persistence.html)

Declaration

+ NetAF.Commands.Region

Map

```
public Dictionary<Attribute, int> GetAsDictionary()
```

(NetAF.Commands.RegionMap.html)

NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Type	Description
Dictionary (https://learn.microsoft.com/dotnet/api/system.collections.generic.dictionary-2) <Attribute (NetAF.Assets.Attributes.Attribute.html), int (https://learn.microsoft.com/dotnet/api/system.int32)>	A dictionary where the key are the attributes and the values are the values.

+ NetAF.Assets

[\(NetAF.Assets.html\)](#)
GetAttributes()

- NetAF.Assets.Attributes

Get all attributes.
[\(NetAF.Assets.Attributes.html\)](#)

Declaration

```
Attribute
  (NetAF.Assets.Attributes.Attribute.html)
  public Attribute[] GetAttributes()
  (NetAF.Assets.Attributes.Attribute.html)
```

+ NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

+ NetAF.Assets.Locations

[\(NetAF.Assets.Locations.html\)](#)

+ NetAF.Commands

[GetValue\(Attribute\)](#)
[\(NetAF.Commands.html\)](#)

Get the value of an attribute.

Conversation

Declaration

[\(NetAF.Commands.Conversation.html\)](#)

+ NetAF.Commands.Frame

[\(NetAF.Commands.Frame.html\)](#)

Parameters

+ NetAF.Commands.Global

Type
[\(NetAF.Commands.Global.html\)](#)

Attribute ([NetAF.Assets.Attributes.Attribute.html](#))

+ NetAF.Commands.

Persistence

Returns

[\(NetAF.Commands.Persistence.html\)](#)

Type

+ NetAF.Commands.Region

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

[\(NetAF.Commands.RegionMap.html\)](#)

+ NetAF.Commands.Scene

[GetValue\(string\)](#)
[\(NetAF.Commands.Scene.html\)](#)

Get the value of an attribute.

+ NetAF Conversations

Declaration

[\(NetAF.Conversations.html\)](#)

+ NetAF.Conversations.

```
public int GetValue(string attributeName)
```

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	attributeName	The name of the attribute.

+ NetAF.Assets

Reference ([NetAF.Assets.html](#))

Type	Description
NetAF.Assets.Attributes (NetAF.Assets.Attributes.html)	

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Attribute

(NetAF.Assets.Attributes.Attribute.html)

Remove(Attribute)

AttributeManager ([NetAF.Assets.Attributes.AttributeManager.html](#))

Remove an attribute.

+ NetAF.Assets.Characters

Declaration ([NetAF.Assets.Characters.html](#))

+ NetAF.Assets.Locations

public void Remove(Attribute attribute)

([NetAF.Assets.Locations.html](#))

+ NetAF.Commands

Parameters ([NetAF.Commands.html](#))

Type	Name	Description
Attribute (NetAF.Assets.Attributes.Attribute.html)	attribute	The attribute.

Conversation

([NetAF.Commands.Conversation.html](#))

Remove(string)ds.Frame

([NetAF.Commands.Frame.html](#))

Remove an attribute.

+ NetAF.Commands.Global

Declaration

([NetAF.Commands.Global.html](#))

+ NetAF.Commands.Persistence

Persistence ([NetAF.Commands.Persistence.html](#))

+ NetAF.Commands.Region

Map

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	attributeName	The name of the attribute.

+ NetAF.Commands.Scene

([NetAF.Commands.Scene.html](#))

+ NetAF.Conversations

([NetAF.Conversations.html](#))

Declaration

+ NetAF.Conversations.

```
public void RemoveAll()
```

RestoreFrom(AttributeManagerSerialization)

Restore this object from a serialization.

+ NetAF.Assets

Declaration

[\(NetAF.Assets.html\)](#)

- NetAF.Assets.Attributes

[\(NetAF.Assets.Attributes.html\)](#)

Parameters

Type [\(NetAF.Assets.Attributes.Attribute.html\)](#)

AttributeManager [\(NetAF.Assets.Attributes.AttributeManager.html\)](#)

AttributeManagerSerialization [\(NetAF.Assets.Attributes.AttributeManagerSerialization.html\)](#)

+ NetAF.Assets.Characters

[\(NetAF.Assets.Characters.html\)](#)

Subtract(Attribute, int)

[\(NetAF.Assets.Locations.html\)](#)

Subtract a value from an attribute.

+ NetAF.Commands

Declaration

[\(NetAF.Commands.html\)](#)

+ NetAF.Commands

[\(NetAF.Commands.Subtract.html\)](#)

Conversation

[\(NetAF.Commands.Conversations.html\)](#)

Parameters

Type [\(NetAF.Commands.Frame.html\)](#)

Attribute [\(NetAF.Assets.Attributes.Attribute.html\)](#)

Name

Description

[attribute](#)

The attribute.

+ NetAF.Commands.Global

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

[value](#)

The value.

+ NetAF.Commands.

Subtract(string, int)

[\(NetAF.Commands.Persistence.html\)](#)

Subtract a value from an attribute.

+ NetAF.Commands.Region

Declaration

[Map](#)

[\(NetAF.Commands.RegionMap.html\)](#)

```
public void Subtract(string attributeName, int value)
```

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Parameters

Type [\(NetAF.Conversations.html\)](#)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Name

Description

[attributeName](#)

The name of the attribute.

+ NetAF.Conversations.

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	value	The value.

Implements

[IRestoreFromObjectSerialization<T>](#) ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))

+ **NetAF.Assets**

[\(NetAF.Assets.html\)](#)

- **NetAF.Assets.Attributes**

[\(NetAF.Assets.Attributes.html\)](#)

Attribute

[\(NetAF.Assets.Attributes.Attribute.html\)](#)

AttributeManager

[\(NetAF.Assets.Attributes.AttributeManager.html\)](#)

+ **NetAF.Assets.Characters**

[\(NetAF.Assets.Characters.html\)](#)

+ **NetAF.Assets.Locations**

[\(NetAF.Assets.Locations.html\)](#)

+ **NetAF.Commands**

[\(NetAF.Commands.html\)](#)

+ **NetAF.Commands.**

Conversation

[\(NetAF.Commands.Conversation.html\)](#)

+ **NetAF.Commands.Frame**

[\(NetAF.Commands.Frame.html\)](#)

+ **NetAF.Commands.Global**

[\(NetAF.Commands.Global.html\)](#)

+ **NetAF.Commands.**

Persistence

[\(NetAF.Commands.Persistence.html\)](#)

+ **NetAF.Commands.Region**

Map

[\(NetAF.Commands.RegionMap.html\)](#)

+ **NetAF.Commands.Scene**

[\(NetAF.Commands.Scene.html\)](#)

+ **NetAF.Conversations**

[\(NetAF.Conversations.html\)](#)

+ **NetAF.Conversations.**

Namespace NetAF.Assets.Characters

Classes

Filter by title

Character ([NetAF.Assets.Characters.Character.html](#))

+ **NetAF.Assets**

Represents a generic in game character.
[\(NetAF.Assets.html\)](#)

+ **NetAF.Assets.Attributes**

NonPlayableCharacter ([NetAF.Assets.Characters.NonPlayableCharacter.html](#))

([NetAF.Assets.Attributes.html](#))
Represents a non-playable character.

- **NetAF.Assets.Characters**

[\(NetAF.Assets.Characters.html\)](#)

PlayableCharacter ([NetAF.Assets.Characters.PlayableCharacter.html](#))

Character
Represents a playable character.
[\(NetAF.Assets.Characters.Character.html\)](#)

IConverser

[\(NetAF.Assets.Characters.IConverser.html\)](#)

NonPlayableCharacter

([NetAF.Assets.Characters.NonPlayableCharacter.html](#))

IConverser ([NetAF.Assets.Characters.IConverser.html](#))

PlayableCharacter
Represents an object that can converse.

+ **NetAF.Assets.Locations**

[\(NetAF.Assets.Locations.html\)](#)

+ **NetAF.Commands**

[\(NetAF.Commands.html\)](#)

+ **NetAF.Commands.**

Conversation

[\(NetAF.Commands.Conversation.html\)](#)

+ **NetAF.Commands.Frame**

[\(NetAF.Commands.Frame.html\)](#)

+ **NetAF.Commands.Global**

[\(NetAF.Commands.Global.html\)](#)

+ **NetAF.Commands.**

Persistence

[\(NetAF.Commands.Persistence.html\)](#)

+ **NetAF.Commands.Region**

Map

[\(NetAF.Commands.RegionMap.html\)](#)

+ **NetAF.Commands.Scene**

[\(NetAF.Commands.Scene.html\)](#)

Class Character

Represents a generic in game character.

Filter by title

Inheritance

+ **NetAF.Assets**

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableObject ([NetAF.Assets.ExaminableObject.html](#))

+ **NetAF.Assets.Attributes**

↳ Character

([NetAF.Assets.Attributes.html](#))

↳ NonPlayableCharacter ([NetAF.Assets.Characters.NonPlayableCharacter.html](#))

- **NetAF.Assets.Characters**

([NetAF.Assets.Characters.html](#))

IInteractWithItem ([NetAF.Assets.IInteractWithItem.html](#))

Character
ItemContainer ([NetAF.Assets.ItemContainer.html](#))

IExaminable ([NetAF.Assets.IExaminable.html](#))

IConverser

IPlayerVisible ([NetAF.Assets.IPlayerVisible.html](#))

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Examinable

NonPlayableCharacter
([NetAF.Serialization.Assets.ExaminableSerialization.html](#))>

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Character

PlayableCharacter
([NetAF.Assets.Characters.Playable.html](#))>

Inherited Members

+ **NetAF.Assets.Locations**

([NetAF.Assets.Locations.html](#))

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examination)

+ **NetAF.Commands**

([NetAF.Commands.html](#))

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Description)

+ **NetAF.Commands**.

Commands

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Commands)

ExaminableObject

Attributes

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Attributes)

+ **NetAF.Commands.Frame**

ExaminableObject.Examine(ExaminationScene)

([NetAF.Commands.Frame.html](#))

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_Examination

Scene)

+ **NetAF.Commands.Global**

ExaminableObject

IsPlayerVisible
([NetAF.Commands.Global.html](#))

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_IsPlayerVisible)

+ **NetAF.Commands.Persist**

ExaminableObject.ExamineFrom(ExaminableSerialization)

(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_RestoreFrom_NetAF_Serialization_As

sets_ExaminableSerialization)

([NetAF.Commands.Persistence.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Commands.Region**

MapEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Commands.RegionMap.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Commands.Scene.html](#))

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

..

Declaration

```
public Item[] Items { get; protected set; }
```

Property Value

Type	Description
Item (NetAF.Assets.Item.html) [] (NetAF.Assets.html)	

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

Methods

- NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

AddItem(Item)

Character

(NetAF.Assets.Characters.Character)
Add an item.
IConverser

Declaration
NetAF.Assets.Characters.IConverser

NonPlayableCharacter

public abstract NonPlayableCharacter (NetAF.Assets.Characters.NonPlayableCharacter)

PlayableCharacter

(NetAF.Assets.Characters.PlayableCharacter)

Parameters

+ NetAF.Assets.Locations

Type

(NetAF.Assets.Locations.html)

Item (NetAF.Assets.Item.html)

+ NetAF.Commands

(NetAF.Commands.html)

FndItem(string, out Item, bool)

Conversation

Find an item.
(NetAF.Commands.Conversation)

Declaration

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

public virtual bool FindItem(string itemName, out Item item, bool includeInvisibleItems)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

Parameters

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

string

Name

Description

The items name.

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

item

The item.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Type	Name	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	<i>includeInvisibleItems</i>	Specify if invisible items should be included.

>Returns

Type	Description
(NetAF.Assets.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the item was found.

+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

GiveItemToCharacter

(NetAF.Assets.Characters.html)

Give an item to another in game Character.

Character

Declaration:

[\(NetAF.Assets.Characters.Character.html\)](#)

IConverser

[public virtual void GiveItem\(Item item, Character character\)](#)

NonPlayableCharacter

[\(NetAF.Assets.Characters.NonPlay](#)

Parameters

PlayableCharacter

Type: [\(NetAF.Assets.Characters.Playable](#)

Name

Description

+ NetAF.Assets.Locations

item

The item to give.

(NetAF.Assets.Locations.html)

Character ([\(NetAF.Assets.Characters.Character.html\)](#))

character

The Character to give the item to.

+ NetAF.Commands

Returns:

(NetAF.Commands.html)

+ NetAF.Commands.

Description

[bool](#)

[\(https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean](#))

True if the transaction completed OK, else false.

(NetAF.Commands.Conversation.html)

+ NetAF.Commands.Frame

HasItem(item, bool)

(NetAF.Commands.Frame.html)

Determine if this PlayableCharacter has an item.

+ NetAF.Commands.Global

Declaration:

(NetAF.Commands.Global.html)

+ NetAF.Commands.

[public virtual bool HasItem\(Item item, bool includeInvisibleItems = false\)](#)

Persistence

(NetAF.Commands.Persistence.html)

Parameters

+ NetAF.Commands.Region

Type:

Map

[\(NetAF.Commands.RegionMap.html\)](#)

Name

Description

item

The item.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Interface IConverser

Represents an object that can converse.

Filter by title

Inherited Members

([NetAF.Assets.html](#))

IExaminable.Identifier ([NetAF.Assets.IExaminable.html](#)#NetAF_Assets_IExaminable_Identifier)

+ **NetAF.Assets.Attributes**
[NetAF.Assets.Attributes.html](#)

IExaminable.Description ([NetAF.Assets.IExaminable.html](#)#NetAF_Assets_IExaminable_Description)

IExaminable.Commands ([NetAF.Assets.IExaminable.html](#)#NetAF_Assets_IExaminable_Commands)

IExaminable.Attributes ([NetAF.Assets.IExaminable.html](#)#NetAF_Assets_IExaminable_Attributes)

([NetAF.Assets.Characters.html](#))

IExaminable.Examine ([ExaminationScene.html](#))

([NetAF.Assets.IExaminable.html](#)#NetAF_Assets_IExaminable_Examine_NetAF_Assets_ExaminationScene_)

Character

IPlayerVisible.IIsPlayerVisible ([IPlayerVisible.html](#)#NetAF_Assets_IPlayerVisible_IsPlayerVisible)

IRestoreFromObjectSerialization<ExaminableSerialization>.RestoreFrom(ExaminableSerialization)

([NetAF.Serialization.IRestoreFromObjectSerialization.html](#))

1.html#NetAF_Serialization_IRestoreFromObjectSerialization_1_RestoreFrom__0_

NonPlayableCharacter

Namespace: NetAF ([NetAF.html](#)).Assets ([NetAF.Assets.html](#)).Characters ([NetAF.Assets.Characters.html](#))

([NetAF.Assets.Characters.NonPlay.html](#))

Assembly: NetAF.dll

PlayableCharacter

Syntax: [NetAF.Assets.Characters.PlayableCharacter.html](#)

+ **NetAF.Assets.Locations**

public interface IConverser : IExaminable, IPlayerVisible, IRestoreFromObjectSerialization<ExaminableSerialization>

+ **NetAF.Commands**

([NetAF.Commands.html](#))

+ **NetAF.Commands.**

Properties

Conversation

([NetAF.Commands.Conversation.html](#))

Conversation

([NetAF.Commands.Frame.html](#))

Get the conversation.

+ **NetAF.Commands.Global**

Declaration: [NetAF.Commands.Global.html](#)

Conversation Conversation { get; }

+ **NetAF.Commands.**

Persistence

Property Value

([NetAF.Commands.Persistence.html](#))

Type

+ **NetAF.Commands.Region**

Map (NetAF.Conversations.Conversation.html)

([NetAF.Commands.RegionMap.html](#))

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

Type	Description
+ NetAF.Commands.Region	

▼

(NetAF.Assets.html)

+ **NetAF.Assets.Attributes**

(NetAF.Assets.Attributes.html)

- **NetAF.Assets.Characters**

(NetAF.Assets.Characters.html)

Character

(NetAF.Assets.Characters.Character.html)

IConverser

(NetAF.Assets.Characters.IConverser.html)

NonPlayableCharacter

(NetAF.Assets.Characters.NonPlayableCharacter.html)

PlayableCharacter

(NetAF.Assets.Characters.PlayableCharacter.html)

+ **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

+ **NetAF.Commands**

(NetAF.Commands.html)

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversation.html)

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

Class NonPlayableCharacter

Represents a non-playable character.

Filter by title

Inheritance

+ NetAF.Assets.Attributes

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Assets.Attributes.html\)](#)
↳ ExaminableObject ([NetAF.Assets.ExaminableObject.html](#))

- NetAF.Assets.Characters

↳ Character ([NetAF.Assets.Characters.Character.html](#))
↳ NonPlayableCharacter

(NetAF.Assets.Characters.htm)

Implements

Character

IInteractWithItem ([NetAF.Assets.IInteractWithItem.html](#))

IItemContainer ([NetAF.Assets.IItemContainer.html](#))

IConverser ([NetAF.Assets.Characters.IConverser.html](#))

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Character

Serialization ([NetAF.Serialization.Assets.CharacterSerialization.html](#))>

NonPlayableCharacter

IConverser ([NetAF.Assets.Characters.IConverser.html](#))

IExaminable ([NetAF.Assets.IExaminable.html](#))

PlayableCharacter

IPlayerVisible ([NetAF.Assets.IPlayerVisible.html](#))

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Examinable

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.htm)

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<NonPlayable

CharacterSerialization ([NetAF.Serialization.Assets.NonPlayableCharacterSerialization.html](#))>

+ NetAF.Commands

Inherited Members

(NetAF.Commands.html)

Character.IsAlive ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_IsAlive)

+ NetAF.Commands.

Character.Interaction

Conversation ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_Interaction)

Converser ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_Kill)

Character.HasItem(Item, bool)

Frame ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_HasItem_NetAF_Assets_Item_System_Boolean_)

+ NetAF.Commands.Frame

Frame ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_HasItem_NetAF_Assets_Item_System_Boolean_)

+ NetAF.Commands.Global

Global ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_FindItem_System_String_NetA

F_Assets_Item_System_Boolean_)

+ NetAF.Commands.Character

Persistence ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_Give_NetAF_Assets_Item_Net

AF_Assets_Characters_Character_)

(NetAF.Commands.Persistence)

Character.Interact(Item)

+ NetAF.Commands.Region

RegionMap ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_Interact_NetAF_Assets_Item_

Character.Items ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_Items)

Character.AddItem(Item)

(NetAF.Commands.RegionMap)

Character.AddItem ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_AddItem_NetAF_Assets_Item_)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Scene ([NetAF.Assets.Characters.Character.html](#)#NetAF_Assets_Characters_Character_RemoveItem_NetAF_Assets_I

tem_)

+ NetAF.Conversations

(NetAF.Conversations.html)

Character.RestoreFrom(CharacterSerialization)
(NetAF.Assets.Characters.Character.html#NetAF_Assets_Characters_Character_RestoreFrom_NetAF_Serialization_Assets_CharacterSerialization_)

ExaminableObject.Examination
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examination)

ExaminableObject.Identifier (NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Identifier)

ExaminableObject.Description
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Description)

+ **NetAF Assets Attributes**
(NetAFAssetsAttributes.html) NetAF_Assets_ExaminableObject_Commands)

ExaminableObject.Attributes
- **NetAF Assets Characters**
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Attributes)

ExaminableObject.Examine(ExaminationScene)
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_ExaminationScene)

NonPlayableCharacter
(NetAF.Assets.Characters.Character.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_ExaminationScene)

ExaminableObject.IsPlayerVisible
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_IsPlayerVisible)

NonPlayableCharacter.RestoreFrom(ExaminableSerialization)
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_RestoreFrom_NetAF_Serialization_Assets_ExaminableSerialization_)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF Assets Locations**
(NetAFAssetsLocations.html)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF Commands**

NonPlayableCharacter (NetAF.html).Assets (NetAF.Assets.html).Characters (NetAF.Assets.Characters.html)

Assets (NetAF.Commands.html)

+ **NetAF.Commands.Conversation**

Syntax

+ **NetAF.Commands.Frame**

(NetAFCommandsFrame.html)

public sealed class NonPlayableCharacter : Character, IInteractWithItem, IItemContainer, IConverser, IExaminable, IPersistent, IPlayerVisible, IRestoreFromObjectSerialization<CharacterSerialization>, IRestoreFromObjectSerialization<ExaminableSerialization>, IRestoreFromObjectSerialization<NonPlayableCharacterSerialization>

+ **NetAF.Commands.Global**

(NetAFCommandsGlobal.html)

+ **NetAF.Commands.**

Persistence

(NetAFCommandsPersistence.html)

CONSTRUCTORS

+ **NetAF.Commands.Region**

Map
NonPlayableCharacter(Identifier, Description, Conversation, CustomCommand[], InteractionCallback, ExaminationCallback)

+ **NetAF.Commands.Scene**

Initializes a new instance of the NonPlayableCharacter class.
(NetAFCommandsScene.html)

Declaration

+ **NetAF.Conversations**

(NetAFConversations.html)

```
public NonPlayableCharacter(Identifier identifier, Description description, Conversation conversation = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null)
```

Parameters

Type	Name	Description
+ NetAF.Assets.Attributes Identifier (NetAF.Assets.Identifier.html) (NetAF.Assets.Attributes.html)	<i>identifier</i>	The identifier.
Description (NetAF.Assets.Description.html)	<i>description</i>	The description.
- NetAF.Assets.Characters Conversation (NetAF.Conversations.Conversation.html) (NetAF.Assets.Characters.html)	<i>conversation</i>	The conversation.
CustomCommand (NetAF.Commands.CustomCommand.html[]) (NetAF.Commands.html)	<i>commands</i>	This objects commands.
InteractionCallback (NetAF.Assets.InteractionCallback.html) (NetAF.Assets.html)	<i>interaction</i>	The interaction.
ExaminationCallback (NetAF.Assets.ExaminationCallback.html) (NetAF.Assets.html)	<i>examination</i>	The examination.

NonPlayableCharacter
(NetAF.Assets.Characters.NonPlayableCharacter.html)

NonPlayableCharacter(Identifier, Description, bool, Conversation, CustomCommand[], InteractionCallback, ExaminationCallback)
[\(NetAF.Assets.Characters.html\)](#)

+ NetAF.Assets.Locations

Initializes a new instance of the NonPlayableCharacter class.
[\(NetAF.Assets.Locations.html\)](#)

Declaration

+ NetAF.Commands

(NetAF.Commands.html)
public NonPlayableCharacter(Identifier identifier, Description description, bool isAlive, Conversation conversation = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null)

+ NetAF.Commands.Conversation

(NetAF.Commands.Conversation.html)

Parameters

+ NetAF.Commands.Frame

Type	Name	Description
(NetAF.Commands.Frame.html)		
Identifier (NetAF.Assets.Identifier.html)	<i>identifier</i>	The identifier.
(NetAF.Commands.Global.html)	<i>description</i>	The description.
+ NetAF.Commands soft.com/dotnet/api/system.boolean)	<i>isAlive</i>	If this character is alive.
Persistence Conversation (NetAF.Conversations.Conversation.html)	<i>conversation</i>	The conversation.
+ NetAF.Commands.Persistence CustomCommand (NetAF.Commands.CustomCommand.html[])	<i>commands</i>	This objects commands.
+ NetAF.Commands.RegionMap InteractionCallback (NetAF.Assets.InteractionCallback.html)	<i>interaction</i>	The interaction.
(NetAF.Commands.RegionMap.html)	<i>examination</i>	The examination.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

NonPlayableCharacter(string, string, Conversation, CustomCommand[], InteractionCallback, ExaminationCallback)
[\(NetAF.Conversations.html\)](#)

Initializes a new instance of the NonPlayableCharacter class.

Declaration

```
public NonPlayableCharacter(string identifier, string description, Conversation conversation = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null)
```

+ NetAF.Assets.Attributes

Parameters

Type	Name	Description
- NetAF.Assets.Characters string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Assets.Characters.htm)	<i>identifier</i>	The identifier.
- NetAF.Assets.Characters string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Assets.Characters.htm)	<i>description</i>	The description.
- NetAF.Assets.Characters Conversation (https://learn.microsoft.com/dotnet/api/system.conversation) (NetAF.Assets.Characters.Conversation.htm)	<i>conversation</i>	The conversation.
- NetAF.Assets.Characters IConverser CustomCommand (https://learn.microsoft.com/dotnet/api/system.customcommand)[] (NetAF.Assets.Characters.IConverser.htm)	<i>commands</i>	This objects commands.
- NetAF.Assets.Characters InteractionCallback (https://learn.microsoft.com/dotnet/api/system.interactioncallback) (NetAF.Assets.Characters.NonPlayableCharacter.htm)	<i>interaction</i>	The interaction.
- NetAF.Assets.Characters ExaminationCallback (https://learn.microsoft.com/dotnet/api/system.examinationcallback) (NetAF.Assets.Characters.PlayableCharacter.htm)	<i>examination</i>	The examination.

(NetAF.Assets.Characters.PlayableCharacter.htm)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.htm)

Properties

+ NetAF.Commands

(NetAF.Commands.html)

Conversation

+ NetAF.Commands.

Get the conversation.

Conversation

Delegates

(NetAF.Commands.Conversation.htm)

+ NetAF.Commands.Frame

```
public Conversation Conversation { get; }
```

(NetAF.Commands.Frame.htm)

+ NetAF.Commands.Global

Property value

(NetAF.Commands.Global.htm)

Type

Description

+ NetAF.Commands.

Conversation (<https://learn.microsoft.com/dotnet/api/system.conversation>)

Persistence

(NetAF.Commands.Persistence.htm)

+ NetAF.Commands.Region

Methods

(NetAF.Commands.RegionMap.htm)

RestoreFrom(NonPlayableCharacterSerialization)

(NetAF.Commands.Scene.htm)

Restore this object from a serialization.

+ NetAF.Conversations

Declaration

(NetAF.Conversations.htm)

```
public void RestoreFrom(NonPlayableCharacterSerialization serialization)
```

Parameters

Type		Name	Description
NonPlayableCharacterSerialization (NetAF.Serialization.Assets.NonPlayableCharacterSerialization.html)		serialization	The serialization to restore from.

+ NetAF.Assets.Attributes (NetAF.Assets.Attributes.html)

implements

(NetAF.Assets.Characters.htm

IInteractWithItem (NetAF.Assets.IInteractWithItem.html)
Character
IItemContainer (NetAF.Assets.IItemContainer.html)
(NetAF.Assets.Characters.Character)
IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)
IConverser (NetAF.Assets.Characters.IConverser.html)
(NetAF.Assets.Characters.IConverser)
IExaminable (NetAF.Assets.IExaminable.html)
NonPlayableCharacter
IPlayerVisible (NetAF.Assets.IPlayerVisible.html)
(NetAF.Assets.Characters.NonPlay
PlayableCharacter
IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)
(NetAF.Assets.Characters.Playable

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversation)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

Class PlayableCharacter

Represents a playable character.

Filter by title

Inheritance

([NetAFAssets.Attributes.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

- **NetAFAssets.Characters**

↳ Character ([NetAFAssets.Characters.Character.html](#))

([NetAFAssets.Characters.html](#))

↳ PlayableCharacter

Character

Implements

([NetAFAssets.Characters.Character.html](#))

IInteractWithItem ([NetAFAssets.IInteractWithItem.html](#))

IConverser

ItemContainer ([NetAFAssets.ItemContainer.html](#))

IExaminable ([NetAFAssets.IExaminable.html](#))

NonPlayableView

IPlayerVisible ([NetAFAssets.IPlayerVisible.html](#))

NonPlayableCharacter

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Examinable

Serialization ([NetAF.Serialization.Assets.ExaminableSerialization.html](#))>

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Character

Serialization ([NetAF.Serialization.Assets.CharacterSerialization.html](#))>

([NetAFAssets.Locations.html](#))

Inherited Members

+ **NetAFCommands**

Character.IsAlive ([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_IsAlive](#))

Character.Interaction

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_Interaction](#))

+ **NetAFCommands**.

Character.Kill () ([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_Kill](#))

Conversation

Character.HasItem (Item, bool)

([NetAFCommands.Conversation.html](#))

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_HasItem_NetAF_Assets_Item_System_Boolean](#))

+ **NetAFCommands.Frame**

Character.FindItem (string, out Item, bool)

([NetAFCommands.Frame.html](#))

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_FindItem_System_String_NetA](#)

F_Assets_Item_System_Boolean

Character.Give (Item, Character)

([NetAFCommands.Global.html](#))

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_Give_NetAF_Assets_Item_Net](#)

A_Assets_Character

Character.Interact (Item)

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_Interact_NetAF_Assets_Item_](#)

([NetAFCommands.Persistence.html](#))

Character.Items ([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_Items](#))

+ **NetAFCommands.Region**

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_AddItem_NetAF_Assets_Item_](#))

Character.RemoveItem (Item)

([NetAFCommands.RegionMap.html](#))

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_RemoveItem_NetAF_Assets_I](#)

tem

+ **NetAFCommands.Scene**

Character.LoadScene (Localization)

([NetAFAssets.Characters.Character.html#NetAF_Assets_Characters_Character_RestoreFrom_NetAF_Serializati](#)

on_Assets_CharacterSerialization

([NetAFCommands.Scene.html](#))

+ **NetAFConversations**

ExaminableObject.Examination
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examination)
ExaminableObject.Identifier (NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Identifier)
ExaminableObject.Description
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Description)
ExaminableObject.Commands
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Commands)
ExaminableObject.Attributes--
(NetAF.Assets.Attributes.html) NetAF_Assets_ExaminableObject_Attributes
ExaminableObject.Examine(ExaminationScene)
- **NetAF.Assets.Characters**
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_Examination_Scene_)
Character
ExaminableObject.IsPlayerVisible
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_IsPlayerVisible)
PlayableObject.RestoreFrom(ExaminableSerialization)
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_RestoreFrom_NetAF_Serialization_Assets_PlayableObject)
object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals(system-object-system-object))
object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals(system-object-system-object))
+ **NetAF.Assets.Locations**
object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)
(NetAF.Assets.Locations.html)
object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)
object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)
object.ToString() (https://learn.microsoft.com/dotnet/api/system.object.tostring)
(NetAF.Commands.html)
Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html).Characters (NetAF.Assets.Characters.html)
+ **NetAF.Commands.**
Assembly: NetAF.dll
Conversation
(NetAF.Commands.Conversation.html)
+ **NetAF.Commands.Frame**
(NetAF.Commands.Frame.html)
+ **NetAF.Commands.Global**
(NetAF.Commands.Global.html)
Constructors
+ **NetAF.Commands.**
Persistence
(NetAF.Commands.Persistence.html)
PlayableCharacter(Identifier, Description, Item[], CustomCommand[], InteractionCallback, ExaminationCallback)
+ **NetAF.Commands.Region**
Map
Initializes a new instance of the PlayableCharacter class.
(NetAF.Commands.RegionMap.html)
Declaration
+ **NetAF.Commands.Scene**
(NetAF.Commands.Scene.html)
Identifier identifier, Description description, Item[] item
s = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null
+ **NetAF.Conversations**
(NetAF.Conversations.html)
+ **NetAF.Conversations**

Parameters

Type	Name	Description
Identifier (NetAF.Assets.Identifier.html)	<i>identifier</i>	The identifier.
Description (NetAF.Assets.Description.html)	<i>description</i>	The description.
Item (NetAF.Assets.Item.html)[]	<i>items</i>	The items.
CustomCommand (NetAF.Commands.CustomCommand.html)[] (NetAF.Assets.Attributes.html)	<i>commands</i>	This objects commands.
InteractionCallback (NetAF.Assets.InteractionCallback.html)	<i>interaction</i>	The interaction.
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	<i>examination</i>	The examination.

Character

(NetAF.Assets.Characters.Character)

PlayableCharacter(Identifier, Description, bool, Item[], CustomCommand[], InteractionCallback, ExaminationCallback)

NonPlayableCharacter

Initializes a new instance of the PlayableCharacter class.

(NetAF.Assets.Characters.NonPlayableCharacter)

PlayableCharacter

(NetAF.Assets.Characters.PlayableCharacter)

+ **NetAF.Assets.Locations**
Identifier identifier, Description description, bool canConverse, Item[] items = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null)
(NetAF.Assets.Locations.html)

+ NetAF.Commands

(NetAF.Commands.html)

Parameters

Type	Name	Description
Conversation Identifier (NetAF.Assets.Identifier.html) (NetAF.Commands.Conversation.html)	<i>identifier</i>	The identifier.
Description (NetAF.Assets.Description.html)	<i>description</i>	The description.
+ NetAF.Commands.Frame		
bool canConverse (NetAF.Commands.Frame.html) (https://learn.microsoft.com/dotnet/api/system.boolean)	<i>canConverse</i>	If this object can converse with an IConverser.
+ NetAF.Commands.Global		
(NetAF.Commands.Global.html) Item (NetAF.Assets.Item.html)[]	<i>items</i>	The items.
+ NetAF.Commands.Persistence		
CustomCommand (NetAF.Commands.Persistence.html)	<i>commands</i>	This objects commands.
+ NetAF.Commands.Region		
InteractionCallback (NetAF.Assets.InteractionCallback.html)	<i>interaction</i>	The interaction.
+ NetAF.Commands.RegionMap		
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	<i>examination</i>	The examination.
+ NetAF.Commands.Scene		
(NetAF.Commands.Scene.html)		

+ **NetAF Conversations**
PlayableCharacter(string, string, Item[], CustomCommand[], InteractionCallback, ExaminationCallback)
(NetAF Conversations.html)

+ **NetAF Conversations**

Initializes a new instance of the PlayableCharacter class.

Declaration

```
public PlayableCharacter(string identifier, string description, Item[] items = null,
    CustomCommand[] commands = null, InteractionCallback interaction = null, Examination
    Callback examination = null)
```

(NetAF.Assets.Attributes.html)

Parameters	Name	Description
- NetAF.Assets.Characters		
(NetAF.Assets.Characters.html)		
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>identifier</i>	The identifier.
Character string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Assets.Characters.Character.html)	<i>description</i>	The description.
Item [NetAF.Assets.Item.html] [] (NetAF.Assets.Characters.IConverser.html)	<i>items</i>	The items.
CustomCommand (NetAF.Commands.CustomCommand.html) [] NonPlayableCharacter	<i>commands</i>	This objects commands.
InteractionCallback (NetAF.Assets.InteractionCallback.html) PlayableCharacter	<i>interaction</i>	The interaction.
ExaminationCallback (NetAF.Assets.ExaminationCallback.html) (NetAF.Assets.Characters.PlayableCharacter.html)	<i>examination</i>	The examination.

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

PlayableCharacter(string, string, bool, Item[], CustomCommand[],
InteractionCallback, ExaminationCallback)

(NetAF.Commands.html)

Initializes a new instance of the PlayableCharacter class.

+ NetAF.Commands.

Declaration

Conversation

(NetAF.Commands.Conversation.html)

```
public PlayableCharacter(string identifier, string description, bool canConverse, It
    em[] items = null, CustomCommand[] commands = null, InteractionCallback interaction
    = null, ExaminationCallback examination = null)
```

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

Parameters

(NetAF.Commands.Global.html)

Type	Name	Description
+ NetAF.Commands.		
Persistence string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.Persistence.html)	<i>identifier</i>	The identifier.
string	<i>description</i>	The description.
+ NetAF.Commands.Region string (https://learn.microsoft.com/dotnet/api/system.string)		
Map bool (NetAF.Commands.RegionMap.html) (https://learn.microsoft.com/dotnet/api/system.boolean)	<i>canConverse</i>	If this object can converse with an IConverser.
+ NetAF.Commands.Scene		
(NetAF.Commands.Scene.html)	<i>items</i>	The items.

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations

Namespace NetAF.Assets.Locations

Classes

Filter by title

Exit (NetAF.Assets.Locations.Exit.html)

Represents an exit from a GameLocation.
+ NetAF.Assets.Attributes

(NetAF.Assets.Attributes.html)

Matrix (NetAF.Assets.Locations.Matrix.html)

+ NetAF.Assets.Characters

Provides a 3D matrix of rooms.

(NetAF.Assets.Characters.html)

- NetAF.Assets.Locations

Overworld (NetAF.Assets.Locations.Overworld.html)

(NetAF.Assets.Locations.html)

Represents an entire overworld.

Direction

(NetAF.Assets.Locations.Direction.html)

Region (NetAF.Assets.Locations.Region.html)

(NetAF.Assets.Locations.Exit.html)

Represents a region.

Matrix

(NetAF.Assets.Locations.Matrix.html)

Room (NetAF.Assets.Locations.Room.html)

(NetAF.Assets.Locations.Overworld.html)

Represents a room.

Region

(NetAF.Assets.Locations.Region.html)

RoomPosition (NetAF.Assets.Locations.RoomPosition.html)

(NetAF.Assets.Locations.Room.html)

Represents a room position.

RoomPosition

(NetAF.Assets.Locations.RoomPosition.html)

ViewPoint (NetAF.Assets.Locations.ViewPoint.html)

(NetAF.Assets.Locations.ViewPoint.html)

Represents a view point from a room.

+ NetAF.Commands

Commands

+ NetAF.Commands.

Conversation

Direction (NetAF.Assets.Locations.Direction.html)

(NetAF.Commands.Conversation.html)

Enumeration of directions.

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

Enum Direction

Enumeration of directions.

Filter by title

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html).Locations (NetAF.Assets.Locations.html)

Assembly: NetAF.dll

+ NetAF.Assets.Attributes

Syntax
([NetAF.Assets.Attributes.html](#))

+ NetAF.Assets.Characters

public enum Direction
([NetAF.Assets.Characters.html](#))

- NetAF.Assets.Locations

([NetAF.Assets.Locations.html](#))

Fields

([NetAF.Assets.Locations.Direction.html](#))

Name	Description
Exit	(NetAF.Assets.Locations.Exit.html)
Down	Down.
Matrix	(NetAF.Assets.Locations.Matrix.html)
East	East.
Overworld	(NetAF.Assets.Locations.Overworld.html)
North	North.
Region	(NetAF.Assets.Locations.Region.html)
South	South.
Up	Up.
Room	(NetAF.Assets.Locations.Room.html)
West	West.
RoomPosition	(NetAF.Assets.Locations.RoomPosition.html)

Extension Methods

([NetAF.Assets.Locations.ViewPoint.html](#))

DirectionExtensions.Inverse(Direction)

+ NetAF.Commands

([NetAF.Extensions.DirectionExtensions.html#NetAF_Extensions_DirectionExtensions_Inverse_NetAF_Assets_Locations_Direction__](#))

+ NetAF.Commands.

Conversation

([NetAF.Commands.Conversation.html](#))

+ NetAF.Commands.Frame

([NetAF.Commands.Frame.html](#))

+ NetAF.Commands.Global

([NetAF.Commands.Global.html](#))

+ NetAF.Commands.

Persistence

([NetAF.Commands.Persistence.html](#))

+ NetAF.Commands.Region

Class Exit

Represents an exit from a GameLocation.

Filter by title

Inheritance

+ NetAF.Assets.Attributes

↳ [\(NetAF.Assets.Attributes.html\)](#) (https://learn.microsoft.com/dotnet/api/system.object)

↳ ExaminableObject ([NetAF.Assets.ExaminableObject.html](#))

+ NetAF.Assets.Characters

↳ Exit

(NetAF.Assets.Characters.htm)

Implements

+ NetAF.Assets.Locations

†Examinable ([NetAF.Assets.Examinable.html](#))

(NetAF.Assets.Locations.Player.htm)

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Examinable
Direction

Serialization ([NetAF.Serialization.Assets.ExaminableSerialization.html](#))>

([NetAF.Assets.Locations.Direction.html](#))

IIInteractWithItem ([NetAF.Assets.IIInteractWithItem.html](#))

Exit

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<ExitSerialization

([NetAF.Assets.Locations.Exit.html](#))

([NetAF.Serialization.Assets.ExitSerialization.html](#))>

Matrix

Inherits [NetAF.Assets.Locations.Matrix.htm](#)

Overworld
ExaminableObject.Examination
([NetAF.Assets.Locations.Overworld.html](#))#NetAF_Assets_ExaminableObject_Examination)
Region
ExaminableObject.Identifier ([NetAF.Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_Identifier)
([NetAF.Assets.Locations.Region.html](#))
ExaminableObject.Description
Room
([NetAF.Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_Description)
([NetAF.Assets.Locations.Room.html](#))
ExaminableObject.Commands
RoomPosition
([NetAF.Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_Commands)
([NetAF.Assets.Locations.RoomPosition.html](#))
ExaminableObject.Attributes
ViewPoint
([NetAF.Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_Attributes)
([NetAF.Assets.Locations.ViewPoint.html](#))
ExaminableObject.Examine(ExaminationScene)

+ NetAF.Commands.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_Examination

Scene
(NetAF.Commands.html)

ExaminableObject.IsPlayerVisible

+ NetAF.Commands.ExaminableObject.html#NetAF_Assets_ExaminableObject_IsPlayerVisible

Conversation RestoreFrom(ExaminableSerialization)

([NetAF.Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_RestoreFrom_NetAF_Serialization_Assets_ExaminableSerialization_)

+ NetAF.Commands.Frame
object.Equals(object) (<https://learn.microsoft.com/dotnet/api/system.object.equals>#system-object-equals(system-object))

(NetAF.Commands.Global.htm)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF.Commands.Persistence.htm)

Namespace: NetAF ([NetAF.html](#)).Assets ([NetAF.Assets.html](#)).Locations ([NetAF.Assets.Locations.html](#))

+ NetAF.Commands.Region

Man

Syntax

```
public sealed class Exit : ExaminableObject, IExaminable, IPlayerVisible, IRotateFor  
omObjectSerialization<ExaminableSerialization>, IInteractWithItem, IRotateFromObjec  
tSerialization<ExitSerialization>
```

▼

Constructors

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters
**Exit(Direction, bool, Identifier, Description, CustomCommand[],
InteractionCallback, ExaminationCallback)**
(NetAF.Assets.Characters.html)

NetAF.Assets.Locations
Initializes a new instance of the Exit class.

(NetAF.Assets.Locations.html)

Declaration
Direction

```
(NetAF.Assets.Direction.  
public Exit(Direction direction, bool isLocked = false, Identifier identifier = nul  
Exit  
l, Description description = null, CustomCommand[] commands = null, InteractionCallb  
NetAF.Assets.Locations.Exit.html)ack interaction = null, ExaminationCallback examination = null)  
Matrix  
(NetAF.Assets.Locations.Matrix.htm
```

Parameters

Overworld

Type	Description
Region	The direction of the exit.
Direction (NetAF.Assets.Direction.html)	direction
Room	If this exit is locked.
bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Room.htm)	isLocked
Identifier (NetAF.Assets.Identifier.html)	identifier
RoomPosition (NetAF.Assets.RoomPosition.html)	description
Description (NetAF.Assets.Description.html)	A description of the exit.
ViewPoint (NetAF.Assets.ViewPoint.html)	commands
CustomCommand (NetAF.Commands.CustomCommand.html)[]	This objects commands.
InteractionCallback (NetAF.Assets.InteractionCallback.html)	interaction
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	examination

+ NetAF.Commands

Conversation

(NetAF.Commands.Conversation.html)

Properties

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Direction

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

Delegates

Persistence

(NetAF.Commands.Persistence.html) { get; }

+ NetAF.Commands.Region

Man

Property Value

Type	Description
Direction (NetAF.Assets.Locations.Direction.html)	



Interaction

+ [NetAF.Assets.Attributes](#)

Get the Interaction

([NetAF.Assets.Attributes.html](#))

Declaration

+ [NetAF.Assets.Characters](#)

([NetAF.Assets.Characters.html](#)

```
    public InteractionCallback Interaction { get; }
```

- [NetAF.Assets.Locations](#)

([NetAF.Assets.Locations.html](#))

Property Value

Direction

Type ([NetAF.Assets.Locations.Direction](#).

Exit

InteractionCallback ([NetAF.Assets.InteractionCallback.html](#))

([NetAF.Assets.Locations.Exit.html](#))

Matrix

([NetAF.Assets.Locations.Matrix.html](#))

IsLocked

Overworld

([NetAF.Assets.Locations.Overworld.html](#))

Get if this Exit is locked.

Region

Declaration ([NetAF.Assets.Locations.Region.html](#))

Room

([NetAF.Assets.Locations.Room.html](#))

RoomPosition

([NetAF.Assets.Locations.RoomPosition.html](#))

Property Value

ViewPoint

Type ([NetAF.Assets.Locations.ViewPoint.html](#))

+ [NetAF.Commands](#)

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

([NetAF.Commands.html](#))

+ [NetAF.Commands.](#)

Conversation

Methods ([NetAF.Commands.Conversation.html](#))

+ [NetAF.Commands.Frame](#)

Interact(Item)

([NetAF.Commands.Frame.html](#))

Interact with an item.

+ [NetAF.Commands.Global](#)

([NetAF.Commands.Global.html](#))

Declaration

+ [NetAF.Commands.](#)

public Interaction Interact(Item item)

Persistence

([NetAF.Commands.Persistence.html](#))

Parameters

+ [NetAF.Commands.Region](#)

Map

Type	Name	Description
Item (NetAF.Assets.Item.html)	<i>item</i>	The item to interact with.

Returns

Type	Description
+ NetAF.Assets.Attributes (NetAF.Assets.Attributes.html)	The interaction.

+ **NetAF.Assets.Characters**
Lock()
(NetAF.Assets.Characters.html)

Lock this exit.

- **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

Direction

public void Lock()

Exit

(NetAF.Assets.Locations.Exit.html)

Matrix

RestoreFrom(ExitSerialization)

(NetAF.Assets.Locations.Matrix.html)

Overworld

Restore this object from a serialization.

(NetAF.Assets.Locations.Overworld.html)

Region

(NetAF.Assets.Locations.Region.html)

Room

public void RestoreFrom(ExitSerialization serialization)

(NetAF.Assets.Locations.Room.html)

RoomPosition

Parameters

(NetAF.Assets.Locations.RoomPos.html)

Type	Name	Description
ViewPoint (NetAF.Assets.Locations.ViewPoint.html)	serialization	The serialization to restore from.

+ **NetAF.Commands**

(NetAF.Serialization.Assets.ExitSerialization.html)

(NetAF.Commands.html)

+ **NetAF.Commands.**

Unlock()

Conversation

(NetAF.Commands.Conversation.html)

Unlock this exit.

+ **NetAF.Commands.Frame**

Declaration

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

IEntity (NetAF.Assets.IEntity.html)

IPlayerVisible (NetAF.Assets.IPlayerVisible.html)

+ **NetAF.Commands.Region**

(NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

Man

IInteractWithItem (NetAF.Assets.IInteractWithItem.html)

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

▼

+ **NetAF.Assets.Attributes**

(NetAF.Assets.Attributes.html)

+ **NetAF.Assets.Characters**

(NetAF.Assets.Characters.html)

- **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

 Direction

 (NetAF.Assets.Locations.Direction.html)

 Exit

 (NetAF.Assets.Locations.Exit.html)

 Matrix

 (NetAF.Assets.Locations.Matrix.html)

 Overworld

 (NetAF.Assets.Locations.Overworld.html)

 Region

 (NetAF.Assets.Locations.Region.html)

 Room

 (NetAF.Assets.Locations.Room.html)

 RoomPosition

 (NetAF.Assets.Locations.RoomPosition.html)

 ViewPoint

 (NetAF.Assets.Locations.ViewPoint.html)

+ **NetAF.Commands**

(NetAF.Commands.html)

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversation.html)

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

(NetAF.Commands.Region.html)

Class Matrix

Provides a 3D matrix of rooms.

Filter by title

Inheritance

([NetAF.Assets.Attributes.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Assets.Characters**

↳ Matrix

([NetAF.Assets.Characters.html](#))

Inherited Members

- **NetAF.Assets.Locations**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Overload

Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html).Locations (NetAF.Assets.Locations.html)

([NetAF.Assets.Locations.Overworld](#))

Assembly: NetAF.dll

Region

Syntax

([NetAF.Assets.Locations.Region.html](#))

Room

public sealed class Matrix ([NetAF.Assets.Locations.Room.html](#))

RoomPosition

([NetAF.Assets.Locations.RoomPosition.html](#))

ViewPoint

([NetAF.Assets.Locations.ViewPoint.html](#))

Constructors

([NetAF.Assets.Locations.ViewPoint.html](#))

+ **NetAF.Commands**

Matrix(RoomPosition[]) ([NetAF.Commands.html](#))

Provides a 3D matrix of rooms.

Declaration

([NetAF.Commands.Conversation.html](#))

public Matrix(RoomPosition[] roomPositions)

+ **NetAF.Commands.Frame**

([NetAF.Commands.Frame.html](#))

Parameters

+ **NetAF.Commands.Global**

Type ([NetAF.Commands.Global.html](#))

RoomPosition ([NetAF.Assets.Locations.RoomPosition.html](#))[]

+ **NetAF.Commands**

Persistence

([NetAF.Commands.Persistence.html](#))

Properties

Map ([NetAF.Commands.Region.Map.html](#))

Region ([NetAF.Commands.Region.Region.html](#))

Rooms ([NetAF.Commands.Region.Rooms.html](#))

ViewPoint ([NetAF.Commands.Region.ViewPoint.html](#))

World ([NetAF.Commands.Region.World.html](#))

Name	Description
roomPositions	The rooms to be represented.

Depth

Get the depth of the matrix.

Declaration

```
public int Depth { get; }
```

(NetAF.Assets.Attributes.html)

Property Value

+ **NetAF.Assets.Characters**

Type

(NetAF.Assets.Characters.htm

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

- **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

Height

Direction

(NetAF.Assets.Locations.Direction.

Get **the height of the matrix.**

(NetAF.Assets.Locations.Exit.html)

Declaration

Matrix

(NetAF.Assets.Locations.Matrix.htm

public int Height { get; }

Overworld

(NetAF.Assets.Locations.Overworld

Region

Property Value

(NetAF.Assets.Locations.Region.htm

Type

Room

(NetAF.Assets.Locations.Room.htm

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

RoomPosition

(NetAF.Assets.Locations.RoomPos

ViewPoint

this[int,int]

NetAF.Commands.

(NetAF.Commands.html)

Declaration

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversati

Parameters

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

Name

Description

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

x

The x position.

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.htm

y

The y position.

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

z

The z position.

Persistence

(NetAF.Commands.Persistence

+ **NetAF.Commands.Region**

Map

Room ([NetAF.Assets.Locations.Room.html](#))

(NetAF.Commands.RegionMap

Description

The room.

Width

Get the width of the matrix.

Declaration

```
public int Width { get; }
```

(NetAF.Assets.Attributes.html)

Property Value

+ **NetAF.Assets.Characters**

Type

(NetAF.Assets.Characters.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

- **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

Direction

Methods

Exit

(NetAF.Assets.Locations.Exit.html)

ToRooms()

(NetAF.Assets.Locations.Matrix.html)

Return this matrix as a one dimensional array of rooms.

Overworld

(NetAF.Assets.Locations.Overworld.html)

Region

(NetAF.Assets.Locations.Region.html)

public Room[] ToRooms()

Room

(NetAF.Assets.Locations.Room.html)

ReturnRoomPosition

(NetAF.Assets.Locations.RoomPosition.html)

Type

ViewPoint

Room[] (<https://learn.microsoft.com/dotnet/api/system.array>)

Description

The rooms, as a one dimensional array.

+ **NetAF.Commands**

(NetAF.Commands.html)

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversation.html)

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

Class Overworld

Represents an entire overworld.

Filter by title

Inheritance

+ NetAFAssets.Characters

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAFAssets.Characters.html\)](#)
↳ ExaminableObject ([NetAF.Assets.ExaminableObject.html](#))

- NetAF.Assets.Locations

Implements

(NetAF.Assets.Locations.html)

IExaminable ([NetAF.Assets.IExaminable.html](#))
Direction
IPlayerVisible ([NetAF.Assets.IPlayerVisible.html](#))
IPlayerVisible.DIRECTION
IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<ExaminableObject
Exit
I restoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Overworld
Matrix
I restoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Overworld
Overworld
I restoreFromObjectSerialization ([NetAF.Serialization.OverworldSerialization.html](#))>
Overworld

Inherited Members

↳ ExaminableObject.Overworld
ExaminableObject.Examination
Region
([NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examination](#))
↳ Region
ExaminableObject.Identifier ([NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Identifier](#))
Room
ExaminableObject.Description
Room
([NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Description](#))
RoomPosition
ExaminableObject.Commands
RoomPos
([NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Commands](#))
ViewPoint
ExaminableObject.Attributes
ViewPoin
([NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Attributes](#))

+ NetAFCommands.PlayerVisible

([NetAF.Commands.html](#))
↳ ExaminableObject.IsPlayerVisible

ExaminableObject.RestoreFrom(ExaminableSerialization)

+ NetAFCommands

([NetAF.Commands.Conversation.html](#))
↳ ExaminableObject.RestoreFrom(NetAF.Serialization_Assembly_Conversation_)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ NetAFCommands.Frame

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

([NetAF.Commands.Frame.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAFCommands

Persistence
Namespace: NetAF (NetAF.html).Assets (NetAF.Assets.html).Locations (NetAF.Assets.Locations.html)

Assembly: NetAF.dll

Syntax

+ NetAFCommands.Region

Map

(NetAF.Commands.RegionMap)

```
public sealed class Overworld : ExaminableObject, IExaminable, IPlayerVisible, IRestoreFromObjectSerialization<ExaminableSerialization>, IRotateFromObjectSerialization<OverworldSerialization>
```

▼ Constructors

+ NetAF.Assets.Characters

Overworld(Identifier, Description, CustomCommand[], ExaminationCallback)

NetAF.Assets.Locations

Initializes a new instance of the overworld class.

(NetAF.Assets.Locations.html)

Declaration
Direction

```
(NetAF.Assets.Direction.  
public Overworld(Identifier identifier, Description description, CustomCommand[] commands = null, ExaminationCallback examination = null)  
(NetAF.Assets.Direction.Exit.html)
```

Matrix

Parameters

(NetAF.Assets.Locations.Matrix.html)

Type	Name	Description
Overworld (NetAF.Assets.Locations.Overworld.html)	identifier	The identifier for this overworld.
Region (NetAF.Assets.Identifier.html)	description	A description of this overworld.
Room (NetAF.Assets.Locations.Region.html)	commands	This objects commands.
RoomPosition (NetAF.Assets.Locations.Room.html)	examination	The examination.

ViewPoint

(NetAF.Assets.Locations.ViewPoint.html)

Overworld(string, string, CustomCommand[], ExaminationCallback)

(NetAF.Commands.html)

Initializes a new instance of the overworld class.

+ NetAF.Commands.

Declaration

Conversation

(NetAF.Commands.Conversation.html)

```
(NetAF.Commands.Conversation.Identifier, string description, CustomCommand[] commands = null, ExaminationCallback examination = null)
```

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Parameters

+ NetAF.Commands.Global

Type

(NetAF.Commands.Global.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Commands.Persistence

(NetAF.Commands.Persistence.html)

CustomCommand (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

Properties

CurrentRegion

Get the current region.

Declaration

+ **NetAF.Assets.Characters**

```
public Region CurrentRegion { get; }
```

(NetAF.Assets.Characters.html)

- **NetAF.Assets.Locations**

Property value

(NetAF.Assets.Locations.html)

Type

Direction

Region (NetAF.Assets.Locations.Region.html)

Exit

(NetAF.Assets.Locations.Exit.html)

Matrix

(NetAF.Assets.Locations.Matrix.html)

Regions

Get the regions in this overworld.

(NetAF.Assets.Locations.Overworld.html)

Declaration

Region

(NetAF.Assets.Locations.Region.html)

```
public Region[] Regions { get; }
```

(NetAF.Assets.Locations.Room.html)

RoomPosition

Property value

(NetAF.Assets.Locations.RoomPos.html)

Type

viewPoint

Description

(NetAF.Assets.Locations.ViewPoint.html)

Region (NetAF.Assets.Locations.Region.html)[]

+ **NetAF.Commands**

(NetAF.Commands.html)

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversation.html)

+ **NetAF.Commands.Frame**

Add (NetAF.Commands.Frame.html)

- **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

```
public void AddRegion(Region region)
```

+ **NetAF.Commands.**

Persistence

Parameters

(NetAF.Commands.Persistence.html)

Type

+ **NetAF.Commands.Region**

Region (NetAF.Assets.Locations.Region.html)

Name

Description

region

The region to add.

(NetAF.Commands.RegionMap.html)

Examine(ExaminationScene)

Examine this object.

Declaration

```
public override ExaminationResult Examine(ExaminationScene scene)
```

+ NetAFAssets.Characters

Type	Name	Description
- ExaminationScene (NetAFAssets.ExaminationScene.html)	scene	The scene this object is being examined from.

Direction

Returns NetAFAssets.Locations.Direction.

Type	Description
Exit (NetAFAssets.Locations.Exit.html)	A ExaminationResult detailing the examination of this object.

Overworld

Overrides NetAFAssets.Locations.Overworld.

Region

ExaminableObject.Examine(ExaminationScene)

(NetAFAssets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_ExaminationScene_Room)

(NetAFAssets.Locations.Room.html)

RoomPosition

FindRegion(string, out Region)

ViewPoint

Find a region
(NetAFAssets.Locations.ViewPoint)

Declaration

+ NetAF.Commands

(NetAFCommands.html)

```
public bool FindRegion(string regionName, out Region region)
```

+ NetAF.Commands.

Conversation

Parameters

(NetAFCommands.Conversation.html)

Type

+ NetAF.Commands.Frame

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAFCommands.Frame.html)

Region (NetAFAssets.Locations.Region.html)

+ NetAF.Commands.Global

(NetAFCommands.Global.html)

Returns

+ NetAF.Commands.

Type

Persistence

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

(NetAFCommands.Persistence.html)

Name	Description
regionName	The regions name.
region	The region.

+ NetAFCommands.Region

Map

MOVE(Region)

(NetAFCommands.RegionMap.html)

Move to a region.

Declaration

```
public bool Move(Region region)
```

Parameters

Type	Name	Description
+ NetAF.Assets.Characters (NetAF.Assets.Characters.html)	region	The region to move to.

- NetAF.Assets.Locations

Returns

(NetAF.Assets.Locations.html)

Type	Description
bool (NetAF.Assets.Locations.Direction.html)	True if the region could be moved to, else false.

Direction
(NetAF.Assets.Locations.Direction.html)

Matrix

RemoveRegion(Region)

(NetAF.Assets.Locations.Matrix.html)

Overworld

Remove a region from this overworld.

(NetAF.Assets.Locations.Overworld.html)

Declaration

(NetAF.Assets.Locations.Region.html)

```
public void RemoveRegion(Region region)
```

(NetAF.Assets.Locations.Room.html)

RoomPosition

Parameters

(NetAF.Assets.Locations.RoomPos.html)

Type	Name	Description
ViewPoint (NetAF.Assets.Locations.ViewPoint.html)	region	The region to remove.

+ NetAF.Commands

(NetAF.Commands.html)

RestoreFrom(OverworldSerialization)

Conversation

Restore this object from a serialization.

(NetAF.Commands.Conversation.html)

Declaration

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

```
public void RestoreFrom(OverworldSerialization serialization)
```

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

Parameters

Type	Name	Description
Persistence OverworldSerialization (NetAF.Serialization.Assets.OverworldSerialization.html)	serialization	The serialization to restore from.

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

Implements

IExaminable (NetAF.Assets.IExaminable.html)

IPlayerVisible (NetAF.Assets.IPlayerVisible.html)

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

▼

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

- NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Direction

(NetAF.Assets.Locations.Direction.

Exit

(NetAF.Assets.Locations.Exit.html)

Matrix

(NetAF.Assets.Locations.Matrix.htm

Overworld

(NetAF.Assets.Locations.Overworl

Region

(NetAF.Assets.Locations.Region.h

Room

(NetAF.Assets.Locations.Room.htm

RoomPosition

(NetAF.Assets.Locations.RoomPos

ViewPoint

(NetAF.Assets.Locations.ViewPoin

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversation)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

Class Region

Represents a region.

Filter by title

Inheritance

↳ [Object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ [ExaminableObject](#) ([NetAF Assets.ExaminableObject.html](#))

- **NetAF Assets.Locations**

↳ [Region](#)

(NetAF Assets.Locations.html)

Implements

Direction

IExaminable ([NetAF Assets.IExaminable.html](#))

↳ [\(NetAF Assets.Locations.Direction.html\)](#)

IPlayerVisible ([NetAF Assets.IPlayerVisible.html](#))

↳ [Exit](#)

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Examinable

↳ [\(NetAF Assets.Locations.Exit.html\)](#)

Serialization ([NetAF.Serialization.Assets.ExaminableSerialization.html](#))>

Matrix

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Region

↳ [\(NetAF Assets.Locations.Matrix.html\)](#)

Serialization ([NetAF.Serialization.Assets.RegionSerialization.html](#))>

Overworld

Inher ([NetAF Assets.Locations.Overworld](#))

Region

ExaminableObject.Examination

↳ [\(NetAF Assets.Locations.Region.html\)](#)

([NetAF Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_Examination)

Room

ExaminableObject.Identifier

↳ [\(NetAF Assets.Locations.Room.html\)](#)

ExaminableObject.Description

RoomPosition

↳ [\(NetAF Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Description\)](#)

↳ [\(NetAF Assets.Locations.RoomPos.html\)](#)

ExaminableObject.Commands

ViewPoint

↳ [\(NetAF Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Commands\)](#)

↳ [\(NetAF Assets.Locations.ViewPoin.html\)](#)

ExaminableObject.Attributes

(NetAF Commands.ExaminableObject.html#NetAF_Assets_ExaminableObject_Attributes)

ExaminableObject.IsPlayerVisible

([NetAF Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_IsPlayerVisible)

+ **NetAF Commands**

Conversation

ExaminableObject.RestoreFrom([ExaminableSerialization](#))

([NetAF Assets.ExaminableObject.html](#)#NetAF_Assets_ExaminableObject_RestoreFrom_NetAF_Serialization_Asset)

set ([ExaminableSerialization](#))

(NetAF Commands.Conversation)

object.Equals(object) ()

+ **NetAF Commands.Frame**

object.Equals(object, object) ()

object.GetHashCode() ()

(NetAF Commands.Global)

object.GetType() ()

object.ReferenceEquals(object, object) ()

object.ToString() ()

Persistence

Namespace: NetAF ([NetAF.html](#)).Assets ([NetAF Assets.html](#)).Locations ([NetAF Assets.Locations.html](#))

Assembly: NetAF.dll

+ **NetAF Commands.Region**

Syntax

Map

(NetAF Commands.RegionMap)

+ **NetAF Commands.Scene**

```
public sealed class Region : ExaminableObject, IExaminable, IPlayerVisible, IRotateFromObjectSerialization<ExaminableSerialization>, IRotateFromObjectSerialization<RegionSerialization>
```

Constructors

[\(NetAF.Assets.Characters.htm\)](#)

Region(Identifier, Description, CustomCommand[], ExaminationCallback)
[\(NetAF.Assets.Locations.htm\)](#)

Initializes a new instance of the Region class.

Direction
 Declaration
[\(NetAF.Assets.Direction.htm\)](#)

```
Exit  

public Region(Identifier identifier, Description description, CustomCommand[] command  

  (NetAF.Assets.Locations.Exit.html)  

  ds = null, ExaminationCallback examination = null)  

Matrix  

  (NetAF.Assets.Locations.Matrix.htm)
```

Overworld

Type	Name	Description
Region	identifier	This Regions identifier.
Identifier (NetAF.Assets.Identifier.htm)	description	The description of this Region.
Room Description (NetAF.Assets.Description.html)	commands	This objects commands.
RoomPosition (NetAF.Commands.CustomCommand.html[]) (NetAF.Assets.Locations.RoomPosition.htm)	examination	The examination.
ViewPoint (NetAF.Assets.ExaminationCallback.html)		

[\(NetAF.Assets.Locations.ViewPoint.htm\)](#)

+ NetAF.Commands

Region(string, string, CustomCommand[], ExaminationCallback)
[\(NetAF.Commands.htm\)](#)

Initializes a new instance of the Region class.

+ NetAF.Commands

Conversation

Declaration
[\(NetAF.Commands.Conversation.htm\)](#)

Identifier
[Identifier \(https://learn.microsoft.com/dotnet/api/system.string\)](#)

+ NetAF.Commands.Frame

[\(https://learn.microsoft.com/dotnet/api/system.string\)](#), ExaminationCallback examination = null)

[\(NetAF.Commands.Frame.htm\)](#)

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	identifier	This Regions identifier.
Persistence (https://learn.microsoft.com/dotnet/api/system.string)	description	The description of this Region.
CustomCommand (NetAF.Commands.CustomCommand.html[])	commands	This objects commands.
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	examination	The examination.

[\(NetAF.Commands.RegionMap.htm\)](#)

+ NetAF.Commands.Scene

Properties

CurrentRoom

Get the current room.

Declaration

+ [NetAF.Assets.Characters.cs](#)

([NetAF.Assets.Characters.htm](#))

```
public Room CurrentRoom { get; }
```

- NetAF.Assets.Locations

([NetAF.Assets.Locations.html](#))

Type	Direction	Description
Room	Exit	(NetAF.Assets.Locations.Room.html)

([NetAF.Assets.Locations.Exit.html](#))

Matrix

([NetAF.Assets.Locations.Matrix.htm](#))

IsVisibleWithoutDiscovery

Overworld

([NetAF.Assets.Locations.Overworld.html](#))

Region

Declaration

([NetAF.Assets.Locations.Region.htm](#))

Room

[NetAF.Assets.Locations.Room.html](#)

RoomPosition

([NetAF.Assets.Locations.RoomPos.htm](#))

Property Value

ViewPoint

Type	NetAF.Assets.Locations.ViewPoint	Description
bool	(https://learn.microsoft.com/dotnet/api/system.boolean)	

([NetAF.Commands.html](#))

+ NetAF.Commands.

this[int, int, int]

Conversation

([NetAF.Commands.Conversation.html](#))

- NetAF.Commands.Frame

([NetAF.Commands.Frame.html](#))

```
public Room this[int x, int y, int z] { get; }
```

+ NetAF.Commands.Global

([NetAF.Commands.Global.html](#))

Parameters

+ NetAF.Commands.

Persistence

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	x	The x position.

int (https://learn.microsoft.com/dotnet/api/system.int32)	y	The y position.
---	---	-----------------

int (https://learn.microsoft.com/dotnet/api/system.int32)	z	The z position.
---	---	-----------------

([NetAF.Commands.RegionMap.html](#))

Property Value

+ NetAF.Commands.Scene

Type	Description
Room (NetAF.Assets.Locations.Room.html)	The room.

Rooms

Get the number of rooms region contains.

(NetAF.Assets.Characters.htm)

Declaration

- **NetAF.Assets.Locations**

(NetAF.Assets.Locations.html)

Direction

Property Value

Exit

Type

(NetAF.Assets.Locations.Exit.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

(NetAF.Assets.Locations.Matrix.htm)

Overworld

(NetAF.Assets.Locations.Overworld.html)

Region

Methods

(NetAF.Assets.Locations.Region.html)

Room

(NetAF.Assets.Locations.Room.html)

AddRoom(Room, int, int, int)

RoomPosition

Add a Room to this region.

ViewPoint

Declaration

(NetAF.Assets.Locations.ViewPoint.html)

+ **NetAF.Commands**

public bool AddRoom(Room room, int x, int y, int z)

(NetAF.Commands.html)

+ **NetAF.Commands.**

Parameters

Type	Name	Description
(NetAF.Commands.Conversation)		
Room (NetAF.Assets.Locations.Room.html)	room	The room to add.
+ NetAF.Commands.Frame	x	The x position within the region.
int (https://learn.microsoft.com/dotnet/api/system.int32) <p>(NetAF.Commands.Frame.html)</p> <td>y</td> <td>The y position within the region.</td>	y	The y position within the region.
int (https://learn.microsoft.com/dotnet/api/system.int32) <p>+ NetAF.Commands.Global</p> <td>z</td> <td>The z position within the region.</td>	z	The z position within the region.
int (https://learn.microsoft.com/dotnet/api/system.int32) <p>(NetAF.Commands.Global.html)</p>		

+ **NetAF.Commands.**

Returns

Persistence

Type

(NetAF.Commands.Persistence.html)

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

Examine(ExaminationScene)

+ **NetAF.Commands.Scene**

Description

Examine this object.

Declaration

```
public override ExaminationResult Examine(ExaminationScene scene)
```



Parameters

Type	Name	Description
(NetAF.Assets.Characters.htm)		
- ExaminationScene (NetAF.Assets.ExaminationScene.html) (NetAF.Assets.Locations.html)	scene	The scene this object is being examined from.

Returns

Type	Description
(NetAF.Assets.Locations.Direction.htm)	
Exit (NetAF.Assets.Locations.Exit.html)	
ExaminationResult Matrix (NetAF.Assets.ExaminationResult.html) (NetAF.Assets.Locations.Matrix.htm)	A ExaminationResult detailing the examination of this object.

Overworld

Overrides
(NetAF.Assets.Locations.Overworld)
ExaminableObject.Examine(ExaminationScene)
Region
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_ExaminationScene)
Room

(NetAF.Assets.Locations.Room.htm)

GetAdjoiningRoom(Direction)

(NetAF.Assets.Locations.RoomPos)

Get a **ViewPoint** room to the Region.CurrentRoom property.

(NetAF.Assets.Locations.ViewPoint)

Declaration

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

Parameters

Type	Name	Description
(NetAF.Commands.Conversation.html)	direction	The direction of the adjoining Room.

Returns

+ NetAF.Commands.Global

Type
(NetAF.Commands.Global.htm)

Room
(NetAF.Assets.Locations.Room.html)

Description

The adjoining Room.

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

GetAdjoiningRoom(Direction, Room)

+ NetAF.Commands.Region

Get a **Map** adjoining room to a room.

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

```
public Room GetAdjoiningRoom(Direction direction, Room room)
```

Parameters

Type	Name	Description
Direction (NetAF.Assets.Direction.html) ↳ NetAF.Assets.Direction.html	direction	The direction of the adjoining room.
Room (NetAF.Assets.Room.html) ↳ NetAF.Assets.Room.html	room	The room to use as the reference.

- NetAF.Assets.Locations

Returns
[\(NetAF.Assets.Locations.html\)](#)

Type	Description
Direction	
Room (NetAF.Assets.Room.html)	The adjoining room.
Exit	
(NetAF.Assets.Exit.html)	
Matrix	

GetPositionOfRoom(Room)

(NetAF.Assets.Matrix.html)
↳ [NetAF.Assets.Matrix.html](#)

Get the position of a room.

(NetAF.Assets.Locations.Overworld.html)

Declaration

```
public RoomPosition GetPositionOfRoom(Room room)
```

(NetAF.Assets.Room.html)

RoomPosition

Parameters
(NetAF.Assets.RoomPosition.html)

Type	Name	Description
ViewPoint		
(NetAF.Assets.ViewPoint.html)		
Room (NetAF.Assets.Room.html)	room	The room.

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

Type	Description
Conversation	The position of the room.

+ NetAF.Commands.Frame

[JumpToRoom\(Point3D\).html](#)

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

Declaration

+ NetAF.Commands.

public void JumpToRoom(Point3D location)

[\(NetAF.Commands.Persistence.html\)](#)

Parameters

+ NetAF.Commands.Region

Type	Name	Description
RegionMap	location	The location of the room.

+ NetAF.Commands.Scene

Returns

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the room could be jumped to, else false.

Move(Direction)

+ [NetAF.Assets.Characters](#)

([NetAF.Assets.Characters.html](#))

NetAF.Assets.Locations

([NetAF.Assets.Locations.html](#))

```
public bool Move(Direction direction)
    Direction
```

([NetAF.Assets.Locations.Direction.html](#))

Parameters

([NetAF.Assets.Locations.Exit.html](#))

Type Matrix

Direction ([NetAF.Assets.Locations.Matrix.html](#))

Name

Description

direction

The direction to move in.

Overworld

([NetAF.Assets.Locations.Overworld.html](#))

Returns Region

Type ([NetAF.Assets.Locations.Region.html](#))

Room

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

([NetAF.Assets.Locations.Room.html](#))

RoomPosition

([NetAF.Assets.Locations.RoomPosition.html](#))

Description

True if the move was successful, else false.

RestoreFrom(RegionSerialization)

([NetAF.Assets.ViewPoint.html](#))

Restore this object from a serialization.

+ NetAF.Commands

Declaration

([NetAF.Commands.html](#))

+ NetAF.Commands

RestoreFrom(RegionSerialization serialization)

Conversation

([NetAF.Commands.Conversation.html](#))

Parameters

Type ([NetAF.Commands.Frame.html](#))

([NetAF.Commands.Frame.html](#))

RegionSerialization

+ ([NetAF.Commands.Global.html](#))

([NetAF.Commands.Global.html](#))

Name

Description

serialization

The serialization to restore from.

+ NetAF.Commands.

SetStartRoom(Room)

Persistence

([NetAF.Commands.Persistence.html](#))

Set the room to start in.

NetAF.Commands.Region

Map

([NetAF.Commands.Region.Map.html](#))

+ NetAF.Commands.Scene

Parameters

Type	Name	Description
Room (NetAF.Assets.Locations.Room.html)	room	The Room to start in.

▼
SetStartRoom(int, int, int)
 ↗ [NetAF.Assets.Characters.cs](#)

(NetAF.Assets.Characters.htm)

Declaration:

NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

```
public void SetStartRoom(int x, int y, int z)
  Direction
```

(NetAF.Assets.Locations.Direction.

Parameters

Exit
 (NetAF.Assets.Locations.Exit.html)

Type	Name	Description
Matrix	x	The x position.
int (https://learn.microsoft.com/dotnet/api/system.int32)	y	The y position.
int (https://learn.microsoft.com/dotnet/api/system.int32)	z	The z position.

Room

(NetAF.Assets.Locations.Room.htm)

ToMatrix()

RoomPosition

(NetAF.Assets.Locations.RoomPos.htm)
 Get this region as a 3D matrix of rooms.

ViewPoint

(NetAF.Assets.Locations.ViewPoint.htm)

Declaration:

+ NetAF.Commands

public Matrix ToMatrix()

(NetAF.Commands.html)

+ NetAF.Commands.

Returns

Conversation

Type	Description
Matrix (NetAF.Assets.Locations.Matrix.html)	This region, as a 3D matrix.

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

TryFindRoom(string, out Room)

(NetAF.Commands.Global.htm)

Try and find a room within this region.

+ NetAF.Commands.

Declaration:

Persistence

(NetAF.Commands.Persistence.html)

```
public bool TryFindRoom(string name, out Room room)
```

+ NetAF.Commands.Region

Map

Parameters

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	name	The rooms name.
Room (NetAF.Assets.Locations.Room.html)	room	The room, if found, else null.

Returns

Type	Description
(NetAF.Assets.Characters.html)	bool (https://learn.microsoft.com/dotnet/api/system.boolean)

- NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

UnlockDoorPair(Direction)

(NetAF.Assets.Direction.html)

Unlock a pair of doors in a specified direction in the CurrentRoom.

Exit

Declaration

Matrix

```
public bool unlockDoorPair(Direction direction)
    Overworld
```

(NetAF.Assets.Locations.Overworld.html)

Parameters

Type	Name	Description
Room		
Direction (NetAF.Assets.Direction.html)	direction	The direction to unlock in.

RoomPosition

Returns

Type	Description
ViewPoint (NetAF.Assets.ViewPoint.html)	True if the door pair could be unlocked, else false.

+ NetAF.Commands

Conversation

IExaminable (NetAF.Assets.IExaminable.html)

(NetAF.Commands.Conversation.html)

IPlayerVisible (NetAF.Assets.IPlayerVisible.html)

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

+ NetAF.Commands.Frame

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

Class Room

Represents a room

Filter by title

Inheritance

([NetAF.Assets.Characters.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

- **NetAF.Assets.Locations**

↳ ExaminableObject ([NetAF.Assets.ExaminableObject.html](#))

([NetAF.Assets.Locations.html](#))

↳ Room

Direction

Implements

([NetAF.Assets.Direction.html](#))

IInteractWithItem ([NetAF.Assets.IInteractWithItem.html](#))

↳ Exit

IItemContainer ([NetAF.Assets.IItemContainer.html](#))

([NetAF.Assets.Locations.Exit.html](#))

IExaminable ([NetAF.Assets.IExaminable.html](#))

↳ Matrix

IPlayerVisible ([NetAF.Assets.IPlayerVisible.html](#))

([NetAF.Assets.Direction.html](#))

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))

<Examinable

Overworld

Serialization ([NetAF.Serialization.Assets.ExaminableSerialization.html](#))

([NetAF.Assets.Locations.Overworld.html](#))

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))

<RoomSerialization

Region

([NetAF.Serialization.Assets.RoomSerialization.html](#))

([NetAF.Assets.Locations.Region.html](#))

Inherited Members

([NetAF.Assets.Locations.Room.html](#))

ExaminableObject.Examination

RoomPosition

([NetAF.Assets.ExaminableObject.html](#))

([NetAF.Assets.Locations.RoomPosition.html](#))

ExaminableObject.Identifier ([NetAF.Assets.ExaminableObject.html](#))

ViewPoint

ExaminableObject.Description

([NetAF.Assets.Locations.ViewPoint.html](#))

([NetAF.Assets.ExaminableObject.html](#))

ExaminableObject.Commands

([NetAF.Commands.html](#))

([NetAF.Commands.ExaminableObject.html](#))

ExaminableObject.Attributes

([NetAF.Assets.ExaminableObject.html](#))

ExaminableObject.Conversation

IsPlayerVisible

([NetAF.Assets.ExaminableObject.html](#))

ExaminableObject.RestoreFrom(ExaminableSerialization)

([NetAF.Assets.ExaminableObject.html](#))

([NetAF.Commands.Frame.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Commands.Global**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object-system-object)))

+ **NetAF.Commands.Persistence**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Commands.Region**

NameSpace: NetAF ([NetAF.html](#)).Assets ([NetAF.Assets.html](#)).Locations ([NetAF.Assets.Locations.html](#))

Assemblies: NetAF

([NetAF.Commands.RegionMap.html](#))

Syntax

+ **NetAF.Commands.Scene**

([NetAF Commands Scene.html](#))

```
public sealed class Room : ExaminableObject, IInteractWithItem, IItemContainer, IExaminable, IPlayerVisible, IRestoreFromObjectSerialization<ExaminableSerialization>, IRestoreFromObjectSerialization<RoomSerialization>
```

▼ Constructors

([NetAF.Assets.Characters.html](#))

- **NetAF.Assets.Locations.Room(Identifier, Description, Exit[], Item[], CustomCommand[], InteractionCallback, ExaminationCallback)**

Direction

Initializes a new instance of the Room class.

Exit

Declaration
([NetAF.Assets.Locations.Exit.html](#))

Matrix

```
public Room(Identifier identifier, Description description, Exit[] exits = null, Item[] items = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null)
```

Region

Parameters
([NetAF.Assets.Locations.Region.html](#))

Type	Name	Description
Room (NetAF.Assets.Locations.Room.html)	identifier	This rooms identifier.
Identifier (NetAF.Assets.Identifier.html)	description	This rooms description.
Exit[] (NetAF.Assets.Locations.ViewPoint.html)	exits	The exits from this room.
+ NetAF Commands	items	The items in this room.
CustomCommand[] (NetAF.Commands.CustomCommand.html)	commands	This objects commands.
+ NetAF Commands	interaction	The interaction.
InteractionCallback (NetAF.Assets.InteractionCallback.html)	examination	The examination.
(NetAF.Commands.Conversation.html)		

+ NetAF.Commands.Frame

Room(string, string, Exit[], Item[], CustomCommand[], InteractionCallback, ExaminationCallback)

([NetAF.Commands.Global.html](#))

Initializes a new instance of the Room class.

+ NetAF Commands.

Persistence

([NetAF.Commands.Persistence.html](#))

Room(string identifier, string description, Exit[] exits = null, Item[] items = null, CustomCommand[] commands = null, InteractionCallback interaction = null, ExaminationCallback examination = null)

Map

([NetAF.Commands.RegionMap.html](#))

Parameters

+ NetAF.Commands.Scene

([NetAF.Commands.Scene.html](#))

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>identifier</i>	This rooms identifier.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i>	This rooms description.
Exit (NetAF.Assets.Locations.Exit.html)[]	<i>exits</i>	The exits from this room.
Item (NetAF.Assets.Item.html)[] ↳ NetAF.Assets.Characters.num	<i>items</i>	The items in this room.
CustomCommand (NetAF.Commands.CustomCommand.html)[]	<i>commands</i>	This objects commands.
- NetAF.Assets.Locations (NetAF.Assets.Locations.html)		
InteractionCallback (NetAF.Assets.InteractionCallback.html)	<i>interaction</i>	The interaction.
ExaminationCallback (NetAF.Assets.ExaminationCallback.html)	<i>examination</i>	The examination.

Properties

(NetAF.Assets.Locations.Matrix.html)

Overworld

Region

Get the characters in this Room Region.html

Room

Declaration
(NetAF.Assets.Locations.Room.html)

RoomPosition

public NonPlayableCharacter[] Characters { get; }

ViewPoint

Property Value
(NetAF.Assets.Locations.ViewPoint.html)

+ NetAF.Commands

(NetAF.Commands.html)

NonPlayableCharacter (NetAF.Assets.Characters.NonPlayableCharacter.html)[]

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversation.html)

EnteredFrom

+ NetAF.Commands.Frame

Get which direction this Room was entered from.

(NetAF.Commands.Frame.html)

Declaration

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

public NonPlayableCharacter[] Characters { get; }

+ NetAF.Commands.

Property Value

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

Exits

(NetAF.Commands.Scene.html)

(NetAF.Commands.Scene.html)

Description

Description

Get the exits.

Declaration

```
public Exit[] Exits { get; }
```



Property Value

Type	Description
- NetAF.Assets.Locations Exit (NetAF.Assets.Locations.Exit.html) (NetAF.Assets.Locations.html)	

Direction

(NetAF.Assets.Locations.Direction.
HasBeenVisited

Exit

Get if this location has been visited.
Matrix

Declaration

Overworld

```
public NetAF.Assets.Locations.Overworld { get; }
```

Region

(NetAF.Assets.Locations.Region.ht

Property Value
Room

Type	Description
NetAF.Assets.Locations.Room.htm	

ViewPoint

(NetAF.Assets.Locations.ViewPoin

Interaction

+ **NetAF.Commands**

(NetAF.Commands.html)

Get the interaction.

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.ConversationInteraction { get; }

+ **NetAF.Commands.Frame**

Property Value

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

InteractionCallback (NetAF.Commands.GlobalInteractionCallback.html)

+ **NetAF.Commands.**

Persistence

this[Direction]

(NetAF.Commands.Persistence)

Get an exit.

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap

public Exit this[Direction direction] { get; }

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

Parameters

Type	Name	Description
Direction (NetAF.Assets.Locations.Direction.html)	<i>direction</i>	The direction of an exit.

Property Value

Type <code>(NetAF.Assets.Characters.num - NetAF.Assets.Locations</code>	Description
Exit (NetAF.Assets.Locations.Exit.html) <code>(NetAF.Assets.Locations.html)</code>	The exit.

Items

Direction (NetAF.Assets.Locations.Direction.html)

Get the items.

(NetAF.Assets.Locations.Exit.html)

Declaration Matrix

(NetAF.Assets.Locations.Matrix.html)

`public Item[] Items { get; }`

`Overworld` (NetAF.Assets.Locations.Overworld.html)

Region (NetAF.Assets.Locations.Region.html)

Property Value

(NetAF.Assets.Locations.Room.html)

Type Room

(NetAF.Assets.Locations.Room.html)

Item (NetAF.Assets.Item.html)

RoomPosition

(NetAF.Assets.Locations.RoomPosition.html)

ViewPoint

UnlockedExits (NetAF.Assets.Locations.ViewPoint.html)

+ NetAF.Commands

GetUnlockedExits

(NetAF.Commands.html)

Declaration

+ NetAF.Commands.

Conversation (NetAF.Commands.Conversation.html)

(NetAF.Commands.Conversations.html)

Property Value

+ NetAF.Commands.Frame

Type (NetAF.Commands.Frame.html)

+ NetAF.Commands.Global (NetAF.Commands.Global.html)

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

Methods

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

AddCharacter(NonPlayableCharacter)

Map

AddNetAFCharacter(RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

```
public void AddCharacter(NonPlayableCharacter character)
```

Parameters

Type	Name	Description
NonPlayableCharacter (NetAF.Assets.Characters.html)	character	The character to add.

- NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

AddItem(Item)

(NetAF.Assets.Locations.Direction.html)
Add an item.
Exit

Declaration
Matrix

[\(NetAF.Assets.Locations.Matrix.html\)](#)
Overworld

(NetAF.Assets.Locations.Overworld.html)

Parameters

Type	Name	Description
Room (NetAF.Assets.Locations.Room.html)	item	The item to add.

RoomPosition

(NetAF.Assets.Locations.RoomPosition.html)

ViewPoint

(NetAF.Assets.Locations.ViewPoint.html)

Test if a move is possible.

+ NetAF.Commands

(NetAF.Commands.html)

+ NetAF.Commands.

public bool CanMove(Direction direction)
Conversation

(NetAF.Commands.Conversation.html)

Parameters

Type	Name	Description
Direction (NetAF.Assets.Locations.Direction.html)	direction	The direction to test.

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

Returns

Type	Description
Persistence bool (https://learn.microsoft.com/dotnet/api/system.boolean)	If a move in the specified direction is possible.

+ NetAF.Commands.Region

Map

ContainsCharacter(NonPlayableCharacter, bool)

(NetAF.Commands.RegionMap.html)

Get if this Room contains a character.

+ NetAF.Commands.Scene

Declaration

(NetAF.Commands.Scene.html)

```
public bool ContainsCharacter(NonPlayableCharacter character, bool includeInvisibleCharacters = false)
```

Parameters

Type	Name	Description
NonPlayableCharacter (NetAF.Assets.Characters.NonPlayableCharacter.html) (NetAF.Assets.Locations.html)	<i>character</i>	The character.
bool Direction (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Direction.Exit)	<i>includeInvisibleCharacters</i>	Specify if invisible characters should be included.

Return Value

Type	Description
Matrix (NetAF.Assets.Locations.Matrix.html)	Overworld

Region

(NetAF.Assets.Locations.Region.html)

Room

ContainsCharacter(string, bool)

(NetAF.Assets.Locations.Room.html)

RoomPosition

Get if this Room contains a character.

(NetAF.Assets.Locations.RoomPosition.html)

Declaration

ViewPoint

(NetAF.Assets.Locations.ViewPoint.html)

```
+ NetAF.Commands
  public bool ContainsCharacter(string characterName, bool includeInvisibleCharacters = false)
```

(NetAF.Commands.html)

NetAF.Commands.

Parameters

Type	Name	Description
Conversation (NetAF.Commands.Conversation.html)	<i>characterName</i>	The character name to check for.
Frame (https://learn.microsoft.com/dotnet/api/system.net.http.framesystem.html) (NetAF.Commands.Frame.html)	<i>includeInvisibleCharacters</i>	Specify if invisible characters should be included.

NetAF.Commands.

Persistence

Returns

Type	Description
RegionMap bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the item is in this room, else false.

(NetAF.Commands.RegionMap.html)

NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Get if this Room contains an exit.

Declaration

```
public bool ContainsExit(Direction direction, bool includeInvisibleExits = false)
```



Parameters

Type	Name	Description
- NetAF.Assets.Locations Direction (NetAF.Assets.Locations.Direction.html) (NetAF.Assets.Locations.html)	<i>direction</i>	The direction of the exit to check for.
bool Direction (https://learn.microsoft.com/dotnet/api/system.boolean) lean Exit	<i>includeInvisibleExits</i>	Specify if invisible exits should be included.

(NetAF.Assets.Locations.Exit.html)

Returns

Matrix

Type	Description
NetAF.Assets.Locations.Matrix.htm Overworld	
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the exit exists, else false.

Region

(NetAF.Assets.Locations.Region.html)

Room

ContainsExit(bool)

(NetAF.Assets.Locations.Room.html)

Get if this Room contains an exit.

RoomPosition

(NetAF.Assets.Locations.RoomPos

Declaration

ViewPoint

(NetAF.Assets.Locations.ViewPoin

```
public bool ContainsExit(bool includeInvisibleExits = false)
```

+ NetAF.Commands

(NetAF.Commands.html)

Parameters

Type	Name	Description
- NetAF.Commands. Conversation		
bool (NetAF.Commands.Conversati (https://learn.microsoft.com/dotnet/api/system.boolean) on	<i>includeInvisibleExits</i>	Specify if invisible exits should be included.

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Returns

+ NetAF.Commands.Global

Type

(NetAF.Commands.Global.html)

Description

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

True if the exit exists, else false.

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

ContainsInteractionTarget(string)

+ NetAF.Commands.Region

Get if this Room contains an interaction target.

Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF Commands Scene.html)

```
public bool ContainsInteractionTarget(string targetName)
```

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) + NetAF.Assets.Characters.num	targetName	The name of the target to check for.

Return Value

([NetAF.Assets.Locations.html](#))

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Locations.Direction.)	True if the target is in this room, else false.

Exit

([NetAF.Assets.Locations.Exit.html](#))

ContainsItem(Item)

([NetAF.Assets.Locations.Matrix.html](#))

Get if this Room contains an item. This will not include items whose ExaminableObject.IsPlayerVisible property is set to false.
+ NetAF.Assets.Locations.Overworld

Region

([NetAF.Assets.Locations.Region.html](#))

Room

public bool ContainsItem(Item item)
([NetAF.Assets.Locations.Room.html](#))

RoomPosition

([NetAF.Assets.Locations.RoomPosition.html](#))

ViewPoint

Type
([NetAF.Assets.Locations.ViewPoint.html](#))

Item
([NetAF.Assets.Item.html](#))

+ NetAF.Commands

([NetAF.Commands.html](#))

Returns

+ NetAF.Commands.

Type

Conversation

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

([NetAF.Commands.Conversation.html](#))

Name

Description

item

The item to check for.

+ NetAF.Commands.Frame

([NetAF.Commands.Frame.html](#))

ContainsItem(String, bool)

+ NetAF.Commands.Global

Get if this Room contains an item.

([NetAF.Commands.Global.html](#))

Declaration

+ NetAF.Commands.

Persistence

public bool ContainsItem(string itemName, bool includeInvisibleItems = false)

([NetAF.Commands.Persistence.html](#))

+ NetAF.Commands.Region

Map

([NetAF.Commands.RegionMap.html](#))

+ NetAF.Commands.Scene

([NetAF.Commands.Scene.html](#))

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	itemName	The item name to check for.
bool (https://learn.microsoft.com/dotnet/api/system.boolean) NetAF.Assets.Characters.Room	includeInvisibleItems	Specify if invisible items should be included.

- NetAF.Assets.Locations

Returns

(NetAF.Assets.Locations.html)

Type	Direction	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean) Exit	(NetAF.Assets.Locations.Direction) (NetAF.Assets.Locations.Exit.html)	True if the item is in this room, else false.

Examine(ExaminationScene)

Overworld

Handle examination this Room
(NetAF.Assets.Locations.Overworld)

Region

Declaration
(NetAF.Assets.Locations.Region.html)

Room

```
public override ExaminationResult Examine(ExaminationScene scene)
(NetAF.Assets.Locations.Room.html)
```

RoomPosition

Param
(NetAF.Assets.Locations.RoomPos)

Type	Name	Description
ViewPoint (NetAF.Assets.Locations.ViewPoint)	scene	The scene this object is being examined from.

+ NetAF.Commands

(NetAF.Commands.ExaminationScene.html)

(NetAF.Commands.html)

Returns

NetAF.Commands.

Type

Conversation	Description
(NetAF.Commands.Conversation)	The result of this examination.

+ NetAF.Commands.Frame

Overrides

(NetAF.Commands.Frame.html)

ExaminableObject.Examine(ExaminationScene)

+ NetAF.Commands.Global
(NetAF.Assets.ExaminableObject.html#NetAF_Assets_ExaminableObject_Examine_NetAF_Assets_ExaminationScene_)

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

FindCharacter(string, out NonPlayableCharacter)

(NetAF.Commands.Persistence)

Find a character. This will not include characters whose ExaminableObject.IsPlayerVisible property is set to false.

+ NetAF.Commands.Region

Declaration

Map

(NetAF.Commands.RegionMap)

```
public bool FindCharacter(string characterName, out NonPlayableCharacter character)
```

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>characterName</i>	The character.
NonPlayableCharacter (NetAF.Assets.Characters.NonPlayableCharacter.html)	<i>character</i>	The character name.

+ **NetAF.Assets.Characters.num**
Returns

Type	Description
- NetAF.Assets.Locations (NetAF.Assets.Locations.html)	

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

Direction

(NetAF.Assets.Locations.Direction.)

Exit

FindCharacter(string, out NonPlayableCharacter, bool)

Matrix

Find a character

(NetAF.Assets.Locations.Matrix.htm

Overworld

(NetAF.Assets.Locations.Overworld)

Region
public bool FindCharacter(string characterName, out NonPlayableCharacter character,
(NetAF.Assets.Locations.Region.htm
b601 includeInvisibleCharacters)

Room

(NetAF.Assets.Locations.Room.htm

Parameters

Rooms position

Type	Name	Description
ViewPoint		
string (NetAF.Assets.Locations.ViewPoin	<i>characterName</i>	The character name.
+ NetAF.Commands (NetAF.Commands.html)		
NonPlayableCharacter	<i>character</i>	The character.
+ NetAF.Commands (NetAF.Commands.NonPlayableCharacter.html)		
Conversation		
- NetAF.Commands.Conversation (NetAF.Commands.Conversation.html)		
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	<i>includeInvisibleCharacters</i>	Specify if invisible characters should be included.
+ NetAF.Commands.Frame (NetAF.Commands.Frame.html)		

+ **NetAF.Commands.Global**

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the character was found.

Persistence

(NetAF.Commands.Persistence)

FindExit(Direction, Region, out Exit)

Map

Find an exit.

(NetAF.Commands.RegionMap)

Declaration

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

```
public bool FindExit(Direction direction, bool includeInvisibleExits, out Exit exit)
```

Parameters

Type	Name	Description
Direction (NetAF.Assets.Locations.Direction.html) (NetAF.Assets.Characters.html)	direction	The exits direction.
bool - NetAF.Assets.Locations (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Locations.html)	includeInvisibleExits	Specify if invisible exists should be included.
Exit (NetAF.Assets.Locations.Exit.html) (NetAF.Assets.Locations.Direction. Exit.html)	exit	The exit.

Returns
(NetAF.Assets.Locations.Exit.html)

Type	Description
Matrix (NetAF.Assets.Locations.Matrix.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean) Overworld	True if the exit was found.

(NetAF.Assets.Locations.Overworld)

Region

FindInteractionTarget(string, out IInteractWithItem)

Room

FindInteractionTarget
(NetAF.Assets.Locations.Room.html)

RoomPosition

Declaration
(NetAF.Assets.Locations.RoomPosition.html)

ViewPoint

```
public bool FindInteractionTarget(string targetName, out IInteractWithItem target)
```

+ NetAF.Commands

Parameters

(NetAF.Commands.html)

Type	Name	Description
+ NetAF.Commands. Conversation string (https://learn.microsoft.com/dotnet/api/system.string)	targetName	The targets name.
IInteractWithItem ((NetAF.Commands.Conversation.IInteractWithItem.html))	target	The target.

+ NetAF.Commands.Frame

Returns
(NetAF.Commands.Frame.html)

Type

+ **NetAF.Commands.Global**

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the target was found.

+ NetAF.Commands.

Persistence

FindItem(string, out Item)

(NetAF.Commands.Persistence.FindItem.html)

Find an item. This will not include items whose ExaminableObject.IsPlayerVisible property is set to false

+ **NetAF.Commands.Region**

Declaration

(NetAF.Commands.RegionMap)

```
public bool FindItem(string itemName, out Item item)
```

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	itemName	The items name. This is case insensitive
Item (NetAF.Assets.Item.html)	item	The item

+ **NetAF.Assets.Characters.num**

Returns

Type	Description
- NetAF.Assets.Locations (NetAF.Assets.Locations.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean) Direction	True if the item was found

(NetAF.Assets.Locations.Direction.

Exit

FindItem(string, out Item, bool)

Matrix

Find an item

(NetAF.Assets.Locations.Matrix.html)

Overworld

(NetAF.Assets.Locations.Overworld.html)

Region
public bool FindItem(string itemName, out Item item, bool includeInvisibleItems)
(NetAF.Assets.Locations.Region.html)

Room

(NetAF.Assets.Locations.Room.html)

Type	Name	Description
RoomPosition (NetAF.Assets.Locations.RoomPosition.html)	itemName	The items name.
string newItemPoint (https://learn.microsoft.com/dotnet/api/system.string)	item	The item.
bool + NetAF.Commands. (https://learn.microsoft.com/dotnet/api/system.boolean) Conversation (NetAF.Commands.Conversation.html)	includeInvisibleItems	Specify is invisible items should be included.

+ **NetAF.Commands.Frame**

Type	Description
+ NetAFCommands.Global bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Commands.Global.html)	True if the item was found.

+ **NetAF.Commands.**

HasLockedExitInDirection(Direction, bool)

(NetAFCommands.Persistence.html)

Get if this room has a visible locked exit in a specified direction.

+ **NetAFCommands.Region**

Declaration

Map

(NetAFCommands.RegionMap.html)
public bool HasLockedExitInDirection(Direction direction, bool includeInvisibleExits
= false)

+ **NetAFCommands.Scene**

(NetAFCommands.Scene.html)

Parameters

Type	Name	Description
Direction (NetAF.Assets.Locations.Direction.html)	<i>direction</i>	The direction to check.
bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Characters.num	<i>includeInvisibleExits</i>	Specify if invisible exits should be included.

Returns

NetAF.Assets.Locations

Type	Description
Direction bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Direction. Exit (NetAF.Assets.Locations.Exit.html)	If there is a locked exit in the specified direction.

HasUnlockedExitInDirection(Direction, bool)

(NetAF.Assets.Locations.Matrix.htm

Get if this room has a visible unlocked exit in a specified direction.
Overworld

Declaration
Region

```
public bool HasUnlockedExitInDirection(Direction direction, bool includeInvisibleExits = false)
    Room
    RoomPosition
```

Parameters
RoomPosition

Type	Name	Description
ViewPoint (NetAF.Assets.Locations.ViewPoin		
Direction (NetAF.Assets.Locations.Direction.html)	<i>direction</i>	The direction to check.

+ NetAF.Commands

bool
(<https://learn.microsoft.com/dotnet/api/system.boolean>)
(NetAF.Commands.html)

+ NetAF.Commands.

Conversation

Return
(NetAF.Commands.Conversati

Type	Description
+ NetAF.Commands.Frame	
bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Commands.Frame.html)	If there is a unlocked exit in the specified direction.

(NetAF.Commands.Global.htm

NetAF.Commands. Interact(item)

Persistence

Interact with an item
(NetAF.Commands.Persistence

Declaration
+ NetAF.Commands.Region

Map

```
public Interaction Interact(Item item)
    RegionMap
```

+ NetAF.Commands.Scene

Parameters
(NetAF Commands Scene html

Type	Name	Description
Item (NetAF.Assets.Item.html)	<i>item</i>	The item to interact with.

Returns

Type	Description
Interaction (NetAF.Assets.Interaction.html)	The interaction.

- NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

MovedInto(Direction?)

Direction

Handles movement locations. Direction.

Exit

Declaration

(NetAF.Assets.Locations.Exit.html)

Matrix

public void MovedInto(Direction? fromDirection)

Overworld

(NetAF.Assets.Locations.Overworld)

Parameters

Region

Type	Name	Description
Room Direction (NetAF.Assets.Locations.Room.htm (NetAF.Assets.Locations.Direction.h tml) ? (NetAF.Assets.Locations.RoomPos ViewPoint	fromDirection	The direction movement into this Room is from. Use null if there is no direction.

(NetAF.Assets.Locations.ViewPoint)

+ NetAF.Commands

RemoveCharacter(NonPlayableCharacter)

(NetAF.Commands.html)

Remove a character from the room.

+ NetAF.Commands.

Declaration

Conversation

(NetAF.Commands.Conversation)

public void RemoveCharacter(NonPlayableCharacter character)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Parameters

+ NetAF.Commands.Global

Type

(NetAF.Commands.Global.html)

NonPlayableCharacter

(NetAF.Assets.Characters.NonPlayableCharacter.html)

Name

Description

character

The character to remove.

Persistence

(NetAF.Commands.Persistence)

RemoveInteractionTarget(IInteractWithItem)

(NetAF.Commands.Region)

Map

Remove an interaction target from the room.

(NetAF.Commands.RegionMap)

Declaration

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

```
public IInteractWithItem RemoveInteractionTarget(IInteractWithItem target)
```

Parameters

Type	Name	Description
IInteractWithItem (NetAF.Assets.IInteractWithItem.html) (NetAF.Assets.Characters.html)	target	The target to remove.

Return Value

(NetAF.Assets.Locations.html)

Type	Description
Direction IInteractWithItem (NetAF.Assets.IInteractWithItem.html) (NetAF.Assets.Direction.html)	The target removed from this room.

Exit

(NetAF.Assets.Locations.Exit.html)

RemoveItem(Item)

(NetAF.Assets.Locations.Matrix.html)

Remove an item.

Overloads

(NetAF.Assets.Locations.Overworld.html)

Declaration

Region

(NetAF.Assets.Locations.Region.html)

public void RemoveItem(Item item)

Room

(NetAF.Assets.Locations.Room.html)

Parameters

Type	Name	Description
ViewPoint	item	The item to remove.

+ NetAF.Commands

(NetAF.Commands.html)

RestoreFrom(RoomSerialization)

+ NetAF.Commands.

Restore this object from a serialization.

Conversation

(NetAF.Commands.Conversation.html)

+ NetAF.Commands.Frame

public void RestoreFrom(RoomSerialization serialization)

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

Parameters

(NetAF.Commands.Global.html)

Type

+ NetAF.Commands.

RoomSerialization

Persistence

(NetAF.Serialization.Assets.RoomSerialization.html)

(NetAF.Commands.Persistence.html)

Type	Name	Description
RoomSerialization	serialization	The serialization to restore from.

+ NetAF.Commands.Region

Map

SpecifyConditionalDescription(ConditionalDescription)

(NetAF.Commands.RegionMap.html)

Specify a conditional description of this room.

+ NetAF.Commands.Scene

Declaration

(NetAF.Commands.Scene.html)

```
public void SpecifyConditionalDescription(ConditionalDescription description)
```

Parameters

Type		Name	Description
ConditionalDescription (NetAF.Assets.ConditionalDescription.html) (NetAF.Assets.Characters.html)		description	The description of this room.

- NetAF.Assets.Locations

[\(NetAF.Assets.Locations.html\)](#)

Direction
(NetAF.Assets.Direction.html)
ItemContainer
(NetAF.Assets.ItemContainer.html)
IExaminable
(NetAF.Assets.IExaminable.html)
IPlayerVisible
(NetAF.Assets.Locations.PlayerVisible.html)
IRestoreFromObjectSerialization<T>
(NetAF.Assets.Locations.Matrix.html)
IRestoreFromObjectSerialization<T>
Overworld
(NetAF.Assets.Locations.Overworld.html)
Region
(NetAF.Assets.Locations.Region.html)
Room
(NetAF.Assets.Locations.Room.html)
RoomPosition
(NetAF.Assets.Locations.RoomPosition.html)
ViewPoint
(NetAF.Assets.Locations.ViewPoint.html)

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

+ NetAF.Commands.

[Conversation](#)

[\(NetAF.Commands.Conversation.html\)](#)

+ NetAF.Commands.Frame

[\(NetAF.Commands.Frame.html\)](#)

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

+ NetAF.Commands.

[Persistence](#)

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.Region

[Map](#)

[\(NetAF.Commands.RegionMap.html\)](#)

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Class RoomPosition

Represents a room position.

Filter by title

Inheritance

- **NetAF.Assets.Locations**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

([NetAF.Assets.Locations.html](#))

Direction

Inherited Members

([NetAF.Assets.Locations.Direction](#).)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

([NetAF.Assets.Locations.Exit.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object-object)))

([NetAF.Assets.Locations.Object.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF ([NetAF.html](#)).Assets ([NetAF.Assets.html](#)).Locations ([NetAF.Assets.Locations.html](#))

RoomPosition

Assembly: NetAF.dll

([NetAF.Assets.Locations.RoomPosition.html](#))

Syntax

ViewPoint

([NetAF.Assets.Locations.ViewPoint.html](#))

public class RoomPosition

+ **NetAF.Commands**

([NetAF.Commands.html](#))

Constructors

Conversation

([NetAF.Commands.Conversation.html](#))

RoomPosition(Room, Point3D)

+ **NetAF.Commands.Frame**

Represents a room position.

([NetAF.Commands.Frame.html](#))

Declaration

+ **NetAF.Commands.Global**

([NetAF.Commands.Global.html](#))

public RoomPosition(Room room, Point3D position)

+ **NetAF.Commands.**

Persistence

Parameters

([NetAF.Commands.Persistence.html](#))

Type

+ **NetAF.Commands.Region**

Room ([NetAF.Assets.Locations.Room.html](#))

Map

([NetAF.Commands.RegionMap.html](#))

Name

Description

room

The room/

position

The position of the room.

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

Properties

Position

Get the position of the room.

Declaration

- NetAF.Assets.Locations

public Point3D Position { get; }

(NetAF.Assets.Locations.html)

Direction

Property Value

NetAF.Assets.Locations.Direction.

Type	Description
Exit (NetAF.Assets.Locations.Exit.html)	
Point3D (NetAF.Assets.Point3D.html)	

(NetAF.Assets.Locations.Matrix.htm

Overworld

(NetAF.Assets.Locations.Overworld

Room

Region

Get the room.

Room

Declaration

(NetAF.Assets.Locations.Room.htm

RoomPosition

public Room Room { get; }

ViewPoint

(NetAF.Assets.Locations.ViewPoin

Property Value

+ NetAF.Commands

Type

(NetAF.Commands.html)

Room (NetAF.Assets.Locations.Room.html)

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversati

Methods

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

Get this Room's frame at a position.

+ NetAF.Commands.

Declaration

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Parameters

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Type	Name	Description
	position	The position.

Returns

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if this is at the position, else false.

IsAtPosition(int, int, int)

- NetAF.Assets.Locations

Get if this RoomPosition is at a position.
[\(NetAF.Assets.Locations.html\)](#)

Declaration
Direction

```
(NetAF.Assets.Direction.  
public bool IsAtPosition(int x, int y, int z)  
    Exit  
(NetAF.Assets.Direction.Exit.html)
```

Matrix

Parameters
(NetAF.Assets.Locations.Matrix.htm

Type	Name	Description
Overworld	x	The X position.
int (https://learn.microsoft.com/dotnet/api/system.int32)	y	The Y position.
Region	z	The Z position.

RoomPosition

Returns
(NetAF.Assets.Locations.RoomPos

Type	Description
ViewPoint	True if this is at the position, else false.

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)

+ NetAF.Commands.

[Conversation](#)

[\(NetAF.Commands.Conversation.html\)](#)

+ NetAF.Commands.Frame

[\(NetAF.Commands.Frame.html\)](#)

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

+ NetAF.Commands.

[Persistence](#)

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.Region

[Map](#)

[\(NetAF.Commands.RegionMap.html\)](#)

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Class ViewPoint

Represents a view point from a room.

Filter by title

Inheritance

([NetAFAssets.Locations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ [Direction](#)

([NetAFAssets.Direction.html](#))

Inherited Members

[Exit](#)

object ([System.Object.html](#)) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

matrix

object ([System.Object.Equals\(System.Object\).html](#)) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object ([System.Object.GetHashCode.html](#)) (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object ([System.Object.GetType.html](#)) (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object ([System.Object.ReferenceEquals\(System.Object\).html](#)) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object ([System.Object.ToString.html](#)) (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAFAssets.Locations.Room.html](#))

RoomPosition

Assembly: NetAF.dll

([NetAFAssets.Locations.RoomPosition.html](#))

Syntax

[ViewPoint](#)

([NetAFAssets.Locations.ViewPoint.html](#))

```
public sealed class ViewPoint
```

+ [NetAF.Commands](#)

([NetAF.Commands.html](#))

+ [NetAF.Commands.](#)

Properties

([NetAF.Commands.Conversation.html](#))

+ [NetAF.Commands.Frame](#)

([NetAF.Commands.Frame.html](#))

Get if there is a view in any direction.

+ [NetAF.Commands.Global](#)

Declaration

([NetAF.Commands.Global.html](#))

+ [NetAF.Commands.GlobalMap](#) { get; }

Persistence

([NetAFCommands.Persistence.html](#))

Property Value

+ [NetAF.Commands.Region](#)

Description

Map

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

([NetAF.Commands.RegionMap.html](#))

+ [NetAF.Commands.Scene](#)

([NetAFCommands.Scene.html](#))

+ [NetAF.Conversations](#)

Get if there is a view in any direction.

Declaration

```
public bool AnyNotVisited { get; }
```

Property Value

Type	Description
(NetAF.Assets.Locations.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.Direction. Exit (NetAF.Assets.Locations.Exit.html) AnyVisited Matrix (NetAF.Assets.Locations.Matrix.html) Get if there is a view in any direction. Overworld Declaration (NetAF.Assets.Locations.Overworld.html) Region (NetAF.Assets.Locations.Region.html) Room (NetAF.Assets.Locations.Room.html) Property Value RoomPosition	

Type	Description
(NetAF.Assets.Locations.RoomPosition.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Assets.ViewPoint.html)	

+ NetAF.Commands

[\(NetAF.Commands.html\)](#)
this[Direction]

+ NetAF.Commands.

Get the room that lies in a specified direction.
Conversation

Declaration

[\(NetAF.Commands.Conversation.html\)](#)

+ NetAF.Commands.Frame

public Room this[Direction direction] { get; }
[\(NetAF.Commands.Frame.html\)](#)

+ NetAF.Commands.Global

Parameters
[\(NetAF.Commands.Global.html\)](#)

Type
[\(NetAF.Commands.Global.html\)](#)
Direction ([\(NetAF.Assets.Direction.html\)](#))

+ NetAF.Commands.Persistence

Property Value

+ NetAF.Commands.Region

Map
Room ([\(NetAF.Assets.Room.html\)](#))
[\(NetAF.Commands.RegionMap.html\)](#)

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

Get a view point representing no view.

Declaration

```
public static ViewPoint NoView { get; }
```

Property Value

Type	Description
(NetAF.Assets.Locations.html)	

ViewPoint (NetAF.Assets.Locations.ViewPoint.html)

(NetAF.Assets.Direction.

Exit

(NetAF.Assets.Locations.Exit.html)

Matrix

(NetAF.Assets.Locations.Matrix.html)

Overworld

(NetAF.Assets.Locations.Overworld.html)

Region

Methods

Create(Region)

Region

Create (NetAF.Assets.Locations.Region.html)

Room

Declaration

(NetAF.Assets.Locations.Room.html)

RoomPosition

public static ViewPoint Create(Region region)

ViewPoint

(NetAF.Assets.Locations.ViewPoint.html)

Parameters

Type	Name	Description
(NetAF.Commands.html)	region	The region to create the view point from.

+ NetAF.Commands.

Conversation

Type	Description
(NetAF.Commands.Conversation.html)	The view point.

+ NetAF.Commands.Frame

ViewPoint (NetAF.Assets.Locations.ViewPoint.html)

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

Namespace NetAF.Commands

Classes

Filter by title

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Commands.Attributes.html)

+ NetAF.Commands.Characters

CustomCommand (NetAF.Commands.CustomCommand.html)

Provides a custom command.

+ NetAF.Commands.Locations

(NetAF.Commands.Locations.html)

Reaction (NetAF.Commands.Reaction.html)

- NetAF.Commands

Represents a reaction

(NetAF.Commands.html)

Interfaces

CommandHelp

(NetAF.Commands.CommandHelp)

CustomCommand

(NetAF.Commands.CustomCommand)

ICommand (NetAF.Commands.ICommand.html)

CustomCommandCallback

Represents a command

CustomCommand

Enums

Reaction

(NetAF.Commands.Reaction.html)

ReactionResult (NetAF.Commands.ReactionResult.html)

(NetAF.Commands.ReactionResult)

Enumeration of reaction results.

+ NetAF.Commands.

Delegates

(NetAF.Commands.Conversation)

+ NetAF.Commands.Frame

CustomCommandCallback (NetAF.Commands.CustomCommandCallback.html)

(NetAF.Commands.Frame.html)

Provides a callback for custom commands.

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

Class CommandHelp

Provides help for a command.

Filter by title

Inheritance

([NetAF.Assets.Attributes.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Assets.Characters**

([NetAF.Assets.Characters.html](#))

Implements

IEquatable (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)<CommandHelp

([NetAF.Commands.CommandHelp.html](#))>

([NetAF.Assets.Locations.html](#))

IEquatable (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)<string

([NetAF.Commands.String.html](#))>

([NetAF.Commands.html](#))

Inherited Members

CommandHelp
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Commands.CommandHelp.html](#))

CustomCommand
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Commands.CustomCommand.html](#))

CustomCommandCallback
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
([NetAF.Commands.CustomCommandCallback.html](#))

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

ICommand
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
([NetAF.Commands.ICommand.html](#))

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Reaction

Namespace: NetAF (NetAF.html) Commands (NetAF.Commands.html)

([NetAF.Commands.Reaction.html](#))

Assembly: NetAF.dll

ReactionResult

Syntax: `NetAF.Commands.ReactionResult`

+ **NetAF.Commands.**

public sealed class CommandHelp : IEquatable<CommandHelp>, IEquatable<string>

Conversation

([NetAF.Commands.Conversation.html](#))

+ **NetAF.Commands.Frame**

Frame

([NetAF.Commands.Frame.html](#))

+ **NetAF.Commands.Global**

CommandHelp(string, string, string)

([NetAF.Commands.Global.html](#))

Provides help for a command.

+ **NetAF.Commands.**

Declaration

Persistence

([NetAF.Commands.Persistence.html](#))

public CommandHelp(string command, string description, string shortcut = "")

+ **NetAF.Commands.Region**

Map

Parameters

([NetAF.Commands.RegionMap.html](#))

Type

+ **NetAF.Commands.Scene**

string (<https://learn.microsoft.com/dotnet/api/system.string>)

([NetAF.Commands.Scene.html](#))

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	command	The command.

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i>	The help.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>shortcut</i>	A shortcut for the command.

▼

Properties

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

Get the command.

(NetAF.Assets.Locations.html)

Declaration

- NetAF.Commands

(NetAFCommands.html) { get; }

CommandHelp

Property Value

CustomCommand

Type

NetAF.Commands.CustomCommand

Description

CustomCommandCallback

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Commands.CustomCommand)

ICommand

(NetAF.Commands.ICommand.html)

Description

(NetAF.Commands.Reaction.html)

Get the description of the command.

ReactionResult

Declaration

+ NetAF.Commands.

public string Description { get; }

Conversation

(NetAF.Commands.Conversation.html)

Property Value

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Description

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Shortcut

Persistence

Get the shortcut for the command.

(NetAF.Commands.Persistence.html)

Declaration

+ NetAF.Commands.Region

Map

public string Shortcut { get; }

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

Property Value

(NetAF.Commands.Scene.html)

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	

Methods

[\(NetAF.Assets.Attributes.html\)](#)

Equals(CommandHelp)

[\(NetAF.Assets.Characters.html\)](#)

Indicates whether the current object is equal to another object of the same type.

+ NetAF.Assets.Locations

Declaration

[\(NetAF.Assets.Locations.html\)](#)

- [NetAF.Commands](#)

[\(NetAF.Commands.html\)](#)

Parameters

CommandHelp

Type	Name	Description
(NetAF.Commands.CommandHelp) CustomCommand CommandHelp (NetAF.Commands.CommandHelp.html)	other	An object to compare with this object.

CustomCommandCallback

Return [\(NetAF.Commands.CustomCommand\)](#)

Type	Description
(NetAF.Commands.ICommand)	
bool Reaction	true (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool) if the (http://dotnetforbeginners.com/reactive-programming) is equal to the other parameter; otherwise,
rosReaction	false (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool). t/api/ (SystemCommands.ReactionResult ean)

+ NetAF.Commands.

[Conversation](#)

[\(NetAF.Commands.Conversation.html\)](#)

Equals(string)

+ NetAF.Commands.Frame

Indicates whether the current object is equal to another object of a different type.

[\(NetAF.Commands.Frame.html\)](#)

Declaration

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

public bool Equals(string other)

+ NetAF.Commands.

[Persistence](#)

Parameters

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.Region

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Map

[\(NetAF.Commands.RegionMap.html\)](#)

Returns

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	true (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool) if the current object is equal to the other parameter; otherwise, false (https://learn.microsoft.com/dotnet/csharp/language-reference/builtin-types/bool).

(NetAF.Assets.Attributes.html)

Implements

NetAF.Assets.Characters

IEquatable<T> (<https://learn.microsoft.com/dotnet/api/system.iequatable-1>)

IComparable<T> (<https://learn.microsoft.com/dotnet/api/system.icomparable-1>)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Extension Methods

- NetAF.Commands

CommandHelpExtensions.FormattedToDisplayShortcut(CommandHelp)

(NetAF.Extensions.CommandHelpExtensions.html#NetAF_Extensions_CommandHelpExtensions_FormattedToDi
CommandHelp

splayShortcut_NetAF_Commands_CommandHelp_)

(NetAF.Commands.CommandHelp

CommandHelpExtensions.FormattedToDisplayShortcutAndVariable(CommandHelp)

CustomCommand

(NetAF.Extensions.CommandHelpExtensions.html#NetAF_Extensions_CommandHelpExtensions_FormattedToDi
NetAF.Commands.CustomComma

splayShortcutAndVariable_NetAF_Commands_CommandHelp_)

CustomCommandCallback

(NetAF.Commands.CustomComma

ICommand

(NetAF.Commands.ICommand.htm

Reaction

(NetAF.Commands.Reaction.html)

ReactionResult

(NetAF.Commands.ReactionResult

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversati

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html

+ NetAF.Commands.Global

(NetAF.Commands.Global.htm

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html

Class CustomCommand

Provides a custom command.

Filter by title

Inheritance

+ [NetAF Assets.Characters](#) (https://learn.microsoft.com/dotnet/api/system.object)

([NetAF Assets.Characters.html](#))

↳ Load ([NetAF.Commands.Persistence.Load.html](#))

+ [NetAF Assets.Locations](#)

↳ Save ([NetAF.Commands.Persistence.Save.html](#))

([NetAF Assets.Locations.html](#))

Implements

+ [NetAF Commands](#) (https://learn.microsoft.com/dotnet/api/system.commands.icommand.html)

IPlayerVisible ([NetAF Assets.IPlayerVisible.html](#))

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<CustomCommand
CommandHelp>

Serialization ([NetAF.Serialization.CustomCommandSerialization.html](#))>

([NetAF.Commands.CommandHelp](#))

Inherited Members

CustomCommand

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object\)](#))
CustomCommandCallback

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-system-object\)](#))
ICommand

([NetAF.Commands.ICommand.html](#))

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))
Reaction

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))
([NetAF.Commands.Reaction.html](#))

object.MemberwiseClone() ([https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone](#))
ReactionResult

object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))
([NetAF.Commands.ReactionResult](#))

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))

+ [NetAF Commands](#) (https://learn.microsoft.com/dotnet/api/system.commands).Commands (NetAF.Commands.html)

Conversation

([NetAF.Commands.Conversation.html](#))

Syntax

+ [NetAF.Commands.Frame](#)

public class CustomCommand : ICommand, IPlayerVisible, IRestoreFromObjectSerialization
<CustomCommandSerialization>

+ [NetAF.Commands.Global](#)

([NetAF.Commands.Global.html](#))

Constructors

NetAF.Commands.

Persistence

([NetAF.Commands.Persistence.html](#))

CustomCommand(CommandHelp, bool, bool, CustomCommandCallback)

+ [NetAF.Commands.Region](#)

Provides a custom command.

Map

Declaration

([NetAF.Commands.RegionMap.html](#))

+ [NetAF Commands Scene](#)

public CustomCommand(CommandHelp help, bool isPlayerVisible, bool interpretIfNotPlay
<Scene> (CustomCommandCallback callback)

+ [NetAF Conversations](#)

Parameters

Type	Name	Description
CommandHelp (NetAF.Commands.CommandHelp.html)	<i>help</i>	The help for this command.
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	<i>isPlayerVisible</i>	If this is visible to the player.
+ NetAF.Assets.Characters bool (NetAF.Assets.Characters.html (https://learn.microsoft.com/dotnet/api/system.boolean))	<i>interpretIfNotPlayerVisible</i>	If this command can be interpreted when the IsPlayerVisible is false.
+ NetAF.Assets.Locations (NetAF.Assets.Locations.html (https://learn.microsoft.com/dotnet/api/system.boolean))	<i>callback</i>	The callback to invoke when this command is invoked.
- NetAF.Commands ICommand (NetAF.Commands.html (https://learn.microsoft.com/dotnet/api/system.boolean))		

CommandHelp

(NetAF.Commands.CommandHelp.html)

CustomCommand

(NetAF.Commands.CustomCommand.html)

CustomCommandCallback

(NetAF.Commands.CustomCommandCallback.html)

Arguments

ICommand

Get or set the arguments.

Reaction

Declaration

([NetAF.Commands.Reaction.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

ReactionResult

public string Arguments { get; set; }

+ **NetAF.Commands.**

Property Value

Conversation

Type
([NetAF.Commands.Conversation.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

Description

+ **NetAF.Commands.Frame**

([NetAF.Commands.Frame.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

+ **NetAF.Commands.Global**

Help

([NetAF.Commands.Global.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

Get the help for this command.

+ **NetAF.Commands.**

Persistence

([NetAF.Commands.Persistence.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

+ **NetAF.Commands.Region**

Map

Property Value

([NetAF.Commands.RegionMap.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

Type

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#)
(<https://learn.microsoft.com/dotnet/api/system.string>))

Description

+ **NetAF Conversations**

InterpretIfNotPlayerVisible

Get if this command can be interpreted when the IsPlayerVisible is false.

Declaration

```
public bool InterpretIfNotPlayerVisible { get; set; }
```

Property Value

+ NetAF.Assets.Characters

(NetAF.Assets.Characters.html)

Description

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

- NetAF.Commands

IsPlayerVisible

(NetAF.Commands.html)

Get if this is visible to the player.

Declaration
CustomCommand

(NetAF.Commands.CustomCommandCallback
CustomCommandCallback)

(NetAF.Commands.CustomCommand)

Property Value

Type (NetAF.Commands.ICommand.html)

Description

Reaction

bool (NetAF.Commands.Reaction.html)

ReactionResult

(NetAF.Commands.ReactionResult)

+ NetAF.Commands.

Methods

(NetAF.Commands.Conversation.html)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Invoke the command.

+ NetAF.Commands.Global

Declaration

(NetAF.Commands.Global.html)

+ NetAF.Commands.Persistence

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Name

Description

Map

Game (NetAF.Logic.Game.html)

game

The game to invoke the command on.

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF Conversations

Type	Description
Reaction (NetAF.Commands.Reaction.html)	The reaction.

RestoreFrom(CustomCommandSerialization)

Restore this object from a serialization.

+ NetAF.Assets.Characters

Declaration

(NetAF.Assets.Characters.html)

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Parameters

- NetAF.Commands

Type (NetAF.Commands.html)

Name

Description

CustomCommandSerialization

serialization

(NetAF.Commands.CustomCommandSerialization.html)

The serialization to restore

from.

Implements

ISystemCommandCallback
(NetAF.Commands.CustomCommandCallback.html)

ICommand (NetAF.Commands.ICommand.html)

IPlayable (NetAF.Assets.Playable.html)

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

(NetAF.Commands.Reaction.html)

ReactionResult

(NetAF.Commands.ReactionResult.html)

+ NetAF.Commands.

Conversation

(NetAF.Commands.Conversation.html)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF Conversations

Delegate CustomCommandCallback

Provides a callback for custom commands.

Filter by title

Namespace: NetAF (NetAF.html).Commands (NetAF.Commands.html)

+ **NetAF.Assets.Characters**

Assembly: NetAF.dll

(NetAF.Assets.Characters.htm)

Syntax

+ **NetAF.Assets.Locations**

(NetAF.Assets.Locations.htm)

 public delegate Reaction CustomCommandCallback(Game game, string[] arguments)

- **NetAF.Commands**

Parent: NetAF

(NetAF.Commands.html)

Type	Name	Description
CommandHelp (NetAF.Commands.CommandHelp Game (NetAF.Logic.Game.html) CustomCommand	game	The game to invoke the command on.
string (NetAF.Commands.CustomCommandCallback (https://github.com/NetAF/net/api/system.string) [] (NetAF.Commands.CustomCommand ICommand (NetAF.Commands.ICommand.htm Returns Reaction	arguments	The arguments to invoke the command with.

Type	Description
Reaction ReactionResult (NetAF.Commands.Reaction.html) (NetAF.Commands.ReactionResult	The reaction to the command.

+ **NetAF.Commands.**

Conversation

(NetAF.Commands.Conversation.htm)

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

Interface ICommand

Represents a command.

Filter by title

Namespace: NetAF (NetAF.html).Commands (NetAF.Commands.html)

(NetAF.Assets.Characters.html)

Assembly: NetAF.dll

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

public interface ICommand

- NetAF.Commands

(NetAF.Commands.html)

CommandHelp

(NetAF.Commands.CommandHelp.html)

CustomCommand

(NetAF.Commands.CustomCommand.html)

CustomCommandCallback

(NetAF.Commands.CustomCommandCallback.html)

Invoke(Game)

(NetAF.Commands.CustomCommand.Invoke.html)

Invoke the command.

(NetAF.Commands.ICommand.html)

Declaration

(NetAF.Commands.Reaction.html)

ReactionResult

(NetAF.Commands.ReactionResult.html)

+ NetAF.Commands.

Parameters

Type	Name	Description
(NetAF.Commands.Conversation.html)	<i>game</i>	The game to invoke the command on.

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Returns

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

Reaction ([NetAF.Commands.Reaction.html](#))

Description

The reaction.

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

Class Reaction

Represents a reaction.

Filter by title

Inheritance

+ **NetAFAssetsLocations**
([NetAFAssetsLocations.html](#))

Inherited Members

([NetAFCommands.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](#))
CommandHelp
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](#))
CustomCommand
object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))
object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))
object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))
object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))
Command

NameSpace: NetAF.Commands.Command (NetAF.Commands.html)

Reaction

Assembly: NetAF.dll
([NetAF.Commands.Reaction.html](#))

Syntax

ReactionResult
(NetAF.Commands.ReactionResult)
public sealed class Reaction

+ **NetAF.Commands.**

Conversation

([NetAFCommands.Conversation.html](#))

Constructors

+ **NetAF.Commands.Frame**

([NetAFCommands.Frame.html](#))
Reaction(ReactionResult, string)

+ **NetAF.Commands.Global**

Represents a reaction.
([NetAFCommands.Global.html](#))

Declaration

+ **NetAF.Commands.**

Persistence

public Reaction(ReactionResult result, string description)
([NetAFCommands.Persistence.html](#))

+ **NetAFCommands.Region**

Parameters

Map Type	Name	Description
NetAFCommands.RegionMap		
ReactionResult (NetAFCommands.ReactionResult.html)	result	The result.

+ **NetAFCommands.Scene**

string ([https://learn.microsoft.com/dotnet/api/system.string](#))
([NetAFCommands.Scene.html](#))

+ **NetAF.Conversations**

([NetAFConversations.html](#))

+ **NetAF.Conversations.**

Properties

Description

Get a description of the result.

Declaration

+ NetAF.Assets.Locations

```
public string Description { get; }
```

(NetAF.Assets.Locations.html)

NetAF.Commands

Property value

(NetAF.Commands.html)

Type

CommandHelp

string (<https://learn.microsoft.com/dotnet/api/system.string>)

CustomCommand

(NetAF.Commands.CustomCommand)

CustomCommandCallback

(NetAF.Commands.CustomCommandCallback)

Result

Get the command

(NetAF.Commands.ICommand.html)

Declaration

Reaction

(NetAF.Commands.Reaction.html)

```
public ReactionResult Result { get; }
```

(NetAF.Commands.ReactionResult)

Property value

+ NetAF.Commands.

Type

(NetAF.Commands.Conversation.html)

ReactionResult ([NetAF.Commands.ReactionResult.html](#))

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Description

Type	Description
CommandHelp string (https://learn.microsoft.com/dotnet/api/system.string)	

Type	Description
CustomCommand (NetAF.Commands.CustomCommand)	

Type	Description
CustomCommandCallback (NetAF.Commands.CustomCommandCallback)	

Type	Description
Get the command (NetAF.Commands.ICommand.html)	

Type	Description
Declaration Reaction (NetAF.Commands.Reaction.html)	

Type	Description
ReactionResult (NetAF.Commands.ReactionResult.html)	

Enum ReactionResult

Enumeration of reaction results.

 Filter by title

+ **NetAF.Assets.Locations**
([NetAF.Assets.Locations.html](#))

Assembly: NetAF.dll

Syntax
- **NetAF.Commands**

([NetAF.Commands.html](#))
public enum ReactionResult

CommandHelp
([NetAF.Commands.CommandHelp.html](#))
CustomCommand
([NetAF.Commands.CustomCommand.html](#))
CustomCommandCallback
([NetAF.Commands.CustomCommandCallback.html](#))

Fields

Name	Description
Command	
Error	An error occurred.
Reaction	
GameModeChanged	The game mode was changed.
Inform	The user should be informed.
Silent	The user should not be informed.

+ **NetAF.Commands.**

Conversation
([NetAF.Commands.Conversation.html](#))

+ **NetAF.Commands.Frame**

([NetAF.Commands.Frame.html](#))

+ **NetAF.Commands.Global**

([NetAF.Commands.Global.html](#))

+ **NetAF.Commands.**

Persistence
([NetAF.Commands.Persistence.html](#))

+ **NetAF.Commands.Region**

Map
([NetAF.Commands.RegionMap.html](#))

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

+ **NetAF.Conversations.**

Instructions

Namespace NetAF.Commands. Conversation

▼ Filter by title

Classes

(NetAF.Assets.Attributes.html)

+ NetAF.Assets.Characters

Next (NetAF.Commands.Conversation.Next.html)

(NetAF.Assets.Characters.html)

Represents the Next command.

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

Respond (NetAF.Commands.Conversation.Respond.html)

+ NetAF.Commands

Represents the Respond command.

(NetAF.Commands.html)

- NetAF.Commands.

Conversation

(NetAF.Commands.Conversation.html)

Next

(NetAF.Commands.Conversation.Next.html)

Respond

(NetAF.Commands.Conversation.Respond.html)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

Class Next

Represents the Next command.

Filter by title

Inheritance

([NetAF.Assets.Characters.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Assets.Locations**

([NetAF.Assets.Locations.html](#))

Implements

ICommand ([NetAF.Commands.ICommand.html](#))

+ **NetAF.Commands**

([NetAF.Commands.html](#))

Inheritance

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

Conversation

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals(system-object-system-object)))

Next

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

Respond

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Commands.Frame**

Assembly: NetAF

([NetAF.Commands.Frame.html](#))

Syntax

+ **NetAF.Commands.Global**

([NetAF.Commands.Global.html](#))

public sealed class Next : ICommand

+ **NetAF.Commands.**

Persistence

([NetAF.Commands.Persistence.html](#))

Methods

+ **NetAF.Commands.Region**

Map

([NetAF.Commands.RegionMap.html](#))

Invoke(Game)

+ **NetAF.Commands.Scene**

Invoke the command.

([NetAF.Commands.Scene.html](#))

Declaration

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

public Reaction Invoke(Game game)

+ **NetAF.Conversations.**

Instructions

([NetAF.Conversations.Instruct.html](#))

Type

Name

Description

+ **NetAF.Extensions**

Game ([NetAF.Logic.Game.html](#))

([NetAF.Extensions.html](#))

game

The game to invoke the command on.

Returns

+ **NetAF.Interpretation**

Type	Description
Reaction (NetAF.Commands.Reaction.html)	The reaction.

Implements

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Assets.Characters.htm

+ NetAF.Assets.Locations

(NetAF.Assets.Locations.html)

+ NetAF.Commands

(NetAF.Commands.html)

- NetAF.Commands.

Conversation

(NetAF.Commands.Conversati

Next

(NetAF.Commands.Conversation.N

Respond

(NetAF.Commands.Conversation.R

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

Class Respond

Represents the Respond command.

 Filter by title

Inheritance

+ [NetAF\(AssetsLocations\)](#)
[\(NetAF.Assets.Locations.html\)](#)

Implements

- [NetAF.Commands](#)

ICommand ([NetAF.Commands.Command.html](#))

Inherited Members

- [NetAF.Commands](#).

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](#))

([NetAF.Commands.Conversation](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](#))

([NetAF.Commands.Conversation](#))

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))

object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))

+ [NetAF.Commands.Frame](#)

Namespace: NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Conversation ([NetAF.Commands.Conversation.html](#))

Assembly: NetAF.dll

+ [NetAF.Commands.Global](#)

Syntax

([NetAF.Commands.Global.html](#))

+ [NetAF.Commands](#):

Persistence

([NetAF.Commands.Persistence](#))

Constructors

+ [NetAF.Commands.Region](#)

Map

([NetAF.Commands.RegionMap](#))

Respond([Response](#))

+ [NetAF.Commands.Scene](#)

Represents the Respond command.

([NetAF.Commands.Scene.html](#))

Declaration

+ [NetAF.Conversations](#)

([NetAF.Conversations.html](#))

+ [NetAF.Conversations](#).

Parameters

Instructions

Type ([NetAF.Conversations.Instruct](#))

Name

Description

+ [NetAF.Extensions](#)
([NetAF.Extensions.html](#))

response

The response.

([NetAF.Extensions.html](#))

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

Methods

Invoke(Game)

Invoke the command.

Declaration

+ **NetAF.Assets.Locations** (NetAF.Assets.Locations.html)

Part A: Commands

Type	Name	Description
- NetAF.Commands	game	The game to invoke the command on.

Conversation

Type	Description
Next (NetAF.Commands.Conversation.N)	
Reaction (NetAF.Commands.Reaction.html)	The reaction.
Respond (NetAF.Commands.Conversation.F)	

t_NetAF Commands.Frame

implements (NetAECommands Frame.htm)

|Command (NetAE Commands |Command.html)

+ NetAE Commands Global

(NetAE Commands Global.htm)

± NetAE Commands

Persistence

(NetAE Commands Persistence)

± NetAE Commands-Region

Map

(NetAECommands.RegionMap

+ NetAECommands.Scene

(NetAF.Commands.Scene

† NetAE Conversations

(NetAF.Conversations

+ NetAE Conversations.

Instructions

(NetAF.Conv)

± NetAE Extensions

(NetAF.Extensions

† NetAE Interpretation

Namespace NetAF.Commands.Frame

Classes

Filter by title

[CommandsOff \(NetAF.Commands.Frame.CommandsOff.html\)](#)

+ [NetAFAssets.Characters](#) Off command.

(NetAF.Assets.Locations.html)

[CommandsOn \(NetAF.Commands.Frame.CommandsOn.html\)](#)

(NetAF.Commands.Scripts) On command.

+ [NetAF.Commands.](#)

[KeyOff \(NetAF.Commands.Frame.KeyOff.html\)](#)

(NetAF.Commands.Conversations)

Represents the KeyOff command.

- [NetAF.Commands.Frame](#)

[KeyOn \(NetAF.Commands.Frame.KeyOn.html\)](#)

Represents the KeyOn command.

(NetAF.Commands.Frame.Comma

CommandsOn

(NetAF.Commands.Frame.Comma

KeyOff

(NetAF.Commands.Frame.KeyOff.I

KeyOn

(NetAF.Commands.Frame.KeyOn.I

+ [NetAF.Commands.Global](#)

(NetAF.Commands.Global.html)

+ [NetAF.Commands.](#)

Persistence

(NetAF.Commands.Persistence)

+ [NetAF.Commands.Region](#)

Map

(NetAF.Commands.RegionMap)

+ [NetAF.Commands.Scene](#)

(NetAF.Commands.Scene.html)

+ [NetAF.Conversations](#)

(NetAF.Conversations.html)

- [NetAF.Commands](#)

Class CommandsOff

Represents the CommandsOff command.

Filter by title

Inheritance

+ NetAF.Assets.Locations

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Assets.Locations.html\)](#)
↳ CommandsOff

+ NetAF.Commands

Implements
[\(NetAF.Commands.html\)](#)
ICommand ([NetAF.Commands.Command.html](#))

+ NetAF.Commands.

Conversation

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
[\(NetAF.Commands.Conversation.html\)](#)

- NetAF.Commands.Frame

equals(system-object-system-object)
[\(NetAF.Commands.Frame.html\)](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(Frame, Object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF.Commands.Frame.Comma

Namespace: NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Frame ([NetAF.Commands.Frame.html](#))

KeyOff

Assembly: NetAF.dll
(NetAF.Commands.Frame.KeyOff.I

Syntax

KeyOn

(NetAF.Commands.Frame.KeyOn.I

```
public sealed class CommandsOff : ICommand
```

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

+ NetAF.Commands.

Properties

[\(NetAF.Commands.Persistence.html\)](#)

NetAF.Commands.Region

Map

Get the command help

[\(NetAF.Commands.RegionMap.html\)](#)

Declaration

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

```
public static CommandHelp CommandHelp { get; }
```

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

Property Value

+ NetAF.Conversations.

Type

Description

Instructions

CommandHelp ([NetAF.Commands.CommandHelp.html](#))

[\(NetAF.Conversations.Instructions.html\)](#)

+ NetAF.Extensions

Methods

Invoke(Game)

Invoke the command.



Declaration

+ NetAF.Assets.Locations

public Reaction Invoke(Game game)
[\(NetAF.Assets.Locations.html\)](#)

+ NetAF.Commands

Parameters

[\(NetAF.Commands.html\)](#)

Type

+ NetAF.Commands.

Game [\(NetAF.Logic.Game.html\)](#)

Conversation
[\(NetAF.Commands.Conversation.html\)](#)

(NetAF.Commands.Conversation)

Returns

- NetAF.Commands.Frame

Type

[\(NetAF.Commands.Frame.html\)](#)

Reaction [\(NetAF.Commands.Reaction.html\)](#)

CommandsOff
[\(NetAF.Commands.Frame.CommandsOff.html\)](#)

(NetAF.Commands.Frame.CommandsOff)

CommandsOn
[\(NetAF.Commands.Frame.CommandsOn.html\)](#)

(NetAF.Commands.Frame.CommandsOn)

KeyOff
[\(NetAF.Commands.Frame.KeyOff.html\)](#)

KeyOn
[\(NetAF.Commands.Frame.KeyOn.html\)](#)

Implements

ICommand [\(NetAF.Commands.ICommand.html\)](#)

[\(NetAF.Commands.Frame.ICommand.html\)](#)

KeyOn
[\(NetAF.Commands.Frame.KeyOn.html\)](#)

(NetAF.Commands.Frame.KeyOn)

+ NetAF.Commands.Global

[\(NetAF.Commands.Global.html\)](#)

+ NetAF.Commands.

Persistence

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.Region

Map

[\(NetAF.Commands.RegionMap.html\)](#)

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

+ NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instructions.html\)](#)

+ NetAF.Extensions

Class CommandsOn

Represents the CommandsOn command.

 Filter by title

Inheritance

(NetAF.Assets.Locations.html)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands**

(NetAF.Commands.html)

ICommand (NetAF.Commands.ICommand.html)

+ **NetAF.Commands**

Inherited Members

Conversation

(NetAF.Commands.Conversation.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

- **NetAF.Commands.Frame**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

KeyOff

Namespace: NetAF (NetAF.html).Commands (NetAF.Commands.html).Frame (NetAF.Commands.Frame.html)

(NetAF.Commands.Frame.KeyOff.html)

Assembly: NetAF.dll

KeyOn

Syntax

NetAF.Commands.Frame.KeyOn.html

+ **NetAF.Commands.Global**

public sealed class CommandsOn : ICommand

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

Properties (NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

CommandHelp

(NetAF.Commands.RegionMap.html)

Get the command help.

+ **NetAF.Commands.Scene**

Declaration

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

CommandHelp CommandHelp { get; }

(NetAF.Conversations.html)

Property Value

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instruct.html)

CommandHelp (NetAF.Commands.CommandHelp.html)

Description

Type	Value	Description
Instructions		

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Methods

Invoke(Game)

Invoke the command.

Declaration

(NetAF.Assets.Locations.html)
public Reaction Invoke(Game game)

+ NetAF.Commands

(NetAF.Commands.html)
Parameters

Type	Name	Description
Conversation		
Game (NetAF.Logic.Game.html)	game	The game to invoke the command on.

ReSharper

(NetAF.Commands.Frame.html)
Type

CommandsOff
Reaction (NetAF.Commands.Reaction.html)
(NetAF.Commands.Frame.Comma

CommandsOn

(NetAF.Commands.Frame.Comma

KeyOff

ICommand (NetAF.Commands.ICommand.html)
KeyOn

(NetAF.Commands.Frame.KeyOn.I

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

Methods

Invoke(Game)

Invoke the command.

Declaration

```
public void Invoke(Game game);
```

+ NetAF.Commands.Invoke(Game game) (NetAF.Commands.html)

Parameters

NetAF.Commands.

Type	Name	Description
(NetAF.Commands.Conversation)	game	The game to invoke the command on.

- NetAF.Commands.Frame

Reimplemented from

NetAF.Commands.Frame.html

Type	Description
CommandsOff (NetAF.Commands.Frame.Comma Reaction)	The reaction.

KeyOn
(NetAF.Commands.Frame.KeyOn.I

KeyOff
(NetAF.Commands.Frame.KeyOff.I
KeyOn
ICommand)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations. Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

Class KeyOn

Represents the KeyOn command.

Filter by title

Inheritance

+ **NetAF.Commands**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ KeyOn

+ **NetAF.Commands.**

Implements

Conversation

ICommand ([NetAF.Commands.ICommand.html](#))

(**NetAF.Commands.Conversation**)

Inherited Members

- **NetAF.Commands.Frame**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

KeyOn

Namespace: NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Frame ([NetAF.Commands.Frame.html](#))

(**NetAF.Commands.Frame.KeyOn**)

Assembly: NetAF.dll

+ **NetAF.Commands.Global**

Syntax

(**NetAF.Commands.Global.htm**)

+ **NetAF.Commands.**

Persistence

(**NetAF.Commands.Persistence**)

+ **NetAF.Commands.Region**

Map

(**NetAF.Commands.RegionMap**)

CommandHelp

+ **NetAF.Commands.Scene**

GetAFCommandHelp

(**NetAF.Commands.Scene.html**)

Declaration

+ **NetAF.Conversations**

(**NetAF.Conversations.html**)

public static CommandHelp CommandHelp { get; }

+ **NetAF.Conversations.**

Instructions

Property Value

(**NetAF.Conversations.Instruct**)

Type

+ **NetAF.Extensions**

CommandHelp ([NetAF.Commands.CommandHelp.html](#))

(**NetAF.Extensions.html**)

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

Description

Methods

Invoke(Game)

Invoke the command.

Declaration
↓

+ NetAF.Commands

(NetAF.Commands.html) Game game)

+ NetAF.Commands.

Parameters

Conversation

Type	Name	Description
Game (NetAF.Commands.html)	game	The game to invoke the command on.

(NetAF.Commands.Frame.html)

Returns
CommandsOff

Type	Description
CommandsOn Reaction (NetAF.Commands.Reaction.html) (NetAF.Commands.Frame.Comma	The reaction.

KeyOff

(NetAF.Commands.Frame.KeyOff.I

KeyOn

(NetAF.Commands.Frame.KeyOn.I

ICommand (NetAF.Commands.ICommand.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Namespace NetAF.Commands.Global

Classes

Filter by title

NetAF Assets Locations

About ([NetAF.Commands.Global.About.html](#))

([NetAF Assets Locations.html](#))

Represents the About command.

+ NetAF.Commands

([NetAF.Commands.html](#))

End ([NetAF.Commands.Global.End.html](#))

+ NetAF.Commands

Represents the End command.

Conversation

([NetAF.Commands.Conversation.html](#))

Exit ([NetAF.Commands.Global.Exit.html](#))

+ NetAF.Commands.Frame

Represents the Exit command.

([NetAF.Commands.Frame.html](#))

NetAF Commands Global

Help ([NetAF.Commands.Global.Help.html](#))

([NetAF.Commands.Global.html](#))

Represents the Help command.

About

([NetAF.Commands.Global.About.html](#))

Map ([NetAF.Commands.Global.Map.html](#))

Represents the Map command.

Exit

([NetAF.Commands.Global.Exit.html](#))

New ([NetAF.Commands.Global.New.html](#))

Represents the New command.

([NetAF.Commands.Global.New.html](#))

Map

([NetAF.Commands.Global.Map.html](#))

New

([NetAF.Commands.Global.New.html](#))

+ NetAF.Commands.

Persistence

([NetAF.Commands.Persistence.html](#))

+ NetAF.Commands.Region

Map

([NetAF.Commands.RegionMap.html](#))

+ NetAF.Commands.Scene

([NetAF.Commands.Scene.html](#))

+ NetAF.Conversations

([NetAF.Conversations.html](#))

+ NetAF.Conversations.

Class About

Represents the About command.

Filter by title

Inheritance ([NetAF.Assets.Locations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands**

↳ About

([NetAF.Commands.html](#))

Implements

ICommand ([NetAF.Commands.ICommand.html](#))

Conversation

Inherited Members

- ([NetAF.Commands.Conversation.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Commands.Frame**

([NetAF.Commands.Frame.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

- **NetAF.Commands.Global**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

([NetAF.Commands.Global.html](#))

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

End

Namespace: NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Global ([NetAF.Commands.Global.html](#))

Assembly: NetAF.dll

Exit

Syntax

([NetAF.Commands.Global.Exit.html](#))

Help

public sealed class About : ICommand

([NetAF.Commands.Global.Help.html](#))

Map

([NetAF.Commands.Global.Map.html](#))

New

([NetAF.Commands.Global.New.html](#))

Properties

+ **NetAF.Commands.**

Persistence

CommandHelp

([NetAF.Commands.Persistence.html](#))

Get the command help

+ **NetAF.Commands.Region**

Map

([NetAF.Commands.RegionMap.html](#))

 public static CommandHelp CommandHelp { get; }

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

Property Value

+ **NetAF.Conversations**

Type

([NetAF.Conversations.html](#))

 CommandHelp ([NetAF.Commands.CommandHelp.html](#))

+ **NetAF.Conversations.**

Instructions

([NetAF.Conversations.Instruct.html](#))

Description

Methods

Invoke(Game)

Invoke the command.

Declaration
↓
(NetAF.Assets.Locations.html)

+ **NetAF.Commands**

(NetAF.Commands.html)

Parameters

+ **NetAF.Commands.**

Type	Name	Description
Conversation (NetAF.Commands.Conversation.html)	game	The game to invoke the command on.

+ **NetAF.Commands.Frame**

Returns
(NetAF.Commands.Frame.html)

Type	Description
NetAF.Commands.Global (NetAF.Commands.Global.html)	The reaction.

About

(NetAF.Commands.Global.About.html)

Implements

ICommand ([NetAF.Commands.ICommand.html](#))

Exit

(NetAF.Commands.Global.Exit.html)

Help

(NetAF.Commands.Global.Help.html)

Map

(NetAF.Commands.Global.Map.html)

New

(NetAF.Commands.Global.New.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instructions.html)

Class End

Represents the End command.

 Filter by title

Inheritance

+ **NetAF.Commands**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Commands.html\)](#)
↳ End

+ **NetAF.Commands.**

↳ **Conversation** ([ICommand.html](#))
[\(NetAFCommands.Conversation.html\)](#)

Inherited Members

+ **NetAF.Commands.Frame**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))
[\(NetAF.Commands.Frame.html\)](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-system-object)))
[\(NetAFCommands.Global.html\)](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

[\(NetAFCommands.Global.End.html\)](#)

Namespace

NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Global ([NetAF.Commands.Global.html](#))

Exit

Assembly

NetAF.dll

[\(NetAF.Commands.Global.Exit.html\)](#)

Syntax

Help

[\(NetAF.Commands.Global.Help.html\)](#)

public sealed class End : ICommand

Map

[\(NetAF.Commands.Global.Map.html\)](#)

New

[\(NetAF.Commands.Global.New.html\)](#)

Properties

Commands

Persistence

[\(NetAFCommands.Persistence.html\)](#)

CommandHelp

+ **NetAF.Commands.Region**

Get the command help.

Map

[\(NetAFCommands.RegionMap.html\)](#)

+ **NetAF.Commands.Scene**

public static CommandHelp CommandHelp { get; }

[\(NetAF.Commands.Scene.html\)](#)

+ **NetAF.Conversations**

Property value

[\(NetAFConversations.html\)](#)

Type

Description

+ **NetAF.Conversations.**

CommandHelp ([NetAFCommands.CommandHelp.html](#))

Instructions

[\(NetAFConversations.Instruct.html\)](#)

Methods

Invoke(Game)

Invoke the command.

Declaration

+ NetAF.Commands

public Reaction Invoke(Game game)
(NetAF.Commands.html)

+ NetAF.Commands.

Parameters

Conversation

Type	Name	Description
Game (NetAF.Logic.Game.html)	game	The game to invoke the command on.

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)
Returns

- NetAF.Commands.Global

Type
(NetAF.Commands.Global.html)

Reaction (NetAF.Commands.Reaction.html)
About

(NetAF.Commands.Global.About.html)

End

(NetAF.Commands.Global.End.html)

Exit

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Commands.Global.Exit.html)

Help

(NetAF.Commands.Global.Help.html)

Map

(NetAF.Commands.Global.Map.html)

New

(NetAF.Commands.Global.New.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct.html)

Class Exit

Represents the Exit command.

 Filter by title

Inheritance

(NetAFCommands.html)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.**

Implementation

ICloneable (<https://learn.microsoft.com/dotnet/api/system.icloneable>)

Inherited Members

+ **NetAF.Commands.Frame**

object (<https://learn.microsoft.com/dotnet/api/system.object>) [object.Equals\(system-object, system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

- **NetAF.Commands.Global**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object, system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object)))

object GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Exit: NetAF (NetAF.html).Commands (NetAF.Commands.html).Global (NetAF.Commands.Global.html)

(NetAF.Commands.Global.Exit.htm)

Assembly: NetAF.dll

Help

Syntax

(NetAF.Commands.Global.Help.htm)

Map

public sealed class Exit : Command

(NetAF.Commands.Global.Map.htm)

New

(NetAF.Commands.Global.New.htm)

+ **NetAF.Commands.**

Properties

(NetAF.Commands.Persistence)

CommandHelp

Commands.Region

Map

Get the command help.

(NetAF.Commands.RegionMap)

Declaration

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

public static CommandHelp CommandHelp { get; }

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Description

Instructions

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Conversations.Instruct)

+ **NetAF.Extensions**

Methods

Invoke(Game)

Invoke the command.

Declaration
↓
`(NetAF.Commands.html)
public Reaction Invoke(Game game)`

+ NetAF.Commands.

Conversation

Parameters

Type	Name	Description
Game (NetAF.Logic.Game.html) (NetAF.Commands.Frame.html)	game	The game to invoke the command on.

Re

NetAF.Commands.Global

Type	Description
About Reaction (NetAF.Commands.Reaction.html) (NetAF.Commands.Global.About.html)	The reaction.

End

(NetAF.Commands.Global.End.html)

Implements

Exit	(NetAF.Commands.Global.Exit.html)
ICommand	(NetAF.Commands.Command.html)
Help	(NetAF.Commands.Global.Help.html)
Map	(NetAF.Commands.Global.Map.html)
New	(NetAF.Commands.Global.New.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct.html)

+ NetAF.Extensions

Methods

Invoke(Game)

Invoke the command.

Declaration
`(NetAF.Commands..html)`

+ **NetAF.Commands.Invoke**(Game game)

Conversation

(NetAF.Commands.Conversation)

Parameters

+ **NetAF.Commands.Frame**

(NetAF.Commands.Frame.html)

Game (NetAF.Logic.Game.html)

Name

Description

game

The game to invoke the command on.

- **NetAF.Commands.Global**

Returns

(NetAF.Commands.Global.html)

Type

About

(NetAF.Commands.Global.About.html)

Reaction (NetAF.Commands.Reaction.html)

End

(NetAF.Commands.Global.End.html)

Exit

(NetAF.Commands.Global.Exit.html)

Help

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Commands.Global.Help.html)

Map

(NetAF.Commands.Global.Map.html)

New

(NetAF.Commands.Global.New.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instruct)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Class Map

Represents the Map command.

 Filter by title

Inheritance

+ **NetAF.Commands.**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ Map

(**NetAF.Commands.Conversation**)

Implements

+ **NetAFCommands.Frame**

ICommand (NetAF.Commands.ICommand.html)

(**NetAFCommands.Frame.html**)

Inherited Members

- **NetAFCommands.Global**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

(**NetAFCommands.Global.html**)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(**NetAFCommands.Global.html**)

Help: NetAF (NetAF.html).Commands (NetAF.Commands.html).Global (NetAF.Commands.Global.html)

Assembly: NetAF.dll

Map

Syntax

(**NetAF.Commands.Global.Map.html**)

New

public sealed class Map : ICommand

(**NetAF.Commands.Global.New.html**)

+ **NetAF.Commands.**

Persistence

(**NetAF.Commands.Persistence.html**)

Properties

+ **NetAF.Commands.Region**

Map

CommandHelp

(**NetAF.Commands.RegionMap.html**)

Get the command help

+ **NetAF.Commands.Scene**

(**NetAF.Commands.Scene.html**)

Declaration

+ **NetAF.Conversations**

public static CommandHelp CommandHelp { get; }

(**NetAF.Conversations.html**)

+ **NetAF.Conversations.**

Property Value

Instructions

Type

(**NetAF.Conversations.Instruct.html**)

Description

CommandHelp (NetAF.Commands.CommandHelp.html)

+ **NetAF.Extensions**

(**NetAF.Extensions.html**)

Methods

Invoke(Game)

Invoke the command.

Declaration

+ NetAF.Commands.

 Conversation
 (NetAF.Commands.Conversati

Parameters

+ NetAF.Commands.Frame

Type	Name	Description
Game (NetAF.Logic.Game.html)	game	The game to invoke the command on.

- NetAF.Commands.Global

 (NetAF.Commands.Global.htm

Returns

 About

Type	Description
End Reaction (NetAF.Commands.Reaction.html) (NetAF.Commands.Global.End.htm	The reaction.

 Exit

 (NetAF.Commands.Global.Exit.htm

 Help

 (NetAF.Commands.Global.Help.htm

 ICommand (NetAF.Commands:ICommand.html)

 Map

 (NetAF.Commands.Global.Map.htm

 New

 (NetAF.Commands.Global.New.htm

+ NetAF.Commands.

 Persistence
 (NetAF.Commands.Persistence

+ NetAF.Commands.Region

 Map
 (NetAF.Commands.RegionMap

+ NetAF.Commands.Scene

 (NetAF.Commands.Scene.html

+ NetAF.Conversations

 (NetAF.Conversations.html)

+ NetAF.Conversations.

 Instructions
 (NetAF.Conversations.Instruct

+ NetAF.Extensions

 (NetAF.Extensions.html)

Class New

Represents the New command.

Filter by title

Inheritance

Conversation

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
(NetAF.Commands.Conversation)
 ↳ New

+ NetAF.Commands.Frame

Implements
(NetAF.Commands.Frame.html)
IClaim (<https://learn.microsoft.com/dotnet/api/claim>)

Inherited Members

NetAF.Commands.Global

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF.Commands.Global.Help.html)

Namespace: NetAF (<https://learn.microsoft.com/NetAF.html>).Global (<NetAF.Commands.Global.html>)

Assembly: NetAF.dll

(NetAF.Commands.Global.Map.html)

Syntax

New

(NetAF.Commands.Global.New.html)
public sealed class New : ICommand

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

Properties

Commands.Region

Map

(NetAF.Commands.RegionMap.html)

CommandHelp

+ NetAF.Commands.Scene

Get the command help.

(NetAF.Commands.Scene.html)

Declaration

+ NetAF.Conversations

(NetAF.Conversations.html)

public static CommandHelp CommandHelp { get; }

+ NetAF.Conversations.

Instructions

Property Value

(NetAF.Conversations.Instruct.html)

Type

+ NetAF.Extensions

CommandHelp (<NetAF.Commands.CommandHelp.html>)

(NetAF.Extensions.html)

+ NetAF.Interpretation

Description

Methods

Invoke(Game)

Invoke the command.

Declaration

Conversation

public Reaction Invoke(Game game)

(NetAF.Commands.Conversation.html)

+ NetAF.Commands.Frame

Parameters

(NetAF.Commands.Frame.html)

Type

- NetAF.Commands.Global

Game (NetAF.Logic.Game.html)

(NetAF.Commands.Global.html)

Name

Description

game

The game to invoke the command on.

About

Returns

(NetAF.Commands.Global.About.html)

Type

End

(NetAF.Commands.Global.End.html)

Reaction (NetAF.Commands.Reaction.html)

Exit

(NetAF.Commands.Global.Exit.html)

Help

(NetAF.Commands.Global.Help.html)

Map

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Commands.Global.Map.html)

New

(NetAF.Commands.Global.New.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

Namespace NetAF.Commands.Persistence

Classes

Filter by title

[Load \(NetAF.Commands.Persistence.Load.html\)](#)

+ [NetAF.Commands](#)

Represents the Load command.
[\(NetAF.Commands.html\)](#)

[Save \(NetAF.Commands.Persistence.Save.html\)](#)

+ [Conversation](#)

Represents the Save command.
[\(NetAF.Commands.Conversation.html\)](#)

[+ NetAF.Commands.Frame](#)

[\(NetAF.Commands.Frame.html\)](#)

[+ NetAF.Commands.Global](#)

[\(NetAF.Commands.Global.html\)](#)

[- NetAF.Commands.](#)

[Persistence](#)

[\(NetAF.Commands.Persistence.html\)](#)

Load

[\(NetAF.Commands.Persistence.Load.html\)](#)

Save

[\(NetAF.Commands.Persistence.Save.html\)](#)

[+ NetAF.Commands.Region](#)

[Map](#)

[\(NetAF.Commands.RegionMap.html\)](#)

[+ NetAF.Commands.Scene](#)

[\(NetAF.Commands.Scene.html\)](#)

[+ NetAF.Conversations](#)

[\(NetAF.Conversations.html\)](#)

[+ NetAF.Conversations.](#)

[Instructions](#)

[\(NetAF.Conversations.Instructions.html\)](#)

[+ NetAF.Extensions](#)

[\(NetAF.Extensions.html\)](#)

[+ NetAF.Interpretation](#)

Class Load

Represents the Load command.

Filter by title

Inheritance

([NetAF.Commands.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands**.

↳ CustomCommand ([NetAF.Commands.CustomCommand.html](#))

Conversation

↳ Load

([NetAF.Commands.Conversation.html](#))

Implements

+ **NetAF.Commands.Frame**

↳ Command ([NetAF.Commands.Command.html](#))

+ **NetAF.Commands.PlayerVisible**

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<CustomCommand

+ **NetAF.Commands.Global**

Serialization ([NetAF.Serialization.CustomCommandSerialization.html](#))>

([NetAF.Commands.Global.html](#))

Inherited Members

- **NetAF.Commands**

CustomCommand.Arguments

Persistence

([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_Arguments)

CustomCommand.Help ([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_Help)

CustomCommand.InterpretIfNotPlayerVisible

Load

([NetAF.Commands.Persistence.Load.html](#)#NetAF_Commands_CustomCommand_InterpretIfNotPlayerVisible)

CustomCommand.Invoke(Game)

Save ([NetAF.Commands.Persistence.Save.html](#)#NetAF_Commands_CustomCommand_Invoke_NetAF_Logic_Game_

)

+ **NetAF.Commands.Region**

CustomCommand.ISLayerVisible

Map ([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_IsPlayerVisible)

CustomCommand.MapCommandSerialization

([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_RestoreFrom_NetAF_Serializ

ation_CustomCommandSerialization_)

object.Equals(object) ([<https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)>](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

object.Equals(object, object) ([<https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)>](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Conversations.html](#))

equals(System.Object) ([<https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)>](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

object.GetHashCode() ([<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>](https://learn.microsoft.com/dotnet/api/system.object.gethashcode))

object.GetType() ([<https://learn.microsoft.com/dotnet/api/system.object.gettype>](https://learn.microsoft.com/dotnet/api/system.object.gettype))

object.ReferenceEquals(object, object) ([<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>](https://learn.microsoft.com/dotnet/api/system.object.referenceequals))

([NetAF.Conversations.Instruct.html](#))

object.ToString() ([<https://learn.microsoft.com/dotnet/api/system.object.tostring>](https://learn.microsoft.com/dotnet/api/system.object.tostring))

+ **NetAF.Extensions**

NameSpace ([NetAF.Extensions.html](#)).Commands ([NetAF.Commands.html](#)).Persistence ([NetAF.Commands.Persistence.html](#))

([NetAF.Extensions.html](#))

Syntax

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

public sealed class Load : CustomCommand, ICommand, IPlayerVisible, IRestoreFromObj

+ **NetAF.Logic**<CustomCommandSerialization>

([NetAF.Logic.html](#))

+ **NetAF.Logic.Callbacks**

Class Save

Represents the Save command.

Filter by title

Inheritance

+ **NetAF.Commands.**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ Conversation ([NetAF.Commands.CustomCommand.html](#))
(NetAF.Commands.Conversati
Save

+ **NetAF.Commands.Frame**

IC ([NetAF.Commands.Frame.html](#))

IPlayerVisible ([NetAF.Assets.IPlayerVisible.html](#))

+ **NetAF.Commands.Global**

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<CustomCommand
Serialization ([NetAF.Serialization.CustomCommandSerialization.html](#))>

Inherited Members

Persistence

CustomCommand.Arguments

([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_Arguments)

CustomCommand.Help ([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_Help)

CustomCommand.InterpretIfNotPlayerVisible

([NetAF.Commands.Persistence.Lo](#)

Save ([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_InterpretIfNotPlayerVisible)

CustomCommand.Invoke(Game)

([NetAF.Commands.Persistence.Sa](#)

([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_Invoke_NetAF_Logic_Game_

+ **NetAF.Commands.Region**

Map

CustomCommand.IsPlayerVisible

([NetAF.Commands.Region.Map.html](#)#NetAF_Commands_CustomCommand_IsPlayerVisible)

CustomCommand.RestoreFrom(CustomCommandSerialization)

+ **NetAF.Commands.Scene**

([NetAF.Commands.CustomCommand.html](#)#NetAF_Commands_CustomCommand_RestoreFrom_NetAF_Serializ

ation_CustomCommandSerialization)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object))

([NetAF.Conversations.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object-system-object-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object-system-object-object)))

+ **NetAF.Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Conversations.Instruct](#)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

Assembly: NetAF.dll

+ **NetAF.Interpretation**

Syntax

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

public sealed class Save : CustomCommand, ICommand, IPlayerVisible, IRestoreFromObj

ect<CustomCommandSerialization>

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

Constructors

Save()

Initializes a new instance of the Save class.

Declaration

+ **NetAF.Commands.**

 public Save()

Conversation

(NetAF.Commands.Conversations.html)

+ **NetAF.Commands.Frame**

implements ICommand

(NetAF.Commands.Frame.html)

+ **NetAF.Commands.Global**

IPlayerVisible (NetAF.Assets.IPlayerVisible.html)

(NetAF.Commands.Global.html)

IRestoreFromObjectSerialization (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

- **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

Load

(NetAF.Commands.Persistence.Load.html)

Save

(NetAF.Commands.Persistence.Save.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instructions.html)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Namespace NetAF.Commands.RegionMap

Classes

Filter by title

[NetAF.Commands.Pan](#)

+ [NetAF.Commands](#).

Represents the Pan command.
[Conversation](#)

([NetAF.Commands.Conversation.html](#))

[NetAF.Commands.PanReset](#)

+ [NetAF.Commands.Frame](#).

Represents the PanReset command.
[\(NetAF.Commands.Frame.html\)](#)

+ [NetAF.Commands.Global](#)

([NetAF.Commands.Global.html](#))

+ [NetAF.Commands](#).

Persistence

([NetAF.Commands.Persistence.html](#))

- [NetAF.Commands.Region](#)

Map

([NetAF.Commands.RegionMap.html](#))

Pan

([NetAF.Commands.RegionMap.Pan.html](#))

PanReset

([NetAF.Commands.RegionMap.PanReset.html](#))

+ [NetAF.Commands.Scene](#)

([NetAF.Commands.Scene.html](#))

+ [NetAF.Conversations](#)

([NetAF.Conversations.html](#))

+ [NetAF.Conversations](#).

Instructions

([NetAF.Conversations.Instructions.html](#))

+ [NetAF.Extensions](#)

([NetAF.Extensions.html](#))

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

+ [NetAF.Logic](#)

Declaration

```
public static CommandHelp SouthCommandHelp { get; }
```

Property Value

Type	Description
Conversation CommandHelp (NetAF.Commands.CommandHelp.html) (NetAF.Commands.Conversation.html)	

+ NetAF.Commands.Frame

UpCommandHelp [UpCommandHelp.Frame.html](#)

+ NetAF.Commands.Global

Get the command help for up.
[\(NetAF.Commands.Global.html\)](#)
Declaration

+ NetAF.Commands.

Persistence
public static CommandHelp UpCommandHelp { get; }
[\(NetAF.Commands.Persistence.html\)](#)

Property Value

- NetAF.Commands.Region

Type	Description
RegionMap CommandHelp (NetAF.Commands.CommandHelp.html)	

Pan

(NetAF.Commands.RegionMap.Pan.html)

PanReset

(NetAF.Commands.RegionMap.PanReset.html)

WestCommandHelp

Get the command help for west.
[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Commands.Scene

Scene
Declaration
[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

WestCommandHelp
public static CommandHelp WestCommandHelp { get; }
[\(NetAF.Conversations.html\)](#)

+ NetAF.Conversations.

Property Value
[Instructions](#)

Type	Description
Instruct CommandHelp (NetAF.Commands.CommandHelp.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

Methods [Interpretation.html](#)

+ NetAF.Logic

GetPanPosition [\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

Get the pan position.
[\(NetAF.Logic.Callbacks.html\)](#)
Declaration

+ NetAF.Logic.Configuration

```
public static Point3D GetPanPosition(Point3D current, Direction direction)
```

Parameters

Type	Name	Description
Point3D (NetAF.Assets.Point3D.html) Conversation (NetAF.Commands.Conversation.html)	current	The current pan position.
Direction (NetAF.Assets.Direction.html)	direction	The direction to pan.

+ NetAF.Commands.Frame

Returns

Type	Description
Point3D (NetAF.Assets.Point3D.html) Global (NetAF.Commands.Global.html)	The modified pan position.

+ NetAF.Commands.

Persistence

Invoke(Game)

(NetAF.Commands.Persistence.html)

Invoke the command.

- NetAF.Commands.Region

Declaration
Map

(NetAF.Commands.RegionMap)

public Reaction Invoke(Game game)

Pan

(NetAF.Commands.RegionMap.Parameters.html)

Parameters

PanReset

Type	Name	Description
Game (NetAF.Logic.Game.html)	game	The game to invoke the command on.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Returns

+ NetAF.Conversations

Instructions

(NetAF.Conversations.Instruct)

Implements

+ NetAF.Extensions

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

Class PanReset

Represents the PanReset command.

Filter by title

Inheritance

([NetAF.Commands.Conversati](#)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAFCommands.Frame**

↳ PanReset

([NetAF.Commands.Frame.html](#))

Implements

ICOMmand ([NetAFCommands.Command.html](#))

([NetAFCommands.Global.html](#))

Inherited Members

+ **NetAF.Commands**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

Persistence

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object-object)))

+ **NetAFCommands.Region**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Pan

Namespace: NetAF (NetAF.dll) Commands (NetAF.Commands.html).RegionMap (NetAF.Commands.RegionMap.html)

Assembly: NetAF.dll

Syntax

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

Properties

Instructions

([NetAF.Conversations.Instruct](#)

CommandHelp

+ **NetAF.Extensions**

Get the command help

([NetAF.Extensions.html](#))

Declaration

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

public static CommandHelp CommandHelp { get; }

+ **NetAF.Logic**

([NetAF.Logic.html](#))

Property Value

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

CommandHelp (NetAF.Commands.CommandHelp.html)

Description

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

Methods

Invoke(Game)

Invoke the command.

Declaration

(NetAF.Commands.Conversati

public Reaction Invoke(Game game)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Parameters

+ NetAF.Commands.Global

Type (NetAF.Commands.Global.htm

Game (NetAF.Logic.Game.html)

+ NetAF.Commands.

Name

Description

game

The game to invoke the command on.

Persistence

Returns

(NetAF.Commands.Persistence

Type

- NetAF.Commands.Region

Reaction (NetAF.Commands.Reaction.html)

Map

Description

The reaction.

(NetAF.Commands.RegionMap

Implements

(NetAF.Commands.RegionMap.Pa

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Commands.RegionMap.Pa

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.htm

Namespace NetAF.Commands.Scene

Classes

Filter by title

CONVERSATION

Drop (NetAF.Commands.Scene.Drop.html)

(NetAF.Commands.Conversation)

Represents the Drop command.

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

Examine (NetAF.Commands.Scene.Examine.html)

+ NetAF.Commands.Global

Represents the Examine command.

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Move (NetAF.Commands.Scene.Move.html)

Persistence

Represents the Move command.

(NetAF.Commands.Persistence)

+ NetAF.Commands.Region

Take (NetAF.Commands.Scene.Take.html)

Map

Represents the Take command.

(NetAF.Commands.RegionMap)

- NetAF.Commands.Scene

TakeAll (NetAF.Commands.Scene.TakeAll.html)

(NetAF.Commands.Scene.html)

Represents the Take all command.

Drop

(NetAF.Commands.Scene.Drop.html)

Examine

Talk (NetAF.Commands.Scene.Talk.html)

(NetAF.Commands.Scene.Examine)

Represents the Talk command.

Move

(NetAF.Commands.Scene.Move.html)

Take

Unactionable (NetAF.Commands.Scene.Unactionable.html)

(NetAF.Commands.Scene.Take.html)

Represents the Unactionable command.

TakeAll

(NetAF.Commands.Scene.TakeAll.html)

Talk

UseOn (NetAF.Commands.Scene.UseOn.html)

(NetAF.Commands.Scene.Talk.html)

Represents the UseOn command.

Unactionable

(NetAF.Commands.Scene.Unactionable.html)

UseOn

(NetAF.Commands.Scene.UseOn.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions)

+ NetAF.Extensions

Class Drop

Represents the Drop command.

Filter by title

Inheritance

↳ [NetAF.Commands.Frame](#) (https://learn.microsoft.com/dotnet/api/system.object)

([NetAF.Commands.Frame.html](#))

Implements

+ [NetAF.Commands.Global](#)

ICommand ([NetAF.Commands ICommand.html](#))

([NetAF.Commands.Global.html](#))

Inherited Members

+ [NetAF.Commands](#).

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](#))

([NetAF.Commands.Persistence.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](#))

+ [NetAF.Commands.RegionMap](#)

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))

([NetAF.Commands.RegionMap.html](#))

object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))

+ [NetAF.Commands.Scene](#)

Name ([https://learn.microsoft.com/dotnet/api/system.object.name](#)) ([NetAF.Commands.Scene.html](#)) Scene ([NetAF.Commands.Scene.html](#))

Assembly: NetAF.dll

Syntax: [NetAF.Commands.Scene.Drop.htm](#)

Examine

([NetAF.Commands.Scene.Examine.html](#))
public sealed class Drop : ICommand

Move

([NetAF.Commands.Scene.Move.html](#))

Take

Constructors

([NetAF.Commands.Scene.Take.html](#))

TakeAll

([NetAF.Commands.Scene.TakeAll.html](#))

Drop(item)

([NetAF.Commands.Scene.Talk.html](#))

Represents the Drop command.

Unactionable

Declaration: [NetAF.Commands.Scene.Unactionable.html](#)

UseOn

([NetAF.Commands.Scene.UseOn.html](#))

public Drop(Item item)

+ [NetAF.Conversations](#)

([NetAF.Conversations.html](#))

Parameters

+ [NetAF.Conversations](#).

Instructions

Item ([NetAF.Assets.Item.html](#))

([NetAF.Conversations.Instruct.html](#))

+ [NetAF.Extensions](#)

([NetAF.Extensions.html](#))

Name	Description
item	The item to take.

Properties

CommandHelp

Get the command help.

Declaration
`

+ NetAF.Commands.Frame

public static CommandHelp CommandHelp { get; }
[\(NetAF.Commands.Frame.html\)](#)

NetAF.Commands.Global

Type	Description
CommandHelp (NetAF.Commands.CommandHelp.html)	

+ NetAF.Commands.Persistence

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.RegionMap

[\(NetAF.Commands.RegionMap.html\)](#)

Methods

Invoke(Game)

[\(NetAF.Commands.Scene.html\)](#)

Invoke the command.

Declaration
Drop
[\(NetAF.Commands.Scene.Drop.html\)](#)

Examine
public Reaction Invoke(Game game)
[\(NetAF.Commands.Scene.Examine.html\)](#)

Move

[\(NetAF.Commands.Scene.Move.html\)](#)

Parameters

Type	Name	Description
(NetAF.Commands.Scene.Take.html)		

Take

[\(NetAF.Commands.Scene.Take.html\)](#)

Game
[\(NetAF.Logic.Game.html\)](#)

[\(NetAF.Commands.Scene.TakeAll.html\)](#)

Talk

Returns
[\(NetAF.Commands.Scene.Talk.html\)](#)

Type
Unactionable

[\(NetAF.Commands.Scene.Unactionable.html\)](#)

UseOn

[\(NetAF.Commands.Scene.UseOn.html\)](#)

Implementations

(NetAF.Conversations.html)

ICommand ([NetAF.Commands.ICommand.html](#))

+ NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instruct.html\)](#)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Class Examine

Represents the Examine command.

Filter by title

Inheritance

+ NetAF.Commands.Frame

↳ [https://learn.microsoft.com/dotnet/api/system.object\)](https://learn.microsoft.com/dotnet/api/system.object)

↳ Examine

+ NetAF.Commands.Global

Implements

(NetAF.Commands.Global.html)

ICommand (NetAF.Commands.ICommand.html)

+ NetAF.Commands.

Inherited Members

Persistence

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object))

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode\)](https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype\)](https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring\)](https://learn.microsoft.com/dotnet/api/system.object.tostring)

(NetAF.Commands.Scene.html)

Namespace: NetAF (NetAF.html).Commands (NetAF.Commands.html).Scene (NetAF.Commands.Scene.html)

Drop

Assembly: NetAF

(NetAF.Commands.Scene.Drop.html)

Examine

(NetAF.Commands.Scene.Examine.html)

Move

public sealed class Examine : ICommand

(NetAF.Commands.Scene.Move.html)

Take

(NetAF.Commands.Scene.Take.html)

Constructors

(NetAF.Commands.Scene.TakeAll.html)

Talk

Examine(IExaminable)

(NetAF.Commands.Scene.Talk.html)

Unactionable

Represents the Examine command.

(NetAF.Commands.Scene.Unactionable.html)

DeclareOn

(NetAF.Commands.Scene.UseOn.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

Parameters

+ NetAF.Conversations.

Type Instructions

(NetAF.Conversations.Instruct.html)

IExaminable (NetAF.Assets.IExaminable.html)

Name

Description

examinable

The examinable.

+ NetAF.Extensions

(NetAF.Extensions.html)

Properties

CommandHelp

Get the command help.

Declaration
↓

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html) `public string CommandHelp { get; }`

+ NetAF.Commands.Global

Property Value
(NetAF.Commands.Global.html)

+ Type

Description

Persistence (NetAF.Commands.CommandHelp.html)

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

Methods

(NetAF.Commands.RegionMap.html)

- NetAF.Commands.Scene

Invoke(Game)

(NetAF.Commands.Scene.html)

Invoke the command.

Drop

(NetAF.Commands.Scene.Drop.html)

Declaration

Examine

(NetAF.Commands.Scene.Examine.html)

Move

(NetAF.Commands.Scene.Move.html)

Take

(NetAF.Commands.Scene.Take.html)

Type

Name

Description

TakeAll

Game (NetAF.Commands.Scene.TakeAll.html)

game

The game to invoke the command on.

Talk

(NetAF.Commands.Scene.Talk.html)

Returns

Unactionable

Type (NetAF.Commands.Scene.Unactionable.html)

Description

UseOn

Reaction (NetAF.Commands.Reaction.html)

The reaction.

(NetAF.Commands.Scene.UseOn.html)

+ NetAF.Conversations

Implementation

(NetAF.Conversations.html)

ICommand (NetAF.Commands.ICommand.html)

Instructions

(NetAF.Conversations.Instruct.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

Class Move

Represents the Move command.

Filter by title

Inheritance

([NetAF.Commands.Frame.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF Commands.Global**

([NetAF.Commands.Global.html](#))

Implements

+ **NetAF Commands**

([NetAF.Commands.ICommand.html](#))

Persistence

Inherited Members

([NetAF.Commands.Persistence](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ **NetAF.Commands.Region**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Commands.RegionMap](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF Commands.Scene**

([NetAF.Commands.Scene.html](#))

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Drop

Namespace: NetAF (NetAF.html) Commands (NetAF.Commands.html).Scene (NetAF.Commands.Scene.html)

Assembly: NetAF.dll

Examine

([NetAF.Commands.Scene.Examine](#))

Move

([NetAF.Commands.Scene.Move.html](#))

Take

([NetAF.Commands.Scene.Take.html](#))

TakeAll

Constructors

([NetAF.Commands.Scene.TakeAll](#))

Talk

([NetAF.Commands.Scene.Talk.html](#))

+ **Move(Direction)**

Unactionable

Represents the Move command.

UseOn

Declaration: NetAF.Commands.Scene.UseOn.I

+ **NetAF.Conversations**

public Move(Direction direction)

([NetAF.Conversations.html](#))

+ **NetAF.Conversations.**

Parameters

Instructions

Type

([NetAF.Conversations.Instruct](#))

Direction

([NetAF.Assets.Locations.Direction.html](#))

Name

Description

direction

The direction to move.

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

Properties

DownCommandHelp

Get the command help for down.

Declaration
↓
Property Value

+ **NetAF.Commands.Frame.html**

```
public static CommandHelp DownCommandHelp { get; }
```

+ **NetAF.Commands.Global**

(NetAF.Commands.Global.htm)

Property Value

+ **NetAF.Commands.**

Type Persistence

(NetAF.Commands.Persistence.CommandHelp.html)

Description

+ **NetAF.Commands.Region**

Map

EastCommandHelp

(NetAF.Commands.RegionMap.htm)

Get the command help for east.

- **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

Drop

```
public static CommandHelp EastCommandHelp { get; }
```

Examine

Property Value

Move

Type NetAF.Commands.Scene.Move.htm

Description

Take

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Commands.Scene.Take.htm)

TakeAll

(NetAF.Commands.Scene.TakeAll.htm)

NorthCommandHelp

(NetAF.Commands.Scene.Talk.htm)

Get the command help for north.

Unactionable

Declaration

UseOn

```
public static CommandHelp NorthCommandHelp { get; }
```

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Description

Instructions

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Conversations.Instruct.htm)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

Get the command help for south.

Declaration

```
public static CommandHelp SouthCommandHelp { get; }
```

Property Value

Type	Description
(NetAF.Commands.CommandHelp.html)	

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

UpCommandHelp

+ NetAF.Commands.

Get the command help for up.

Persistence

Declaration

+ NetAF.Commands.Region

```
public static CommandHelp UpCommandHelp { get; }
```

Map

(NetAF.Commands.RegionMap)

Property Value

- NetAF.Commands.Scene

Type

(NetAF.Commands.Scene.html)

Description

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Commands.Scene.Drop.html)

Examine

(NetAF.Commands.Scene.Examine.html)

Move

(NetAF.Commands.Scene.Move.html)

Get the command help for west.

Take

Declaration

(NetAF.Commands.Scene.Take.html)

TakeAll

```
public static CommandHelp WestCommandHelp { get; }
```

Talk

(NetAF.Commands.Scene.Talk.html)

Property Value

Unactionable

Type

(NetAF.Commands.Scene.Unactionable.html)

Description

UseOn

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Commands.Scene.UseOn.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

Methods

+ NetAF.Conversations.

Instructions

Invoke(Game)

+ NetAF.Extensions

Invoke the command.

(NetAF.Extensions.html)

Declaration

+ NetAF.Interpretation

```
public Reaction Invoke(Game game)
```

Parameters

Type	Name	Description
Game (NetAF.Logic.Game.html) (NetAF.Commands.Frame.html)	game	The game to invoke the command on.

Returns

+ [NetAF.Commands.Global](#)

Type	Description
NetAF.Commands.Global.html	

+ [Reaction](#) (NetAF.Commands.Reaction.html)

The reaction.

+ [NetAF.Commands](#):

Persistence

[\(NetAF.Commands.Persistence.html\)](#)

Implements

+ [NetAF.Commands.Region](#)

ICommand (NetAF.Commands.ICommand.html)

Map

[\(NetAF.Commands.RegionMap.html\)](#)

- [NetAF.Commands.Scene](#)

[\(NetAF.Commands.Scene.html\)](#)

Drop

[\(NetAF.Commands.Scene.Drop.html\)](#)

Examine

[\(NetAF.Commands.Scene.Examine.html\)](#)

Move

[\(NetAF.Commands.Scene.Move.html\)](#)

Take

[\(NetAF.Commands.Scene.Take.html\)](#)

TakeAll

[\(NetAF.Commands.Scene.TakeAll.html\)](#)

Talk

[\(NetAF.Commands.Scene.Talk.html\)](#)

Unactionable

[\(NetAF.Commands.Scene.Unactionable.html\)](#)

UseOn

[\(NetAF.Commands.Scene.UseOn.html\)](#)

+ [NetAF.Conversations](#)

[\(NetAF.Conversations.html\)](#)

+ [NetAF.Conversations](#).

Instructions

[\(NetAF.Conversations.Instructions.html\)](#)

+ [NetAF.Extensions](#)

[\(NetAF.Extensions.html\)](#)

+ [NetAF.Interpretation](#)

Class Take

Represents the Take command.

Filter by title

Inheritance

↳ [NetAF.Commands.Global](#)
↳ [Object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Commands.Global.html\)](#)

Implementation

ICloneable ([NetAF.Commands.ICommand.html](#))

Implementation

↳ [NetAF.Commands.Region](#)
↳ [Map](#)
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

↳ [NetAF.Commands.Scene](#)
object.Equals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)
[\(NetAF.Commands.Scene.Drop.html\)](#)

Namespace
↳ [Examine](#) ([NetAF \(NetAF.html\).Commands \(NetAF.Commands.html\).Scene \(NetAF.Commands.Scene.html\)](#))

Assembly
↳ [NetAF](#) ([NetAF.Commands.Scene.Examine.html](#))

Syntax

Move
↳ [\(NetAF.Commands.Scene.Move.html\)](#)

Take
public sealed class Take : ICommand
↳ [\(NetAF.Commands.Scene.Take.html\)](#)

TakeAll

↳ [\(NetAF.Commands.Scene.TakeAll.html\)](#)

Constructors

↳ [\(NetAF.Commands.Scene.Talk.html\)](#)

Unactionable

Take(Item)
↳ [\(NetAF.Commands.Scene.Unactionable.html\)](#)

UseOn

Represents the Take command.
↳ [\(NetAF.Commands.Scene.UseOn.html\)](#)

Declaration

+ [NetAF.Conversations](#)

↳ [\(NetAF.Conversations.html\)](#)
public Take(Item item)

+ [NetAF.Conversations](#).

Instructions

Parameters

↳ [\(NetAF.Conversations.Instruct.html\)](#)

Type

+ [NetAF.Extensions](#)

Item ([NetAF.Assets.Item.html](#))
↳ [\(NetAF.Extensions.html\)](#)

+ [NetAF.Interpretation](#)

↳ [\(NetAF.Interpretation.html\)](#)

Type	Name	Description
	item	The item to take.

Properties

CommandHelp

Get the command help.



Declaration

+ NetAF.Commands.Global

```
public static CommandHelp CommandHelp { get; }
```

(NetAF.Commands.Global.htm)

+ NetAF.Commands.

Property value

Persistence	Type	Description
	(NetAF.Commands.Persistence)	

CommandHelp (NetAF.Commands.CommandHelp.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

Methods

NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Invoke(Game)

(NetAF.Commands.Scene.Drop.htm)

Invoke the command.

Examine

(NetAF.Commands.Scene.Examine)

Declaration

Move

(NetAF.Commands.Scene.Move.htm)

```
public Reaction Invoke(Game game)
```

Take

(NetAF.Commands.Scene.Take.htm)

Parameters

Type	Name	Description
Talk	game	The game to invoke the command on.

Unactionable

(NetAF.Commands.Scene.Unactionable)

Returns

UseOn

Type (NetAF.Commands.Scene.UseOn)

Type	Description
Reaction (NetAF.Commands.Reaction.html)	The reaction.

+ NetAF.Conversations

(NetAF.Conversations.html)

Implements

Instructions

ICommand (NetAF.Commands.ICommand.html)

(NetAF.Conversations.Instruct)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Class TakeAll

Represents the Take all command.

Filter by title

Inheritance

+ [NetAF.Commands.Global](#)

↳ [Object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ TakeAll

+ [NetAF.Commands.](#)

Implements

[Persistence](#)

ICommand ([NetAF.Commands.ICommand.html](#))

([NetAF.Commands.Persistence](#))

Inherited Members

+ [NetAF.Commands.Region](#)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

([NetAF.Commands.RegionMap](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

[NetAF.Commands.Scene](#) (object)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

([NetAF.Commands.Scene.Drop](#))

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Examine

Namespace: NetAF ([NetAF.html](#)) Commands ([NetAF.Commands.html](#)).Scene ([NetAF.Commands.Scene.html](#))

Assembly: NetAF.dll

Syntax: [NetAF.Commands.Scene.Move.html](#)

Take

([NetAF.Commands.Scene.Take.html](#))
public sealed class TakeAll : ICommand

TakeAll

([NetAF.Commands.Scene.TakeAll.html](#))

Talk

([NetAF.Commands.Scene.Talk.html](#))

Properties

([NetAF.Commands.Scene.Unaction.html](#))

UseOn

([NetAF.Commands.Scene.UseOn.html](#))

+ [NetAF.Conversations](#)

Get the Command Help

([NetAF.Conversations.html](#))

Declaration

+ [NetAF.Conversations.](#)

Instructions: `public CommandHelp CommandHelp { get; }`

([NetAF.Conversations.Instruct.html](#))

Property Value

+ [NetAF.Extensions](#)

([NetAF.Extensions.html](#))

Description

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

+ [NetAF.Ionic](#)

Methods

Invoke(Game)

Invoke the command.



Declaration

+ [NetAF.Commands.Global](#)

([NetAFCommands.Global.html](#))

 public Reaction Invoke(Game game)

+ [NetAF.Commands.](#)

Persistence

Type	Name	Description
NetAFCommands.RegionMap	game	The game to invoke the command on.

Returns [NetAF.Commands.RegionMap](#)

- [NetAF.Commands.Scene](#)

([NetAFCommands.Scene.html](#))

 Reaction ([NetAF.Commands.Reaction.html](#))

Drop

([NetAF.Commands.Scene.Drop.html](#))

Examine

([NetAF.Commands.Scene.Examine.html](#))

ICommand ([NetAF.Commands.ICommand.html](#))

Move

([NetAF.Commands.Scene.Move.html](#))

Take

([NetAF.Commands.Scene.Take.html](#))

TakeAll

([NetAF.Commands.Scene.TakeAll.html](#))

Talk

([NetAF.Commands.Scene.Talk.html](#))

Unactionable

([NetAF.Commands.Scene.Unactionable.html](#))

UseOn

([NetAF.Commands.Scene.UseOn.html](#))

+ [NetAF.Conversations](#)

([NetAFConversations.html](#))

+ [NetAF.Conversations.](#)

Instructions

([NetAFConversations.Instruct.html](#))

+ [NetAF.Extensions](#)

([NetAFExtensions.html](#))

+ [NetAF.Interpretation](#)

([NetAFInterpretation.html](#))

+ [NetAFIonic](#)

Class Talk

Represents the Talk command.

Filter by title

Inheritance

([NetAF.Commands.Global.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.**

↳ Talk

Persistence

Implements

([NetAF.Commands.Persistence.html](#))

ICommand ([NetAF.Commands.ICommand.html](#))

+ **NetAF.Commands.Region**

Inherited Members

Map

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

Drop

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Commands.Scene.Drop.html](#))

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

Examine

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Commands.Scene.Examine.html](#))

Namespace: NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Scene ([NetAF.Commands.Scene.html](#))

Move

Assembly: NetAF

([NetAF.Commands.Scene.Move.html](#))

Syntax

([NetAF.Commands.Scene.Take.html](#))

TakeAll
public sealed class Talk : ICommand

([NetAF.Commands.Scene.TakeAll.html](#))

Talk

([NetAF.Commands.Scene.Talk.html](#))

Constructors

Unaction

([NetAF.Commands.Scene.Unaction.html](#))

UseOn

([NetAF.Commands.Scene.UseOn.html](#))

¶ [NetAF.Conversations](#)

([NetAF.Conversations.html](#))

Declaration

+ **NetAF.Conversations.**

public Talk(IConverser converser)

Instructions

Instruct

Parameters

+ **NetAF.Extensions**

Type ([NetAF.Extensions.html](#))

Name

Description

IConverser ([NetAF.Assets.Characters.IConverser.html](#))

converser

The converser.

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

([NetAF.Logic.html](#))

Properties

TalkCommandHelp

Get the command help.

Declaration
Declaration

(NetAF.Commands.Global.htm)

+ NetAF.Commands.

Persistence

Property Value

(NetAF.Commands.Persistence.htm)

+ Type

Description

NetAF.Commands.Region

Map

CommandHelp (NetAF.Commands.CommandHelp.html)

(NetAF.Commands.RegionMap)

- NetAF.Commands.Scene

ToCommandHelp

(NetAF.Commands.Scene.html)

Drop

Get the command help for to.

(NetAF.Commands.Scene.Drop.htm)

Declaration

Examine

(NetAF.Commands.Scene.Examine.htm)

public static CommandHelp ToCommandHelp { get; }

(NetAF.Commands.Scene.Move.htm)

Take

Property Value

(NetAF.Commands.Scene.Take.htm)

Type

Description

TakeAll

(NetAF.Commands.Scene.TakeAll.htm)

CommandHelp (NetAF.Commands.CommandHelp.html)

Talk

(NetAF.Commands.Scene.Talk.htm)

Unactionable

(NetAF.Commands.Scene.Unactionable.htm)

UseOn

(NetAF.Commands.Scene.UseOn.htm)

In NetAF.Commands

(NetAF.Conversations.html)

Invoke the command.

+ NetAF.Conversations.

Declaration

Instructions

(NetAF.Conversations.Instruct.htm)

public Reaction Invoke(Game game)

+ NetAF.Extensions

(NetAF.Extensions.html)

Parameters

+ Type

Name

Description

(NetAF.Interpretation.html)

Game (NetAF.Logic.Game.html)

game

The game to invoke the command on.

+ NetAF.Logic

(NetAF.Logic.html)

Returns

Type	Description
Reaction (NetAF.Commands.Reaction.html)	The reaction.

Implements

(NetAF.Commands.Global.html)
ICommand (NetAF.Commands.ICommand.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

- NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Drop

(NetAF.Commands.Scene.Drop.html)

Examine

(NetAF.Commands.Scene.Examine.html)

Move

(NetAF.Commands.Scene.Move.html)

Take

(NetAF.Commands.Scene.Take.html)

TakeAll

(NetAF.Commands.Scene.TakeAll.html)

Talk

(NetAF.Commands.Scene.Talk.html)

Unactionable

(NetAF.Commands.Scene.Unactionable.html)

UseOn

(NetAF.Commands.Scene.UseOn.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

Class Unactionable

Represents the Unactionable command.

Filter by title

Inheritance

+ **NetAFCommands.**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

Persistence

(**NetAFCommands.Persistence**)

Implements

+ **ICloneable**

([ICloneable.html](#))

Map

Inherited Members

(**NetAFCommands.RegionMap**)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-object)))

+ **NetAFCommands.Scene**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-system-object)))

Drop

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

([NetAFCommands.Scene.Drop.html](#))

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

Examine

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

([NetAFCommands.Scene.Examine.html](#))

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Move

Namespace: NetAF (NetAF.html) Commands (NetAF.Commands.html).Scene (NetAF.Commands.Scene.html)

Assembly: NetAF.dll

Syntax: [\(NetAF.Commands.Scene.Move.html\)](#)

TakeAll

([NetAF.Commands.Scene.TakeAll.html](#))

Talk

([NetAF.Commands.Scene.Talk.html](#))

Unactionable

Constructors

([NetAF.Commands.Scene.Unactionable.html](#))

UseOn

([NetAF.Commands.Scene.UseOn.html](#))

+ **Unactionable()**

+ **NetAF.Conversations**

Initializes a new instance of the Unactionable class.

([\(NetAF.Conversations.html\)](#))

Declaration:

+ **NetAF.Conversations.**

Instructions

public Unactionable()

([\(NetAF.Conversations.Instruct.html\)](#))

+ **NetAF.Extensions**

([\(NetAF.Extensions.html\)](#))

+ **Unactionable(string)**

+ **NetAF.Interpretation**

Initializes a new instance of the Unactionable class.

([\(NetAF.Interpretation.html\)](#))

Declaration:

+ **NetAF.Logic**

([\(NetAF.Logic.html\)](#))

```
public Unactionable(string description)
```

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i>	The description.

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

Properties

+ NetAF.Commands.Region

Map

Description

(NetAF.Commands.RegionMap.html)

Get the description.

NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Declaration

Drop

(NetAF.Commands.Scene.Drop.html)

Examine

(NetAF.Commands.Scene.Examine.html)

Property Value

Move

Type	Description
NetAF.Commands.Scene.Move.html	

Take

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Commands.Scene.Take.html)

TakeAll

(NetAF.Commands.Scene.TakeAll.html)

Talk

(NetAF.Commands.Scene.Talk.html)

Unactionable

(NetAF.Commands.Scene.Unactionable.html)

Invoke(Game)

(NetAF.Commands.Scene.UseOn.html)

Invoke the command.

+ NetAF.Conversations

Declaration

(NetAF.Conversations.html)

+ NetAF.Conversations

make(Game game)

Instructions

(NetAF.Conversations.Instruct.html)

Parameters

Type	Name	Description
NetAF.Extensions.html		

(NetAF.Extensions.html)

Game ([NetAF.Logic.Game.html](#))

game

The game to invoke the command on.

+ NetAF.Interpretation

Returns

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

Reactions

(NetAF.Logic.Reactions.html)

Type	Description
NetAF.Logic.Reactions.html	The reaction.

Implements

ICommand ([NetAF.Commands.ICommand.html](#))

▼

+ **NetAF.Commands.
Persistence**
([NetAF.Commands.Persistence.html](#))

+ **NetAF.Commands.Region
Map**
([NetAF.Commands.RegionMap.html](#))

- **NetAF.Commands.Scene**
([NetAF.Commands.Scene.html](#))

Drop
([NetAF.Commands.Scene.Drop.html](#))
Examine
([NetAF.Commands.Scene.Examine.html](#))
Move
([NetAF.Commands.Scene.Move.html](#))
Take
([NetAF.Commands.Scene.Take.html](#))
TakeAll
([NetAF.Commands.Scene.TakeAll.html](#))
Talk
([NetAF.Commands.Scene.Talk.html](#))
Unactionable
([NetAF.Commands.Scene.Unactionable.html](#))
UseOn
([NetAF.Commands.Scene.UseOn.html](#))

+ **NetAF.Conversations**
([NetAF.Conversations.html](#))

+ **NetAF.Conversations.
Instructions**
([NetAF.Conversations.Instructions.html](#))

+ **NetAF.Extensions**
([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**
([NetAF.Interpretation.html](#))

+ **NetAF.Logic**
([NetAF.Logic.html](#))

Class UseOn

Represents the UseOn command.

Filter by title

Inheritance Commands.

Persistence

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

([NetAF.Commands.Persistence](#))

+ NetAFCommands.Region

ICloneable ([NetAF.Commands.ICommand.html](#))

([NetAFCommands.RegionMap](#))

object NetAFCommands.Scene

([NetAF.Commands.Scene.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

Drop ([NetAF.Commands.Scene.Drop.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

Examine

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

Move ([NetAF.Commands.Scene.Examine.html](#))

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

Move

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Commands.Scene.Move.html](#))

Namespace: NetAF ([NetAF.html](#)).Commands ([NetAF.Commands.html](#)).Scene ([NetAF.Commands.Scene.html](#))

Take

([NetAF.Commands.Scene.Take.html](#))

Syntax

TakeAll

([NetAF.Commands.Scene.TakeAll.html](#))

Talk

public sealed class UseOn : ICommand

([NetAF.Commands.Scene.Talk.html](#))

Unactionable

([NetAF.Commands.Scene.Unactionable.html](#))

Constructors

([NetAF.Commands.Scene.UseOn.html](#))

NetAFConversations

useOn(item, interactWithItem)

([NetAF.Conversations.html](#))

Represents the UseOn command.

+ NetAF.Conversations.

Declaration

Instructions

([NetAF.Conversations.Instruct.html](#))

public UseOn(Item item, IInteractWithItem target)

+ NetAF.Extensions

([NetAF.Extensions.html](#))

Parameters

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

Item ([NetAF.Assets.Item.html](#))

Name

Description

item

The item to use.

+ NetAF.Logic

IInteractWithItem ([NetAF.Assets.IInteractWithItem.html](#))

([NetAF.Logic.html](#))

target

The target of the command.

+ NetAF.Logic.Callbacks

Properties

OnCommandHelp

Get the command help for on.

Declaration
+ NetAF.Commands.

Persistence

```
public static CommandHelp OnCommandHelp { get; }
```

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Property value

Map

Type
(NetAF.Commands.RegionMap)

Description

CommandHelp (NetAF.Commands.CommandHelp.html)

- NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

UseCommandHelp

Drop
(NetAF.Commands.Scene.Drop.html)

Examine
Get the command help.

(NetAF.Commands.Scene.Examine.html)

Declaration
Move

(NetAF.Commands.Scene.Move.html)

```
public static CommandHelp UseCommandHelp { get; }
```

Take
(NetAF.Commands.Scene.Take.html)

TakeAll

Property value
(NetAF.Commands.Scene.TakeAll.html)

Type

talk

Description

(NetAF.Commands.Scene.Talk.html)

CommandHelp (NetAF.Commands.CommandHelp.html)

Unactionable

(NetAF.Commands.Scene.Unactionable.html)

UseOn

(NetAF.Commands.Scene.UseOn.html)

Methods

+ NetAF.Conversations

(NetAF.Conversations.html)

Invoke(Game)

+ NetAF.Conversations.

InvokeInstructions

Instruct
(NetAF.Conversations.Instruct.html)

+ NetAF.Extensions

```
public Reaction Invoke(Game game)
```

(NetAF.Extensions.html)

+ NetAF.Interpretation

Parameters

(NetAF.Interpretation.html)

Type

+ NetAF.Logic

Game (NetAF.Logic.Game.html)

(NetAF.Logic.html)

Type	Name	Description
Game (NetAF.Logic.Game.html)	game	The game to invoke the command on.

+ NetAF.Logic.Callbacks

Returns

Type	Description
Reaction (NetAF.Commands.Reaction.html)	The reaction.

Implements

[NetAF.Commands.](#)

ICommand (NetAF.Commands.ICommand.html)

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

- NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Drop

(NetAF.Commands.Scene.Drop.html)

Examine

(NetAF.Commands.Scene.Examine.html)

Move

(NetAF.Commands.Scene.Move.html)

Take

(NetAF.Commands.Scene.Take.html)

TakeAll

(NetAF.Commands.Scene.TakeAll.html)

Talk

(NetAF.Commands.Scene.Talk.html)

Unactionable

(NetAF.Commands.Scene.Unactionable.html)

UseOn

(NetAF.Commands.Scene.UseOn.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

Namespace NetAF.Conversations

Classes

Filter by title ▾

Conversation (NetAF.Conversations.Conversation.html)

+ NetAF.Commands.Frame

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

LogItem (NetAF.Conversations.LogItem.html)

(NetAF.Commands.Global.html)

Provides a container for log items.

+ NetAF.Commands.

Persistence

Paragraph (NetAF.Conversations.Paragraph.html)

(NetAF.Commands.Persistence.html)

Represents a paragraph in a Conversation.

+ NetAF.Commands.Region

Map

Response (NetAF.Conversations.Response.html)

(NetAF.Commands.Region.html)

Provides a response to a conversation.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Enums

- NetAF.Conversations

(NetAF.Conversations.html)

Participant (NetAF.Conversations.Participant.html)

Conversation

(NetAF.Conversations.Participant.html)

Provides a participant in a conversation.

ConversationActionCallback

(NetAF.Conversations.ConversationActionCallback.html)

LogItem

(NetAF.Conversations.LogItem.html)

Paragraph

(NetAF.Conversations.Paragraph.html)

Participant

(NetAF.Conversations.Participant.html)

Provides a callback that can be used in conversations invoking actions.

(NetAF.Conversations.Participant.html)

Response

(NetAF.Conversations.Response.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

Class Conversation

Represents a conversation.

Filter by title

Inheritance

([NetAF.Commands.Frame.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.Global**

([NetAF.Commands.Global.htm](#))

Implements

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Conversation>

+ **NetAF.Commands**

Serialization ([NetAF.Serialization.Assets.ConversationSerialization.html](#))>

Persistence

Inherited Members

([NetAF.Commands.Persistence](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Commands.Region**

Map

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Commands.RegionMap](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Commands.Scene](#))

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

NetAF.Conversations

([NetAF.Conversations.html](#))

Assembly: NetAF.dll

Syntax: `NetAF.Conversations.Conversation`

 ConversationActionCallback

 ([NetAF.Conversations.Conversation](#))

 public sealed class Conversation : IRestoreFromObjectSerialization<ConversationSerializat

 ionItem>

 ([NetAF.Conversations.LogItem.html](#))

 Paragraph

 ([NetAF.Conversations.Paragraph.html](#))

 Participant

 ([NetAF.Conversations.Participant.html](#))

 Response

Conversation(params Paragraph[])

 ([NetAF.Conversations.Response.html](#))

Represents a conversation.

+ **NetAF.Conversations.Instructions**

Declaration:

([NetAF.Conversations.Instruct](#))

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

Parameters

+ **NetAF.Interpretation**

Type: ([NetAF.Interpretation.html](#))

Paragraph ([NetAF.Conversations.Paragraph.html](#))[]

+ **NetAF.Logic**

([NetAF.Logic.html](#))

	Name	Description
Paragraph (NetAF.Conversations.Paragraph.html)[]	paragraphs	The paragraphs.

Properties

CurrentParagraph

Get the current paragraph in the conversation.

Declaration

(NetAF.Commands.Frame.html)
public Paragraph CurrentParagraph { get; }

+ NetAF.Commands.Global

(NetAF.Commands.Global.htm)
Property Value

+ **NetAF.Commands.**

Type

Persistence

Paragraph (NetAF.Conversations.Paragraph.html)

Description

(NetAF.Commands.Persistence)

+ NetAF.Commands.Region

Map

Log

(NetAF.Commands.RegionMap)

Get the log.

+ NetAF.Commands.Scene

Declaration

(NetAF.Commands.Scene.html)

- NetAF.Conversations

LogItem [] Log { get; }

(NetAF.Conversations.html)

Conversation

Property Value

(NetAF.Conversations.Conversation)

Type ConversationActionCallback

Description

(NetAF.Conversations.Conversation)

LogItem (NetAF.Conversations.LogItem.html) []

LogItem

(NetAF.Conversations.LogItem.html)

Paragraph

Paragraphs

(NetAF.Conversations.Paragraph.html)

Participant

Get the current paragraph in the conversation.

(NetAF.Conversations.Participant.html)

Declaration

Response

(NetAF.Conversations.Response.html)

+ NetAF.Conversations.

Instructions

Properties

(NetAF.Conversations.Instruct)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Paragraph (NetAF.Conversations.Paragraph.html) []

Description

+ NetAF.Interpretation

(NetAF.Interpretation.html)

NetAF.Logic

(NetAF.Logic.html)

Next(Game)

Trigger the next line in this conversation.

Declaration

```
public Reaction Next(Game game)
```

(NetAF.Commands.Frame.html)

Parameters

+ Type	Name	Description
NetAF.Commands.Global	game	The game.

+ NetAF.Commands.

Returns Persistence

Type	Description
NetAF.Commands.Persistence	The reaction to the line.

+ NetAF.Commands.Region

Map (NetAF.Commands.Region.html)

Map

(NetAF.Commands.RegionMap)

Respond(Response, Game)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Respond to the conversation.

NetAF Conversations

(NetAF.Conversations.html)

```
public Reaction Respond(Response response, Game game)
```

Conversation (NetAF.Conversations.Conversation.html)

ConversationActionCallback

Parameters (NetAF.Conversations.Conversation.html)

Type	Name	Description
LogItem		
Response (NetAF.Conversations.Response.html)	response	The response.
Paragraph		

Game (NetAF.Logic.Game.html)

Participant

Return (NetAF.Conversations.Participant.html)

Type	Description
Response (NetAF.Conversations.Response.html)	The reaction to the response.

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct)

RestoreFrom(ConversationSerialization)

+ NetAF.Extensions

Restore this object from a serialization.

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

```
public void RestoreFrom(ConversationSerialization serialization)
```

+ NetAF.Logic

(NetAF.Logic.html)

Parameters

Type	Name	Description
ConversationSerialization (NetAF.Serialization.Assets.ConversationSerialization.html)	<i>serialization</i>	The serialization to restore from.

▼

Implements

(NetAF.Commands.Frame.html)

IRestoreFromObjectSerialization<T> (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)
+ **NetAF.Commands.Global**

(NetAF.Commands.Global.html)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

- **NetAF.Conversations**

(NetAF.Conversations.html)

Conversation

(NetAF.Conversations.Conversation.html)

ConversationActionCallback

(NetAF.Conversations.ConversationActionCallback.html)

LogItem

(NetAF.Conversations.LogItem.html)

Paragraph

(NetAF.Conversations.Paragraph.html)

Participant

(NetAF.Conversations.Participant.html)

Response

(NetAF.Conversations.Response.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instructions.html)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Delegate ConversationActionCallback

Provides a callback that can be used in conversations invoking actions.

Filter by title

Namespace: NetAF (NetAF.html) Conversations (NetAF.Conversations.html)

Assembly: NetAF.dll

+ **NetAF.Commands.Global**

Syntax
[\(NetAF.Commands.Global.html\)](#)

+ **NetAF.Commands**

 public delegate void ConversationActionCallback(Game game)

Persistence

[\(NetAFCommands.Persistence.html\)](#)

Parameters

Type	Name	Description
Map Game (NetAF.Logic.Game.html) (NetAFCommands.RegionMap.html)	game	The game to invoke the callback on.

+ **NetAF.Commands.Scene**

[\(NetAF.Commands.Scene.html\)](#)

- **NetAF.Conversations**

[\(NetAF.Conversations.html\)](#)

Conversation

[\(NetAF.Conversations.Conversation.html\)](#)

ConversationActionCallback

[\(NetAF.Conversations.ConversationActionCallback.html\)](#)

LogItem

[\(NetAF.Conversations.LogItem.html\)](#)

Paragraph

[\(NetAF.Conversations.Paragraph.html\)](#)

Participant

[\(NetAF.Conversations.Participant.html\)](#)

Response

[\(NetAF.Conversations.Response.html\)](#)

+ **NetAF.Conversations.**

Instructions

[\(NetAF.Conversations.Instructions.html\)](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

Class LogItem

Provides a container for log items.

Filter by title

Inheritance

+ NetAF.Commands.Global

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ LogItem

+ NetAF.Commands.

Inherited Members

Persistence

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ NetAF.Commands.RegionMap

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ NetAF.Commands.Scene

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html)

- NetAF.Conversations

Assembly: NetAF.dll

(NetAF.Conversations.html)

Syntax

Conversation

```
(NetAF.Conversations.Conversation  
public sealed class LogItem  
    ConversationActionCallback
```

```
    (NetAF.Conversations.Conversation
```

LogItem

(NetAF.Conversations.LogItem.htm

Paragraph

(NetAF.Conversations.Paragraph.h

LogItem(Participant, string)

(NetAF.Conversations.Participant.h

Provides a container for log items.

(NetAF.Conversations.Response.h

Declaration

+ NetAF.Conversations.

Instructions

LogItem(Participant participant, string line)

(NetAF.Conversations.Instruct

Parameters

+ NetAF.Extensions

T(NetAF.Extensions.html)

Name	Description
------	-------------

Participant (<NetAF.Conversations.Participant.html>)

participant	The participant.
-------------	------------------

(NetAF.Interpretation.html)

String (<https://learn.microsoft.com/dotnet/api/system.string>)

line	The line.
------	-----------

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

LogItem(Participant participant, string line)

Properties

Line

Get the line.



Declaration

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Property Value

Persistence

Type (NetAF.Commands.Persistence)

Description

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

Participant

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Get the participant.

NetAF.Conversations

(NetAF.Conversations.html)

public Participant Participant { get; }

Conversation

(NetAF.Conversations.Conversatio

Property Value

ConversationActionCallback

(NetAF.Conversations.Conversatio

Type LogItem

Description

(NetAF.Conversations.LogItem.html)

Participant (NetAF.Conversations.Participant.html)

Paragraph

(NetAF.Conversations.Paragraph.h

Participant

(NetAF.Conversations.Participant.h

Response

(NetAF.Conversations.Response.h

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Class Paragraph

Represents a paragraph in a Conversation.

Filter by title

Inheritance

(NetAF.Commands.Global.html)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.**

Paragraph

Inherited Members

(NetAF.Commands.Persistence.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Commands.Region.html**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

(NetAF.Commands.RegionMap.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

+ **NetAF.Commands.Scene.html**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

- **NetAF.Conversations.html**

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html)

(NetAF.Conversations.html)

Assembly: NetAF.dll

Conversation

Syntax

(NetAF.Conversations.Conversation.h)

ConversationActionCallback

public sealed class Paragraph

(NetAF.Conversations.Conversation.h)

LogItem

(NetAF.Conversations.LogItem.html)

Paragraph

Constructors

(NetAF.Conversations.Paragraph.h)

Participant

(NetAF.Conversations.Participant.h)

Response

(NetAF.Conversations.Response.h)

Represents a paragraph in a Conversation.

+ **NetAF.Conversations.html**

Declaration

Instructions

(NetAF.Conversations.Instruct.html)

public Paragraph(string line, ConversationActionCallback action, IEndOfParagraphInstruction instruction, string name = "")

+ **NetAF.Extensions.html**

(NetAF.Extensions.html)

Parameters

+ **NetAF.Interpretation.html**

(NetAF.Interpretation.html)

Type

Name

Description

+ **NetAF.Logic.html**

(NetAF.Logic.html)

System.String

line

Specify the line.

+ **NetAF.Logic.Callbacks.html**

(NetAF.Logic.Callbacks.html)

Type	Name	Description
ConversationActionCallback (NetAF.Conversations.ConversationActionCallback.html)	action	Specify any action to be carried out with this line.
IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html) (NetAF.Commands.Global.html)	instruction	Specify the end of paragraph instruction. This can be applied to a conversation to direct the conversation after this paragraph.
+ NetAF.Commands.Persistence (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.Persistence.html)	name	Specify the name of the paragraph.

+ NetAF.Commands.Region

Paragraph(string, ConversationActionCallback, string)

(NetAF.Commands.RegionMap.html)

Initializes a new instance of the Paragraph class.

+ NetAF.Commands.Scene

Declaration

(NetAF.Commands.Scene.html)

- NetAF.Conversations

Parameters (string line, ConversationActionCallback action, string name = "")

(NetAF.Conversations.html)

Conversation

Type	Name	Description
ConversationActionCallback		
string (https://learn.microsoft.com/dotnet/api/system.string)	line	Specify the line.
LogItem (NetAF.Conversations.LogItem.html)		
ConversationActionCallback (NetAF.Conversations.ConversationActionCallback.html)	action	Specify any action to be carried out with this line.
Paragraph (NetAF.Conversations.Paragraph.html)	name	Specify the name of the paragraph.
Participant (NetAF.Conversations.Participant.html)		
Response (NetAF.Conversations.Response.html)		

Paragraph(string, IEndOfParagraphInstruction, string)

(NetAF.Conversations.html) the Paragraph class.

Instructions

Declaration

(NetAF.Conversations.Instruct.html)

+ NetAF.Extensions

Parameters (string line, IEndOfParagraphInstruction instruction, string name = "")

(NetAF.Extensions.html)

+ NetAF.Interpretation

Parameters

(NetAF.Interpretation.html)

Type

+ NetAF.Logic

string
(NetAF.Logic.html)

(https://learn.microsoft.com/dotnet/api/system.string)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Type	Name	Description
string (NetAF.Logic.html)	line	Specify the line.

Type	Name	Description
IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)	<i>instruction</i>	Specify the end of paragraph instruction. This can be applied to a conversation to direct the conversation after this paragraph.
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.Global.html)	<i>name</i>	Specify the name of the paragraph.

+ NetAF.Commands.

Persistence **Paragraph(string, string)** (NetAF.Commands.Persistence)

Initializes a new instance of the Paragraph class.

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

```
public Paragraph(string line, string name = "")
```

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Parameters

- NetAF.Conversations

Type **(NetAF.Conversations.html)**

string (<https://learn.microsoft.com/dotnet/api/system.string>)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

ConversationActionCallback

(NetAF.Conversations.ConversationActionCallback)

LogItem

(NetAF.Conversations.LogItem.html)

Paragraph

(NetAF.Conversations.Paragraph.html)

Participant

(NetAF.Conversations.Participant.html)

Action

Response

Get or set any action to carry out on this line.

(NetAF.Conversations.Response.html)

Declaration

+ NetAF.Conversations.

Instructions

```
public ConversationActionCallback Action { get; set; }
```

(NetAF.Conversations.Instruct

Properties

NetAF.Extensions

Type **(NetAF.Extensions.html)**

+ NetAF.Interpretation

ConversationActionCallback (<NetAF.Conversations.ConversationActionCallback.html>)

(NetAF.Interpretation.html)

+ NetAF.Logic

CanRespond

(NetAF.Logic.html)

Get if logic is capable

NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Declaration

Description

```
public bool CanRespond { get; }
```

Property Value

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Commands.Global.html)	

+ NetAF.Commands. Instruction Persistence

(NetAF.Commands.Persistence)

Get the end of paragraph instruction. This can be applied to a conversation to direct the conversation after this paragraph.

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

```
public IEndOfParagraphInstruction Instruction { get; }
```

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Property Value

- NetAF.Conversations

Type	Description
(NetAF.Conversations.html) IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)	

(NetAF.Conversations.Conversation)

ConversationActionCallback

(NetAF.Conversations.Conversation)

LogItem

Get [\(NetAF.Conversations.LogItem.html\)](#)

Paragraph

Declaration

(NetAF.Conversations.Paragraph.h)

Participant

```
public string Line { get; set; }
```

Participant

Response

(NetAF.Conversations.Response.h)

Property Value

+ NetAF.Conversations. Type

Instructions	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Conversations.Instruct	

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

Get the name.

(NetAF.Interpretation.html)

Declaration

+ NetAF.Logic

(NetAF.Logic.html)

```
public string Value { get; }
```

+ NetAF.Logic.Callbacks

Property Value

(NetAF.Logic.Callbacks.html)

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	

Responses

Get or set the responses, applicable to the last line.

[\(NetAF.Commands.Global.html\)](#)

Declaration

+ NetAF.Commands.

Persistence

```
public Response[] Responses { get; set; }
```

[\(NetAF.Commands.Persistence.html\)](#)

+ NetAF.Commands.Region

Property value

Map

Type

[\(NetAF.Commands.RegionMap.html\)](#)

Response ([NetAF.Conversations.Response.html](#))[]

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

- NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

Conversation

[\(NetAF.Conversations.Conversation.html\)](#)

ConversationActionCallback

[\(NetAF.Conversations.ConversationActionCallback.html\)](#)

LogItem

[\(NetAF.Conversations.LogItem.html\)](#)

Paragraph

[\(NetAF.Conversations.Paragraph.html\)](#)

Participant

[\(NetAF.Conversations.Participant.html\)](#)

Response

[\(NetAF.Conversations.Response.html\)](#)

+ NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instructions.html\)](#)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Enum Participant

Enumeration of participants in a conversation.

 Filter by title

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html)

Assembly: NetAF.dll

NetAF.Commands.

Persistence

(NetAF.Commands.Persistence)

public enum Participant

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

Fields

Commands.Scene

(NetAF.Commands.Scene.html)

Name	Description
- NetAF.Conversations	
Other (NetAF.Conversations.html)	Any other participant.

Player Conversation The player.

(NetAF.Conversations.Conversatio

ConversationActionCallback

(NetAF.Conversations.Conversatio

LogItem

(NetAF.Conversations.LogItem.htm

Paragraph

(NetAF.Conversations.Paragraph.h

Participant

(NetAF.Conversations.Participant.h

Response

(NetAF.Conversations.Response.h

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

Class Response

Provides a response to a conversation.

Filter by title

Inheritance

+ NetAF.Commands.

↳ [Persistence](#) (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Commands.Persistence.html\)](#)

Inherited Members

+ NetAF.Commands.Region

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

(NetAF.Commands.RegionMap)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

- NetAF.Commands.Scene

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

- NetAFConversations

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Name [Conversation](#) ([NetAF.html](#)).Conversations ([NetAF.Conversations.html](#))

Assembly: [NetAF.dll](#)

ConversationActionCallback

Syntax [\(NetAF.Conversations.Conversation.html\)](#)

LogItem

public sealed class Response

[\(NetAF.Conversations.LogItem.html\)](#)

Paragraph

[\(NetAF.Conversations.Paragraph.html\)](#)

Participant

[\(NetAF.Conversations.Participant.html\)](#)

Response

[\(NetAF.Conversations.Response.html\)](#)

+ NetAF.Conversations.

Initializes a new instance of the Response class.

Instructions

Declaration [\(NetAF.Conversations.Instruct.html\)](#)

+ NetAF.Extensions.

public Response(string line)

[\(NetAF.Extensions.html\)](#)

Parameters

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Name

Description

+ NetAF.Logic.

string (<https://learn.microsoft.com/dotnet/api/system.string>)

line

The line to trigger this response.

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

Response(string, EndOfParagraphInstruction)

[\(NetAF.Logic.Callbacks.html\)](#)

Provides a response to a conversation.

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

Declaration

```
public Response(string line, IEndOfParagraphInstruction instruction)
```

Parameters

Type	Name	Description
+ NetAF.Commands.Persistence (https://learn.microsoft.com/dotnet/api/system.net.http.commands.persistence) (NetAF.Commands.Persistence)	<i>line</i>	The line to trigger this response.
+ NetAF.Commands.RegionMap (https://learn.microsoft.com/dotnet/api/system.net.http.commands.instructions.endofparagraphinstruction.html) (NetAF.Commands.RegionMap)	<i>instruction</i>	Specify the end of paragraph instruction. This can be applied to a conversation to direct the conversation after this paragraph.

+ **NetAF.Commands.Scene**
[\(NetAF.Commands.Scene.html\)](https://learn.microsoft.com/dotnet/api/system.net.http.commands.scene.html)

Properties
NetAF.Conversations
(NetAF.Conversations.html)

Instruction

Get the end of paragraph instruction. This can be applied to a conversation to direct the conversation after this paragraph.
[\(https://learn.microsoft.com/dotnet/api/system.net.http.conversations.conversation.endofparagraphinstructioncallback\)](https://learn.microsoft.com/dotnet/api/system.net.http.conversations.conversation.endofparagraphinstructioncallback)

LogItem
Declaration
(NetAF.Conversations.LogItem.html)

Paragraph
public IEndOfParagraphInstruction Instruction { get; }
(NetAF.Conversations.Paragraph.h)

Participant

Property Value
(NetAF.Conversations.Participant.h)

Type	Description
Response (NetAF.Conversations.Response.h)	IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

+ **NetAF.Conversations**.

Instructions
(NetAF.Conversations.Instruct

Line

+ **NetAF.Extensions**

Get the line
(NetAF.Extensions.html)

Declaration

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)
public string Line { get; }

+ **NetAF.Logic**

(NetAF.Logic.html)

Property Value

Type	Description
NetAF.Logic.Callbacks (NetAF.Logic.Callbacks.html)	string (https://learn.microsoft.com/dotnet/api/system.string)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)



- + **NetAF.Commands.**
 Persistence
 ([NetAF.Commands.Persistence.html](#))
- + **NetAF.Commands.Region**
 Map
 ([NetAF.Commands.RegionMap.html](#))
- + **NetAF.Commands.Scene**
 ([NetAF.Commands.Scene.html](#))
- **NetAF.Conversations**
 ([NetAF.Conversations.html](#))
 - Conversation
 ([NetAF.Conversations.Conversation.html](#))
 - ConversationActionCallback
 ([NetAF.Conversations.ConversationActionCallback.html](#))
 - LogItem
 ([NetAF.Conversations.LogItem.html](#))
 - Paragraph
 ([NetAF.Conversations.Paragraph.html](#))
 - Participant
 ([NetAF.Conversations.Participant.html](#))
 - Response
 ([NetAF.Conversations.Response.html](#))
- + **NetAF.Conversations.**
 Instructions
 ([NetAF.Conversations.Instructions.html](#))
- + **NetAF.Extensions**
 ([NetAF.Extensions.html](#))
- + **NetAF.Interpretation**
 ([NetAF.Interpretation.html](#))
- + **NetAF.Logic**
 ([NetAF.Logic.html](#))
- + **NetAF.Logic.Callbacks**
 ([NetAF.Logic.Callbacks.html](#))
- + **NetAF.Logic.Configuration**
 ([NetAF.Logic.Configuration.html](#))

Namespace NetAF.Conversations.Instructions

▼ Filter by title

Classes

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

ByCallback (NetAF.Conversations.Instructions.ByCallback.html)

(NetAF.Commands.Global.htm)

An end of paragraph instruction that shifts paragraphs based on a callback.

+ NetAF.Commands.

Persistence

First (NetAF.Conversations.Instructions.First.html)

(NetAF.Commands.Persistence.htm)

An end of paragraph instruction that shifts paragraphs to the start.

+ NetAF.Commands.Region

Map

GoTo (NetAF.Conversations.Instructions.GoTo.html)

(NetAF.Commands.RegionMap.htm)

An end of paragraph instruction that shifts paragraphs based on an absolute index.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Jump (NetAF.Conversations.Instructions.Jump.html)

+ NetAF.Conversations

An end of paragraph instruction that shifts paragraphs based on a delta.

(NetAF.Conversations.html)

NetAF.Conversations.

Last (NetAF.Conversations.Instructions.Last.html)

Instructions

An end of paragraph instruction that shifts paragraphs to the end.

(NetAF.Conversations.Instruct

ByCallback

Next (NetAF.Conversations.Instructions.Next.html)

First

An end of paragraph instruction that shifts paragraphs to the next paragraph.

(NetAF.Conversations.Instructions.

GoTo

Previous (NetAF.Conversations.Instructions.Previous.html)

EndOfParagraphInstruction

An end of paragraph instruction that shifts paragraphs to the previous paragraph.

(NetAF.Conversations.Instructions.

Jump

Repeat (NetAF.Conversations.Instructions.Repeat.html)

Last

An end of paragraph instruction that repeats.

(NetAF.Conversations.Instructions.

Next

ToName (NetAF.Conversations.Instructions.ToName.html)

Previous

An end of paragraph instruction that shifts paragraphs based on a name.

(NetAF.Conversations.Instructions.

Repeat

(NetAF.Conversations.Instructions.

ToName

(NetAF.Conversations.Instructions.

Interfaces

IEndOfParagraphInstruction

(NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

Represents an instruction to be carried out at the end of a paragraph.

(NetAF.Commands.Frame.html)

+ NetAF.Commands.Global

(NetAF.Commands.Global.html)

+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

- NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

ByCallback

(NetAF.Conversations.Instructions.ByCallback.html)

First

(NetAF.Conversations.Instructions.First.html)

GoTo

(NetAF.Conversations.Instructions.GoTo.html)

IEndOfParagraphInstruction

(NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

Jump

(NetAF.Conversations.Instructions.Jump.html)

Last

(NetAF.Conversations.Instructions.Last.html)

Next

(NetAF.Conversations.Instructions.Next.html)

Previous

(NetAF.Conversations.Instructions.Previous.html)

Repeat

(NetAF.Conversations.Instructions.Repeat.html)

ToName

(NetAF.Conversations.Instructions.ToName.html)

Properties

Callback

Get the callback that decides the instruction to use.

Declaration

(NetAF.Commands.Global.htm)

```
public Func<IEndOfParagraphInstruction> Callback { get; }
```

+ NetAF.Commands.

Persistence

Property Value

(NetAFCommands.Persistence)

Type

+ NetAF.Commands.Region

Func (<https://learn.microsoft.com/dotnet/api/system.func-1>)<

Map

IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)>

(NetAF.Commands.RegionMap)

Description

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Methods

+ NetAF.Conversations

(NetAF.Conversations.html)

GetIndexOfNext(Paragraph, Paragraph[])

- NetAF.Conversations.

Instructions

Gets the index of the next paragraph.

(NetAF.Conversations.Instruct

Declaration

ByCallback

(NetAF.Conversations.Instructions

```
public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)
```

First

(NetAF.Conversations.Instructions.

Parameters

current

Type (NetAF.Conversations.Instructions.

IEndOfParagraphInstruction

Paragraph (NetAF.Conversations.Paragraph.html)

Name

Description

current (NetAF.Conversations.Paragraph.html)

current

The current paragraph.

paragraphs (NetAF.Conversations.Paragraph.html[])

paragraphs

The collection of paragraphs.

Last

Returns

(NetAF.Conversations.Instructions.

Type

Next

Description

(NetAF.Conversations.Instructions.

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Previous

The index of the next paragraph.

(NetAF.Conversations.Instructions.

Repeat

Implements

NetAF.Conversations.Instructions.

ToName

IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

(NetAF.Conversations.Instructions.

+ NetAF.Extensions

(NetAF.Extensions.html)

▼

(NetAF.Commands.Global.htm)

+ **NetAF.Commands.**

Persistence

(NetAF.Commands.Persistence.htm)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.htm)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

- **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instructions.htm)

ByCallback

(NetAF.Conversations.Instructions.ByCallback.htm)

First

(NetAF.Conversations.Instructions.First.htm)

GoTo

(NetAF.Conversations.Instructions.GoTo.htm)

IEndOfParagraphInstruction

(NetAF.Conversations.Instructions.IEndOfParagraphInstruction.htm)

Jump

(NetAF.Conversations.Instructions.Jump.htm)

Last

(NetAF.Conversations.Instructions.Last.htm)

Next

(NetAF.Conversations.Instructions.Next.htm)

Previous

(NetAF.Conversations.Instructions.Previous.htm)

Repeat

(NetAF.Conversations.Instructions.Repeat.htm)

ToName

(NetAF.Conversations.Instructions.ToName.htm)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Class First

An end of paragraph instruction that shifts paragraphs to the start.

Filter by title

Inheritance

+ [NetAF.Commands](#)

First

Persistence

([NetAF.Commands.Persistence](#))

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

+ [NetAF.Commands.Region](#)

Inherited Members

Map

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](#))

+ [NetAF.Commands.Scene](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](#))

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))

([NetAF.Conversations.html](#))

object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))

[NetAF Conversations](#)

Instructions ([NetAF.html](#)).Conversations ([NetAF.Conversations.html](#)).Instructions ([NetAF.Conversations.Instructions.html](#))

([NetAF.Conversations.Instruct](#))

Syntax

By Callback

([NetAF.Conversations.Instructions](#).

public sealed class First : IEndOfParagraphInstruction

([NetAF.Conversations.Instructions](#).

GoTo

([NetAF.Conversations.Instructions](#).

IEndOfParagraphInstruction

([NetAF.Conversations.Instructions](#).

Methods

Jump

([NetAF.Conversations.Instructions](#).

GetIndexOfNext(Paragraph, Paragraph[])

Last

([NetAF.Conversations.Instructions](#).

Get the index of the next paragraph.

Next

Declaration

[NetAF.Conversations.Instructions](#).

Previous

public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)

Repeat

([NetAF.Conversations.Instructions](#).

Parameters

ToName

Type	Name	Description
NetAF.Conversations.Instructions .	current	The current paragraph.
NetAF.Extensions	paragraphs	The collection of paragraphs.

+ [NetAF.Interpretation](#)

Returns

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	The index of the next paragraph.

Implements

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))
+ **NetAF.Commands.**

Persistence

([NetAF.Commands.Persistence.html](#))

+ **NetAF.Commands.Region**

Map

([NetAF.Commands.RegionMap.html](#))

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

- **NetAF.Conversations.**

Instructions

([NetAF.Conversations.Instructions.html](#))

ByCallback

([NetAF.Conversations.Instructions.ByCallback.html](#))

First

([NetAF.Conversations.Instructions.First.html](#))

GoTo

([NetAF.Conversations.Instructions.GoTo.html](#))

IEndOfParagraphInstruction

([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

Jump

([NetAF.Conversations.Instructions.Jump.html](#))

Last

([NetAF.Conversations.Instructions.Last.html](#))

Next

([NetAF.Conversations.Instructions.Next.html](#))

Previous

([NetAF.Conversations.Instructions.Previous.html](#))

Repeat

([NetAF.Conversations.Instructions.Repeat.html](#))

ToName

([NetAF.Conversations.Instructions.ToName.html](#))

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

Class GoTo

An end of paragraph instruction that shifts paragraphs based on an absolute index.

Filter by title

Inheritance

+ **NetAF.Commands.**

↳ **object** (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ **GoTo**

(**NetAF.Commands.Persistence**)

Implements

+ **NetAF.Commands.Region**

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

Map

Inherited Members

(**NetAF.Commands.RegionMap**)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Commands.Scene**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

(**NetAF.Conversations.html**)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Instructions

Name: [IEndOfParagraphInstruction](#) ([NetAF.Conversations.html](#)).Instructions ([NetAF.Conversations.Instructions.html](#))

Assembly: NetAF.dll

ByCallback

Syntax

(**NetAF.Conversations.Instructions**)

First

p(**NetAF.Conversations.Instructions**).EndOfParagraphInstruction

GoTo

(**NetAF.Conversations.Instructions**.

IEndOfParagraphInstruction

(**NetAF.Conversations.Instructions**.

Jump

(**NetAF.Conversations.Instructions**.

Last

(**NetAF.Conversations.Instructions**.

An end of paragraph instruction that shifts paragraphs based on an absolute index.

Next

Declaration

(**NetAF.Conversations.Instructions**.

Previous

p(**NetAF.Conversations.Instructions**).Instructions.

Repeat

(**NetAF.Conversations.Instructions**.

Parameters

ToName

Type	Name	Description
NetAF.Extensions (https://learn.microsoft.com/dotnet/api/system.int32)	index	The index of the next paragraph.

(**NetAF.Extensions.html**)

+ **NetAF.Interpretation**

(**NetAF.Interpretation.html**)

Properties

Index

Get the index.



Declaration

+ NetAF.Commands.

Persistence Index { get; }

(NetAF.Commands.Persistence.html)

Property Value

+ NetAF.Commands.Region

Type

(NetAF.Commands.RegionMap)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Description

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Methods

(NetAF.Conversations.html)

- NetAF.Conversations.

GetIndexOfNext(Paragraph, Paragraph[])

Instructions

Get (NetAF.Conversations.Instruction)

By Callback

(NetAF.Conversations.Instructions.

First
public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)
(NetAF.Conversations.Instructions.)

GoTo

Parameters
(NetAF.Conversations.Instructions.

Type

IEndOfParagraphInstruction

(NetAF.Conversations.Instructions.

Name

Description

Paragraph (NetAF.Conversations.Paragraph.html)

current

The current paragraph.

Paragraph (NetAF.Conversations.Instructions.

Paragraph (NetAF.Conversations.Paragraph.html)[]

paragraphs

The collection of paragraphs.

Returns
(NetAF.Conversations.Instructions.

Next

Type

NetAF.Conversations.Instructions.

Description

Previous

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

(NetAF.Conversations.Instructions.)

Repeat

(NetAF.Conversations.Instructions.

Implements

IToName

(NetAF.Conversations.Instructions.

IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

▼

- + **NetAF.Commands.**
 Persistence
 ([NetAF.Commands.Persistence.html](#))
- + **NetAF.Commands.Region**
 Map
 ([NetAF.Commands.RegionMap.html](#))
- + **NetAF.Commands.Scene**
 ([NetAF.Commands.Scene.html](#))
- + **NetAF.Conversations**
 ([NetAF.Conversations.html](#))
- **NetAF.Conversations.**
 Instructions
 ([NetAF.Conversations.Instructions.html](#))
 - ByCallback
 - ([NetAF.Conversations.Instructions.ByCallback.html](#))
 - First
 - ([NetAF.Conversations.Instructions.First.html](#))
 - GoTo
 - ([NetAF.Conversations.Instructions.GoTo.html](#))
 - IEndOfParagraphInstruction
 - ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))
 - Jump
 - ([NetAF.Conversations.Instructions.Jump.html](#))
 - Last
 - ([NetAF.Conversations.Instructions.Last.html](#))
 - Next
 - ([NetAF.Conversations.Instructions.Next.html](#))
 - Previous
 - ([NetAF.Conversations.Instructions.Previous.html](#))
 - Repeat
 - ([NetAF.Conversations.Instructions.Repeat.html](#))
 - ToName
 - ([NetAF.Conversations.Instructions.ToName.html](#))
- + **NetAF.Extensions**
 ([NetAF.Extensions.html](#))
- + **NetAF.Interpretation**
 ([NetAF.Interpretation.html](#))

Interface IEndOfParagraphInstruction

Represents an instruction to be carried out at the end of a paragraph.

Filter by title

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html).Instructions (NetAF.Conversations.Instructions.html)

Assembly: NetAF.dll

(NetAF.Commands.Persistence)

Syntax

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Methods

+ NetAF.Conversations

(NetAF.Conversations.html)

GetIndexOfNext(Paragraph, Paragraph[])

- NetAF.Conversations.

Get the index of the next paragraph.

Instructions

(NetAF.Conversations.Instruct

Declaration

ByCallback

i(NetAF.Conversations.Instructions. current, Paragraph[] paragraphs)

First

(NetAF.Conversations.Instructions.
Parameters
GoTo

Type	Name	Description
NetAF.Conversations.Instructions. IEndOfParagraphInstruction Paragraph (NetAF.Conversations.Paragraph.html) (NetAF.Conversations.Instructions.)	current	The current paragraph.
Paragraph (NetAF.Conversations.Paragraph.html)[] (NetAF.Conversations.Instructions.	paragraphs	The collection of paragraphs.

Last

Returns

Type	Description
Next (NetAF.Conversations.Instructions. int (https://learn.microsoft.com/dotnet/api/system.int32)	The index of the next paragraph.

Previous

(NetAF.Conversations.Instructions.

Repeat

(NetAF.Conversations.Instructions.

ToName

(NetAF.Conversations.Instructions.

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Class Jump

An end of paragraph instruction that shifts paragraphs based on a delta.

Filter by title

Inheritance

(NetAF.Commands.Persistence)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.Region**

Map

Implements

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

Inherited Members

NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

(NetAF.Conversations.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

(NetAF.Conversations.Instruct

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

ByCallback

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html).Instructions (NetAF.Conversations.Instructions.html)

(NetAF.Conversations.Instructions.

Assembly: NetAF.dll

First

Syntax

`(NetAF.Conversations.Instructions.`

 GoTo

`p(NetAF.Conversations.Instructions$EndOfParagraphInstruction`

 IEndOfParagraphInstruction

`(NetAF.Conversations.Instructions.`

 Jump

`(NetAF.Conversations.Instructions.`

 Last

`(NetAF.Conversations.Instructions.`

Jump(int)

 Next

`(NetAF.Conversations.Instructions.`

An end of paragraph instruction that shifts paragraphs based on a delta.

 Previous

Declaration: (NetAF.Conversations.Instructions.

 Repeat

`p(NetAF.Conversations.Instructions.`

 ToName

`(NetAF.Conversations.Instructions.`

Parameters

+ **NetAF.Extensions**

Type

(NetAF.Extensions.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Name	Description
<i>delta</i>	The delta to shift paragraphs by.

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

Properties

Delta

Get the delta.



Declaration

```
(NetAF.Commands.Persistence)
    public int Delta { get; }
```

+ NetAF.Commands.Region

Map

Property Value

```
(NetAF.Commands.RegionMap)
```

Type

+ NetAF.Commands.Scene

```
int (https://learn.microsoft.com/dotnet/api/system.int32)
```

```
(NetAF.Commands.Scene.html)
```

+ NetAF.Conversations

```
(NetAF.Conversations.html)
```

Methods

NetAF.Conversations.

Instructions

```
(NetAF.Conversations.Instructions)
```

GetIndexOfNext(Paragraph, Paragraph[])

ByCallback

Get the index of the next paragraph.

```
(NetAF.Conversations.Instructions.
```

Declaration

```
(NetAF.Conversations.Instructions.
```

```
public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)
```

```
(NetAF.Conversations.Instructions.
```

IEndOfParagraphInstruction

Parameters

```
(NetAF.Conversations.Instructions.
```

Type

```
Jump
```

```
(NetAF.Conversations.Instructions.
```

Paragraph

```
(NetAF.Conversations.Paragraph.html)
```

End

```
(NetAF.Conversations.Instructions.
```

```
Paragraph (NetAF.Conversations.Paragraph.html)[]
```

Next

```
(NetAF.Conversations.Instructions.
```

Returns

Previous

```
Type
```

```
NetAF.Conversations.Instructions.
```

Repeat

```
int (https://learn.microsoft.com/dotnet/api/system.int32)
```

```
(NetAF.Conversations.Instructions.
```

ToName

```
(NetAF.Conversations.Instructions.
```

Implements

+ NetAF.Extensions

IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

```
(NetAF.Extensions.html)
```

+ NetAF.Interpretation

```
(NetAF.Interpretation.html)
```

+ NetAF.Logic

▼

(NetAF.Commands.Persistence.html)

- + **NetAF.Commands.Region**
Map
(NetAF.Commands.RegionMap.html)
- + **NetAF.Commands.Scene**
(NetAF.Commands.Scene.html)
- + **NetAF.Conversations**
(NetAF.Conversations.html)
- **NetAF.Conversations.**
Instructions
(NetAF.Conversations.Instruct

ByCallback
(NetAF.Conversations.Instructions.
First
(NetAF.Conversations.Instructions.
GoTo
(NetAF.Conversations.Instructions.
IEndOfParagraphInstruction
(NetAF.Conversations.Instructions.
Jump
(NetAF.Conversations.Instructions.
Last
(NetAF.Conversations.Instructions.
Next
(NetAF.Conversations.Instructions.
Previous
(NetAF.Conversations.Instructions.
Repeat
(NetAF.Conversations.Instructions.
ToName
(NetAF.Conversations.Instructions.

- + **NetAF.Extensions**
(NetAF.Extensions.html)
- + **NetAF.Interpretation**
(NetAF.Interpretation.html)
- + **NetAF.Logic**

Class Last

An end of paragraph instruction that shifts paragraphs to the end.

Filter by title

Inheritance

+ [NetAF.Commands.RegionMap](#) (https://learn.microsoft.com/dotnet/api/system.object)

Map

([NetAF.Commands.RegionMap](#))

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

+ [NetAF.Commands.Scene](#) (https://learn.microsoft.com/dotnet/api/system.object)

Inherited Members

([NetAF.Commands.Scene.html](#))

object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

+ [NetAF.Conversations](#) (https://learn.microsoft.com/dotnet/api/system.object)

Instructions

object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

object.ToString() (https://learn.microsoft.com/dotnet/api/system.object.tostring)

([NetAF.Conversations.Instructions](#))

Namespace: NetAF ([NetAF.html](#)).Conversations ([NetAF.Conversations.html](#)).Instructions ([NetAF.Conversations.Instructions.html](#))

First

Assembly: NetAF.dll

([NetAF.Conversations.Instructions](#))

Syntax

GoTo

([NetAF.Conversations.Instructions](#))

plEndOfParagraphInstruction : IEndOfParagraphInstruction

([NetAF.Conversations.Instructions](#))

Jump

([NetAF.Conversations.Instructions](#))

Last

Methods

([NetAF.Conversations.Instructions](#))

Next

([NetAF.Conversations.Instructions](#))

GetIndexOfNext(Paragraph, Paragraph[])

Previous

([NetAF.Conversations.Instructions](#))

Get the index of the next paragraph.

Repeat

([NetAF.Conversations.Instructions](#))

ToName

public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)

+ [NetAF.Extensions](#)

([NetAF.Extensions.html](#))

Type	Name	Description
+ NetAF.Interpretation		
(NetAF.Interpretation.html)		

Paragraph ([NetAF.Conversations.Paragraph.html](#))

current

The current paragraph.

+ [NetAF.Logic](#)

Paragraph ([NetAF.Conversations.Paragraph.html](#))[]

paragraphs

The collection of paragraphs.

([NetAF.Logic.html](#))

Returns

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	The index of the next paragraph.

Implements

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))
+ **NetAF.Commands.Region**

Map

([NetAF.Commands.RegionMap](#))

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

- **NetAF.Conversations.**

Instructions

([NetAF.Conversations.Instruct](#))

ByCallback

([NetAF.Conversations.Instructions.](#)

First

([NetAF.Conversations.Instructions.](#)

GoTo

([NetAF.Conversations.Instructions.](#)

IEndOfParagraphInstruction

([NetAF.Conversations.Instructions.](#)

Jump

([NetAF.Conversations.Instructions.](#)

Last

([NetAF.Conversations.Instructions.](#)

Next

([NetAF.Conversations.Instructions.](#)

Previous

([NetAF.Conversations.Instructions.](#)

Repeat

([NetAF.Conversations.Instructions.](#)

ToName

([NetAF.Conversations.Instructions.](#)

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

([NetAF.Logic.html](#))

Class Next

An end of paragraph instruction that shifts paragraphs to the next paragraph.

Filter by title

Inheritance

+ NetAF.Commands.Region

↳ **Map** (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ **Next**
(NetAF.Commands.RegionMap)

Implements

+ NetAF.Commands.Scene

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))
(NetAF.Commands.Scene.html)

Inherited Members

+ NetAF.Conversations

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
(NetAF.Conversations.html)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

By Callback

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

First

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html).Instructions (NetAF.Conversations.Instructions.html)
(NetAF.Conversations.Instructions)

Assembly: NetAF.dll

Goto

Syntax

(NetAF.Conversations.Instructions.

IEndOfParagraphInstruction

public class IEndOfParagraphInstruction : EndOfParagraphInstruction

Jump

(NetAF.Conversations.Instructions.

Last

(NetAF.Conversations.Instructions.

Methods

Next

(NetAF.Conversations.Instructions.

Previous

GetIndexOfNext(Paragraph, Paragraph[])

(NetAF.Conversations.Instructions.

Repeat

Get the index of the next paragraph.

(NetAF.Conversations.Instructions.

Declaration

(NetAF.Conversations.Instructions.

public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)

+ NetAF.Extensions

(NetAF.Extensions.html)

Parameters

+ NetAF.Interpretation

Type
(NetAF.Interpretation.html)

Paragraph ([NetAF.Conversations.Paragraph.html](#))

Name

Description

+ NetAF.Logic

(NetAF.Logic.html)

current

The current paragraph.

Paragraphs ([NetAF.Conversations.Paragraph.html](#))[]

paragraphs

The collection of paragraphs.

... - - - - -

Class Previous

An end of paragraph instruction that shifts paragraphs to the previous paragraph.

Filter by title

Inheritance

Map

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ Previous

+ **NetAF.Commands.Scene**

Implements

[\(NetAFCommands.Scene.html\)](#)

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

+ **NetAF.Conversations**

Inherited Members

[\(NetAFConversations.html\)](#)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

NetAF.Conversations.

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object-object)))

[\(NetAFConversations.Instruct](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

↳ ByCallback

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

[\(NetAFConversations.Instruction](#)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

[\(NetAFConversations.Instruc](#)

Namespace: NetAF ([NetAF.html](#)).Conversations ([NetAF.Conversations.html](#)).Instructions ([NetAF.Conversations.Instructions.html](#))

↳ Goto

Assembly: NetAF.dll

[\(NetAFConversations.Instruc](#)

Syntax

[IEndOfParagraphInstruction](#)

[\(NetAFConversations.Instruc](#)

public sealed class Previous : IEndOfParagraphInstruction

[\(NetAFConversations.Instruc](#)

Last

[\(NetAFConversations.Instruc](#)

Next

[\(NetAFConversations.Instruc](#)

Methods

[\(NetAFConversations.Instruc](#)

Previous

[\(NetAFConversations.Instruc](#)

GetIndexOfNext(Paragraph, Paragraph[])

[Repeat](#)

[\(NetAFConversations.Instruc](#)

Get the index of the next paragraph.

ToName

Declaration

[\(NetAFConversations.Instruc](#)

+ **NetAF.Extensions**

public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)

[\(NetAFExtensions.html\)](#)

+ **NetAF.Interpretation**

Parameters

[\(NetAFInterpretation.html\)](#)

Type

Name

Description

+ **NetAF.Logic**

Paragraph ([NetAFConversations.Paragraph.html](#))

[\(NetAFLogic.html\)](#)

current

The current paragraph.

Paragraph ([NetAFConversations.Paragraph.html](#))[]

paragraphs

The collection of paragraphs.

+ **NetAF.Logic.Callbacks**

Returns

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	The index of the next paragraph.

Implements

Map

IEndOfParagraphInstruction ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))
(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

- NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instruct](#)

ByCallback

[\(NetAF.Conversations.Instructions.](#)

First

[\(NetAF.Conversations.Instructions.](#)

GoTo

[\(NetAF.Conversations.Instructions.](#)

IEndOfParagraphInstruction

[\(NetAF.Conversations.Instructions.](#)

Jump

[\(NetAF.Conversations.Instructions.](#)

Last

[\(NetAF.Conversations.Instructions.](#)

Next

[\(NetAF.Conversations.Instructions.](#)

Previous

[\(NetAF.Conversations.Instructions.](#)

Repeat

[\(NetAF.Conversations.Instructions.](#)

ToName

[\(NetAF.Conversations.Instructions.](#)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

Class Repeat

An end of paragraph instruction that repeats.

Filter by title

Inheritance

(NetAF.Commands.RegionMap)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAFCommands.Scene**

(NetAFCommands.Scene.html)

Implements

IEndOfParagraphInstructions ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

Inherited from **Object**

(NetAFConversations.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

Instructions

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

ByCallback

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

First

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

GoTo

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html).Instructions (NetAF.Conversations.Instructions.html)

Assembly: NetAF.dll

IEndOfParagraphInstruction

Syntax

Jump

(NetAFConversations.Repetitions.IEndOfParagraphInstruction)

Last

(NetAF.Conversations.Instructions.)

Next

(NetAF.Conversations.Instructions.)

Previous

Methods

(NetAF.Conversations.Instructions.)

Repeat

GetIndexOfNext(Paragraph, Paragraph[])

(NetAF.Conversations.Instructions.)

ToName

Get the index of the next paragraph.

(NetAF.Conversations.Instructions.)

Declaration

+ **NetAF.Extensions**

(NetAF.Extensions.html)

public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)

+ **NetAF.Interpretation**

(NetAFInterpretation.html)

Parameters

+ **NetAF.Logic**

(NetAFLogic.html)

Paragraph ([NetAF.Conversations.Paragraph.html](#))

Name

Description

current

The current paragraph.

paragraphs

The collection of paragraphs.

+ **NetAF.Logic.Callbacks**

Paragraph ([NetAF.Conversations.Paragraph.html](#))[]

(NetAFLogic.Callbacks.html)

Returns

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	The index of the next paragraph.

Implements

[IEndOfParagraphInstruction](#) ([NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html](#))

+ **NetAF.Commands.Scene**

[\(NetAF.Commands.Scene.html\)](#)

+ **NetAF.Conversations**

[\(NetAF.Conversations.html\)](#)

- **NetAF.Conversations.**

Instructions

[\(NetAF.Conversations.Instruct](#)

ByCallback

[\(NetAF.Conversations.Instructions.](#)

First

[\(NetAF.Conversations.Instructions.](#)

GoTo

[\(NetAF.Conversations.Instructions.](#)

IEndOfParagraphInstruction

[\(NetAF.Conversations.Instructions.](#)

Jump

[\(NetAF.Conversations.Instructions.](#)

Last

[\(NetAF.Conversations.Instructions.](#)

Next

[\(NetAF.Conversations.Instructions.](#)

Previous

[\(NetAF.Conversations.Instructions.](#)

Repeat

[\(NetAF.Conversations.Instructions.](#)

ToName

[\(NetAF.Conversations.Instructions.](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

Class ToName

An end of paragraph instruction that shifts paragraphs based on a name.

Filter by title

Inheritance

+ [NetAF.Commands.Scene](#) (https://learn.microsoft.com/dotnet/api/system.object)
ToName (NetAF.Commands.Scene.html)

Implements

+ [NetAF.Conversations](#)
IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

Inherited Members

- [NetAF.Conversations](#).

object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

(NetAF.Conversations.Instruct
object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object))
ByCallback (NetAF.Conversations.Instructions)

object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

First (NetAF.Conversations.Instructions)

object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

object.ToString() (https://learn.microsoft.com/dotnet/api/system.object.tostring)
(NetAF.Conversations.Instructions)

Namespace: NetAF (NetAF.html).Conversations (NetAF.Conversations.html).Instructions (NetAF.Conversations.Instructions.html)
IEndOfParagraphInstruction

Assembly: NetAF.dll

(NetAF.Conversations.Instructions).

Syntax

Jump
(NetAF.Conversations.Instructions.
public sealed class ToName : IEndOfParagraphInstruction
(NetAF.Conversations.Instructions.

Next

(NetAF.Conversations.Instructions.
Previous

(NetAF.Conversations.Instructions.

Repeat

ToName(string)

(NetAF.Conversations.Instructions.

ToName

An end of paragraph instruction that shifts paragraphs based on a name.

(NetAF.Conversations.Instructions.

Declaration

+ [NetAF.Extensions](#)

(NetAF.Extensions.html)
public ToName(string name)

+ [NetAF.Interpretation](#)

(NetAF.Interpretation.html)

+ [NetAF.Logic](#)

(NetAF.Logic.html)
string (https://learn.microsoft.com/dotnet/api/system.string) name The name of the paragraph to jump to.

+ [NetAF.Logic.Callbacks](#)

(NetAF.Logic.Callbacks.html)

+ [NetAF.Logic.Configuration](#)

Properties

Name

Get the name of the paragraph to jump to.

Declaration
·

+ NetAF.Commands.Scene

```
public string Name { get; }
```

(NetAF.Commands.Scene.html)

Properties

NetAF.Conversations

Type	Description
- NetAF.Conversations	string (https://learn.microsoft.com/dotnet/api/system.string)

Instructions

(NetAF.Conversations.Instruct

ByCallback

Methods

NetAF.Conversations.Instructions.

First

(NetAF.Conversations.Instructions.

GetIndexOfNext(Paragraph, Paragraph[])

(NetAF.Conversations.Instructions.

Get the index of the next paragraph.

IEndOfParagraphInstruction

Declaration
·

Jump

(NetAF.Conversations.Instructions.

public int GetIndexOfNext(Paragraph current, Paragraph[] paragraphs)

Last

(NetAF.Conversations.Instructions.

Parameters

Next

Type	Name	Description
NetAF.Conversations.Instructions.		
Previous		

Paragraph (NetAF.Conversations.Paragraph.html)

current

The current paragraph.

Repeat

Paragraph (NetAF.Conversations.Paragraph.html)[]

paragraphs

The collection of paragraphs.

ToName

Returns
·

(NetAF.Conversations.Instructions.

Type

+ NetAF.Extensions

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Description

The index of the next paragraph.

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Implements

IEndOfParagraphInstruction (NetAF.Conversations.Instructions.IEndOfParagraphInstruction.html)

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

▼

- + **NetAF.Commands.Scene**
[\(NetAF.Commands.Scene.html\)](#)
- + **NetAF.Conversations**
[\(NetAF.Conversations.html\)](#)
- **NetAF.Conversations.**
Instructions
[\(NetAF.Conversations.Instruct](#)
 - ByCallback
 - (NetAF.Conversations.Instructions.
 - First
 - (NetAF.Conversations.Instructions.
 - GoTo
 - (NetAF.Conversations.Instructions.
 - IEndOfParagraphInstruction
 - (NetAF.Conversations.Instructions.
 - Jump
 - (NetAF.Conversations.Instructions.
 - Last
 - (NetAF.Conversations.Instructions.
 - Next
 - (NetAF.Conversations.Instructions.
 - Previous
 - (NetAF.Conversations.Instructions.
 - Repeat
 - (NetAF.Conversations.Instructions.
 - ToName
 - (NetAF.Conversations.Instructions.
- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- + **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
- + **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)
- + **NetAF.Logic.Configuration**

Namespace NetAF.Extensions

Classes

Filter by title

[NetAF.Commands.Global.html](#) (NetAF.Extensions.CommandHelpExtensions.html)

+ [NetAF.Commands.](#)

Persistence

[NetAF.Commands.Persistence.html](#) (NetAF.Extensions.DirectionExtensions.html)

+ [NetAF.Commands.Region](#)

Map

[NetAF.Commands.RegionMap.html](#) (NetAF.Extensions.StringBuilderExtensions.html)

+ [NetAF.Commands.Scene](#)

Scene

[NetAF.Commands.Scene.html](#) (NetAF.Commands.Scene.html)

[NetAF.Extensions.StringExtensions.html](#) (NetAF.Extensions.StringExtensions.html)

Includes extension methods for strings.

+ [NetAF.Conversations.](#)

Instructions

(NetAF.Conversations.Instruct

- [NetAF.Extensions](#)

(NetAF.Extensions.html)

CommandHelpExtensions

(NetAF.Extensions.CommandHelpExtens

DirectionExtensions

(NetAF.Extensions.DirectionExtens

StringBuilderExtensions

(NetAF.Extensions.StringBuilderEx

StringExtensions

(NetAF.Extensions.StringExtension

+ [NetAF.Interpretation](#)

(NetAF.Interpretation.html)

+ [NetAF.Logic](#)

(NetAF.Logic.html)

+ [NetAF.Logic.Callbacks](#)

(NetAF.Logic.Callbacks.html)

Class CommandHelpExtensions

Provides extension methods for CommandHelp.

Filter by title

Inheritance

+ **NetAF.Commands.**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

Persistence

↳ CommandHelpExtensions

(NetAF.Commands.Persistence.html)

Inherited Members

+ **NetAF.Commands.Region**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

Map

(NetAF.Commands.RegionMap.html)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Commands.Scene**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

(NetAF.Commands.Scene.html)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Conversations**

Namespace: NetAF ([NetAF.html](#)).Extensions ([NetAF.Extensions.html](#))

Instructions

Assembly: NetAF.dll

(NetAF.Conversations.Instruct.html)

Syntax

- **NetAF.Extensions**

↳ public static class CommandHelpExtensions

(NetAF.Extensions.html)

CommandHelpExtensions

(NetAF.Extensions.CommandHelp.html)

DirectionExtensions

(NetAF.Extensions.DirectionExtensions.html)

StringBuilderExtensions

(NetAF.Extensions.StringBuilderExtensions.html)

FormattedToDisplayShortcut(CommandHelp)

(NetAF.Extensions.StringExtension.html)

Returns this CommandHelp formatted to display command in the format Command/Shortcut.

+ **NetAF.Interpretation**

Declaration

(NetAF.Interpretation.html)

+ **NetAF.Logic**

↳ public static CommandHelp FormattedToDisplayShortcut(this CommandHelp value)

(NetAF.Logic.html)

NetAF.Logic.Callbacks

Type: **(NetAF.Logic.Callbacks.html)**

+ **NetAF.Logic.Configuration**

↳ public static ConfigurationCommandHelp ConfigurationCommandHelp.html

(NetAF.Logic.Configuration.html)

Returns

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

Type	Name	Description
(NetAF.Logic.Configuration.html)	value	The value.

Type	Description
CommandHelp (NetAF.Commands.CommandHelp.html)	The formatted CommandHelp.

FormattedToDisplayShortcutAndVariable(CommandHelp)

Returns this CommandHelp formatted to display command in the format Command/Shortcut ____.

+ NetAF.Commands.

Declaration

Persistence

(NetAF.Commands.Persistence)

```
public static CommandHelp FormattedToDisplayShortcutAndVariable(this CommandHelp val
```

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap)

Parameters

+ Type **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

CommandHelp (NetAF.Commands.CommandHelp.html)

Name

Description

value

The value.

+ NetAF.Conversations

Return **(NetAF.Conversations.html)**

+ Type **NetAF.Conversations.**

Instructions

CommandHelp (NetAF.Commands.CommandHelp.html)

Description

The formatted CommandHelp.

(NetAF.Conversations.Instruct

- NetAF.Extensions

(NetAF.Extensions.html)

CommandHelpExtensions

(NetAF.Extensions.CommandHelpExtensi

DirectionExtensions

(NetAF.Extensions.DirectionExtensi

StringBuilderExtensions

(NetAF.Extensions.StringBuilderExt

StringExtensions

(NetAF.Extensions.StringExtension

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Class DirectionExtensions

Provides extension versions for Directions.

Filter by title

Inheritance

Persistence

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
(NetAF.Commands.Persistence)
↳ DirectionExtensions

+ NetAF.Commands.Region

Map

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
(NetAF.Commands.RegionMap)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
(NetAF.Commands.Scene.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)
(NetAF.Conversations.html)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Name [Instructions](#) ([NetAF.html](#)).Extensions ([NetAF.Extensions.html](#))

Assembly [NetAF](#)

Syntax

NetAF.Extensions

(NetAF.Extensions.html)

```
public static class DirectionExtensions  
    CommandHelpExtensions
```

(NetAF.Extensions.CommandHelp)

DirectionExtensions

(NetAF.Extensions.DirectionExtens

StringBuilderExtensions

(NetAF.Extensions.StringBuilderEx

StringExtensions

Inverse([Direction](#)) [StringExtension](#)

+ NetAF.Interpretation

Get an inverse direction.

(NetAF.Interpretation.html)

Declaration

+ NetAF.Logic

(NetAF.Logic.html)

Direction Inverse(this [Direction](#) value)

+ NetAF.Logic.Callbacks

Parameters

(NetAF.Logic.Callbacks.html)

Type

NetAF.Logic.Configuration

Direction ([NetAF.Logic.Configuration.html](#))

Name	Description
value	The direction.

+ NetAF.Logic.Modes

Returns

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

Type	Description
Direction (NetAF.Assets.Locations.Direction.html)	The inverse direction.

▼

Persistence

(NetAF.Commands.Persistence.html)

- + NetAF.Commands.RegionMap
(NetAF.Commands.RegionMap.html)
- + NetAF.Commands.Scene
(NetAF.Commands.Scene.html)
- + NetAF.Conversations
(NetAF.Conversations.html)
- + NetAF.Conversations.Instructions
(NetAF.Conversations.Instructions.html)
- NetAF.Extensions
(NetAF.Extensions.html)
 - CommandHelpExtensions
(NetAF.Extensions.CommandHelpExtensions.html)
 - DirectionExtensions
(NetAF.Extensions.DirectionExtensions.html)
 - StringBuilderExtensions
(NetAF.Extensions.StringBuilderExtensions.html)
 - StringExtensions
(NetAF.Extensions.StringExtensions.html)
- + NetAF.Interpretation
(NetAF.Interpretation.html)
- + NetAF.Logic
(NetAF.Logic.html)
- + NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)
- + NetAF.Logic.Configuration
(NetAF.Logic.Configuration.html)
- + NetAF.Logic.Modes
(NetAF.Logic.Modes.html)
- + NetAF.Persistence
(NetAF.Persistence.html)

Class StringBuilderExtensions

Provides extension methods for `StringBuilder`.

Filter by title

Inheritance

+ **NetAF.Commands.Persistence**

↳ `Object` (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ `StringBuilderExtensions`

+ **NetAF.Commands.Region**

Inherited Members

+ **NetAF.Commands.RegionMap**

`object.Equals(object)` ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Commands.Scene**

`object.Equals(object, object)` ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Commands.Scene.html](#))

`object.GetHashCode()` (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

`object.GetType()` (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Conversations.html](#))

`object.MemberwiseClone()` (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

↳ **NetAF.Conversations**

`object.ReferenceEquals(object, object)` (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

`object.ToString()` (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Conversations.Instruct.html](#))

Assembly: `NetAF.dll`

- **NetAF.Extensions**

Syntax

([NetAF.Extensions.html](#))

```
public static class StringBuilderExtensions  
    (NetAF.Extensions.CommandHelp)  
    DirectionExtensions  
    (NetAF.Extensions.DirectionExtens  
    StringBuilderExtensions  
    (NetAF.Extensions.StringBuilderEx  
    StringExtensions  
    (NetAF.Extensions.StringExtension
```

Methods

+ **EnsureFinishedSentence(StringBuilder)**

([NetAF.Interpretation.html](#))

Ensures that the provided `StringBuilder` instance ends in either ?, ! or .

↳ **NetAF.Logic**

([NetAF.Logic.html](#))

```
public static void EnsureFinishedSentence(this StringBuilder value)
```

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

Parameters

+ **NetAF.Logic.Configuration**

Type
([NetAF.Logic.Configuration.html](#))

`StringBuilder` (<https://learn.microsoft.com/dotnet/api/system.text.stringbuilder>)

+ **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

+ **NetAF.Persistence**

([NetAF.Persistence.html](#))

	Name	Description
	<code>value</code>	The string to finish.

▼

PERSISTENCE

(NetAF.Commands.Persistence.html)

+ **NetAF.Commands.Region**

Map

(NetAF.Commands.RegionMap.html)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instruct

- **NetAF.Extensions**

(NetAF.Extensions.html)

CommandHelpExtensions

(NetAF.Extensions.CommandHelpEx

DirectionExtensions

(NetAF.Extensions.DirectionExtens

StringBuilderExtensions

(NetAF.Extensions.StringBuilderEx

StringExtensions

(NetAF.Extensions.StringExtension

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Class StringExtensions

Provides extension methods for strings.

Filter by title

Inheritance

([NetAF.Commands.Persistence](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ [NetAF.Commands.Region](#)

↳ StringExtensions

Map

Inherited Members

([NetAF.Commands.RegionMap](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ [NetAF.Commands.Scene](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ [NetAF.Conversations](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ [NetAF.Conversations](#)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF ([NetAF.html](#)).Extensions ([NetAF.Extensions.html](#))

- [NetAF.Extensions](#)

Assembly: NetAF.dll

([NetAF.Extensions.html](#))

Syntax

```
CommandHelpExtensions  
  (NetAF.Extensions.CommandHelp)  
public static class StringExtensions  
  DirectionExtensions  
    (NetAF.Extensions.DirectionExtens  
  StringBuilderExtensions  
    (NetAF.Extensions.StringBuilderEx  
  UriExtensions  
    (NetAF.Extensions.StringExtension
```

Methods

+ [NetAF.Interpretation](#)

AddSentence(string, string)
([NetAF.Interpretation.html](#))

Add a sentence to this string.

+ [NetAF.Logic](#)

([NetAF.Logic.html](#))

+ [NetAF.Logic.Callbacks](#)

```
public static string AddSentence(this string value, string other)  
(NetAF.Logic.Callbacks.html)
```

+ [NetAF.Logic.Configuration](#)

([NetAF.Logic.Configuration.html](#))
Type

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	value	The value.
string (https://learn.microsoft.com/dotnet/api/system.string)	other	The other value.

+ [NetAF.Logic.Modes](#)

string (<https://learn.microsoft.com/dotnet/api/system.string>)
([NetAF.Logic.Modes.html](#))

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ [NetAF.Persistence](#)

([NetAF.Persistence.html](#))

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	The concatenated string.

CASEINSENSITIVECONTAINS(string, string)

Returns a value indicating whether the specified substring occurs within this string. This is not case sensitive.

NetAF.Commands.Region

Map

([NetAF.Commands.RegionMap](#))

+ NetAF.Commands.Scene

Parameters

([NetAF.Commands.Scene.html](#))

Type	Name	Description
+ NetAF.Conversations		
string (https://learn.microsoft.com/dotnet/api/system.string)	value	The value.

+ NetAF.Conversations

Instructions

Returns

([NetAF.Conversations.Instruct](#))

Type	Description
- NetAF.Extensions	

bool ([NetAF.Extensions.html](#))

(<https://learn.microsoft.com/dotnet/api/system.boolean>)

True if the value parameter occurs within this string, or if value is the empty string (""); otherwise, false.

DirectionExtensions

([NetAF.Extensions.DirectionExtens](#))

ENSUREFINISHEDSENTENCE(string)

([NetAF.Extensions.StringBuilderEx](#))

Ensures this string is a finished sentence, ending in either ?, ! or .

([StringExtensions](#))

([NetAF.Extensions.StringExtension](#))

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

+ NetAF.Logic

Parameters

([NetAF.Logic.html](#))

Type	Name	Description
+ NetAF.Logic.Callbacks		

string (<https://learn.microsoft.com/dotnet/api/system.string>)

value

The string to finish.

+ NetAF.Logic.Configuration

Returns ([NetAF.Logic.Configuration.html](#))

Type

+ NetAF.Logic.Modes

string (<https://learn.microsoft.com/dotnet/api/system.string>)

([NetAF.Logic.Modes.html](#))

Description

The finished string.

+ NetAF.Persistence

EQUALSEXAMINABLE(string, IExaminable)

Determine if this string equals an IExaminable.

Declaration

```
public static bool EqualsExaminable(this string value, IExaminable examinable)
```



Parameters

Type	Name	Description
+ NetAF.Commands.RegionMap string (https://learn.microsoft.com/dotnet/api/system.string)	value	The value.
IExaminable (NetAF Assets/IExaminable.html)	examinable	The examinable.

+ **NetAF.Commands.Scene**

Returns

Type	Description
+ NetAF.Conversations bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if this string equals the identifier, else false.

+ **NetAF.Conversations.**

Instructions

EqualIdentifier(string, Identifier)

([NetAF.Conversations.Instruct](#))

Determine if this string equals an identifier.

- **NetAF.Extensions**

Declaration

([NetAF.Extensions.html](#))

```
CommandHelpExtensions  
public static bool EqualsIdentifier(this string value, Identifier identifier)  
(NetAF.Extensions.CommandHelp)
```

DirectionExtensions

Parameters

([NetAF.Extensions.DirectionExtens](#))

Type	Name	Description
StringBuilderExtensions (NetAF.Extensions.StringBuilderEx)		
string (https://learn.microsoft.com/dotnet/api/system.string)	value	The value.

+ **NetAF.Interpretation**

Returns

([NetAF.Interpretation.html](#))

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if this string equals the identifier, else false.

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

GetObjectifier(string)

+ **NetAF.Logic.Configuration**

GetNetAFConfigForConfig

([NetAF.Logic.Configuration.html](#))

Declaration

NetAF.Logic.Modes

([NetAF.Logic.Modes.html](#))

```
public static string GetObjectifier(this string word)
```

+ **NetAF.Persistence**

([NetAF.Persistence.html](#))

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	word	The word.

Returns

Type (NetAF.Commands.Persistence)	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	The objectifier.

+ NetAF.Commands.Region

Map

[\(NetAF.Commands.RegionMap\)](#) [InsensitiveEquals\(string, string\)](#)

+ NetAF.Commands.Scene

Compare this string to another, with no case sensitivity.

[\(NetAF.Commands.Scene.html\)](#)

Declaration

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

```
public static bool InsensitiveEquals(this string value, string other)
```

+ NetAF.Conversations.

Instructions

Parameters

Type	Name	Description
- NetAF.Extensions string (https://learn.microsoft.com/dotnet/api/system.string)	value	The value.
- (NetAF.Extensions.html) string (https://learn.microsoft.com/dotnet/api/system.string) CommandHelpExtensions	other	The other value.

[\(NetAF.Extensions.CommandHelp\)](#)

Returns

[DirectionExtensions](#)

Type	Description
(NetAF.Extensions.DirectionExtensions) StringBuilderExtensions bool (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Extensions.StringBuilderExtensions)	The number of lines in the string.

[StringExtensions](#)

[\(NetAF.Extensions.StringExtension\)](#)

IsPlural(string)

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Get if a word is plural.

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Parameters

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

Returns

+ NetAF.Persistence

[\(NetAF.Persistence.html\)](#)

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the word is plural.

IIsVowel(string)

Get a character is a vowel.

NetAF.Commands.Region

Map

([NetAF.Commands.RegionMap](#))

+ NetAF.Commands.Scene

Parameters
([NetAF.Commands.Scene.html](#))

Type	Name	Description
+ NetAF.Conversations		

string (<https://learn.microsoft.com/dotnet/api/system.string>)

value

The value to check.

+ NetAF.Conversations.

Returns

Instructions

Type	Description
+ NetAF.Conversations.Instruct	

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

True if the character is a vowel.

- NetAF.Extensions

([NetAF.Extensions.html](#))

CommandHelpExtensions

LineCount(string)

([NetAF.Extensions.CommandHelp](#))

DirectionExtensions

Determine the number of lines in this string.

([NetAF.Extensions.DirectionExtens](#))

Declaration

StringBuilderExtensions

([NetAF.Extensions.StringBuilderEx](#))

StringExtensions int LineCount(this string value)

([NetAF.Extensions.StringExtension](#))

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

Type	Name	Description
+ NetAF.Logic		

string (<https://learn.microsoft.com/dotnet/api/system.string>)

value

The value.

Returns

+ NetAF.Logic.Callbacks

Type ([NetAF.Logic.Callbacks.html](#))

Type	Description
+ NetAF.Logic.Configuration	

([NetAF.Logic.Configuration.html](#))

+ NetAF.Logic.Modes

RemoveSentenceEnd(string)

([NetAF.Logic.Modes.html](#))

Ensure this string is not a finished sentence, ending in either ?, ! or .

+ NetAF.Persistence

Declaration

([NetAF.Persistence.html](#))

```
public static string RemoveSentenceEnd(this string value)
```

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.Persistence)	value	The string to ensure isn't finished finish.

+ NetAF.Commands.Region

Type	Description
(NetAF.Commands.RegionMap) string (https://learn.microsoft.com/dotnet/api/system.string)	The unfinished string.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

ToDescription(string)

(NetAF.Conversations.html)

Returns this string as a Description.

+ NetAF.Conversations.

Declaration

Instructions

(NetAF.Conversations.Instruct)

```
public static Description ToDescription(this string value)
```

- NetAF.Extensions

(NetAF.Extensions.html)

Type	Name	Description
CommandHelpExtensions (NetAF.Extensions.CommandHelp) string (https://learn.microsoft.com/dotnet/api/system.string) DirectionExtensions	value	The value.

(NetAF.Extensions.DirectionExtensions)

Returns

StringBuilderExtensions

Type	Description
StringExtensions (NetAF.Extensions.StringExtensions)	This string as a description.

+ NetAF.Interpretation

(NetAF.Interpretation.html)

ToIdentifier(string)

+ NetAF.Logic

Returns this string as an Identifier.

(NetAF.Logic.html)

Declaration

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

```
public static Identifier ToIdentifier(this string value)
```

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Parameters

Type	Name	Description
(NetAF.Logic.Modes) string (https://learn.microsoft.com/dotnet/api/system.string)	value	The value.

+ NetAF.Persistence

Returns

(NetAF.Persistence.html)

Type	Description
Identifier (NetAF.Assets.Identifier.html)	This string as an identifier.

ToSentenceCase(string)

Converts a string to sentence case.

Declaration

Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

Parameters

(NetAF.Commands.Scene.html)

Type

+ NetAF.Conversations

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Conversations.html)

+ NetAF.Conversations.

Returns

Instructions

Type

(NetAF.Conversations.Instruct)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

- NetAF.Extensions

(NetAF.Extensions.html)

ToSpeech(string)

CommandHelpExtensions

(NetAF.Extensions.CommandHelp)

DirectionExtensions

Convert a string to speech.

(NetAF.Extensions.DirectionExtens)

Declaration

StringBuilderExtensions

(NetAF.Extensions.StringBuilderEx)

StringExtension<string> ToSpeech(this string value)

(NetAF.Extensions.StringExtension)

Partial API

NetAF.Interpretation

(NetAF.Interpretation.html)

Type

+ NetAF.Logic

String (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Logic.html)

Returns

+ NetAF.Logic.Callbacks

Type (NetAF.Logic.Callbacks.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

Namespace NetAF.Interpretation

Classes

Filter by title

ConversationCommandInterpreter

(NetAF.Interpretation.ConversationCommandInterpreter.html)

Provides an object that can be used for interpreting conversation commands.

+ NetAF.Commands.Region

CustomCommandInterpreter

(NetAF.Interpretation.Regions.CustomCommandInterpreter.html)

Provides an object that can be used for interpreting custom commands.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

FrameCommandInterpreter (NetAF.Interpretation.FrameCommandInterpreter.html)

+ NetAF.Conversations

Provides an object that can be used for interpreting frame commands.

+ NetAF.Conversations.

GlobalCommandInterpreter (NetAF.Interpretation.GlobalCommandInterpreter.html)

Instructions

Provides an object that can be used for interpreting global commands.

+ NetAF.Extensions

InputInterpreter (NetAF.Interpretation.InputInterpreter.html)

Provides an object that can be used for interpreting game input.

- NetAF.Interpretation

(NetAF.Interpretation.html)

InterpretationResult (NetAF.Interpretation.InterpretationResult.html)

ConversationCommand

Represents the result of an interpretation.

(NetAF.Interpretation.Conversation

CustomCommandInterpreter

Interpreters (NetAF.Interpretation.Interpreters.html)

Provides a collection of interpreters.

(NetAF.Interpretation.FrameComm

GlobalCommandInterpreter

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapCommandInterpreter.html)

Interpreters

Provides an interpreter for interpreting region map commands.

InputInterpreter

(NetAF.Interpretation.InputInterpreter

SceneCommandInterpreter (NetAF.Interpretation.SceneCommandInterpreter.html)

Provides an object that can be used for interpreting scene commands.

Interpreters

(NetAF.Interpretation.Interpreters.h

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

Interfaces

IInterpreter (NetAF.Interpretation.IInterpreter.html)

Represents any object that can act as an interpreter for input.



+ NetAF.Commands.

Persistence

(NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Map

(NetAF.Commands.RegionMap.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

- NetAF.Interpretation

(NetAF.Interpretation.html)

ConversationCommand

Interpreter

(NetAF.Interpretation.Conversation

CustomCommandInterpreter

(NetAF.Interpretation.CustomCom

FrameCommandInterpreter

(NetAF.Interpretation.FrameComm

GlobalCommandInterpreter

(NetAF.Interpretation.GlobalComm

IInterpreter

(NetAF.Interpretation.IInterpreter.h

InputInterpreter

(NetAF.Interpretation.InputInterpre

InterpretationResult

(NetAF.Interpretation.Interpretation

Interpreters

(NetAF.Interpretation.Interpreters.h

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

Class ConversationCommandInterpreter

Provides an object that can be used for interpreting conversation commands.

Filter by title

Inheritance

Persistence

↳ [https://learn.microsoft.com/dotnet/api/system.object\)](https://learn.microsoft.com/dotnet/api/system.object)

↳ ConversationCommandInterpreter

+ NetAF.Commands.Region

Implements

Map

IInterpreter (NetAF.Interpretation.IInterpreter.html)

(NetAF.Commands.RegionMap)

Inherited Members

+ NetAF.Commands.Scene

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode\)](https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype\)](https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals\)](https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring\)](https://learn.microsoft.com/dotnet/api/system.object.tostring)

Namespace: NetAF (NetAF.html).Interpretation (NetAF.Interpretation.html)

+ NetAF.Extensions

Assembly: NetAF.dll

(NetAF.Extensions.html)

Syntax

- NetAF.Interpretation

(NetAF.Interpretation.html) ConversationCommandInterpreter : IInterpreter

ConversationCommand

Interpreter

(NetAF.Interpretation.Conversation

CustomCommandInterpreter

(NetAF.Interpretation.CustomCom

FrameCommandInterpreter

(NetAF.Interpretation.FrameCom

GlobalCommandInterpreter

Properties

DefaultSupportedCommands

Get an array of supported commands.

Interpreter

Declaration: <https://learn.microsoft.com/dotnet/api/system.object.get>

<https://learn.microsoft.com/dotnet/api/system.object.get>

InputInterpreter

public static ICommandInterpreter DefaultSupportedCommands { get; }

InterpretationResult

(NetAF.Interpretation.Interpretation

PropertyValue

Interpreters

Type: <https://learn.microsoft.com/dotnet/api/system.object.get>

Description

RegionMapCommandInterpreter

CommandHelp (NetAF.Commands.CommandHelp.html)[]

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

(NetAF.Interpretation.SceneComm

SupportedCommands

Get an array of all supported commands.

Declaration

```
public CommandHelp[] SupportedCommands { get; }
```

Persistence

Property Value

(NetAF.Commands.Persistence)

Type

+ NetAF.Commands.Region

CommandHelp (NetAF.Commands.CommandHelp.html)[]

Description

Map
(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

NetAF.Commands.Scene.html

+ NetAF.Conversations

(NetAF.Conversations.html)

GetContextualCommandHelp(Game)

+ NetAF Conversations

Get contextual command help for a game, based on its current state.

Instructions

Declaration

(NetAF.Conversations.Instruct)

+ NetAF Extensions

public CommandHelp[] GetContextualCommandHelp(Game game)

(NetAF.Extensions.html)

Part of NetAF Interpretation

(NetAF.Interpretation.html)

ConversationCommand
Game (NetAF.Logic.Game.html)
Interpreter

Name

Description

game

The game.

(NetAF.Interpretation.Conversation)
Returns
CustomCommandInterpreter

Type
(NetAF.Interpretation.CustomCom
FrameCommandInterpreter
CommandHelp (NetAF.Commands.CommandHelp.html)[]
(NetAF.Interpretation.FrameComm

Description

The contextual help.

Interpret(string, Game)

(NetAF.Interpretation.IInterpreter.ht

Interpreter string parameter

(NetAF.Interpretation.InputInterpret
Declaration
InterpretationResult

(NetAF.Interpretation.Interpretation
public InterpretationResult Interpret(string input, Game game)
Interpreters

(NetAF.Interpretation.Interpreters.h

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

(NetAF.Interpretation.SceneComm

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>input</i>	The string to interpret.
Game (NetAF.Logic.Game.html)	<i>game</i>	The game.

Returns

Type	Description
Persistence (NetAF.Commands.Persistence)	The result of the interpretation.

+ NetAF.Commands.Region

Map

Implements

[\(NetAF.Commands.RegionMap\)](#)

IInterpreter ([NetAF.Interpretation.IInterpreter.html](#))

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

+ NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instruct](#)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

- NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

ConversationCommand

Interpreter

[\(NetAF.Interpretation.Conversation](#)

CustomCommandInterpreter

[\(NetAF.Interpretation.CustomComr](#)

FrameCommandInterpreter

[\(NetAF.Interpretation.FrameComm](#)

GlobalCommandInterpreter

[\(NetAF.Interpretation.GlobalComm](#)

IInterpreter

[\(NetAF.Interpretation.IInterpreter.ht](#)

InputInterpreter

[\(NetAF.Interpretation.InputInterpre](#)

InterpretationResult

[\(NetAF.Interpretation.Interpretation](#)

Interpreters

[\(NetAF.Interpretation.Interpreters.h](#)

RegionMapCommandInterpreter

[\(NetAF.Interpretation.RegionMapC](#)

SceneCommandInterpreter

[\(NetAF.Interpretation.SceneComm](#)

Class CustomCommandInterpreter

Provides an object that can be used for interpreting custom commands.

Filter by title

Inheritance

+ **NetAF.Commands.Region** (Object) (https://learn.microsoft.com/dotnet/api/system.object)

Map CustomCommandInterpreter

Implements **(NetAF.Commands.RegionMap)**

+ **NetAF.Commands.Scene** (Interpreter.IInterpreter.html)

Implements **(NetAF.Commands.Scene.html)**

+ **NetAF.Conversations** (Object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

(NetAF.Conversations.html)

object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object))

+ **NetAF.Conversations** (InstructionsCode.html)

InstructionsCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

 object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)

 object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

+ **NetAF.Extensions** (Object.ToString.html)

(NetAF.Extensions.html)

Namespace: NetAF (NetAF.html).Interpretation (NetAF.Interpretation.html)

Assembly: NetAF.dll

NetAF.Interpretation

(NetAF.Interpretation.html)

ConversationCommand

Interpreter

(NetAF.Interpretation.Conversation)

 CustomCommandInterpreter

(NetAF.Interpretation.CustomCom

 FrameCommandInterpreter

(NetAF.Interpretation.FrameComm

 GlobalCommandInterpreter

(NetAF.Interpretation.GlobalComm

 Interpreter

Properties

SupportedCommands

Get an array of supported commands.

InputInterpreter

Declaration

(NetAF.Interpretation.InputInterpret

 InterpretationResult

public ICommand[] SupportedCommands { get; }

 Interpreters

(NetAF.Interpretation.Interpreters.h

Property Value

 RegionMapCommandInterpreter

Type

NetAF.Interpretation.RegionMapC

 SceneCommandInterpreter

 CommandHelp (NetAF.Commands.CommandHelp.html)[]

(NetAF.Interpretation.SceneComm

Description

+ **NetAF.Logic**

Methods

GetContextualCommandHelp(Game)

Get contextual command help for a game, based on its current state.

Declaration

+ NetAF.Commands.Region

```
public CommandHelp[] GetContextualCommandHelp(Game game)
```

Map

(NetAF.Commands.RegionMap)

Parameters

+ NetAF.Commands.Scene

```
Type  
(NetAF.Commands.Scene.html)
```

Game (NetAF.Logic.Game.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

Returns

+ Type

Instructions

```
CommandHelp (NetAF.Commands.CommandHelp.html)[]  
(NetAF.Conversations.Instruct)
```

+ NetAF.Extensions

(NetAF.Extensions.html)

- NetAF.Interpretation

Interpret a string.

(NetAF.Interpretation.html)

Declaration

ConversationCommand

Interpreter

```
public InterpretationResult Interpret(string input, Game game)
```

(NetAF.Interpretation.Conversation)

CustomCommandInterpreter

Parameters

(NetAF.Interpretation.CustomCommand)

Type
FrameCommandInterpreter

(NetAF.Interpretation.FrameCommand)

StringGlobalCommandInterpreter

(NetAF.Interpretation.GlobalCommand)

Game (NetAF.Logic.Game.html)

Interpreter

(NetAF.Interpretation.IInterpreter.html)

Returns

InputInterpreter

Type
(NetAF.Interpretation.InputInterpreter)

InterpretationResult

InterpretationResult (NetAF.Interpretation.InterpretationResult.html)

(NetAF.Interpretation.IInterpretation)

Interpreters

(NetAF.Interpretation.Interpreters.html)

RegionCommandInterpreter

(NetAF.Interpretation.RegionMapC)

IInterpreter (NetAF.Interpretation.IInterpreter.html)

SceneCommandInterpreter

(NetAF.Interpretation.SceneCommand)

+ NetAF.Logic

▼

- + **NetAF.Commands.RegionMap**
[\(NetAF.Commands.RegionMap\)](#)
- + **NetAF.Commands.Scene**
[\(NetAF.Commands.Scene.html\)](#)
- + **NetAF.Conversations**
[\(NetAF.Conversations.html\)](#)
- + **NetAF.Conversations.Instructions**
[\(NetAF.Conversations.Instruct](#)
- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
 - ConversationCommand
 - Interpreter
 - [\(NetAF.Interpretation.Conversation\)](#)
 - CustomCommandInterpreter
 - [\(NetAF.Interpretation.CustomComr\)](#)
 - FrameCommandInterpreter
 - [\(NetAF.Interpretation.FrameComm\)](#)
 - GlobalCommandInterpreter
 - [\(NetAF.Interpretation.GlobalComm\)](#)
 - IInterpreter
 - [\(NetAF.Interpretation.IInterpreter.ht\)](#)
 - InputInterpreter
 - [\(NetAF.Interpretation.InputInterpre](#)
 - InterpretationResult
 - [\(NetAF.Interpretation.Interpretation\)](#)
 - Interpreters
 - [\(NetAF.Interpretation.Interpreters.h\)](#)
 - RegionMapCommandInterpreter
 - [\(NetAF.Interpretation.RegionMapC\)](#)
 - SceneCommandInterpreter
 - [\(NetAF.Interpretation.SceneComm\)](#)
- + **NetAF.Logic**

Class FrameCommandInterpreter

Provides an object that can be used for interpreting frame commands.

Filter by title

Inheritance

+ NetAF.Commands.Region

↳ [Object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)

(NetAF.Commands.RegionMap)

Implements

+ NetAF.Commands.Scene

IIInterpreter ([NetAF Interpretation.IIInterpreter.html](#))

(NetAF.Commands.Scene.html)

Inherited Members

+ NetAF.Conversations

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ NetAF Conversations

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ NetAF.Extensions

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF ([NetAF.html](#)).Interpretation ([NetAF.Interpretation.html](#))

- NetAF.Interpretation

Assembly: NetAF.dll

(NetAF.Interpretation.html)

Syntax

```
ConversationCommand  
Interpreter
```

```
public sealed class FrameCommandInterpreter : IInterpreter
```

```
(NetAF.Interpretation.Conversation)
```

```
CustomCommandInterpreter
```

```
(NetAF.Interpretation.CustomComr)
```

```
FrameCommandInterpreter
```

```
(NetAF.Interpretation.FrameComm)
```

```
GlobalCommandInterpreter
```

```
(NetAF.Interpretation.GlobalComm)
```

```
Interpreter
```

Properties

DefaultSupportedCommands

```
(NetAF.Interpretation.IIInterpreter.ht
```

InputInterpreter

Get an array of supported commands.

```
(NetAF.Interpretation.InputInterpret
```

Declaration

```
InterpretationResult
```

```
(NetAF.Interpretation.Interpretation
```

```
public static CommandHelp[] DefaultSupportedCommands { get; }
```

```
(NetAF.Interpretation.Interpreters.h
```

```
RegionMapCommandInterpreter
```

Property Value

```
(NetAF.Interpretation.RegionMapC
```

Type SceneCommandInterpreter

```
(NetAF.Interpretation.SceneComm
```

CommandHelp ([NetAF.Commands.CommandHelp.html](#))[]

+ NetAF.Logic

(NetAF.Logic.html)

Description

SupportedCommands

Get an array of all supported commands.

Declaration

```
public CommandHelp[] SupportedCommands { get; }
```

+ NetAF.Commands.Region

Property Value

Type [NetAF.Commands.RegionMap](#)

Description

+ NetAF.Commands.Scene

([NetAF.Commands.Scene.html](#))

+ NetAF.Conversations

([NetAF.Conversations.html](#))

Methods

+ NetAF.Conversations.

Instructions

GetContextualCommandHelp(Game)

([NetAF.Conversations.Instruct](#))

Get contextual command help for a game, based on its current state.

+ NetAF.Extensions

Declaration

([NetAF.Extensions.html](#))

- NetAF.Interpretation

public CommandHelp[] GetContextualCommandHelp(Game game)

([NetAF.Interpretation.html](#))

ConversationCommand

Parameters

Interpreter

Type [NetAF.Interpretation.Conversation](#)

Name

Description

CustomCommandInterpreter

Game ([NetAF.Logic.Game.html](#))

([NetAF.Interpretation.CustomComr](#))

game

The game.

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>input</i>	The string to interpret.
Game (NetAF.Logic.Game.html)	<i>game</i>	The game.

Returns

+ Type NetAF.Commands.Region	Description
Map InterpretationResult (NetAF.Interpretation.InterpretationResult.html) (NetAF.Commands.RegionMap)	The result of the interpretation.
+ NetAF.Commands.Scene Implements (NetAF.Commands.Scene.html)	
+ NetAF.Conversations (NetAF.Conversations.html)	
+ NetAF.Conversations. Instructions (NetAF.Conversations.Instruct	
+ NetAF.Extensions (NetAF.Extensions.html)	
- NetAF.Interpretation (NetAF.Interpretation.html)	
ConversationCommand Interpreter (NetAF.Interpretation.Conversation CustomCommandInterpreter (NetAF.Interpretation.CustomCom FrameCommandInterpreter (NetAF.Interpretation.FrameComm GlobalCommandInterpreter (NetAF.Interpretation.GlobalComm IInterpreter (NetAF.Interpretation.IInterpreter.h InputInterpreter (NetAF.Interpretation.InputInterpre InterpretationResult (NetAF.Interpretation.Interpretation Interpreters (NetAF.Interpretation.Interpreters.h RegionMapCommandInterpreter (NetAF.Interpretation.RegionMapC SceneCommandInterpreter (NetAF.Interpretation.SceneComm	
+ NetAF.Logic (NetAF.Logic.html)	

Class GlobalCommandInterpreter

Provides an object that can be used for interpreting global commands.

Filter by title

Inheritance Map

↳ **NetAF.Commands.RegionMap** (https://learn.microsoft.com/dotnet/api/system.object)
↳ GlobalCommandInterpreter
+ **NetAF.Commands.Scene**
Implements
 (NetAF.Commands.Scene.html)
IInterpreter (NetAF.Interpretation.IInterpreter.html)
+ **NetAF.Conversations**
Inherited Members
 (NetAF.Conversations.html)
object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))
+ **NetAF.Conversations.**
object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object))
↳ **NetAF.Conversations.MStruct**
object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)
object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)
object.ToString() (https://learn.microsoft.com/dotnet/api/system.object.tostring)
- **NetAF.Interpretation**
Namespace: NetAF (NetAF.html) Interpretation (NetAF.Interpretation.html)
 (NetAF.Interpretation.html)
Assembly: NetAF.dll
 ConversationCommand
Syntax
 Interpreter
 (NetAF.Interpretation.Conversation
 public sealed class GlobalCommandInterpreter : IInterpreter
 CustomCommandInterpreter
 (NetAF.Interpretation.CustomComr
 FrameCommandInterpreter
 (NetAF.Interpretation.FrameComm
 GlobalCommandInterpreter
 (NetAF.Interpretation.GlobalComm
 IInterpreter
 (NetAF.Interpretation.IInterpreter ht
 InputInterpreter
Get an array of supported commands.
 InterpretationResult
Declaration
 (NetAF.Interpretation.Interpretation
 Interpreters
 public static CommandHelp[] DefaultSupportedCommands { get; }
 (NetAF.Interpretation.Interpreters.h
 RegionMapCommandInterpreter
 (NetAF.Interpretation.RegionMapC
Property Value
 SceneCommandInterpreter
Type
 NetAF.Interpretation.SceneComm
+ **NetAF.Logic** (NetAF.Commands.CommandHelp.html)[]

Properties

DefaultSupportedCommands

Get an array of supported commands.
 InterpretationResult
Declaration
 (NetAF.Interpretation.Interpretation
 Interpreters
 public static CommandHelp[] DefaultSupportedCommands { get; }
 (NetAF.Interpretation.Interpreters.h
 RegionMapCommandInterpreter
 (NetAF.Interpretation.RegionMapC

Property Value
 SceneCommandInterpreter

Type
 NetAF.Interpretation.SceneComm

Description

+ **NetAF.Logic** (NetAF.Commands.CommandHelp.html)[]

(NetAF.Logic.html)

↳ **NetAF.Logic Callbacks**

SupportedCommands

Get an array of all supported commands.

Declaration

```
public CommandHelp[] SupportedCommands { get; }
```

Map

Property Value

(NetAF.Commands.RegionMap)

Type

+ NetAF.Commands.Scene

CommandHelp (NetAF.Commands.CommandHelp.html)[]

Description

+ NetAF.Conversations

(NetAF.Conversations.html)

Methods

NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct)

GetContextualCommandHelp(Game)

+ NetAF.Extensions

Get contextual command help for a game, based on its current state.

(NetAF.Extensions.html)

Declaration

- NetAF.Interpretation

(NetAF.Interpretation.html)

```
public CommandHelp GetContextualCommandHelp(Game game)
```

ConversationCommand

Interpreter

Parameters

(NetAF.Interpretation.Conversation)

Type

CustomCommandInterpreter

Name

Description

(NetAF.Interpretation.CustomComr

Game (NetAF.Logic.Game.html)

FrameCommandInterpreter

game

The game.

Returns

GlobalCommandInterpreter

Type

NetAF.Interpretation.GlobalComm

Description

Interpreter

CommandHelp (NetAF.Commands.CommandHelp.html)[]

(NetAF.Interpretation.IInterpreter.h

InputInterpreter

(NetAF.Interpretation.InputInterpret

Interpret(string, Game)

(NetAF.Interpretation.Interpretation

Interpreting.

(NetAF.Interpretation.Interpreters.h

Declaration

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

```
public InterpretationResult Interpret(string input, Game game)
```

SceneCommandInterpreter

(NetAF.Interpretation.SceneComm

Parameters

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic Callbacks

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>input</i>	The string to interpret.
Game (NetAF.Logic.Game.html)	<i>game</i>	The game.

Returns

Type	Description
Map (NetAF.Commands.RegionMap.html)	The result of the interpretation.

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Implements

+ NetAF.Conversations

[IIInterpreter \(NetAF.Interpretation.IIInterpreter.html\)](#)
[\(NetAF.Conversations.html\)](#)

+ NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instruct.html\)](#)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

- NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

ConversationCommand

Interpreter

[\(NetAF.Interpretation.Conversation.html\)](#)

CustomCommandInterpreter

[\(NetAF.Interpretation.CustomCommandInterpreter.html\)](#)

FrameCommandInterpreter

[\(NetAF.Interpretation.FrameCommandInterpreter.html\)](#)

GlobalCommandInterpreter

[\(NetAF.Interpretation.GlobalCommandInterpreter.html\)](#)

IInterpreter

[\(NetAF.Interpretation.IInterpreter.html\)](#)

InputInterpreter

[\(NetAF.Interpretation.InputInterpreter.html\)](#)

InterpretationResult

[\(NetAF.Interpretation.InterpretationResult.html\)](#)

Interpreters

[\(NetAF.Interpretation.Interpreters.html\)](#)

RegionMapCommandInterpreter

[\(NetAF.Interpretation.RegionMapCommandInterpreter.html\)](#)

SceneCommandInterpreter

[\(NetAF.Interpretation.SceneCommandInterpreter.html\)](#)

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

↳ NetAF.Logic Callbacks

Interface IInterpreter

Represents any object that can act as an interpreter for input.

Filter by title

Namespace: NetAF (NetAF.html).Interpretation (NetAF.Interpretation.html)
(NetAF.Commands.RegionMap)

Assembly: NetAF.dll

t [NetAF.Commands.Scene](#)

Syntax

[\(NetAF.Commands.Scene.html\)](#)

public interface IInterpreter

+ [NetAF.Conversations](#)

[\(NetAF.Conversations.html\)](#)

+ [NetAF.Conversations.](#)

Instructions

[\(NetAF.Conversations.Instruct\)](#)

Properties

[\(NetAF.Conversations.Instruct\)](#)

+ [NetAF.Extensions](#)

[SupportedCommands](#)

[\(NetAF.Extensions.html\)](#)

Get an array of all supported commands.

- [NetAF.Interpretation](#)

Declaration

[\(NetAF.Interpretation.html\)](#)

ConversationCommand

CommandHelp[] SupportedCommands { get; }

Interpreter

[\(NetAF.Interpretation.Conversation\)](#)

CustomCommandInterpreter

[\(NetAF.Interpretation.CustomCom\)](#)

Type FrameCommandInterpreter

Description

[\(NetAF.Interpretation.FrameCom\)](#)

CommandHelp ([NetAF.Commands.CommandHelp.html](#))[]

GlobalCommandInterpreter

[\(NetAF.Interpretation.GlobalCom\)](#)

IInterpreter

[\(NetAF.Interpretation.IInterpreter.ht\)](#)

InputInterpreter

[\(NetAF.Interpretation.InputInterpre](#)

InterpretationResult

[\(NetAF.Interpretation.Interpretation](#)

Methods

[GetContextualCommandHelp\(Game\)](#)

[\(NetAF.Interpretation.Interpreta](#)

Interpreters

Get contextual command help for a game, based on its current state.

[\(NetAF.Interpretation.Interpreters.h](#)

Declaration RegionMapCommandInterpreter

[\(NetAF.Interpretation.RegionMapC](#)

SceneObjectCommandInterpreter GetContextualCommandHelp(Game game)

[\(NetAF.Interpretation.SceneCom](#)

Part AF Logic

[\(NetAF.Logic.html\)](#)

Type

Name

Description

+ [NetAF.Logic.Callbacks](#)

[\(NetAF.Logic.Game.html\)](#)

[\(NetAF.Logic.Scene.html\)](#)

game

The game.

Returns

Type	Description
CommandHelp (NetAF.Commands.CommandHelp.html)[]	The contextual help.



Interpret(string, Game)
(NetAF.Commands.RegionMap)
Interpret a string.
+ **NetAF.Commands.Scene**
Declaration
(NetAF.Commands.Scene.html)

+ **NetAF.Conversations** Interpret(string input, Game game)
(NetAF.Conversations.html)

Parameters

Instructions	Name	Description
(NetAF.Conversations.Instruct string (https://learn.microsoft.com/dotnet/api/system.string))	input	The string to interpret.
+ NetAF.Extensions Game (NetAF.Logic.Game.html) (NetAF.Extensions.html)	game	The game.

Returns

NetAF.Interpretation

Type	Description
ConversationCommand InterpretationResult (NetAF.Interpretation.InterpretationResult.html) Interpreter	The result of the interpretation.

(NetAF.Interpretation.Conversation
CustomCommandInterpreter
(NetAF.Interpretation.CustomComr
FrameCommandInterpreter
(NetAF.Interpretation.FrameComm
GlobalCommandInterpreter
(NetAF.Interpretation.GlobalComm
IInterpreter
(NetAF.Interpretation.IInterpreter.ht
InputInterpreter
(NetAF.Interpretation.InputInterpret
InterpretationResult
(NetAF.Interpretation.Interpretation
Interpreters
(NetAF.Interpretation.Interpreters.h
RegionMapCommandInterpreter
(NetAF.Interpretation.RegionMapC
SceneCommandInterpreter
(NetAF.Interpretation.SceneComm

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

NetAF.Logic.Callbacks.html

Class InputInterpreter

Provides an object that can be used for interpreting game input.

Filter by title

Inheritance

+ **NetAF Commands Scene**
↳ [Object](https://learn.microsoft.com/dotnet/api/system.object) ([object.Equals\(object, object\)](https://learn.microsoft.com/dotnet/api/system.object>equals#system-object-equals(system-object-object)))
[\(NetAF.Commands.Scene.html\)](#)
↳ [InputInterpreter](#)

+ **NetAF Conversations**

↳ [\(NetAF.Conversations.html\)](#)
↳ [InputInterpreter.html](#)

Inherited Members

+ **NetAF Conversations.**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))
[\(NetAF.Conversations.Instruct](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object-system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object-system-object-object)))

+ **NetAF Extensions.**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

- **NetAF Interpretation.**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

ConversationCommand
Namespace: NetAF ([NetAF.html](#)).Interpretation ([NetAF.Interpretation.html](#))

Interpreter
Assembly: NetAF.dll

(NetAF.Interpretation.Conversation

Syntax
CustomCommandInterpreter

(NetAF.Interpretation.CustomComr

public sealed class InputInterpreter : IInterpreter

(NetAF.Interpretation.FrameComm

GlobalCommandInterpreter

(NetAF.Interpretation.GlobalComm

IInterpreter

(NetAF.Interpretation.IInterpreter.ht

InputInterpreter(params IInterpreter[])

(NetAF.Interpretation.InputInterpret

Provides an [interpretation result](#) can be used for interpreting game input.

(NetAF.Interpretation.Interpretation

Declaration
Interpreters

(NetAF.Interpretation.Interpreters.h

public InputInterpreter(params IInterpreter[] interpreters)

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

(NetAF.Interpretation.SceneComm

Type

+ **NetAF.Logic**

!Interpreter ([NetAF.Interpretation.IInterpreter.html](#))[]

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

Type	Name	Description
(NetAF.Logic.html)	<i>interpreters</i>	The interpreters.

Properties

SupportedCommands

Get an array of all supported commands.

Declaration

+ **NetAF.Commands.Scene**

```
public CommandHelp[] SupportedCommands { get; }
```

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

Property value

([NetAF.Conversations.html](#))

Type

Description

+ **NetAF.Conversations.**

CommandHelp ([NetAF.Commands.CommandHelp.html](#))

Instructions

([NetAF.Conversations.Instruct](#)

+ **NetAF.Extensions**

Methods

([NetAF.Extensions.html](#))

- **NetAF.Interpretation**

GetContextualCommandHelp(Game)

ConversationCommand

Get contextual command help for a game, based on its current state.

Interpreter

Declaration

([NetAF.Interpretation.Conversation](#)

CustomCommandInterpreter

([NetAF.Interpretation.CustomCommandInterpreter.html](#))

FrameCommandInterpreter

([NetAF.Interpretation.FrameComm](#)

Parameters

GlobalCommandInterpreter

Type [NetAF.Interpretation.GlobalComm](#)

Name

Description

IInterpreter

game

The game.

InputInterpreter

Returns [NetAF.Interpretation.InputInterpret](#)

Type InterpretationResult

Description

([NetAF.Interpretation.Interpretation](#)

CommandHelp ([NetAF.Commands.CommandHelp.html](#))

The contextual help.

([NetAF.Interpretation.Interpreters.h](#)

RegionMapCommandInterpreter

([NetAF.Interpretation.RegionMapC](#)

SceneCommandInterpreter

Interpreter [NetAF.Interpretation.SceneComm](#)

NetAF.Logic

([NetAF.Logic.html](#))

```
public InterpretationResult Interpret(string input, Game game)
```

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>input</i>	The string to interpret.
Game (NetAF.Logic.Game.html)	<i>game</i>	The game.

▼

Returns

+ NetAF.Commands.Scene	Description
(NetAF.Commands.Scene.html) InterpretationResult (NetAF.Interpretation.InterpretationResult.html)	The result of the interpretation.

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

Implements

+ NetAF.Conversations.

IInterpreter (NetAF.Interpretation.IInterpreter.html)

[\(NetAF.Conversations.Instruct](#)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

- NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

ConversationCommand

Interpreter

(NetAF.Interpretation.Conversation

CustomCommandInterpreter

(NetAF.Interpretation.CustomComr

FrameCommandInterpreter

(NetAF.Interpretation.FrameComm

GlobalCommandInterpreter

(NetAF.Interpretation.GlobalComm

IInterpreter

(NetAF.Interpretation.IInterpreter.ht

InputInterpreter

(NetAF.Interpretation.InputInterpret

InterpretationResult

(NetAF.Interpretation.Interpretation

Interpreters

(NetAF.Interpretation.Interpreters.h

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

(NetAF.Interpretation.SceneComm

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Class InterpretationResult

Represents the result of an interpretation.

Filter by title

Inheritance

+ **NetAF.Commands.Scene**

↳ [Object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ InterpretationResult

+ **NetAF.Conversations**

Inherited Members

([NetAF.Conversations.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

Instructions

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Conversations.Instruct.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Extensions.html](#))

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF ([NetAF.html](#)).Interpretation ([NetAF.Interpretation.html](#))

ConversationCommand

Assembly: NetAF.dll

Syntax

```
NetAF.Interpretation.Conversation  
    CustomCommandInterpreter
```

```
public class InterpretationResult  
    FrameCommandInterpreter
```

([NetAF.Interpretation.FrameComm.html](#))

GlobalCommandInterpreter

Constructor

([NetAF.Interpretation.GlobalComm.html](#))

IInterpreter

([NetAF.Interpretation.IInterpreter.html](#))

InputInterpreter

([NetAF.Interpretation.InputInterpreter.html](#))

Represents the result of an interpretation.

InterpretationResult

Declaration

NetAF.Interpretation.Interpretation

Interpreters

```
public InterpretationResult(bool wasInterpretedSuccessfully, ICommand command)
```

RegionMapCommandInterpreter

([NetAF.Interpretation.RegionMapC.html](#))

Parameters

SceneCommandInterpreter

Type	Name	Description
NetAF.Interpretation.SceneCommandInterpreter	wasInterpretedSuccessfully	If interpretation was successful.
NetAF.Logic	command	The command.

+ **NetAF.Logic.Configuration**

Properties

Command

Get the command.

Declaration

+ **NetAF.Commands.Scene**

([NetAFCommands.Scene.html](#))

```
public ICommand Command { get; }
```

+ NetAF.Conversations

([NetAFConversations.html](#))

+ **NetAF.Conversations.**

Description

Instructions

ICommand ([NetAF.Commands.ICommand.html](#))

([NetAFConversations.Instruct.html](#))

+ NetAF.Extensions

([NetAFExtensions.html](#))

Get the interpretation.

([NetAFInterpretation.html](#))

Declaration

ConversationCommand

Interpreter

```
public static InterpretationResult Fail { get; }
```

([NetAFInterpretation.Conversation.html](#))

CustomCommandInterpreter

Property Value

([NetAFInterpretation.CustomCom.html](#))

Type FrameCommandInterpreter

Description

([NetAFInterpretation.FrameComm.html](#))

InterpretationResult ([NetAFInterpretation.InterpretationResult.html](#))

GlobalCommandInterpreter

([NetAFInterpretation.GlobalCom.html](#))

IInterpreter

([NetAFInterpretation.IInterpreter.html](#))

InputInterpreter

([NetAFInterpretation.InputInterpret.html](#))

Get if the interpretation was successful.

InterpretationResult

Declaration

([NetAFInterpretation.Interpretation.html](#))

Interpreters

```
public bool WasInterpretedSuccessfully { get; }
```

([NetAFInterpretation.WasInterpretedSuccessfully.html](#))

RegionMapCommandInterpreter

([NetAFInterpretation.RegionMapCom.html](#))

SceneCommandInterpreter

([NetAFInterpretation.SceneCom.html](#))

Type [bool](#) ([https://docs.microsoft.com/dotnet/api/system.boolean](#))

Description

([NetAFLogic.html](#))

+ NetAF.Logic.Callbacks

([NetAFLogic.Callbacks.html](#))

+ NetAFLogic.Configuration

▼

- + **NetAF.Commands.Scene**
[\(NetAF.Commands.Scene.html\)](#)
- + **NetAF.Conversations**
[\(NetAF.Conversations.html\)](#)
- + **NetAF.Conversations.**
 Instructions
[\(NetAF.Conversations.Instruct](#)
- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
 - ConversationCommand
 - Interpreter
 - [\(NetAF.Interpretation.Conversation](#)
 - CustomCommandInterpreter
 - [\(NetAF.Interpretation.CustomComr](#)
 - FrameCommandInterpreter
 - [\(NetAF.Interpretation.FrameComm](#)
 - GlobalCommandInterpreter
 - [\(NetAF.Interpretation.GlobalComm](#)
 - IInterpreter
 - [\(NetAF.Interpretation.IInterpreter.ht](#)
 - InputInterpreter
 - [\(NetAF.Interpretation.InputInterpret](#)
 - InterpretationResult
 - [\(NetAF.Interpretation.Interpretation](#)
 - Interpreters
 - [\(NetAF.Interpretation.Interpreters.h](#)
 - RegionMapCommandInterpreter
 - [\(NetAF.Interpretation.RegionMapC](#)
 - SceneCommandInterpreter
 - [\(NetAF.Interpretation.SceneComm](#)
- + **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)
- + **NetAF.Logic.Configuration**

Class Interpreters

Provides collections of interpreters.

Filter by title

Inheritance

([NetAF.Commands.Scene.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Conversations**

↳ Interpreters

([NetAF.Conversations.html](#))

Inherited Members

+ **NetAF.Conversations**.

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

([NetAF.Conversations.Instruct.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Extensions**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

([NetAF.Extensions.html](#))

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

ConversationCommand

Namespace: NetAF ([NetAF.html](#)).Interpretation ([NetAF.Interpretation.html](#))

Interpreter

Assembly: NetAF.dll

([NetAF.Interpretation.Conversation.html](#))

Syntax: CustomCommandInterpreter

([NetAF.Interpretation.CustomCommandInterpreter.html](#))

public static class Interpreters

([NetAF.Interpretation.FrameCommandInterpreter.html](#))

GlobalCommandInterpreter

([NetAF.Interpretation.GlobalCommandInterpreter.html](#))

IInterpreter

Properties

ConversationInterpreter ([NetAF.Interpretation.IInterpreter.html](#))

InputInterpreter

([NetAF.Interpretation.InputInterpreter.html](#))

ConversationInterpreter ([NetAF.Interpretation.IInterpreter.html](#))

Get the conversation command interpreter.
Interpreters

Declaration: [NetAF.Interpretation.Interpreters.html](#)

RegionMapCommandInterpreter

([NetAF.Interpretation.RegionMapCommandInterpreter.html](#))

SceneCommandInterpreter

([NetAF.Interpretation.SceneCommandInterpreter.html](#))

Property Value

+ **NetAF.Logic**

Type: ([NetAF.Logic.html](#))

Description

IInterpreter ([NetAF.Interpretation.IInterpreter.html](#))

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

NetAF.Logic.Configuration

([NetAF.Logic.Configuration.html](#))

Default

([NetAF.Logic.Configuration.Default.html](#))

Get the default interpreters.

Declaration

```
public static IInterpreter Default { get; }
```



Property Value

Type	Description
IInterpreter (NetAF.Interpretation.IInterpreter.html) (NetAF.Conversations.html)	

+ NetAF.Conversations.

RegionMapCommandInterpreter

[\(NetAF.Conversations.Instruct.html\)](#)

Get the region map command interpreter.

+ NetAF.Extensions

Declaration

[\(NetAF.Extensions.html\)](#)

- NetAF.Interpretation.IInterpreter RegionMapCommandInterpreter { get; }

[\(NetAF.Interpretation.html\)](#)

Property Value

Type	Description
IInterpreter (NetAF.Interpretation.ConversationInterpreter.html)	
IInterpreter (NetAF.Interpretation.FrameCommandInterpreter.html)	

SceneInterpreter

Get the scene command interpreter.

IInterpreter

Declaration

[\(NetAF.Interpretation.IInterpreter.html\)](#)

InputInterpreter

[\(NetAF.Interpretation.InputInterpreter.SceneInterpreter { get; }\)](#)

InterpretationResult

[\(NetAF.Interpretation.Interpretation.html\)](#)

Property Value

Interpreters

Type	Description
IInterpreter (NetAF.Interpretation.IInterpreters.html)	
IInterpreter (NetAF.Interpretation.RegionMapCommandInterpreter.html)	

SceneCommandInterpreter

[\(NetAF.Interpretation.SceneCommandInterpreter.html\)](#)

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

Class RegionMapCommandInterpreter

Provides an object that can be used for interpreting region map commands.

Filter by title

Inheritance

+ **NetAF Conversations**

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF Conversations.html\)](#)
↳ [RegionMapCommandInterpreter](#)

+ **NetAF Conversations.**

Implements [IInterpreter](#) ([NetAF.Interpretation.IInterpreter.html](#))

Instructions
[\(NetAF Conversations.Instruct\)](#)

Inherited Members

+ **NetAF Extensions**

[object.Equals](#) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-object)))
[\(NetAF.Extensions.html\)](#)

[object.Equals](#) ([object, object](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-object-system-object))) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-object-system-object)))
[\(NetAF Interpretation.html\)](#)

[object.GetHashCode](#) (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

[object.GetType](#) () (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

[object.ReferenceEquals](#) ([object, object](https://learn.microsoft.com/dotnet/api/system.object.referenceequals)) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

[object.ToString](#) () (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

CustomCommandInterpreter
[Namespace](#): [NetAF](#) ([NetAF.Interpretation](#) ([NetAF.Interpretation.html](#)))

Assembly: [NetAF.dll](#)

FrameCommandInterpreter

Syntax
[\(NetAF.Interpretation.FrameComm\)](#)

GlobalCommandInterpreter

public sealed class RegionMapCommandInterpreter : IInterpreter
[\(NetAF.Interpretation.GlobalComm\)](#)

IInterpreter

[\(NetAF.Interpretation.IInterpreter.html\)](#)

InputInterpreter

[\(NetAF.Interpretation.InputInterpreter\)](#)

InterpretationResult

[\(NetAF.Interpretation.Interpretation\)](#)

Interpreters

DefaultSupportedCommands

[\(NetAF.Interpretation.Interpreters.html\)](#)

Get all region map command interpreter supported commands.

[\(NetAF.Interpretation.RegionMapC\)](#)

Declaration

SceneCommandInterpreter

[\(NetAF.Interpretation.SceneComm\)](#)

public static CommandHelp[] DefaultSupportedCommands { get; }

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

Property Value

+ **NetAF.Logic.Callbacks**

Type

[\(NetAF.Logic.Callbacks.html\)](#)

CommandHelp ([NetAF.Commands.CommandHelp.html](#))[]

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

Description

SupportedCommands

Get an array of all supported commands.

Declaration

```
public CommandHelp[] SupportedCommands { get; }
```

+ NetAF.Conversations

Type
[\(NetAF.Conversations.html\)](#)

Description

+ NetAF.Conversations

CommandHelp ([NetAF.Commands.CommandHelp.html](#))[]
Instructions

[\(NetAF.Conversations.Instruct](#)

+ NetAF.Extensions

Methods

[\(NetAF.Extensions.html\)](#)

- NetAF.Interpretation

GetContextualCommandHelp(Game)

ConversationCommand

Get contextual command help for a game, based on its current state.

Interpreter

Declaration
[\(NetAF.Interpretation.Conversation](#)

CustomCommandInterpreter

[public CommandHelp GetContextualCommandHelp\(Game game\)](#)

FrameCommandInterpreter

[\(NetAF.Interpretation.FrameComm](#)

Parameters

GlobalCommandInterpreter

Type
[\(NetAF.Interpretation.GlobalComm](#)

Name

Description

IInterpreter
Game ([NetAF.Logic.Game.html](#))
[\(NetAF.Interpretation.IInterpreter.ht](#)

game

The game.

InputInterpreter

Returns
[\(NetAF.Interpretation.InputInterpret](#)

Type
[\(NetAF.Interpretation.Interpretation](#)

CommandHelp ([NetAF.Commands.CommandHelp.html](#))[]
Interpreters

Description

The contextual help.

Interpret(string, Game)

[\(NetAF.Interpretation.RegionMapC](#)

SceneCommandInterpreter

Interprets string
[\(NetAF.Interpretation.SceneComm](#)

NetAF.Logic

[\(NetAF.Logic.html\)](#)

[public InterpretationResult Interpret\(string input, Game game\)](#)

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Parameters

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.htm](#)

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>input</i>	The string to interpret.
Game (NetAF.Logic.Game.html)	<i>game</i>	The game.

Returns

Type	Description
+ NetAF.Conversations InterpretationResult (NetAF.Interpretation.InterpretationResult.html) (NetAF.Conversations.html)	The result of the interpretation.

+ NetAF.Conversations.

Implements

(NetAF.Conversations.Instruct

IInterpreter ([NetAF.Interpretation.IInterpreter.html](#))

+ NetAF.Extensions

(NetAF.Extensions.html)

- NetAF.Interpretation

(NetAF.Interpretation.html)

ConversationCommand

Interpreter

(NetAF.Interpretation.Conversation

CustomCommandInterpreter

(NetAF.Interpretation.CustomComr

FrameCommandInterpreter

(NetAF.Interpretation.FrameComm

GlobalCommandInterpreter

(NetAF.Interpretation.GlobalComm

IInterpreter

(NetAF.Interpretation.IInterpreter.ht

InputInterpreter

(NetAF.Interpretation.InputInterpret

InterpretationResult

(NetAF.Interpretation.Interpretation

Interpreters

(NetAF.Interpretation.Interpreters.h

RegionMapCommandInterpreter

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

(NetAF.Interpretation.SceneComm

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.htm

Class SceneCommandInterpreter

Provides an object that can be used for interpreting scene commands.

Filter by title

Inheritance Conventions

(NetAF Conversations.html)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ NetAF.Conversations

Instructions

(NetAF ConversationsInterpreter.html)

Inherited Members

+ NetAF.Extensions

object ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

- NetAF Interpretation

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF Interpretation Custom Comm)

Namespace: NetAF (NetAF.html), Interpretation (NetAF.Interpretation.html)

Assembly: NetAF.dll

(NetAF.Interpretation.FrameComm)

Syntax

GlobalCommandInterpreter

(NetAF.Interpretation.GlobalComm)

public sealed class SceneCommandInterpreter : IInterpreter

(NetAF.Interpretation.IInterpreter.ht)

InputInterpreter

(NetAF.Interpretation.InputInterpret

InterpretationResult

(NetAF.Interpretation.Interpretation)

Interpreters

Me (NetAF.Interpretation.Interpreters.h

RegionMapCommandInterpreter

Get the Me command

(NetAF.Interpretation.RegionMapC

SceneCommandInterpreter

Declaration

(NetAF.Interpretation.SceneComm

+ NetAF Logic

public const string Me = "Me"

(NetAF.Logic.html)

NetAF Logic Callbacks

(NetAF.Logic.Callbacks.html)

Type

Description

+ NetAF Logic Configuration

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Logic.Configuration.html)

+ NetAF Logic Modes

Overworld

Get the overworld command.

Declaration

```
public const string Overworld = "Overworld"
```

- [View Conversations](#)

File: [\(NetAF.Conversations.html\)](#)

+ [Type](#) [NetAF.Conversations.](#)

[Instructions](#)
[string \(https://learn.microsoft.com/dotnet/api/system.string\)](#)
[\(NetAF.Conversations.Instruct](#)

Description

+ [NetAF.Extensions](#)

[Region](#) [\(NetAF.Extensions.html\)](#)

Get the Region command

[NetAF.Interpretation](#)
[\(NetAF.Interpretation.html\)](#)

Declaration

ConversationCommand

Interpreter
public const string Region = "Region"
[\(NetAF.Interpretation.Conversation](#)

CustomCommandInterpreter

Field Value
[\(NetAF.Interpretation.CustomCom](#)

Type FrameCommandInterpreter

[\(NetAF.Interpretation.FrameComm](#)
[string \(https://learn.microsoft.com/dotnet/api/system.string\)](#)
[GlobalCommandInterpreter](#)

Description

(NetAF.Interpretation.GlobalComm

IInterpreter

[Room](#) [\(NetAF.Interpretation.IInterpreter.h](#)

InputInterpreter

Get the Room command
[\(NetAF.Interpretation.InputInterpret](#)

InterpretationResult

Declaration
[\(NetAF.Interpretation.Interpretation](#)

Interpreters

public const string Room = "Room"
[\(NetAF.Interpretation.Interpreters.h](#)

RegionMapCommandInterpreter

Field Value
[\(NetAF.Interpretation.RegionMapC](#)

SceneCommandInterpreter

Type [\(NetAF.Interpretation.SceneComm](#)

Description

[string \(https://learn.microsoft.com/dotnet/api/system.string\)](#)

+ [NetAF.Logic](#)

[\(NetAF.Logic.html\)](#)

+ [NetAF.Logic.Callbacks](#)

[Properties](#) [\(NetAF.Logic.Callbacks.html\)](#)

+ [NetAF.Logic.Configuration](#)

[\(NetAF.Logic.Configuration.html\)](#)

DefaultSupportedCommands

+ [NetAF.Logic.Modes](#)

Get an array of all supported commands.

Declaration

```
public static CommandHelp[] DefaultSupportedCommands { get; }
```

Property Value

Type	Description
(NetAF.Conversations.html)	CommandHelp (NetAF.Commands.CommandHelp.html)[]

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct)

SupportedCommands

+ NetAF.Extensions

Get an array of all supported commands.

(NetAF.Extensions.html)

Declaration

NetAF.Interpretation

(NetAF.Interpretation.html)

```
public CommandHelp[] SupportedCommands { get; }
```

ConversationCommand

Interpreter

Property Value

Type	Description
(NetAF.Interpretation.CustomCommand.html)	CommandHelp (NetAF.Commands.CommandHelp.html)[]

(NetAF.Interpretation.FrameCommand)

GlobalCommandInterpreter

(NetAF.Interpretation.GlobalCommand.html)

Interpreter

(NetAF.Interpretation.IInterpreter.html)

InputInterpreter

(NetAF.Interpretation.InputInterpreter.html)

InterpretationResult

GetContextualCommandHelp(Game)

Get contextual command help for a game, based on its current state.

Interpreters

Declaration

(NetAF.Interpretation.Interpreters.html)

RegionMapCommandInterpreter

```
public CommandHelp[] GetContextualCommandHelp(Game game)
```

(NetAF.Interpretation.RegionMapCommand.html)

SceneCommandInterpreter

(NetAF.Interpretation.SceneCommandInterpreter.html)

Parameters

+ NetAF.Logic

(NetAF.Logic.html)

Game (NetAF.Logic.Game.html)

Name

Description

game

The game.

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ Type

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

CommandHelp (NetAF.Commands.CommandHelp.html)[]

Description

The contextual help.

+ NetAF.Logic.Modes

Interpret(string, Game)

Interpret a string.

Declaration

```
public InterpretationResult Interpret(string input, Game game)
```

- [View Conversations](#)

Part of [NetAF Conversations.html](#)

+ Type	Name	Description
NetAF.Conversations.		
Instructions String (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Conversations.Instruct Game (NetAF.Logic.Game.html)	<i>input</i>	The string to interpret.

+ NetAF.Extensions

Ref [NetAF.Extensions.html](#)

- Type	Description
NetAF.Interpretation (NetAF.Interpretation.html)	The result of the interpretation.

ConversationCommand

Interpreter

Implements

[NetAF.Interpretation.Conversation](#)

[CustomCommandInterpreter](#)

[IInterpreter \(NetAF.Interpretation.IInterpreter.html\)](#)

[\(NetAF.Interpretation.CustomCom](#)

FrameCommandInterpreter

[\(NetAF.Interpretation.FrameComm](#)

GlobalCommandInterpreter

[\(NetAF.Interpretation.GlobalComm](#)

IInterpreter

[\(NetAF.Interpretation.IInterpreter.ht](#)

InputInterpreter

[\(NetAF.Interpretation.InputInterpre](#)

InterpretationResult

[\(NetAF.Interpretation.Interpretation](#)

Interpreters

[\(NetAF.Interpretation.Interpreters.h](#)

RegionMapCommandInterpreter

[\(NetAF.Interpretation.RegionMapC](#)

SceneCommandInterpreter

[\(NetAF.Interpretation.SceneComm](#)

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.htm](#)

+ NetAF.Logic.Modes

Namespace NetAF.Logic

Classes

Filter by title

Persistence

AssetCatalog (NetAF.Logic.AssetCatalog.html)

(NetAF.Commands.Persistence)

Provides a catalog of all assets in a game.

+ NetAF.Commands.Region

Map

AssetGenerator (NetAF.Logic.AssetGenerator.html)

(NetAF.Commands.RegionMap)

Represents a generator for game assets.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

EndCheckResult (NetAF.Logic.EndCheckResult.html)

+ NetAF.Conversations

Represents the result of an end check.

(NetAF.Conversations.html)

+ NetAF.Conversations

Game (NetAF.Logic.Game.html)

Instructions

Represents a game.

(NetAF.Conversations.Instruct)

+ NetAF.Extensions

GameEndConditions (NetAF.Logic.GameEndConditions.html)

(NetAF.Extensions.html)

Provides a container for game end conditions.

+ NetAF.Interpretation

(NetAF.Interpretation.html)

GameInfo (NetAF.Logic.GameInfo.html)

- NetAF.Logic

Provides information about a game.

(NetAF.Logic.html)

AssetCatalog

PlayableCharacterLocation (NetAF.Logic.PlayableCharacterLocation.html)

(NetAF.Logic.AssetCatalog.html)

Provides a record of the location of a playable character.

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

EndCheck

(NetAF.Logic.EndCheck.html)

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

ExitMode (NetAF.Logic.ExitMode.html)

ExitMode

Enumeration of exit modes.

(NetAF.Logic.ExitMode.html)

Game

(NetAF.Logic.Game.html)

GameEndConditions

(NetAF.Logic.GameEndConditions.html)

Enumeration of game states.

GameInfo

(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLocation.html)

Enums

GameState (NetAF.Logic.GameState.html)

(NetAF.Logic.GameEndConditions.html)

Enumeration of game states.

GameInfo

(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLocation.html)

Class AssetCatalog

Provides a catalog of all assets in a game.

Filter by title

Inheritance

+ [NetAF.Commands.RegionMap](#)
↳ [AssetCatalog](#)

Inheritance

+ [NetAF.Commands.Scene](#)
↳ [\(NetAF.Commands.Scene.html\)](#)
object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))
object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object, system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object))
+ [NetAF.Conversations](#)
↳ [\(NetAF.Conversations.html\)](#)
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html)

+ [NetAF.Extensions](#)
Assembly: NetAF.dll
↳ [\(NetAF.Extensions.html\)](#)

Syntax

+ [NetAF.Interpretation](#)

↳ [\(NetAF.Interpretation.html\)](#)

- [NetAF.Logic](#)

↳ [\(NetAF.Logic.html\)](#)

AssetCatalog

↳ [\(NetAF.Logic.AssetCatalog.html\)](#)

AssetGenerator

↳ [\(NetAF.Logic.AssetGenerator.html\)](#)

Characters

EndCheck

↳ [\(NetAF.Logic.EndCheck.html\)](#)

Get the characters.

EndCheckResult

Declaration

↳ [\(NetAF.Logic.EndCheckResult.html\)](#)

ExitMode

public NonPlayableCharacter[] Characters { get; }

Game (NetAF.Logic.Game.html)

GameEndConditions

Property Value

↳ [\(NetAF.Logic.GameEndConditions.html\)](#)

Type GameInfo

↳ [\(NetAF.Logic.GameInfo.html\)](#)

NonPlayableCharacter (NetAF.Assets.Characters.NonPlayableCharacter.html)[]

GameState

↳ [\(NetAF.Logic.GameState.html\)](#)

PlayableCharacterLocation

↳ [\(NetAF.Logic.PlayableCharacterLocation.html\)](#)

Examnables

Description

--	--

Get the examinables.

Declaration

```
public IExaminable[] Examinables { get; }
```

Property Value

Type	Description
+ NetAF.Commands.RegionMap IExaminable (NetAF.Assets.IExaminable.html)	

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Get the item containers.

+ NetAF.Conversations

Declaration

(NetAF.Conversations.html)

+ NetAF.Conversations

```
public IItemContainer[] ItemContainers { get; }
```

Instructions

(NetAF.Conversations.Instruct

Property Value

+ NetAF.Extensions

Type (NetAF.Extensions.html)

IItemContainer (NetAF.Assets.IItemContainer.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Items

(NetAF.Logic.html)

Get the items.

AssetCatalog

Declaration

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

```
public IItem[Item] AssetGenerator
```

EndCheck

(NetAF.Logic.EndCheck.html)

Property Value

EndCheckResult

Type NetAF.Logic.EndCheckResult.htm

Description

ExitMode

Item (NetAF.Assets.Item.html)

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

GameEndConditions

Players

(NetAF.Logic.GameEndConditions.html)

GameInfo

Get the players

(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

```
public PlayableCharacter[] Players { get; }
```

(NetAF.Logic.PlayableCharacterLo

Property Value

Type	Description
PlayableCharacter (NetAF.Assets.Characters.PlayableCharacter.html)[]	

Rooms

Get the rooms.

+ NetAF.Commands.Region

Declaration

(NetAF.Commands.RegionMap)

```
public Room[] Rooms { get; }
```

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Property Value

+ NetAF.Conversations

Type
(NetAF.Conversations.html)

Room (NetAF.Assets.Locations.Room.html)[]

+ NetAF.Conversations

Instructions

(NetAF.Conversations.Instruct)

Methods

Extensions

(NetAF.Extensions.html)

FromGame(Game)

(NetAF.Interpretation.html)

Create a new AssetCatalog from a game.

- NetAF.Logic

Declaration

(NetAF.Logic.html)

```
PUBLIC STATIC AssetCatalog FromGame(Game game)
```

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

Parameters

(NetAF.Logic.AssetGenerator.html)

Type	Name	Description
EndCheck (NetAF.Logic.EndCheck.html)	game	The game to create the catalog from.

(NetAF.Logic.EndCheckResult.html)

Returns

ExitMode

Type	Description
Game (NetAF.Logic.Game.html)	The populated asset catalog.

(NetAF.Logic.AssetCatalog.html)

(NetAF.Logic.GameEndConditions.html)

GameInfo

(NetAF.Logic.GameInfo.html)

Register(params IExaminable[])

GameState

(NetAF.Logic.GameState.html)

Registers a collection of Examinables.

PlayableCharacterLocation

Declaration

(NetAF.Logic.PlayableCharacterLo

```
public void Register(params IExaminable[] examinables)
```

Parameters

Type	Name	Description
IExaminable (NetAF.Assets.IExaminable.html) www.unity3d.com/asset-store	examinables	The examinables to register.

+ NetAF.Commands.Region

Map
Register(params IAssetTemplate<IExaminable>[])
(NetAF.Commands.RegionMap)

Registers a collection of examinables.

+ NetAF.Commands.Scene

Delegates
(NetAF.Commands.Scene.html)

+ NetAF.Conversations

public void Register(params IAssetTemplate<IExaminable>[] templates)
(NetAF.Conversations.html)

+ NetAF.Conversations.

Parameters

Instructions	Name	Description
Type (NetAF.Conversations.Instruct) IAssetTemplate (NetAF.Utilities.IAssetTemplate-1.html)< IExaminable (NetAF.Assets.IExaminable.html)>[] (NetAF.Extensions.html)	templates	The templates to register.

+ NetAF.Interpretation

(NetAF.Interpretation.html)

- NetAF.Logic

(NetAF.Logic.html)

AssetCatalog

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

EndCheck

(NetAF.Logic.EndCheck.html)

EndCheckResult

(NetAF.Logic.EndCheckResult.htm

ExitMode

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

GameEndConditions

(NetAF.Logic.GameEndConditions.

GameInfo

(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLo

Class AssetGenerator

Represents a generator for game assets.

Filter by title

Inheritance

+ **NetAF.Commands.Region**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ AssetGenerator

(**NetAF.Commands.RegionMap**

Inherited Members

+ **NetAF.Commands.Scene**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ **NetAF.Conversations** ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html)

+ **NetAF.Extensions**

Assembly: NetAF.dll

(**NetAF.Extensions.html**)

Syntax

+ **NetAF.Interpretation**

(**NetAF.Interpretation.html**)

public sealed class AssetGenerator

- **NetAF.Logic**

(**NetAF.Logic.html**)

AssetCatalog

Methods

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

Custom(OverworldCreationCallback, PlayerCreationCallback)

(NetAF.Logic.EndCheck.html)

Create an asset generator that creates custom values. Callbacks determine the overworld and player that will be returned on each call to GetOverworld and GetPlayer.

(NetAF.Logic.EndCheckResult.html)

Declares **ExitMode**

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

public static AssetGenerator Custom(OverworldCreationCallback overworldCreationCallback, PlayerCreationCallback playerCreationCallback)

GameEndConditions (NetAF.Logic.GameEndConditions.html)

(NetAF.Logic.GameEndConditions.html)

GameInfo

Parameters

(NetAF.Logic.GameInfo.html)

Type	Name	Description
GameState (NetAF.Logic.GameState.html) OverworldCreationCallback PlayableCharacterLocation (NetAF.Logic.Callbacks.OverworldCreationCallback.html) I	overworldCreationCallback	The overworld creation callback.

+ **NetAF.Logic.Callbacks**

Type	Name	Description
PlayerCreationCallback (NetAF.Logic.Callbacks.PlayerCreationCallback.html)	<i>playerCreationCallback</i>	The player creation callback.

Returns

Type

+ **NetAF.Commands.Region**

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

(NetAF.Commands.RegionMap)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

- **NetAF.Conversations**

GetOverworld

(NetAF.Conversations.html)

Declaration

+ **NetAF.Conversations.**

Instructions overworld GetOverworld()

(NetAF.Conversations.Instruct

Returns

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation** Locations.Overworld.html)

(NetAF.Interpretation.html)

- **NetAF.Logic**

GetPlayer()

(NetAF.Logic.html)

Get the player

AssetCatalog

(NetAF.Logic.AssetCatalog.html)

Declaration

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

public PlayableCharacter GetPlayer()

EndCheck

(NetAF.Logic.EndCheck.html)

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

Type

ExitMode

(NetAF.Logic.ExitMode.html)

PlayableCharacter (NetAF.Assets.Characters.PlayableCharacter.html)

Game (NetAF.Logic.Game.html)

GameEndConditions

(NetAF.Logic.GameEndConditions.

New(IAssetTemplate<Overworld>, IAssetTemplate<PlayableCharacter>)

GameInfo

(NetAF.Logic.GameInfo.html)

Create an asset generator that creates new values. Different instances of overworld and player will be returned on each call to GetOverworld and GetPlayer.

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLo

+ **NetAF.Logic.Callbacks**

```
public static AssetGenerator New(IAssetTemplate<Overworld> overworldTemplate, IAssetTemplate<PlayableCharacter> playerTemplate)
```

Parameters

Type	Name	Description
+ NetAF.Commands.Region IAssetTemplate<AssetTemplate-1.html><Overworld (NetAF.Assets.Locations.Overworld.html)>	overworldTemplate	The overworld template.
+ NetAF.Commands.RegionMap IAssetTemplate<AssetTemplate-1.html><PlayableCharacter (NetAF.Assets.Characters.PlayableCharacter.html)>	playerTemplate	The player template.
> (NetAF.Commands.Scene.html)		

Related

[NetAF.Conversations](#)

Type	Description
+ NetAF.Conversations.AssetGenerator (NetAF.Logic.AssetGenerator.html)	Asset generation that will always return a new overworld and a new player.

Related

[\(NetAF.Conversations.Instruct.html\)](#)

Related

+ [NetAF.Extensions](#)

New(OverworldMaker, IAssetTemplate<PlayableCharacter>)

Creates an asset generator that creates new values. Different instances of overworld and player will be returned on each call to GetOverworld and GetPlayer.

Related

[\(NetAF.Interpretation.html\)](#)

Declaration

- [NetAF.Logic](#)

[\(NetAF.Logic.html\)](#)

```
public static AssetGenerator New(OverworldMaker overworldMaker, IAssetTemplate<PlayableCharacter> playerTemplate)
```

[AssetCatalog](#) (NetAF.Logic.AssetCatalog.html)

AssetGenerator

Parameters
(NetAF.Logic.AssetGenerator.html)

Type	Name	Description
EndCheck (NetAF.Logic.EndCheck.html)		
OverworldMaker (NetAF.Utilities.OverworldMaker.html) EndCheckResult (NetAF.Logic.EndCheckResult.html)	overworldMaker	The overworld maker.

GameEndConditions

Returns
(NetAF.Logic.GameEndConditions)

Type	Description
GameInfo (NetAF.Logic.GameInfo.html)	Asset generation that will always return a new overworld and a new player.

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLo

Retained(Overworld, PlayableCharacter)

+ [NetAF.Logic.Callbacks](#)

Create an asset generator that uses retained value. The same instance of overworld and player will be returned on each call to GetOverworld and GetPlayer.

Declaration

```
public static AssetGenerator Retained(Overworld overworld, PlayableCharacter player)
```

Parameters

+ NetAF.Commands.Region

Type	Name	Description
(NetAF.Commands.RegionMap) Overworld (NetAF.Assets.Locations.Overworld.html)	overworld	The overworld.
(NetAF.Commands.Scene) PlayableCharacter (NetAF.Assets.Characters.PlayableCharacter.html) (NetAF.Commands.Scene.html)	player	The player.

Returns

+ NetAF.Conversations

Type	Description
(NetAF.Conversations.html) AssetGenerator	Asset generation that will always return the same instance overworld and the same instance of the player.

(NetAF.Conversations.Instruct)

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

- NetAF.Logic

[\(NetAF.Logic.html\)](#)

AssetCatalog

[\(NetAF.Logic.AssetCatalog.html\)](#)

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

EndCheck

[\(NetAF.Logic.EndCheck.html\)](#)

EndCheckResult

[\(NetAF.Logic.EndCheckResult.html\)](#)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Game [\(NetAF.Logic.Game.html\)](#)

GameEndConditions

[\(NetAF.Logic.GameEndConditions.html\)](#)

GameInfo

[\(NetAF.Logic.GameInfo.html\)](#)

GameState

[\(NetAF.Logic.GameState.html\)](#)

PlayableCharacterLocation

[\(NetAF.Logic.PlayableCharacterLocation.html\)](#)

+ NetAF.Logic.Callbacks

Delegate EndCheck

Represents the callback used for end checks.

Filter by title

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html)

Map

Assembly: NetAF.dll

(NetAF.Commands.RegionMap)

Syntax

+ **NetAF.Commands.Scene**

 public delegate EndCheckResult EndCheck(Game game)

+ **NetAF.Conversations**

Parameters

(NetAF.Conversations.html)

Type

+ **NetAF.Conversations.**

Game (NetAF.Logic.Game.html)

Instructions

(NetAF.Conversations.Instruct

Returns

+ **NetAF.Extensions**

Type

(NetAF.Extensions.html)

EndCheckResult (NetAF.Logic.EndCheckResult.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

- **NetAF.Logic**

(NetAF.Logic.html)

AssetCatalog

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

EndCheck

(NetAF.Logic.EndCheck.html)

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

ExitMode

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

GameEndConditions

(NetAF.Logic.GameEndConditions.html)

GameInfo

(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

Class EndCheckResult

Represents the result of an end check.

Filter by title

Inheritance

(NetAF.Commands.RegionMap)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ NetAF.Commands.Scene

(NetAFCommands.Scene.html)

Inherited Members

+ NetAFConversations ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

(NetAF.Conversations.html)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ NetAFConversations

(NetAFConversations.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object (NetAFConversations.html)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

+ NetAFExtensions

(NetAFExtensions.html)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAFInterpretation

(NetAF.Interpretation.html)

Assembly: NetAF.dll

- NetAF.Logic

(NetAF.Logic.html)

public class EndCheckResult

AssetCatalog

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

Constructors

EndCheckResult(bool, string, string)

(NetAF.Logic.EndCheckResult.html)

Represents the result of an end check.

ExitMode

Declaration

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

GameEndConditionsResult(bool hasEnded, string title, string description)

(NetAF.Logic.GameEndConditions.html)

GameInfo

Parameters

(NetAF.Logic.GameInfo.html)

Type	Name	Description
gameState	hasEnded	If the game has ended.
(NetAF.Logic.GameState.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean)	PlayableCharacterLocation	A title to describe the end.
string (https://learn.microsoft.com/dotnet/api/system.string)	title	A description of the end.

+ NetAFLogicCallbacks

(NetAF.Logic.Callbacks.html)

Properties

Description

Get a description of the end.

Declaration

(NetAF.Commands.RegionMap)

```
public string Description { get; }
```

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Property Value

+ NetAF.Conversations

Type

(NetAF.Conversations.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct)

HasEnded

+ NetAF.Extensions

Get if the game has come to an end.

(NetAF.Extensions.html)

Declaration

+ NetAF.Interpretation

(NetAF.Interpretation.html)

```
public bool HasEnded { get; }
```

- NetAF.Logic

(NetAF.Logic.html)

Type

AssetCatalog

(NetAF.Logic.AssetCatalog.html)

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

EndCheck

(NetAF.Logic.EndCheck.html)

EndCheckResult

Get a default result for EndCheckResult.

(NetAF.Logic.EndCheckResult.html)

ExitMode

Declaration

(NetAF.Logic.ExitMode.html)

Game

(NetAF.Logic.Game.html)

```
public static EndCheckResult NotEnded { get; }
```

GameEndConditions

(NetAF.Logic.GameEndConditions.html)

GameInfo

Property Value

(NetAF.Logic.GameInfo.html)

Type

GameState

(NetAF.Logic.GameState.html)

EndCheckResult ([NetAF.Logic.EndCheckResult.html](#))

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLo)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Get a title to describe the end.

... [NetAF.Logic.Callbacks.html](#)

Description

Declaration

```
public string Title { get; }
```

Property Value

Type	Description
string (http://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.RegionMap)	

- + **NetAF.Commands.Scene**
[\(NetAF.Commands.Scene.html\)](#)
- + **NetAF.Conversations**
[\(NetAF.Conversations.html\)](#)
- + **NetAF.Conversations.**
 Instructions
[\(NetAF.Conversations.Instruct](#)
- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- + **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
- **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
 - AssetCatalog
[\(NetAF.Logic.AssetCatalog.html\)](#)
 - AssetGenerator
[\(NetAF.Logic.AssetGenerator.html\)](#)
 - EndCheck
[\(NetAF.Logic.EndCheck.html\)](#)
 - EndCheckResult
[\(NetAF.Logic.EndCheckResult.htm](#)
 - ExitMode
[\(NetAF.Logic.ExitMode.html\)](#)
 - Game
[\(NetAF.Logic.Game.html\)](#)
 - GameEndConditions
[\(NetAF.Logic.GameEndConditions.](#)
 - GameInfo
[\(NetAF.Logic.GameInfo.html\)](#)
 - GameState
[\(NetAF.Logic.GameState.html\)](#)
 - PlayableCharacterLocation
[\(NetAF.Logic.PlayableCharacterLo](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)

Enum ExitMode

Enumeration of exit modes.

Filter by title

Namespace: NetAF (NetAF.html), Logic (NetAF.Logic.html)

Assembly: NetAF.dll

+ NetAF.Commands.Scene

Syntax
[\(NetAF.Commands.Scene.html\)](#)

+ NetAF.Conversations

PUBLIC ENUM EXITMODE
[\(NetAF.Conversations.html\)](#)

+ NetAF.Conversations.

Instructions

Fields

[\(NetAF.Conversations.Instruct](#)

Name	Description
ExitApplication	Exit the application.
ReturnToTitleScreen	Return to the title screen.

- NetAF.Logic

[\(NetAF.Logic.html\)](#)

AssetCatalog

[\(NetAF.Logic.AssetCatalog.html\)](#)

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

EndCheck

[\(NetAF.Logic.EndCheck.html\)](#)

EndCheckResult

[\(NetAF.Logic.EndCheckResult.htm](#)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Game [\(NetAF.Logic.Game.html\)](#)

GameEndConditions

[\(NetAF.Logic.GameEndConditions.](#)

GameInfo

[\(NetAF.Logic.GameInfo.html\)](#)

GameState

[\(NetAF.Logic.GameState.html\)](#)

PlayableCharacterLocation

[\(NetAF.Logic.PlayableCharacterLo](#)

+ NetAF.Logic.Callbacks

Class Game

Represents a game.

Filter by title

Inheritance

+ NetAF.Commands.Scene

↳ [https://learn.microsoft.com/dotnet/api/system.object\)](https://learn.microsoft.com/dotnet/api/system.object)

↳ Game

+ NetAF.Conversations

Implements

[\(NetAF.Conversations.html\)](#)

IRestoreFromObjectSerialization ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Game

[\(NetAF.Conversations.GameSerialization.html\)](#)>

Instructions

Inherited members

(NetAF.Conversations.Instruct

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](#))

+ NetAF.Extensions

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](#))

[\(NetAF.Extensions.html\)](#)

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))

object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))

- NetAF.Logic

object.ToString() ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))

[\(NetAF.Logic.html\)](#)

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#))

AssetCatalog

Assembly: NetAF

[\(NetAF.Logic.AssetCatalog.html\)](#)

Syntax

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

public sealed class Game : IRestoreFromObjectSerialization<GameSerialization>

EndCheck

[\(NetAF.Logic.EndCheck.html\)](#)

EndCheckResult

[\(NetAF.Logic.EndCheckResult.html\)](#)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Game ([NetAF.Logic.Game.html](#))

GameEndConditions

[\(NetAF.Logic.GameEndConditions.html\)](#)

Get the catalog of assets for this game.

[\(NetAF.Logic.GameInfo.html\)](#)

Declaration

GameState

[\(NetAF.Logic.GameState.html\)](#)

public AssetCatalog Catalog { get; }

[\(NetAF.Logic.PlayableCharacterLo](#)

Property Value

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Description

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

[\(NetAF.Logic.Configuration.html\)](#)

Configuration

Get the configuration.

Declaration

```
public IGameConfiguration Configuration { get; }
```

+ NetAF.Commands.Scene

Property Value

(NetAF.Commands.Scene.html)

Type

+ NetAF.Conversations

IGameConfiguration (NetAF.Logic.Configuration.IGameConfiguration.html)

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

EndConditions

(NetAF.Conversations.Instruct)

Get the end conditions.

+ NetAF.Extensions

Declaration

(NetAF.Extensions.html)

+ NetAF.Interpretation

```
public GameEndConditions EndConditions { get; }
```

(NetAF.Interpretation.html)

NetAF.Logic

Type

AssetCatalog

GameEndConditions (NetAF.Logic.GameEndConditions.html)

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

Info

EndCheck

(NetAF.Logic.EndCheck.html)

Get the info

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

Declaration

ExitMode

(NetAF.Logic.ExitMode.html)

```
public GameInfo Info { get; }
```

Game (NetAF.Logic.Game.html)

GameEndConditions

(NetAF.Logic.GameEndConditions.html)

Property Value

GameInfo

Type

(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLocation.html)

Introduction

+ NetAF.Logic.Callbacks

Get the introduction

(NetAF.Logic.Callbacks.html)

Declaration

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Description

Description

Description

```
public string Introduction { get; }
```

Property Value

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	

+ NetAF.Commands.Scene

[\(NetAF.Commands.Scene.html\)](#)

Mode

+ NetAF.Conversations

[\(NetAF.Conversations.html\)](#)

Get the mode.

+ NetAF.Conversations.

Declaration

[Instructions](#)

[\(NetAF.Conversations.Instruct.html\)](#)

```
public IGameMode Mode { get; }
```

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Property Value

Type	Description
NetAF.Interpretation	

[\(NetAF.Interpretation.html\)](#)

[IGameMode \(\[NetAF.Logic.Modes.IGameMode.html\]\(#\)\)](#)

- NetAF.Logic

[\(NetAF.Logic.html\)](#)

Overworld

AssetCatalog

[\(NetAF.Logic.AssetCatalog.html\)](#)

Get the overworld.

AssetGenerator

Declaration

[\(NetAF.Logic.AssetGenerator.html\)](#)

EndCheck

[\(NetAF.Logic.EndCheck.html\)](#)

EndCheckResult

[\(NetAF.Logic.EndCheckResult.html\)](#)

Property Value

ExitMode

Type	Description
NetAF.Logic.ExitMode.html	
Game (NetAF.Logic.Game.html)	

[Overworld \(\[NetAF.Assets.Locations.Overworld.html\]\(#\)\)](#)

[GameEndConditions](#)

[\(NetAF.Logic.GameEndConditions.html\)](#)

GameInfo

[\(NetAF.Logic.GameInfo.html\)](#)

Player

GameState

Get

[\(NetAF.Logic.GameState.html\)](#)

PlayableCharacterLocation

Declaration

[\(NetAF.Logic.PlayableCharacterLo](#)

+ NetAF.Logic.Callbacks

```
public PlayableCharacter Player { get; }
```

[\(NetAF.Logic.Callbacks.html\)](#)

Property Value

NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

Type	Description
PlayableCharacter (NetAF.Assets.Characters.PlayableCharacter.html)	

Methods

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)
ChangeMode(IGameMode)

+ NetAF.Conversations

Change mode to a specified mode
(NetAF.Conversations.html)

Declaration

+ NetAF.Conversations.

Instructions

```
public void ChangeMode(IGameMode mode)
(NetAF.Conversations.Instruct
```

+ NetAF.Extensions

Parameters

(NetAF.Extensions.html)

Type

+ NetAF.Interpretation

IGameMode (NetAF.Logic.Modes.IGameMode.html)
(NetAF.Interpretation.html)

- NetAF.Logic

ChangePlayer(PlayableCharacter, bool)

AssetCatalog

Change to a specified player.
(NetAF.Logic.AssetCatalog.html)

Declaration

AssetGenerator

(NetAF.Logic.AssetGenerator.html)

EndCheck void ChangePlayer(PlayableCharacter player, bool jumpToLastLocation = true)
(NetAF.Logic.EndCheck.html)

EndCheckResult

Parameters

(NetAF.Logic.EndCheckResult.html)

Type	Name	Description
ExitMode (NetAF.Logic.ExitMode.html)		
PlayableCharacter (NetAF.Logic.Game.html) (NetAF.Assets.Characters.GameEndConditions) (NetAF.Logic.GameEndConditions.html)	player	The player to change to.
bool (NetAF.Logic.GameInfo.html) (https://learn.microsoft.com/en-us/dotnet/api/system.boolean) (NetAF.Logic.GameState.html)	jumpToLastLocation	Jump to the last location, if it is known. Then true the player will be added at the last location, when false the current location will be used. By default this is true.

NetAF.Logic.Callbacks

Create(GameInfo, String, AssetGenerator, GameEndConditions, IGameConfiguration, GameSetupCallback)

+ NetAF.Logic.Configuration

Create a new callback for generating instances of a game.

(NetAF.Logic.Configuration.html)

Declaration

```
public static GameCreationCallback Create(GameInfo info, string introduction, AssetGenerator assetGenerator, GameEndConditions conditions, IGameConfiguration configuration, GameSetupCallback setup = null)
```



Parameters

Type	Name	Description
+ NetAF.Commands.Scene (NetAF.Commands.Scene.html) GameInfo (NetAF.Logic.GameInfo.html)	<i>info</i>	Information about the game.
+ NetAF.Conversations string (NetAF.Conversations.html) (https://learn.microsoft.com/dotnet/api/system .	<i>introduction</i>	An introduction to the game.
+ NetAF.Conversations.		
Instructions AssetGenerator (NetAF.Conversations.Instructions.html)	<i>assetGenerator</i>	The generator to use to create game assets.
+ NetAF.Extensions GameEndConditions (NetAF.Extensions.html)	<i>conditions</i>	The game conditions.
+ NetAF.Interpretation (NetAF.Interpretation.html)	<i>configuration</i>	The configuration for the game.
- NetAF.Logic GameSetupCallback (NetAF.Logic.html) (NetAF.Logic.Callbacks.GameSetupCallback.html)	<i>setup</i>	A setup function to run on the created game after it has been created.

AssetCatalog
(NetAF.Logic.AssetCatalog.html)

AssetGenerator
(NetAF.Logic.AssetGenerator.html)

Type	Description
EndCheck (NetAF.Logic.EndCheck.html)	A new GameCreationHelper that will create a GameCreator with the parameters specified.

GameCreationCallback
EndCheckResult
(NetAF.Logic.Callbacks.GameCreationCallback.html)

ExitMode
(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

End()

GameEndConditions
(NetAF.Logic.GameEndConditions.html)

End the game
GameInfo

Declaration
(NetAF.Logic.GameInfo.html)

GameState

(NetAF.Logic.GameState.html)

public void End()

PlayableCharacterLocation

(NetAF.Logic.PlayableCharacterLo

+ **NetAF.Logic.Callbacks**

Execute(GameCreationCallback)

(NetAF.Logic.Callbacks.html)

Execute a game

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

Declaration

```
public static void Execute(GameCreationCallback creator)
```

Parameters

Type	Name	Description
GameCreationCallback + NetAF.Commands.Scene (NetAF.Logic.Callbacks.GameCreationCallback.html) (NetAF.Commands.Scene.html)	creator	The creator to use to create the game.

+ NetAF.Conversations

FindInteractionTarget(string)

Find an interaction target within the current scope for this Game.

Instructions

Declaration

(NetAF.Conversations.Instruct

```
+ public IInteractWithItem FindInteractionTarget(string name)
```

(NetAF.Extensions.html)

Parameters

+ NetAF.Interpretation

Type
(NetAF.Interpretation.html)

- string (<https://learn.microsoft.com/dotnet/api/system.string>)

Name

Description

name

The targets name.

(NetAF.Logic.html)

Returns

AssetCatalog

Type
(NetAF.Logic.AssetCatalog.html)

Description

IInteractWithItem

(NetAF.Logic.AssetGenerator.html)

(NetAF.Assets.IInteractWithItem.html)

The first IInteractWithItem object which has a name that matches the name parameter.

EndCheck

(NetAF.Logic.EndCheck.html)

EndCheckResult

GetAllPlayerVisibleExaminables()

ExitMode

Get all examinables that are currently visible to the player.

(NetAF.Logic.ExitMode.html)

Declaration

Game
(NetAF.Logic.Game.html)

GameEndConditions

(NetAF.Logic.GameEndConditions

```
public IExamitable[] GetAllPlayerVisibleExaminables()
```

GameInfo

(NetAF.Logic.GameInfo.html)

Returns

GameState

Type
(NetAF.Logic.GameState.html)

Description

PlayableCharacterLocation

IExamitable
(NetAF.Assets.Examitable.html)

An array of all examinables that are currently visible to the player.

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

GetActivePlayerConfigurations()

(NetAF.Logic.Configuration.html)

Get an array of inactive player locations.

Declaration

```
public PlayableCharacterLocation[] GetInactivePlayerLocations()
```

>Returns

Type	Description
+ NetAF.Commands.Scene (NetAF.Commands.Scene.html) PlayableCharacterLocation + NetAF.Conversations (NetAF.Conversations.html)	An array containing all locations of inactive platers.

+ **NetAF.Conversations.**

Instructions
[RestoreFrom\(GameSerialization\)](#)
[\(NetAF.Conversations.Instruct.html\)](#)

Restore this object from a serialization.

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

```
public void RestoreFrom(GameSerialization serialization)  
\(NetAF.Interpretation.html\)
```

- **NetAF.Logic**

Parameters

Type	Name	Description
AssetCatalog GameSerialization (NetAF.Serialization.GameSerialization.html)	serialization	The serialization to restore from.

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

Implements

[IRestoreFromObjectSerialization<T>](#) ([\(NetAF.Serialization.IRestoreFromObjectSerialization-1.html\)](#))

[EndCheckResult](#)

[\(NetAF.Logic.EndCheckResult.html\)](#)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Game ([NetAF.Logic.Game.html](#))

GameEndConditions

[\(NetAF.Logic.GameEndConditions.html\)](#)

GameInfo

[\(NetAF.Logic.GameInfo.html\)](#)

GameState

[\(NetAF.Logic.GameState.html\)](#)

PlayableCharacterLocation

[\(NetAF.Logic.PlayableCharacterLocation.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

Class GameEndConditions

Provides a container for game end conditions.

Filter by title

Inheritance

[\(NetAF.Commands.Scene.html\)](#)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ [NetAF Conversations](#)

[\(NetAF Conversations.html\)](#)

Inherited Members

+ [NetAF Conversations](#)

[Instructions](#)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ [NetAF Extensions](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ [NetAF Interpretation](#)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

[\(NetAF.Interpretation.html\)](#)

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html)

[NetAF Logic](#)

Assembly: NetAF.dll

[\(NetAF.Logic.html\)](#)

Syntax

AssetCatalog

[\(NetAF.Logic.AssetCatalog.html\)](#) Conditions

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

EndCheck

[\(NetAF.Logic.EndCheck.html\)](#)

EndCheckResult

[\(NetAF.Logic.EndCheckResult.html\)](#)

GameEndConditions(EndCheck, EndCheck)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Provides a container for game end conditions.

Game ([NetAF.Logic.Game.html](#))

Declaration

[GameEndConditions](#)

[\(NetAF.Logic.GameEndConditions.html\)](#)

ClientInfo

[GameEndConditions\(EndCheck completionCondition, EndCheck gameOverCondition\)](#)

[\(NetAF.Logic.GameInfo.html\)](#)

GameState

Parameters

[\(NetAF.Logic.GameState.html\)](#)

Type	Name	Description
PlayableCharacterLocation EndCheck + NetAF Logic Callbacks	completionCondition	The condition that determines if the game was completed.
EndCheck + NetAF Logic Configuration	gameOverCondition	The condition that determines if the game has ended.
(NetAF.Logic.Configuration.html)		

[\(NetAF.Logic.Configuration.html\)](#)

+ [NetAF Logic Modes](#)

Properties

CompletionCondition

Get the condition that determines if the game was completed.

Declaration

(NetAF.Commands.Scene.html)

```
public EndCheck CompletionCondition { get; }
```

+ **NetAF.Conversations**

(NetAF.Conversations.html)

Property Value

+ **NetAF.Conversations.**

Type
Instructions

Description

EndCheck (NetAF.Logic.EndCheck.html)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

GameOverCondition

+ **NetAF.Interpretation**

Get the condition that determines if the game has ended.

(NetAF.Interpretation.html)

Declaration

- **NetAF.Logic**

(NetAF.Logic.html)

```
public EndCheck GameOverCondition { get; }
```

AssetCatalog

(NetAF.Logic.AssetCatalog.html)

Property Value

AssetGenerator

Description

Type (NetAF.Logic.AssetGenerator.html)

EndCheck

EndCheck (NetAF.Logic.EndCheck.html)

(NetAF.Logic.EndCheck.html)

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

NoEnd

(NetAF.Logic.ExitMode.html)

Get Game (NetAF.Logic.Game.html)

GameEndConditions

Declaration
(NetAF.Logic.GameEndConditions.html)

GameInfo

```
public static GameEndConditions NoEnd { get; }
```

(NetAF.Logic.GameInfo.html)

GameState

Property Value
(NetAF.Logic.GameState.html)

PlayableCharacterLocation

Type (NetAF.Logic.PlayableCharacterLo

Description

GameEndConditions (NetAF.Logic.GameEndConditions.html)

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

NotEnded (NetAF.Logic.Configuration.html)

Get an end check that returns EndCheckResult.NotEnded.

+ **NetAF Logic Modes**

Declaration

```
public static EndCheck NotEnded { get; }
```

Property Value

Type	Description
E(NetAF.Conversations.Scheduled.html)	

+ NetAF.Conversations
(NetAF.Conversations.html)

+ NetAF.Conversations.
Instructions
(NetAF.Conversations.Instruct

+ NetAF.Extensions
(NetAF.Extensions.html)

+ NetAF.Interpretation
(NetAF.Interpretation.html)

- NetAF.Logic
(NetAF.Logic.html)

AssetCatalog
(NetAF.Logic.AssetCatalog.html)

AssetGenerator
(NetAF.Logic.AssetGenerator.html)

EndCheck
(NetAF.Logic.EndCheck.html)

EndCheckResult
(NetAF.Logic.EndCheckResult.htm

ExitMode
(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

GameEndConditions
(NetAF.Logic.GameEndConditions.

GameInfo
(NetAF.Logic.GameInfo.html)

GameState
(NetAF.Logic.GameState.html)

PlayableCharacterLocation
(NetAF.Logic.PlayableCharacterLo

+ NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration
(NetAF.Logic.Configuration.htm

+ NetAF.Logic Modes

Class GameInfo

Provides information about a game.

Filter by title

Inheritance

+ **NetAF.Conversations**
object (<https://learn.microsoft.com/dotnet/api/system.object>)
[\(NetAF.Conversations.html\)](#)

+ **NetAF.Conversations.**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
[\(NetAF.Conversations.Instruct\)](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object-system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object-system-object-system-object)))
+ **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Interpretation**
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
[\(NetAF.Interpretation.html\)](#)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic** ([NetAF.html](#)).Logic ([NetAF.Logic.html](#))

[\(NetAF.Logic.html\)](#)

Syntax

AssetCatalog
([NetAF.Logic.AssetCatalog.html](#))

AssetGenerator class GameInfo
([NetAF.Logic.AssetGenerator.html](#))

EndCheck
([NetAF.Logic.EndCheck.html](#))

EndCheckResult
([NetAF.Logic.EndCheckResult.html](#))

Constructors

+ **GameInfo(string, string, string)**
([NetAF.Logic.Game.html](#))

Provides information about a game.

GameEndConditions

Declaration

([NetAF.Logic.GameEndConditions.html](#))

GameInfo

param ([NetAF.Logic.GameInfo.html](#)) name, string description, string author)

GameState

([NetAF.Logic.GameState.html](#))

Parameters

PlayableCharacterLocation

Type	Name	Description
NetAF.Logic.PlayableCharacterLocation		
+ NetAF.Logic.Callbacks string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Logic.Callbacks.html)	name	The name of the game.
string (https://learn.microsoft.com/dotnet/api/system.string)	description	A description of the game.
+ NetAF.Logic.Configuration string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Logic.Configuration.html)	author	A author of the game.

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

Properties

Author

Get the author.



Declaration

+ NetAF.Conversations

```
public string Author { get; set; }
```

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

Type

(NetAF.Conversations.Instruct

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Extensions

(NetAF.Extensions.html)

Descriptioninterpretation

(NetAF.Interpretation.html)

Get the description of the game.

- NetAF.Logic

Declaration

(NetAF.Logic.html)

```
AssetCatalog Description { get; }
```

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

Property Value

(NetAF.Logic.AssetGenerator.html)

Type

EndCheck

(NetAF.Logic.EndCheck.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

ExitMode

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

Get the name of the game.

GameEndConditions.

Declaration

Gamelinfo

(NetAF.Logic.Gamelinfo.html)

```
public string Name { get; }
```

Gamemode

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

Property Value

(NetAF.Logic.PlayableCharacterLo

Type

+ NetAF.Logic.Callbacks

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Description

Instructions	Description
Type (NetAF.Conversations.Instruct string (https://learn.microsoft.com/dotnet/api/system.string)	

+ NetAF.Extensions

(NetAF.Extensions.html)

Descriptioninterpretation

(NetAF.Interpretation.html)

Get the description of the game.

- NetAF.Logic

Declaration

(NetAF.Logic.html)

```
AssetCatalog Description { get; }
```

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

Property Value

(NetAF.Logic.AssetGenerator.html)

Type

EndCheck

(NetAF.Logic.EndCheck.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

EndCheckResult

(NetAF.Logic.EndCheckResult.html)

ExitMode

(NetAF.Logic.ExitMode.html)

Game (NetAF.Logic.Game.html)

Get the name of the game.

GameEndConditions.

Declaration

Gamelinfo

(NetAF.Logic.Gamelinfo.html)

```
public string Name { get; }
```

Gamemode

(NetAF.Logic.GameState.html)

PlayableCharacterLocation

Property Value

(NetAF.Logic.PlayableCharacterLo

Type

+ NetAF.Logic.Callbacks

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Description

Type	Description
EndCheck (NetAF.Logic.EndCheck.html) string (https://learn.microsoft.com/dotnet/api/system.string)	

- NetAF.Logic

Declaration

(NetAF.Logic.html)

```
AssetCatalog Description { get; }
```

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

Property Value

(NetAF.Logic.AssetGenerator.html)

Type

+ NetAF.Logic.Callbacks

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Description

Type	Description
EndCheck (NetAF.Logic.EndCheck.html) string (https://learn.microsoft.com/dotnet/api/system.string)	

- NetAF.Logic

Declaration

(NetAF.Logic.html)

```
AssetCatalog Description { get; }
```

(NetAF.Logic.AssetCatalog.html)

AssetGenerator

Property Value

(NetAF.Logic.AssetGenerator.html)

Type

+ NetAF.Logic.Callbacks

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)



- + **NetAF.Conversations**
[\(NetAF.Conversations.html\)](#)
- + **NetAF.Conversations.**
Instructions
[\(NetAF.Conversations.Instruct](#)
- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- + **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
- **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
 - AssetCatalog
[\(NetAF.Logic.AssetCatalog.html\)](#)
 - AssetGenerator
[\(NetAF.Logic.AssetGenerator.html\)](#)
 - EndCheck
[\(NetAF.Logic.EndCheck.html\)](#)
 - EndCheckResult
[\(NetAF.Logic.EndCheckResult.htm](#)
 - ExitMode
[\(NetAF.Logic.ExitMode.html\)](#)
 - Game
[\(NetAF.Logic.Game.html\)](#)
 - GameEndConditions
[\(NetAF.Logic.GameEndConditions.](#)
 - GameInfo
[\(NetAF.Logic.GameInfo.html\)](#)
 - GameState
[\(NetAF.Logic.GameState.html\)](#)
 - PlayableCharacterLocation
[\(NetAF.Logic.PlayableCharacterLo](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)
- + **NetAF.Logic.Configuration**
[\(NetAF.Logic.Configuration.ht](#)
- + **NetAF.Logic.Modes**
[\(NetAF.Logic.Modes.html\)](#)

Enum GameState

Enumeration of game states.

Filter by title

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html)

+ **NetAF.Conversations**
(NetAF.Conversations.html)

Syntax

+ **NetAF.Conversations.**

Instructions

```
public enum GameState  
(NetAF.Conversations.Instruct
```

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Fields

+ **NetAF.Interpretation**

Name	Description
- NetAF.Logic (NetAF.Logic.html)	Active.
Finished	Finished.
AssetCatalog	
Finishing	Finishing.
AssetGenerator	
NotStarted	Not started.

(NetAF.Logic.AssetCatalog.html)
(NetAF.Logic.AssetGenerator.html)
EndCheck
(NetAF.Logic.EndCheck.html)
EndCheckResult
(NetAF.Logic.EndCheckResult.htm)
ExitMode
(NetAF.Logic.ExitMode.html)
Game (NetAF.Logic.Game.html)
GameEndConditions
(NetAF.Logic.GameEndConditions.
GameInfo
(NetAF.Logic.GameInfo.html)
GameState
(NetAF.Logic.GameState.html)
PlayableCharacterLocation
(NetAF.Logic.PlayableCharacterLo

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.htm

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

Class PlayableCharacterLocation

Provides a record of the location of a playable character.

 Filter by title

Inheritance

+ **NetAF.Conversations**

↳ [Object](#) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ PlayableCharacterLocation

+ **NetAF.Conversations**.

Implements

Instructions

[IRestoreFromObjectSerialization](#) ([NetAF.Serialization.IRestoreFromObjectSerialization-1.html](#))<Playable

CharacterLocationSerialization ([NetAF.Serialization.Assets.PlayableCharacterLocationSerialization.html](#))>

+ **NetAF.Extensions**

Inherited Members

- **(NetAF.Extensions.html)**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Interpretation**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

- **NetAF.Logic**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

- **(NetAF.Logic.html)**

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: [NetAF](#) ([NetAF.html](#)).[Logic](#) ([NetAF.Logic.html](#))

Assembly: [NetAF.dll](#)

↳ [\(NetAF.Logic.EndCheck.html\)](#)

Syntax

EndCheckResult

 ([NetAF.Logic.EndCheckResult.html](#))

 public class PlayableCharacterLocation : IRestoreFromObjectSerialization<PlayableCha

 racterLocationSerialization>

 ([NetAF.Logic.ExitMode.html](#))

 Game ([NetAF.Logic.Game.html](#))

 GameEndConditions

 ([NetAF.Logic.GameEndConditions.html](#))

 GameInfo

 ([NetAF.Logic.GameInfo.html](#))

Constructors

PlayableCharacterLocation(string, string, string)

 ([NetAF.Logic.GameState.html](#))

Provides a record of the location of a playable character.

 ([NetAF.Logic.PlayableCharacterLo](#)

 Declaration

+ **NetAF.Logic.Callbacks**

 ([NetAF.Logic.Callbacks.html](#))

 PlayableCharacterLocation(string playerIdentifier, string regionIdentifier, s

 tring roomIdentifier)

+ **NetAF.Logic.Configuration**

 ([NetAF.Logic.Configuration.html](#))

Parameters

+ **NetAF.Logic.Modes**

 ([NetAF.Logic.Modes.html](#))

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>playerIdentifier</i>	The player identifier.
string (https://learn.microsoft.com/dotnet/api/system.string) NetAF.Conversations (NetAF.Conversations.html)	<i>regionIdentifier</i>	The identifier for the region that the player is in.
string + NetAF.Conversations.Instructions (NetAF.Conversations.Instruct	<i>roomIdentifier</i>	The identifier for the room that the player is in.

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Properties

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

PlayerIdentifier

- NetAF.Logic

Get the player.

[\(NetAF.Logic.html\)](#)

Declaration

AssetCatalog

[\(NetAF.Logic.AssetCatalog.html\)](#)

public string PlayerIdentifier { get; }

[\(NetAF.Logic.AssetGenerator.html\)](#)

EndCheck

Property Value

[\(NetAF.Logic.EndCheck.html\)](#)

Type EndCheckResult

Description

[\(NetAF.Logic.EndCheckResult.html\)](#)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Game ([\(NetAF.Logic.Game.html\)](#)

RegionIdentifier

[\(NetAF.Logic.GameEndConditions.html\)](#)

Get the identifier for the region that the player is in.

GamerInfo

Declaration

GameState

[\(NetAF.Logic.GameState.html\)](#)

public string RegionIdentifier { get; }

PlayableCharacterLocation

[\(NetAF.Logic.PlayableCharacterLo](#)

Property Value

+ NetAF.Logic.Callbacks

Type

Description

[\(NetAF.Logic.Callbacks.html\)](#)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

RoomIdentifier

[\(NetAF.Logic.Modes.html\)](#)

Get the identifier for room that the player is in.

Declaration

```
public string RoomIdentifier { get; }
```



Property Value

+ NetAF.Conversations

Type
[\(NetAF.Conversations.html\)](#)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Conversations.

Description

Instructions

[\(NetAF.Conversations.Instruct](#)

Methods

[\(NetAF.Extensions.html\)](#)

FromSerialization(PlayableCharacterLocationSerialization)

[\(NetAF.Interpretation.html\)](#)

Create a new instance of PlayableCharacterLocation from a serialization.

- NetAF.Logic

Declaration

[\(NetAF.Logic.html\)](#)

```
public static PlayableCharacterLocation FromSerialization(PlayableCharacterLocationsS  
e<NetAF.Logic.AssetCatalog> assetCatalog)
```

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

Parameters

EndCheck

Type
[\(NetAF.Logic.EndCheck.html\)](#)

Name

Description

EndCheckResult

PlayableCharacterLocationSerialization
[\(NetAF.Logic.EndCheckResult.html\)](#)

serialization

The
serialization.

[\(NetAF.Serialization.Assets.PlayableCharacterLocationSerialization.html\)](#)

ExitMode
[\(NetAF.Logic.ExitMode.html\)](#)

Returns

Game
[\(NetAF.Logic.Game.html\)](#)

Type
[\(NetAF.Logic.GameEndConditions.html\)](#)

Description

PlayableCharacterLocation
[\(NetAF.Logic.PlayableCharacterLocation.html\)](#)

The location.

[\(NetAF.Logic.GameInfo.html\)](#)

GameState

[\(NetAF.Logic.GameState.html\)](#)

RestoreFrom(PlayableCharacterLocationSerialization)

PlayableCharacterLocation

[\(NetAF.Logic.PlayableCharacterLoca](#)

Restores object from a serialization.

+ NetAF.Logic.Callbacks

Declaration

[\(NetAF.Logic.Callbacks.html\)](#)

```
public void RestoreFrom(PlayableCharacterLocationSerialization serialization)
```

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

Parameters

+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

Type	Name	Description
PlayableCharacterLocationSerialization (NetAF.Serialization.Assets.PlayableCharacterLocationSerialization.h ml)	serialization	The serialization to restore from.

▼

Implements

[IRestoreFromObjectSerialization<T>](#) (NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

+ **NetAF.Conversations.**

Instructions

[\(NetAF.Conversations.Instruct](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

- **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

AssetCatalog

[\(NetAF.Logic.AssetCatalog.html\)](#)

AssetGenerator

[\(NetAF.Logic.AssetGenerator.html\)](#)

EndCheck

[\(NetAF.Logic.EndCheck.html\)](#)

EndCheckResult

[\(NetAF.Logic.EndCheckResult.htm](#)

ExitMode

[\(NetAF.Logic.ExitMode.html\)](#)

Game ([NetAF.Logic.Game.html](#))

GameEndConditions

[\(NetAF.Logic.GameEndConditions.](#)

GameInfo

[\(NetAF.Logic.GameInfo.html\)](#)

GameState

[\(NetAF.Logic.GameState.html\)](#)

PlayableCharacterLocation

[\(NetAF.Logic.PlayableCharacterLo](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.htm](#)

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

Namespace NetAF.Logic.Callbacks

Delegates

GameCreationCallback (NetAF.Logic.Callbacks.GameCreationCallback.html)

+ **NetAF.Commands.Region**

Represents the callback used for Game creation.

Map

(NetAF.Commands.RegionMap)

GameSetupCallback (NetAF.Logic.Callbacks.GameSetupCallback.html)

+ **NetAF.Commands.Scene**

Represents the callback used for Game setup.

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

OverworldCreationCallback

(NetAF.Conversations.html)

(NetAF.Logic.Callbacks.OverworldCreationCallback.html)

+ **NetAF.Conversations**

Represents a callback for Overworld creation.

Instructions

(NetAF.Conversations.Instruct)

PlayerCreationCallback (NetAF.Logic.Callbacks.PlayerCreationCallback.html)

+ **NetAF.Extensions**

Represents a callback for Player creation.

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

- **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

GameCreationCallback

(NetAF.Logic.Callbacks.GameCreationCallback.html)

GameSetupCallback

(NetAF.Logic.Callbacks.GameSetupCallback.html)

OverworldCreationCallback

(NetAF.Logic.Callbacks.OverworldCreationCallback.html)

PlayerCreationCallback

(NetAF.Logic.Callbacks.PlayerCreationCallback.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

Delegate GameCreationCallback

Represents the callback used for Game creation.

 Filter by title

Namespace: [NetAF](#).[NetAE](#).[Logic](#) ([NetAF.Logic.html](#)).Callbacks ([NetAF.Logic.Callbacks.html](#))

Assembly: NetAF.dll

Syntax

+ **NetAF.Commands.Scene**

`public delegate Game GameCreationCallback()`
[\(NetAF.Commands.Scene.html\)](#)

+ **NetAF.Conversations**

Returns

[\(NetAF.Conversations.html\)](#)

Type

+ **NetAF.Conversations.**

`Game` ([NetAF.Logic.Game.html](#))

Instructions

[\(NetAF.Conversations.Instruct](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

- **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

`GameCreationCallback`

[\(NetAF.Logic.Callbacks.GameCreationCallback.html\)](#)

`GameSetupCallback`

[\(NetAF.Logic.Callbacks.GameSetupCallback.html\)](#)

`OverworldCreationCallback`

[\(NetAF.Logic.Callbacks.OverworldCreationCallback.html\)](#)

`PlayerCreationCallback`

[\(NetAF.Logic.Callbacks.PlayerCreationCallback.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

Type	Description
(NetAF.Conversations.html)	A game created by the callback.

Delegate GameSetupCallback

Represents the callback used for Game setup.

Filter by title

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html).Callbacks (NetAF.Logic.Callbacks.html)

Assembly: NetAF.dll
[\(NetAF.Commands.RegionMap\)](#)

Syntax

+ [NetAF.Commands.Scene](#)

([NetAF.Commands.Scene.html](#))

```
public delegate void GameSetupCallback(Game game)
```

+ [NetAF.Conversations](#)

([NetAF.Conversations.html](#))

Parameters

+ [NetAF.Conversations.](#)

	Name	Description
Instructions Game (NetAF.Logic.Game.html) (NetAF.Conversations.Instruct)	game	The game to setup.

+ [NetAF.Extensions](#)

([NetAF.Extensions.html](#))

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

+ [NetAF.Logic](#)

([NetAF.Logic.html](#))

- [NetAF.Logic.Callbacks](#)

([NetAF.Logic.Callbacks.html](#))

GameCreationCallback

([NetAF.Logic.Callbacks.GameCreationCallback.html](#))

GameSetupCallback

([NetAF.Logic.Callbacks.GameSetupCallback.html](#))

OverworldCreationCallback

([NetAF.Logic.Callbacks.OverworldCreationCallback.html](#))

PlayerCreationCallback

([NetAF.Logic.Callbacks.PlayerCreationCallback.html](#))

+ [NetAF.Logic.Configuration](#)

([NetAF.Logic.Configuration.html](#))

+ [NetAF.Logic.Modes](#)

([NetAF.Logic.Modes.html](#))

+ [NetAF.Persistence](#)

([NetAF.Persistence.html](#))

Delegate OverworldCreationCallback

Represents a callback for Overworld creation.

Filter by title

Namespace: NetAF (NetAF.html) Logic (NetAF.Logic.html).Callbacks (NetAF.Logic.Callbacks.html)

Assembly: NetAF.dll

+ **NetAF.Commands.Scene**

Syntax

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations** Overworld OverworldCreationCallback()

(NetAF.Conversations.html)

Returns

+ **NetAF.Conversations**.

Type	Instructions	Description
	(NetAF.Conversations.Instruct Overworld (NetAF.Assets.Locations.Overworld.html))	A generated Overworld.

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

- **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

GameCreationCallback

(NetAF.Logic.Callbacks.GameCreationCallback)

GameSetupCallback

(NetAF.Logic.Callbacks.GameSetupCallback)

OverworldCreationCallback

(NetAF.Logic.Callbacks.OverworldCreationCallback)

PlayerCreationCallback

(NetAF.Logic.Callbacks.PlayerCreationCallback)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Delegate PlayerCreationCallback

Represents a callback for Player creation.

Filter by title

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html).Callbacks (NetAF.Logic.Callbacks.html)

+ **NetAF.Commands.Scene**

Assembly: NetAF.dll

([NetAF.Commands.Scene.html](#))

Syntax

+ **NetAF.Conversations**

 public delegate PlayableCharacter PlayerCreationCallback()

([NetAF.Conversations.html](#))

+ **NetAF.Conversations.**

Returns

Instructions

Type

([NetAF.Conversations.Instruct](#))

Type	Description
PlayableCharacter (NetAF.Assets.Characters.PlayableCharacter.html)	A generated Player.

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

([NetAF.Logic.html](#))

- **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

GameCreationCallback

([NetAF.Logic.Callbacks.GameCreationCallback.html](#))

GameSetupCallback

([NetAF.Logic.Callbacks.GameSetupCallback.html](#))

OverworldCreationCallback

([NetAF.Logic.Callbacks.OverworldCreationCallback.html](#))

PlayerCreationCallback

([NetAF.Logic.Callbacks.PlayerCreationCallback.html](#))

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

+ **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

+ **NetAF.Persistence**

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

Namespace NetAF.Logic.Configuration

Classes

Filter by title

~~ConsoleGameConfiguration~~

(NetAF.Logic.Configuration.ConsoleGameConfiguration.html)

Represents a configuration for a console game.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Interfaces

+ NetAF.Conversations

(NetAF.Conversations.html)

IGameConfiguration (NetAF.Logic.Configuration.IGameConfiguration.html)

+ NetAF.Conversations.

Represents a configuration for a game.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

- NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

ConsoleGameConfiguration

(NetAF.Logic.Configuration.ConsoleGameConfiguration.html)

IGameConfiguration

(NetAF.Logic.Configuration.IGameConfiguration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Class ConsoleGameConfiguration

Represents a configuration for a console game.

Filter by title

Inheritance

+ [NetAF.Commands.RegionMap](#) (https://learn.microsoft.com/dotnet/api/system.object)

ConsoleGameConfiguration

Implements [IGameConfiguration](#) (NetAF.Logic.Configuration.IGameConfiguration.html)

+ [NetAF.Commands.Scene](#)

Inherited Members

([NetAF.Commands.Scene.html](#))

object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

([NetAF.Conversations.html](#))

object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object))

+ [NetAF.Conversations](#)

Instructions

object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

+ [NetAF.Extensions](#)

ToString

NaamSpace: NetAF.Logic (NetAF.Logic.html).Configuration (NetAF.Logic.Configuration.html)

Assembly: NetAF.dll

+ [NetAF.Interpretation](#)

Syntax

([NetAF.Interpretation.html](#))

+ [NetAF.Logic](#)

public sealed class ConsoleGameConfiguration : IGameConfiguration

([NetAF.Logic.html](#))

+ [NetAF.Logic.Callbacks](#)

Constructors

([NetAF.Logic.Callbacks.html](#))

- [NetAF.Logic.Configuration](#)

ConsoleGameConfiguration(Size, ExitMode, IIOWrapper)

ConsoleGameConfiguration

Represents a configuration for a console game.

([NetAF.Logic.Configuration.ConsoleGameConfiguration.html](#))

Declaration

ConsoleGameConfiguration

(NetAF.Logic.Configuration.IGameConfiguration.html)

+ [NetAF.Logic.Modes](#)

Modes

public ConsoleGameConfiguration(Size displaySize, ExitMode exitMode, IIOWrapper adapter)

([NetAF.Logic.Modes.html](#))

+ [NetAF.Persistence](#)

Parameters

([NetAF.Persistence.html](#))

Type

+ [NetAF.Persistence.Json](#)

Size ([NetAF.Assets.Size.html](#))

([NetAF.Persistence.Json.html](#))

ExitMode ([NetAF.Logic.ExitMode.html](#))

+ [NetAF.Rendering](#)

Rendering

([NetAF.Rendering.html](#))

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

+

Type	Name	Description
IIOAdapter (NetAF.Adapters.IIOAdapter.html)	adapter	The I/O adapter.

Properties

+ **NetAF.Commands.Region Adapter Map**

(NetAF.Commands.RegionMap)

Get the I/O adapter.

Declaration

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

Property Value

+ **NetAF.Conversations.**

Type

Description

IInstructions

(NetAF.Conversations.Instruction.html)

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Default

+ **NetAF.Interpretation**

Get the default game configuration.

(NetAF.Interpretation.html)

Declaration

+ **NetAF.Logic**

(NetAF.Logic.html)

public static IGameConfiguration Default { get; }

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Property Value

- **NetAF.Logic.Configuration**

Type

Description

(NetAF.Logic.Configuration.html)

IGameConfiguration (NetAF.Logic.Configuration.IGameConfiguration.html)

ConsoleGameConfiguration

(NetAF.Logic.Configuration.Console)

IGameConfiguration

DisplayCommandListInSceneFrames

Get the value of the `DisplayCommandListInSceneFrames` property.

+ **NetAF.Logic.Modes**

list is displayed in scene frames.

(NetAF.Logic.Modes.html)

Declaration

+ **NetAF.Persistence**

public bool DisplayCommandListInSceneFrames { get; set; }

+ **NetAF.Persistence.Json**

Property Value

(NetAF.Persistence.Json.html)

+ **NetAF.Rendering**

Type	Description
bool (https://learn.microsoft.com/dotnet/api/system.boolean)	

DisplaySize

Get the display size.

+ NetAF.Commands.Region

Declaration

Map

([NetAF.Commands.RegionMap.html](#))

+ NetAF.Commands.Scene

([NetAF.Commands.Scene.html](#))

+ Type

Description

([NetAF.Conversations.html](#))

+ NetAF.Conversations.

Instructions

Error Prefix

([NetAF.Conversations.Instruct.html](#))

- NetAF.Extensions

use when displaying errors.

([NetAF.Extensions.html](#))

+ NetAF.Interpretation

public string ErrorPrefix { get; set; }

([NetAF.Interpretation.html](#))

+ NetAF.Logic

Property Value

([NetAF.Logic.html](#))

Type

+ NetAF.Logic.Callbacks

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Description

- NetAF.Logic.Configuration

([NetAF.Logic.Configuration.html](#))

ExitMode

ConsoleGameConfiguration

Get the exit mode.

([NetAF.Logic.Configuration.ConsoleGameConfiguration.html](#))

IGameConfiguration

Declaration

([NetAF.Logic.Configuration.IGameConfiguration.html](#))

+ NetAF.Logic.Modes

public ExitMode { get; }

([NetAF.Logic.Modes.html](#))

Property Value

+ NetAF.Persistence

([NetAF.Persistence.html](#))

Description

+ NetAF.Persistence.Json

([NetAF.Persistence.Json.html](#))

+ NetAF.Rendering

FrameBuilders

Get or set the collection of frame builders to use to render the game.

Declaration

```
public FrameBuilderCollection FrameBuilders { get; set; }
```

Property Value

+ NetAF.Commands.Region

Type

(NetAF.Commands.Region.html)

FrameBuilderCollection (NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Interpreter

+ NetAF.Conversations

(NetAF.Conversations.html)

Get or set the interpreter for interpreting input.

- NetAF.Conversations.

Instructions

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

Property Value

(NetAF.Extensions.html)

Type

+ NetAF.Interpretation

Interpreter (NetAF.Interpretation.Interpreter.html)

+ NetAF.Logic

(NetAF.Logic.html)

SceneMapKeyType

+ NetAF.Logic.Callbacks

Get or set the type of key to use on the scene map.

(NetAF.Logic.Callbacks.html)

Declaration

- NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

```
public KeyType SceneMapKeyType { get; set; }
```

ConsoleGameConfiguration

(NetAF.Logic.Configuration.ConsoleGameConfiguration.html)

Property Value

IGameConfiguration

Type

(NetAF.Logic.Configuration.IGameConfiguration.html)

Description

+ NetAF.Logic.Modes

KeyType (NetAF.Rendering.KeyType.html)

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

Implements

(NetAF.Persistence.html)

IGameConfiguration (NetAF.Logic.Configuration.IGameConfiguration.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

▼

- + **NetAF.Commands.Region**
Map
(NetAF.Commands.RegionMap)
- + **NetAF.Commands.Scene**
(NetAF.Commands.Scene.html)
- + **NetAF.Conversations**
(NetAF.Conversations.html)
- + **NetAF.Conversations.**
Instructions
(NetAF.Conversations.Instruct)
- + **NetAF.Extensions**
(NetAF.Extensions.html)
- + **NetAF.Interpretation**
(NetAF.Interpretation.html)
- + **NetAF.Logic**
(NetAF.Logic.html)
- + **NetAF.Logic.Callbacks**
(NetAF.Logic.Callbacks.html)
- **NetAF.Logic.Configuration**
(NetAF.Logic.Configuration.html)
 - ConsoleGameConfiguration
(NetAF.Logic.Configuration.ConsoleGameConfiguration)
 - IGameConfiguration
(NetAF.Logic.Configuration.IGameConfiguration)
- + **NetAF.Logic.Modes**
(NetAF.Logic.Modes.html)
- + **NetAF.Persistence**
(NetAF.Persistence.html)
- + **NetAF.Persistence.Json**
(NetAF.Persistence.Json.html)
- + **NetAF.Rendering**
...

Interface IGameConfiguration

Represents a configuration for a game.

Filter by title

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html).Configuration (NetAF.Logic.Configuration.html)

Assembly: NetAF.dll

+ **NetAF.Commands.Region**

Syntax

Map

(**NetAF.Commands.RegionMap**
public interface IGameConfiguration

+ **NetAF.Commands.Scene**

(**NetAF.Commands.Scene.html**

+ **NetAF.Conversations**

(**NetAF.Conversations.html**)

+ **NetAF.Conversations.**

Adapters

(**NetAF.Conversations.Instruct**

Get the I/O adapter.

+ **NetAF.Extensions**

Declaration

(**NetAF.Extensions.html**)

+ **NetAF.Interpretation** { get; }

(**NetAF.Interpretation.html**)

Property Value

+ **NetAF.Logic**

Type (**NetAF.Logic.html**)

Description

+ **NetAF.Logic.Callbacks**

(**NetAF.Logic.Callbacks.html**)

- **NetAF.Logic.Configuration**

DisplayCommandListInSceneFrames

(**NetAF.Logic.Configuration.html**)

Get Configuration displayed in scene frames.

(**NetAF.Logic.Configuration.Console**

Declaration

IGameConfiguration

(**NetAF.Logic.Configuration.IGameConfiguration**

bool DisplayCommandListInSceneFrames { get; set; }

+ **NetAF.Logic.Modes**

(**NetAF.Logic.Modes.html**)

Property Value

+ **NetAF.Persistence**

Type (**NetAF.Persistence.html**)

Description

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

+ **NetAF.Persistence.Json**

(**NetAF.Persistence.Json.html**)

DisplaySize

DisplaySize

Property Value

Type	Description
FrameBuilderCollection (NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)	

Interpreter

Get or set the interpreter used for interpreting input.

NetAF.Commands.Region

Declaration

(NetAF.Commands.RegionMap

+ `TTInterpreter Interpreter { get; set; }`

NetAF.Commands.Scene

(NetAF.Commands.Scene.html

Property Value

NetAF.Conversations

Type [\(NetAF.Conversations.html\)](#)

Description

+ `IIInterpreter Interpreter (NetAF.Interpretation.IIInterpreter.html)`

Instructions

(NetAF.Conversations.Instruct

SceneMapKeyType

+ `NetAF.Extensions`

Get or set the type of key to use on the scene map.

(NetAF.Extensions.html)

Declaration

NetAF.Interpretation

(NetAF.Interpretation.html)

`KeyType SceneMapKeyType { get; set; }`

NetAF.Logic

(NetAF.Logic.html)

Property Value

NetAF.Logic.Callbacks

Type

(NetAF.Logic.Callbacks.html)

`KeyType (NetAF.Rendering.KeyType.html)`

Description

NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

ConsoleGameConfiguration

[\(NetAF.Logic.Configuration.ConsoleGameConfiguration.html\)](#)

IGameConfiguration

[\(NetAF.Logic.Configuration.IGameConfiguration.html\)](#)

NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

NetAF.Persistence

(NetAF.Persistence.html)

NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

NetAF.Rendering

Namespace NetAF.Logic.Modes

Classes

Filter by title

[AboutMode \(NetAF.Logic.Modes.AboutMode.html\)](#)
(NetAF.Commands.RegionMap)

+ [NetAF.Commands.Scene](#)
Provides a display mode for about.
(NetAF.Commands.Scene.html)

[CompletionMode \(NetAF.Logic.Modes.CompletionMode.html\)](#)

(NetAF.Conversations.html)
Provides a display mode for completion.

+ [NetAF.Conversations](#).

[ConversationMode \(NetAF.Logic.Modes.ConversationMode.html\)](#)

(NetAF.Conversations.Instruct)
Provides a display mode for conversation.

+ [NetAF.Extensions](#)

[GameOverMode \(NetAF.Logic.Modes.GameOverMode.html\)](#)

+ [NetAF.Interpretation](#) for game over.
(NetAF.Interpretation.html)

[HelpMode \(NetAF.Logic.Modes.HelpMode.html\)](#)

(NetAF.Logic.html)
Provides a display mode for help.

+ [NetAF.Logic.Callbacks](#)

[ReactionMode \(NetAF.Logic.Modes.ReactionMode.html\)](#)

+ [NetAF.Logic.Configuration](#)

(NetAF.Logic.Configuration.html)

[RegionMapMode \(NetAF.Logic.Modes.RegionMapMode.html\)](#)

(NetAF.Logic.Modes.html)
Provides a display mode for region map.

AboutMode

(NetAF.Logic.Modes.AboutMode.html)

[SceneMode \(NetAF.Logic.Modes.SceneMode.html\)](#)

CompletionMode
Provides a display mode for a scene.
(NetAF.Logic.Modes.CompletionMode.html)

ConversationMode

(NetAF.Logic.Modes.ConversationMode.html)

[TitleMode \(NetAF.Logic.Modes.TitleMode.html\)](#)

GameModeType
Provides a display mode for title.
(NetAF.Logic.Modes.GameModeType.html)

GameOverMode

(NetAF.Logic.Modes.GameOverMode.html)

[Interfaces](#)

(NetAF.Logic.Modes.Interfaces.GameOverMode.html)

HelpMode

(NetAF.Logic.Modes.HelpMode.html)

[IGameMode \(NetAF.Logic.Modes.IGameMode.html\)](#)

(NetAF.Logic.Modes.IGameMode.html)
Represents a mode for a game.

ReactionMode

Enums

GameModeType (NetAF.Logic.Modes.GameModeType.html)

Enumeration of game mode types.

▼

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.ht

- NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

AboutMode

(NetAF.Logic.Modes.AboutMode.h

CompletionMode

(NetAF.Logic.Modes.CompletionMo

ConversationMode

(NetAF.Logic.Modes.Conversation

GameModeType

(NetAF.Logic.Modes.GameModeTy

GameOverMode

(NetAF.Logic.Modes.GameOverMo

HelpMode

(NetAF.Logic.Modes.HelpMode.htm

IGameMode

(NetAF.Logic.Modes.IGameMode.h

ReactionMode

Class AboutMode

Provides a display mode for about.

Filter by title

Inheritance

+ NetAF.Commands.Scene

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ AboutMode

+ NetAF.Conversations

Implements

([NetAF.Conversations.html](#))

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ NetAF.Conversations.

Inherited Members

Instructions

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Extensions.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAF.Logic

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

([NetAF.Logic.html](#))

Assembly: NetAF.dll

+ NetAF.Logic.Callbacks

([NetAF.Logic.Callbacks.html](#))

public sealed class AboutMode : IGameMode

+ NetAF.Logic.Configuration

([NetAF.Logic.Configuration.html](#))

- NetAF.Logic.Modes

([NetAF.Logic.Modes.html](#))

Properties

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

Interpreter

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

Get the interpreter

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

Declaration

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

public Interpreter Interpreter { get; }

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

Property Value

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

Description

Interpreter ([NetAF.Interpretation.Interpreter.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

—

Type

Get the type of mode this provides.

Declaration

```
public GameModeType Type { get; }
```

+ NetAF.Commands.Scene

Property Value

(NetAF.Commands.Scene.html)

Type

+ NetAF.Conversations

GameModeType (NetAF.Logic.Modes.GameModeType.html)

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

Methods

+ NetAF.Extensions

(NetAF.Extensions.html)

Render(Game)

+ NetAF.Interpretation

Render the current state of a game.

(NetAF.Interpretation.html)

Declaration

+ NetAF.Logic

(NetAF.Logic.html) (Game game)

+ NetAF.Logic.Callbacks

Parameters

(NetAF.Logic.Callbacks.html)

Type

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

- NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Implements

AboutMode

IGameMode (NetAF.Logic.Modes.IGameMode.html)

(NetAF.Logic.Modes.AboutMode.html)

CompletionMode

(NetAF.Logic.Modes.CompletionMode.html)

ConversationMode

(NetAF.Logic.Modes.ConversationMode.html)

GameModeType

(NetAF.Logic.Modes.GameModeType.html)

GameOverMode

(NetAF.Logic.Modes.GameOverMode.html)

HelpMode

(NetAF.Logic.Modes.HelpMode.html)

IGameMode

(NetAF.Logic.Modes.IGameMode.html)

ReactionMode

(NetAF.Logic.Modes.ReactionMode.html)

Description

Class CompletionMode

Provides a display mode for completion.

Filter by title

Inheritance

([NetAF.Commands.Scene.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF Conversations**

([NetAF Conversations.html](#))

Implements

+ [IGameMode](#) ([NetAF Modes.IGameMode.html](#))

Instructions

([NetAF Conversations.Instruct](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Extensions**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ [NetAF Interpretation](#) (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ **NetAF Logic**

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF Logic.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

Associated: NetAF!Callbacks

Syntax: ([NetAF.Logic.Callbacks.html](#))

+ **NetAF.Logic.Configuration**

public sealed class CompletionMode : IGameMode
([NetAF.Logic.Configuration.html](#))

- **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

Constructors

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode(string, string)

([NetAF.Logic.Modes.CompletionMode.html](#))

Provides a display mode for completion.

ConversationMode

Declaration: [NetAF.Logic.Modes.Conversation!](#)

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

Parameters

HelpMode

Type	Name	Description
NetAF.Logic.Modes.HelpMode.html		
IGameMode		

string (<https://learn.microsoft.com/dotnet/api/system.string>)

title

The title.

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

message

The message.

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

Implements

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

▼

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

+ **NetAF.Conversations.**

Instructions

([NetAF.Conversations.Instruct](#))

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

([NetAF.Logic.html](#))

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

- **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

Class ConversationMode

Provides a display mode for conversation.

Filter by title

Inheritance

+ [NetAF.Conversations](#)
([NetAF.Conversations.html](#))

+ [NetAF.Conversations](#).
Instructions
([NetAF.Conversations.Instruct](#))

+ [NetAF.Extensions](#)
([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object, system-object\)](#))

+ [NetAF.Interpretation](#).
Object
([NetAF.Interpretation.html](#))

object.GetHashCode() ([https://learn.microsoft.com/dotnet/api/system.object.gethashcode](#))

object.GetType() ([https://learn.microsoft.com/dotnet/api/system.object.gettype](#))

+ [NetAF.Logic](#)
object.ReferenceEquals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.referenceequals](#))
([NetAF.Logic.html](#)) ([https://learn.microsoft.com/dotnet/api/system.object.tostring](#))

Namespace: NetAF ([NetAF.html](#)) Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))
Assembly: NetAF.dll
([NetAF.Logic.Callbacks.html](#))

Syntax

+ [NetAF.Logic.Configuration](#)
([NetAF.Logic.Configuration.html](#))

public sealed class ConversationMode : IGameMode

- [NetAF.Logic.Modes](#)

([NetAF.Logic.Modes.html](#))

Constructors

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

Initializes a new instance of the ConversationMode class.

([NetAF.Logic.Modes.ConversationMode.html](#))

Declaration

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

Parameters

([NetAF.Logic.Modes.HelpMode.html](#))

Type	Name	Description
GameMode		
(NetAF.Logic.Modes.IGameMode.html)		
IConverser	converser	The IConverser the conversation is being held with.
ReactionMode		
(NetAF.Logic.Modes.ReactionMode.html)		
RegionMapMode		
(NetAF.Logic.Modes.RegionMapMode.html)		
...		

Properties

Converser

Get the converser.



Declaration

+ NetAF.Conversations

```
public IConverser Converser { get; }
```

(NetAF.Conversations.html)

NetAF.Conversations.

Instructions

Type

(NetAF.Conversations.Instruct

IConverser (NetAF.Assets.Characters.IConverser.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

Interpreter

Interpretation

(NetAF.Interpretation.html)

Get the interpreter.

+ NetAF.Logic

Declaration

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

NetAF.Logic.Configuration

Type

(NetAF.Logic.Configuration.htm

Description

- NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

AboutMode

Type

(NetAF.Logic.Modes.AboutMode.h

CompletionMode

Get the type of mode this provides.

(NetAF.Logic.Modes.CompletionMo

ConversationMode

(NetAF.Logic.Modes.Conversation

GameModeType

```
public GameModeType Type { get; }
```

(NetAF.Logic.Modes.GameModeTy

GameOverMode

Property Value

(NetAF.Logic.Modes.GameOverMo

Type

(NetAF.Logic.Modes.HelpMode.htm

GameModeType (NetAF.Logic.Modes.GameModeType.html)

Description

(NetAF.Logic.Modes.IGameMode.h

ReactionMode

(NetAF.Logic.Modes.ReactionMode

RegionMapMode

(NetAF.Logic.Modes.RegionMapMo

- ...

Methods

Render(Game)

Render the current state of a game.

Declaration

```
public void Render(Game game)
```

Parameters

+ NetAF.Conversations

Type (NetAF.Conversations.html)

+ NetAF.Conversations (NetAF.Conversations.html)

Instructions

(NetAF.Conversations.Instruct)

Implements

+ NetAF.Extensions

IGameMode (NetAF.Logic.Modes.IGameMode.html)
(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

- NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

AboutMode

(NetAF.Logic.Modes.AboutMode.html)

CompletionMode

(NetAF.Logic.Modes.CompletionMode.html)

ConversationMode

(NetAF.Logic.Modes.ConversationMode.html)

GameModeType

(NetAF.Logic.Modes.GameModeType.html)

GameOverMode

(NetAF.Logic.Modes.GameOverMode.html)

HelpMode

(NetAF.Logic.Modes.HelpMode.html)

IGameMode

(NetAF.Logic.Modes.IGameMode.html)

ReactionMode

(NetAF.Logic.Modes.ReactionMode.html)

RegionMapMode

(NetAF.Logic.Modes.RegionMapMode.html)

- ...

Enum GameModeType

Enumeration of game mode types.

Filter by title

Namespace: NetAF (NetAF.html).Logic (NetAF.Logic.html).Modes (NetAF.Logic.Modes.html)

+ **NetAF.Conversations**

Assembly: NetAF.dll

(NetAF.Conversations.html)

Syntax

+ **NetAF.Conversations.**

Instructions

public enum GameModeType

(NetAF.Conversations.Instruct

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Fields

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

Description

+ **NetAF.Logic**

Information

(NetAF.Logic.html)

Interactive

An information mode.

An interactive mode.

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

- **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

AboutMode

(NetAF.Logic.Modes.AboutMode.html)

CompletionMode

(NetAF.Logic.Modes.CompletionMode.html)

ConversationMode

(NetAF.Logic.Modes.ConversationMode.html)

GameModeType

(NetAF.Logic.Modes.GameModeType.html)

GameOverMode

(NetAF.Logic.Modes.GameOverMode.html)

HelpMode

(NetAF.Logic.Modes.HelpMode.html)

IGameMode

(NetAF.Logic.Modes.IGameMode.html)

ReactionMode

(NetAF.Logic.Modes.ReactionMode.html)

Class GameOverMode

Provides a display mode for game over.

Filter by title

Inheritance

([NetAF.Conversations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF Conversations.**

↳ GameOverMode

Instructions

Implements

([NetAF.Conversations.Instruct](#)

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ **NetAF Extensions**

Inherited Members

([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-system-object)))

+ **NetAF Interpretation**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-system-object-object)))

+ **NetAF Logic**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ **NetAF Logic Callbacks**

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Callbacks.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

* **NetAF Logic Configuration**

([NetAF.Logic.Configuration.html](#))

Syntax

- **NetAF.Logic.Modes**

public sealed class GameOverMode : IGameMode

([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

GameModeType

Provides a display mode for game over.

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

public GameOverMode(string title, string message)

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

Parameters

([NetAF.Logic.Modes.IGameMode.html](#))

Type ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

string (<https://learn.microsoft.com/dotnet/api/system.string>)

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

string (<https://learn.microsoft.com/dotnet/api/system.string>)

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

Type	Name	Description
ReactionMode		
string (https://learn.microsoft.com/dotnet/api/system.string)	title	The title.
RegionMapMode		
string (https://learn.microsoft.com/dotnet/api/system.string)	message	The message.
SceneMode		
(NetAF.Logic.Modes.SceneMode.html)		

Properties

Interpreter

Get the interpreter.

Declaration

[\(NetAF.Conversations.html\)](#)

```
public IInterpreter Interpreter { get; }
```

+ [NetAF.Conversations](#).

Instructions

Property Value

[\(NetAF.Conversations.Instruct](#)

Type
+ [NetAF.Extensions](#)

Description

[\(NetAF.Extensions.html\)](#)

+ [NetAF.Interpretation](#)

[\(NetAF.Interpretation.html\)](#)

Type

+ [NetAF.Logic](#)

Get the type of mode this provides.

[\(NetAF.Logic.html\)](#)

Declaration

+ [NetAF.Logic.Callbacks](#)

[\(NetAF.Logic.Callbacks.html\)](#)

```
public GameModeType Type { get; }
```

+ [NetAF.Logic.Configuration](#)

[\(NetAF.Logic.Configuration.html\)](#)

Property Value

- Type
+ [NetAF.Logic.Modes](#)

Description

[\(NetAF.Logic.Modes.html\)](#)

GameModeType ([NetAF.Logic.Modes.GameModeType.html](#))

AboutMode

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

CompletionMode

[\(NetAF.Logic.Modes.CompletionMode.html\)](#)

ConversationMode

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

[\(NetAF.Logic.Modes.GameModeType.html\)](#)

GameOverMode

Render the current state of a game.

[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

Declaration

HelpMode

[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode Render (Game game)

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

ReactionMode

Parameters
[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

Type
RegionMapMode

[\(NetAF.Logic.Modes.RegionMapMode.html\)](#)

Game ([NetAF.Logic.Game.html](#))

SceneMode

[\(NetAF.Logic.Modes.SceneMode.html\)](#)

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

... . . .

Implements

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

▼

([NetAF.Conversations.html](#))

- + **NetAF.Conversations.**
Instructions
[\(NetAF.Conversations.Instruct](#)
- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- + **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
- + **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)
- + **NetAF.Logic.Configuration**
[\(NetAF.Logic.Configuration.ht](#)
- **NetAF.Logic.Modes**
[\(NetAF.Logic.Modes.html\)](#)
 - AboutMode
[\(NetAF.Logic.Modes.AboutMode.h](#)
 - CompletionMode
[\(NetAF.Logic.Modes.CompletionMo](#)
 - ConversationMode
[\(NetAF.Logic.Modes.Conversation](#)
 - GameModeType
[\(NetAF.Logic.Modes.GameModeTy](#)
 - GameOverMode
[\(NetAF.Logic.Modes.GameOverMo](#)
 - HelpMode
[\(NetAF.Logic.Modes.HelpMode.htm](#)
 - IGameMode
[\(NetAF.Logic.Modes.IGameMode.h](#)
 - ReactionMode
[\(NetAF.Logic.Modes.ReactionMode](#)
 - RegionMapMode
[\(NetAF.Logic.Modes.RegionMapMo](#)
 - SceneMode
[\(NetAF.Logic.Modes.SceneMode.h](#)
 -

Class HelpMode

Provides a display mode for help.

Filter by title

Inheritance

([NetAF.Conversations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Conversations.**

↳ HelpMode

Instructions

Implements

([NetAF.Conversations.Instruct](#)

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ **NetAF.Extensions**

Inherited Members

([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#)) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Logic**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Callbacks.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

+ **NetAF.Logic.Configuration**

Assembly: NetAF.dll

([NetAF.Logic.Configuration.html](#))

Syntax

- **NetAF.Logic.Modes**

public sealed class HelpMode : IGameMode

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

Constructors

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

Provides a display mode for help.

([NetAF.Logic.Modes.GameModeType.html](#))

Declaration

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

public HelpMode(CommandHelp[] commands)

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

Parameters

([NetAF.Logic.Modes.IGameMode.html](#))

Type

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

CommandHelp[]

([NetAF.Commands.CommandHelp.html](#))[]

Name

Description

commands

The commands to display.

RegionMapMode

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Properties

Interpreter

Get the interpreter.



Declaration

[\(NetAF.Conversations.html\)](#)

+ **NetAF.Conversations.**

Instructions

Provides the instructions.

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

Description

Provides the interpretation.

[\(NetAF.Interpretation.html\)](#)

Type

+ **NetAF.Logic**

Gets the logic.

[\(NetAF.Logic.html\)](#) provides.

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

public GameModeType Type { get; }

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

Property Value

- **NetAF.Logic.Modes**

Type

[\(NetAF.Logic.Modes.html\)](#)

GameModeType ([NetAF.Logic.Modes.GameModeType.html](#))

Description

AboutMode

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

CompletionMode

[\(NetAF.Logic.Modes.CompletionMode.html\)](#)

ConversationMode

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

[\(NetAF.Logic.Modes.GameModeType.html\)](#)

GameOverMode

Render the current state of a game.

[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

HelpMode

[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode

public void Render(Game game)

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

ReactionMode

Parameters

[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

Type

[RegionMapMode](#)

[\(NetAF.Logic.Modes.RegionMapMode.html\)](#)

Game ([NetAF.Logic.Game.html](#))

SceneMode

[\(NetAF.Logic.Modes.SceneMode.html\)](#)

TitleMode

Type	Name	Description
RegionMapMode	game	The game.

Implements

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

▼

([NetAF.Conversations.html](#))

- + **NetAF.Conversations.**
Instructions
([NetAF.Conversations.Instruct](#))
- + **NetAF.Extensions**
([NetAF.Extensions.html](#))
- + **NetAF.Interpretation**
([NetAF.Interpretation.html](#))
- + **NetAF.Logic**
([NetAF.Logic.html](#))
- + **NetAF.Logic.Callbacks**
([NetAF.Logic.Callbacks.html](#))
- + **NetAF.Logic.Configuration**
([NetAF.Logic.Configuration.html](#))
- **NetAF.Logic.Modes**
([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Interface IGameMode

Represents a mode for a game.

Filter by title

Namespace: NetAF (NetAF.html) Logic (NetAF.Logic.html).Modes (NetAF.Logic.Modes.html)

Assembly: NetAF.dll

+ **NetAF.Conversations.**

Syntax

Instructions

([NetAF Conversations Instructions](#))

public interface IGameMode

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

Properties ([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

Interpreter ([NetAF.Logic.html](#))

Get the interpreter.

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

Declaration

+ **NetAF.Logic.Configuration**

IInterpreter Interpreter { get; }

([NetAF.Logic.Configuration.html](#))

- **NetAF.Logic.Modes**

Property Value

([NetAF.Logic.Modes.html](#))

Type

AboutMode

IInterpreter ([NetAF.Interpretation.IInterpreter.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

Get the type of mode this provides.

([NetAF.Logic.Modes.GameModeType.html](#))

Declaration

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

GameModeType Type { get; }

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

Property Value

([NetAF.Logic.Modes.IGameMode.html](#))

Type

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

GameModeType ([NetAF.Logic.Modes.GameModeType.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Description

Methods

Render(Game)

Render the current state of a game.

Declaration
[\(NetAF.Conversations.html\)](#)

+ **NetAF.Conversations.**

Instructions

Part of [NetAF](#)

+ **Type**

[\(NetAF.Extensions.html\)](#)

Game ([NetAF.Logic.Game.html](#))

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

- **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

AboutMode

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

CompletionMode

[\(NetAF.Logic.Modes.CompletionMode.html\)](#)

ConversationMode

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

[\(NetAF.Logic.Modes.GameModeType.html\)](#)

GameOverMode

[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

HelpMode

[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

ReactionMode

[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

RegionMapMode

[\(NetAF.Logic.Modes.RegionMapMode.html\)](#)

SceneMode

[\(NetAF.Logic.Modes.SceneMode.html\)](#)

TitleMode

[\(NetAF.Logic.TitleMode.html\)](#)

Type	Name	Description
Game (NetAF.Logic.Game.html)	game	The game.

Class ReactionMode

Provides a display mode for reaction.

Filter by title

Inheritance

([NetAF.Conversations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Conversations.**

↳ ReactionMode

Instructions

Implements

([NetAF.Conversations.Instruct](#)

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ **NetAF.Extensions**

Inherited Members

([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#)) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Callbacks.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

+ **NetAF.Logic.Configuration**

Assembly: NetAF.dll

([NetAF.Logic.Configuration.html](#))

Syntax

- **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

Constructors

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

ReactionMode(string, string)

([NetAF.Logic.Modes.GameMode.html](#))

Provides a display mode for reaction.

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

public ReactionMode(string title, string message)

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

Parameters

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Name

Description

title

The title.

([NetAF.Logic.Modes.RegionMapMode.html](#))

message

The message.

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Properties

Interpreter

Get the interpreter.



Declaration

[\(NetAF.Conversations.html\)](#)

+ **NetAF.Conversations.**

Instructions

Provides the instructions.

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

Description

Provides the interpretation.

[\(NetAF.Interpretation.html\)](#)

Type

+ **NetAF.Logic**

Gets the logic.

[\(NetAF.Logic.html\)](#) provides.

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

public GameModeType Type { get; }

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

Property Value

- **NetAF.Logic.Modes**

Type

[\(NetAF.Logic.Modes.html\)](#)

GameModeType ([NetAF.Logic.Modes.GameModeType.html](#))

Description

AboutMode

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

CompletionMode

[\(NetAF.Logic.Modes.CompletionMode.html\)](#)

ConversationMode

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

[\(NetAF.Logic.Modes.GameModeType.html\)](#)

GameOverMode

Render the current state of a game.

[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

HelpMode

[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode

public void Render(Game game)

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

ReactionMode

Parameters

[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

Type

RegionMapMode

[\(NetAF.Logic.Modes.RegionMapMode.html\)](#)

Game ([NetAF.Logic.Game.html](#))

SceneMode

[\(NetAF.Logic.Modes.SceneMode.html\)](#)

TitleMode

Type	Name	Description
GameModeType (NetAF.Logic.Game.html)	game	The game.

Implements

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

▼

([NetAF.Conversations.html](#))

- + **NetAF.Conversations.**
Instructions
([NetAF.Conversations.Instruct](#))
- + **NetAF.Extensions**
([NetAF.Extensions.html](#))
- + **NetAF.Interpretation**
([NetAF.Interpretation.html](#))
- + **NetAF.Logic**
([NetAF.Logic.html](#))
- + **NetAF.Logic.Callbacks**
([NetAF.Logic.Callbacks.html](#))
- + **NetAF.Logic.Configuration**
([NetAF.Logic.Configuration.html](#))
- **NetAF.Logic.Modes**
([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Class RegionMapMode

Provides a display mode for region map.

Filter by title

Inheritance

([NetAF.Conversations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Conversations.**

↳ RegionMapMode

Instructions

Implements

([NetAF.Conversations.Instruct](#))

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ **NetAF.Extensions**

Inherited Members

([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#)) // [https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object))

equals(system-object-system-object))

+ **NetAF.Logic**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Callbacks.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

+ **NetAF.Logic.Configuration**

Assembly: NetAF.dll

([NetAF.Logic.Configuration.html](#))

Syntax

- **NetAF.Logic.Modes**

public sealed class RegionMapMode : IGameMode

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

Constructors

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

GameModeType

Provides a display mode for region map.

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

public RegionMapMode(Point3D focusPosition)

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

Parameters

([NetAF.Logic.Modes.IGameMode.html](#))

Type	Name	Description
ReactionMode	(NetAF.Logic.Modes.ReactionMode.html)	
Point3D	RegionMapMode	The position to focus on. To use the player position use RegionMapMode.Player.
(NetAF.Logic.Modes.Point3D.html)	focusPosition	
SceneMode	(NetAF.Logic.Modes.SceneMode.html)	
TitleMode	(NetAF.Logic.Modes.TitleMode.html)	

Properties

FocusPosition

Get or set the position to focus on. To use the player position use RegionMapMode.Player.

Declaration
[\(NetAF.Conversations.html\)](#)

+ **NetAF.Conversations.**[FocusPosition](#) { get; set; }

Instructions

Properties
[\(NetAF.Conversations.Instruct](#)

+ **Type**
[NetAF.Extensions](#)

[\(NetAF.Extensions.html\)](#)
POINT3D ([NetAF.Assets.POINT3D.html](#))

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

Interpreter

+ **NetAF.Logic**

Get [\(NetAF.Logic.html\)](#)

Declarations
[NetAF.Logic.Callbacks](#)

[\(NetAF.Logic.Callbacks.html\)](#)

public IInterpreter Interpreter { get; }

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

Property Value

- **NetAF.Logic.Modes**

Type

[\(NetAF.Logic.Modes.html\)](#)

IInterpreter ([NetAF.Interpretation.IInterpreter.html](#))
AboutMode

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

CompletionMode

Player
[\(NetAF.Logic.Modes.CompletionMode.html\)](#)

ConversationMode

Get the value to use to display the player level.

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

[\(NetAF.Logic.Modes.GameModeType.html\)](#)

GameOverMode

public static Point3D Player { get; }
[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

HelpMode

Properties
[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode

Type

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

Point3D ([NetAF.Assets.POINT3D.html](#))

[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

RegionMapMode

[\(NetAF.Logic.Modes.RegionMapMode.html\)](#)

Type

SceneMode

[\(NetAF.Logic.Modes.SceneMode.html\)](#)

Get the type of mode this provides.

TitleMode

[\(NetAF.Logic.Modes.TitleMode.html\)](#)

Get the type of mode this provides.

TitleMode

Description

Type
[\(NetAF.Logic.Modes.html\)](#)

IInterpreter ([NetAF.Interpretation.IInterpreter.html](#))
AboutMode

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

CompletionMode

[\(NetAF.Logic.Modes.CompletionMode.html\)](#)

ConversationMode

Get the value to use to display the player level.

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

[\(NetAF.Logic.Modes.GameModeType.html\)](#)

GameOverMode

public static Point3D Player { get; }
[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

HelpMode

Properties
[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode

Type

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

Point3D ([NetAF.Assets.POINT3D.html](#))

[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

RegionMapMode

[\(NetAF.Logic.Modes.RegionMapMode.html\)](#)

Type

SceneMode

[\(NetAF.Logic.Modes.SceneMode.html\)](#)

Get the type of mode this provides.

TitleMode

[\(NetAF.Logic.Modes.TitleMode.html\)](#)

Get the type of mode this provides.

TitleMode

Declaration

```
public GameModeType Type { get; }
```

Property Value

Type	Description
(NetAF.Conversations.html) GameModeType (NetAF.Logic.Modes.GameModeType.html)	

+ NetAF.Conversations.

Instructions

[\(NetAF.Conversations.Instruct.html\)](#)

Methods

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

CanPanToPosition(Region, Point3D)

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Declarations

NetAF.Logic

[\(NetAF.Logic.html\)](#)

```
public static bool CanPanToPosition(Region region, Point3D position)
```

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Parameters

Type	Name	Description
(NetAF.Logic.Configuration.html) Region (NetAF.Assets.Locations.Region.html)	region	The region.
(NetAF.Logic.Modes.html) Point3D (NetAF.Assets.Point3D.html)	position	The position.

AboutMode

Returns

[\(NetAF.Logic.Modes.AboutMode.html\)](#)

Type

[CompletionMode](#)

Type	Description
(NetAF.Logic.Modes.CompletionMode.html) bool (https://learn.microsoft.com/dotnet/api/system.boolean)	True if the pan position is valid, else false.

ConversationMode

[\(NetAF.Logic.Modes.ConversationMode.html\)](#)

GameModeType

Render(Game)

[\(NetAF.Logic.Modes.RenderGame.html\)](#)

GameOverMode

Render the current state of a game

[\(NetAF.Logic.Modes.GameOverMode.html\)](#)

HelpMode

[\(NetAF.Logic.Modes.HelpMode.html\)](#)

IGameMode

[\(NetAF.Logic.Modes.IGameMode.html\)](#)

ReactionMode

Parameters

[\(NetAF.Logic.Modes.ReactionMode.html\)](#)

Type

[RegionMapMode](#)

Game

[\(NetAF.Logic.Game.html\)](#)

TitleMode

(NetAF.Logic.SceneMode.html)

Type	Name	Description
	game	The game.

Implements

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

▼

([NetAF.Conversations.html](#))

- + **NetAF.Conversations.**
Instructions
([NetAF.Conversations.Instruct](#))
- + **NetAF.Extensions**
([NetAF.Extensions.html](#))
- + **NetAF.Interpretation**
([NetAF.Interpretation.html](#))
- + **NetAF.Logic**
([NetAF.Logic.html](#))
- + **NetAF.Logic.Callbacks**
([NetAF.Logic.Callbacks.html](#))
- + **NetAF.Logic.Configuration**
([NetAF.Logic.Configuration.html](#))
- **NetAF.Logic.Modes**
([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Class SceneMode

Provides a display mode for a scene.

Filter by title

Inheritance

([NetAF.Conversations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Conversations.**

↳ SceneMode
Instructions

Implements

([NetAF.Conversations.Instruct.html](#))

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ **NetAF.Extensions**

Inherited Members

([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Logic**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Callbacks.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

+ **NetAF.Logic.Configuration**

Assembly: NetAF.dll

([NetAF.Logic.Configuration.html](#))

Syntax

- **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

Properties

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

Interpreter

([NetAF.Logic.Modes.GameModeType.html](#))

Get the interpreter

([NetAF.Logic.Modes.GameOverMode.html](#))

Declaration

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

public IInterpreter Interpreter { get; }

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Type	Description
RegionMapMode	
SceneMode	
TitleMode	

Type

Get the type of mode this provides.

Declaration

```
public GameModeType Type { get; }
```

([NetAF.Conversations.html](#))

Property Value

+ **NetAF.Conversations.**

Type
Instructions

GameModeType ([NetAF.Logic.Modes.GameModeType.html](#))

Description

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

Methods

NetAF.Interpretation

([NetAF.Interpretation.html](#))

Render(Game)

([NetAF.Logic.html](#))

Render the current state of a game.

+ **NetAF.Logic.Callbacks**

Declaration

([NetAF.Logic.Callbacks.html](#))

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

Parameters

- **NetAF.Logic.Modes**

Type ([NetAF.Logic.Modes.html](#))

AboutMode ([NetAF.Logic.Game.html](#))

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Class TitleMode

Provides a display mode for title.

Filter by title

Inheritance

([NetAF.Conversations.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Conversations.**

↳ TitleMode

Instructions

Implements

([NetAF.Conversations.Instruct](#)

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

+ **NetAF.Extensions**

Inherited Members

([NetAF.Extensions.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#)) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Callbacks.html](#))

Namespace: NetAF ([NetAF.html](#)).Logic ([NetAF.Logic.html](#)).Modes ([NetAF.Logic.Modes.html](#))

+ **NetAF.Logic.Configuration**

Assembly: NetAF.dll

([NetAF.Logic.Configuration.html](#))

Syntax

- **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

AboutMode

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

Properties

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

Interpreter

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

Get the interpreter

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

Declaration

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

public IInterpreter Interpreter { get; }

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

Properties

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

Type

RegionMapMode

Description

IInterpreter ([NetAF.Logic.Modes.RegionMapMode.html](#))

Interpreter

([NetAF.Logic.Modes.Interpreter.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Type

Get the type of mode this provides.

Declaration

```
public GameModeType Type { get; }
```

([NetAF.Conversations.html](#))

Property Value

+ **NetAF.Conversations.**

Type
Instructions

GameModeType ([NetAF.Logic.Modes.GameModeType.html](#))

Description

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

Methods

NetAF.Interpretation

([NetAF.Interpretation.html](#))

Render(Game)

([NetAF.Logic.html](#))

Render the current state of a game.

+ **NetAF.Logic.Callbacks**

Declaration

([NetAF.Logic.Callbacks.html](#))

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

Parameters

- **NetAF.Logic.Modes**

Type ([NetAF.Logic.Modes.html](#))

AboutMode ([NetAF.Logic.Game.html](#))

([NetAF.Logic.Modes.AboutMode.html](#))

CompletionMode

([NetAF.Logic.Modes.CompletionMode.html](#))

ConversationMode

([NetAF.Logic.Modes.ConversationMode.html](#))

IGameMode ([NetAF.Logic.Modes.IGameMode.html](#))

GameModeType

([NetAF.Logic.Modes.GameModeType.html](#))

GameOverMode

([NetAF.Logic.Modes.GameOverMode.html](#))

HelpMode

([NetAF.Logic.Modes.HelpMode.html](#))

IGameMode

([NetAF.Logic.Modes.IGameMode.html](#))

ReactionMode

([NetAF.Logic.Modes.ReactionMode.html](#))

RegionMapMode

([NetAF.Logic.Modes.RegionMapMode.html](#))

SceneMode

([NetAF.Logic.Modes.SceneMode.html](#))

TitleMode

Namespace NetAF.Persistence

Classes

Filter by title

RestorePoint (NetAF.Persistence.RestorePoint.html) (NetAF.Commands.RegionMap)

Represents a restore point for a Game.

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instruct

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.htm

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

- **NetAF.Persistence**

(NetAF.Persistence.html)

RestorePoint

(NetAF.Persistence.RestorePoint.h

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

+ **NetAF.Rendering**

(NetAF.Rendering.html)

Class RestorePoint

Represents a restore point for a Game.

Filter by title

Inheritance

+ **(NetAF.Commands.Persistence)**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.Region**

Map

Inherited Members

+ **(NetAF.Commands.RegionMap)**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Commands.Scene**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Conversations.Instruction**

Namespace: NetAF (NetAF.html).Persistence (NetAF.Persistence.html)

Assembly: NetAF

NetAF.Extensions

Syntax (<NetAF.Extensions.html>)

+ **NetAF.Interpretation**

public class RestorePoint
(<NetAF.Interpretation.html>)

+ **NetAF.Logic**

(<NetAF.Logic.html>)

Properties

+ **NetAF.Logic.Callbacks**

(<NetAF.Logic.Callbacks.html>)

+ **NetAF.Logic.Configuration**

(<NetAF.Logic.Configuration.html>)

Get or set the creation time of this save.

+ **NetAF.Logic.Modes**

Declaration

(<NetAF.Logic.Modes.html>)

- **NetAF.Persistence**

public DateTime CreationTime { get; set; }

(<NetAF.Persistence.html>)

Property Value

RestorePoint

Type (<NetAF.Persistence.RestorePoint.html>)

+ **NetAF.Persistence.Json**

DateOffset (<https://learn.microsoft.com/dotnet/api/system.datetime>)

(<NetAF.Persistence.Json.html>)

+ **NetAF.Rendering**

Game (<NetAF.Rendering.html>)

Description

Get or set the serialized game.

Declaration

```
public GameSerialization Game { get; set; }
```

Property Value

Type	Description
(NetAF.Commands.Persistence.html)	

+ [NetAF.Commands.Region](#)
Map
[\(NetAF.Commands.RegionMap.html\)](#)

Name
+ [NetAF.Commands.Scene](#)

[\(NetAF.Commands.Scene.html\)](#)

Get or set the name of this save.

- [NetAF.Conversations](#)

[\(NetAF.Conversations.html\)](#)

public string Name { get; set; }

+ [NetAF.Conversations.](#)

Instructions

Property Value

[\(NetAF.Conversations.Instruct.html\)](#)

Type
+ [NetAF.Extensions](#)

[\(NetAF.Extensions.html\)](#)

+ [NetAF.Interpretation](#)

[\(NetAF.Interpretation.html\)](#)

Methods

[\(NetAF.Logic.html\)](#)

>Create(string name)

[\(NetAF.Logic.Callbacks.html\)](#)

Create a new restore point.

+ [NetAF.Logic.Configuration](#)

Declaration

[\(NetAF.Logic.Configuration.html\)](#)

+ [NetAF.Logic.Modes](#)
RestorePoint Create(string name, Game game)

[\(NetAF.Logic.Modes.html\)](#)

Parameters

- [NetAF.Persistence](#)

Type
[\(NetAF.Persistence.html\)](#)

	Name	Description
RestorePoint (NetAF.Persistence.RestorePoint.h)	name	The name of the restore point.
Game (NetAF.Logic.Game.html)	game	The game to create the restore point for.

+ [NetAF.Persistence.Json](#)

[\(NetAF.Persistence.Json.html\)](#)

Returns

+ [NetAF.Rendering](#)

[\(NetAF.Rendering.html\)](#)

Type	Description
RestorePoint (NetAF.Persistence.RestorePoint.html)	The restore point.

▼

(NetAF.Commands.Persistence)

- + NetAF.Commands.Region
Map
(NetAF.Commands.RegionMap.html)
- + NetAF.Commands.Scene
(NetAF.Commands.Scene.html)
- + NetAF.Conversations
(NetAF.Conversations.html)
- + NetAF.Conversations.
Instructions
(NetAF.Conversations.Instruct
- + NetAF.Extensions
(NetAF.Extensions.html)
- + NetAF.Interpretation
(NetAF.Interpretation.html)
- + NetAF.Logic
(NetAF.Logic.html)
- + NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)
- + NetAF.Logic.Configuration
(NetAF.Logic.Configuration.htm
- + NetAF.Logic.Modes
(NetAF.Logic.Modes.html)
- NetAF.Persistence
(NetAF.Persistence.html)
 - RestorePoint
(NetAF.Persistence.RestorePoint.h
- + NetAF.Persistence.Json
(NetAF.Persistence.Json.html)
- + NetAF.Rendering
(NetAF.Rendering.html)

Namespace NetAF.Persistence.Json

Classes

Filter by title

JsonSave (NetAF.Persistence.Json.JsonSave.html) (NetAF.Commands.RegionMap)

Provides persistence for a save in the Json format.

+ **NetAF.Commands.Scene** (NetAF.Commands.Scene.html)

+ **NetAF.Conversations** (NetAF.Conversations.html)

+ **NetAF.Conversations.** Instructions (NetAF.Conversations.Instruct

+ **NetAF.Extensions** (NetAF.Extensions.html)

+ **NetAF.Interpretation** (NetAF.Interpretation.html)

+ **NetAF.Logic** (NetAF.Logic.html)

+ **NetAF.Logic.Callbacks** (NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration** (NetAF.Logic.Configuration.htm

+ **NetAF.Logic.Modes** (NetAF.Logic.Modes.html)

+ **NetAF.Persistence** (NetAF.Persistence.html)

- **NetAF.Persistence.Json** (NetAF.Persistence.Json.html)

 JsonSave
 (NetAF.Persistence.Json.JsonSave

+ **NetAF.Rendering** (NetAF.Rendering.html)

Class JsonSave

Provides persistence for a save in the Json format.

Filter by title

Inheritance

(NetAF.Commands.Persistence)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.Region**

Map

Inherited Members

(NetAF.Commands.RegionMap)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Commands.Scene**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Conversations.Instruction**

Namespace: NetAF ([NetAF.html](#)).Persistence ([NetAF.Persistence.html](#)).Json ([NetAF.Persistence.Json.html](#))

+ **NetAF.Extensions**

Syntax ([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

public static class JsonSave
(NetAF.Interpretation.html)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

Methods

[NetAF.Logic.Callbacks](#)

[\(NetAF.Logic.Callbacks.html\)](#)

[FromFile\(string, out RestorePoint, out string\)](#)

[NetAF.Logic.Configuration](#)

[\(NetAF.Logic.Configuration.html\)](#)

Return a restore point from a file.

+ **NetAF.Logic.Modes**

Declaration

[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

Message

[\(NetAF.Persistence.html\)](#)

- **NetAF.Persistence.Json**

Parameters

[\(NetAF.Persistence.Json.html\)](#)

Type

JsonSave

Name

path

Description

The file path.

+ **NetAF.Rendering**

net/api/system/string)

[\(NetAF.Rendering.html\)](#)

Type	Name	Description
RestorePoint (NetAF.Persistence.RestorePoint.html)	<i>restorePoint</i>	The restore point.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>message</i>	A message detailing the result of the load, if the load was unsuccessful. If the load was successful this will be empty. (NetAF.Commands.Persistence.html)

+ NetAF.Commands.Region

Returns

Map Type	Description
(NetAF.Commands.RegionMap.html)	True if the load was successful else false.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

FromJson(Region)

(NetAF.Conversations.html)

Create a restore point from Json.

+ NetAF.Conversations.

Declaration

Instructions

(NetAF.Conversations.Instruct.html)

```
public static RestorePoint FromJson(string json)
```

+ NetAF.Extensions

(NetAF.Extensions.html)

Parameters

+Type NetAF.Interpretation

(NetAF.Interpretation.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

Name

Description

json

The json.

+ NetAF.Logic

Returns

(NetAF.Logic.html)

Type

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Description

The restore point created from the Json.

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

ToFile(string, RestorePoint, out string)

+ NetAF.Logic.Modes

Permit restore point to file

(NetAF.Logic.Modes.html)

Declaration

+ NetAF.Persistence

(NetAF.Persistence.html)

```
public static bool ToFile(string path, RestorePoint restorePoint, out string message)
```

- NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Parameters

JsonSave

(NetAF.Persistence.Json.JsonSave.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>path</i>	The file path.
RestorePoint (NetAF.Persistence.RestorePoint.html)	<i>restorePoint</i>	The restore point to persist.
+ NetAF.Commands.RegionMap (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.RegionMap)	<i>message</i>	A message detailing the result of the save, if the save was unsuccessful. If the save was successful this will be empty.

Return **NetAF.Commands.Scene**

Type	Description
+ NetAF.Conversations (https://learn.microsoft.com/dotnet/api/system.boolean) (NetAF.Conversations.html)	True if the save was successful else false.

+ NetAF.Conversations. ToJson(RestorePoint) Instructions

Convert a restore point to Json.

+ NetAF.Extensions

Declaration

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Parameters

+ NetAF.Logic

Type
(NetAF.Logic.html)

RestorePoint ([NetAF.Persistence.RestorePoint.html](https://learn.microsoft.com/dotnet/api/NetAF.Persistence.RestorePoint.html))

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Returns

+ NetAF.Logic.Configuration

Type

(NetAF.Logic.Configuration.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

- NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

JsonSave

(NetAF.Persistence.Json.JsonSave)

+ NetAF.Rendering

(NetAF.Rendering.html)

Namespace NetAF.Rendering

Enums

Filter by title

(NetAF.Commands.RegionMap) KeyType (NetAF.Rendering.KeyType.html)

+ NetAF.Commands.Scene
Enumeration of key types.
(NetAF.Commands.Scene.html)

(NetAF.Conversations) RegionMapMode (NetAF.Rendering.RegionMapMode.html)

(NetAF.Conversations.html)
Enumeration of region map modes.
+ NetAF.Conversations.
Instructions
(NetAF.Conversations.Instruct

+ NetAF.Extensions
(NetAF.Extensions.html)

+ NetAF.Interpretation
(NetAF.Interpretation.html)

+ NetAF.Logic
(NetAF.Logic.html)

+ NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration
(NetAF.Logic.Configuration.htm

+ NetAF.Logic.Modes
(NetAF.Logic.Modes.html)

+ NetAF.Persistence
(NetAF.Persistence.html)

+ NetAF.Persistence.Json
(NetAF.Persistence.Json.html)

- NetAF.Rendering
(NetAF.Rendering.html)

KeyType
(NetAF.Rendering.KeyType.html)
RegionMapMode

Enum KeyType

Enumeration of key types.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html)

Assembly: NetAF.dll

+ **NetAF.Commands.Region**

Syntax

Map

(**NetAF.Commands.RegionMap**)

public enum KeyType

+ **NetAF.Commands.Scene**

(**NetAF.Commands.Scene.html**)

+ **NetAF.Conversations**

Fields (**NetAF.Conversations.html**)

+ **NetAF.Conversations**

Name Description

Instructions

Dynamic Dynamic key, only show relevant key items.

(**NetAF.Conversations.Instruct**)

Full

Full key.

+ **NetAF.Extensions**

None

No key.

(**NetAF.Extensions.html**)

+ **NetAF.Interpretation**

(**NetAF.Interpretation.html**)

+ **NetAF.Logic**

(**NetAF.Logic.html**)

+ **NetAF.Logic.Callbacks**

(**NetAF.Logic.Callbacks.html**)

+ **NetAF.Logic.Configuration**

(**NetAF.Logic.Configuration.html**)

+ **NetAF.Logic.Modes**

(**NetAF.Logic.Modes.html**)

+ **NetAF.Persistence**

(**NetAF.Persistence.html**)

+ **NetAF.Persistence.Json**

(**NetAF.Persistence.Json.html**)

- **NetAF.Rendering**

(**NetAF.Rendering.html**)

KeyType

(**NetAF.Rendering.KeyType.html**)

RegionMapMode

Enum RegionMapMode

Enumeration of region map modes.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html)

Assembly: NetAF.dll

+ **NetAF.Commands.Region**

Syntax

Map

(**NetAF.Commands.RegionMap**

 public enum RegionMapMode

+ **NetAF.Commands.Scene**

(**NetAF.Commands.Scene.html**)

+ **NetAF.Conversations**

Fields (**Conversations.html**)

+ **NetAF.Conversations.**

Name Description

Instructions

Detailed Shows rooms at a detailed level.

(**NetAF.Conversations.Instruct**

Dynamic

Dynamic region map - uses detailed if there is room, else map will be undetailed.

+ **NetAF.Extensions**

Undetailed

Shows rooms as one character, which allows larger maps to be displayed in a limited area.

(**NetAF.Extensions.html**)

+ **NetAF.Interpretation**

(**NetAF.Interpretation.html**)

+ **NetAF.Logic**

(**NetAF.Logic.html**)

+ **NetAF.Logic.Callbacks**

(**NetAF.Logic.Callbacks.html**)

+ **NetAF.Logic.Configuration**

(**NetAF.Logic.Configuration.html**)

+ **NetAF.Logic.Modes**

(**NetAF.Logic.Modes.html**)

+ **NetAF.Persistence**

(**NetAF.Persistence.html**)

+ **NetAF.Persistence.Json**

(**NetAF.Persistence.Json.html**)

- **NetAF.Rendering**

(**NetAF.Rendering.html**)

KeyType

(**NetAF.Rendering.KeyType.html**)

RegionMapMode

Namespace NetAF.Rendering.FrameBuilders

▼ Filter by title

Classes

+ [NetAF.Conversations.](#)

[Instructions](#)

[FrameBuilderCollection](#)

([NetAF.Conversations.Instruct](#))

([NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html](#))

+ [NetAF.Extensions](#)

 Provides extensions of all of the frame builders required to run a game.

 ([NetAF.Extensions.html](#))

[FrameBuilderCollections](#)

([NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html](#))

+ [NetAF.Logic](#)

 ([NetAF.Logic.html](#))

[GridStringBuilder](#) ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

 ([NetAF.Logic.Callbacks](#))

 Provides a class for building strings as part of a grid.

 ([NetAF.Logic.Callbacks.html](#))

+ [NetAF.Logic.Configuration](#)

[SceneHelper](#) ([NetAF.Rendering.FrameBuilders.SceneHelper.html](#))

 ([NetAF.Logic.Configuration.html](#))

 Provides helper functionality for scenes.

+ [NetAF.Logic.Modes](#)

 ([NetAF.Logic.Modes.html](#))

[Interfaces](#)

+ [NetAF.Persistence](#)

 ([NetAF.Persistence.html](#))

[IAboutFrameBuilder](#) ([NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html](#))

+ [NetAF.Persistence.Json](#)

 Represents any object that can build about frames.

 ([NetAF.Persistence.Json.html](#))

[CompletionFrameBuilder](#)

 ([NetAF.Rendering.FrameBuilders.CompletionFrameBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html](#))

- [NetAF.Rendering.Frame](#)

 Builders

 ([NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html](#))

[ConversationFrameBuilder](#)

([NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html](#))

 ([NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html](#))

 Represents any object that can build conversation frames.

 FrameBuilderCollections

 ([NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html](#))

[GameOverFrameBuilder](#)

([NetAF.Rendering.FrameBuilders.IGameOverFrameBuilder.html](#))

 AboutFrameBuilder

 Represents any object that can build game over frames.

 ([NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html](#))

[CompletionFrameBuilder](#)

IHelpFrameBuilder (NetAF.Rendering.FrameBuilders.IHelpFrameBuilder.html)

Represents any object that can build help frames.

IReactionFrameBuilder

(NetAF.Rendering.FrameBuilders.IReactionFrameBuilder.html)

Represents any object that can build reaction frames.

+ NetAF.Conversations.

IRRegionMapBuilder (NetAF.Rendering.FrameBuilders.IRegionMapBuilder.html)

(NetAF.Conversations.Instruction)

Represents any object that can build region maps.

+ NetAF.Extensions

IRRegionMapFrameBuilder

(NetAF.Rendering.FrameBuilders.IRegionMapFrameBuilder.html)

+ NetAF.Interpretation

Represents any object that can build region map frames.

(NetAF.Interpretation.html)

+ NetAF.Logic

IRoomMapBuilder (NetAF.Rendering.FrameBuilders.IRoomMapBuilder.html)

(NetAF.Logic.html)

Represents any object that can build room maps.

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

ISceneFrameBuilder (NetAF.Rendering.FrameBuilders.ISceneFrameBuilder.html)

+ NetAF.Logic.Configuration

Represents any object that can build scene frames.

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

ITitleFrameBuilder (NetAF.Rendering.FrameBuilders.ITitleFrameBuilder.html)

(NetAF.Logic.Modes.html)

Represents any object that can build title frames.

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

- NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilders)

FrameBuilderCollection

(NetAF.Rendering.FrameBuilders.FrameBuilderCollection)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder)

ICompletionFrameBuilder

Class FrameBuilderCollection

Provides a collection of all of the frame builders required to run a game.

Filter by title

Inheritance

[\(NetAF.Conversations.Instruct\)](#)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ [NetAF.Extensions](#)

[\(NetAF.Extensions.html\)](#)

Inherited Members

+ [NetAF.Interpretation](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

[\(NetAF.Interpretation.html\)](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ [NetAF.Logic](#)

[\(NetAF.Logic.html\)](#)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ [NetAF.Logic.Callbacks](#)

[\(NetAF.Logic.Callbacks.html\)](#)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

[\(NetAF.Logic.Callbacks.html\)](#)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ [NetAF.Logic.Configuration](#)

[\(NetAF.Logic.Configuration.html\)](#)

Name: NetAF (NetAF.dll) Declared in: [\(NetAF.Rendering.html\)](#).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#))

Assembly: NetAF.dll

+ [NetAF.Logic.Modes](#)

Syntax

[\(NetAF.Logic.Modes.html\)](#)

+ [NetAF.Persistence](#)

FrameBuilderCollection<FrameBuilder> FrameBuilderCollection

[\(NetAF.Persistence.html\)](#)

+ [NetAF.Persistence.Json](#)

Constructors

[\(NetAF.Persistence.Json.html\)](#)

+ [NetAF.Rendering](#)

FrameBuilderCollection<FrameBuilder> FrameBuilderCollection

([\(NetAF.Rendering.FrameBuilders.html\)](#))

IRegionMapFrameBuilder, IHelpFrameBuilder, ICompletionFrameBuilder,

IGameOverFrameBuilder, IAAboutFrameBuilder, IReactionFrameBuilder,

IConversationFrameBuilder)

[\(NetAF.Rendering.FrameBuilderCollection.html\)](#)

Provides a collection of all of the frame builders required to run a game.

FrameBuilderCollection<FrameBuilder>

Declaration

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html\)](#)

FrameBuilderCollections

public FrameBuilderCollection<FrameBuilder> FrameBuilderCollection(ITitleFrameBuilder titleFrameBuilder, ISceneFrameBuilder sceneFrameBuilder, IGridFrameBuilder gridFrameBuilder, IRegionMapFrameBuilder regionMapFrameBuilder, IHelpFrameBuilder helpFrameBuilder, ICompletionFrameBuilder completionFrameBuilder, IGameOverFrameBuilder gameOverFrameBuilder, IAAboutFrameBuilder aboutFrameBuilder, IReactionFrameBuilder reactionFrameBuilder, IConversationFrameBuilder conversationFrameBuilder)

ICompletionFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

Type	Name	Description
ITitleFrameBuilder (NetAF.Rendering.FrameBuilders.ITitleFrameBuilder.html)	<i>titleFrameBuilder</i>	The builder to use for building title frames.
ISceneFrameBuilder (NetAF.Rendering.FrameBuilders.ISceneFrameBuilder.html) (NetAF.Conversations.Instruct	<i>sceneFrameBuilder</i>	The builder to use for building scene frames.
+ NetAF.Extensions IRegionMapFrameBuilder (NetAF.Extensions.html) (NetAF.Extensions.html)	<i>regionMapFrameBuilder</i>	The builder to use for building region map frames.
+ NetAF.Interpretation IHelpFrameBuilder (NetAF.Interpretation.html) (NetAF.Interpretation.html)	<i>helpFrameBuilder</i>	The builder to use for building help frames.
+ NetAF.Logic (NetAF.Logic.html) ICompletionFrameBuilder (NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html) (NetAF.Logic.Callbacks (NetAF.Logic.Callbacks.html)	<i>completionFrameBuilder</i>	The builder to use for building completion frames.
+ NetAF.Logic.Configuration IGameOverFrameBuilder (NetAF.Rendering.FrameBuilders.IGameOverFrameBuilder.html) (NetAF.Logic.Configuration.html)	<i>gameOverFrameBuilder</i>	The builder to use for building game over frames.
+ NetAF.Logic.Modes (NetAF.LogicModes.html) (NetAF.LogicModes.html)	<i>aboutFrameBuilder</i>	The builder to use for building about frames.
+ NetAF.Persistence IReactionFrameBuilder (NetAF.Persistence.html) (NetAF.Persistence.html)	<i>reactionFrameBuilder</i>	The builder to use for building reaction frames.
+ NetAF.Persistence.Json (NetAF.Persistence.Json.html) IConversationFrameBuilder (NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html) (NetAF.Rendering.html)	<i>conversationFrameBuilder</i>	The builder to use for building conversation frames.

- NetAF.Rendering.Frame Builders

Properties

FrameBuilderCollection

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections

AboutFrameBuilder
Get the builder to use for about frames.
GridStringBuilder

Declaration
(NetAF.Rendering.FrameBuilders.C

IAboutFrameBuilder

public **IAboutFrameBuilder** AboutFrameBuilder { get; }

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.I

Property Value
IConversationFrameBuilder
(NetAF.Rendering.FrameBuilders.I

Type	Description
IAboutFrameBuilder (NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)	

CompletionFrameBuilder

Get the builder to use for completion frames.

(NetAF.Conversations.Instruct)

Declaration

+ NetAF.Extensions

(NetAF.Extensions.html)

```
public ICompletionFrameBuilder CompletionFrameBuilder { get; }
```

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Property Value

+ NetAF.Logic

(NetAF.Logic.html)

ICompletionFrameBuilder (NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

ConversationFrameBuilder

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Get the builder to use for conversation frames.

Declaration

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

```
public IConversationFrameBuilder ConversationFrameBuilder { get; }
```

+ NetAF.Persistence

(NetAF.Persistence.html)

Property Value

+ NetAF.Persistence.Json

Type

(NetAF.Persistence.Json.html)

IConversationFrameBuilder (NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

GameOverFrameBuilder

Builders

Get the builder to use for game over frames.

(NetAF.Rendering.FrameBuilders.IGameOverFrameBuilder)

Declaration

FrameBuilderCollection

(NetAF.Rendering.FrameBuilders.FrameBuilderCollection)

FrameBuilderCollection

GameOverFrameBuilder GameOverFrameBuilder { get; }

(NetAF.Rendering.FrameBuilders.GameOverFrameBuilder)

GridStringBuilder

Property Value

(NetAF.Rendering.FrameBuilders.GridStringBuilder)

Type

AboutFrameBuilder

Description

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder)

IGameOverFrameBuilder (NetAF.Rendering.FrameBuilders.IGameOverFrameBuilder.html)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder)

HelpFrameBuilder

Get the builder to use for help frames.

Declaration

```
public IHelpFrameBuilder HelpFrameBuilder { get; }
```

(NetAF.Conversations.Instruct

Property Value

+ NetAF.Extensions

(NetAF.Extensions.html)

IHelpFrameBuilder (NetAF.Rendering.FrameBuilders.IHelpFrameBuilder.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

ReactionModeFrameBuilder

NetAF.Logic

(NetAF.Logic.html)

Get the builder to use for reaction frames.

+ NetAF.Logic.Callbacks

Declaration

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Property Value

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

IReactionFrameBuilder (NetAF.Rendering.FrameBuilders.IReactionFrameBuilder.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Get the builder to use for region map frames.

+ NetAF.Rendering

Declaration

(NetAF.Rendering.html)

- NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder

Property Value

FrameBuilderCollection

Type (NetAF.Rendering.FrameBuilders.FrameBuilderCollection)

Description

IRegionMapFrameBuilder (NetAF.Rendering.FrameBuilders.IRegionMapFrameBuilder.html)

(NetAF.Rendering.FrameBuilders.IRegionMapFrameBuilder)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder)

SceneFrameBuilder

IAutoFrameBuilder

(NetAF.Rendering.FrameBuilders.IAutoFrameBuilder)

Get the builder to use for scene frames.

ICompletionFrameBuilder

Declaration

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder)

```
public ISceneFrameBuilder SceneFrameBuilder { get; }
```

Property Value

Type	Description
ISceneFrameBuilder (NetAF.Rendering.FrameBuilders.ISceneFrameBuilder.html) (NetAF.Conversations.Instruct	

+ **NetAF.Extensions**

TitleFrameBuilder
(NetAF.Extensions.html)

Get the builder to use for title frames.

(NetAF.Interpretation

(NetAF.Interpretation.html)

+ **NetAF.Logic**

public ITitleFrameBuilder TitleFrameBuilder { get; }

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

Property Value

(NetAF.Logic.Callbacks.html)

Type

+ **NetAF.Logic.Configuration**

ITitleFrameBuilder (NetAF.Rendering.FrameBuilders.ITitleFrameBuilder.html)

(NetAF.Logic.Configuration.html)

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

+ **NetAF.Rendering**

(NetAF.Rendering.html)

- **NetAF.Rendering.Frame**

Builders

(NetAF.Rendering.FrameBuilders.html)

FrameBuilderCollection

(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder.html)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

Class FrameBuilderCollections

Provides a container from frame builder collections.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**

↳ FrameBuilderCollections

([NetAF.Extensions.html](#))

Inherited Members

+ **NetAF.Interpretation**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Logic**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ **NetAF.Logic.Configuration**

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Configuration.html](#))

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#))

* **NetAF.LogicModes**

([NetAF.Logic.Modes.html](#))

+ **NetAF.Persistence**

public static class FrameBuilderCollections
([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

Properties

[NetAF.Rendering](#)

([NetAF.Rendering.html](#))

Default [NetAF.Rendering.Frame](#)

Builders

Get the default frame builder collection.

([NetAF.Rendering.FrameBuilders.html](#))

Declaration

FrameBuilderCollection

([NetAF.Rendering.FrameBuilders.F](#)

public static FrameBuilderCollection Default { get; }

FrameBuilderCollections

([NetAF.Rendering.FrameBuilders.F](#)

GridStringBuilder

([NetAF.Rendering.FrameBuilders.C](#)

Type AboutFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

ICompletionFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

IConversationFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

Description

Type AboutFrameBuilder	(NetAF.Rendering.FrameBuilders.I)
FrameBuilderCollection (NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)	
ICompletionFrameBuilder	(NetAF.Rendering.FrameBuilders.I)
IConversationFrameBuilder	(NetAF.Rendering.FrameBuilders.I)

▼

(NetAF.Conversations.Instruction)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

[\(NetAF.Persistence.html\)](#)

+ **NetAF.Persistence.Json**

[\(NetAF.Persistence.Json.html\)](#)

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

- **NetAF.Rendering.Frame**

Builders

[\(NetAF.Rendering.FrameBuilders\)](#)

FrameBuilderCollection

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html\)](#)

FrameBuilderCollections

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html\)](#)

GridStringBuilder

[\(NetAF.Rendering.FrameBuilders.GridStringBuilder.html\)](#)

IAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html\)](#)

ICompletionFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

Class GridStringBuilder

Provides a class for building strings as part of a grid.

Filter by title

Inheritance

(NetAF.Conversations.Instruction.html)

↳ object (https://learn.microsoft.com/dotnet/api/system.object)

+ NetAF.Extensions

↳ GridStringBuilder

(NetAF.Extensions.html)

Inherited Members

+ NetAF.Interpretation

object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

+ NetAF.Logic

object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object))

object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.MemberwiseClone() (https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone)

object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

+ NetAF.Logic.Configuration

object.ToString() (https://learn.microsoft.com/dotnet/api/system.object.tostring)

(NetAF.Logic.Configuration.html)

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

* NetAF.LogicModes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

public class GridStringBuilder
(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Constructors

+ NetAF.Rendering

(NetAF.Rendering.html)

GridStringBuilder(char, char, char)

- NetAF.Rendering.Frame

Provides a class for building strings as part of a grid.

Builders

Declaration

(NetAF.Rendering.FrameBuilders.html)

```
FrameBuilderCollection
public GridStringBuilder(char leftBoundaryCharacter = '|', char rightBoundaryCharacter = '|', char horizontalDividerCharacter = '-')
    : base(leftBoundaryCharacter, rightBoundaryCharacter, horizontalDividerCharacter)
    , frameBuilderCollections()
{}
```

(NetAF.Rendering.FrameBuilders.F

Parameters

Type	Name	Description
IAboutFrameBuilder	leftBoundaryCharacter	The character to use for left boundaries.

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.I


```
public char LeftBoundaryCharacter { get; set; }
```

Property Value

Type	Description
char (https://learn.microsoft.com/dotnet/api/system.char) (NetAF.Conversations.Instruction)	

+ NetAF.Extensions

([NetAF.Extensions.html](#))

+ NetAF.Interpretation

Get or set the line terminator.
([NetAF.Interpretation.html](#))

Declaration

+ NetAF.Logic

([NetAF.Logic.html](#))
public string LineTerminator { get; set; }

+ NetAF.Logic.Callbacks

Property Value
([NetAF.Logic.Callbacks.html](#))

+ NetAF.Logic.Configuration

([NetAF.Logic.Configuration.html](#))
string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Logic.Modes

([NetAF.Logic.Modes.html](#))

RightBoundaryCharacter

+ NetAF.Persistence

Get or set the character used for right boundary.
([NetAF.Persistence.html](#))

Declaration

+ NetAF.Persistence.Json

([NetAF.Persistence.Json.html](#))

```
public char RightBoundaryCharacter { get; set; }
```

+ NetAF.Rendering

([NetAF.Rendering.html](#))

Property Value

- NetAF.Rendering.Frame

Type

Builders

char (<https://learn.microsoft.com/dotnet/api/system.char>)

(NetAF.Rendering.FrameBuilder)

FrameBuilderCollection

([NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html](#))

FrameBuilderCollections

([NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html](#))

GridStringBuilder

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

Methods

DrawBoundary(AnsiColor)

IAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html](#))

ICompletionFrameBuilder

Declaration
([NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html](#))

IConversationFrameBuilder

([NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html](#))

```
public void DrawBoundary(AnsiColor color)
```

Parameters

Type	Name	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html) (NetAF.Conversations.Instruction)	color	The color to draw the boundary.

+ NetAF.Extensions

(NetAF.Extensions.html)

DrawCentralisedWrapped(string, int, int, AnsiColor, out int, out int)

Draw a wrapped string.

(NetAF.Interpretation.html)

Declaration

+ NetAF.Logic

(NetAF.Logic.html)

CentralisedWrapped(string value, int startY, int maxWidth, AnsiColor color, out int endX, out int endY)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Parameters

+ NetAF.Logic.Configuration

Type

(NetAF.Logic.Configuration.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

+ NetAF.Persistence

(NetAF.Persistence.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

color The color to draw the text.

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	value	The string.

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	startY	The start y position.

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	maxWidth	The max width of the string.

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	endX	The end x position.

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	endY	The end y position.

Type	Name	Description
+ NetAF.Rendering		

(NetAF.Rendering.html)

DrawHorizontalDivider(int, AnsiColor)

- NetAF.Rendering.Frame

Draws a horizontal divider.

(NetAF.Rendering.FrameBuilder)

Declaration

FrameBuilderCollection

public void DrawHorizontalDivider(int y, AnsiColor color)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.F

Parameters

IStringBuilder

Type	Name	Description
IAutoFrameBuilder	y	The y position of the divider.
int (https://learn.microsoft.com/dotnet/api/system.int32)	color	The color to draw the boundary.

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.I

DrawUnderline(int, int, int, ConsoleColor)

Draw an underline.

Declaration

```
public void DrawUnderline(int x, int y, int length, ConsoleColor color)
```

(NetAF.Conversations.Instruction.html)

Parameters

+ NetAF.Extensions

Type
(NetAF.Extensions.html)

int (https://learn.microsoft.com/dotnet/api/system.int32)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

int (https://learn.microsoft.com/dotnet/api/system.int32)

+ NetAF.Logic

int (https://learn.microsoft.com/dotnet/api/system.int32)

(NetAF.Logic.html)

AnsiColor

+ NetAF.Logic.Callbacks

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

(NetAF.Logic.Callbacks.html)

Name

Description

x	The position of the underline, in x.
y	The position of the underline, in y.
length	The length of the underline.
color	The color of the underline.

+ NetAF.Logic.Configuration

DrawWrappedConfiguration(int, int, ConsoleColor, out int, out int)

+ NetAF.Logic.Modes

Draw a wrapped string.

(NetAF.Logic.Modes.html)

Declaration

+ NetAF.Persistence

(NetAF.Persistence.html)(string value, int startX, int startY, int maxWidth, ConsoleColor color, out int endX, out int endY)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Parameters

+ NetAF.Rendering

Type
(NetAF.Rendering.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

- NetAF.Rendering.Frame

int (https://learn.microsoft.com/dotnet/api/system.int32)

Name

Description

value	The string.
startX	The start x position.
startY	The start y position.
maxWidth	The max width of the string.
color	The color to draw the text.
endX	The end x position.
endY	The end y position.

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder)

Flush()

(NetAF.Rendering.FrameBuilders.IFlush)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder)

Flush the buffer.

(NetAF.Rendering.FrameBuilders.IFlush)

Declaration

```
public void Flush()
```

GetCellColor(int, int)

[\(NetAF.Conversations.Instruction.html\)](#)
Get a color for a cell.

+ NetAF.Extensions

Declaration

[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Parameters

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

Name

Description

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

x

The x position of the cell.

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

y

The y position of the cell.

+ NetAF.Logic.Configuration

Returns

[\(NetAF.Logic.Configuration.html\)](#)

Type
+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

Description

The cell color.

+ NetAF.Persistence

[\(NetAF.Persistence.html\)](#)

GetCharacter(int, int)

+ NetAF.Persistence.Json

Get a character from the buffer.

[\(NetAF.Persistence.Json.html\)](#)

Declaration

+ NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

```
public char GetCharacter(int x, int y)
```

- NetAF.Rendering.Frame

Builders

Parameters

[\(NetAF.Rendering.FrameBuilder.html\)](#)

Type
FrameBuilder

FrameBuilderCollection

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Name

Description

x

The x position of the character.

FrameBuilderCollections

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

y

The y position of the character.

GridStringBuilder

Returns
[\(NetAF.Rendering.FrameBuilders.GridStringBuilder.html\)](#)

Type
AboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html\)](#)

char (<https://learn.microsoft.com/dotnet/api/system.char>)

ICompletionFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

GetNumberOffline(string, int, int)

Get the number of lines a string will take up.

Declaration

```
public static int GetNumberOfLines(string value, int startY, int maxWidth)
```



Parameters

Type	Name	Description
+ NetAF.Extensions string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Extensions.html)	<i>value</i>	The string.
+ NetAF.Interpretation int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Interpretation.html)	<i>startY</i>	The start y position.
+ NetAF.Logic int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Logic.html)	<i>maxWidth</i>	The max width of the string.

+ **NetAF.Logic**

Returns

Type	Description
+ NetAF.Logic.Callbacks int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Logic.Callbacks.html)	The number of lines the string will take up.

+ **NetAF.Logic.Configuration**

[\(NetAF.Size\).Configuration.html](#)

+ **NetAF.Logic.Modes**

Resize this builder.

[\(NetAF.Logic.Modes.html\)](#)

Declaration

+ **NetAF.Persistence**

[\(NetAF.Persistence.html\)](#) *displaySize*)

+ **NetAF.Persistence.Json**

Parameters

[\(NetAF.Persistence.Json.html\)](#)

Type	Name	Description
+ NetAF.Rendering (NetAF.Rendering.html)	<i>displaySize</i>	The new size.

- **NetAF.Rendering.Frame**

Builders

[SetCell\(int, int, char, AnsiColor\)](#)
[\(NetAF.Rendering.FrameBuilders.html\)](#)

Set a cell in the FrameBuilderCollection

Declaration

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.F

```
public void SetCell(int x, int y, char character, AnsiColor color)
```

(NetAF.Rendering.FrameBuilders.C

About FrameBuilder

Parameters

[\(NetAF.Rendering.FrameBuilders.I](#)

Type CompletionFrameBuilder

Type	Name	Description
CompletionFrameBuilder	<i>x</i>	The x position of the cell.

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

IConversationFrameBuilder

int (https://learn.microsoft.com/dotnet/api/system.int32)	<i>y</i>	The y position of the cell.
---	----------	-----------------------------

[\(NetAF.Rendering.FrameBuilders.I](#)

Type	Name	Description
char (https://learn.microsoft.com/dotnet/api/system.char)	<i>character</i>	The character.
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	<i>color</i>	The color of the character.

▼

[NetAF.Conversations.Instruction](#)

- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- + **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
- + **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)
- + **NetAF.Logic.Configuration**
[\(NetAF.Logic.Configuration.html\)](#)
- + **NetAF.Logic.Modes**
[\(NetAF.Logic.Modes.html\)](#)
- + **NetAF.Persistence**
[\(NetAF.Persistence.html\)](#)
- + **NetAF.Persistence.Json**
[\(NetAF.Persistence.Json.html\)](#)
- + **NetAF.Rendering**
[\(NetAF.Rendering.html\)](#)
- **NetAF.Rendering.Frame Builders**
[\(NetAF.Rendering.FrameBuilders.html\)](#)

FrameBuilderCollection
[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html\)](#)

FrameBuilderCollections
[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html\)](#)

GridStringBuilder
[\(NetAF.Rendering.FrameBuilders.GridStringBuilder.html\)](#)

IAboutFrameBuilder
[\(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html\)](#)

ICompletionFrameBuilder
[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder
[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

Interface IAboutFrameBuilder

Represents any object that can build about frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, Game, Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string title, Game game, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Name	Description
title	The title.
game	The game.
size	The size of the frame.

+ **NetAF.Rendering**

Game (NetAF.Logic.Game.html)

(NetAF.Rendering.html)

Size (NetAF.Assets.Size.html)

- **NetAF.Rendering.Frame**

Builders

Returns

(NetAF.Rendering.FrameBuilders.IFrameBuilder)

Type

FrameBuilderCollection

IFrameBuilder (NetAF.Rendering.FrameBuilders.IFrameBuilder.html)

Description

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder.html)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

Interface ICompletionFrameBuilder

Represents any object that can build completion frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, string, Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string message, string reason, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

Name

Description

message

The message to display to the user.

+ **NetAF.Rendering**

string (https://learn.microsoft.com/dotnet/api/system.string)

(NetAF.Rendering.html)

reason

The reason the game ended.

Size (NetAF.Assets.Size.html)

size

The size of the frame.

- **NetAF.Rendering.Frame**

Builders

Returns

(NetAF.Rendering.FrameBuilders.html)

Type

FrameBuilderCollection

Description

IFrame (NetAF.Rendering.FrameBuilders.IFrame.html)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder.html)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

Interface IConversationFrameBuilder

Represents any object that can build conversation frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, IConverser, CommandHelp[], Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string title, IConverser converser, CommandHelp[] contextualCommands, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

Type	Name	Description
+ NetAF.Persistence.Json.html		
+ NetAF.Rendering	<i>title</i>	The title to display to the user.
(NetAF.Rendering.html)		
- NetAF.Rendering.Frame	<i>converser</i>	The converser.
IConverser		
Builders		
(NetAF.Assets.Characters.IConverser.html)		
(NetAF.Rendering.FrameBuilders.html)		
CommandHelp	<i>contextualCommands</i>	The contextual commands to display.
FrameBuilderCollection		
(NetAF.Commands.CommandHelp.html)		
(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)		
FrameBuilderCollections		
Size	<i>size</i>	The size of the frame.
(NetAF.Assets.Size.html)		
GridStringBuilder		

Returns

IAboutFrameBuilder

Type

Description

ICompletionFrameBuilder

IFrame

(NetAF.Rendering.Frames.IFrame.html)

(NetAF.Rendering.FrameBuilders.IFrameBuilder.html)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

▼

[\(NetAF.Conversations.Instruction.html\)](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

[\(NetAF.Persistence.html\)](#)

+ **NetAF.Persistence.Json**

[\(NetAF.Persistence.Json.html\)](#)

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

- **NetAF.Rendering.FrameBuilders**

[\(NetAF.Rendering.FrameBuilders.html\)](#)

FrameBuilderCollection

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html\)](#)

FrameBuilderCollections

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html\)](#)

GridStringBuilder

[\(NetAF.Rendering.FrameBuilders.GridStringBuilder.html\)](#)

IAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html\)](#)

ICompletionFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

Interface IGameOverFrameBuilder

Represents any object that can build game over frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, string, Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string message, string reason, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

Name

Description

message

The message to display to the user.

+ **NetAF.Rendering**

string (https://learn.microsoft.com/dotnet/api/system.string)

(NetAF.Rendering.html)

reason

The reason the game ended.

Size (NetAF.Assets.Size.html)

size

The size of the frame.

- **NetAF.Rendering.Frame**

Builders

Returns

(NetAF.Rendering.FrameBuilder)

Type

FrameBuilderCollection

Description

IFrame (NetAF.Rendering.FrameBuilders.IFrame.html)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder.html)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

Interface IHelpFrameBuilder

Represents any object that can build help frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, string, CommandHelp[], Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string title, string description, CommandHelp[] commandHelp, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

Name

Description

title

The title.

+ **NetAF.Rendering**

string (https://learn.microsoft.com/dotnet/api/system.string)

(NetAF.Rendering.html)

description

The description.

- **NetAF.Rendering.Frame**

CommandHelp (NetAF.Commands.CommandHelp.html)[]

commandHelp

The command help.

- **NetAF.Rendering.FrameBuilders**

Size (NetAF.Assets.Size.html)

size

The size of the frame.

(NetAF.Rendering.FrameBuilders.html)

Returns

FrameBuilderCollection

Type: NetAF.Rendering.FrameBuilders.FrameBuilderCollection

Description

FrameBuilderCollections

IFrame (NetAF.Rendering.Frames.IFrame.html)

(NetAF.Rendering.FrameBuilders.FrameBuilderCollection)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder)

Interface IReactionFrameBuilder

Represents any object that can build reaction frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, string, Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string title, string message, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

Name

Description

title

The title to display to the user.

+ **NetAF.Rendering**

string (https://learn.microsoft.com/dotnet/api/system.string)

(NetAF.Rendering.html)

message

The message to display to the user.

Size (NetAF.Assets.Size.html)

size

The size of the frame.

- **NetAF.Rendering.Frame**

Builders

Returns

(NetAF.Rendering.FrameBuilder)

Type

FrameBuilderCollection

Description

IFrame (NetAF.Rendering.Frames.Frame.html)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.F

GridStringBuilder

(NetAF.Rendering.FrameBuilders.C

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.I

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.I

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.I

Interface IRegionMapBuilder

Represents any object that can build region maps.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

BuildRegionMap(Region, Point2D, Point3D, Size)

+ **NetAF.Logic.Configuration**

Build a map of a region.

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

void BuildRegionMap(Region region, Point2D startPosition, Point3D focusPosition, Size maxSize);

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

Type	Name	Description
+ NetAF.Persistence.Json		
+ NetAF.Rendering	<i>region</i>	The region.
(NetAF.Assets.Region.html)		
- NetAF.Rendering.FrameBuilders	<i>startPosition</i>	The position to start building at.
(NetAF.Assets.Point2D.html)		
- NetAF.Rendering.FrameBuilders	<i>focusPosition</i>	The position to focus on.
(NetAF.Assets.Point3D.html)		
- NetAF.Rendering.FrameBuilders	<i>maxSize</i>	The maximum size available in which to build the map.
Size (NetAF.Assets.Size.html)		
FrameBuilderCollection		
(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)		

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder.html)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)

Interface IRegionMapFrameBuilder

Represents any object that can build region map frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(Region, Point3D, CommandHelp[], Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(Region region, Point3D focusPosition, CommandHelp[] contextualCommands,

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

Type (NetAF.Persistence.Json.html)

Name

Description

+ **NetAF.Rendering**

(NetAF.Rendering.html)

Point3D (NetAF.Assets.Point3D.html)

region

The region.

focusPosition

The position to focus on.

- **NetAF.Rendering.Frame**

Builders

(NetAF.Commands.CommandHelp.html)

IFrameBuilder

contextualCommands

The contextual commands to display.

Size (NetAF.Assets.Size.html)

size

The size of the frame.

Returns FrameBuilderCollection

(NetAF.Rendering.FrameBuilders.F

Type GridStringBuilder

Description

IFrame (NetAF.Rendering.Frames.IFrame.html)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.I

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.I

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.I

▼

(NetAF.Conversations.Instruction)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

[\(NetAF.Persistence.html\)](#)

+ **NetAF.Persistence.Json**

[\(NetAF.Persistence.Json.html\)](#)

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

- **NetAF.Rendering.Frame**

Builders

[\(NetAF.Rendering.FrameBuilders\)](#)

FrameBuilderCollection

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html\)](#)

FrameBuilderCollections

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html\)](#)

GridStringBuilder

[\(NetAF.Rendering.FrameBuilders.GridStringBuilder.html\)](#)

IAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html\)](#)

ICompletionFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

Interface IRoomMapBuilder

Represents any object that can build room maps.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

BuildRoomMap(Room, ViewPoint, KeyType, Point2D, out int, out int)

+ **NetAF.Logic.Configuration**

Build a map for a room.

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

void BuildRoomMap(Room room, ViewPoint viewPoint, KeyType key, Point2D startPosition, out int endX, out int endY)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

T(NetAF.Persistence.Json.html)

Name

Description

+ R(NetAF.Persistence.Json.Room.html)

room

The room.

(NetAF.Rendering.html)

ViewPoint (NetAF.Assets.Locations.ViewPoint.html)

viewPoint

The viewpoint from the room.

- **NetAF.Rendering.FrameBuilders**

KeyType (NetAF.Rendering.KeyType.html)

key

The key type.

Point2D (NetAF.Assets.Point2D.html)

startPosition

The position to start building at.

(NetAF.Rendering.FrameBuilders.F

int (https://learn.microsoft.com/dotnet/api/system.int32)

endX

The end position, x.

int (https://learn.microsoft.com/dotnet/api/system.int32)

endY

The end position, x.

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.F

GridStringBuilder

(NetAF.Rendering.FrameBuilders.C

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.I

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.I

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.I

Interface ISceneFrameBuilder

Represents any object that can build scene frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(Room, ViewPoint, PlayableCharacter, CommandHelp[], KeyType, Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(Room room, ViewPoint viewPoint, PlayableCharacter player, CommandHelp[])

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

Type	Name	Description
IFrame (NetAF.Persistence.Json.html)	room	Specify the Room.
+ NetAF.Rendering	viewPoint	Specify the viewpoint from the room.
- NetAF.Rendering.Frame	player	Specify the player.
Builders	contextualCommands	The contextual commands to display.
PlayableCharacter (NetAF.Rendering.FrameBuilders.IPlayableCharacter.html)	keyType	The type of key to use.
FrameBuilderCollection (NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html)	size	The size of the frame.
CommandHelp (NetAF.Rendering.FrameBuilders.CommandHelp.html)		
FrameBuilderCollections (NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html)		
KeyStringBuilder (NetAF.Rendering.KeyType.html)		
Size (NetAF.Assets.Size.html)		
IAboutFrameBuilder (NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html)		
Returns ICompletionFrameBuilder (NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html)		
Type	Description	
IConversationFrameBuilder (NetAF.Rendering.Frames.IFrame.html)		
IFrame (NetAF.Rendering.Frames.IFrame.html)		
(NetAF.Rendering.FrameBuilders.IFrameBuilder.html)		

▼

[\(NetAF.Conversations.Instruction.html\)](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**

[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

[\(NetAF.Persistence.html\)](#)

+ **NetAF.Persistence.Json**

[\(NetAF.Persistence.Json.html\)](#)

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

- **NetAF.Rendering.Frame**

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

FrameBuilderCollection

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html\)](#)

FrameBuilderCollections

[\(NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html\)](#)

GridStringBuilder

[\(NetAF.Rendering.FrameBuilders.GridStringBuilder.html\)](#)

IAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html\)](#)

ICompletionFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html\)](#)

IConversationFrameBuilder

[\(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html\)](#)

Interface ITitleFrameBuilder

Represents any object that can build title frames.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html)

Assembly: NetAF.dll

+ **NetAF.Extensions**

Syntax

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Build(string, string, Size)

+ **NetAF.Logic.Configuration**

Build a frame

(NetAF.Logic.Configuration.html)

Declaration

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

IFrame Build(string title, string description, Size size)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

Parameters

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

string (https://learn.microsoft.com/dotnet/api/system.string)

Name

Description

title

The title.

+ **NetAF.Rendering**

string (https://learn.microsoft.com/dotnet/api/system.string)

(NetAF.Rendering.html)

description

The description.

Size (NetAF.Assets.Size.html)

size

The size of the frame.

- **NetAF.Rendering.Frame**

Builders

Returns

(NetAF.Rendering.FrameBuilders.IFrameBuilderCollection)

Type

FrameBuilderCollection

Description

IFrame (NetAF.Rendering.FrameBuilders.IFrame.html)

FrameBuilderCollections

(NetAF.Rendering.FrameBuilders.FrameBuilderCollections)

GridStringBuilder

(NetAF.Rendering.FrameBuilders.GridStringBuilder)

IAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.IAboutFrameBuilder)

ICompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder)

IConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.IConversationFrameBuilder)

Class SceneHelper

Provides helper functionality for scenes.

Filter by title

Inheritance

([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**

↳ SceneHelper

([NetAF.Extensions.html](#))

Inherited Members

+ **NetAF.Interpretation**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Logic**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ **NetAF.Logic.Configuration**

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Logic.Configuration.html](#))

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#))

* **NetAF.LogicModes**

([NetAF.Logic.Modes.html](#))

+ **NetAF.Persistence**

public static class SceneHelper
([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

Methods

[NetAF.Rendering](#)

([NetAF.Rendering.html](#))

[CreateNPCString\(Room\)](#)

Builders

Create a description of the NPC's as a string.

([NetAF.Rendering.FrameBuilder](#))

Declaration

FrameBuilderCollection

([NetAF.Rendering.FrameBuilders.F](#)

public static string CreateNPCString(Room room)

FrameBuilderCollections

([NetAF.Rendering.FrameBuilders.F](#)

GridStringBuilder

([NetAF.Rendering.FrameBuilders.C](#)

Type AboutFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

ICompletionFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

Returns IConversationFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

IConversationFrameBuilder

([NetAF.Rendering.FrameBuilders.I](#)

Type	Name	Description
AboutFrameBuilder	room	The room.

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	The characters, as a string.

CreateViewpointAsString(Room, ViewPoint)

Create a viewpoint as a string.

NetAF.Extensions

([NetAF.Extensions.html](#))

```
public static string CreateViewpointAsString(Room room, ViewPoint viewPoint)
```

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

Parameters

+ NetAF.Logic

Type

([NetAF.Logic.html](#))

Room ([NetAF.Assets.Locations.Room.html](#))

+ NetAF.Logic.Callbacks

ViewPoint ([NetAF.Assets.Locations.ViewPoint.html](#))

([NetAF.Logic.Callbacks.html](#))

Name

Description

room

The room.

viewPoint

The view point.

+ NetAF.Logic.Configuration

Returns

([NetAF.Logic.Configuration.html](#))

Type

Description

+ NetAF.Logic.Modes

string (<https://learn.microsoft.com/dotnet/api/system.string>)

([NetAF.Logic.Modes.html](#))

The view point, as a string.

+ NetAF.Persistence

([NetAF.Persistence.html](#))

+ NetAF.Persistence.Json

([NetAF.Persistence.Json.html](#))

+ NetAF.Rendering

([NetAF.Rendering.html](#))

- NetAF.Rendering.Frame

Builders

([NetAF.Rendering.FrameBuilders.html](#))

FrameBuilderCollection

([NetAF.Rendering.FrameBuilders.FrameBuilderCollection.html](#))

FrameBuilderCollections

([NetAF.Rendering.FrameBuilders.FrameBuilderCollections.html](#))

GridStringBuilder

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

IAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html](#))

ICompletionFrameBuilder

([NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html](#))

IConversationFrameBuilder

([NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html](#))

Namespace NetAF.Rendering.FrameBuilders.Console

▼ Filter by title

Classes

(NetAF.Conversations.Instruct

+ NetAF.Extensions

ConsoleAboutFrameBuilder

(NetAF.Extensions.html)

(NetAF.Rendering.FrameBuilders.Console.ConsoleAboutFrameBuilder.html)

+ NetAF.Interpretation

Provides a builder of console about frames.

(NetAF.Interpretation.html)

ConsoleCompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleCompletionFrameBuilder.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

ConsoleConversationFrameBuilder

+ NetAF.Logic.Configuration

(NetAF.Rendering.FrameBuilders.Console.ConsoleConversationFrameBuilder.html)

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

Provides a builder of conversation frames.

(NetAF.Logic.Modes.html)

ConsoleGameOverFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleGameOverFrameBuilder.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

ConsoleHelpFrameBuilder

+ NetAF.Rendering

(NetAF.Rendering.FrameBuilders.Console.ConsoleHelpFrameBuilder.html)

(NetAF.Rendering.html)

Provides a builder of help frames.

+ NetAF.Rendering.Frame

Builders

ConsoleReactionFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleReactionFrameBuilder.html)

- NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.ConsoleBuilder.html)

ConsoleRegionMapBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleRegionMapBuilder.html)

(NetAF.Rendering.FrameBuilders.Console.ConsoleRegionMapBuilder.html)

Provides a builder for region maps.

ConsoleAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleAboutFrameBuilder.html)

(NetAF.Rendering.FrameBuilders.Console.ConsoleAboutFrameBuilder.html)

Provides a builder of region map frames.

ConsoleConversationFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleConversationFrameBuilder.html)

(NetAF.Rendering.FrameBuilders.Console.ConsoleConversationFrameBuilder.html)

Provides a builder of region map frames.

ConsoleCompletionFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.ConsoleCompletionFrameBuilder.html)

(NetAF.Rendering.FrameBuilders.Console.ConsoleCompletionFrameBuilder.html)

Provides a builder of region map frames.

ConsoleRoomMapBuilder

([NetAF.Rendering.FrameBuilders.Console.ConsoleRoomMapBuilder.html](#))

Provides a room map builder.

ConsoleSceneFrameBuilder

([NetAF.Rendering.FrameBuilders.Console.ConsoleSceneFrameBuilder.html](#))

[NetAF.ConversationFrame](#)

+ [NetAF.Extensions](#)

ConsoleTitleFrameBuilder

([NetAF.Rendering.FrameBuilders.Console.ConsoleTitleFrameBuilder.html](#))

+ [NetAF.Interpretation](#)

Provides a builder of title frames.
([NetAF.Interpretation.html](#))

NetAF.Logic

([NetAF.Logic.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.Console.AnsiColor.html](#))

([NetAF.Logic.Callbacks.html](#))

Enumeration of ANSI colors.

+ [NetAF.Logic.Configuration](#)

([NetAF.Logic.Configuration.html](#))

+ [NetAF.Logic.Modes](#)

([NetAF.Logic.Modes.html](#))

+ [NetAF.Persistence](#)

([NetAF.Persistence.html](#))

+ [NetAF.Persistence.Json](#)

([NetAF.Persistence.Json.html](#))

+ [NetAF.Rendering](#)

([NetAF.Rendering.html](#))

+ [NetAF.Rendering.Frame](#)

Builders

([NetAF.Rendering.FrameBuilders.html](#))

- [NetAF.Rendering.Frame](#)

Builders.Console

([NetAF.Rendering.FrameBuilders.Console.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.Console.AnsiColor.html](#))

ConsoleAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.Console.AboutFrameBuilder.html](#))

ConsoleCompletionFrame

Builder

([NetAF.Rendering.FrameBuilders.Console.CompletionFrameBuilder.html](#))

ConsoleConversationFrame

Enum AnsiColor

Enumeration of ANSI colors.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).FrameBuilders (NetAF.Rendering.FrameBuilders.html).Console (NetAF.Rendering.FrameBuilders.Console.html)

↳ **NetAF.Extensions**

Syntax: [\(NetAF.Extensions.html\)](#)

+ **NetAF.Interpretation**

public enum AnsiColor
[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

[\(NetAF.Logic.html\)](#)

Fields

[NetAF.Logic.Callbacks](#)

Name	Description
Black	Black (30).
Blue	Blue (34).
BrightBlack	Bright black (90).
BrightBlue	Bright blue (94).
BrightCyan	Bright cyan (96).
BrightGreen	Bright green (92).
BrightMagenta	Bright magenta (95).
BrightRed	Bright red (91).
BrightWhite	Bright white (97).
BrightYellow	Bright yellow (93).
Cyan	Cyan (36).
Green	Green (32).
Magenta	Magenta (35).
Red	Red (31).
AnsiColor	
Reset	Reset (0).
White	White (37).
Yellow	Yellow (33).
Builder	
ConsoleAboutFrameBuilder	
ConsoleCompletionFrame	
ConsoleConversationFrame	
...	

▼

(NetAF.Conversations.Instruction)

- + **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)
- + **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)
- + **NetAF.Logic**
[\(NetAF.Logic.html\)](#)
- + **NetAF.Logic.Callbacks**
[\(NetAF.Logic.Callbacks.html\)](#)
- + **NetAF.Logic.Configuration**
[\(NetAF.Logic.Configuration.html\)](#)
- + **NetAF.Logic.Modes**
[\(NetAF.Logic.Modes.html\)](#)
- + **NetAF.Persistence**
[\(NetAF.Persistence.html\)](#)
- + **NetAF.Persistence.Json**
[\(NetAF.Persistence.Json.html\)](#)
- + **NetAF.Rendering**
[\(NetAF.Rendering.html\)](#)
- + **NetAF.Rendering.FrameBuilders**
[\(NetAF.Rendering.FrameBuilders.html\)](#)
- **NetAF.Rendering.FrameBuilders.Console**
[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)
 - AnsiColor
 - [\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)
 - ConsoleAboutFrameBuilder
 - [\(NetAF.Rendering.FrameBuilders.Console.AboutFrameBuilder.html\)](#)
 - ConsoleCompletionFrame
 - Builder
 - [\(NetAF.Rendering.FrameBuilders.Console.Builder.html\)](#)
 - ConsoleConversationFrame
 - ...

Class ConsoleAboutFrameBuilder

Provides a builder of console about frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleAboutFrameBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**
IAboutFrameBuilder ([NetAF.Rendering.FrameBuilders.IAboutFrameBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Logic.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**
[NetAF.Logic.Configuration.html](#)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors
([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleAboutFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))

Provides a builder of console about frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

Parameters

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleConversationFrame

- ...

Name

Description

gridStringBuilder

A builder to use for the string layout.

Properties

AuthorColor

Get or set the author color.

Declaration
↳ [NetAF.Conversations.Instruction](#)

+ [NetAF.Extensions](#)
([NetAF.Extensions.html](#))

Property Value
+ [NetAF.Interpretation](#)

Type ([NetAF.Interpretation.html](#))

+ [NetAF.Logic](#)
([NetAF.Logic.html](#))

+ [NetAF.Logic.Callbacks](#)

BackgroundColor
([NetAF.Logic.Callbacks.html](#))

Get or set the background color.

+ [NetAF.Logic.Configuration](#)

Declaration
([NetAF.Logic.Configuration.html](#))

+ [NetAF.Logic.Modes](#)

public AnsiColor BackgroundColor { get; set; }

([NetAF.Logic.Modes.html](#))

+ [NetAF.Persistence](#)

Property Value
([NetAF.Persistence.html](#))

Type

AnsiColor

([NetAF.Persistence.Json.html](#))

+ [NetAF.Rendering](#)

BorderColor
([NetAF.Rendering.html](#))

+ [NetAF.Rendering.Frame](#)

Get or set the border color.

Builders

Declaration
([NetAF.Rendering.FrameBuilders.html](#))

- [NetAF.Rendering.Frame](#)
BorderColor { get; set; }

Builders.Console

Property Value
([NetAF.Rendering.FrameBuilders.html](#))

Type

AnsiColor
([NetAF.Rendering.FrameBuilders.Console.html](#))

AnsiColor ([NetAF.Rendering.FrameBuilders.Console.AnsiColor.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleCompletionFrame

Builder

([NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html](#))

ConsoleConversationFrame

Get or set the description color.

- ...

Description

Description

Description

Declaration

```
public AnsiColor DescriptionColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

(NetAF.Extensions.html)

NameColor

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Get or set the NAME color.

+ NetAF.Logic

(NetAF.Logic.html)

```
public AnsiColor NameColor { get; set; }
```

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Property Value

+ NetAF.Logic.Configuration

Type (NetAF.Logic.Configuration.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

TitleColor

(NetAF.Persistence.html)

Get or set the title color.

+ NetAF.Persistence.Json

Declaration (NetAF.Persistence.Json.html)

+ NetAF.Rendering

TitleColor [get; set;]

(NetAF.Rendering.html)

Property Value

NetAF.Rendering.Frame

Builders

Type (NetAF.Rendering.FrameBuilders.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

- NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.html)

Methods

AnsiColor

(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

ConsoleAboutFrameBuilder (NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

ConsoleCompletionFrame

Build a frame.

Builder

Declaration (NetAF.Rendering.FrameBuilders.ConsoleBuilder.html)

ConsoleConversationFrame

- ...

```
public IFrame Build(string title, Game game, Size size)
```

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Conversations.Instruction.html)	title	The title.
Game (NetAF.Logic.Game.html) + NetAF.Extensions	game	The game.
Size (NetAF.Assets.Size.html) (NetAF.Extensions.html)	size	The size of the frame.

+ NetAF.Interpretation

Returns
[\(NetAF.Interpretation.html\)](#)

Type	Description
IFrame (NetAF.Rendering.Frames.IFrame.html) (NetAF.Logic.html)	

+ NetAF.Logic.Callbacks

Implements
[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration
[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

+ NetAF.Persistence

[\(NetAF.Persistence.html\)](#)

+ NetAF.Persistence.Json

[\(NetAF.Persistence.Json.html\)](#)

+ NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

- NetAF.Rendering.Frame

Builders.Console

[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

ConsoleCompletionFrame

Builder

[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

ConsoleConversationFrame

- ...

Class ConsoleCompletionFrameBuilder

Provides a builder of completion frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**

↳ ConsoleCompletionFrameBuilder

([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**

ICompletionFrameBuilder ([NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html](#))

([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json** ConsoleCompletionFrameBuilder : ICompletionFrameBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors

([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleCompletionFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))

Provides a builder of completion frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

Method: ConsoleCompletionFrameBuilder(GridStringBuilder gridStringBuilder)

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

Parameters

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrameBuilder	gridStringBuilder	A builder to use for the string layout.

Properties

BackgroundColor

Get or set the background color.

Declaration

`(NetAF.Conversations.Instruction)`

+ **NetAF.Extensions**
 BackgroundColor { get; set; }

[\(NetAF.Extensions.html\)](#)

Property Value

+ **NetAF.Interpretation**

Type
[\(NetAF.Interpretation.html\)](#)

Description

+ **NetAF.Logic**
 AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

BorderColor
[\(NetAF.Logic.Callbacks.html\)](#)

Get or set the border color.

+ **NetAF.Logic.Configuration**

Declaration
[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**

public AnsiColor BorderColor { get; set; }
[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

Property Value
[\(NetAF.Persistence.html\)](#)

Description

+ **NetAF.Persistence.Json**
 AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

[\(NetAF.Persistence.Json.html\)](#)

+ **NetAF.Rendering**

Declaration
[\(NetAF.Rendering.html\)](#)

+ **NetAF.Rendering.Frame**

Get or set the description color.

Builders

Declaration
[\(NetAF.Rendering.FrameBuilders.html\)](#)

- **NetAF.Rendering.Frame**
 DescriptionColor { get; set; }

Builders.Console

Property Value
[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

Description

Type `AnsiColor`
[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

`AnsiColor` (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

`ConsoleCompletionFrame`

`Builder`

[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

TitleColor
[\(NetAF.Rendering.FrameBuilders.TitleColor.html\)](#)

Get or set the title color.

`...
_`

Declaration

```
public AnsiColor TitleColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Methods

[\(NetAF.Interpretation.html\)](#)

+ NetAF.Logic

Build(string, string, Size)
[\(NetAF.Logic.html\)](#)

Build a frame.

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

`public IFrame Build(string message, string reason, Size size)`
[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Persistence.html)	<i>message</i>	The message to display to the user.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>reason</i>	The reason the game ended.
Size (NetAF.Assets.Size.html) (NetAF.Persistence.Json.html)	<i>size</i>	The size of the frame.

* NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

[IFrame](#) ([NetAF.Rendering.Frames.IFrame.html](#))

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

Implements

[NetAF.Rendering.Frame](#)

Builders Console

[ICompletionFrameBuilder](#) ([NetAF.Rendering.FrameBuilders.ICompletionFrameBuilder.html](#))

(NetAF.Rendering.FrameBuilders.html)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

ConsoleCompletionFrame

Builder

[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

ConsoleConversationFrame

- ...

Class ConsoleConversationFrameBuilder

Provides a builder of conversation frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleConversationFrameBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**
IConversationFrameBuilder ([NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Logic.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**
[NetAF.Logic.Configuration.html](#)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json** ConsoleConversationFrameBuilder : IConversationFrameBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors ([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

Builders ConsoleConversationFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))

Provides a builder of conversation frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrameBuilder	gridStringBuilder	A builder to use for the string layout.

Properties

BackgroundColor

Get or set the background color.

Declaration

`(NetAF.Conversations.Instruction)`

+ **NetAF.Extensions**
`public AnsiColor BackgroundColor { get; set; }`

[\(NetAF.Extensions.html\)](#)

Property Value

+ **NetAF.Interpretation**

Type
`(NetAF.Interpretation.html)`

Description

+ **NetAF.Logic**
`AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)`

[\(NetAF.Logic.html\)](#)

+ **NetAF.Logic.Callbacks**

BorderColor
`(NetAF.Logic.Callbacks.html)`

Get or set the border color.

+ **NetAF.Logic.Configuration**

Declaration
`(NetAF.Logic.Configuration.html)`

+ **NetAF.Logic.Modes**

`public AnsiColor BorderColor { get; set; }`
`(NetAF.Logic.Modes.html)`

+ **NetAF.Persistence**

Property Value
`(NetAF.Persistence.html)`

Description

+ **NetAF.Persistence.Json**

`AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)`
`(NetAF.Persistence.Json.html)`

+ **NetAF.Rendering**

Implementation
`(NetAF.Rendering.html)`

+ **NetAF.Rendering.Frame**

Get or set the frame color.

Builders

Declaration
`(NetAF.Rendering.FrameBuilders.html)`

- **NetAF.Rendering.Frame**
`public AnsiColor FrameColor { get; set; }`

Builders.Console

Property Value
`(NetAF.Rendering.FrameBuilders.Console.html)`

Description

Type
`AnsiColor (NetAF.Rendering.FrameBuilders.Console.html)`

`AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)`

`(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)`

`ConsoleCompletionFrame`

`Builder`

NonPlayerMessageColor
`(NetAF.Rendering.FrameBuilders.ConsoleNonPlayerMessageColor.html)`

Get or set the non player message color.

`...`

Declaration

```
public AnsiColor NonPlayerMessageColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

(NetAF.Extensions.html)

PlayerMessageColor

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Get or set the player message color.

+ NetAF.Logic

(NetAF.Logic.html)

```
public AnsiColor PlayerMessageColor { get; set; }
```

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Property Value

+ NetAF.Logic.Configuration

Type (NetAF.Logic.Configuration.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

ResponseColor

(NetAF.Persistence.html)

Get or set the response color.

+ NetAF.Persistence.Json

Declaration

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

ResponseColor { get; set; }

(NetAF.Rendering.html)

Property Value

NetAF.Rendering.Frame

Builders

Type (NetAF.Rendering.FrameBuilders.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

- NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.html)

TitleColor

AnsiColor

Get or set the title color.

(NetAF.Rendering.FrameBuilders.Console.html)

Declaration

(NetAF.Rendering.FrameBuilders.Console.html)

ConsoleCompletionFrame

public AnsiColor TitleColor { get; set; }

Builder

(NetAF.Rendering.FrameBuilders.Console.html)

Property Value

ConsoleConversationFrame

- ...

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

Methods

(NetAF.Conversations.InstructionFrameBuilder.html)

+ NetAF.Extensions
Build(string, IConverser, CommandHelp[], Size)
 (NetAF.Extensions.html)

Build a frame.

+ NetAF.Interpretation

Declaration

(NetAF.Interpretation.html)

+ NetAF.Logic

public static Frame Build(string title, IConverser converser, CommandHelp[] contextualCommands, Size size)

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

Parameters

(NetAF.Logic.Callbacks.html)

Type

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

string title
 (https://learn.microsoft.com/dotnet/api/system.string)
)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

IConverser

+ NetAF.Persistence

(NetAF.Assets.Characters.IConverser.html)

(NetAF.Persistence.html)

CommandHelp

+ NetAF.Persistence.CommandHelp.html)

[], Size size)

(NetAF.Persistence.Json.html)

Size (NetAF.Assets.Size.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

Returns

+ NetAF.Rendering.Frame

Type

Builders

IFrame (NetAF.Rendering.Frames.IFrame.html)

(NetAF.Rendering.FrameBuilder.html)

- NetAF.Rendering.Frame

Builders Console

(NetAF.Rendering.FrameBuilder.html)

IConversationFrameBuilder (NetAF.Rendering.FrameBuilders.IConversationFrameBuilder.html)
 AnsiColor

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

ConsoleAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

ConsoleCompletionFrame

Builder

(NetAF.Rendering.FrameBuilders.Builder.html)

ConsoleConversationFrame

- ...

- ...

Class ConsoleGameOverFrameBuilder

Provides a builder of game over frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**

↳ ConsoleGameOverFrameBuilder

([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**

IGameOverFrameBuilder ([NetAF.Rendering.FrameBuilders.IGameOverFrameBuilder.html](#))

([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Rendering.FrameBuilders.Console.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors

([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleGameOverFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))
Provides a builder of game over frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrame	gridStringBuilder	A builder to use for the string layout.

Declaration

```
public AnsiColor TitleColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Methods

[\(NetAF.Interpretation.html\)](#)

+ NetAF.Logic

Build(string, string, Size)
[\(NetAF.Logic.html\)](#)

Build a frame.

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

`public IFrame Build(string message, string reason, Size size)`
[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Persistence.html)	<i>message</i>	The message to display to the user.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>reason</i>	The reason the game ended.
Size (NetAF.Assets.Size.html) (NetAF.Persistence.Json.html)	<i>size</i>	The size of the frame.

* NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

Type	Description

+ NetAF.Rendering.Frame

[IFrame](#) ([NetAF.Rendering.Frames.IFrame.html](#))

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

Implements

[NetAF.Rendering.Frame](#)

[IGameOverFrameBuilder](#) ([NetAF.Rendering.FrameBuilders.IGameOverFrameBuilder.html](#))

(NetAF.Rendering.FrameBuilders.html)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

ConsoleCompletionFrame

Builder

[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

ConsoleConversationFrame

- ...

Class ConsoleHelpFrameBuilder

Provides a builder of help frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleHelpFrameBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF Interpretation**
IHelpFrameBuilder ([NetAF.Rendering.FrameBuilders.IHelpFrameBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Logic.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF Logic Configuration**
[NetAF.Logic.Configuration.html](#)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF Logic Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF Persistence Json** ConsoleHelpFrameBuilder : IHelpFrameBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF Rendering**

Constructors
([NetAF.Rendering.html](#))

+ **NetAF Rendering Frame Builders**

ConsoleHelpFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilders.ConsoleHelpFrameBuilder.html](#))
Provides a builder of help frames.

NetAF Rendering Frame Builders

Declaration

Console

([NetAF.Rendering.FrameBuilders.Console.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.AnsiColor.html](#))

Parameters

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrame	gridStringBuilder	A builder to use for the string layout.

Declaration

```
public AnsiColor CommandDescriptionColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

(NetAF.Extensions.html)

DescriptionColor

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Get or set the description color.

+ NetAF.Logic

(NetAF.Logic.html)

```
public AnsiColor DescriptionColor { get; set; }
```

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Property Value

+ NetAF.Logic.Configuration

Type (NetAF.Logic.Configuration.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

TitleColor

(NetAF.Persistence.html)

Get or set the title color.

+ NetAF.Persistence.Json

Declaration (NetAF.Persistence.Json.html)

+ NetAF.Rendering

TitleColor [get; set;]

(NetAF.Rendering.html)

Property Value

+ NetAF.Rendering.Frame

Builders

Type (NetAF.Rendering.FrameBuilders.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

- NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.html)

Methods

AnsiColor

(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

ConsoleAboutFrameBuilder (NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

ConsoleCompletionFrame

Build a frame.

Builder

Declaration (NetAF.Rendering.FrameBuilders.ConsoleBuilder.html)

ConsoleConversationFrame

- ...

```
public IFrame Build(string title, string description, CommandHelp[] commandHelp, Size size)
```

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>title</i>	The title.
+ NetAF.Extensions String ((NetAF.Extensions.html))	<i>description</i>	The description.
+ NetAF.Interpretation Size ((NetAF.Interpretation.html))	<i>commandHelp</i>	The command help.
	<i>size</i>	The size of the frame.

Related

Type	Description
+ NetAF.Logic (NetAF.Logic.html)	

+ **NetAF.Logic.Callbacks**

IFrame ([\(NetAF.Rendering.Frames.IFrame.html\)](#))
([\(NetAF.Logic.Callbacks.html\)](#))

+ **NetAF.Logic.Configuration**

Implementation
([\(NetAF.Logic.Configuration.html\)](#))

IHelpFrameBuilder ([\(NetAF.Rendering.FrameBuilders.IHelpFrameBuilder.html\)](#))

+ **NetAF.Logic.Modes**

([\(NetAF.Logic.Modes.html\)](#))

+ **NetAF.Persistence**

([\(NetAF.Persistence.html\)](#))

+ **NetAF.Persistence.Json**

([\(NetAF.Persistence.Json.html\)](#))

+ **NetAF.Rendering**

([\(NetAF.Rendering.html\)](#))

+ **NetAF.Rendering.Frame**

Builders

([\(NetAF.Rendering.FrameBuilders.html\)](#))

- **NetAF.Rendering.Frame**

Builders.Console

([\(NetAF.Rendering.FrameBuilders.Console.html\)](#))

AnsiColor

([\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#))

ConsoleAboutFrameBuilder

([\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#))

ConsoleCompletionFrame

Builder

([\(NetAF.Rendering.FrameBuilders.ConsoleBuilder.html\)](#))

ConsoleConversationFrame

- ...

Class ConsoleReactionFrameBuilder

Provides a builder of reaction frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**

↳ ConsoleReactionFrameBuilder

([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**

IReactionFrameBuilder ([NetAF.Rendering.FrameBuilders.IReactionFrameBuilder.html](#))

([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

ConsoleReactionFrameBuilder : IReactionFrameBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors

([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleReactionFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))

Provides a builder of reaction frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrame	gridStringBuilder	A builder to use for the string layout.

Declaration

```
public AnsiColor TitleColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Methods

[\(NetAF.Interpretation.html\)](#)

+ NetAF.Logic

Build(string, string, Size)
[\(NetAF.Logic.html\)](#)

Build a frame.

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

public IFrame Build(string title, string message, Size size)
[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Persistence.html)	<i>title</i>	The title to display to the user.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>message</i>	The message to display to the user.
Size (NetAF.Assets.Size.html) (NetAF.Persistence.Json.html)	<i>size</i>	The size of the frame.

* NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

Type	Description

+ NetAF.Rendering.Frame

[IFrame](#) ([NetAF.Rendering.Frames.IFrame.html](#))

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

Implements

[NetAF.Rendering.Frame](#)

[IReactionFrameBuilder](#) ([NetAF.Rendering.FrameBuilders.IReactionFrameBuilder.html](#))

(NetAF.Rendering.FrameBuilders.html)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

ConsoleCompletionFrame

Builder

[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

ConsoleConversationFrame

- ...

Class ConsoleRegionMapBuilder

Provides a builder for region maps.

Filter by title

Inheritance ([NetAF.Conversations.Instruction.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleRegionMapBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**
IRegionMapBuilder ([NetAF.Rendering.FrameBuilders.IRegionMapBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Logic.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**
[NetAF.Logic.Configuration.html](#)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json** ConsoleRegionMapBuilder : IRegionMapBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors
([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleRegionMapBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))
Provides a builder for region maps.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrameBuilder	gridStringBuilder	The grid string builder.

Declaration

```
public char HorizontalBoundary { get; set; }
```

Property Value

Type	Description
char (NetAF.Conversations.Instruction.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

LockedExit

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Get or set the character used for representing a locked exit.

Declaration

[\(NetAF.Logic.html\)](#)

```
public char LockedExit { get; set; }
```

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Property Value

+ NetAF.Logic.Configuration

Type

[\(NetAF.Logic.Configuration.html\)](#)

char ([https://learn.microsoft.com/dotnet/api/system.char](#))

+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

NetAF.Persistence

LockedExitColor

[\(NetAF.Persistence.html\)](#)

Get or set the locked exit color.

+ NetAF.Persistence.Json

Declaration

[\(NetAF.Persistence.Json.html\)](#)

+ NetAF.Rendering

```
public char LockedExitColor { get; set; }
```

[\(NetAF.Rendering.html\)](#)

Property Value

NetAF.Rendering.Frame

Builders

Type

[\(NetAF.Rendering.FrameBuilders.html\)](#)

AnsiColor ([NetAF.Rendering.FrameBuilders.Console.AnsiColor.html](#))

- NetAF.Rendering.Frame

[Builders.Console](#)

[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

LowerLevel

AnsiColor

Get or set the character to use for lower levels.

[\(NetAF.Rendering.FrameBuilders.Console.CompletionFrame.html\)](#)

Declaration

[\(NetAF.Rendering.FrameBuilders.Console.CompletionFrame.html\)](#)

```
public char LowerLevel { get; set; }
```

Builder

[\(NetAF.Rendering.FrameBuilders.Console.CompletionFrameBuilder.html\)](#)

Property Value

[ConsoleConversationFrame](#)

- ...

Type	Description
char (https://learn.microsoft.com/dotnet/api/system.char)	

LowerLevelColor

Get or set the lower level color structure.

NetAF.Extensions

([NetAF.Extensions.html](#))

```
public AnsiColor LowerLevelColor { get; set; }
```

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

Property Value

+ [NetAF.Logic](#)

Type

([NetAF.Logic.html](#))

```
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)
```

+ [NetAF.Logic.Callbacks](#)

([NetAF.Logic.Callbacks.html](#))

NetAF.Logic.Configuration

([NetAF.Logic.Configuration.html](#))

Get or set the character to use for indicating the player.

+ [NetAF.Logic.Modes](#)

Declaration

([NetAF.Logic.Modes.html](#))

+ [NetAF.Persistence](#)

```
Player { get; set; }
```

([NetAF.Persistence.html](#))

Property Value

+ [NetAF.Persistence.Json](#)

Type

([NetAF.Persistence.Json.html](#))

+ [NetAF.Rendering](#)

```
char (https://learn.microsoft.com/dotnet/api/system.char)
```

([NetAF.Rendering.html](#))

+ [NetAF.Rendering.Frame](#)

PlayerColor

Builders

([NetAF.Rendering.FrameBuilders.PlayerColor.html](#))

Get or set the player color.

+ [NetAF.Rendering.Frame](#)

Declaration

Builders.Console

([NetAF.Rendering.FrameBuilders.Console.html](#))

AnsiColor

Property Value

ConsoleAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleCompletionFrame

```
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)
```

Builder

([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Description
ConsoleAboutFrameBuilder (NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)	

ShowLowerFloors

Get or set if lower floors should be shown.

Declaration

```
public bool ShowLowerFloors { get; set; }
```

INetAF.Conversations.Instruction

Property Value

+ **NetAF.Extensions**

Type
[\(NetAF.Extensions.html\)](#)

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

INetAF.Logic

UNLOCKED_EXIT

[\(NetAF.Logic.html\)](#)

Get or set the character used for representing an unlocked exit.

+ **NetAF.Logic.Callbacks**

Declaration
[\(NetAF.Logic.Callbacks.html\)](#)

+ **NetAF.Logic.Configuration**

[\(NetAF.Logic.Configuration.html\)](#)

Property Value

INetAF.Logic.Modes

Type
[\(NetAF.Logic.Modes.html\)](#)

+ **NetAF.Persistence**

<https://learn.microsoft.com/dotnet/api/system.char>)

[\(NetAF.Persistence.html\)](#)

+ **NetAF.Persistence.Json**

UnvisitedBoundaryColor

[\(NetAF.Persistence.Json.html\)](#)

Get or set the unvisited room boundary color.

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

Declaration

+ **NetAF.Rendering.Frame**

[public AnsiColor UnvisitedBoundaryColor { get; set; }](#)

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

Property Value

- **NetAF.Rendering.Frame**

Type
[\(NetAF.Rendering.FrameBuilders.html\)](#)

A [\(NetAF.Rendering.FrameBuilders.html\)](#)

Console

[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

Get [ConsoleConversationFrame](#) for vertical boundaries.

Builder

Declaration
[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

[ConsoleConversationFrame](#)

- ...

VerticalBoundary

[\(NetAF.Rendering.FrameBuilders.VerticalBoundary.html\)](#)

```
public char VerticalBoundary { get; set; }
```

Property Value

Type	Description
char (https://learn.microsoft.com/dotnet/api/system.char) (NetAF.Conversations.Instruction)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

Get or Set the visited room boundary color.

[\(NetAF.Interpretation.html\)](#)

Declaration

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

+ NetAF.Logic.Callbacks

Property Value

[\(NetAF.Logic.Callbacks.html\)](#)

Type	Description
NetAF.Logic.Configuration	

+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

Methods

[\(NetAF.Persistence.html\)](#)

BuiltRegionMap(Region, Point2D, Point3D, Size)

[\(NetAF.Persistence.Json.html\)](#)

Build a map of a region.

+ NetAF.Rendering

Declaration

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

[\(NetAF.Rendering.FrameBuilder.html\)](#)

Builds a frame map.

[\(NetAF.Rendering.FrameBuilder.html\)](#)

Parameters

- NetAF.Rendering.Frame

Type	Name	Description
Builders.Console		
(NetAF.Rendering.FrameBuilder.html)	<i>region</i>	The region.
(NetAF.Assets.Locations.Region.html)		
(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)	<i>startPosition</i>	The position to start building at.
(NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html)	<i>focusPosition</i>	The position to focus on.
(NetAF.Rendering.FrameBuilders.Size.html)	<i>maxSize</i>	The maximum size available in which to build the map.
(NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html)		
ConsoleConversationFrame		
- ...		

Implements

IRegionMapBuilder (NetAF.Rendering.FrameBuilders.IRegionMapBuilder.html)

▼

(NetAF.Conversations.Instructions.html)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilders.html)

- NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.html)

AnsiColor

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

ConsoleAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.Console.AboutFrameBuilder.html)

ConsoleCompletionFrame

Builder

(NetAF.Rendering.FrameBuilders.Console.Builder.html)

ConsoleConversationFrame

- ...

Class ConsoleRegionMapFrameBuilder

Provides a builder of region map frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**

↳ ConsoleRegionMapFrameBuilder

([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**

IRegionMapFrameBuilder ([NetAF.Rendering.FrameBuilders.IRegionMapFrameBuilder.html](#))

([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

([NetAF.Logic.Configuration.html](#))

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json** ConsoleRegionMapFrameBuilder : IRegionMapFrameBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors

([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleRegionMapFrameBuilder(GridStringBuilder, IRegionMapBuilder)

([NetAF.Rendering.FrameBuilder.html](#))

Provides a builder of region map frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilders.html](#))

ConsoleRegionMapFrameBuilder(GridStringBuilder gridStringBuilder, IRegionMapBuilder regionMapBuilder)

ANSIColor

([NetAF.Rendering.FrameBuilders.html](#))

ConsoleAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.html](#))

Type ConsoleCompletionFrame

Name

Description

Builder GridStringBuilder

gridStringBuilder

A builder to use for the string layout.

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
IRegionMapBuilder (NetAF.Rendering.FrameBuilders.IRegionMapBuilder.html)	regionMapBuilder	A builder for region maps.

▼

Properties

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

Get or set the background color.

(NetAF.Interpretation.html)

Declaration

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

Property Value

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

BorderColor

+ NetAF.Persistence

Get or set the border color.

(NetAF.Persistence.html)

Declaration

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

```
public AnsiColor BorderColor { get; set; }
```

+ NetAF.Rendering

(NetAF.Rendering.html)

Property Value

+ NetAF.Rendering.Frame

Type

Builders

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

(NetAF.Rendering.FrameBuilders.html)

- NetAF.Rendering.Frame

Builders Console

CommandsColor

(NetAF.Rendering.FrameBuilders.html)

Get or set the commands color.

AnsiColor

Declaration

ConsoleAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.html)

```
public ANSI_COLOR CommandsColor { get; set; }
```

ConsoleCompletionFrame

Builder

Property Value

(NetAF.Rendering.FrameBuilders.html)

ConsoleConversationFrame

- ...

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

InputColor

Get or set the input colors. Instructs the system to use the specified colors.

NetAF.Extensions

(NetAF.Extensions.html)

```
public AnsiColor InputColor { get; set; }
```

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Property Value

+ NetAF.Logic

Type

(NetAF.Logic.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

TitleColor

(NetAF.Logic.Configuration.html)

Get or set the title color.

+ NetAF.Logic.Modes

Declaration

(NetAF.Logic.Modes.html)

+ NetAF.Persistence TitleColor { get; set; }

(NetAF.Persistence.html)

Property Value

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

Methods

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

- NetAF.Rendering.Frame

Build(Region, Point3D, CommandHelp[], Size)

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

Declaration

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

ConsoleAboutFrameBuilder

```
public IFrame Build(Region region, Point3D focusPosition, CommandHelp[] contextualCommands, Size size)
```

ConsoleCompletionFrame

Builder

Parameters

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

ConsoleConversationFrame

- ...

Type	Name	Description
Region (NetAF.Assets.Locations.Region.html)	<i>region</i>	The region.
Point3D (NetAF.Assets.Point3D.html)	<i>focusPosition</i>	The position to focus on.
CommandHelp (NetAF.Commands.CommandHelp.html) + NetAF.Conversations.Instruction + NetAF.Extensions	<i>contextualCommands</i>	The contextual commands to display.
Size (NetAF.Assets.Size.html)	<i>size</i>	The size of the frame.

(NetAF.Extensions.html)

Returns

+ NetAF.Interpretation

Type

(NetAF.Interpretation.html)

IFrame (NetAF.Rendering.Frames.IFrame.html)

+ NetAF.Logic

(NetAF.Logic.html)

Implements

NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

IRegionMapFrameBuilder (NetAF.Rendering.FrameBuilders.IRegionMapFrameBuilder.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilders.html)

- NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.html)

AnsiColor

(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

ConsoleAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

ConsoleCompletionFrame

Builder

(NetAF.Rendering.FrameBuilders.ConsoleBuilder.html)

ConsoleConversationFrame

- ...

Description

Class ConsoleRoomMapBuilder

Provides a room map builder.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleRoomMapBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**
IRoomMapBuilder ([NetAF.Rendering.FrameBuilders.IRoomMapBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Logic.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json** ConsoleRoomMapBuilder : IRoomMapBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors
([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleRoomMapBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilders.html](#))

Provides a room map builder.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilders.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrameBuilder	gridStringBuilder	The grid string builder.

Properties

BoundaryColor

Get or set the room boundary color.

Declaration
`(NetAF.Conversations.Instruct`

+ **NetAF.Extensions**
`(NetAF.Extensions.html)`

Property Value
+ **NetAF.Interpretation**

Type
`(NetAF.Interpretation.html)`

+ **NetAF.Logic**
`AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)`

`(NetAF.Logic.html)`

+ **NetAF.Logic.Callbacks**

Corner
`(NetAF.Logic.Callbacks.html)`

Get or set the character to use for corners.
+ **NetAF.Logic.Configuration**

Declaration
`(NetAF.Logic.Configuration.html)`

+ **NetAF.Logic.Modes**

`public char Corner { get; set; }`
`(NetAF.Logic.Modes.html)`

+ **NetAF.Persistence**

Property Value
`(NetAF.Persistence.html)`

Type

+ **NetAF.Persistence.Json**
`char (https://learn.microsoft.com/dotnet/api/system.char)`
`(NetAF.Persistence.Json.html)`

+ **NetAF.Rendering**

HorizontalBoundary
`(NetAF.Rendering.html)`

+ **NetAF.Rendering.Frame**

Get or set the character to use for horizontal boundaries.

Builders
Declaration
`(NetAF.Rendering.FrameBuild`

- **NetAF.Rendering.Frame**
`HorizontalBoundary { get; set; }`

Builders.Console

Property Value
`(NetAF.Rendering.FrameBuild`

Type
`AnsiColor`

`(NetAF.Rendering.FrameBuilders.C`

`char (https://learn.microsoft.com/dotnet/api/system.char)`

`ConsoleCompletionFrame`

`ConsoleCompletionFrame`

HorizontalExitBorder
`(NetAF.Rendering.FrameBuild`

`ConsoleConversationFrame`

Get or set the character to use for horizontal exit borders.

`_ ..`

Description

Declaration

```
public char HorizontalExitBorder { get; set; }
```

Property Value

Type	Description
char (NetAF.Conversations.Instruction.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

ItemOrCharacterColor

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Get or set the item or character color.

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

```
public AnsiColor ItemOrCharacterColor { get; set; }
```

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

Property Value

+ NetAF.Logic.Configuration

Type [\(NetAF.Logic.Configuration.html\)](#)

AnsiColor ([NetAF.Rendering.FrameBuilders.Console.AnsiColor.html](#))

+ NetAF.Logic.Modes

[\(NetAF.Logic.Modes.html\)](#)

+ NetAF.Persistence

ItemOrCharacterInRoom

[\(NetAF.Persistence.html\)](#)

Get or set the character used for representing there is an item or a character in the room.

+ NetAF.Persistence.Json

Declaration

[\(NetAF.Persistence.Json.html\)](#)

+ NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

Property Value

NetAF.Rendering.Frame

Builders

Type

[\(NetAF.Rendering.FrameBuilder.html\)](#)

char ([NetAF.Rendering.FrameBuilders.Character.html](#))

- NetAF.Rendering.Frame

[Builders.Console](#)

[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

KeyPadding

AnsiColor

Get or set the padding between the key and the map.

[\(NetAF.Rendering.FrameBuilders.KeyPadding.html\)](#)

Declaration

[\(NetAF.Rendering.FrameBuilders.KeyPadding.html\)](#)

ConsoleCompletionFrame

public int KeyPadding { get; set; }

Builder

[\(NetAF.Rendering.FrameBuilders.KeyPaddingBuilder.html\)](#)

Property Value

ConsoleConversationFrame

- ...

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	

LockedExit

Get or set the character used for representing a locked exit.

NetAF.Extensions

([NetAF.Extensions.html](#))

```
public char LockedExit { get; set; }
```

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

Property Value

+ NetAF.Logic

Type

([NetAF.Logic.html](#))

char (<https://learn.microsoft.com/dotnet/api/system.char>)

+ NetAF.Logic.Callbacks

([NetAF.Logic.Callbacks.html](#))

LockedExitColor

([NetAF.Logic.Configuration.html](#))

Get or set the locked exit color.

+ NetAF.Logic.Modes

Declaration

([NetAF.Logic.Modes.html](#))

+ NetAF.Persistence

LockedExitColor { get; set; }

([NetAF.Persistence.html](#))

Property Value

+ NetAF.Persistence.Json

([NetAF.Persistence.Json.html](#))

+ NetAF.Rendering

([NetAF.Rendering.html](#))

+ NetAF.Rendering.Frame

UnvisitedExitColor Builders

([NetAF.Rendering.FrameBuilders.html](#))

Get or set the unvisited exit color.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilders.Console.html](#))

AnsiColor

Property Value

ConsoleAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleCompletionFrame

([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrame.html](#))

Builder

([NetAF.Rendering.FrameBuilders.Builder.html](#))

ConsoleConversationFrame

([NetAF.Rendering.FrameBuilders.ConsoleConversationFrame.html](#))

- ...

Type	Description
ConsoleAboutFrameBuilder (NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)	

VerticalBoundary

Get or set the character to use for vertical boundaries.

Declaration

```
public char VerticalBoundary { get; set; }
```

+ [NetAF.Conversations.Instruction](#)

Property Value

+ [NetAF.Extensions](#)

Type
[\(NetAF.Extensions.html\)](#)

char (<https://learn.microsoft.com/dotnet/api/system.char>)

+ [NetAF.Interpretation](#)

[\(NetAF.Interpretation.html\)](#)

+ [NetAF.Logic](#)

VerticalExitBorder

[\(NetAF.Logic.html\)](#)

Get or set the character to use for vertical exit borders.

+ [NetAF.Logic.Callbacks](#)

Declaration

[\(NetAF.Logic.Callbacks.html\)](#)

+ [NetAF.Logic.Configuration](#)

[VerticalExitBorder { get; set; }](#)

[\(NetAF.Logic.Configuration.html\)](#)

Property Value

+ [NetAF.Logic.Modes](#)

Type
[\(NetAF.Logic.Modes.html\)](#)

+ [NetAF.Persistence](#)

char (<https://learn.microsoft.com/dotnet/api/system.char>)

[\(NetAF.Persistence.html\)](#)

+ [NetAF.Persistence.Json](#)

VisitedExitColor

[\(NetAF.Persistence.Json.html\)](#)

Get or set the visited exit color.

+ [NetAF.Rendering](#)

[\(NetAF.Rendering.html\)](#)

Declaration

+ [NetAF.Rendering.Frame](#)

[public AnsiColor VisitedExitColor { get; set; }](#)

[Builders](#)

[\(NetAF.Rendering.FrameBuilders.html\)](#)

Property Value

- [NetAF.Rendering.Frame](#)

Type
[Builders.Console](#)

[\(NetAF.Rendering.FrameBuilders.html\)](#)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

Methods

ConsoleCompletionFrame

Builder

BuildRoomMap(Room, ViewPoint, KeyType, Point2D, out int, out int)

[ConsoleConversationFrame](#)

- ...

Build a map for a room.

Declaration

```
public void BuildRoomMap(Room room, ViewPoint viewPoint, KeyType key, Point2D startPosition, out int endX, out int endY)
```



Parameters

Parameter	Type	Name	Description
+ NetAF.Extensions (NetAF.Extensions.html)			
Room (NetAF.Assets.Locations.Room.html)	room		The room.
+ NetAF.Interpretation (NetAF.Interpretation.html)	ViewPoint (NetAF.Assets.Locations.ViewPoint.html)	viewPoint	The viewpoint from the room.
KeyType (NetAF.Rendering.KeyType.html)	key		The key type.
+ NetAF.Logic (NetAF.Logic.html)	Point2D (NetAF.Assets.Point2D.html)	startPosition	The start position.
int (https://learn.microsoft.com/dotnet/api/system.int32)	endX		The end position, x.
+ NetAF.Logic.Callbacks (NetAF.Logic.Callbacks.html)	int (https://learn.microsoft.com/dotnet/api/system.int32)	endY	The end position, x.

+ NetAF.Logic.Configuration

[NetAF.Logic.Configuration.html](#)

+ NetAF.Logic.Modes

IRoomMapBuilder ([NetAF.Rendering.FrameBuilders.IRoomMapBuilder.html](#))

[\(NetAF.Logic.Modes.html\)](#)

+ NetAF.Persistence

[\(NetAF.Persistence.html\)](#)

+ NetAF.Persistence.Json

[\(NetAF.Persistence.Json.html\)](#)

+ NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

- NetAF.Rendering.Frame

Builders.Console

[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)

AnsiColor

([NetAF.Rendering.FrameBuilders.Console.AnsiColor.html](#))

ConsoleAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

ConsoleCompletionFrame

Builder

([NetAF.Rendering.FrameBuilders.Builder.html](#))

ConsoleConversationFrame

- ...

Class ConsoleSceneFrameBuilder

Provides a builder for scene frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction.html](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleSceneFrameBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**
ISceneFrameBuilder ([NetAF.Rendering.FrameBuilders.ISceneFrameBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json** ConsoleSceneFrameBuilder : ISceneFrameBuilder

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors ([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

Builders ConsoleSceneFrameBuilder(GridStringBuilder, IRoomMapBuilder)

([NetAF.Rendering.FrameBuilders.html](#))

Provides a builder for scene frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#)) ConsoleSceneFrameBuilder(GridStringBuilder gridStringBuilder, IRoomMapBuilder roomMapBuilder)

([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

ConsoleAboutFrameBuilder

([NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html](#))

Type ConsoleCompletionFrame

([NetAF.Rendering.FrameBuilders.ConsoleCompletionFrame.html](#))

Builder GridStringBuilder

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrame	gridStringBuilder	A builder to use for the string layout.

Type	Name	Description
IRoomMapBuilder (NetAF.Rendering.FrameBuilders.IRoomMapBuilder.html)	roomMapBuilder	A builder to use for room maps.

▼

Properties

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

Get or set the background color.

(NetAF.Interpretation.html)

Declaration

+ NetAF.Logic

(NetAF.Logic.html)

BackgroundColor { get; set; }

+ NetAF.Logic.Callbacks

Property Value

(NetAF.Logic.Callbacks.html)

+ Type

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

Description

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

BorderColor

+ NetAF.Persistence

Get or set the border color.

(NetAF.Persistence.html)

Declaration

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

public AnsiColor BorderColor { get; set; }

+ NetAF.Rendering

(NetAF.Rendering.html)

Property Value

+ NetAF.Rendering.Frame

Type

Builders

AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)

Description

- NetAF.Rendering.Frame

Builders.Console

CommandsColor

(NetAF.Rendering.FrameBuilders.Console.CommandsColor.html)

Get or set the commands color.

AnsiColor

Declaration

ConsoleAboutFrameBuilder

(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html)

public AnsiColor CommandsColor { get; set; }

ConsoleCompletionFrame

Builder

Property Value

(NetAF.Rendering.FrameBuilders.ConsoleBuilder.html)

ConsoleConversationFrame

- ...

Methods

Build(Room, ViewPoint, PlayableCharacter, CommandHelp[], KeyType, Size)

Build a frame.



Declaration

[\(NetAF.Conversations.InstructionFrameBuilder.html\)](#)

+ **NetAF.Extensions**
+ **NetAF.Extensions**
[\(NetAF.Extensions.html\)](#)

+ NetAF.Interpretation

Parameters

[\(NetAF.Interpretation.html\)](#)

Type

+ NetAF.Logic

Room ([NetAF.Assets.Locations.Room.html](#))
[\(NetAF.Logic.html\)](#)

ViewPoint ([NetAF.Assets.Locations.ViewPoint.html](#))
+ **NetAF.Logic.Callbacks**

[\(NetAF.Logic.Callbacks.html\)](#)

PlayableCharacter

+ **NetAF.Logic.Configuration**
([NetAF.Assets.Characters.PlayableCharacter.html](#))

[\(NetAF.Logic.Configuration.html\)](#)

CommandHelp

+ **NetAF.Logic.Modes**
([NetAF.Logic.Modes.CommandHelp.html](#))

[\(NetAF.Logic.Modes.html\)](#)

KeyType ([NetAF.Rendering.KeyType.html](#))
+ **NetAF.Persistence**

[\(NetAF.Persistence.html\)](#)

Size ([NetAF.Assets.Size.html](#))

Name	Description
room	Specify the Room.
viewPoint	Specify the viewpoint from the room.
player	Specify the player.
contextualCommands	The contextual commands to display.
keyType	The type of key to use.
size	The size of the frame.

+ NetAF.Persistence.Json

Returns

[\(NetAF.Persistence.Json.html\)](#)

Type

+ NetAF.Rendering

IFrame ([NetAF.Rendering.Frames.IFrame.html](#))
[\(NetAF.Rendering.html\)](#)

Description

+ NetAF.Rendering.Frame

Implements

[\(NetAF.Rendering.FrameBuilder.html\)](#)

ISceneFrameBuilder ([NetAF.Rendering.FrameBuilders.ISceneFrameBuilder.html](#))

- NetAF.Rendering.Frame

Builders.Console

[\(NetAF.Rendering.FrameBuilders.ConsoleBuilder.html\)](#)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleCompletionFrameBuilder.html\)](#)

ConsoleCompletionFrame

Builder

[\(NetAF.Rendering.FrameBuilders.ConsoleConversationFrameBuilder.html\)](#)

ConsoleConversationFrame

- ...

Class ConsoleTitleFrameBuilder

Provides a builder of title frames.

Filter by title

Inheritance ([NetAF.Conversations.Instruction](#))

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Extensions**
↳ ConsoleTitleFrameBuilder
([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**
TitleFrameBuilder ([NetAF.Rendering.FrameBuilders.ITitleFrameBuilder.html](#))
([NetAF.Interpretation.html](#))

Inherited Members

+ **NetAF.Logic**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))
([NetAF.Logic.html](#))

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
([NetAF.Logic.Callbacks.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Configuration**
[NetAF.Logic.Configuration.html](#)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Logic.Modes**

Namespace: NetAF ([NetAF.html](#)).Rendering ([NetAF.Rendering.html](#)).FrameBuilders ([NetAF.Rendering.FrameBuilders.html](#)).Console
([NetAF.Logic.Modes.html](#))

Assembly: NetAF.dll

+ **NetAF.Persistence**

Syntax

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

Constructors
([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

ConsoleTitleFrameBuilder(GridStringBuilder)

([NetAF.Rendering.FrameBuilder.html](#))

Provides a builder of title frames.

NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

AnsiColor

([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

ConsoleAboutFrameBuilder

Type ([NetAF.Rendering.FrameBuilders.ConsoleBuilder.html](#))

ConsoleCompletionFrame

GridStringBuilder

Builder ([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

([NetAF.Rendering.FrameBuilders.GridStringBuilder.html](#))

ConsoleConversationFrame

- ...

Type	Name	Description
ConsoleCompletionFrame	gridStringBuilder	A builder to use for the string layout.

Declaration

```
public AnsiColor TitleColor { get; set; }
```

Property Value

Type	Description
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Methods

[\(NetAF.Interpretation.html\)](#)

+ NetAF.Logic

Build(string, string, Size)
[\(NetAF.Logic.html\)](#)

Build a frame.

+ NetAF.Logic.Callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

public IFrame Build(string title, string description, Size size)
[\(NetAF.Logic.Configuration.html\)](#)

+ NetAF.Logic.Modes

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Persistence.html)	<i>title</i>	The title.
string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i>	The description.
Size (NetAF.Assets.Size.html) (NetAF.Persistence.Json.html)	<i>size</i>	The size of the frame.

* NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

[IFrame](#) ([NetAF.Rendering.Frames.IFrame.html](#))

Builders

[\(NetAF.Rendering.FrameBuilders.html\)](#)

Implements

[NetAF.Rendering.Frame](#)

[ITitleFrameBuilder](#) ([NetAF.Rendering.FrameBuilders.ITitleFrameBuilder.html](#))

(NetAF.Rendering.FrameBuilders.html)

AnsiColor

[\(NetAF.Rendering.FrameBuilders.Console.AnsiColor.html\)](#)

ConsoleAboutFrameBuilder

[\(NetAF.Rendering.FrameBuilders.ConsoleAboutFrameBuilder.html\)](#)

ConsoleCompletionFrame

Builder

[\(NetAF.Rendering.FrameBuilders.Builder.html\)](#)

ConsoleConversationFrame

- ...

Namespace NetAF.Rendering.Frames

Classes

Filter by title

(NetAF.Commands.RegionMap)

GridTextFrame (NetAF.Rendering.Frames.GridTextFrame.html)

+ NetAF.Commands.Scene

Provides a grid based frame for displaying a command based interface.

(NetAF.Commands.Scene.html)

Interfaces

(NetAF.Conversations.html)

IFrame (NetAF.Rendering.Frames.IFrame.html)

Instructions

Represents any object that is a frame that can display a command based interface.

(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.htm

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuild

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	<i>cursorTop</i>	The cursor top position.
AnsiColor (NetAF.Rendering.FrameBuilders.Console.AnsiColor.html)	<i>backgroundColor</i>	The background color.

▼

+ NetAF.Commands.Region Map

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Declaration

(NetAF.Conversations.html)

```
public AnsiColor BackgroundColor { get; }
```

+ NetAF.Conversations.

Instructions

Property Value

(NetAF.Conversations.Instruct

Type

+ NetAF.Extensions

AnsiColor (<https://learn.microsoft.com/dotnet/api/system.console.ansicolor>.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

CursorLeft

+ NetAF.Logic

Get the cursor left position.

(NetAF.Logic.html)

Declaration

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

```
public int CursorLeft { get; }
```

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Property Value

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

+ NetAF.Persistence

(NetAF.Persistence.html)

CursorTop

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Get the cursor top position.

Declaration

(NetAF.Rendering.html)

```
public int CursorTop { get; }
```

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder

Property Value

Type	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	

ShowCursor

Gets or sets if the cursor should be shown.

NetAF.Commands.Region

Declaration

(NetAF.Commands.RegionMap)

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Property Value

+ NetAF.Conversations

Type ([NetAF.Conversations.html](#))

Description

+ NetAF.Conversations

Instructions

(NetAF.Conversations.Instruct)

Methods

(NetAF.Extensions.html)

NetAF.Interpretation

Render(IFramePresenter)

(NetAF.Interpretation.html)

Render this frame on a presenter.

+ NetAF.Logic

Declaration

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Parameters

+ NetAF.Logic.Configuration

Type ([NetAF.Logic.Configuration.html](#))

Name

Description

+ NetAF.Logic.Modes ([Rendering.Presenters.IFramePresenter.html](#))

presenter

The presenter.

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

ToString()

(NetAF.Persistence.html)

Returns a string that represents the current object.

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Declaration

+ NetAF.Rendering

public override string ToString()

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Returns

Builders

(NetAF.Rendering.FrameBuilder.html)

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	A string that represents the current object.

Overrides

`object.ToString()` (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Implements

+ **NetAF.Commands.Region**

`IRegion` ([NetAF.Rendering.Frames.IFrame.html](#))

(NetAF.Commands.RegionMap)

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Instructions

(NetAF.Conversations.Instruct

+ **NetAF.Extensions**

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.htm

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

+ **NetAF.Rendering**

(NetAF.Rendering.html)

+ **NetAF.Rendering.Frame**

Builders

(NetAF.Rendering.FrameBuild

Get or set if the cursor should be shown.

Declaration

```
bool ShowCursor { get; set; }
```



Property Value

Type	Description
+ NetAF.Commands.RegionMap bool (https://learn.microsoft.com/dotnet/api/system.boolean)	

([NetAF.Commands.RegionMap](#))

+ **NetAF.Commands.Scene**

([NetAF.Commands.Scene.html](#))

+ **NetAF.Conversations**

([NetAF.Conversations.html](#))

Render(IFramePresenter)

+ **NetAF.Conversations.**

Render this frame on a presenter.

Instructions

Declaration

([NetAF.Conversations.Instruct](#))

+ **NetAF.Extensions**

void Render(IFramePresenter presenter)

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

IFramePresenter ([NetAF.Rendering.Presenters.IFramePresenter.html](#))

([NetAF.Logic.html](#))

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

+ **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

+ **NetAF.Persistence**

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

Builders

([NetAF.Rendering.FrameBuilder.html](#))

Namespace NetAF.Rendering.Presenters

Classes

Filter by title

(NetAF.Commands.RegionMap)
TextWriterPresenter ([NetAF.Rendering.Presenters.TextWriterPresenter.html](#))

+ **NetAF.Commands.Scene**
Represents a presenter for TextWriter.
([NetAF.Commands.Scene.html](#))

Interfaces

(NetAF.Conversations.html)

IFramePresenter ([NetAF.Rendering.Presenters.IFramePresenter.html](#))

Instruct
Represents an object that can render a frame.
([NetAF.Conversations.Instruct.html](#))

+ **NetAF.Extensions**

([NetAF.Extensions.html](#))

+ **NetAF.Interpretation**

([NetAF.Interpretation.html](#))

+ **NetAF.Logic**

([NetAF.Logic.html](#))

+ **NetAF.Logic.Callbacks**

([NetAF.Logic.Callbacks.html](#))

+ **NetAF.Logic.Configuration**

([NetAF.Logic.Configuration.html](#))

+ **NetAF.Logic.Modes**

([NetAF.Logic.Modes.html](#))

+ **NetAF.Persistence**

([NetAF.Persistence.html](#))

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

+ **NetAF.Rendering**

([NetAF.Rendering.html](#))

+ **NetAF.Rendering.Frame**

Builders

([NetAF.Rendering.FrameBuilder.html](#))

Interface IFramePresenter

Represents an object that can render a frame.

Filter by title

Namespace: NetAF (NetAF.html).Rendering (NetAF.Rendering.html).Presenters (NetAF.Rendering.Presenters.html)

Assembly: NetAF.dll

+ NetAF.Commands.Region

Syntax

Map

(NetAF.Commands.RegionMap

public interface IFramePresenter

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html

+ NetAF.Conversations

Methods

(NetAF.Conversations.html

+ NetAF.Conversations.

Write(char)

(NetAF.Conversations.Instruct

Write a character.

+ NetAF.Extensions

Declaration

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Parameters

+ NetAF.Logic

Type

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

Type

Name

Description

value

The character to write.

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

Write(string)

(NetAF.Logic.Configuration.html)

Write a string.

+ NetAF.Logic.Modes

Type

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

void Write(string value)

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

Parameters

Type

(NetAF.Persistence.Json.html)

Name

Description

+ NetAF.Rendering

string (https://learn.microsoft.com/dotnet/api/system.string)

(NetAF.Rendering.html)

value

The string to write.

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

▼

- + **NetAF.Commands.Region**
Map
(NetAF.Commands.RegionMap)
- + **NetAF.Commands.Scene**
(NetAF.Commands.Scene.html)
- + **NetAF.Conversations**
(NetAF.Conversations.html)
- + **NetAF.Conversations.**
Instructions
(NetAF.Conversations.Instruct)
- + **NetAF.Extensions**
(NetAF.Extensions.html)
- + **NetAF.Interpretation**
(NetAF.Interpretation.html)
- + **NetAF.Logic**
(NetAF.Logic.html)
- + **NetAF.Logic.Callbacks**
(NetAF.Logic.Callbacks.html)
- + **NetAF.Logic.Configuration**
(NetAF.Logic.Configuration.html)
- + **NetAF.Logic.Modes**
(NetAF.Logic.Modes.html)
- + **NetAF.Persistence**
(NetAF.Persistence.html)
- + **NetAF.Persistence.Json**
(NetAF.Persistence.Json.html)
- + **NetAF.Rendering**
(NetAF.Rendering.html)
- + **NetAF.Rendering.Frame**
Builders
(NetAF.Rendering.FrameBuilder)

Class TextWriterPresenter

Represents a presenter for TextWriter.

Filter by title

Inheritance

+ [NetAF.Commands.Region](#) (https://learn.microsoft.com/dotnet/api/system.object)

MapTextWriterPresenter

Implements [\(NetAF.Commands.RegionMap\)](#)

IFramePresenter ([NetAF.Rendering.Presenters.IFramePresenter.html](#))

+ [NetAF.Commands.Scene](#)

Inherited Members

[\(NetAF.Commands.Scene.html\)](#)

object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))

+ [\(NetAF.Conversations.html\)](#)

object.Equals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object, system-object))

+ [\(NetAF.Conversations\)](#)

object.GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)

object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype)

object.ReferenceEquals(object, object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)

+ [NetAF.Extensions](#)

Namespace: [NetAF](#) ([NetAF.html](#)).[Rendering](#) ([NetAF.Rendering.html](#)).[Presenters](#) ([NetAF.Rendering.Presenters.html](#))

+ [\(NetAF.Extensions.html\)](#)

Assembly: [NetAF.dll](#)

Syntax

+ [NetAF.Interpretation](#)

(NetAF.Interpretation.html)

public sealed class TextWriterPresenter : IFramePresenter

+ [NetAF.Logic](#)

(NetAF.Logic.html)

Outstanding callbacks

[\(NetAF.Logic.Callbacks.html\)](#)

[TextWriterPresenter\(TextWriter\)](#)

(NetAF.Logic.Configuration.html)

Represents a presenter for TextWriter.

+ [NetAF.Logic.Modes](#)

Declaration

[\(NetAF.Logic.Modes.html\)](#)

+ [NetAF.Persistence](#) (TextWriter writer)

(NetAF.Persistence.html)

Parameters

+ [NetAF.Persistence.Json](#)

(NetAF.Persistence.Json.html)

+ [NetAF.Rendering](#) (https://learn.microsoft.com/dotnet/api/system.io.textwriter)

(NetAF.Rendering.html)

+ [NetAF.Rendering.Frame](#)

Builders

[\(NetAF.Rendering.FrameBuilder.html\)](#)

Properties

Events

Protected Constructors

Protected Fields

Protected Methods

Public Constructors

Public Fields

Public Methods

Protected Properties

Public Properties

Protected Indexers

Public Indexers

Protected Events

Public Events

Methods

ToString()

Returns a string that represents the current object.

Declaration
`

+ NetAF.Commands.RegionMap

(NetAF.Commands.RegionMap)
Returns

+ NetAF.Commands.SceneType

(NetAF.Commands.Scene.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Conversations

(NetAF.Conversations.html)

object ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAF.Extensions

Write a character.

(NetAF.Extensions.html)

Declaration
`

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

Parameters

(NetAF.Logic.html)

Type

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

char (<https://learn.microsoft.com/dotnet/api/system.char>)

Name

Description

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Write(string)

+ NetAF.Logic.Modes

Write a string.

(NetAF.Logic.Modes.html)

Declaration

+ NetAF.Persistence

(NetAF.Persistence.html)

public void Write(string value)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Parameters

+ NetAF.Rendering

(NetAF.Rendering.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Name

Description

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

Implements

IFramePresenter (NetAF.Rendering.Presenters.IFramePresenter.html)

▼

- NetAF.Commands.Region
Map
(NetAF.Commands.RegionMap)
- NetAF.Commands.Scene
(NetAF.Commands.Scene.html)
- NetAF.Conversations
(NetAF.Conversations.html)
- NetAF.Conversations.
Instructions
(NetAF.Conversations.Instruct)
- NetAF.Extensions
(NetAF.Extensions.html)
- NetAF.Interpretation
(NetAF.Interpretation.html)
- NetAF.Logic
(NetAF.Logic.html)
- NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)
- NetAF.Logic.Configuration
(NetAF.Logic.Configuration.htm)
- NetAF.Logic.Modes
(NetAF.Logic.Modes.html)
- NetAF.Persistence
(NetAF.Persistence.html)
- NetAF.Persistence.Json
(NetAF.Persistence.Json.html)
- NetAF.Rendering
(NetAF.Rendering.html)
- NetAF.Rendering.Frame
Builders
(NetAF.Rendering.FrameBuild)

Namespace NetAF.Serialization

Classes

Filter by title

CustomCommandSerialization

(NetAF.Serialization.CustomCommandSerialization.html)

+ NetAF.Commands.Scene

Represents a serialization of a CustomCommand.

(NetAF.Commands.Scene.html)

+ NetAF.Conversations

GameSerialization (NetAF.Serialization.GameSerialization.html)

(NetAF.Conversations.html)

Represents a serialization of a Game.

+ NetAF.Conversations.

Interfaces

(NetAF.Conversations.Instruct

+ NetAF.Extensions

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

(NetAF.Extensions.html)

Represents any object that is a serialization of another object.

+ NetAF.Interpretation

(NetAF.Interpretation.html)

IRestoreFromObjectSerialization<T>

(NetAF.Serialization.IRestoreFromObjectSerialization-1.html)

(NetAF.Logic.html)

Represents any object that can restore from an IObjectSerialization.

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frame

Builders.Console

Class CustomCommandSerialization

Represents a serialization of a CustomCommand.

Filter by title

Inheritance

(NetAF.Commands.RegionMap)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ NetAF.Commands.Scene

CustomCommandSerialization

(NetAFCommands.Scene.html)

Implements

+ Object.Serialization (NetAF.Serialization.IObjectSerialization-1.html) <CustomCommand

(NetAFCommands.CustomCommand.html) >

(NetAF.Conversations.html)

Inherited Members

+ NetAF.Conversations.

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

(NetAF.Conversations.Instruct)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

+ NetAF.Extensions.

(NetAF.Extensions.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ NetAF.Interpretation

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAF.Logic

Namespace: NetAF (NetAF.html).Serialization (NetAF.Serialization.html)

(NetAF.Logic.html)

Assembly: NetAF.dll

+ NetAF.Logic.Callbacks

Syntax
(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

Constructors
(NetAF.Logic.Modes.html)

+ NetAF.Persistence

CustomCommandSerialization(CustomCommand)

(NetAF.Persistence.html)

Represents a serialization of a CustomCommand.

+ NetAF.Persistence.Json

Delegates
(NetAF.Persistence.Json.html)

+ NetAF.Rendering

public CustomCommandSerialization(CustomCommand command)

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Parameters

Builders

Type

(NetAF.Rendering.FrameBuilder)

CustomCommand (NetAF.Commands.CustomCommand.html)

+ NetAF.Rendering.Frame

Builders.Console

Type	Name	Description
CustomCommand (NetAF.Commands.CustomCommand.html)	command	The command.

Properties

CommandName

Get or set the command name.

Declaration

([NetAF.Commands.RegionMap](#))

```
public string CommandName { get; set; }
```

+ [NetAF.Commands.Scene](#)

([NetAF.Commands.Scene.html](#))

Property Value

+ [NetAF.Conversations](#)

Type

([NetAF.Conversations.html](#))

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ [NetAF.Conversations](#).

Instructions

([NetAF.Conversations.Instruct](#))

IsPlayerVisible

+ [NetAF.Extensions](#)

Get or set if it is player visible.

([NetAF.Extensions.html](#))

Declaration

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

```
public bool IsPlayerVisible { get; set; }
```

+ [NetAF.Logic](#)

([NetAF.Logic.html](#))

+ [NetAF.Logic.Callbacks](#)

Description

([NetAF.Logic.Callbacks.html](#))

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

+ [NetAF.Logic.Configuration](#)

([NetAF.Logic.Configuration.html](#))

Methods

[NetAF.Logic.Modes](#)

([NetAF.Logic.Modes.html](#))

+ [NetAF.Persistence](#)

Restore(CustomCommand)

([NetAF.Persistence.html](#))

Restore an instance from this serialization.

+ [NetAF.Persistence.Json](#)

Declaration

([NetAF.Persistence.Json.html](#))

+ [NetAF.Rendering](#)

```
public virtual void Restore(CustomCommand command)
```

([NetAF.Rendering.html](#))

+ [NetAF.Rendering.Frame](#)

Parameters

Builders

Type

([NetAF.Rendering.FrameBuilder](#))

CustomCommand ([NetAF.Commands.CustomCommand.html](#))

Name

Description

command

The command to restore.

+ [NetAF.Rendering.Frame](#)

Builders.Console

Implements

IObjectSerialization<T> ([NetAF.Serialization.IObjectSerialization-1.html](#))

▼

- ([NetAF.Commands.RegionMap.html](#))
- + **NetAF.Commands.Scene**
([NetAF.Commands.Scene.html](#))
- + **NetAF.Conversations**
([NetAF.Conversations.html](#))
- + **NetAF.Conversations.**
Instructions
([NetAF.Conversations.Instructions.html](#))
- + **NetAF.Extensions**
([NetAF.Extensions.html](#))
- + **NetAF.Interpretation**
([NetAF.Interpretation.html](#))
- + **NetAF.Logic**
([NetAF.Logic.html](#))
- + **NetAF.Logic.Callbacks**
([NetAF.Logic.Callbacks.html](#))
- + **NetAF.Logic.Configuration**
([NetAF.Logic.Configuration.html](#))
- + **NetAF.Logic.Modes**
([NetAF.Logic.Modes.html](#))
- + **NetAF.Persistence**
([NetAF.Persistence.html](#))
- + **NetAF.Persistence.Json**
([NetAF.Persistence.Json.html](#))
- + **NetAF.Rendering**
([NetAF.Rendering.html](#))
- + **NetAF.Rendering.Frame**
Builders
([NetAF.Rendering.FrameBuilders.html](#))
- + **NetAF.Rendering.Frame**
Builders.Console
([NetAF.Rendering.FrameBuilders.Console.html](#))

Class GameSerialization

Represents a serialization of a Game.

Filter by title

Inheritance

(NetAF.Commands.RegionMap)

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

+ **NetAF.Commands.Scene**

Implements
IObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<Game ([NetAF.Logic.Game.html](#))>

Implementation
(NetAFConversations.html)

↳ **NetAFConversations** ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

Instructions

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Extensions** (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF ([NetAF.html](#)).Serialization ([NetAF.Serialization.html](#))

Assembly: NetAF.dll
(NetAF.Logic.html)

Syntax

+ **NetAF.Logic.Callbacks**

(NetAFLogic_Callbacks.html)

public class GameSerialization : IObjectSerialization<Game>

+ **NetAF.Logic.Configuration**

(NetAFLogic_Configuration.html)

Constructors

+ **NetAF.Logic.Modes**

(NetAFLogic_Modes.html)

GameSerialization(Game)

+ **NetAF.Persistence**

(NetAFPersistence.html)

Represents a serialization of a Game.

+ **NetAF.Persistence.Json**

(NetAFPersistence.Json.html)

public GameSerialization(Game game)

+ **NetAF.Rendering**

(NetAFRendering.html)

Parameters

+ **NetAF.Rendering.Frame**

Type
Builders

(NetAFRenderingFrameBuilder)

Type	Name	Description
(NetAFRenderingFrameBuilder)	game	The game to serialize.

+ **NetAF.Rendering.Frame**

Builders.Console

Properties

ActivePlayerIdentifier

Get or set the active player identifier.

Declaration

(NetAF.Commands.RegionMap)

```
public string ActivePlayerIdentifier { get; set; }
```

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Property Value

+ NetAF.Conversations

Type

(NetAF.Conversations.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct)

InactivePlayerLocations

+ NetAF.Extensions

Get or set the overworld serialization.

(NetAF.Extensions.html)

Declaration

+ NetAF.Interpretation

(NetAF.Interpretation.html)

```
public PlayableCharacterLocationSerialization[] InactivePlayerLocations { get; set; }
```

+ NetAF.Logic

(NetAF.Logic.html)

Property Value

+ NetAF.Logic.Callbacks

Type

(NetAF.Logic.Callbacks.html)

PlayableCharacterLocationSerialization

(NetAF.Serialization.Assets.PlayableCharacterLocationSerialization.html)

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Overworld

NetAF.Persistence

(NetAF.Persistence.html)

Get or set the overworld serialization.

+ NetAF.Persistence.Json

Declaration

(NetAF.Persistence.Json.html)

```
public OverworldSerialization Overworld { get; set; }
```

+ NetAF.Rendering

(NetAF.Rendering.html)

Property Value

+ NetAF.Rendering.Frame

Type

Builders

(NetAF.Rendering.FrameBuilder)

OverworldSerialization.Asset.OverworldSerialization.html

+ NetAF.Rendering.Frame

Builders.Console

Type	Description

Type	Description

Type	Description

Players

Get or set the player serializations.

Declaration

```
public CharacterSerialization[] Players { get; set; }
```

Property Value
(NetAF.Commands.RegionMap

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html

CharacterSerialization (NetAF.Serialization.Assets.CharacterSerialization.html)[]

+ NetAF.Conversations

(NetAF.Conversations.html)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct

Restore(Game)

+ NetAF.Extensions

(NetAF.Extensions.html)

- NetAF.Interpretation

(NetAF.Interpretation.html)

public void Restore(Game game)

+ NetAF.Logic

(NetAF.Logic.html)

Parameters

+ NetAF.Logic.Callbacks

Type

(NetAF.Logic.Callbacks.html)

Game (NetAF.Logic.Game.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Implements

NetAFLogicModes

(NetAF.Logic.Modes.html)

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frame

Builders.Console

Interface IObjectSerialization<T>

Represents any object that is a serialization of another object.

Filter by title

Namespace: NetAF (NetAF.html).Serialization (NetAF.Serialization.html)

(NetAF.Commands.RegionMap)

Assembly: NetAF.dll

\$NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

public interface IObjectSerialization<in T>

+ NetAF.Conversations

(NetAF.Conversations.html)

Type Parameters

+ NetAF.Conversations.

Name	Description
Instructions	The type of object that this serialization represents.

T(NetAF.Conversations.Instruct

+ NetAF.Extensions

(NetAF.Extensions.html)

Methods

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Restore(T)

(NetAF.Logic.html)

Restore an instance from this serialization.

+ NetAF.Logic.Callbacks

Declaration

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Parameters

+ NetAF.Logic.Modes

Type: (NetAF.Logic.Modes.html)

Name

Description

+ NetAF.Persistence

obj

The obj to restore.

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frame

Builders.Console

Interface IRestoreFromObject Serialization<T>

▼ Filter by title

Represents any object that can restore from an IObjectSerialization.

(NetAF.Commands.RegionMap)

Namespace: NetAF (NetAF.html).Serialization (NetAF.Serialization.html)

+ **NetAF.Commands.Scene**

Assembly: NetAF.dll

(NetAF.Commands.Scene.html)

Syntax

+ **NetAF.Conversations**

(NetAF.Conversations.html)

+ **NetAF.Conversations.**

Type Instructions

(NetAF.Conversations.Instruct

Name Description

+ **NetAF.Extensions**

The type of serialization that this object restores from.

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

Methods

+ **NetAF.Logic**

(NetAF.Logic.html)

RestoreFrom(T)

+ **NetAF.Logic.Callbacks**

Restore this object from a serialization.

(NetAF.Logic.Callbacks.html)

Declaration

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

void RestoreFrom(T serialization)

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

Parameters

+ **NetAF.Persistence**

(NetAF.Persistence.html)

T serialization

Description

The serialization to restore from.

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

+ **NetAF.Rendering**

(NetAF.Rendering.html)

+ **NetAF.Rendering.Frame**

Builders

(NetAF.Rendering.FrameBuilder.html)

+ **NetAF.Rendering.Frame**

Builders.Console

Namespace NetAF.Serialization.Assets

Classes

Filter by title

INSTRUCTIONS

AttributeManagerSerialization

(NetAF.Serialization.Assets.AttributeManagerSerialization.html)

+ NetAF.Extensions

Represents a serialization of an AttributeManager.
(NetAF.Extensions.html)

AttributeSerialization

(NetAF.Serialization.Assets.AttributeSerialization.html)

(NetAF.Interpretation.html)

Represents a serialization of an Attribute.

+ NetAF.Logic

(NetAF.Logic.html)

CharacterSerialization

(NetAF.Serialization.Assets.CharacterSerialization.html)

+ NetAF.Logic.Callbacks

Represents a serialization of a Character.
(NetAF.Logic.Callbacks.html)

ConversationSerialization

(NetAF.Serialization.Assets.ConversationSerialization.html)

(NetAF.Logic.Configuration.html)

Represents a serialization of a Conversation.

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

ExaminableSerialization

(NetAF.Serialization.Assets.ExaminableSerialization.html)

+ NetAF.Persistence

Represents a serialization of an Examinable.
(NetAF.Persistence.html)

+ NetAF.Persistence.Json

ExitSerialization

(NetAF.Serialization.Assets.ExitSerialization.html)

(NetAF.Persistence.Json.html)

Represents a serialization of an Exit.

+ NetAF.Rendering

(NetAF.Rendering.html)

ItemSerialization

(NetAF.Serialization.Assets.ItemSerialization.html)

+ NetAF.Rendering.Frame

Represents a serialization of an Item.

Builders

(NetAF.Rendering.FrameBuilder)

NonPlayableCharacterSerialization

(NetAF.Rendering.Frame)

(NetAF.Serialization.Assets.NonPlayableCharacterSerialization.html)

Builders

Represents a serialization of a NonPlayableCharacter.

(NetAF.Rendering.FrameBuilder)

+ NetAF.Rendering.Frames

OverworldSerialization

(NetAF.Rendering.Frames.html)

Represents a serialization of an Overworld.

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

PlayableCharacterLocationSerialization

(NetAF.Serialization.Assets.PlayableCharacterLocationSerialization.html)

(NetAF.Serialization.html)

Represents a serialization of a PlayableCharacterLocation.

RegionSerialization (NetAF.Serialization.Assets.RegionSerialization.html)

Represents a serialization of a Region.

▼

RoomSerialization (NetAF.Serialization.Assets.RoomSerialization.html)

(NetAF.Conversations.Instruction)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilders.html)

+ NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilders.Console.html)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Class AttributeManagerSerialization

Represents a serialization of an AttributeManager.

Filter by title

Inheritance

(NetAF Conversations.Instruction.html)

↳ [Object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ AttributeManagerSerialization

+ NetAF.Extensions

Implements

(NetAF.Extensions.html)

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html)<AttributeManager

(NetAF.Assets.Attributes.AttributeManager.html)>

(NetAF.Interpretation.html)

Inherited Members

+ NetAF.Logic

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

(NetAF.Logic.html)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

(NetAF.Logic.Callbacks.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

(NetAF.Logic.Configuration.html)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAF.Logic.Modes

Namespace: NetAF.html.[Serialization](https://NetAF.Serialization.html).[Assets](https://NetAF.Serialization.Assets.html) (NetAF.Serialization.Assets.html)

(NetAF.Logic.Modes.html)

Assembly: NetAF.dll

Syntax

(NetAF.Persistence.html)

public sealed class AttributeManagerSerialization : IObjectSerialization<AttributeManager>

+ NetAF.Persistence.Json

↳ [Hagenaars](#)

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

Constructors

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

AttributeManagerSerialization(AttributeManager)

(NetAF.Rendering.FrameBuilder.html)

Represents a serialization of an AttributeManager.

+ NetAF.Rendering.Frame

Declaration

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

public AttributeManagerSerialization(AttributeManager attributeManager)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

Parameters

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

AttributeManager

(NetAF.Assets.Attributes.AttributeManager.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

AttributeManager

(NetAF.Assets.Attributes.AttributeManager.html)

Assembly: NetAF.dll

Namespace: NetAF.html.[Serialization](https://NetAF.Serialization.html).[Assets](https://NetAF.Serialization.Assets.html) (NetAF.Serialization.Assets.html)

Assembly: NetAF.dll

Version: NetAF.html 1.0.0.0

File: NetAF.dll

Location: NetAF.dll

Path: NetAF.dll

Region: NetAF.dll

Properties

Values

Get or set the values.

Declaration
INSTRUCTIONS

(NetAF.Conversations.Instruct)

```
public Dictionary<AttributeSerialization, int> Values { get; set; }
```

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Dictionary (<https://learn.microsoft.com/dotnet/api/system.collections.generic.dictionary-2>)<

+ NetAF.Logic

(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Methods

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Restore

(NetAF.Logic.Modes.html)

Restore an instance from this serialization.

+ NetAF.Persistence

Declaration

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Parameters

+ NetAF.Rendering

Type

(NetAF.Rendering.html)

AttributeManager

+ NetAF.Rendering.Frame

(NetAF.Assets.Attributes.AttributeManager.html)

Builders

(NetAF.Rendering.FrameBuilder)

Implements

NetAF.Rendering.Frame

Builders.Console

IObjectSerialization < T > ([NetAF.Serialization.IObjectSerialization-1.html](#))

(NetAF.Rendering.FrameBuilder)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Description

Description

Description

Description

Properties

Description

Get or set the description.

Declaration
INSTRUCTIONS

([NetAF.Conversations.Instruct](#))

```
public string Description { get; set; }
```

+ NetAF.Extensions

([NetAF.Extensions.html](#))

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

string (<https://learn.microsoft.com/dotnet/api/system.string>)

Description

+ NetAF.Logic

([NetAF.Logic.html](#))

Maximum

+ NetAF.Logic.Callbacks

([NetAF.Logic.Callbacks.html](#))

Get or set the maximum.

Declaration
INSTRUCTIONS

([NetAF.Logic.Configuration.html](#))

```
public int Maximum { get; set; }
```

+ NetAF.Logic.Modes

([NetAF.Logic.Modes.html](#))

Property Value

+ NetAF.Persistence

Type

([NetAF.Persistence.html](#))

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

Description

+ NetAF.Persistence.Json

([NetAF.Persistence.Json.html](#))

Minimum

([NetAF.Rendering.html](#))

Get or set the minimum.

+ NetAF.Rendering.Frame

Declaration
INSTRUCTIONS

Builders

([NetAF.Rendering.FrameBuilder](#))

```
public int Minimum { get; set; }
```

+ NetAF.Rendering.Frame

Builders
Console

([NetAF.Rendering.FrameBuilder](#))

Type

+ NetAF.Rendering.Frames

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

([NetAF.Rendering.Frames.html](#))

Description

+ NetAF.Rendering.Presenters

([NetAF.Rendering.Presenters.html](#))

+ NetAF.Serialization

Get or set the name.

Declaration

```
public string Name { get; set; }
```

Property Value

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Conversations.Instruct	

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Methods

+ NetAF.Interpretation

[\(NetAF.Interpretation.html\)](#)

Restore(Attribute)

+ NetAF.Logic

[\(NetAF.Logic.html\)](#)

Restore an instance from this serialization.

Delegates

[\(NetAF.Logic.Callbacks.html\)](#)

public void Restore(Attribute attribute)

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

Parameters

+ NetAF.Logic.Modes

Type

[\(NetAF.Logic.Modes.html\)](#)

Attribute

[\(NetAF.Assets.Attributes.Attribute.html\)](#)

+ NetAF.Persistence

[\(NetAF.Persistence.html\)](#)

Implements

+ NetAF.Persistence.Json

[\(NetAF.Persistence.Json.html\)](#)

IObjectSerialization<T>

[\(NetAF.Serialization.IObjectSerialization-1.html\)](#)

+ NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

Builders

[\(NetAF.Rendering.FrameBuilder.html\)](#)

+ NetAF.Rendering.Frame

Builders.Console

[\(NetAF.Rendering.FrameBuilderConsole.html\)](#)

+ NetAF.Rendering.Frames

[\(NetAF.Rendering.Frames.html\)](#)

+ NetAF.Rendering.Presenters

[\(NetAF.Rendering.Presenters.html\)](#)

+ NetAF.Serialization

[\(NetAF.Serialization.html\)](#)

Class CharacterSerialization

Represents a serialization of a Character.

Filter by title

Inheritance

(NetAF Conversations.Instruction)

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization (NetAF.Serialization.Assets.ExaminableSerialization.html)

+ NetAF.Extensions

↳ CharacterSerialization

(NetAF.Extensions.html)

↳ NonPlayableCharacterSerialization (NetAF.Serialization.Assets.NonPlayableCharacterSerialization.html)

+ NetAF.Interpretation

Implements

(NetAF.Interpretation.html)

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < IExaminable

(NetAF_Assets.IExaminable.html) >

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < Character

(NetAF.Logic.html)

(NetAF_Assets.Characters.Character.html) >

+ NetAF.Logic.Callbacks

Inherited Members

(NetAF.Logic.Callbacks.html)

ExaminableSerialization.Identifier

↳ NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Identifier

(NetAF.Logic.Configuration.html)

ExaminableSerialization.IsPlayerVisible

↳ NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_IsPlayerVisible

(NetAF.Logic.Modes.html)

ExaminableSerialization.AttributeManager

↳ NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_AttributeManager

(NetAF.Persistence.html)

ExaminableSerialization.Commands

↳ NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Commands

(NetAF.Persistence.Json.html)

ExaminableSerialization.Restore(IExaminable)

↳ NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Restore_NetAF_Assets_IExaminable_

+ NetAF.Rendering.Frame

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-object)))

Builders

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals\(system-object-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-object-equals(system-object-object-system-object)))

+ NetAF.Rendering.Frame

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ NetAF.Rendering.Frames

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF.Rendering.Frames.html)

Namespace: NetAF ([NetAF.html](#)).Serialization (NetAF.Serialization.html).Assets (NetAF.Serialization.Assets.html)

Assembly: NetAF.dll

+ NetAF.Rendering.Presenters

Syntax ([NetAF.Rendering.Presenters.html](#))

+ NetAF.Serialization

```
public class CharacterSerialization : ExaminableSerialization, IObjectSerialization<IExaminable>, IObjectSerialization<Character>
```

Constructors

INSTRUCTIONS

(NetAF.Conversations.Instruction) CharacterSerialization(Character)

+ NetAF.Extensions

Represents a serialization of a Character.
[\(NetAF.Extensions.html\)](#)

Declaration

+ NetAF.Interpretation

(NetAF.Interpretation.html) CharacterSerialization(Character character)

+ NetAF.Logic

(NetAF.Logic.html)

+ Type NetAF.Logic.Callbacks

Name	Description
character	The character to serialize.

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Properties

NetAF.Logic.Modes (NetAF.Logic.Modes.html)

+ ISAME

(NetAF.Persistence.html)

Get or set if the character is alive.

+ NetAF.Persistence.Json

Declaration

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html) CharacterSerialization.isLive { get; set; }

NetAF.Rendering.Frame (NetAF.Rendering.Frame.html)

Builders

(NetAF.Rendering.FrameBuilder.html)

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

Description

+ NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

Items

+ NetAF.Rendering.Frames

Get or set the item serializations.

(NetAF.Rendering.Frames.html)

Declaration

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html) CharacterSerialization.Items { get; set; }

+ NetAF.Serialization

(NetAF.Serialization.html)

Type	Description
ItemSerialization (NetAF.Serialization.Assets.ItemSerialization.html)[]	

▼

Methods

(NetAF.Conversations.Instruct)

+ NetAF.Extensions

Restore(Character)
(NetAF.Extensions.html)

Restore an instance from this serialization.

+ NetAF.Interpretation

Declaration
(NetAF.Interpretation.html)

+ NetAF.Logic

public void Restore(Character character)
(NetAF.Logic.html)

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Type	Name	Description
Character (NetAF.Assets.Characters.Character.html)	character	The character to restore.

+ NetAF.Logic.Modes

Implements
(NetAF.Logic.Modes.html)

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ NetAF.Persistence

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)
(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Class ConversationSerialization

Represents a serialization of a Conversation.

Filter by title

Inheritance

(NetAF Conversations.Instruction)

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ConversationSerialization

+ NetAF.Extensions

Implements

(NetAF.Extensions.html)

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html)<Conversation

(NetAF.Conversations.Conversation.html)>

(NetAF.Interpretation.html)

Inherited Members

+ NetAF.Logic

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

(NetAF.Logic.html)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

(NetAF.Logic.Callbacks.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

(NetAF.Logic.Configuration.html)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAF.Logic.Modes

Namespace: NetAF (NetAF.html).Serialization (NetAF.Serialization.html).Assets (NetAF.Serialization.Assets.html)

(NetAF.Logic.Modes.html)

Assembly: NetAF.dll

Syntax

(NetAF.Persistence.html)

public sealed class ConversationSerialization : IObjectSerialization<Conversation>

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Constructors

(NetAF.Rendering.html)

CONVERSATIONSERIALIZATION(Conversation)

Builders

Represents a serialization of a Conversation.

(NetAF.Rendering.FrameBuilder)

Declaration

+ NetAF.Rendering.Frame

Builders.Console

public ConversationSerialization(Conversation conversation)

(NetAF.Rendering.FrameBuilder)

+ NetAF.Rendering.Frames

Parameters

(NetAF.Rendering.Frames.html)

Type

+ NetAF.Rendering.Presenters

Conversation (NetAF.Conversations.Conversation.html)

(NetAF.Rendering.Presenters)

+ NetAF.Serialization

INetAF (NetAF.html)

Fields

NoCurrentParagraph

Get the value for no current paragraph.

Declaration
INSTRUCTIONS

([NetAF.Conversations.Instruct](#))

```
public const int NoCurrentParagraph = -1
```

+ NetAF.Extensions

([NetAF.Extensions.html](#))

+ [NetAF.Interpretation](#)

([NetAF.Interpretation.html](#))

```
int (https://learn.microsoft.com/dotnet/api/system.int32)
```

+ NetAF.Logic

([NetAF.Logic.html](#))

Properties

NetAF.Logic.Callbacks

([NetAF.Logic.Callbacks.html](#))

+ NetAF.Logic.Configuration

CurrentParagraph

([NetAF.Logic.Configuration.html](#))

Get or set if the index of the current paragraph.

+ NetAF.Logic.Modes

Declaration

([NetAF.Logic.Modes.html](#))

+ NetAF.Persistence

```
public int CurrentParagraph { get; set; }
```

([NetAF.Persistence.html](#))

+ [NetAF.Persistence.Json](#)

Properties

Type

([NetAF.Persistence.Json.html](#))

+ NetAF.Rendering

int (<https://learn.microsoft.com/dotnet/api/system.int32>)

([NetAF.Rendering.html](#))

+ NetAF.Rendering.Frame

Builders

Methods

([NetAF.Rendering.FrameBuilder.html](#))

+ NetAF.Rendering.Frame

Restore(Conversation)

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

Restore an instance from this serialization.

+ NetAF.Rendering.Frames

Declaration

([NetAF.Rendering.Frames.html](#))

+ public void Restore(Conversation conversation)

+ NetAF.Rendering.Presenters

([NetAF.Rendering.Presenters.html](#))

Parameters

+ NetAF.Serialization

([NetAF.Serialization.html](#))

Description

Description

Type	Name	Description
Conversation (NetAF.Conversations.Conversation.html)	<i>conversation</i>	The conversation to restore.

Implements

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

(NetAF.Conversations.Instruct

- + NetAF.Extensions
(NetAF.Extensions.html)
- + NetAF.Interpretation
(NetAF.Interpretation.html)
- + NetAF.Logic
(NetAF.Logic.html)
- + NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)
- + NetAF.Logic.Configuration
(NetAF.Logic.Configuration.html)
- + NetAF.Logic.Modes
(NetAF.Logic.Modes.html)
- + NetAF.Persistence
(NetAF.Persistence.html)
- + NetAF.Persistence.Json
(NetAF.Persistence.Json.html)
- + NetAF.Rendering
(NetAF.Rendering.html)
- + NetAF.Rendering.Frame
Builders
(NetAF.Rendering.FrameBuilders.html)
- + NetAF.Rendering.Frame
Builders.Console
(NetAF.Rendering.FrameBuilders.Console.html)
- + NetAF.Rendering.Frames
(NetAF.Rendering.Frames.html)
- + NetAF.Rendering.Presenters
(NetAF.Rendering.Presenters.html)
- + NetAF.Serialization
(NetAF.Serialization.html)

Class ExaminableSerialization

Represents a serialization of an Examinable.

Filter by title

Inheritance

(NetAF Conversations.Instruction)

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization

↳ CharacterSerialization ([NetAF.Serialization.Assets.CharacterSerialization.html](#))

↳ ExitSerialization ([NetAF.Serialization.Assets.ExitSerialization.html](#))

+ NetAF.Extensions

↳ ItemSerialization ([NetAF.Serialization.Assets.ItemSerialization.html](#))

↳ OverworldSerialization ([NetAF.Serialization.Assets.OverworldSerialization.html](#))

↳ RegionSerialization ([NetAF.Serialization.Assets.RegionSerialization.html](#))

+ NetAF.Interpretation

↳ RoomSerialization ([NetAF.Serialization.Assets.RoomSerialization.html](#))

+ NetAF.Logic

↳ Localization ([NetAF.Localization.html](#))

Implements

IObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<IExaminable

([NetAF.Assets.IExaminable.html](#))>

([NetAF.Logic.Callbacks.html](#))

Inherited Members

+ NetAF.Logic.Configuration

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-object)))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.MemberwiseClone() (<https://learn.microsoft.com/dotnet/api/system.object.memberwiseclone>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ NetAF.Persistence.Json

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

([NetAF.Persistence.Json.html](#))

Namespace: NetAF ([NetAF.html](#)).Serialization ([NetAF.Serialization.html](#)).Assets ([NetAF.Serialization.Assets.html](#))

Assembly: NetAF

(NetAF.Rendering.html)

Syntax

Assembly: NetAF

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

public class ExaminableSerialization : IObjectSerialization<IExaminable>

Builders

([NetAF.Rendering.FrameBuilder.html](#))

+ NetAF.Rendering.Frame

Builders.Console

([NetAF.Rendering.FrameBuilder.html](#))

ExaminableSerialization(IExaminable)

+ NetAF.Rendering.Frames

ReSharper.Fody.Examinable

Properties

NetAF.Rendering.Presenters

([NetAF.Rendering.Presenters.html](#))

+ NetAF.Serialization

([NetAF.Serialization.html](#))

```
public ExaminableSerialization(IExaminable examinable)
```

Parameters

Type	Name	Description
IExaminable (NetAF.Assets.IExaminable.html) Instructions	<i>examinable</i>	The examinable.

(NetAF.Conversations.Instruct)

+ NetAF.Extensions

Properties

+ NetAF.Interpretation

AttributeManager

+ NetAF.Logic

Get or set the attribute manager serializations.

(NetAF.Logic.html)

Declaration

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

Property Value

(NetAF.Logic.Configuration.html)

+ Type

NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

Commands

+ NetAF.Persistence.Json

Get or set the command serializations.

(NetAF.Persistence.Json.html)

Declaration

NetAF.Rendering

(NetAF.Rendering.html)

```
public CustomCommandSerialization[] Commands { get; set; }
```

+ NetAF.Rendering.Frame

Builders

Property Value

(NetAF.Rendering.FrameBuilder.html)

Type

+ NetAF.Rendering.Frame

CustomCommandSerialization (NetAF.Serialization.CustomCommandSerialization.html)[]

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

Get or set the identifier.

+ NetAF.Rendering.Presenters

Declaration

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Description

Description

```
public string Identifier { get; set; }
```

Property Value

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string) Instructions	

(NetAF.Conversations.Instruct

+ NetAF.Extensions

IsPlayerVisible

(NetAF.Extensions.html)

Get or set if it is player visible.

+ NetAF.Interpretation

Declaration

(NetAF.Interpretation.html)

+ NetAF.Logic

```
public bool IsPlayerVisible { get; set; }
```

(NetAF.Logic.html)

Properties

NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Type

Type	Description

+ NetAF.Logic.Configuration

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

Methods

+ NetAF.Persistence

(NetAF.Persistence.html)

Restore(IExaminable)

+ NetAF.Persistence.Json

Restore an instance from this serialization.

(NetAF.Persistence.Json.html)

Declaration

NetAF.Rendering

(NetAF.Rendering.html)

```
public virtual void Restore(IExaminable examinable)
```

+ NetAF.Rendering.Frame

Builders

Parameters

(NetAF.Rendering.FrameBuilder)

Type

+ NetAF.Rendering.Frame

IExaminable ([NetAF.Assets.IExaminable.html](#))

Builders.Console

(NetAF.Rendering.FrameBuilder)

Implementation

NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

IObjectSerialization<T> ([NetAF.Serialization.IObjectSerialization-1.html](#))

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

▼

INSTRUCTIONS

(NetAF.Conversations.Instruct

- + NetAF.Extensions
(NetAF.Extensions.html)
- + NetAF.Interpretation
(NetAF.Interpretation.html)
- + NetAF.Logic
(NetAF.Logic.html)
- + NetAF.Logic.Callbacks
(NetAF.Logic.Callbacks.html)
- + NetAF.Logic.Configuration
(NetAF.Logic.Configuration.html)
- + NetAF.Logic.Modes
(NetAF.Logic.Modes.html)
- + NetAF.Persistence
(NetAF.Persistence.html)
- + NetAF.Persistence.Json
(NetAF.Persistence.Json.html)
- + NetAF.Rendering
(NetAF.Rendering.html)
- + NetAF.Rendering.Frame
Builders
(NetAF.Rendering.FrameBuilders.html)
- + NetAF.Rendering.Frame
Builders.Console
(NetAF.Rendering.FrameBuilders.Console.html)
- + NetAF.Rendering.Frames
(NetAF.Rendering.Frames.html)
- + NetAF.Rendering.Presenters
(NetAF.Rendering.Presenters.html)
- + NetAF.Serialization
(NetAF.Serialization.html)

Class ExitSerialization

Represents a serialization of an Exit.

 Filter by title

Inheritance

- | |
|--|
| ↳ Object (https://learn.microsoft.com/dotnet/api/system.object) |
| + NetAF.Extensions
(NetAF.Extensions.html) |
| Implements |
| + NetAF.Interpretation
IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html)<IExaminable
(NetAF.Assets.Examinable.html) |
| IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html)<Exit (NetAF.Assets.Locations.Exit.html)> |
| + NetAF.Logic
(NetAF.Logic.html) |
| Inherited Members |
| + NetAF.Logic.Callbacks
(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_IIdentifier)
(NetAF.Logic.Callbacks.html) |
| ExaminableSerialization.Identifier |
| + NetAF.Logic.Configuration
ISPlayerVisible
(NetAF.Logic.Configuration.html)
sPlayerVisible |
| + NetAF.Logic.Modes
AttributeManager
(NetAF.Logic.Models.html) |
| AttributeManager |
| + NetAF.Persistence
ExaminableSerialization.Commands
(NetAF.Persistence.html) |
| Commands |
| + NetAF.Persistence.Json
ExaminableSerialization.Restore(IExaminable)
(NetAF.Persistence.Json.html) |
| Restore(IExaminable) |
| + NetAF.Rendering
object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object))
(NetAF.Rendering.html) |
| object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)) |
| + NetAF.Rendering.FrameBuilders
object GetHashCode() (https://learn.microsoft.com/dotnet/api/system.object.gethashcode)
object.GetType() (https://learn.microsoft.com/dotnet/api/system.object.gettype) |
| + NetAF.Rendering.FrameBuilders.Console
object.Equals(object) (https://learn.microsoft.com/dotnet/api/system.object.referenceequals)
object.ToString() (https://learn.microsoft.com/dotnet/api/system.object.tostring) |
| + NetAF.Rendering.FrameBuilder (NetAF.Serialization.html).Assets (NetAF.Serialization.Assets.html) |
| Assembly: NetAF.dll |
| + NetAF.Rendering.Frames
(NetAF.Rendering.Frames.html) |
| Syntax |
| + NetAF.Rendering.Presenters
IObjectSerialization : ExaminableSerialization, IObjectSerialization
TAPresenter : IObjectSerialization<Exit>
(NetAF.Rendering.Presenters.html) |
| + NetAF.Serialization |

Constructors

ExitSerialization(Exit)

Represents a serialization of an Exit.

Declaration

INSTRUCTIONS

(NetAF.Conversations.Instruct

public ExitSerialization(Exit exit)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Exit (NetAF.Assets.Locations.Exit.html)

Name

Description

exit

The exit to serialize.

+ NetAF.Logic

(NetAF.Logic.html)

Properties

NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

IsLocked

(NetAF.Logic.Configuration.html)

Get or set if the exit is locked.

+ NetAF.Logic.Modes

Declaration

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

public bool IsLocked { get; set; }

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

Properties

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

bool (<https://team.microsoft.com/dotnet/api/system.boolean>)

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

Methods

(NetAF.Rendering.FrameBuilder)

+ NetAF.Rendering.Frame

Restore(Exit)

Builders.Console

(NetAF.Rendering.FrameBuilder)

Restore an instance from this serialization.

+ NetAF.Rendering.Frames

Declaration

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

Parameters

+ NetAF.Serialization

(NetAF.Serialization.html)

Type	Name	Description
Exit (NetAF.Assets.Locations.Exit.html)	exit	The exit to restore.

Implements

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)
IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)
(NetAF.Conversations.Instruct

- + NetAF.Extensions
[\(NetAF.Extensions.html\)](#)
- + NetAF.Interpretation
[\(NetAF.Interpretation.html\)](#)
- + NetAF.Logic
[\(NetAF.Logic.html\)](#)
- + NetAF.Logic.Callbacks
[\(NetAF.Logic.Callbacks.html\)](#)
- + NetAF.Logic.Configuration
[\(NetAF.Logic.Configuration.html\)](#)
- + NetAF.Logic.Modes
[\(NetAF.Logic.Modes.html\)](#)
- + NetAF.Persistence
[\(NetAF.Persistence.html\)](#)
- + NetAF.Persistence.Json
[\(NetAF.Persistence.Json.html\)](#)
- + NetAF.Rendering
[\(NetAF.Rendering.html\)](#)
- + NetAF.Rendering.Frame
Builders
[\(NetAF.Rendering.FrameBuilders.html\)](#)
- + NetAF.Rendering.Frame
Builders.Console
[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)
- + NetAF.Rendering.Frames
[\(NetAF.Rendering.Frames.html\)](#)
- + NetAF.Rendering.Presenters
[\(NetAF.Rendering.Presenters.html\)](#)
- + NetAF.Serialization
[\(NetAF.Serialization.html\)](#)

Class ItemSerialization

Represents a serialization of an Item.

Filter by title

Inheritance

(NetAF Conversations.Instruction)

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization (NetAF.Serialization.Assets.ExaminableSerialization.html)

+ NetAF.Extensions

↳ ItemSerialization

(NetAF.Extensions.html)

Implements

+ NetAF.Interpretation

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < IExaminable

(NetAF.Interpretation.html)

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < Item (NetAF.Assets.Item.html) >

+ NetAF.Logic

Inherited Members

(NetAF.Logic.html)

ExaminableSerialization Identifier

+ NetAF.Logic.Callbacks

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_IIdentifier)

ExaminableSerialization IsPlayerVisible

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_ISPlayerVisible)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

ExaminableSerialization AttributeManager

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_AttributeManager)

+ NetAF.Persistence

ExaminableSerialization Commands

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Commands)

+ NetAF.Persistence.Json

ExaminableSerialization Restore(IExaminable)

(NetAF.Persistence.Json.html)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Restore_NetAF_Assets_IExaminable_)

+ NetAF.Rendering

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ NetAF.Rendering.Frame

(NetAF.Rendering.Frame.html)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ NetAF.Rendering.Frame

(NetAF.Rendering.Frame.html)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ NetAF.Rendering.Frame

(NetAF.Rendering.Frame.html)

Name (NetAF.Rendering.FrameBuilder) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>) (NetAF.Serialization.html).Assets (NetAF.Serialization.Assets.html)

Assembly: NetAF.dll

+ NetAF.Rendering.Frames

Syntax

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

object.Equals(ItemSerialization : ExaminableSerialization, IObjectSerialization<Item>) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Constructors

ItemSerialization(Item)

Represents a serialization of an Item.

Declaration
INSTRUCTIONS

(NetAF.Conversations.Instruct)
public ItemSerialization(Item item)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)
Item (NetAF.Assets.Item.html)

Name

Description

item

The item to serialize.

+ NetAF.Logic

(NetAF.Logic.html)

Methods

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

Restore(item)

(NetAF.Logic.Configuration.html)

Restore an instance from this serialization.

+ NetAF.Logic.Modes

Declaration
(NetAF.Logic.Modes.html)

+ NetAF.Persistence

public void Restore(Item item)
(NetAF.Persistence.html)

+ NetAF.Persistence.Json

Parameters
Type (NetAF.Persistence.Json.html)

Name

Description

item

The item to restore.

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Class NonPlayableCharacterSerialization

Represents a serialization of a NonPlayableCharacter.

Filter by title

Inheritance

(NetAF Conversations Instruct)

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization (NetAF.Serialization.Assets.ExaminableSerialization.html)

+ NetAF.Extensions

↳ CharacterSerialization (NetAF.Serialization.Assets.CharacterSerialization.html)

(NetAF.Extensions.html)

↳ NonPlayableCharacterSerialization

+ NetAF Interpretation

Implements

(NetAF Interpretation.html)

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < IExaminable

(NetAF Assets.IExaminable.html) >

+ NetAF Logic

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < Character

(NetAF Logic.html)

(NetAF Assets.Characters.Character.html) >

+ NetAF Logic Callbacks

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < NonPlayableCharacter

(NetAF Assets.Characters.NonPlayableCharacter.html) >

(NetAF Logic Callbacks.html)

Inherited Members

+ NetAF Logic Configuration

CharacterSerialization.Items

(NetAF Logic Configuration.html)

(NetAF.Serialization.Assets.CharacterSerialization.html#NetAF_Serialization_Assets_CharacterSerialization_Items)

+ NetAF Logic Modes

CharacterSerialization.Restore (Character)

(NetAF Logic Modes.html)

(NetAF.Serialization.Assets.CharacterSerialization.html#NetAF_Serialization_Assets_CharacterSerialization_Restore)

+ NetAF Persistence

CharacterSerialization.Restore (Character)

(NetAF.Serialization.Assets.CharacterSerialization.html#NetAF_Serialization_Assets_CharacterSerialization_Restore_NetAF_Assets_Characters_Character_)

(NetAF Persistence Json.html)

ExaminableSerialization.Identifier

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Identifer)

+ NetAF Rendering

(NetAF Rendering.html)

ExaminableSerialization.IsPlayerVisible

(NetAF.Rendering.Attributes.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_IsPlayerVisible)

Builders

(NetAF Rendering FrameBuilder)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_AttributeManager)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Commands)

At NetAF Rendering Frame

ExaminableSerialization.Commands

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Commands)

ExaminableRendering Frames

(ExaminableRenderingFrames)(Examinable)

(NetAF.Rendering.Attributes.ExaminableRenderingFrames.html#NetAF_Serialization_Assets_ExaminableSerialization_ExaminableRenderingFrames)

Restore_NetAF_Assets_IExaminable_()

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

(NetAF Rendering Presenters.html)

+ NetAF Serialization

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))
object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)
object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)
object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)
object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

Namespace: NetAF (NetAF.html).Serialization ([NetAF.Serialization.html](#)).Assets ([NetAF.Serialization.Assets.html](#))

Assembly: NetAF.dll

(NetAF.Conversations.Instruct

Syntax

+ NetAF.Extensions

([NetAF.Extensions.html](#)) PlayableCharacterSerialization : CharacterSerialization, IObjectSerialization<IExaminable>, IObjectSerialization<Character>, IObjectSerialization<NonPlayableCharacter>

+ NetAF.Interpretation

([NetAF.Interpretation.html](#))

+ NetAF.Logic

Constructors

([NetAF.Logic.html](#))

+ NetAF.Logic.Callbacks

NonPlayableCharacterSerialization(NonPlayableCharacter)

+ NetAF.Logic.Configuration

Represents the configuration of a PlayableCharacter.

([NetAF.Logic.Configuration.html](#))

+ NetAF.Logic.Modes

([NetAF.Logic.Modes.html](#)) NonPlayableCharacterSerialization(NonPlayableCharacter character)

+ NetAF.Persistence

Parameters

([NetAF.Persistence.html](#))

Type

+ NetAF.Persistence.Json

NonPlayableCharacter

([NetAF.Persistence.Json.html](#))

([NetAF.Assets.Characters.NonPlayableCharacter.html](#))

+ NetAF.Rendering

([NetAF.Rendering.html](#))

+ NetAF.Rendering.Frame

Properties

([NetAF.Rendering.FrameBuilder.html](#))

Conversation

([NetAF.Rendering.Frame](#))

Builders

Get or set the conversation serialization.

([NetAF.Rendering.FrameBuilder.html](#))

Declaration

+ NetAF.Rendering.Frames

([NetAF.Rendering.Frames.html](#)) public ConversationSerialization Conversation { get; set; }

+ NetAF.Rendering.Presenters

Properties

([NetAF.Rendering.Presenters.html](#))

+ NetAF.Serialization

([NetAF.Serialization.html](#))

Type	Name	Description
NonPlayableCharacter	character	The character to serialize.

Type	Description
ConversationSerialization (NetAF.Serialization.Assets.ConversationSerialization.html)	

Methods

↳ [Instructions](#)

+ **Restore(NonPlayableCharacter)**
(NetAF.Extensions.html)

Restores a character from serialization.

↳ [NetAF Interpretation](#)

+ **(NetAF.Interpretation.html)**

public void Restore(NonPlayableCharacter character)

+ **NetAF.Logic**

+ **(NetAF.Logic.html)**

Parameters

+ **NetAF.Logic.Callbacks**

Type
(NetAF.Logic.Callbacks.html)

NonPlayableCharacter

+ **NetAF.Logic.Configuration**

(NetAF.Assets.Characters.NonPlayableCharacter.html)

+ **(NetAF.Logic.Configuration.html)**

+ **NetAF.Logic.Modes**

↳ [Implements](#)

+ **(NetAF.Logic.Modes.html)**

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ **NetAF.Persistence**

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ **(NetAF.Persistence.html)**

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ **NetAF.Persistence.Json**

+ **(NetAF.Persistence.Json.html)**

+ **NetAF.Rendering**

+ **(NetAF.Rendering.html)**

+ **NetAF.Rendering.Frame**

Builders

+ **(NetAF.Rendering.FrameBuilder.html)**

+ **NetAF.Rendering.Frame**

Builders.Console

+ **(NetAF.Rendering.FrameBuilderConsole.html)**

+ **NetAF.Rendering.Frames**

+ **(NetAF.Rendering.Frames.html)**

+ **NetAF.Rendering.Presenters**

+ **(NetAF.Rendering.Presenters.html)**

+ **NetAF.Serialization**

+ **(NetAF.Serialization.html)**

Name	Description
character	The character to restore.

Class OverworldSerialization

Represents a serialization of an Overworld.

Filter by title

Inheritance

+ **NetAF.Conversations.Instruction**

↳ [Object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization ([NetAF.Serialization.Assets.ExaminableSerialization.html](#))

+ **NetAF.Extensions**

↳ OverworldSerialization

([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**

IObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<IExaminable
([NetAF_Assets_Examinable.html](#))

IObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<Overworld

+ **NetAF.Logic**

([NetAF_Assets_Locations_Overworld.html](#))>

([NetAF.Logic.html](#))

Inherited Members

+ **NetAF.Logic.Callbacks**

ExaminableSerialization.Identifier

([NetAF.Logic.Callbacks.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_Identifi

+ **NetAF.Logic.Configuration**

ExaminableSerialization.IsPlayerVisible

([NetAF.Logic.Configuration.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_I

+ **NetAF.Logic.Modes**

ExaminableSerialization.AttributeManager

([NetAF.Logic.Modes.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_A

+ **NetAF.Persistence**

ExaminableSerialization.Commands

([NetAF.Persistence.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_C

+ **NetAF.Persistence.Json**

([NetAF.Persistence.Json.html](#))

ExaminableSerialization.Restore(IExaminable)

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_R

+ **NetAF.Rendering**

Restore([NetAF_Assets_IExaminable](#))

([NetAF.Rendering.html](#))

object.Equals(object) ([### + **NetAF.Rendering.Frame**](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-</p></div><div data-bbox=)

object.Equals(object, object) ([object.equals\(system-object-system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-</p></div><div data-bbox=)

([NetAF.Rendering.FrameBuilder.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

+ **NetAF.Rendering.FrameBuilders**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

([NetAF.Rendering.FrameBuilderConsole.html](#))

Namespace: NetAF ([NetAF.html](#)).Serialization ([NetAF.Serialization.html](#)).Assets ([NetAF.Serialization.Assets.html](#))

+ **NetAF.Rendering.Frames**

Assembly: NetAF.dll

([NetAF.Rendering.Frames.html](#))

Syntax

+ **NetAF.Rendering.Presenters**

([NetAF.Rendering.Presenters.html](#))

IDLSerialization : ExaminableSerialization, IObjectSeriali

zation<IExaminable>, IObjectSerializati<Overworld>

+ **NetAF.Serialization**

([NetAF.Serialization.html](#))

Constructors

OverworldSerialization(Overworld)

Represents a serialization of an Overworld.

Declaration

INSTRUCTIONS

(NetAF.Conversations.Instruct

public OverworldSerialization(Overworld overworld)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ Type: NetAF.Interpretation

(NetAF.Interpretation.html)

Overworld (NetAF.Assets.Locations.Overworld.html)

Name

Description

The overworld to serialize.

+ NetAF.Logic

(NetAF.Logic.html)

Properties

NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

CurrentRegion

(NetAF.Logic.Configuration.html)

Get or set the current region.

+ NetAF.Logic.Modes

Declaration

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

public string CurrentRegion { get; set; }

(NetAF.Persistence.html)

+ Property: NetAF.Persistence.Json

Type **(NetAF.Persistence.Json.html)**

Description

+ NetAF.Rendering

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Regions

(NetAF.Rendering.FrameBuilder

Get or set the region serializations.

+ NetAF.Rendering.Frame

Declaration

Builders.Console

(NetAF.Rendering.FrameBuilder

public RegionSerialization[] Regions { get; set; }

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ Type: NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

RegionSerialization (NetAF.Serialization.Assets.RegionSerialization.html)[]

+ NetAF.Serialization

(NetAF.Serialization.html)

Methods

Restore(Overworld)

Restore an instance from this serialization.

Declaration
INSTRUCTIONS

(NetAF.Conversations.Instruct)
public void Restore(Overworld overworld)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Overworld (NetAF.Assets.Locations.Overworld.html)

Name

Description

overworld The overworld to restore.

+ NetAF.Logic

(NetAF.Logic.html)

Implements

+ NetAF.Logic.Callbacks

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frame

Builders.Console

(NetAF.Rendering.FrameBuilderConsole.html)

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Class PlayableCharacterLocation Serialization

▼ Filter by title

Represents a serialization of a PlayableCharacterLocation.

[Instructions](#)

(NetAF.Conversations.Instruct

Inheritance

+ **NetAF.Extensions**

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

[\(NetAF.Extensions.html\)](#)

↳ PlayableCharacterLocationSerialization

+ **NetAF.Interpretation**

Implements

[\(NetAF.Interpretation.html\)](#)

IOObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<PlayableCharacterLocation

([NetAF.Logic.PlayableCharacterLocation.html](#))>

+ **NetAF.Logic**

Inherited Members

[\(NetAF.Logic.html\)](#)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

[\(NetAF.Logic.Callbacks.html\)](#)

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object>equals(system-object-system-object)))

+ **NetAF.Logic.Configuration**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

+ **NetAF.Logic.Modes**

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

[\(NetAF.Logic.Modes.html\)](#)

Namespace: NetAF ([NetAF.html](#)).Serialization ([NetAF.Serialization.html](#)).Assets ([NetAF.Serialization.Assets.html](#))

+ **NetAF.Persistence**

Assembly: [NetAF.dll](#)

[\(NetAF.Persistence.html\)](#)

Syntax

+ **NetAF.Persistence.Json**

[\(NetAF.Persistence.Json.html\)](#)

public sealed class PlayableCharacterLocationSerialization : IOObjectSerialization<PlayableCharacterLocation>

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

+ **NetAF.Rendering.Frame**

Builders

[\(NetAF.Rendering.FrameBuilder.html\)](#)

PlayableCharacterLocationSerialization(PlayableCharacterLocation)

+ **NetAF.Rendering.Frame**

Represents a serialization of a PlayableCharacterLocation.

[Builders.Console.html](#)

[\(NetAF.Rendering.FrameBuilder.html\)](#)

+ **NetAF.Rendering.Frames**

public PlayableCharacterLocationSerialization(PlayableCharacterLocation location)

[\(NetAF.Rendering.Frames.html\)](#)

+ **NetAF.Rendering.Presenters**

Parameters

[\(NetAF.Rendering.Presenters.html\)](#)

+ **NetAF.Serialization**

[\(NetAF.Serialization.html\)](#)

Type	Name	Description
PlayableCharacterLocation (NetAF.Logic.PlayableCharacterLocation.html)	<i>location</i>	The location to serialize.

Properties

Instructions

(NetAF.Conversations.Instruct)

PlayerIdentifier

+ NetAF.Extensions

Get (NetAF.Extensions.html)

PlayerID

NetAF.Interpretation

(NetAF.Interpretation.html)

public string PlayerIdentifier { get; set; }

+ NetAF.Logic

(NetAF.Logic.html)

Property Value

+ NetAF.Logic.Callbacks

Type

(NetAF.Logic.Callbacks.html)

string (<https://learn.microsoft.com/dotnet/api/system.string>)

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Description

RegionIdentifier

(NetAF.Logic.Modes.html)

Get or set the region identifier.

+ NetAF.Persistence

Declaration

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Property Value

+ NetAF.Rendering

(NetAF.Rendering.html)

Description

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder)

RoomIdentifier

+ NetAF.Rendering.Frame

Builders Console

(NetAF.Rendering.FrameBuilder)

Declaration

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

Property Value

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	

Methods

[Instructions](#)

([NetAF.Conversations.Instruct.html](#))
Restore(PlayableCharacterLocation)
+ [NetAF.Extensions](#)

[\(NetAF.Extensions.html\)](#) Serializes the specified object.

[Parameters](#)

([NetAF.Interpretation.html](#))

```
public void Restore(PlayableCharacterLocation location)
+ NetAF.Logic
```

([NetAF.Logic.html](#))

Parameters

+ [NetAF.Logic.Callbacks](#)

Type ([NetAF.Logic.Callbacks.html](#))

PlayableCharacterLocation ([NetAF.Logic.PlayableCharacterLocation.html](#))

+ [NetAF.Logic.Configuration](#)

([NetAF.Logic.Configuration.html](#))

[Implements](#)

+ [NetAF.Logic.Modes](#)

([NetAF.Logic.Modes.html](#))

IObjectSerialization<T> ([NetAF.Serialization.IObjectSerialization-1.html](#))

+ [NetAF.Persistence](#)

([NetAF.Persistence.html](#))

+ [NetAF.Persistence.Json](#)

([NetAF.Persistence.Json.html](#))

+ [NetAF.Rendering](#)

([NetAF.Rendering.html](#))

+ [NetAF.Rendering.Frame](#)

Builders

([NetAF.Rendering.FrameBuilder.html](#))

+ [NetAF.Rendering.Frame](#)

Builders.Console

([NetAF.Rendering.FrameBuilderConsole.html](#))

+ [NetAF.Rendering.Frames](#)

([NetAF.Rendering.Frames.html](#))

+ [NetAF.Rendering.Presenters](#)

([NetAF.Rendering.Presenters.html](#))

+ [NetAF.Serialization](#)

([NetAF.Serialization.html](#))

Type	Name	Description
	<i>location</i>	The attribute to restore.

Class RegionSerialization

Represents a serialization of a Region.

Filter by title

Inheritance

+ **NetAF.Conversations.Instruction**

↳ Object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization (NetAF.Serialization.Assets.ExaminableSerialization.html)

+ **NetAF.Extensions**

↳ RegionSerialization

(**NetAF.Extensions.html**)

Implements

+ **NetAF.Interpretation**

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < IExaminable

(**NetAF.Interpretation.html**)

IObjectSerialization (NetAF.Serialization.IObjectSerialization-1.html) < Region

+ **NetAF.Logic**

(NetAF.Assets.Locations.Region.html)

(**NetAF.Logic.html**)

Inherited Members

+ **NetAF.Logic.Callbacks**

ExaminableSerialization.Identifier

(**NetAF.Logic.Callbacks.html**)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Identifi

+ **NetAF.Logic.Configuration**

ExaminableSerialization.IsPlayerVisible

(**NetAF.Logic.Configuration.html**)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_IsPla

+ **NetAF.Logic.Modes**

ExaminableSerialization.AttributeManager

(**NetAF.Logic.Modes.html**)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Attribut

+ **NetAF.Persistence**

ExaminableSerialization.Commands

(**NetAF.Persistence.html**)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Commands

+ **NetAF.Persistence.Json**

ExaminableSerialization.Restore(IExaminable)

(NetAF.Serialization.Assets.ExaminableSerialization.html#NetAF_Serialization_Assets_ExaminableSerialization_Restore_

+ **NetAF.Rendering**

Restore(NetAF_Assets_IExaminable_)

object.Equals(object) ([### + **NetAF.Rendering.Frame**](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-</p></div><div data-bbox=)

object.Equals(object, object) ([object.equals\(system-object-system-object\)\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-</p></div><div data-bbox=)

(**NetAF.Rendering.FrameBuilder**)

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

+ **NetAF.Rendering.FrameBuilder**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(**NetAF.Rendering.FrameBuilder**)

Namespace: NetAF (NetAF.html).Serialization (NetAF.Serialization.html).Assets (NetAF.Serialization.Assets.html)

+ **NetAF.Rendering.Frames**

Assembly: NetAF.dll

(**NetAF.Rendering.Frames.html**)

Syntax

+ **NetAF.Rendering.Presenters**

(**NetAF.Rendering.Presenters**)
object : ExaminableSerialization, IObjectSerialization<IExaminable>, IObjectSerialization<Region>

+ **NetAF.Serialization**

(**NetAF.Serialization.html**)

Constructors

RegionSerialization(Region)

Represents a serialization of a Region.

Declaration

INSTRUCTIONS

(NetAF.Conversations.Instruct

public RegionSerialization(Region region)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

Region (NetAF.Assets.Locations.Region.html)

Name

Description

region

The region to serialize.

+ **NetAF.Logic**

(NetAF.Logic.html)

Properties

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

CurrentRoom

(NetAF.Logic.Configuration.html)

Get or set the current room.

+ **NetAF.Logic.Modes**

Declaration

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

public string CurrentRoom { get; set; }

(NetAF.Persistence.html)

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

Type

Description

+ **NetAF.Rendering**

string (<https://learn.microsoft.com/dotnet/api/system.string>)

(NetAF.Rendering.html)

+ **NetAF.Rendering.Frame**

IsVisibleWithoutDiscovery

(NetAF.Rendering.FrameBuilder.html)

Get or set if the region is visible without discovery.

+ **NetAF.Rendering.Frame**

Declaration

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

public bool IsVisibleWithoutDiscovery { get; set; }

+ **NetAF.Rendering.Frames**

(NetAF.Rendering.Frames.html)

Property Value

+ **NetAF.Rendering.Presenters**

(NetAF.Rendering.Presenters.html)

bool (<https://learn.microsoft.com/dotnet/api/system.boolean>)

+ **NetAF.Serialization**

(NetAF.Serialization.html)

Description

Rooms

Get or set the room serializations.

Declaration

```
public RoomSerialization[] Rooms { get; set; }
```

INSTRUCTIONS
Project: [NetAF](#) | [Conversations.Instruction](#)

Type	Description
(NetAF.Extensions.html) RoomSerialization[] (NetAF.Serialization.Assets.RoomSerialization.html)	

+ **NetAF.Interpretation**
[\(NetAF.Interpretation.html\)](#)

Methods
[\(NetAF.Logic.html\)](#)

Restore(Region)

[\(NetAF.Logic.Callbacks.html\)](#)
Restore an instance from this serialization.

+ **NetAF.Logic.Configuration**
Declaration
[\(NetAF.Logic.Configuration.html\)](#)

+ **NetAF.Logic.Modes**
Mode(Region region)
[\(NetAF.Logic.Modes.html\)](#)

Parameters

+ **NetAF.Persistence**

Type	Name	Description
(NetAF.Persistence.html) Region (NetAF.Serialization.Assets.Region.html)	region	The region to restore.

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)
IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

+ **NetAF.Rendering.Frame**
IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)

Builders
[\(NetAF.Rendering.FrameBuilder.html\)](#)

+ **NetAF.Rendering.Frame**
Builders.Console
[\(NetAF.Rendering.FrameBuilder.html\)](#)

+ **NetAF.Rendering.Frames**
[\(NetAF.Rendering.Frames.html\)](#)

+ **NetAF.Rendering.Presenters**
[\(NetAF.Rendering.Presenters.html\)](#)

+ **NetAF.Serialization**

Class RoomSerialization

Represents a serialization of a Room.

Filter by title

Inheritance

+ **NetAF.Conversations.Instruction**

↳ [Object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ ExaminableSerialization ([NetAF.Serialization.Assets.ExaminableSerialization.html](#))

+ **NetAF.Extensions**

↳ RoomSerialization

([NetAF.Extensions.html](#))

Implements

+ **NetAF.Interpretation**

IObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<IExaminable

([NetAF.Interpretation.html](#))

IObjectSerialization ([NetAF.Serialization.IObjectSerialization-1.html](#))<Room

+ **NetAF.Logic**

([NetAF.Assets.Locations.Room.html](#))>

([NetAF.Logic.html](#))

Inherited Members

+ **NetAF.Logic.Callbacks**

ExaminableSerialization.Identifier

([NetAF.Logic.Callbacks.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_Identifier)

+ **NetAF.Logic.Configuration**

ExaminableSerialization.IsPlayerVisible

([NetAF.Logic.Configuration.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_IsPlayerVisible)

+ **NetAF.Logic.Modes**

ExaminableSerialization.AttributeManager

([NetAF.Logic.Modes.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_AttributeManager)

+ **NetAF.Persistence**

ExaminableSerialization.Commands

([NetAF.Persistence.html](#))

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_Commands)

+ **NetAF.Persistence.Json**

ExaminableSerialization.Restore(IExaminable)

([NetAF.Serialization.Assets.ExaminableSerialization.html](#)#NetAF_Serialization_Assets_ExaminableSerialization_Restore_NetAF_Assets_IExaminable_)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Rendering**

Restore_NetAF_Assets_IExaminable_

([NetAF.Rendering.html](#))

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF.Rendering.Frame**

object.Equals(object, object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

([NetAF.Rendering.FrameBuilder.html](#))

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

+ **NetAF.Rendering.FrameBuilder**

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

([NetAF.Rendering.FrameBuilderConsole.html](#))

Namespace: NetAF ([NetAF.html](#)).Serialization ([NetAF.Serialization.html](#)).Assets ([NetAF.Serialization.Assets.html](#))

+ **NetAF.Rendering.Frames**

Assembly: NetAF.dll

([NetAF.Rendering.Frames.html](#))

Syntax

+ **NetAF.Rendering.Presenters**

([NetAF.Rendering.Presenters.html](#))
object.Equals(object, object) : ExaminableSerialization, IObjectSerialization
n<IExaminable>, IObjectSerialization<Room>

+ **NetAF.Serialization**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

Constructors

RoomSerialization(Room)

Represents a serialization of a Room.

Declaration

INSTRUCTIONS

(NetAF.Conversations.Instruct

public RoomSerialization(Room room)

+ NetAF.Extensions

(NetAF.Extensions.html)

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Room (NetAF.Assets.Locations.Room.html)

Name

Description

room

The room to serialize.

+ NetAF.Logic

(NetAF.Logic.html)

Properties

(NetAF.Logic.Callbacks.html)

+ NetAF.Logic.Configuration

Characters

(NetAF.Logic.Configuration.html)

Get or set the character serializations.

+ NetAF.Logic.Modes

Declaration

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

public NonPlayableCharacterSerialization[] Characters { get; set; }

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Type

Description

+ NetAF.Rendering

NonPlayableCharacterSerialization

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

Exits

+ NetAF.Rendering.Frame

Get or set the exit serializations.

Builders.Console

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frames

public ExitSerialization[] Exits { get; set; }

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

Property Value

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Type	Description
ExitSerialization (NetAF.Serialization.Assets.ExitSerialization.html)[]	

HasBeenVisited

Get or set if the room has been visited.

(NetAF.Conversations.Instruct)
Declaration

+ NetAF.Extensions

(NetAF.Extensions.html) `public bool HasVisited { get; set; }`

+ NetAF.Interpretation

Property Value
(NetAF.Interpretation.html)

+ NetAF.Logic

b (NetAF.Logic.html) `soft.com/dotnet/api/system.boolean`

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Items

+ NetAF.Logic.Configuration

Get or set the item serializations.

(NetAF.Logic.Configuration.html)

Declaration

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

`public ItemSerialization[] Items { get; set; }`

+ NetAF.Persistence

(NetAF.Persistence.html)

Property Value

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

`ItemSerialization (NetAF.Serialization.Assets.ItemSerialization.html)[]`

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

Restore(Room)

+ NetAF.Rendering.Frame

Builders Console

Rebuilds the state from this serialization.

(NetAF.Rendering.FrameBuilder.html)

Declaration

+ NetAF.Rendering.Frames

(NetAF.Rendering.Frames.html)

+ NetAF.Rendering.Presenters

Parameters

(NetAF.Rendering.Presenters.html)

+ NetAF.Serialization

(NetAF.Serialization.html)

Type	Name	Description
Room (NetAF.Assets.Locations.Room.html)	<i>room</i>	The room to restore.

Implements

IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)
IObjectSerialization<T> (NetAF.Serialization.IObjectSerialization-1.html)
(NetAF.Conversations.Instruct

- + NetAF.Extensions
[\(NetAF.Extensions.html\)](#)
- + NetAF.Interpretation
[\(NetAF.Interpretation.html\)](#)
- + NetAF.Logic
[\(NetAF.Logic.html\)](#)
- + NetAF.Logic.Callbacks
[\(NetAF.Logic.Callbacks.html\)](#)
- + NetAF.Logic.Configuration
[\(NetAF.Logic.Configuration.html\)](#)
- + NetAF.Logic.Modes
[\(NetAF.Logic.Modes.html\)](#)
- + NetAF.Persistence
[\(NetAF.Persistence.html\)](#)
- + NetAF.Persistence.Json
[\(NetAF.Persistence.Json.html\)](#)
- + NetAF.Rendering
[\(NetAF.Rendering.html\)](#)
- + NetAF.Rendering.Frame
Builders
[\(NetAF.Rendering.FrameBuilders.html\)](#)
- + NetAF.Rendering.Frame
Builders.Console
[\(NetAF.Rendering.FrameBuilders.Console.html\)](#)
- + NetAF.Rendering.Frames
[\(NetAF.Rendering.Frames.html\)](#)
- + NetAF.Rendering.Presenters
[\(NetAF.Rendering.Presenters.html\)](#)
- + NetAF.Serialization
[\(NetAF.Serialization.html\)](#)

Namespace NetAF.Utilities

Classes

Filter by title

Map

[OverworldMaker \(NetAF.Utilities.OverworldMaker.html\)](#)

(NetAF.Commands.RegionMap)

Provides a class for helping to make Regions.

+ [NetAF.Commands.Scene](#)

(NetAF.Commands.Scene.html)

[RegionMaker \(NetAF.Utilities.RegionMaker.html\)](#)

+ [NetAF.Commands](#) Provides a class for helping to make Regions.

(NetAF.Conversations.html)

[StringUtilities \(NetAF.Utilities.StringUtilities.html\)](#)

Instruct

Provides a helper class for string interpretation.

(NetAF.Conversations.Instruct

Interfaces

+ [NetAF.Extensions](#)

(NetAF.Extensions.html)

[IAssetTemplate<T> \(NetAF.Utilities.IAssetTemplate-1.html\)](#)

(NetAF.Interpretation.html) Template for an asset.

+ [NetAF.Logic](#)

(NetAF.Logic.html)

+ [NetAF.Logic.Callbacks](#)

(NetAF.Logic.Callbacks.html)

+ [NetAF.Logic.Configuration](#)

(NetAF.Logic.Configuration.html)

+ [NetAF.Logic.Modes](#)

(NetAF.Logic.Modes.html)

+ [NetAF.Persistence](#)

(NetAF.Persistence.html)

+ [NetAF.Persistence.Json](#)

(NetAF.Persistence.Json.html)

+ [NetAF.Rendering](#)

(NetAF.Rendering.html)

+ [NetAF.Rendering.Frame](#)

Builders

(NetAF.Rendering.FrameBuilder.html)

+ [NetAF.Rendering.Frame](#)

Interface IAssetTemplate<T>

Represents any object that is a template for an asset.

 Filter by title

Namespace: NetAF (NetAF.html).Utilities (NetAF.Utilities.html)

Map

Assembly: NetAF.dll

(NetAF.Commands.RegionMap)

Syntax

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

+ **NetAF.Conversations**

Type Parameters
(NetAF.Conversations.html)

Name	Description
+ NetAF.Conversations	

TInstructions	The type of asset being templated.
----------------------	------------------------------------

(NetAF.Conversations.Instruct

+ **NetAF.Extensions**

(NetAF.Extensions.html)

Methods

+ **NetAF.Interpretation**

(NetAF.Interpretation.html)

Instantiate()

+ **NetAF.Logic**

Instantiate a new instance of the templated asset.

(NetAF.Logic.html)

Declaration

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

+ **Instantiate()**

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

Returns

+ **NetAF.Logic.Modes**

Description
+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

The asset.

+ **NetAF.Persistence**

(NetAF.Persistence.html)

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

+ **NetAF.Rendering**

(NetAF.Rendering.html)

+ **NetAF.Rendering.Frame**

Builders

(NetAF.Rendering.FrameBuilder.html)

+ **NetAF.Rendering.Frame**

Class OverworldMaker

Provides a class for helping to make Regions.

Filter by title

Inheritance

Map

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ OverworldMaker

+ **NetAF.Commands.Scene**

Inherited Members

(NetAF.Commands.Scene.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Extensions**

Namespace: NetAF (NetAF.html).Utilities (NetAF.Utilities.html)

(NetAF.Extensions.html)

Assembly: NetAF.dll

+ **NetAF.Interpretation**

Syntax

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

Constructors

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

OverworldMaker(Identifier, Description, params RegionMaker[])

(NetAF.Logic.Configuration.html)

Provides a class for helping to make Regions.

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

public OverworldMaker(Identifier identifier, Description description, params RegionM
aker[] regionMakers)

(NetAF.Persistence.html)

+ **NetAF.Persistence.Json**

(NetAF.Persistence.Json.html)

+ NetAF.Rendering	Name	Description
(NetAF.Rendering.html) Identifier (NetAF.Assets.Identifier.html)	identifier	An identifier for the region.
+ NetAF.Rendering.Frame Description (NetAF.Assets.Description.html)	description	A description for the region.
Builders RegionMaker (NetAF.Utilities.RegionMaker.html) (NetAF.Rendering.FrameBuilder.html)	regionMakers	The region makes to use to construct regions.

+ **NetAF.Rendering.Frame**

OverworldMaker(string, string, params RegionMaker[])

Initializes a new instance of the OverworldMaker class.

Declaration

```
public OverworldMaker(string identifier, string description, params RegionMaker[] regionMakers)
```

Map

(NetAF.Commands.RegionMap)

Parameters

Name	Description
+ NetAF.Commands.Scene (NetAF.Commands.Scene.html) string (https://learn.microsoft.com/dotnet/api/system.string)	<i>identifier</i> An identifier for the region.
+ NetAF.Conversations (NetAF.Conversations.html) string (https://learn.microsoft.com/dotnet/api/system.string)	<i>description</i> A description for the region.
+ NetAF.Conversations.Instructions RegionMaker[] (NetAF.Utilities.RegionMaker.html) (NetAF.Conversations.Instruct	<i>regionMakers</i> The region makes to use to construct regions.

+ NetAF.Extensions

[\(NetAF.Extensions.html\)](#)

Methods

Interpretation

[\(NetAF.Interpretation.html\)](#)

Logic

[\(NetAF.Logic.html\)](#)

Make an overworld.

+ NetAF.Logic.Callbacks

Declaration

[\(NetAF.Logic.Callbacks.html\)](#)

+ NetAF.Logic.Configuration

[\(NetAF.Logic.Configuration.html\)](#)

Returns

+ NetAF.Logic.Modes

Type:

[\(NetAF.Logic.Modes.html\)](#)

Description

Overworld([NetAF.Assets.Locations.Overworld.html](#))

The created overworld.

+ NetAF.Persistence

[\(NetAF.Persistence.html\)](#)

+ NetAF.Persistence.Json

[\(NetAF.Persistence.Json.html\)](#)

+ NetAF.Rendering

[\(NetAF.Rendering.html\)](#)

+ NetAF.Rendering.Frame

Builders

[\(NetAF.Rendering.FrameBuilder.html\)](#)

+ NetAF.Rendering.Frame

Class RegionMaker

Provides a class for helping to make Regions.

Filter by title

Inheritance

Map

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)

↳ RegionMaker

+ **NetAF.Commands.Scene**

Inherited Members

(NetAF.Commands.Scene.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

+ **NetAF.Extensions**

Namespace: NetAF (NetAF.html).Utilities (NetAF.Utilities.html)

(NetAF.Extensions.html)

Assembly: NetAF.dll

+ **NetAF.Interpretation**

Syntax

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

Constructors

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

RegionMaker(Identifier, Description)

(NetAF.Logic.Configuration.html)

Provides a class for helping to make Regions.

+ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

public RegionMaker(Identifier identifier, Description description)

(NetAF.Persistence.html)

+ **NetAF Persistence.Json**

Parameters

(NetAF.Persistence.Json.html)

Type

+ **NetAF.Rendering**

Identifier ([NetAF.Assets.Identifier.html](https://learn.microsoft.com/dotnet/api/NetAF.Assets.Identifier.html))

(NetAFRendering.html)

Description ([NetAF.Assets.Description.html](https://learn.microsoft.com/dotnet/api/NetAF.Assets.Description.html))

+ **NetAF.Rendering.Frame**

Builders

(NetAF.Rendering.FrameBuilder.html)

RegionMaker(string, string)

+ **NetAF.Rendering.Frame**

	Name	Description
identifier	<i>identifier</i>	An identifier for the region.
description	<i>description</i>	A description for the region.

Initializes a new instance of the RegionMaker class.

Declaration

```
public RegionMaker(string identifier, string description)
```

Parameters

Type	Name	Description
(NetAF.Commands.RegionMap string (https://learn.microsoft.com/dotnet/api/system.string)	<i>identifier</i>	An identifier for the region.
+ NetAF.Commands.Scene string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.Scene.html	<i>description</i>	A description for the region.

+ NetAF.Conversations

 ([NetAF.Conversations.html](#))

Properties

+ NetAF.Conversations.

 Instructions

 ([NetAF.Conversations.Instruct](#)

+ NetAF.Extensions

 Get or set the room's location.

 ([NetAF.Extensions.html](#))

Declaration

+ NetAF.Interpretation

 ([NetAF.Interpretation.html](#))

+ NetAF.Logic

Parameters

 ([NetAF.Logic.html](#))

Type

+ NetAF.Logic.Callbacks

 int ([NetAF.Logic.Callbacks.html](#))

Name

Description

x

The x position.

+ NetAF.Logic.Configuration

 ([NetAF.Logic.Configuration.html](#))

y

The y position.

 int ([NetAF.Logic.Configuration.html](#))

z

The z position.

+ NetAF.Logic.Modes

Property Value

 ([NetAF.Logic.Modes.html](#))

Type

+ NetAF.Persistence

Room ([NetAF.Assets.Locations.Room.html](#))

Description

The room.

+ NetAF.Persistence.Json

 ([NetAF.Persistence.Json.html](#))

Methods

+ NetAF.Rendering

 ([NetAF.Rendering.html](#))

CanPlaceRoom(int, int)

Builders

Determine if a room can be placed at a location

 ([NetAF.Rendering.FrameBuilder.html](#))

Declaration

+ NetAF.Rendering.Frame

```
public bool CanPlaceRoom(int x, int y, int z)
```

Parameters

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32)	x	The X position.
Map int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Commands.RegionMap	y	The Y position.
int (https://learn.microsoft.com/dotnet/api/system.int32)	z	The Z position.

+ NetAF.Commands.Scene

(NetAF.Commands.Scene.html)

Returns

Type	Description
(NetAF.Conversations.html)	bool (https://learn.microsoft.com/dotnet/api/system.boolean)

+ NetAF.Conversations.

Instructions

(NetAF.Conversations.Instruct GetRoomPositions())

+ NetAF.Extensions.

Get all current room positions.

(NetAF.Extensions.html)

Declaration

+ NetAF.Interpretation

(NetAF.Interpretation.html)

+ NetAF.Logic

Returns

(NetAF.Logic.html)

Type	Description
(NetAF.Logic.Callbacks.html)	The room positions.

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

Make()

+ NetAF.Logic.Modes

Makes a new mode.

(NetAF.Logic.Modes.html)

Declaration

+ NetAF.Persistence

(NetAF.Persistence.html)

public Region Make()

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

Returns

Type	Description
(NetAF.Rendering.html)	The created region.

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

Make(RoomPosition)

+ NetAF.Rendering.Frame

Make a region.

Declaration

```
public Region Make(RoomPosition startPosition)
```

Parameters

Type	Name	Description
(NetAF.Commands.RegionMap) RoomPosition (NetAF.Assets.Locations.RoomPosition.html)	<i>startPosition</i>	The start position.

+ **NetAF.Commands.Scene**

[\(NetAF.Commands.Scene.html\)](#)

Type	Description
(NetAF.Conversations) (NetAF.Conversations.html) Region (NetAF.Assets.Locations.Region.html)	The created region.

+ **NetAF.Conversations.**

Instructions

[\(NetAF.Conversations.Instruct.html\)](#)

+ **NetAF.Extensions**

[\(NetAF.Extensions.html\)](#)

Declaration

+ **NetAF.Interpretation**

[\(NetAF.Interpretation.html\)](#)

+ **NetAF.Logic**

Parameters

[\(NetAF.Logic.html\)](#)

Type

+ **NetAF.Logic.Callbacks**

Type	Name	Description
int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Logic.Callbacks.html)	x	The start x position.
int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Logic.Configuration.html)	y	The start y position.
int (https://learn.microsoft.com/dotnet/api/system.int32) (NetAF.Logic.Configuration.html)	z	The start z position.

+ **NetAF.Logic.Modes**

Returns

[\(NetAF.Logic.Modes.html\)](#)

Type

+ **NetAF.Persistence**

Region ([NetAF.Assets.Locations.Region.html](#))

[\(NetAF.Persistence.html\)](#)

Description

The created region.

+ **NetAF.Persistence.Json**

[\(NetAF.Persistence.Json.html\)](#)

+ **NetAF.Rendering**

[\(NetAF.Rendering.html\)](#)

+ **NetAF.Rendering.Frame**

Builders

[\(NetAF.Rendering.FrameBuilder.html\)](#)

+ **NetAF.Rendering.Frame**

Class StringUtilities

Provides a helper class for string interpretation.

Filter by title

Inheritance

Map

↳ object (<https://learn.microsoft.com/dotnet/api/system.object>)
↳ StringUtilities

+ **NetAF.Commands.Scene**

Inherited Members

(NetAF.Commands.Scene.html)

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object)))

+ **NetAF.Conversations**

object.Equals(object) ([https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals\(system-object-system-object\)](https://learn.microsoft.com/dotnet/api/system.object.equals#system-object-equals(system-object-system-object)))

+ **NetAF Conversations**

object.GetHashCode() (<https://learn.microsoft.com/dotnet/api/system.object.gethashcode>)

object.GetType() (<https://learn.microsoft.com/dotnet/api/system.object.gettype>)

(NetAF.Conversations.Instruction.html)

object.ReferenceEquals(object, object) (<https://learn.microsoft.com/dotnet/api/system.object.referenceequals>)

+ **NetAF.Extensions**

object.ToString() (<https://learn.microsoft.com/dotnet/api/system.object.tostring>)

(NetAF.Extensions.html)

Namespace: NetAF (NetAF.html).Utilities (NetAF.Utilities.html)

* **NetAF.Interpretation**

↳ **(NetAF.Interpretation.html)**

Syntax

+ **NetAF.Logic**
public static class StringUtilities

(NetAF.Logic.html)

+ **NetAF.Logic.Callbacks**

(NetAF.Logic.Callbacks.html)

Fields

↳ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

€ **NetAF.Logic.Modes**

(NetAF.Logic.Modes.html)

Get the character for carriage return.

+ **NetAF.Persistence**

Declaration

(NetAF.Persistence.html)

+ **NetAF.Persistence.Json** 'r'

(NetAF.Persistence.Json.html)

Field Value

+ **NetAF.Rendering**

T(NetAF.Rendering.html)

+ **NetAF.Rendering.Frame**

Description

Builders

(NetAF.Rendering.FrameBuilder.html)

LF

+ **NetAF.Rendering.Frame**

Get the character for line feed.

Declaration

```
public const char LF = '\n'
```

Field Value

Type	Description
(NetAF.Commands.RegionMap char (https://learn.microsoft.com/dotnet/api/system.char)	

+ **NetAF.Commands.Scene**

(NetAF.Commands.Scene.html)

Newline

+ **NetAF.Conversations**

(NetAF.Conversations.html)

Get the new line string.

+ **NetAF.Conversations.**

Declaration

Instructions

(NetAF.Conversations.Instruct
public const string NEWLINE = "\n"

+ **NetAF.Extensions**

Field Value

(NetAF.Extensions.html)

+ Type

NetAF.Interpretation

(NetAF.Interpretation.html)

+ **NetAF.Logic**

(NetAF.Logic.html)

Methods

(NetAF.Logic.Callbacks.html)

+ **NetAF.Logic.Configuration**

(NetAF.Logic.Configuration.html)

Construct a line describing a series of attributes.

+ **NetAF.Logic.Modes**

Declaration

(NetAF.Logic.Modes.html)

+ **NetAF.Persistence**

(NetAF.Persistence.html)

ConstructAttributesAsString(Dictionary<Attribute, int> attribut

+ **NetAF.Persistence.Json**

Parameters

(NetAF.Persistence.Json.html)

Type

+ **NetAF.Rendering**

(NetAF.Rendering.html)

(<https://learn.microsoft.com/dotnet/api/system.collections.generic.dictionary-2>)

+ **NetAF.Rendering.Frame**

<Attribute ([NetAF.Assets.Attributes.Attribute.html](https://learn.microsoft.com/dotnet/api/NetAF.Assets.Attributes.Attribute.html)),

int (<https://learn.microsoft.com/dotnet/api/system.int32>)>

(NetAF.Rendering.FrameBuilder

Returns

+ **NetAF.Rendering.Frame**

Description

Description

Name

Description

attributes

The attributes.

Declaration

```
public static string ExtractNextWordFromString(ref string input)
```

Parameters

Type	Name	Description
Map (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Commands.RegionMap)	input	The input string.

Returns

+ NetAF.Commands.Scene

Type	Description
string (https://learn.microsoft.com/dotnet/api/system.string) (NetAF.Conversations)	The extracted word.

(NetAF.Conversations.html)

+ NetAF.Conversations. PreenInput(string)

Instructions

(NetAF.Conversations.html) To remove special characters.

NetAF.Extensions

(NetAF.Extensions.html)

```
public static string PreenInput(string input)
```

+ NetAF.Interpretation

(NetAF.Interpretation.html)

Parameters

Type	Name	Description
string (https://learn.microsoft.com/dotnet/api/system.string)	input	The input.

+ NetAF.Logic.Callbacks

(NetAF.Logic.Callbacks.html)

Returns

+ NetAF.Logic.Configuration

(NetAF.Logic.Configuration.html)

string (https://learn.microsoft.com/dotnet/api/system.string)	Description
	The preened input.

+ NetAF.Logic.Modes

(NetAF.Logic.Modes.html)

+ NetAF.Persistence

(NetAF.Persistence.html)

+ NetAF.Persistence.Json

(NetAF.Persistence.Json.html)

+ NetAF.Rendering

(NetAF.Rendering.html)

+ NetAF.Rendering.Frame

Builders

(NetAF.Rendering.FrameBuilder.html)

+ NetAF.Rendering.Frame