



[BIT703 Web Technologies](#) / [Contents](#) / Topic 7: Client-side web application development and programming – JavaScript / UI frameworks for client-side development

AngularJS 5m

For a beginner summary of AngularJS, return to the page on JavaScript frameworks. In this topic, we'll focus on more advanced AngularJS features and cover material relevant to your assessments.

AngularJS uses data binding. Data binding automatically keeps information on a page up to date. Data binding can be used to specify the source of images, the state of a button or the state of data to a user.

Data binding

Input controls provide data binding by using the ng-model directive. Below is an example that illustrates the use of an AngularJS framework in a simple problem. The commands are explained after the example.



[Skip to main content](#)

HTMLJSResultEDIT ON

LIVE

```
<div ng-app="myApp" ng-controller="formCtrl">
  <form novalidate>
    <label for="firstName">First
Name:</label><br>
    <input type="text" ng-model="user.firstName"
id="firstName"><br>
    <label for="lastName">Last Name:
</label><br>
    <input type="text" ng-model="user.lastName" id="lastName">
<br><br>
    <button type="button" ng-click="reset()">RESET</button>
  </form>
  <p>form = {{user}}</p>
  <p>master = {{master}}</p>
</div>
```

First Name:

Last Name:

form =
{ "firstName": "John", "lastName": "Doe" }

master =
{ "firstName": "John", "lastName": "Doe" }

Resources1x0.5x0.25xRerun

Example 7.10 AngularJS



The commands shown in the example above are explained below.

- The **ng-app** directive defines the AngularJS application.
- The **ng-controller** directive defines the application controller.
- The **ng-model** directive binds two input elements to the **user** object in the model.

Skip to main content

- ▶ The **formCtrl** controller sets initial values to the **master** object and defines the **reset()** method.
- ▶ The **reset() method** sets the **user** object equal to the **master** object.
- ▶ The **ng-click** directive invokes the **reset()** method only if the button is clicked.



Thoughts on this page?

