



[BIT703 Web Technologies](#) / [Contents](#) / [Topic 10: Server-side web application development with procedural and object-oriented database programming](#) / [Database operations in PHP](#)

CRUD: Delete 5m

The delete operation performs the delete function, used to delete existing records. This section shows how to delete an existing database record. This is the final operation of the CRUD operations.

This example assumes you have already successfully performed the insert and update functions from the previous pages. It is important that you have already performed these functions because this delete example will be deleting those data values.



If you haven't performed the insert or update functions, we recommend taking a look at the following pages:

[Create using the OOP approach](#) →

[Update using the OOP approach](#) →

To delete records in the database, you need to execute a delete statement against the data. Apart from the use of the delete statement, the code here is very similar to that used for the inserting and updating records examples given earlier.



Copy

[Skip to main content](#)

```
1 // prepare the statement
2 $query = "DELETE FROM tbl_restaurant WHERE resta_name=? ";
3 $stmt = mysqli_prepare($db_connection, $query);
4 // place data into the variables
5 $resta_name = "SWEET CUPCAKES";
6 $resta_address = "345 BROADWAY ROAD";
7
8 // bind the 2 strings to the values from above
9 mysqli_stmt_bind_param($stmt, 'ss', $resta_name, $resta_address); //associate the ? v
10
11 mysqli_stmt_execute($stmt);
12 mysqli_stmt_close($stmt);
13
14 // close the connection once done
15 mysqli_close($db_connection);
```

aistfile1.txt hosted with ❤ by GitHub

[view raw](#)



Thoughts on this page?

