



[BIT703 Web Technologies](#) / [Contents](#) / Topic 10: Server-side web application development with procedural and object-oriented database programming / Database operations in PHP

CRUD: Update 5m

The update operation performs the edit function, used to update existing records.

The following code example shows how to update an existing database record.

This example assumes you have already successfully performed the insert function from a previous page, where you inserted a new record. It is important that you have already performed this function because this example will be looking for the inserted data.



If you haven't performed the insert function, we recommend taking another look at this page:

[CRUD: Create](#) ➔

To update records in the database, you must execute an update statement against the data. Again, you use a prepared statement to set up the data.

There are no new MySQLi functions introduced in this example. You have seen them all in the previous example. Again, you can confirm if the update was successful by opening the PHP page that runs the select query. This is the only part of the code that is different from the previous examples.



[Skip to main content](#)



Copy

```
1 // prepare the statement with placeholders (?) for the variable data
2 $query = "UPDATE tbl_restaurant SET resta_name=? WHERE resta_name=?";
3 $stmt = mysqli_prepare($db_connection, $query); //prepare the query
4 // place data into the variables
5 $newname = "SWEET CUPCAKES";
6 $resta_name = "SWEET PANCAKES";
7
8 // bind the 2 strings to the values from above
9 mysqli_stmt_bind_param($stmt, 'ss', $newname, $resta_name); //associate the ? with va
10 mysqli_stmt_execute($stmt);
11 mysqli_stmt_close($stmt);
```

aistfile1.txt hosted with ❤ by GitHub

[view raw](#)

Thoughts on this page?

