



[BIT703 Web Technologies](#) / [Contents](#) / [Topic 10: Server-side web application development with procedural and object-oriented database programming](#) / [Database operations in PHP](#)

Connecting to MySQL using the OOP approach

3m

Now we'll learn about the OOP approach. In this approach, classes, constructors, methods and attributes will be used to demonstrate the OO concepts.

Before we can perform the CRUD operations, it is important to ensure the database is created in phpMyAdmin and is available to use in the PHP program. Then we must establish a database connection and perform the required CRUD operations.

The files and classes covered in this section are available in the archive `CRUD_Topic_10.zip` in the folder `CRUD_ver3`.

This example uses a different table structure (different fields) from what you might have seen before, however, the code and functionality remain the same. The code used to demonstrate the various PHP MySQLi database functions are snippets of a much larger piece of code. Change the SQL and PHP in the above demo code to suit your needs if you want to try out the code yourself.

The example below matches the default username and password of MySQL and the name of the restaurant database you created in a previous topic.



[Skip to main content](#)



[Skip to main content](#)

```

1  <?php
2
3  include_once 'config.php';
4
5  class DbConfig
6  {
7      private $_host;          // This may vary. Connect to your localhost or 12
7.0.0.1 or localhost:8080
8      private $_username;      // Enter the username of phpMyAdmin. This is to co
nnect with phpMyAdmin
9      private $_password;      // Enter the password of phpMyAdmin.
10     private $_database;      // This is to connect with phpMyAdmin to establish
DB connection.
11     protected $connection;    // Connection handle for the database
12
13     // Close the database connection
14     public function __destruct() {
15         if ($this->connection) {
16             $this->connection->close();
17         }
18     }
19
20     public function __construct($host, $username, $password, $database)
21     {
22         // Values passed from the DB config
23         $this->_host = $host;
24         $this->_username = $username;
25         $this->_password = $password;
26         $this->_database = $database;
27
28         if (!isset($this->connection)) {
29             $this->connection = new mysqli($this->_host, $this->_username,
$this->_password, $this->_database);
30
31             if (!$this->connection) {
32                 echo 'Cannot connect to database server';
33                 exit;
34             }
35         }
36
37         return $this->connection;

```

Skip to main content

```
38     }  
39 }  
40 ?>
```



Thoughts on this page?

