



[BIT703 Web Technologies](#) / [Contents](#) / Topic 11: Server-side web application admin panel development / Creating an admin panel

Creating the database 60m

Before you can start writing the PHP code to build the interface and functionality of the admin panel, you first must create the database and tables to store and retrieve the admin panel data.

Remember to check that:

- your server is installed and running on your computer
- MySQL is running on your computer
- MySQL and phpMyAdmin are connected.

The Kākahu retail store has requested an admin panel so that they can have complete control over their online store. Based on their request, we can conclude that they will require a database to store and retrieve data for:

- admin panel users/administrators to manage permissions and access
- the shopping cart to manage the items in customers' shopping carts
- categories to manage the categories of clothing available
- orders to manage the customer and payment details of each order
- order details to manage information about the items that have been ordered
- products to manage the items available
- product size variations to manage the different sizes available in each product
- sizes to manage the different sizes.

We created a database called **db_admin_panel_ver4** and then created tables for users, carts, categories, orders, order_details, products, product_size_variations and sizes. The [video below](#) shows the data types and fields that have been defined for each of the

database tables.

Table naming convention

SQL tables typically use singular nouns such as the preferred 'user' instead of 'users' as found in the provided code. The names have not been changed in the code provided throughout the topic because of the use of the external code. If you want to follow the preferred naming convention then you can change the SQL files and all of the affected PHP files that make reference to the tables listed below (this includes the original code and the code within this topic).

Suggested changes from table name to table name:

- users to user
- orders to order
- sizes to size (note: this is a reserved word so alternate names would be better)

Take your time reading the SQL queries and see if you can identify the data types, lengths and key constraints used in each table.

#	Table	SQL query
---	-------	-----------

[Skip to main content](#)

1	Users	<pre>DROP TABLE IF EXISTS `users`; CREATE TABLE IF NOT EXISTS `users` (`user_id` int(11) NOT NULL AUTO_INCREMENT, `user_name` varchar(50) NOT NULL, `first_name` varchar(200) NOT NULL, `last_name` varchar(255) NOT NULL, `email` varchar(255) NOT NULL, `password` varchar(150) NOT NULL, `contact_no` varchar(10) NOT NULL, `registered_at` datetime NOT NULL DEFAULT current_timestamp(), `isAdmin` int(11) NOT NULL DEFAULT 0, `user_address` varchar(255) NOT NULL, PRIMARY KEY (`user_id`)) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8mb4;</pre>
---	-------	---

[Skip to main content](#)

2	Cart	<pre> DROP TABLE IF EXISTS `cart`; CREATE TABLE IF NOT EXISTS `cart` (`cart_id` int(11) NOT NULL AUTO_INCREMENT, `user_id` int(11) NOT NULL, `variation_id` int(11) NOT NULL, `quantity` int(11) NOT NULL, `price` int(11) NOT NULL, PRIMARY KEY (`cart_id`), UNIQUE KEY `uc_cart` (`user_id`,`variation_id`), KEY `variation_id` (`variation_id`)) ENGINE=InnoDB AUTO_INCREMENT=10 DEFAULT CHARSET=utf8mb4; </pre>
3	Category	<pre> DROP TABLE IF EXISTS `category`; CREATE TABLE IF NOT EXISTS `category` (`category_id` int(11) NOT NULL AUTO_INCREMENT, `category_name` varchar(150) NOT NULL, PRIMARY KEY (`category_id`)) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8mb4; </pre>

[Skip to main content](#)

4	Orders	<pre>DROP TABLE IF EXISTS `orders`; CREATE TABLE IF NOT EXISTS `orders` (`order_id` int(11) NOT NULL AUTO_INCREMENT, `user_id` int(11) NOT NULL, `delivered_to` varchar(150) NOT NULL, `phone_no` varchar(10) NOT NULL, `deliver_address` varchar(255) NOT NULL, `pay_method` varchar(50) NOT NULL, `pay_status` int(11) NOT NULL, `order_status` int(11) NOT NULL DEFAULT 0, `order_date` datetime NOT NULL DEFAULT current_timestamp(), PRIMARY KEY (`order_id`), KEY `user_id` (`user_id`)) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4;</pre>
---	--------	---

[Skip to main content](#)

5	Order_details	<pre>DROP TABLE IF EXISTS `order_details`; CREATE TABLE IF NOT EXISTS `order_details` (`detail_id` int(11) NOT NULL AUTO_INCREMENT, `order_id` int(11) NOT NULL, `variation_id` int(11) NOT NULL, `quantity` int(11) NOT NULL, `price` int(11) NOT NULL, PRIMARY KEY (`detail_id`), KEY `order_id` (`order_id`), KEY `variation_id` (`variation_id`)) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4;</pre>
---	---------------	---

[Skip to main content](#)

6	Product	<pre>DROP TABLE IF EXISTS `product`; CREATE TABLE IF NOT EXISTS `product` (`product_id` int(11) NOT NULL AUTO_INCREMENT, `product_name` varchar(200) NOT NULL, `product_desc` text NOT NULL, `product_image` varchar(255) NOT NULL, `price` int(11) NOT NULL, `category_id` int(11) NOT NULL, `uploaded_date` datetime NOT NULL DEFAULT current_timestamp(), PRIMARY KEY (`product_id`), KEY `category_id` (`category_id`)) ENGINE=InnoDB AUTO_INCREMENT=8 DEFAULT CHARSET=utf8mb4;</pre>
---	---------	--

[Skip to main content](#)

7	Product_size_variation	<pre> DROP TABLE IF EXISTS `product_size_variation`; CREATE TABLE IF NOT EXISTS `product_size_variation` (`variation_id` int(11) NOT NULL AUTO_INCREMENT, `product_id` int(11) NOT NULL, `size_id` int(11) NOT NULL, `quantity_in_stock` int(11) NOT NULL, PRIMARY KEY (`variation_id`), UNIQUE KEY `uc_ps` (`product_id`,`size_id`)) ENGINE=InnoDB AUTO_INCREMENT=11 DEFAULT CHARSET=utf8mb4; </pre>
8	Sizes	<pre> DROP TABLE IF EXISTS `sizes`; CREATE TABLE IF NOT EXISTS `sizes` (`size_id` int(11) NOT NULL AUTO_INCREMENT, `size_name` varchar(100) NOT NULL, PRIMARY KEY (`size_id`)) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8mb4; </pre>



[Skip to main content](#)

☒ Tables

Non-Assessed

Have a go at recreating the tables for Kākahu's online store by using the SQL queries for each of the eight tables provided in the table we just looked at. Take note of the fact that the SQL queries specify the data types, lengths and key constraints so you have everything you need to create these tables.

You may choose to create these tables using the SQL query workspace or the structure tab within phpMyAdmin.

☐ I've completed the activity

Submit



Once the tables are created, the next step is to populate them with data. In this case, we will populate the tables with dummy data. Once this is done, the creation of the tables in phpMyAdmin is complete.



Thoughts on this page?



[Skip to main content](#)

