




[BIT703 Web Technologies](#) / [Contents](#) / [Topic 10: Server-side web application development with procedural and object-oriented database programming](#) / [Database operations in PHP](#)

Delete using the OOP approach 5m

When a particular record is selected by the user to delete, the record id for that selected record will be fetched, and a message will be produced to ask for confirmation before the selected record can be deleted. The code to perform this delete CRUD operation is shown below:



Copy


[Skip to main content](#)

```
1  <?php
2  //including the database connection file
3  include_once("classes/Crud.php");
4
5  //An object is created for class crud
6  $crud = new Crud();
7
8  //getting id of the data from url/ link
9  $id = $crud->escape_string($_GET['id']);
10 //NOTE: validation has not been performed on the id
11
12 //deleting the row from table
13 //$result = $crud->execute("DELETE FROM tbl_restaurant WHERE id=$id");
14 $result = $crud->delete($id, 'users');
15
16 if ($result) {
17     //redirecting to the display page (index.php in our case)
18     header("Location:index.php");
19 }
20 ?>
```

gistfile1.txt hosted with ❤ by GitHub

[view raw](#)

The `$crud->delete($id, 'users')` is extended from class `crud`. The delete functionality code is given below:



Copy

[Skip to main content](#)

```
1  public function delete($id, $table)
2      {
3          $query = "DELETE FROM $table WHERE id = $id";
4
5          $result = $this->connection->query($query);
6
7          if ($result == false) {
8              echo 'Error: cannot delete id ' . $id . ' from table ' . $table;
9              return false;
10         } else {
11             return true;
12         }
13     }
```

aistfile1.txt hosted with ❤ by GitHub

[view raw](#)



Thoughts on this page?

