



[BIT703 Web Technologies](#) / [Contents](#) / Topic 7: Client-side web application development and programming – JavaScript / Understanding jQuery

JavaScript vs jQuery 4m

What is jQuery?

We briefly introduced jQuery earlier with AJAX and learned that it is a library written in JavaScript. It is a free, open-source library that is fast, concise and feature rich. It also has cross-browser compatibility.

Some of the key features of jQuery are:

- DOM manipulation – DOM elements can be easily traversed and modified
- animations – lots of built-in features for animations
- HTML event handling and manipulation
- AJAX has a simple and easy-to-use API that works across a multitude of browsers
- CSS manipulation is made easy
- a high-level UI widget library
- cross-browser support – jQuery works well on a range of browsers like Chrome, Opera, etc.
- considered lightweight when compared with similar libraries.

jQuery HTML

The jQuery library is a single JavaScript file, and it is referenced with the HTML tag (note that the tag should be inside the section).

The `html()` method in jQuery is used to set or return the `innerHTML` content of the selected element.

[Skip to main content](#)

The syntax used is:

- ▶ `$(selector).html()` – returns the content of the first matched element.
- ▶ `$(selector).html(content)` – sets the content of the matched element.
- ▶ `$(selector).html(function(index, currentcontent))` – sets the content using a function.



The validation in the following CodePen will not run in iQualify due to iframe restrictions. To test the validation, select "Open in new tab" on "Edit on CodePen"



[Skip to main content](#)

HTMLJSResult

EDIT ON

LIVE

```
<!DOCTYPE html>
<html>
<head>
  <title>
    jQuery html() Method
  </title>
  <script src=
"https://ajax.googleapis.com/ajax/li
bs/jquery/3.3.1/jquery.min.js">
  </script>
</head>
<body style = "text-align:center;">
  <h1 style = "color:blue;" >
    Open Polytechnic
  </h1>
  <h2>
    jQuery | html() Method
  </h2>
  <button>Click</button>
</body>
</html>
```

Resources1x0.5x0.25xRerun

Example 7.8 HTML() method

☒ HTML() method

Non-Assessed

Status: Done
Skip to main content

Reset ↺

In Example 7.8, an alert message appears on the screen after you click on the button. In this activity, we will change this so that when you click on the button, the text on the screen changes rather than an alert message appearing.

To do this, you will need to update the `HTML()` method so that when a user clicks on the button, the text 'jQuery | `html()` Method' is replaced by the text 'Hello BIT703 learners'. You will be creating a fade-out effect where the text on screen changes once the button is clicked.

Have a go at editing the `HTML()` method code so that it sets the content of the element to change the text.



I have completed this task!



Did you successfully use the `HTML()` method to create a fade-in effect where the text on screen is changed when a user clicks on a button?

Compare your code to ours:

[Skip to main content](#)

```
<!DOCTYPE html>
<html>

<head>
  <title>
    jQuery html() Method
  </title>

  <script src=
    "https://ajax.googleapis.com/ajax/libs/jquery/3.3.1/jquery.min.
js">
  </script>
</head>

<body style = "text-align:center;">

  <h1 style = "color:blue;" >
    Open Polytechnic
  </h1>

  <h2>
    jQuery | html() Method
  </h2>

  <button>Click</button>

  <script>
    $(document).ready(function(){
      $("button").click(function(){
        $("h2").html("Hello <b>GEEKS!</b>");
        $("h2").fadeOut(1000); //slowly fade out
      });
    });
  </script>
</body>

</html>
```

Previous attempts ▼

[Skip to main content](#)



Thoughts on this page?

