




[BIT703 Web Technologies](#) / [Contents](#) / Topic 10: Server-side web application development with procedural and object-oriented database programming / Database operations in PHP

Read using the OOP approach 5m

The select query can also be used in the OOP approach to display the restaurant details from the MySQL database. Once an object has been created, you can then call the method `$crud->getData($query)` to get the restaurant records from the database. The code below shows how you can use the select query to display the restaurant details.



Copy

```
1  <?php
2  //including the database connection file
3  include_once("classes/Crud.php");
4
5  $crud = new Crud();
6
7  //fetching data in descending order (latest entry first)
8  $query = "SELECT * FROM tbl_restaurant ORDER BY rest_id DESC";
9  $result = $crud->getData($query);
10 echo '<pre>'; print_r($result); exit;
11 ?>
```

gistfile1.txt hosted with ❤ by GitHub

[view raw](#)

[Skip to main content](#)

It is important you also include the following code in the Crud.php file, which is where the `getData($query)` function is defined. This function is called when the index.php is executed, and all the available records will be displayed.

 Copy

```
1 public function getData($query)
2     {
3         $result = $this->connection->query($query);
4
5         if ($result == false) {
6             return false;
7         }
8
9         $rows = array();
10
11        while ($row = $result->fetch_assoc()) {
12            $rows[] = $row;
13        }
14
15        return $rows;
16    }
```

gistfile1.txt hosted with ❤ by GitHub

[view raw](#)

As with the procedural read operations, avoid using the **fetch_all** function.



[Skip to main content](#)

Thoughts on this page?

