



[BIT703 Web Technologies](#) / [Contents](#) / Topic 10: Server-side web application development with procedural and object-oriented database programming / Database operations in PHP

Update using the OOP approach 5m

The update function can also be used in the OOP approach to update existing records in a database. To perform the update operation, two steps are involved:

- Retrieve the selected record from the database
- Update the selected record.

We will start with step 1: Retrieve the selected record from the database. The code below demonstrates how to retrieve a record from our restaurant database. As we said earlier, the class defined in `classes\Crud.php` only contains the minimal code required to implement an OO database class. This means code for the prepare statements has not been included. You will need to include this in your own code implementation as described earlier in this section.



Copy

[Skip to main content](#)

```
1  <?php
2  // including the database connection file
3  include_once("classes/Crud.php");
4
5  $crud = new Crud();
6
7  //getting id from url/link
8  // this is not validated or checked, make sure you do!
9  $id = $crud->escape_string($_GET['id']);
10
11 //selecting data associated with this particular id
12 $result = $crud->getData("SELECT * FROM tbl_restaurant WHERE id=$id");
13
14 foreach ($result as $res) {
15     $resta_name = $res['restaurant name'];
16     $resta_address = $res['restaurant address'];
17     $resta_category = $res['restaurant category'];
18 }
19 ?>
```

gistfile1.txt hosted with ❤ by GitHub

[view raw](#)



[Skip to main content](#)

Once you've retrieved the selected record from the database, you are able to update that selected record. The code below demonstrates how to update the selected record by using the update function. It performs an update function on the fetched table `tbl_restaurant` to modify the data. The new data will then be copied to the database once the required fields (restaurant name, restaurant address and restaurant category) have passed validation.

```
//updating the table
```

```
$result = $crud->execute("UPDATE tbl_restaurant SET restaurant  
name='$resta_name', restaurant address='$resta_address', restaurant  
category='$resta_category' WHERE id=$id");
```



Thoughts on this page?

