





USB Subsystem in Zephyr

For nRF52840 DK

USB in Zephyr

Zephyr provides USB device functionality

- CDC ACM (serial)
- HID (input devices)
- RNDIS (networking)
- Mass Storage




Common USB Use Cases



Serial (CDC ACM)

Virtual COM port for device communication



Input Devices (HID)

Keyboards, mice, custom controllers



Networking

ECM/RNDIS for IP communication



Firmware Updates

DFU for over-USB updates

HID Sample Overview

Human Interface Device

- Path: samples/subsys/usb/hid-mouse
- Simulates mouse movement
- Appears as standard HID device



```
5  host uve abiication pulliation
1  tPESD,
7  Penuine derient labes.fortication.(98)
8. built rectstty to four the lad, an.Soc (098,
11 ceceoder, save fout (2.50.12.4)
15 subcal exides to tour bestion, 48 10.102
11 at 1R8,

4  1:
11 last Corpericent cube.for 650.6D
12 contte coact to 000 = fast.200;
13 in they chiled endivs fut for avpler (0lect contbalj);
11 mult-extecte an = (10.0.0)
18 oution instraes = 16.50..145.
```

Building HID Sample


```
west build -b nrf52840dk/nrf52840 samples/subsys/usb/hid-mouse
west flash
```

RNDIS Overview

Remote Network Driver Interface

Device appears as Ethernet adapter on host

Enables IP networking over USB



Creating RNDIS App

Copy HID sample as starting point

Remove unneeded files

- README
- .yaml file
- usbd_next_prj.conf

Modify project structure


Device Tree Configuration

Update CMakeLists.txt

Change project name to rndis

Create .overlay file

```
&zephyr_udc0 {  
    rndis_func: rndis  
    {  
        compatible = "zephyr,usb-rndis";  
    };  
};
```



Implementation Details

- Use the files `main.c` to create network interface
- Use the file `prj.conf` to enable all the relevant configs

Testing the Demo



Build & Flash

Deploy to nRF52840



Verify Connection

Check dmesg and ip addr



Configure IP

Set host to 2.2.2.1/24



Test Connection

Ping in both directions

Telnet

- Add telnet server as backend in prj.conf

CONFIG_SHELL_BACKEND_TELNET=y

CONFIG_SHELL_TELNET_SUPPORT_COMMAND=y

- Connect from the host to telnet and run the shell
 - Telnet 2.2.2.2

Extra Exercise

- Create echo UDP socket on the ip on listening on port 4242 and answer the data he receive
- Hint: add CONFIG_NET_UDP=y, CONFIG_NET_SOCKETS=y and read about socket.
can take a look in samples/net/sockets/echo_server