

SINGULARITIES IN THE GENERALIZED CONSTANTIN–LAX–MAJDA
EQUATION

ON A SEARCH FOR FINITE-TIME SINGULARITIES IN THE GENERALIZED
CONSTANTIN–LAX–MAJDA EQUATION

By NOAH BENSLER, B.Sc.

A Project Submitted to Math 745

Computational Science & Engineering

McMaster University

©Copyright by Noah Bensler, 17 December 2025.

Project Proposal

For my term project I will compute and analyse solutions of the Generalized Constantine-Lax-Majda equation. The Constantine-Lax-Majda (CLM) equation was proposed as a one-dimensional model for the three-dimensional vorticity equation and has the form

$$\omega_t - u_x \omega = 0, \quad u_x = H\omega$$

where ω is the vorticity of the fluid and u is the fluid velocity. For this analysis the equations will be examined on the periodic domain $x \in [-\pi, \pi]$. The Hilbert transform of the vorticity is defined as

$$H\omega(x, t) = \frac{1}{2\pi} \int_{-\pi}^{\pi} \omega(y, t) \cot\left(\frac{x-y}{t}\right) dy,$$

which has a singularity at $x = y$ and so must be evaluated using the Cauchy Principle Value. The CLM equation was later expanded on by De Gregorio to include the convection term $u\omega_x$. The De Gregorio equation has the form

$$\omega_t + u\omega_x - u_x \omega = 0, \quad u_x = H\omega.$$

The De Gregorio equation was later generalized by Okamoto et al. to include the real parameter a . The result is the Generalized Constantin-Lax-Majda equation (GCLM)

$$\omega_t + au\omega_x - u_x \omega = 0, \quad u_x = H\omega.$$

The parameter a determines the relative strength of the convection term. When $a = 0$ the GCLM is equal to the CLM, and when $a = 1$ it is equal to the De Gregorio equation. The CLM equation was proposed in 1985 and has been shown to exhibit finite time blow-up. While the De Gregorio equation was proposed shortly after in 1989, questions still remain as to whether or not the equation permits finite time blow-up. The goal of this analysis will be to examine the affect the parameter a has on the finite time blow-up of the GCLM equation. I will explore solutions of the GCLM for values of $a \in [-1, 1]$.

Abstract

The Constantin-Lax-Majda (CLM) equation was proposed as a one-dimensional model for the three-dimensional vorticity equation. The CLM equation was later expanded on by De Gregorio to include the convection term $u\omega_x$. The De Gregorio equation was generalized by Okamoto et al. to include the real parameter a which determines the relative strength of the convection term. The result is the Generalized Constantin-Lax-Majda equation (GCLM). In this analysis we examine the affect the parameter $a \in [-1, 1]$ has on the finite time blow-up of the GCLM equation on the periodic domain $x \in [-\pi, \pi]$.

The analysis found RESULTS RESULTS RESULTS. CONCLUSION CONCLUSION CONCLUSION.

Nearly all values of a resulted in blow-up or blow-up like behaviour. The results for most a values are inconclusive as the resolution was insufficient to properly capture the singular behaviour. However, the results indicate that all values of $a < 0.8$ would result in a finite-time singularity. The primary effect a had was on how quickly the singularity formed.

Contents

1	Introduction	1
1.1	The GCLM Equation	2
1.2	Blow-up Criteria	3
1.3	Overview	3
2	Numerical Methods	4
2.1	Physical and Fourier Representation	4
2.2	Time Stepping	5
2.3	Complete Numerical Method	6
2.4	Initial Conditions	6
3	Results	7
4	Conclusion	7
5	Appendix	7
5.1	Derivation of Hilbert Transform in Fourier space	7
5.2	Derivation of the Velocity in Fourier space	8

1 Introduction

The three-dimensional Euler equations are a simplified form of the Navier-Stokes equations which describe the flow of inviscid incompressible fluids. The Euler equations are

$$u_t + u \cdot \nabla u + \nabla p = 0, \quad (1.1a)$$

$$\nabla \cdot u = 0, \quad (1.1b)$$

where u is the velocity field and p is the scalar pressure. By substituting in the vorticity ($\omega = \nabla \times u$) these equations can be re-expressed in the three-dimensional vorticity equation

$$\omega_t + (u \nabla) \omega = (\omega \nabla) u, \quad (1.2)$$

where the velocity can be computed from the vorticity field with the equation

$$u = -\nabla \times (\nabla^{-1} \omega). \quad (1.3)$$

A central question in fluid dynamics is whether or not finite-time singularities can form in fluid flows with smooth initial conditions [2]. As first demonstrated by Beale, Kato, and Majda, singularities can form if and only if the maximum vorticity of the flow becomes infinite [1]. The vorticity equation allows for the direct modelling of the vorticity and so is a very useful tool for studying singularity formation in the Euler equations. WHY USE 1D MODELS.

1.1 The GCLM Equation

The Constantin-Lax-Majda (CLM) equation was the first one-dimensional model of the three-dimensional vorticity equation for an incompressible fluid [2]. The CLM equation is

$$\omega_t = H(\omega)\omega \quad (1.4)$$

where H is the Hilbert transform

$$H(\omega) = \frac{1}{\pi} \text{P.V.} \int \frac{\omega(y)}{(x-y)} dy. \quad (1.5)$$

with P.V. indicating the integral must be evaluated using the Cauchy Principle Value due to the singularity at $x = y$. It was demonstrated that most solutions to (1.4) form finite-time singularities CITATION. A significant advantage of this model was that its simplicity allowed for the derivation of an explicit solution to (1.4) [2]. The solution of the CLM equation is

$$\omega(x, t) = \frac{4\omega_0(x)}{(2 - tH\omega_0(x))^2 + t^2\omega_0^2(x)}. \quad (1.6)$$

However, De Gregorio noted three shortcomings of the model [3].

1. asdf

Due to these problems, De Gregorio proposed a new one-dimensional model that improved upon the CLM equation by ... [3]. The De Gregorio equation is

$$\omega_t + u\omega_x - u_x\omega = 0. \quad (1.7)$$

adds the convection term. De Gregorio claimed that (1.7) is globally well posed, although was not able to prove it CITATION.

The De Gregorio equation was later generalized to the Generalized Constantin-Lax-Majda (GCLM) equation [5]. The GCLM equation adds the real parameter a which controls the relative strength of the convection term. The GCLM equation is

$$\omega_t + au\omega_x - u_x\omega = 0. \quad (1.8)$$

When $a = 0$ the GCLM is equal to the (1.4), and when $a = 1$ it is (1.7). Okamoto et al. showed that in the limit of $a \rightarrow \infty$ (1.8) does not permit blowup CITATION.

$$H\omega(x, t) = \frac{1}{2\pi} \int_{-\pi}^{\pi} \omega(y, t) \cot\left(\frac{x-y}{2}\right) dy. \quad (1.9)$$

1.2 Blow-up Criteria

Okamoto et al. (2008) prove Theorem 3.1 and Theorem 3.2.

Theorem 1.1. *Let $a \in \mathbb{R}$ be given. For all $\omega_0 \in H^1(S^1)/\mathbb{R}$, there exists a $T > 0$ depending only on a and $\|\omega_{0,x}\|$ such that there exists a unique solution $\omega \in C^0([0, T]; H^1(S^1)/\mathbb{R}) \cap C^1([0, T]; L^2(S^1)/\mathbb{R})$ of (GCLM ref) with $\omega(0, x) = w_0$.*

1.3 Overview

In this paper we will conduct a search for singularity formation in the GCLM by

In this analysis we present results for the GCLM for different values of $a \in [-1, 1]$. We use the same pseudo-spectral numerical methods as [5] which are described in Section 2. In Section 3 we present the results and summarize in Section 4.

2 Numerical Methods

To model the GCLM equation numerically we must compute the values of the four components, ω , ω_x , u , and u_x . These components are used to calculate the nonlinear convection term $u_x\omega$, the nonlinear stretching term $u\omega_x$, and the time stepping. The methods for calculating the components, terms, and time stepping are described below.

2.1 Physical and Fourier Representation

The terms of (1.8) are represented in physical space on a grid of $N = 2^{14}$ equispaced points on the domain $x \in [-\pi, \pi]$. Because the domain is periodic we must avoid double counting the grid point on the boundary. Therefore we set $x_0 = -\pi$ and $x_N = \pi - h$, where h is the distance between points. The terms are represented in Fourier space using a truncated Fourier series

$$f(x, t) = \sum_{k=-N/2}^{N/2-1} \hat{f}_k(t) \exp(ikx). \quad (2.1)$$

Transformation from physical to Fourier space, and vice versa, are performed using the standard Matlab fft and ifft functions respectively.

We compute the terms ω_x , u and u_x from w . Calculations of the derivative of the vorticity ω_x is performed in Fourier space using the standard formula

$$\omega_x(t) = \sum_{k=-N/2}^{N/2-1} (ik) \hat{\omega}_k(t) \exp(ikx). \quad (2.2)$$

As shown in (ref EQUATION), the velocity can be computed from the vorticity in physical space. However, due to the singularity, this equation must be solved using the Cauchy Principle value, which is difficult to compute numerically. Therefore, we compute the value of u in

Fourier Space using the formula

$$u(x, t) = - \sum_{k=-N/2, k \neq 0}^{N/2-1} \frac{\text{sgn}(k) \hat{\omega}_k(t) \exp(ikx)}{k}. \quad (2.3)$$

The derivation of this equation from (ref EQUATION) is shown in Section 5.2. The derivative of the velocity is calculated using the Hilbert Transform (ref EQUATION). To calculate the derivative of the velocity in physical space would again require the CPV and so is calculated in Fourier space using the formula

$$u(x, t) = - \sum_{k=-N/2}^{N/2-1} i \text{sgn}(k) \hat{\omega}_k(t) e^{ikx}. \quad (2.4)$$

The derivation of this formula from (ref EQUATION) is shown in section 5.1.

For REASON we compute the stretching and convection terms in physical space. To avoid errors due to aliasing we apply the 2/3 dealiasing rule to the terms. Additionally, as in [5], we apply a filter to prevent small values at each time step.

2.2 Time Stepping

When modelling time dependent PDEs it is best practice to use explicit time stepping methods for non-linear terms in order to reduce computation cost, and use implicit methods for linear term to improve stability [6]. As described in prior sections, both the convection term and stretching term of the GCLM are non-linear. Therefore, we perform time stepping using the explicit fourth-order Runge-Kutta (RK4) method. The RK4 time stepping is performed with the formula

$$\omega^{(n+1)} = \omega^{(n)} + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4) \quad (2.5)$$

where $\omega^{(n)}$ is the vorticity at iteration n and the k_i terms are calculated using

$$k_1 = F(\omega^{(n)}, t^{(n)}) \quad (2.6a)$$

$$k_2 = F(\omega^{(n)} + dt \cdot k_1/2, t^{(n)} + dt/2) \quad (2.6b)$$

$$k_3 = F(\omega^{(n)} + dt \cdot k_2/2, t^{(n)} + dt/2) \quad (2.6c)$$

$$k_4 = F(\omega^{(n)} + dt \cdot k_3, t^{(n)} + dt) \quad (2.6d)$$

where $dt = 1E - 4$ is the time step size. The function F in the above equations is given by

$$f(\omega^{(n)}, t^{(n)}) = u_x \omega - au \omega_x \quad (2.7)$$

The derivatives u_x and ω_x are computed in Fourier space. The

2.3 Complete Numerical Method

Combining the methods described above, we use the following procedure

1. Convert $\omega^{(n)}$ from Physical space to Fourier space using FFT.
2. Calculate u_x

2.4 Initial Conditions

Okamoto et al. (2008) showed that any solution that satisfies (GCLM ref) must also satisfy

$$\frac{d}{dt} \int_{-\pi}^{\pi} \omega(t, x) dx = \int_{-\pi}^{\pi} (-au \omega_x + u_x \omega) dx = (a + 1) \int_{-\pi}^{\pi} u_x \omega dx = (a + 1)(H\omega, \omega), \quad (2.8)$$

where $(\cdot, \cdot)$ denotes the L^2 inner product (Okamoto et al., 2008). Therefore, we may assume without loss of generality that the initial condition satisfies

$$\int_{-\pi}^{\pi} \omega(0, x) dx = 0.$$

3 Results

these are the results

4 Conclusion

this is the conclusion

5 Appendix

5.1 Derivation of Hilbert Transform in Fourier space

The Hilbert transform is defined as

$$H\omega(x, t) = \frac{1}{2\pi} \int_{-\pi}^{\pi} \omega(y, t) \cot\left(\frac{x-y}{2}\right) dy.$$

The solution $\omega(y, t)$ is represented as the truncated Fourier series

$$\omega(y, t) = \sum_{k=-N/2}^{N/2-1} \hat{\omega}_k(t) \exp(iky).$$

Substituting this into the Hilbert transform

$$H\omega(x, t) = \frac{1}{2\pi} \int_{-\pi}^{\pi} \sum_{k=-N/2}^{N/2-1} \hat{\omega}_k(t) \exp(iky) \cot\left(\frac{x-y}{2}\right) dy.$$

We can swap the integral and sum to obtain

$$H\omega(x, t) = \frac{1}{2\pi} \sum_{k=-N/2}^{N/2-1} \hat{\omega}_k(t) \int_{-\pi}^{\pi} \exp(iky) \cot\left(\frac{x-y}{2}\right) dy.$$

The integral has a singularity at $x = y$ and so must be evaluated using the Cauchy Principle Value. The Cauchy Principle values of this equation is the well known result used in [4] and [5],

$$H\omega(x, t) = - \sum_{k=-N/2}^{N/2-1} i \operatorname{sgn}(k) \hat{\omega}_k(t) e^{ikx}$$

where sgn is the sign function

$$\operatorname{sgn}(k) = \begin{cases} 1, & \text{if } k > 0 \\ 0, & \text{if } k = 0 \\ -1 & \text{if } k < 0. \end{cases}$$

5.2 Derivation of the Velocity in Fourier space

The velocity field is defined as

$$u(x, t) = \frac{1}{\pi} \int_{-\pi}^{\pi} \omega(y, t) \log \left| \sin \left(\frac{x-y}{2} \right) \right| dy.$$

The solution $\omega(y, t)$ is represented as the truncated Fourier series

$$\omega(y, t) = \sum_{k=-N/2}^{N/2-1} \omega_k(t) \exp(iky).$$

Substituting this into the velocity equation

$$u(t, x) = \frac{1}{\pi} \int_{-\pi}^{\pi} \sum_{k=-N/2}^{N/2-1} \hat{\omega}_k(t) \exp(iky) \log \left| \sin \left(\frac{x-y}{2} \right) \right| dy.$$

We can swap the integral and sum to obtain

$$u(t, x) = \frac{1}{\pi} \sum_{k=-N/2}^{N/2-1} \hat{\omega}_k(t) \int_{-\pi}^{\pi} \exp(iky) \log \left| \sin \left(\frac{x-y}{2} \right) \right| dy.$$

The integral has a singularity at $x = y$ and so must be evaluated using the Cauchy Principle Value. The Cauchy Principle values of this equation is

$$u(t, x) = -4 \ln(2) w_0(t) - \sum_{k=-N/2, k \neq 0}^{N/2-1} \frac{\text{sgn}(k) \hat{\omega}_k(t) \exp(ikx)}{k}$$

For functions $w(x, t)$ with a mean of zero over the domain, the Fourier coefficient $\hat{w}_0(t)$ is zero. Since the mean of the solution is constant over time, and we use initial conditions with a mean of zero, we can simplify the velocity equation to that used in [4] and [5],

$$u(t, x) = - \sum_{k=-N/2, k \neq 0}^{N/2-1} \frac{\text{sgn}(k) \hat{\omega}_k(t) \exp(ikx)}{k}$$

where sgn is the sign function

$$\text{sgn}(k) = \begin{cases} 1, & \text{if } k > 0 \\ 0, & \text{if } k = 0 \\ -1 & \text{if } k < 0. \end{cases}$$

References

- [1] J. T. Beale, T. Kato, and A. Majda. Remarks on the breakdown of smooth solutions for the 3-D Euler equations. *Communications in Mathematical Physics*, 94(1):61–66, March 1984.
- [2] P. Constantin, P. D. Lax, and A. Majda. A simple one-dimensional model for the three-dimensional vorticity equation. *Communications on Pure and Applied Mathematics*, 38(6):715–724, 1985. _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/cpa.3160380605>.
- [3] Salvatore De Gregorio. On a one-dimensional model for the three-dimensional vorticity equation. *Journal of Statistical Physics*, 59(5):1251–1263, June 1990.
- [4] Sato Hideki and Sakajo Takashi. Numerical study of De Gregorio’s model for the 3-D vorticity equation(Theory,Scientific Computation and Numerical Analysis), 2006.
- [5] Hisashi Okamoto, Takashi Sakajo, and Marcus Wunsch. On a generalization of the Constantin–Lax–Majda equation. *Nonlinearity*, 21(10):2447, September 2008.
- [6] Bartosz Protas. Spectral Methods (III) - Nonlinear Evolution PDEs, 2025.