



Cycles and Cuts

Cycle. Set of edges the form $a-b, b-c, c-d, \dots, y-z, z-a$.



Cycle $C = 1-2, 2-3, 3-4, 4-5, 5-6, 6-1$


Cutset. A cut is a subset of nodes S . The corresponding cutset D is the subset of edges with exactly one endpoint in S .



Cut $S = \{4, 5, 8\}$
Cutset $D = 5-6, 5-7, 3-4, 3-5, 7-8$


Cycle-Cut Intersection

Claim. A cycle and a cutset intersect in an even number of edges.



Cycle $C = 1-2, 2-3, 3-4, 4-5, 5-6, 6-1$
Cutset $D = 3-4, 3-5, 5-6, 5-7, 7-8, 8-4$
Intersection = $3-4, 5-6$

Pf. (by picture)




Greedy Algorithms

Simplifying assumption. All edge costs c_e are distinct.

Cut property. Let S be any subset of nodes, and let e be the min cost edge with exactly one endpoint in S . Then the MST T^* contains e .


Pf. (exchange argument)

- Suppose e does not belong to T^* , and let's see what happens.
- Adding e to T^* creates a cycle C in T^* .
- Edge e is both in the cycle C and in the cutset D corresponding to S
 \Rightarrow there exists another edge, say f , that is in both C and D .
- $T' = T^* \cup \{e\} - \{f\}$ is also a spanning tree.
- Since $c_e < c_f$, $\text{cost}(T') < \text{cost}(T^*)$.
- This is a contradiction. ■



Chapter 6

Dynamic Programming



Slides by Kevin Wayne.
Copyright © 2005 Pearson-Addison Wesley.
All rights reserved.

Algorithmic Paradigms

Greed. Build up a solution incrementally, myopically optimizing some local criterion.

Divide-and-conquer. Break up a problem into two sub-problems, solve each sub-problem independently, and combine solution to sub-problems to form solution to original problem.

Dynamic programming. Break up a problem into a series of overlapping sub-problems, and build up solutions to larger and larger sub-problems.

Dynamic Programming History

Bellman. Pioneered the systematic study of dynamic programming in the 1950s.

Etymology.

- Dynamic programming = planning over time.
- Secretary of Defense was hostile to mathematical research.
- Bellman sought an impressive name to avoid confrontation.
 - "it's impossible to use dynamic in a pejorative sense"
 - "something not even a Congressman could object to"

Reference: Bellman, R. E. *Eye of the Hurricane, An Autobiography*.

Dynamic Programming Applications

Areas.

- Bioinformatics.
- Control theory.
- Information theory.
- Operations research.
- Computer science: theory, graphics, AI, systems,

Some famous dynamic programming algorithms.


- Viterbi for hidden Markov models.
- Unix diff for comparing two files.
- Smith-Waterman for sequence alignment.
- Bellman-Ford for shortest path routing in networks.
- Cocke-Kasami-Younger for parsing context free grammars.

6.1 Weighted Interval Scheduling

Weighted Interval Scheduling

Weighted interval scheduling problem.

- Job j starts at s_j , finishes at f_j , and has weight or value v_j .
- Two jobs **compatible** if they don't overlap.
- Goal: find maximum **weight** subset of mutually compatible jobs.




Unweighted Interval Scheduling Review

Recall. Greedy algorithm works if all weights are 1.

- Consider jobs in ascending order of finish time.
- Add job to subset if it is compatible with previously chosen jobs.

Observation. Greedy algorithm can fail spectacularly if arbitrary weights are allowed.




Weighted Interval Scheduling

Notation. Label jobs by finishing time: $f_1 \leq f_2 \leq \dots \leq f_n$.

Def. $p(j)$ = largest index $i < j$ such that job i is compatible with j .

Ex: $p(8) = 5$, $p(7) = 3$, $p(2) = 0$.



Dynamic Programming: Binary Choice

Notation. $OPT(j)$ = value of optimal solution to the problem consisting of job requests 1, 2, ..., j.

- Case 1: OPT selects job j.
 - can't use incompatible jobs $\{ p(j) + 1, p(j) + 2, \dots, j - 1 \}$
 - must include optimal solution to problem consisting of remaining compatible jobs 1, 2, ..., $p(j)$
- Case 2: OPT does not select job j.
 - must include optimal solution to problem consisting of remaining compatible jobs 1, 2, ..., $j-1$

↖
↙
optimal substructure

$$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max \{ v_j + OPT(p(j)), OPT(j-1) \} & \text{otherwise} \end{cases}$$

Weighted Interval Scheduling: Brute Force

Brute force algorithm.

Input: $n, s_1, \dots, s_n, f_1, \dots, f_n, v_1, \dots, v_n$

Sort jobs by finish times so that $f_1 \leq f_2 \leq \dots \leq f_n$.

Compute $p(1), p(2), \dots, p(n)$

```
Compute-Opt(j) {  
    if (j = 0)  
        return 0  
    else  
        return max( $v_j + \text{Compute-Opt}(p(j))$ ,  $\text{Compute-Opt}(j-1)$ )  
}
```

Weighted Interval Scheduling: Brute Force

Observation. Recursive algorithm fails spectacularly because of redundant sub-problems \Rightarrow exponential algorithms.

Ex. Number of recursive calls for family of "layered" instances grows like Fibonacci sequence.

