


Chapter 4

Greedy Algorithms




Slides by Kevin Wayne.
Copyright © 2005 Pearson-Addison Wesley.
All rights reserved.

4.1 Interval Scheduling

Interval Scheduling

Interval scheduling.

- Job j starts at s_j and finishes at f_j .
- Two jobs **compatible** if they don't overlap.
- Goal: find maximum subset of mutually compatible jobs.



Interval Scheduling: Greedy Algorithms

Greedy template. Consider jobs in some order. Take each job provided it's compatible with the ones already taken.

- [Earliest start time] Consider jobs in ascending order of start time s_j .
- [Earliest finish time] Consider jobs in ascending order of finish time f_j .
- [Shortest interval] Consider jobs in ascending order of interval length $f_j - s_j$.
- [Fewest conflicts] For each job, count the number of conflicting jobs c_j . Schedule in ascending order of conflicts c_j .

Interval Scheduling: Greedy Algorithms

Greedy template. Consider jobs in some order. Take each job provided it's compatible with the ones already taken.



breaks earliest start time



breaks shortest interval




breaks fewest conflicts

Interval Scheduling: Greedy Algorithm

Greedy algorithm. Consider jobs in increasing order of finish time. Take each job provided it's compatible with the ones already taken.

```
Sort jobs by finish times so that  $f_1 \leq f_2 \leq \dots \leq f_n$ .
```

```
    ↙ jobs selected  
A ←  $\phi$   
for j = 1 to n {  
    if (job j compatible with A)  
        A ← A  $\cup$  {j}  
}  
return A
```



Implementation. $O(n \log n)$.


- Remember job j^* that was added last to A.
- Job j is compatible with A if $s_j \geq f_{j^*}$.

Interval Scheduling: Analysis

Theorem. Greedy algorithm is optimal.

Pf. (by contradiction)

- Assume greedy is not optimal, and let's see what happens.
- Let i_1, i_2, \dots, i_k denote set of jobs selected by greedy.
- Let j_1, j_2, \dots, j_m denote set of jobs in the optimal solution with $i_1 = j_1, i_2 = j_2, \dots, i_r = j_r$ for the largest possible value of r .



Interval Scheduling: Analysis

Theorem. Greedy algorithm is optimal.

Pf. (by contradiction)

- Assume greedy is not optimal, and let's see what happens.
- Let i_1, i_2, \dots, i_k denote set of jobs selected by greedy.
- Let j_1, j_2, \dots, j_m denote set of jobs in the optimal solution with $i_1 = j_1, i_2 = j_2, \dots, i_r = j_r$ for the largest possible value of r .

