

Magnetic separator selection checklist

Arrowmatics Magnets · 1 page · tick as you go, then send it with a photo.

1. How does your material move?

- ☐ Dry powder or granules through a hopper or chute: grate or drawer magnet
- ☐ Material on a conveyor belt: overband, suspended plate or magnetic pulley
- ☐ Liquid, paste or slurry in a pipe: liquid-line magnetic trap
- ☐ Powder or pellets in a pipe or pneumatic line: bullet magnet
- ☐ Chute wall, tank or hygiene-sensitive spot: plate magnet
- ☐ Small parts, OEM or heat/corrosion duty: NdFeB or SmCo magnet

2. Measure and note

- ☐ Opening size, belt width or pipe size
- ☐ Hanging height and burden depth (conveyors)
- ☐ Material, particle size and flow rate
- ☐ Moisture and temperature
- ☐ What iron you are finding: rust, wear fragments, tramp iron
- ☐ Room around the magnet to reach and clean it

3. Choose the build

- ☐ Stainless grade: 304, 316 or 316L (316 / 316L generally suit more corrosive or washdown duty)
- ☐ Full weld if you want no screws or crevices (built to order)
- ☐ Cleaning method: by hand, drawer pull-out or self-cleaning belt
- ☐ Seams and finish you can wipe and inspect

4. Confirm before you order

- ☐ Field strength at your working gap (typical rare-earth separators sit around 10,000–13,000 gauss at the pole; plate magnets up to about 10,000 Gauss typical; not a guarantee)
- ☐ Temperature limit: NdFeB for normal duty, SmCo for heat and corrosion
- ☐ Written spec with size, grade and build
- ☐ Which documents your quality system needs (ask at quotation)
- ☐ Who cleans and inspects it, and how often

5. Send it

- ☐ Photo of the spot: one wide, one close, with a ruler for scale
- ☐ This list, filled in as far as you can
- ☐ WhatsApp +60 12-211 2522 or the form at magnets.com.my

General guidance only; size, grade, gauss and build are confirmed at quotation. We publish no RM list prices. Arrowmatics is not itself certified to ISO 22000, HACCP or GMP.

Arrowmatics AI Sdn Bhd (1305806-W) · No. 64, Jalan Kapar 27/89, Megah Industrial Park, Taman Alam Megah, Section 27, 40400 Shah Alam, Selangor · Tel +603 5191 0299 · WhatsApp +60 12-211 2522 · magnets.com.my