



Comment	Description	Designator	Footprint	LibRef	Quantity
	100uF Filter				
100uF	Capacitor	C1	CAPR5-4X5	Cap2	1
	0805 (2012 Metric)		CAPC0805(2012)145		
CAP0805	Chip Capacitor	C2, C3	_L	CMP-1590-00003-1	2
0.1uF	Capacitor	C4, C5	CAPR5-4X5	Cap2	2
Header 4	Header, 4-Pin	P1, P2	HDR1X4	Header 4	2
	0805 (2012 Metric)				
RES0805	Chip Resistor	R1	RESC0805(2012)_L	CMP-1591-00002-1	1
	2512 (6432 Metric)				
RES2512	Chip Resistor	R2	RESC2512(6432)_L	CMP-1591-00007-1	1
DRV8872DDAR	Imported	U1	DDA0008H_N	DRV8872DDAR	1
	One of Two				
	Noninverting				
	Demultiplexer with 3-				
	State Deselected				
	Output, DBV0006A,				
SN74LVC1G18DBVR	LARGE T&R	U2	DBV0006A_L	CMP-0859-00184-3	1
	I linda Annuana				
	High Accuracy,				
	Galvanically Isolated				
	Current Sensor IC, 3				
	to 3.6 V, -5 to 5 A IP,				
4.0070011.070.0545	-40 to 150 degC, 8-				
ACS722LLCTR-05AB-	Pin SOIC (LC), RoHS,		AL FOLLO 6 34	ON 4D 4557 00007 1	
1	Tape and Reel	U3	ALEG-LC-8_V	CMP-1557-00006-1	1