


 Code

 Issues

 Pull requests

 Actions

 Projects

 Wiki

 Security

 master ▾

...

[ece523_doc21](#) / [ece523](#) / [hw](#) / [hw2](#) / hw2code.pdf



SafwanElmadani update

 History

 1 contributor

605 KB

...

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
from sklearn.model_selection import train_test_split
import matplotlib.pyplot as plt
import numpy as np
from matplotlib import cm
import matplotlib.mlab as mlab
from scipy.interpolate import griddata
```

HW2 Q2

Using real data from <https://github.com/gditzler/UA-ECE-523-Sp2018/tree/master/data>

```
In [2]: path = '/home/safwan/Documents/spring2021/ece523/hw/hw2/acute-nephritis.csv'
data_pd = pd.read_csv(path, header=None)
```

```
In [3]: data_pd
```

```
Out[3]:
```

	0	1	2	3	4	5	6
0	-1.77236	-0.562162	0.841625	-1.408310	-0.979364	-0.841625	0
1	-1.55248	-0.562162	-1.178280	0.704154	1.012560	1.178280	0
2	-1.55248	-0.562162	0.841625	-1.408310	-0.979364	-0.841625	0
3	-1.49751	-0.562162	-1.178280	0.704154	1.012560	1.178280	0
4	-1.49751	-0.562162	0.841625	-1.408310	-0.979364	-0.841625	0
...
115	1.47094	-0.562162	0.841625	0.704154	-0.979364	1.178280	1
116	1.52591	-0.562162	-1.178280	-1.408310	-0.979364	-0.841625	0
117	1.52591	1.764020	0.841625	-1.408310	1.012560	-0.841625	1
118	1.52591	-0.562162	0.841625	0.704154	-0.979364	1.178280	1
119	1.52591	-0.562162	0.841625	0.704154	-0.979364	1.178280	1

120 rows × 7 columns

```
In [4]: #seperating the features and labels.
x = data_pd.iloc[:, 0:-1]
y = data_pd.iloc[:, -1]
#converting to array
x_arr = x.values
y_arr = y.values
```

```
In [5]: # Adding 1 at the begining of every feature vector
x_arr = np.c_[np.ones((x_arr.shape[0], 1)), x_arr]
y_arr = y_arr[:, np.newaxis]
w = np.zeros((x_arr.shape[1],1)) #initializing the parameter vector w.
```

```
In [37]: #creating training test date
X_train, X_test, y_train, y_test = \
    train_test_split(x_arr, y_arr, test_size=0.20)
```

```
In [38]: #creating the logistic function
def logistic_func(w, x):
    #x is a feature vector
    #w is the parameter vector
    regression = np.dot(x, w) #finding weighted sum of inputs
    result = 1 / (1 + np.exp(- regression))
    return result
```

```
In [39]: #creating cross entropy function
def cross_entropy_func(w, x, y):
    result = - np.sum (y * np.log(logistic_func(w,x)) + (1-y)* np.log(1- logisti
    return result
```

```
In [40]: #gradient function
def gradient_func(w, x, y, learning_rate):
    result = np.dot(x.T, logistic_func(w, x) - y)
    return learning_rate * result
```

```
In [41]: #gradient descent function
def sgd(w,x,y,iterations, learning_rate):
    m = len(y) # size of the training dataset
    cost_history = []
    for _ in range(iterations):
```

```

    for j in range(m): #loop through every sample
        x_i = x[1,:].reshape((1,len(w)))
        y_i = y[1,:].reshape((1,1))
        w = w - gradient_func(w,x_i,y_i, learning_rate)
        cost = cross_entropy_func(w, x_i, y_i)
        cost_history.append(cost)

    return w, cost_history

```

In []:

```

In [42]: #testing the model
        train = sgd(w, X_train, y_train,500, 0.005)

```

```

In [43]: #the optimized parameters
        w_t = train[0]
        w_t

```

```

Out[43]: array([[0.86030556],
                [0.93441229],
                [1.51759622],
                [0.72405467],
                [0.6057876 ],
                [0.871111 ],
                [1.01368084]])

```

```

In [44]: #showing some values of the cost function
        train[1][:10]

```

localhost:8888/nbconvert/html/ece523/hw/hw2/hw2code.ipynb?download=false

2/6

2/17/2021

hw2code

```

Out[44]: [0.2267844997750445,
          0.12419529120361983,
          0.08384644412720996,
          0.06284558529725653,
          0.0500969894039993,
          0.041576957340538706,
          0.03549744285766436,
          0.030948776299568707,
          0.027421255026845663,
          0.024607842100965876]

```

```

In [45]: #testing with new data
        predict = logistic_func(w_t, X_test)
        # predict

```

```

In [46]: #finding the accuracy
        for i in range(len(predict)):
            if predict[i] >= 0.5:
                predict[i] = 1
            else:
                predict[i] = 0
        # predict= 0
        diff = predict - y_test
        accuracy = (1.0 - (float(np.count_nonzero(diff)) / len(diff)))*100
        accuracy

```

```

Out[46]: 83.33333333333334

```

```

In [16]: # predict.shape

```

HW2 Q3

Density estimation

```

In [17]: #generating training dataset
        def gen_cb(N, a, alpha):
            """
            N: number of points on the checkerboard
            a: width of the checker board (0<a<1)
            alpha: rotation of the checkerboard in radians
            """
            d = np.random.rand(N, 2).T # THIS IS THE LINE OF CODE THAT IS DIFFERENT
            d_transformed = np.array([d[0]*np.cos(alpha)-d[1]*np.sin(alpha),
                                     d[0]*np.sin(alpha)+d[1]*np.cos(alpha)]).T
            s = np.ceil(d_transformed[:,0]/a)+np.floor(d_transformed[:,1]/a)
            lab = 2 - (s%2)
            data = d.T
            return data, lab

```

```

In [18]: X, y = gen_cb(3000, .25, np.pi / 3)
        plt.figure()
        plt.plot(X[np.where(y==1)[0], 0], X[np.where(y==1)[0], 1], 'o')
        plt.plot(X[np.where(y==2)[0], 0], X[np.where(y==2)[0], 1], 's', c = 'r')
        plt.xlabel("x1")
        plt.ylabel("x2")

```


```

Out[18]: Text(0, 0.5, 'x2')

```

2/17/2021

hw2code



```
In [19]: #creating a function for implementing k nearest neighbor (knn)
def knn(k, X, y, point):
    x1, x2 = X[y==1], X[y==2] #x1blue x2red
    n1 = len(x1)
    n2 = len(x2)

    dataset = X.tolist()
    for i in range(len(dataset)):
        dataset[i].append(y[i])

    n=len(dataset)
    dist_list = []
    for i in dataset:
        dist = np.linalg.norm(point-np.array(i[:-1])) #find the euclidean distance
        dist_list.append(dist)
    dataset.sort(key=lambda tup: tup[3]) #sort
    k_nearest = dataset[:k] #take only the first k elements
    largest_k = max(k_nearest, key=lambda x: x[3])

    #now find how many neighbor in class blue 1
    k_1 = [x for x in k_nearest if x[2] == 1.0]

    #now find how many neighbor in class blue 2
    k_2 = [x for x in k_nearest if x[2] == 2.0]

    #calculating the volume
    r = largest_k[-1]

    #radius of the circle
    v = np.pi * (r**2)

    #p(x|y=blue)
    pb = (len(k_1)/(n1*v))

    #p(x|y=red)
    pr = (len(k_2)/(n2*v))

    #p(x)
    px = len(k_nearest)/(n*v)

    return pr, pb, px
```

2/17/2021

hw2code


computing the likelihood


```
In [20]: x1, x2 = X[y==1], X[y==2] #x1blue x2red
#py(blue)
p_blue = len(x1)/len(X)
#py(red)
p_red = len(x2)/len(X)
```

generating test dataset

```
In [21]: X_t, y_t = gen_cb(2000, .25, np.pi / 3)
plt.figure()
plt.plot(X_t[np.where(y_t==1)[0], 0], X_t[np.where(y_t==1)[0], 1], 'o')
plt.plot(X_t[np.where(y_t==2)[0], 0], X_t[np.where(y_t==2)[0], 1], 's', c = 'r')
plt.xlabel("x1")
plt.ylabel("x2")
```

```
Out[21]: Text(0, 0.5, 'x2')
```





```
In [22]: #testing the model
result = X_t.tolist()
for i in range(len(X_t)):
    px_r,px_b,px = knn(15,X, y, X_t[i,:])
    p_1 = px_b*p_blue/px
    p_2 = px_r*p_red/px
    if p_1 > p_2:
        result[i].append(1.0)
    else:
        result[i].append(2.0)
```

```
In [23]: #convert to np array
r = np.array(result)
x_r = r[:, :2]
y_r = r[:, -1]
```

```
In [24]: def plot_contour(x,y,z,resolution = 50,contour_method='linear'):
resolution = str(resolution)+'j'
X,Y = np.mgrid[min(x):max(x):complex(resolution), min(y):max(y):complex(resolution)]
points = [[a,b] for a,b in zip(x,y)]
Z = griddata(points, z, (X, Y), method=contour_method)
```

localhost:8888/nbconvert/html/ece523/hw/hw2/hw2code.ipynb?download=false

5/6


2/17/2021

hw2code

```
return X,Y,Z
```


```
X,Y,Z = plot_contour(r[:,0],r[:,1],r[:,2],resolution = 50,contour_method='linear')
```

```
In [25]: #plotting P(x|y) with pcolor
plt.pcolor(X,Y, Z, cmap = 'jet')
plt.colorbar()
plt.xlabel("x1")
plt.ylabel("x2")
plt.show()
```



```
In [26]: #plotting P(x|y) with plot
plt.plot(x_r[np.where(y_r==1)[0], 0], x_r[np.where(y_r==1)[0], 1], 'o')
plt.plot(x_r[np.where(y_r==2)[0], 0], x_r[np.where(y_r==2)[0], 1], 's', c = 'r')
plt.xlabel("x1")
plt.ylabel("x2")
```

Out[26]: Text(0, 0.5, 'x2')



In []:

