

-----  
*This documentation and its accompanying audio file by [Martin Zuther](#) is licensed under a [Creative Commons Attribution-ShareAlike 4.0](#) International License.*  
-----

### **FLAC-compressed wave file (44.1 kHz, 16 bit, 8 channels)**

=====

Please verify correctness of peak and average meters visually.

Given levels describe the first channel. The other channels have been amplified in steps of +5.00 dB per channel (first test) and +1.00 dB (all other tests), respectively. All readouts are given in K-20.

00:00.000 - 00:01.000   silence  
00:01.000 - 00:04.000   sine wave (997 Hz, -60.10 dB FS peak, -40.10 dB K-20)

[signal meter ch. 1 should not light]  
[signal meter ch. 2 should       light]  
[signal meter ch. 3 should       light]  
[signal meter ch. 4 should       light]  
[signal meter ch. 5 should       light]  
[signal meter ch. 6 should       light]  
[signal meter ch. 7 should       light]  
[signal meter ch. 8 should       light]

00:04.000 - 00:05.000   silence  
00:05.000 - 00:08.000   sine wave (997 Hz, -24.05 dB FS peak, -4.05 dB K-20)

[peak meter ch. 1 should read -4.05 dB]   [---]  
[peak meter ch. 2 should read -3.05 dB]   [LOW]  
[peak meter ch. 3 should read -2.05 dB]  
[peak meter ch. 4 should read -1.05 dB]  
[peak meter ch. 5 should read -0.05 dB]  
[peak meter ch. 6 should read +0.95 dB]  
[peak meter ch. 7 should read +1.95 dB]  
[peak meter ch. 8 should read +2.95 dB]

[RMS meter ch. 1 should read -4.05 dB]   [---]  
[RMS meter ch. 2 should read -3.05 dB]   [---]  
[RMS meter ch. 3 should read -2.05 dB]   [---]  
[RMS meter ch. 4 should read -1.05 dB]   [---]  
[RMS meter ch. 5 should read -0.05 dB]   [---]  
[RMS meter ch. 6 should read +0.95 dB]   [---]  
[RMS meter ch. 7 should read +1.95 dB]   [---]  
[RMS meter ch. 8 should read +2.95 dB]   [LOW]

[maximum peaks should not be visible]  
[all signal meters should light]

00:08.000 - 00:08.500 silence  
00:08.500 - 00:11.500 sine wave (997 Hz, -23.95 dB FS peak, -3.95 dB K-20)

[peak meter ch. 1 should read -3.95 dB] [LOW]  
[peak meter ch. 2 should read -2.95 dB]  
[peak meter ch. 3 should read -1.95 dB]  
[peak meter ch. 4 should read -0.95 dB]  
[peak meter ch. 5 should read +0.05 dB]  
[peak meter ch. 6 should read +1.05 dB]  
[peak meter ch. 7 should read +2.05 dB]  
[peak meter ch. 8 should read +3.05 dB] [OVR]

[RMS meter ch. 1 should read -3.95 dB] [---]  
[RMS meter ch. 2 should read -2.95 dB] [---]  
[RMS meter ch. 3 should read -1.95 dB] [---]  
[RMS meter ch. 4 should read -0.95 dB] [---]  
[RMS meter ch. 5 should read +0.05 dB] [---]  
[RMS meter ch. 6 should read +1.05 dB] [---]  
[RMS meter ch. 7 should read +2.05 dB] [LOW]  
[RMS meter ch. 8 should read +3.05 dB]

[maximum peaks should be visible]  
[all signal meters should light]

00:11.500 - 00:12.500 silence  
00:12.500 - 00:15.500 sine wave (997 Hz, -16.05 dB FS peak, +3.95 dB K-20)

[peak meter ch. 1 should read +3.95 dB] [OVR]  
[peak meter ch. 2 should read +4.95 dB] [OVR]  
[peak meter ch. 3 should read +5.95 dB] [OVR]  
[peak meter ch. 4 should read +6.95 dB] [OVR]  
[peak meter ch. 5 should read +7.95 dB] [OVR]  
[peak meter ch. 6 should read +8.95 dB] [OVR]  
[peak meter ch. 7 should read +9.95 dB] [OVR]  
[peak meter ch. 8 should read +10.95 dB] [OVR]

[RMS meter ch. 1 should read +3.95 dB]  
[RMS meter ch. 2 should read +4.95 dB]  
[RMS meter ch. 3 should read +5.95 dB]  
[RMS meter ch. 4 should read +6.95 dB]  
[RMS meter ch. 5 should read +7.95 dB]  
[RMS meter ch. 6 should read +8.95 dB]  
[RMS meter ch. 7 should read +9.95 dB]  
[RMS meter ch. 8 should read +10.95 dB]

[maximum peaks should not be visible]  
[all signal meters should light]

00:15.500 - 00:16.000 silence  
00:16.000 - 00:19.000 sine wave (997 Hz, -15.95 dB FS peak, +4.05 dB K-20)

[peak meter ch. 1 should read +4.05 dB] [OVR]  
[peak meter ch. 2 should read +5.05 dB] [OVR]  
[peak meter ch. 3 should read +6.05 dB] [OVR]  
[peak meter ch. 4 should read +7.05 dB] [OVR]  
[peak meter ch. 5 should read +8.05 dB] [OVR]  
[peak meter ch. 6 should read +9.05 dB] [OVR]  
[peak meter ch. 7 should read +10.05 dB] [OVR]  
[peak meter ch. 8 should read +11.05 dB] [OVR]

[RMS meter ch. 1 should read +4.05 dB]  
[RMS meter ch. 2 should read +5.05 dB]  
[RMS meter ch. 3 should read +6.05 dB]  
[RMS meter ch. 4 should read +7.05 dB]  
[RMS meter ch. 5 should read +8.05 dB]  
[RMS meter ch. 6 should read +9.05 dB]  
[RMS meter ch. 7 should read +10.05 dB]  
[RMS meter ch. 8 should read +11.05 dB] [OVR]

[maximum peaks should be visible]  
[all signal meters should light]

00:19.000 - 00:20.000 silence

#### Validation settings

=====

File: level\_meters\_multi.flac

Host SR: 44 100 Hz

Channel: All

Display: [ ] Peak meter level  
[ ] Average meter level