

pdInd: G matrix with pattern of zeros

Georges Monette

2018-04-27

Contents

Predictor transformations to improve convergence	3
Improving convergence – IN PROGRESS	4
Nuts and Bolts of the G matrix in lme – IN PROGRESS	4
pdInd methods	4
pdMat methods	6
pdSymm methods	12
lme	14

pdInd is a constructor for **pdClasses** that define G matrices to model the variance of random effects for models in the **nlme** package.

Mixed models in which many predictors have random slopes often fail to converge in part because of the large number of parameters in the full covariance (G) matrix for random effects. One way of fitting a more parsimonious model that includes random slopes is to use **pdDiag** with zeros off the diagonal. However, this also forces zero covariances between random slopes and the random intercept, resulting in a model that is not equivariant with respect to location transformations of the predictors with random slopes. The alternative remedy of omitting random slopes for some predictors can lead to biased estimates and incorrect standard errors of regression coefficients.

The default covariance pattern for **pdInd** produces a G matrix with zero covariances except in the first row and column. If the first random effect is the intercept, the resulting model assumes independence between random slopes without imposing minimality of variance over the possibly arbitrary origin. This imposition is the reason that having all covariances equal to zero results in a model that fails to be equivariant under location transformations.

The optional **cov** parameter can be used to allow selected non-zero covariance between random slopes.

For example, if two variables, **X1** and **X2** have random effects, the random effects model would be specified in a call to **lme** as **random = ~ 1 + X1 + X2**.

The default G matrix has the form:

$$G = \begin{pmatrix} g_{00} & g_{01} & g_{02} \\ g_{10} & g_{11} & g_{12} \\ g_{20} & g_{21} & g_{22} \end{pmatrix}$$

With **pdDiag**, all the off-diagonal elements of G are constrained to 0. Forcing g_{01} and g_{02} to be 0 produces a model that is not equivariant with respect to location changes in **X1** and **X2**. The value at which the variance of **Y** given **X1** and **X2** is minimized is forced to be 0 for both variables.

However, constraining $g_{12} = 0$ produces a model that is equivariant with respect to location-scale transformation of **X1** and **X2** and in which the random between cluster values of regression slopes for each variable are independent of each other.

The `pdInd` class of positive-definite matrices creates, by default, a matrix with arbitrary values along the diagonal and in the first row and column, but zeros elsewhere. In the case of a 4×4 matrix, this produces:

$$G = \begin{pmatrix} g_{00} & g_{01} & g_{02} & g_{03} \\ g_{10} & g_{11} & 0 & 0 \\ g_{20} & 0 & g_{22} & 0 \\ g_{30} & 0 & 0 & g_{33} \end{pmatrix}$$

The challenge in parametrizing the G matrix is finding an unconstrained parametrization that results in a positive-definite matrix with selected covariances constrained to 0.

We consider a right-Cholesky decomposition noting that the diagonal component in the following factorization results in a diagonal component in the variance matrix.

$$\begin{pmatrix} G_{11} & G_{12} \\ G'_{12} & G_{22} \end{pmatrix} = \begin{pmatrix} R_{11} & R_{12} \\ 0 & D_{22} \end{pmatrix} \begin{pmatrix} R'_{11} & 0 \\ R'_{12} & D_{22} \end{pmatrix} = \begin{pmatrix} R_{11}R'_{11} + R_{12}R'_{12} & R_{12}D_{22} \\ D_{22}R'_{12} & D_{22}^2 \end{pmatrix}$$

With R_{11} square upper-triangular and D_{22} square diagonal, G_{22} must be diagonal. In addition, patterns of zeros in the R_{12} matrix, lying above the diagonal D_{22} matrix, are preserved in G_{12} .

Note that the unconstrained Cholesky parametrization uses the log of the diagonal elements of the triangular factor.

```
(fac <- cbind( c(1,0,0,0,0), c(1,2,0,0,0), c(0,1,3,0,0), c(1,0,0,4,0), c(0,1,0, 0, 5) ))
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	1	1	0	1	0
[2,]	0	2	1	0	1
[3,]	0	0	3	0	0
[4,]	0	0	0	4	0
[5,]	0	0	0	0	5

```
fac %*% t(fac)
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	3	2	0	4	0
[2,]	2	6	3	0	5
[3,]	0	3	9	0	0
[4,]	4	0	0	16	0
[5,]	0	5	0	0	25

Note how the pattern of zeros in the last three columns of the first two rows is preserved in the cross product since the lower 3×3 diagonal block matrix is itself diagonal.

However, if the lower 3×3 block diagonal matrix is not diagonal, then the pattern of zeros in the top two rows above it is not necessarily preserved.

```
(fac <- cbind( c(1,0,0,0,0), c(1,2,0,0,0), c(0,1,3,0,0), c(1,0,0,4,0), c(0,1,0, -1, 5) ))
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	1	1	0	1	0
[2,]	0	2	1	0	1
[3,]	0	0	3	0	0
[4,]	0	0	0	4	-1
[5,]	0	0	0	0	5

```
fac %*% t(fac)
```

	[,1]	[,2]	[,3]	[,4]	[,5]
[1,]	3	2	0	4	-1
[2,]	2	6	3	0	4
[3,]	0	3	9	0	0
[4,]	4	0	0	16	-4
[5,]	-1	4	0	-4	5

[1,]	3	2	0	4	0
[2,]	2	6	3	-1	5
[3,]	0	3	9	0	0
[4,]	4	-1	0	17	-5
[5,]	0	5	0	-5	25

But patterns of zeros above non-diagonal blocks are not necessarily preserved.

The `cov` parameter allows the user to specify a pattern of zeros in the upper triangle of the upper-triangular ‘R’ factor of the the G matrix. As observed above, in some cases this will result in the same pattern in the G matrix. Even if the pattern in the R factor does not create a similar pattern in the G matrix, the model for the G matrix will nevertheless have the number of additional parameters for covariance as given by the `TRUE` entries in the upper diagonal of the `cov` matrix.

Predictor transformations to improve convergence

We will show how to use `lchol(getG(fit))` to suggest transformations of predictors that appear in random effects models to help improve the convergence of mixed models fits.

We conjecture that the condition number of the Hessian matrix for the parameters in the G matrix may be approximately the square of the condition number for the G matrix. Thus a condition number for G in the vicinity of 10^7 would effectively result in singularity of the Hessian.

Rescaling and relocating the predictors with random slopes can improve ill-conditioning of the G matrix.

Let

$$\mathbf{Z} = \begin{pmatrix} 1 \\ Z_1 \\ \vdots \\ Z_k \end{pmatrix}$$

represent the vector of variables with random effects \mathbf{u} . For the i th cluster the contribution from level-2 random effects is:

$$\mathbf{Z}'_i \mathbf{u}_i$$

Consider a location-scale transformation of the variables in \mathbf{Z} . It has the form $\mathbf{Z}^* = T\mathbf{Z}$ where T is lower triangular with the form

$$T = \begin{bmatrix} 1 & 0 \\ a_1 & \\ a_2 & \\ \vdots & B \\ a_k & \end{bmatrix}$$

with B a diagonal matrix containing scaling coefficients, b_1, b_2, \dots, b_k , so that

$$Z_i^* = a_i + b_i Z_i$$

If $G = \text{Var}(\mathbf{u})$ then

$$G^* = T'^{-1}GT^{-1}$$

where $G^* = \text{Var}(\mathbf{u}^*)$ with

$$\mathbf{Z}'_i \mathbf{u}_i = \mathbf{Z}_i^{*'} \mathbf{u}_i^*$$

Therefore, if we factor

$$G = T'T$$

with T lower-triangular, $\frac{1}{t_{11}}T$ provides a transformation of \mathbf{Z} that minimizes the condition number of G^* . In R, using `spida2::lchol` this is simply `getG(fit) %>% lchol %>% {./.[1,1]}`.

Improving convergence – IN PROGRESS

1. Location scale transformations of Z variables. Note: don't need to change to X variables but might like to for purposes of inference.
2. Parsimonious G matrices: Use `pdInd` and `pdDiag`.
3. Note that LRTs with anova are likely to be informative to compare nested RE models with singular Hessians provided differences are only in covariance structure, i.e. same non-zero diagonal elements.
4. STUDY: any effect on `vcov` of changing to equivalent Zs without changing X.

Nuts and Bolts of the G matrix in lme – IN PROGRESS

The initial call to `pdConstruct.pdInd` occurs in the initialization phase of `lme` which call `reStruct` which in turn calls `pdMat` that creates an empty `pdInd` object, sets `value <- numeric(0)` and returns:

```
pdConstruct(object, value, form, nam, data)
```

pdInd methods

```
methods(class='pdInd')
```

```
[1] pdConstruct pdFactor    pdMatrix    solve  
see '?methods' for accessing help and source code
```

```
gnew:::pdInd
```

Running `.onLoad`

```
function (value = numeric(0), form = NULL, nam = NULL,  
          data = sys.parent(), cov = NULL)  
{  
  # unchanged  
  object <- numeric(0)  
  class(object) <- c("pdInd", "pdMat")  
  pdConstruct(object, value, form, nam, data, cov)  
}
```

<environment: namespace:gnew>

```
gnew:::pdConstruct.pdInd
```

```
function (object, value = numeric(0), form = formula(object),  
          nam = Names(object), data = sys.parent(),  
          cov = NULL,  
          ...)  
{  
  # note that pdConstruct.pdMat return an upper-triangular R factor, === might not be correct  
  if(!is.null(attr(object, 'cov'))) cov <- attr(object, 'cov')  
  if(!is.null(attr(value, 'cov'))) cov <- attr(value, 'cov')  
  val <- nlme:::pdConstruct.pdMat(object,  
                                value = value,  
                                form = form,  
                                nam = nam,  
                                data = data)
```

```

attr(val,'cov') <- cov
if (length(val) == 0) {
  class(val) <- c("pdInd", "pdMat")
  return(val)
}
# mod 2015 07 04: added arbitrary cov structure of non zero
# covariance
isRmat <- function(x) all( x[row(x) > col(x)] == 0) # is lower triangle == 0?
if (is.matrix(val)) {
  if(is.null(cov)) {
    if(!is.null(attr(val,'cov'))) cov <- attr(val,'cov')
    else cov <- (row(val) == 1) & (col(val) > 1)
  }
  # disp(cov)
  if(isRmat(val)){
    value <- c(log(diag(val)), val[cov])
    # keeping only the entries that should be non-zero
  } else stop("matrix should be an upper triangular matrix")
  attributes(value) <-
    attributes(val)[names(attributes(val)) != "dim"]
  attr(value,"cov") <- cov
  class(value) <- c("pdInd", "pdMat")
  attr(value,"invert") <- FALSE
  return(value)
}
stop("shouldn't get here in pdConstruct.pdInd")
Ncol <- (length(val) + 1)/2
if (length(val) != 2*round(Ncol) - 1) {
  stop(gettextf("an object of length %d does not match a pdInd factor (diagonal + covariances with
length(val)), domain = NA)
}
class(val) <- c("pdInd", "pdMat")
val
}
<environment: namespace:gnew>
gnew::pdFactor.pdInd

function (object)
{
  invert <- attr(object,"invert")
  cov <- attr(object,"cov")
  object <- as.vector(object)
  Ncov <- sum(cov)
  Ncol <- length(object) - Ncov
  # was:
  # L <- matrix(0,Ncol,Ncol)
  # diag(L) <- exp( object[1:Ncol])
  # if ( Ncol > 1 ) L[row(L)>1 & col(L)==1] <-
  #   object[(Ncol+1):length(object)]
  # if(invert) c(t(solve(L))) else c(L2R(L))
  R <- matrix(0,Ncol,Ncol)
  diag(R) <- exp( object[1:Ncol])
  if ( Ncol > 1 ) R[cov] <-
    object[(Ncol+1):length(object)]

```

```

      if(invert) c(t(solve(f2L(R)))) else c(R)
    }
  }
  <environment: namespace:gnew>
gnew:::pdMatrix.pdInd

function (object, factor = FALSE)
{
  if (!isInitialized(object)) {
    stop("cannot extract matrix from an uninitialized object")
  }
  cov <- attr(object,"cov")
  Ncov <- sum(cov)
  Ncol <- length(object) - Ncov
  value <- array(pdFactor(object), c(Ncol, Ncol),
                 attr(object, "Dimnames"))
  ob <- as.vector(object) # subsetting object calls pdMatrix!
  attr(value, "logDet") <- 2*sum(ob[1:Ncol])
  if (factor) value else crossprod(value)
}
  <environment: namespace:gnew>

```

```

gnew:::solve.pdInd

function (a, b, ...)
{
  if (!isInitialized(a)) {
    stop("cannot get the inverse of an uninitialized object")
  }
  attr(a, 'invert') <- !attr(a, 'invert')
  a
  #   Ncol <- (length(a) + 1)/2
  #   ob <- as.vector(a)
  #   if( Ncol == 1) ret <- -ob[1]
  #   else ret <-
  #     c( -ob[1:Ncol] ,
  #       - exp(ob[1])*ob[(Ncol+1):length(ob)]/exp(ob[2:Ncol]))
  #   attributes(ret) <- attributes(a)
  #   ret
}
  <environment: namespace:gnew>

```

pdMat methods

```
methods(class='pdMat')
```

[1] [[<-	as.matrix	coef	coef<-
[6] corMatrix	Dim	formula	isInitialized	logDet
[11] matrix<-	Names	Names<-	pdConstruct	pdFactor
[16] pdMatrix	plot	print	solve	summary
[21] VarCorr				

see '?methods' for accessing help and source code

```
nlme:::pdMat
```

```
function (value = numeric(0), form = NULL, nam = NULL, data = sys.frame(sys.parent()),
  pdClass = "pdSymm")
{
  if (inherits(value, "pdMat")) {
    pdClass <- class(value)
  }
  object <- numeric(0)
  class(object) <- unique(c(pdClass, "pdMat"))
  pdConstruct(object, value, form, nam, data)
}
<bytecode: 0x00000000232d4d38>
<environment: namespace:nlme>
```

```
nlme:::pdConstruct.pdMat
```

```
function (object, value = numeric(0), form = formula(object),
  nam = Names(object), data = sys.frame(sys.parent()), ...)
{
  if (inherits(value, "pdMat")) {
    if (length(form) == 0) {
      form <- formula(value)
    }
    if (length(nam) == 0) {
      nam <- Names(value)
    }
    if (isInitialized(value)) {
      return(pdConstruct(object, as.matrix(value), form,
        nam, data))
    }
    else {
      return(pdConstruct(object, form = form, nam = nam,
        data = data))
    }
  }
  if (length(value) > 0) {
    if (inherits(value, "formula") || data.class(value) ==
      "call") {
      if (!is.null(form)) {
        warning("ignoring argument 'form'")
      }
      form <- formula(value)
      if (length(form) == 3) {
        form <- list(form)
      }
    }
    else if (is.character(value)) {
      if (length(nam) > 0) {
        warning("ignoring argument 'nam'")
      }
      nam <- value
    }
    else if (is.matrix(value)) {
      vdim <- dim(value)
    }
  }
}
```

```

    if (length(vdim) != 2 || diff(vdim) != 0) {
      stop("'value' must be a square matrix")
    }
    if (length(unlist(vnam <- dimnames(value))) > 0) {
      vnam <- unique(unlist(vnam))
      if (length(vnam) != vdim[1]) {
        stop("dimnames of 'value' must match or be NULL")
      }
      dimnames(value) <- list(vnam, vnam)
      if (length(nam) > 0) {
        if (any(is.na(match(nam, vnam))) || any(is.na(match(vnam,
          nam)))) {
          stop("names of 'value' are not consistent with 'nam' argument")
        }
        value <- value[nam, nam, drop = FALSE]
      }
      else {
        nam <- vnam
      }
    }
    form <- form
    nam <- nam
    object <- chol((value + t(value))/2)
    attr(object, "dimnames") <- NULL
    attr(object, "rank") <- NULL
  }
  else if (is.numeric(value)) {
    value <- as.numeric(value)
    attributes(value) <- attributes(object)
    object <- value
  }
  else if (data.class(value) == "list") {
    if (!is.null(form)) {
      warning("ignoring argument 'form'")
    }
    form <- value
  }
  else {
    stop(gettextf("%s is not a valid object for \"pdMat\"",
      sQuote(deparse(object))), domain = NA)
  }
}

if (!is.null(form)) {
  if (inherits(form, "formula") && length(form) == 3) {
    form <- list(form)
  }
  if (is.list(form)) {
    if (any(!unlist(lapply(form, function(el) {
      inherits(el, "formula") && length(el) == 3
    })))) {
      stop("all elements of 'form' list must be two-sided formulas")
    }
    val <- list()
    for (i in seq_along(form)) {

```



```

      if (is.name(form[[i]][[2]])) {
        val <- c(val, list(form[[i]]))
      }
      else {
        val <- c(val, eval(parse(text = paste("list(",
          paste(paste(all.vars(form[[i]][[2]]), deparse(form[[i]][[3]]),
            sep = "~"), collapse = ",", " "))))))
      }
    }
    form <- val
    class(form) <- "listForm"
    namesForm <- Names(form, data)
  }
  else {
    if (inherits(form, "formula")) {
      namesForm <- Names(asOneSidedFormula(form), data)
    }
    else {
      stop("'form' can only be a formula or a list of formulae")
    }
  }
}
if (length(namesForm) > 0) {
  if (length(nam) == 0) {
    nam <- namesForm
  }
  else {
    if (any(noMatch <- is.na(match(nam, namesForm)))) {
      err <- TRUE
      namCopy <- nam
      indNoMatch <- seq_along(nam)[noMatch]
      if (any(wch1 <- (nchar(nam, "c") > 12))) {
        wch1 <- substring(nam, nchar(nam, "c") -
          10) == "(Intercept)"
        if (any(wch1)) {
          namCopy[indNoMatch[wch1]] <- substring(nam[wch1],
            1, nchar(nam[wch1], "c") - 12)
          noMatch[wch1] <- FALSE
          indNoMatch <- indNoMatch[!wch1]
        }
      }
      if (sum(noMatch) > 0) {
        namCopy[indNoMatch] <- paste(namCopy[indNoMatch],
          "(Intercept)", sep = ".")
      }
      if (!any(is.na(match(namCopy, namesForm)))) {
        err <- FALSE
      }
      if (err)
        stop("'form' not consistent with 'nam'")
    }
  }
}
}
if (is.matrix(object)) {

```

```

        if (length(nam) > 0 && (length(nam) != dim(object)[2])) {
          stop("length of 'nam' not consistent with dimensions of initial value")
        }
      }
      attr(object, "formula") <- form
      attr(object, "Dimnames") <- list(nam, nam)
      object
    }
    <bytecode: 0x0000000023341cd8>
    <environment: namespace:nlme>
nlme:::pdMatrix.pdMat

function (object, factor = FALSE)
{
  if (!isInitialized(object)) {
    stop("cannot access the matrix of uninitialized objects")
  }
  if (factor) {
    stop("no default method for extracting the square root of a \"pdMat\" object")
  }
  else {
    crossprod(pdMatrix(object, factor = TRUE))
  }
}
<bytecode: 0x000000001e592f20>
<environment: namespace:nlme>
nlme:::pdFactor.pdMat

function (object)
{
  c(qr.R(qr(pdMatrix(object))))
}
<bytecode: 0x000000001e6b6840>
<environment: namespace:nlme>
nlme:::solve.pdMat

function (a, b, ...)
{
  if (!isInitialized(a)) {
    stop("cannot get the inverse of an uninitialized object")
  }
  matrix(a) <- solve(as.matrix(a))
  a
}
<bytecode: 0x000000001e5efe88>
<environment: namespace:nlme>
nlme:::VarCorr.pdMat

function (x, sigma = 1, rdig = 3, ...)
{
  sx <- summary(x)
  sd <- sigma * attr(sx, "stdDev")
  var <- sd^2

```

```

p <- dim(sx)[2]
v <- array(c(var, sd), c(p, 2), list(names(sd), c("Variance",
  "StdDev")))
attr(v, "formStr") <- if (inherits(attr(x, "formula"), "listForm")) {
  paste(class(x)[[1]], "(list(", paste(sapply(attr(x, "formula"),
    function(x) as.character(deparse(x))), collapse = ","),
    ")))", sep = "")
}
else {
  paste(class(x)[[1]], "(", substring(deparse(attr(x, "formula")),
    2), ")", sep = "")
}
if (attr(sx, "noCorrelation") || p <= 1)
  return(v)
ll <- lower.tri(sx)
sx[ll] <- format(round(sx[ll], digits = rdig))
sx[!ll] <- ""
if (!is.null(colnames(sx))) {
  sx[1, ] <- abbreviate(colnames(sx), minlength = rdig +
    3)
}
dimnames(sx) <- list(names(sd), c("Corr", rep("", p - 1)))
attr(v, "corr") <- sx[, -p, drop = FALSE]
v
}
<bytecode: 0x000000001e4cd778>
<environment: namespace:nlme>

```

```
nlme:::as.matrix.pdMat
```

```

function (x, ...)
pdMatrix(x)
<bytecode: 0x000000001e399b90>
<environment: namespace:nlme>

```

```
nlme:::`matrix<-`.pdMat`
```

```

function (object, value)
{
  value <- as.matrix(value)
  if (isInitialized(object) && any(dim(value) != Dim(object))) {
    stop("cannot change dimensions on an initialized \"pdMat\" object")
  }
  pdConstruct(object, value)
}
<bytecode: 0x000000001e4b1950>
<environment: namespace:nlme>

```

```
nlme:::coef.pdMat
```

```

function (object, unconstrained = TRUE, ...)
{
  if (unconstrained || !isInitialized(object)) {
    as.vector(object)
  }
  else {

```

```

        stop("do not know how to obtain constrained coefficients")
    }
}
<bytecode: 0x000000001e65e498>
<environment: namespace:nlme>
nlme:::`coef<-pdMat`

function (object, ..., value)
{
  value <- as.numeric(value)
  if (isInitialized(object)) {
    if (length(value) != length(object)) {
      stop("cannot change the length of the parameter after initialization")
    }
  }
  else {
    return(pdConstruct(object, value))
  }
  class(value) <- class(object)
  attributes(value) <- attributes(object)
  value
}
<bytecode: 0x000000001e5aac68>
<environment: namespace:nlme>

```

pdSymm methods

```
nlme:::pdSymm
```

```

function (value = numeric(0), form = NULL, nam = NULL, data = parent.frame())
{
  object <- numeric(0)
  class(object) <- c("pdSymm", "pdMat")
  pdConstruct(object, value, form, nam, data)
}
<bytecode: 0x000000001bae23e8>
<environment: namespace:nlme>

```

```
methods(class='pdSymm')
```

```

[1] coef      Dim      logDet    pdConstruct pdFactor   pdMatrix
[7] solve     summary
see '?methods' for accessing help and source code

```

```
nlme:::pdConstruct.pdSymm
```

```

function (object, value = numeric(0), form = formula(object),
  nam = Names(object), data = sys.frame(sys.parent()), ...)
{
  val <- NextMethod()
  if (length(val) == 0) {
    class(val) <- c("pdSymm", "pdMat")
    return(val)
  }
}

```

```

    if (is.matrix(val)) {
      vald <- svd(val, nu = 0)
      object <- vald$v %*% (log(vald$d) * t(vald$v))
      value <- object[row(object) <= col(object)]
      attributes(value) <- attributes(val)[names(attributes(val)) !=
        "dim"]
      class(value) <- c("pdSymm", "pdMat")
      return(value)
    }
    Ncol <- round((sqrt(8 * length(val) + 1) - 1)/2)
    if (length(val) != round((Ncol * (Ncol + 1))/2)) {
      stop(gettextf("an object of length %d does not match the required parameter size",
        length(val)), domain = NA)
    }
    class(val) <- c("pdSymm", "pdMat")
    val
  }
<bytecode: 0x000000001b5ac978>
<environment: namespace:nlme>
nlme:::pdMatrix.pdSymm

function (object, factor = FALSE)
{
  if (!isInitialized(object))
    stop("cannot extract matrix from an uninitialized object")
  if (factor) {
    Ncol <- Dim(object)[2]
    value <- array(pdFactor(object), c(Ncol, Ncol), attr(object,
      "Dimnames"))
    attr(value, "logDet") <- sum(log(abs(svd.d(value))))
    value
  }
  else {
    NextMethod()
  }
}
<bytecode: 0x000000001b49ac58>
<environment: namespace:nlme>
nlme:::pdFactor.pdSymm

function (object)
{
  Ncol <- round((-1 + sqrt(1 + 8 * length(object)))/2)
  .C(matrixLog_pd, Factor = double(Ncol * Ncol), as.integer(Ncol),
    as.double(object))$Factor
}
<bytecode: 0x000000001b4e1f20>
<environment: namespace:nlme>
nlme:::solve.pdSymm

function (a, b, ...)
{
  if (!isInitialized(a)) {

```

```

        stop("cannot extract the inverse from an uninitialized object")
      }
      coef(a) <- -coef(a, TRUE)
      a
    }
    <bytecode: 0x000000001b144aa8>
    <environment: namespace:nlme>
nlme:::coef.pdSymm

function (object, unconstrained = TRUE, ...)
{
  if (unconstrained || !isInitialized(object))
    NextMethod()
  else {
    val <- as.matrix(object)
    aN <- Names(object)
    aN1 <- paste("cov(", aN, sep = "")
    aN2 <- paste(aN, ")", sep = "")
    aNmat <- t(outer(aN1, aN2, paste, sep = ","))
    aNmat[row(aNmat) == col(aNmat)] <- paste("var(", aN,
      ")", sep = "")
    val <- val[row(val) <= col(val)]
    names(val) <- aNmat[row(aNmat) <= col(aNmat)]
    val
  }
}
<bytecode: 0x000000001a728b90>
<environment: namespace:nlme>

```

lme

```

nlme:::lme.formula

function (fixed, data = sys.frame(sys.parent()), random = pdSymm(eval(as.call(fixed[-2]))),
  correlation = NULL, weights = NULL, subset, method = c("REML",
    "ML"), na.action = na.fail, control = list(), contrasts = NULL,
  keep.data = TRUE)
{
  Call <- match.call()
  miss.data <- missing(data) || !is.data.frame(data)
  controlvals <- lmeControl()
  if (!missing(control)) {
    controlvals[names(control)] <- control
  }
  fixedSigma <- controlvals$sigma > 0
  if (!inherits(fixed, "formula") || length(fixed) != 3) {
    stop("\nfixed-effects model must be a formula of the form \"resp ~ pred\"")
  }
  method <- match.arg(method)
  REML <- method == "REML"
  reSt <- reStruct(random, REML = REML, data = NULL)
  groups <- getGroupsFormula(reSt)

```

```

if (is.null(groups)) {
  if (inherits(data, "groupedData")) {
    groups <- getGroupsFormula(data)
    namGrp <- rev(names(getGroupsFormula(data, asList = TRUE)))
    Q <- length(namGrp)
    if (length(reSt) != Q) {
      if (length(reSt) != 1) {
        stop("incompatible lengths for 'random' and grouping factors")
      }
      randL <- vector("list", Q)
      names(randL) <- rev(namGrp)
      for (i in 1:Q) randL[[i]] <- random
      reSt <- reStruct(as.list(randL), REML = REML,
        data = NULL)
    }
    else {
      names(reSt) <- namGrp
    }
  }
  else {
    groups <- ~1
    names(reSt) <- "1"
  }
}
if (!is.null(correlation)) {
  add.form <- FALSE
  if (!is.null(corGrpsForm <- getGroupsFormula(correlation,
    asList = TRUE))) {
    corGrpsForm <- unlist(lapply(corGrpsForm, function(el) deparse(el[[2L]])))
    lmeGrpsForm <- unlist(lapply(splitFormula(groups),
      function(el) deparse(el[[2L]])))
    corQ <- length(corGrpsForm)
    lmeQ <- length(lmeGrpsForm)
    if (corQ <= lmeQ) {
      if (any(corGrpsForm != lmeGrpsForm[1:corQ])) {
        stop("incompatible formulas for groups in 'random' and 'correlation'")
      }
      if (corQ < lmeQ) {
        warning("cannot use smaller level of grouping for 'correlation' than for 'random'.")
        add.form <- TRUE
      }
    }
    else if (any(lmeGrpsForm != corGrpsForm[1:lmeQ])) {
      stop("incompatible formulas for groups in 'random' and 'correlation'")
    }
  }
  else {
    add.form <- TRUE
    corQ <- lmeQ <- 1
  }
  if (add.form)
    attr(correlation, "formula") <- eval(substitute(~COV |
      GRP, list(COV = getCovariateFormula(formula(correlation))[[2L]],
        GRP = groups[[2L]])))

```

```

}
else {
  corQ <- lmeQ <- 1
}
lmeSt <- lmeStruct(reStruct = reSt, corStruct = correlation,
  varStruct = varFunc(weights))
mfArgs <- list(formula = asOneFormula(formula(lmeSt), fixed,
  groups), data = data, na.action = na.action)
if (!missing(subset)) {
  mfArgs[["subset"]] <- asOneSidedFormula(Call[["subset"]])[[2L]]
}
mfArgs$drop.unused.levels <- TRUE
dataMix <- do.call(model.frame, mfArgs)
origOrder <- row.names(dataMix)
for (i in names(contrasts)) contrasts(dataMix[[i]]) = contrasts[[i]]
grps <- getGroups(dataMix, groups)
if (inherits(grps, "factor")) {
  ord <- order(grps)
  grps <- data.frame(grps)
  row.names(grps) <- origOrder
  names(grps) <- as.character(deparse((groups[[2L]])))
}
else {
  ord <- do.call(order, grps)
  for (i in 2:ncol(grps)) {
    grps[, i] <- as.factor(paste(as.character(grps[,
      i - 1]), as.character(grps[, i]), sep = "/"))
  }
}
if (corQ > lmeQ) {
  ord <- do.call(order, getGroups(dataMix, getGroupsFormula(correlation)))
}
grps <- grps[ord, , drop = FALSE]
dataMix <- dataMix[ord, , drop = FALSE]
revOrder <- match(origOrder, row.names(dataMix))
N <- nrow(grps)
Z <- model.matrix(reSt, dataMix)
ncols <- attr(Z, "ncols")
Names(lmeSt$reStruct) <- attr(Z, "nams")
contr <- attr(Z, "contr")
X <- model.frame(fixed, dataMix)
Terms <- attr(X, "terms")
auxContr <- lapply(X, function(el) if (inherits(el, "factor") &&
  length(levels(el)) > 1)
  contrasts(el))
contr <- c(contr, auxContr[is.na(match(names(auxContr), names(contr)))])
contr <- contr[!unlist(lapply(contr, is.null))]
X <- model.matrix(fixed, data = X)
y <- eval(fixed[[2L]], dataMix)
ncols <- c(ncols, dim(X)[2L], 1)
Q <- ncol(grps)
attr(lmeSt, "conLin") <- list(Xy = array(c(Z, X, y), c(N,
  sum(ncols)), list(row.names(dataMix), c(colnames(Z),
  colnames(X), deparse(fixed[[2L]])))), dims = MEdims(grps,

```



```

      ncols), logLik = 0, sigma = controlvals$sigma, auxSigma = 0)
tmpDims <- attr(lmeSt, "conLin")$dims
if (max(tmpDims$ZXlen[[1L]]) < tmpDims$qvec[1L]) {
  warning(gettextf("fewer observations than random effects in all level %s groups",
    Q), domain = NA)
}
fixDF <- getFixDF(X, grps, attr(lmeSt, "conLin")$dims$ngrps,
  terms = Terms)
lmeSt <- Initialize(lmeSt, dataMix, grps, control = controlvals)
parMap <- attr(lmeSt, "pmap")
if (length(lmeSt) == 1) {
  oldConLin <- attr(lmeSt, "conLin")
  decomp <- TRUE
  attr(lmeSt, "conLin") <- MEdecomp(attr(lmeSt, "conLin"))
}
else decomp <- FALSE
numIter <- 0
repeat {
  oldPars <- coef(lmeSt)
  optRes <- if (controlvals$opt == "nlminb") {
    control <- list(iter.max = controlvals$msMaxIter,
      eval.max = controlvals$msMaxEval, trace = controlvals$msVerbose)
    keep <- c("abs.tol", "rel.tol", "x.tol", "xf.tol",
      "step.min", "step.max", "sing.tol", "scale.init",
      "diff.g")
    control <- c(control, controlvals[names(controlvals) %in%
      keep])
    nlminb(c(coef(lmeSt)), function(lmePars) -logLik(lmeSt,
      lmePars), control = control)
  }
  else {
    reltol <- controlvals$reltol
    if (is.null(reltol))
      reltol <- 100 * .Machine$double.eps
    control <- list(trace = controlvals$msVerbose, maxit = controlvals$msMaxIter,
      reltol = if (numIter == 0) controlvals$msTol else reltol)
    keep <- c("fnscale", "parscale", "ndeps", "abstol",
      "alpha", "beta", "gamma", "REPORT", "type", "lmm",
      "factr", "pgtol", "temp", "tmax")
    control <- c(control, controlvals[names(controlvals) %in%
      keep])
    optim(c(coef(lmeSt)), function(lmePars) -logLik(lmeSt,
      lmePars), control = control, method = controlvals$optimMethod)
  }
  coef(lmeSt) <- optRes$par
  attr(lmeSt, "lmeFit") <- MEestimate(lmeSt, grps)
  if (!needUpdate(lmeSt)) {
    if (optRes$convergence) {
      msg <- gettextf("%s problem, convergence error code = %s\n message = %s",
        controlvals$opt, optRes$convergence, paste(optRes$message,
          collapse = ""))
      if (!controlvals$returnObject)
        stop(msg, domain = NA)
      else warning(msg, domain = NA)
    }
  }
}

```

```

    }
    break
  }
  numIter <- numIter + 1L
  lmeSt <- update(lmeSt, dataMix)
  aConv <- coef(lmeSt)
  conv <- abs((oldPars - aConv)/ifelse(aConv == 0, 1, aConv))
  aConv <- NULL
  for (i in names(lmeSt)) {
    if (any(parMap[, i])) {
      aConv <- c(aConv, max(conv[parMap[, i]]))
      names(aConv)[length(aConv)] <- i
    }
  }
  if (max(aConv) <= controlvals$tolerance) {
    break
  }
  if (numIter > controlvals$maxIter) {
    msg <- gettext("maximum number of iterations (lmeControl(maxIter)) reached without converge")
    if (controlvals$returnObject) {
      warning(msg, domain = NA)
      break
    }
    else stop(msg, domain = NA)
  }
}
lmeFit <- attr(lmeSt, "lmeFit")
names(lmeFit$beta) <- namBeta <- colnames(X)
attr(fixDF, "varFixFact") <- varFix <- lmeFit$sigma * lmeFit$varFix
varFix <- crossprod(varFix)
dimnames(varFix) <- list(namBeta, namBeta)
Fitted <- fitted(lmeSt, level = 0:Q, conLin = if (decomp)
  oldConLin
else attr(lmeSt, "conLin"))[revOrder, , drop = FALSE]
Resid <- y[revOrder] - Fitted
rownames(Resid) <- rownames(Fitted) <- origOrder
attr(Resid, "std") <- lmeFit$sigma/(varWeights(lmeSt)[revOrder])
grps <- grps[revOrder, , drop = FALSE]
lmeSt$reStruct <- solve(lmeSt$reStruct)
dims <- attr(lmeSt, "conLin")$dims[c("N", "Q", "qvec", "ngrps",
  "ncol")]
attr(lmeSt, "fixedSigma") <- fixedSigma
apVar <- if (controlvals$apVar) {
  lmeApVar(lmeSt, lmeFit$sigma, .relStep = controlvals[[".relStep"]],
    minAbsPar = controlvals[["minAbsParApVar"]], natural = controlvals[["natural"]])
}
else {
  "Approximate variance-covariance matrix not available"
}
attr(lmeSt, "conLin") <- NULL
attr(lmeSt, "lmeFit") <- NULL
grpDta <- inherits(data, "groupedData")
structure(class = "lme", list(modelStruct = lmeSt, dims = dims,
  contrasts = contr, coefficients = list(fixed = lmeFit$beta,

```

```

        random = lmeFit$b), varFix = varFix, sigma = lmeFit$sigma,
        apVar = apVar, logLik = lmeFit$logLik, numIter = if (needUpdate(lmeSt)) numIter,
        groups = grps, call = Call, terms = Terms, method = method,
        fitted = Fitted, residuals = Resid, fixDF = fixDF, na.action = attr(dataMix,
            "na.action"), data = if (keep.data && !miss.data) data),
        units = if (grpDta)
            attr(data, "units"), labels = if (grpDta)
            attr(data, "labels"))
    }
    <bytecode: 0x0000000022ca7698>
    <environment: namespace:nlme>
nlme:::reStruct

function (object, pdClass = "pdLogChol", REML = FALSE, data = sys.frame(sys.parent()))
{
  if (inherits(object, "reStruct")) {
    if (!missing(REML))
      attr(object, "settings")[1] <- as.integer(REML)
    object[] <- lapply(object, function(el, data) {
      pdMat(el, data = data)
    }, data = data)
    return(object)
  }
  plen <- NULL
  if (inherits(object, "formula")) {
    if (is.null(grpForm <- getGroupsFormula(object, asList = TRUE))) {
      object <- list(object)
    }
    else {
      if (length(object) == 3) {
        object <- eval(parse(text = paste(deparse(getResponseFormula(object)[[2]]),
          deparse(getCovariateFormula(object)[[2]], width.cutoff = 500),
          sep = "~")))
      }
      else {
        object <- getCovariateFormula(object)
      }
      object <- rep(list(object), length(grpForm))
      names(object) <- names(grpForm)
    }
  }
  else if (inherits(object, "pdMat")) {
    if (is.null(formula(object))) {
      stop("\"pdMat\" element must have a formula")
    }
    object <- list(object)
  }
  else {
    if (data.class(object) != "list") {
      stop("'object' must be a list or a formula")
    }
    if (is.null(names(object)) && all(unlist(lapply(object,
      function(el) {
        inherits(el, "formula") && length(el) == 3

```

```

        })))) {
        object <- list(object)
    }
    else {
        object <- lapply(object, function(el) {
            if (inherits(el, "pdMat")) {
                if (is.null(formula(el))) {
                    stop("\\"pdMat\\" elements must have a formula")
                }
                return(el)
            }
            if (inherits(el, "formula")) {
                grpForm <- getGroupsFormula(el)
                if (!is.null(grpForm)) {
                    el <- getCovariateFormula(el)
                    attr(el, "grpName") <- deparse(grpForm[[2]])
                }
                return(el)
            }
            else {
                if (data.class(el) == "list" && all(unlist(lapply(el,
                    function(el1) {
                        inherits(el1, "formula") && length(el1) ==
                            3
                    })))) {
                    return(el)
                }
                else {
                    stop("elements in 'object' must be formulas or\\"pdMat\\" objects")
                }
            }
        })
    }
    if (is.null(namObj <- names(object))) {
        namObj <- rep("", length(object))
    }
    aux <- unlist(lapply(object, function(el) {
        if (inherits(el, "formula") && !is.null(attr(el,
            "grpName"))) {
            attr(el, "grpName")
        }
        else ""
    })))
    auxNam <- namObj == ""
    if (any(auxNam)) {
        namObj[auxNam] <- aux[auxNam]
    }
    names(object) <- namObj
}
object <- lapply(object, function(el, pdClass, data) {
    pdMat(el, pdClass = pdClass, data = data)
}, pdClass = pdClass, data = data)
object <- rev(object)
if (all(unlist(lapply(object, isInitialized)))) {

```

```

    plen <- unlist(lapply(object, function(el) length(coef(el))))
  }
  pC <- unlist(lapply(object, data.class))
  pC <- match(pC, c("pdSymm", "pdDiag", "pdIdent", "pdCompSymm",
    "pdLogChol"), 0) - 1
  attr(object, "settings") <- c(as.integer(REML), 1, 0, pC)
  attr(object, "plen") <- plen
  class(object) <- "reStruct"
  object
}
<bytecode: 0x0000000022d32400>
<environment: namespace:nlme>

```