iFly Res

Data Warehouse- Data Model

Version	:	*3.2*
Date	:	*11.05.2016*
Status	:	*Draft*
Author	:	*Ramesh R Warrier*
File	:	*iFly Res Data Ware House Data Model*
Pages	:	*36*
Classification	:	*<No classification>*
Distribution	:	*IBS, Airline IT Team*

Proprietary & Confidential to Avient Solutions (An IBS Group Company)

History

Version	Date	Author	Remark
0.1	17.08.2010	Ramesh R Warrier	First Draft
1.0	03.11.2010	Ramesh R Warrier	Valid
2.0	24.02.2012	Ramesh R Warrier	Valid
2.1	26.06.2013	Ramesh R Warrier	Draft. Added Ticket details
3.0	13.12.2013	Ramesh R Warrier	Modified to add specific attributes of internal tickets
3.1	05.05.2016	Joel Joe Joseph	Draft
3.2	11.05.2016	Ramesh R Warrier	Modified the checkin tables
3.3	11.11.2016	Joel Joe Joseph	Draft

Table of Contents

1. Introduction 4

2. Naming Convention 4

3. Table Details 4

3.1 Dimension Tables 4
3.1.1 Date Dimension 4
3.1.2 Time Dimension 5
3.1.3 Airport Dimension 5
3.1.4 Sector Details 5
3.1.5 Agency Details 6
3.1.6 Agency Address 6
3.1.7 Channel Details 7
3.1.8 Flight Details 7
3.1.9 Flight Leg Details 8
3.1.10 Flight Segment Details 8
3.1.11 Flight Airport Details 9
3.1.12 Fare Details 10
3.1.13 GDS Fare Details 11
3.1.14 User Details 11
3.1.15 User Duty Code Mapping 12
3.1.16 Business Actions 12
3.1.17 Passenger Types 13
3.1.18 PNR specific details 13
3.1.19 Passenger Details 14
3.1.20 Pricing Components 14
3.1.21 Status Codes 15
3.1.22 Payment Codes 15
3.1.23 Service Initiator Details 16
3.1.24 Car Rental Details 16
3.1.25 Ticket Details 16
3.1.26 Ticket Coupon Details 18
3.1.27 MCO Coupon Details 18
3.1.28 DCS Passenger Details 19
3.1.29 DCS Passenger Seat Details 21
3.1.30 DCS Passenger SSR Details 21
3.1.31 DCS Passenger Connection Info 22
3.1.32 DCS Passenger Ticket Details 23
3.1.33 DCS Passenger Baggage Details 23
3.1.34 DCS Check-in Fee Details 24
3.1.35 DCS Passenger Infant Details 24
3.1.36 DCS Passenger OA Details 25
3.1.37 Group Quote General 25
3.1.38 Group Quote Segment Details 27
3.1.39 Group Quote Sales Details 28
3.1.40 News Letter Subscription Details 28

3.2 Fact Tables 29
3.2.1 PNR Booking Sales Details 29
3.2.2 PNR Ticket Details 30
3.2.3 Payment Details 31
3.2.4 Ticket Sales 32
3.2.5 Revenue Doc Sales 33
3.2.6 Agency credit record 35

1. Introduction

This document serves as the base document for the iFly Res Data Ware House data model. The scope of the document is to list the possible facts and the dimensions associated to each fact and the table details.

2. Naming Convention

The naming convention to be followed throughout the document is given below.

Object	Naming Convention
Fact Tables	ires_<<fact>>_<<meaningful name>>
Dimension Tables	ires_<<dim>>_<<meaningful name>>
Surrogate keys	<<meaningful name>>_id
Primary Keys	<<meaningful name>>_id

Examples

Object	Attribute Names	Naming Convention
Fact Tables	Sales table	ires_fact_pnr_sales
Dimension Tables	Flight Table	ires_dim_flight
Surrogate keys	Sector	sector_id
Primary Keys	Channel	channel_id

3. Table Details

This section describes the various table structures

3.1 Dimension Tables

3.1.1 Date Dimension

Table Name	ires_dim_date
Description	This table contains the date information. Unique id will be used to denote each date.
Primary Key	date_id. Surrogate Key
Index(s)	actual_date – unique key

Column Name	Data Type	Description
date_id	integer	
actual_date	date	Eg. 01-Nov-2010

month	varchar	November
year	integer	2010
day	varchar	01
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.2 Time Dimension

Table Name	ires_dim_time
Description	This table contains the time from 00:00 to 23:59. Each minute is stored in this table and unique id is used to represent each minute
Primary Key	time_id – surrogate key
Indexes	actual_time – unique key

Column Name	Data Type	Description
time_id	integer	
actual_time	varchar	eg: 22:13
part_of_day	varchar	AM/PM
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.3 Airport Dimension

Table Name	ires_dim_airport_details
Description	This table contains the airport specific details
Primary Key	airport_id – surrogate key
Indexes	airline_iata_code, airport_iata_time – unique key

Column Name	Data Type	Description
airport_id	integer	
airline_iata_code	varchar	
airport_iata_code	varchar	3 letter code to represent the airport
airport_name	varchar	
city_code	varchar	
remarks	varchar	
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.4 Sector Details

Table Name	ires_dim_sector_details
Description	This table contains the route details and the mileage between the city pairs
Primary Key	sector_id – surrogate key
Indexes	airline_iata_code, bd_airport_code, off_airport_code – unique key

Column Name	Data Type	Description
sector_id	integer	
airline_iata_code	varchar	
bd_airport_code	varchar	segment board airport code

off_airport_code	varchar	segment off airport code
sector_code	varchar	the concatenation of bd airport code and off airport code. Eg; ABC-XYZ
mileage	integer	mileage between the city pairs
sector_type	varchar	Determines whether International or Domestic
route_type	varchar	Determines whether long haul, short haul, medium haul
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.5 Agency Details

Table Name	ires_dim_agency_profile
Description	This table contains the agency specific information.
Primary Key	agency_id – surrogate key
Indexes	airline_iata_code, agency_iata_code – unique key

Column Name	Data Type	Description
agency_id	integer	
airline_iata_code	varchar	
agency_iata_code	varchar	The unique code assigned to an agency. For an agency, this field will hold its unique IATA/ARC/TIDS number
agency_number	varchar	The unique code assigned to an agency excluding the IATA check digit
agency_type	varchar	Determines whether the agency is CORPORATE or TRAVEL_AGENCY
agency_name	varchar	Agency name
arln_controlled_ind	varchar	
address1	varchar	Address details of the agency
address2	varchar	Address details of the agency
address3	varchar	Address details of the agency
city	varchar	Address details of the agency
province	varchar	Address details of the agency
country_name	varchar	Address details of the agency
postal_code	varchar	Address details of the agency
phone_number	varchar	Phone number of the agency
fax_number	varchar	Fax number of the agency
email_id	varchar	Email address of the agency
language	varchar	Language of the agency
manager_first_name	varchar	Manager first name
manager_last_name	varchar	Manager last name
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.6 Agency Address

Table Name	ires_dim_agency_address
Description	This table contains the agency address other than location. Includes MAILING/BANK/MANAGER

Primary Key	agency_id, address_type
Indexes	ires_dim_agency_address_fk – agency_id

Column Name	Data Type	Description
agency_id	integer	Id in the agency profile table
address_type	varchar	Address type of the agency, Values could be MAILING/BANK/MANAGER
address1	varchar	Address details of the agency
address2	varchar	Address details of the agency
address3	varchar	Address details of the agency
city	varchar	City of the agency
province	varchar	Province of the agency
country_name	varchar	Country of the agency
postal_code	varchar	Postal code of the agency
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.7 Channel Details

Table Name	ires_dim_channel_details
Description	This table contains the channel details through which bookings can happen.Eg: Web, messaging, aiRES client.
Primary Key	channel_id – surrogate key
Indexes	airline_iata_code, channel_code – unique key

Column Name	Data Type	Description
agency_id	integer	
airline_iata_code	varchar	
channel_code	varchar	stores the channel codes. Eg. AIRES APP for iFly RES thick client, Guest En for Web
channel_type	varchar	
channel_name	varchar	
user_id	varchar	default user id for the channel
duty_code	varchar	default duty code for the channel
description	varchar	channel description
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.8 Flight Details

Table Name	ires_dim_flight
Description	This table contains the fight details. Includes the operating carrier flight details and the route
Primary Key	flight_id – surrogate key
Indexes	airline_iata_code, flight_carrier, flight_number, flight_date, flight_suffix – unique key

Column Name	Data Type	Description

flight_id	integer	
airline_iata_code	varchar	
flight_carrier	varchar	
flight_number	integer	
flight_date	date	
flight_suffix	varchar	
route	varchar	concatenated route string of the flight. Eg. ABC-DEF-XYZ
remarks	varchar	
operating_flight_carrier	varchar	
operating_flight_number	integer	
operating_carrier_name	varchar	
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.9 Flight Leg Details

Table Name	ires_dim_flt_leg
Description	This table contains the fight leg details. Includes the departure and arrival times and the order of the stops
Primary Key	flt_leg_id – surrogate key
Indexes	airline_iata_code, flight_carrier, flight_number, flight_date, flight_suffix, bd_airport_code, off_airport_code – unique key flight_id, bd_airport_code,off_airport_code – normal index

Column Name	Data Type	Description
flt_leg_id	integer	
airline_iata_code	varchar	
flight_carrier	varchar	
flight_number	integer	
flight_date	date	Flight date
flight_id	integer	
bd_airport_code	varchar	Board Airport code in the leg
off_airport_code	varchar	Off Airport code in the leg
dep_time_ltc	datetime	Departure time of the flight in Local time zone
arr_time_ltc	datetime	Arrival time of the flight in local timezone
bd_point_order	integer	The order of the airport in the route
equipment_code	varchar	Equipment code used in the leg. Eg: 767
eqp_version_code	varchar	Equipment Version code used in the leg. Eg: 700A
template_code	varchar	Template code used in the leg. Eg: 767300A
total_seats	integer	Total seats in the equipment
service_type	varchar	Eg : J
created_date	datetime	Creation time of the flight in the system in GMT
last_modified_date	datetime	Last Modified date in GMT

3.1.10 Flight Segment Details

Table Name	ires_dim_flt_seg
Description	This table contains the fight segment / market details. Includes the departure and arrival times in both local and GMT times and the order of the origin and destination airports
Primary Key	flt_seg_id – surrogate key
Indexes	airline_iata_code, flight_carrier, flight_number, flight_date, flight_suffix, bd_airport_code, off_airport_code – unique key flight_id, bd_airport_code,off_airport_code – normal index

Column Name	Data Type	Description
flt_seg_id	integer	
airline_iata_code	varchar	
flight_carrier	varchar	
flight_number	integer	
flight_date	date	Flight date
flight_id	integer	
bd_airport_code	varchar	Board Airport code in the seg
off_airport_code	varchar	Off Airport code in the seg
dep_time_ltc	datetime	Departure time of the flight in Local time zone
arr_time_ltc	datetime	Arrival time of the flight in local time zone
dep_time_utc	datetime	Departure time of the flight in GMT
arr_time_utc	datetime	Arrival time of the flight in GMT
bd_point_order	integer	The order of the origin airport in the route
off_point_order	integer	The order of the destination airport in the route
created_date_ltc	datetime	Creation time of the flight in the system in local time zone.
last_modified_date	datetime	Last Modified date in GMT

3.1.11 Flight Airport Details

Table Name	ires_dim_ flt_airport
Description	This table contains the fight details which includes the operating carrier flight details ,route and the status
Primary Key	flt_airport_id
Indexes	airline_iata_code,flight_carrier,flight_number,flight_suffix flight_date,departure_index,airport_order

Column Name	Data Type	Description
flt_airport_id	integer	Auto generated
airline_iata_code	varchar	Hosted airline code
flight_carrier	varchar	The flight carrier code
flight_number	integer	The number used to uniquely identify the flight
flight_suffix	varchar	Suffix of flight number
flight_date	datetime	The date at which the flight is scheduled

departure_index	varchar	The departure index
airport_order	integer	The order of airport for connection flights
estimated_dep_time_ltc	datetime	The estimated departure time in local timing
estimated_arr_time_ltc	datetime	The estimated arrival time in local timing
actual_dep_time_ltc	datetime	Actual departure time in local timing
actual_arr_time_ltc	datetime	Actual arrival time in local timing
boarding_time	datetime	The time at which the flight boards
onground_time	datetime	The time at which the flight reaches ground
offground_time	datetime	The time at which the flight departs from ground
closed_time	datetime	The time at which the flight was closed
boarding_ind	varchar	Indicates whether the flight was boarded
flight_reopen_ind	varchar	Indicates whether the flight is reopen
irop_ind	varchar	Indicates whether the flight is iropped
weather_wise_ind	varchar	Indicates weather
apis_sent_ind	varchar	Indicates whether apis send
er_ind	varchar	Indicates er
locked_ind	varchar	Wheher locked or not
terminal	varchar	The airport terminal
delay_code	varchar	The baggage delay code
locked_duty_code	varchar	The dutycode of agent who locked
tarmac	varchar	Airport runway number
arrival_gate	varchar	Arrival gate number
departure_gate	varchar	Departure gate number
total_checkin_weight	integer	Total weight of checked in bags
irop_comments	varchar	Any irop comments
weath-er_wise_comments	varchar	Any comments related to weather
delay_comments	varchar	Any comments indicating flight delay
airport_comments	varchar	Airport related comments
offblock_time	datetime	The off block time
inblock_time	datetime	The in block time
last_generated_security_num	integer	The last sequence number generated for the passen-gers from that airport
fuel_burnt	integer	Total amount of burnt fuel
fuel_uplift	integer	Maximum fuel capacity during flight take off
manual_reverse_ind	varchar	The manual reverse indicator(y or n)
standby_clr_restricted_ind	varchar	The indicator (y or n) decide whether stand by check in allowed or not
last_generated_group_id	integer	Group id generated at last time
old_flt_status	varchar	This column will store old flight status before cancella-tion
arrival_spot	varchar	Stores the arrival spot of the particular leg
departure_spot	varchar	Stores the departure spot of the particular leg
locked_channels	varchar	The channels through within checkin has been sus-pended

crew_comments	varchar	Crew comments
last_modified_time_utc	datetime	Stores the flight modified time in utc

3.1.12 Fare Details

Table Name	ires_dim_fare_details
Description	This table contains the fare basis and fare class information.
Primary Key	Fare_details_id – surrogate key
Indexes	airline_iata_code, fare_class, fare_basis_code – unique key

Column Name	Data Type	Description
fare_details_id	integer	
airline_iata_code	varchar	
fare_class	varchar	stores the different fare class specified for the fare basis code
fare_basis_code	varchar	
description	varchar	
cabin_class	varchar	store the cabin class associated with the fare basis code
refundable_ind	integer	Indicator to denote whether the fare is refundable or not
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.13 GDS Fare Details

Table Name	ires_dim_fre_fare
Description	This table contains the fare class, fare basis and the fares published to the GDS for a particular period. This table will be used to prorate the fare for the GDS sales in ticket hist fact table. This table will be loaded using the excel sheet provided by BV manually.
Primary Key	airline_iata_code, origin, destination, eff_sale_start_date , fare_class, farebasis_code
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
origin	varchar	
destination	varchar	
eff_sale_start_date	varchar	Effective sale start date for the fare
eff_sale_end_date	varchar	Effective sale end date for the fare
fare_class	integer	
farebasis_code	datetime	Fare basis code to be used for the GDS sales
Type		Indicates whether the fare is NORMAL or CORPORATE
fare_amount		
channel_type		Currently the value supported is GDS.
fare_details_id		Indicates the id in the fare details dimension

sector_id		Indicates the id in the sector details dimension
last_modified_date		Last modified date in GMT

3.1.14 User Details

Table Name	ires_dim_user_details
Description	This table contains the agents and the users details.
Primary Key	user_details_id – surrogate key
Indexes	airline_iata_code, src_user_id – unique key

Column Name	Data Type	Description
user_details_id	integer	
Airline_iata_code	varchar	
src_user_id	varchar	user ids defined in the source system
first_name	varchar	first name of the user
middle_name	varchar	
last_name	varchar	
job_title	varchar	Eg. Res Agent
department	varchar	
def_office_code	varchar	Eg. FCOHQ
country_code	varchar	Eg: IT
agency_code	varchar	
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.15 User Duty Code Mapping

Table Name	ires_dim_user_dutycode
Description	This table contains the mapping between the users and their dutycodes. Unique id is assigned for each user id, duty codes
Primary Key	user_id – surrogate key
Indexes	airline_iata_code, src_user_id, duty_code – unique key

Column Name	Data Type	Description
user_id	integer	
airline_iata_code	varchar	
user_details_id	integer	Id in the user details table.
src_user_id	varchar	user id from the source system
duty_code	varchar	stores the various duty codes assigned to the user
office_code	varchar	store the various office codes the user is assigned
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.16 Business Actions

Table Name	ires_dim_business_actions
Description	This table contains the mapping between the modules and the business actions
Primary Key	user_id – surrogate key

Indexes	airline_iata_code, module, business_action – unique key

Column Name	Data Type	Description
action_id	integer	
airline_iata_code	varchar	
module	varchar	represents the module in the transaction. For eg. Booking, Payment.
business_action	varchar	This signifies the action. Eg. AVAILABILITY_SEARCH
description	varchar	

3.1.17 Passenger Types

Table Name	ires_dim_passenger_types
Description	This table defines the various guest types like adult, child and related information
Primary Key	pax_type_id – surrogate key
Indexes	airline_iata_code, src_user_id, duty_code – unique key

Column Name	Data Type	Description
pax_type_id	integer	
airline_iata_code	varchar	
pax_type	varchar	guest type – Adult, child
start_age	date	start age for the guest type
end_age	date	end age for the guest type
description	varchar	
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.18 PNR specific details

Table Name	ires_dim_pnr_main
Description	This table contains the pnr level data which will not change over period of time like the agency associated, creation time etc.
Primary Key	airline_iata_code, pnr_number
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
pnr_number	varchar	stores the pnr number generated by the source system. Eg: XXXXXX
record_locator	varchar	This uniquely identifies the pnr in the system. This will be used by messages coming from other systems whose pnr cannot be uniquely identified by the pnr number alone since they may conflict with the pnr numbers in our system.
parent_pnr	varchar	parent pnr of the pnr
Language_code	Varchar	Language
address_one	varchar	first address of the HOME_CONTACT

address_two	varchar	address of the HOME_CONTACT
alt_email_id	varchar	
child_pnrs	varchar	child pnrs of the pnr
direct_pnrs	varchar	directly cross referenced pnr numbers of this pnr
cell_phone_no	varchar	
city	varchar	
country	varchar	
dest_phone_no	varchar	
email_id	varchar	
province	varchar	
tour_operator_number	varchar	Stores the tour operator number of the pnr .
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.19 Passenger Details

Table Name	ires_dim_pnr_pax
Description	This table contains the passenger level data. This will be populated during the dimension table load.
Primary Key	passenger_id
Indexes	airline_iata_code, pnr_number, src_pax_id

Column Name	Data Type	Description
passenger_id	integer	
airline_iata_code	varchar	
pnr_number	varchar	stores the pnr number generated by the source system
src_pax_id	integer	stores the unique id used to represent the passenger in the source system
first_name	varchar	first name of the passenger
middle_name	varchar	middle name
last_name	varchar	last name of the passenger
pax_type_id	integer	refers to the passenger type id in passenger type table
pax_added_date	date	passenger addition date in GMT
date_of_birth	date	
deletion_ind	integer	indicates whether the guest is deleted or active. Only possible values are 0,1.
profile_id	varchar	customer profile id attached to the passenger
discount_code	varchar	
bonus_code	varchar	loyalty bonus code
exemption_codes	varchar	stores the exemption codes applied. Stored as comma separated values
exemption_remarks	varchar	remarks added when the exemption is applied
standby_emp_hire_date	date	hire date of the standby employees
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.20 Pricing Components

Table Name	ires_dim_price_details
Description	This table defines each of the pricing components and its codes like fare tax codes, fare, fee codes
Primary Key	price_type_id
Indexes	airline_iata_code, type, type_code, sub_type_code – Unique Key

Column Name	Data Type	Description
price_type_id	integer	
airline_iata_code	varchar	
type	varchar	indicates the various pricing types. Possible values are Applied Fare, Fare Tax, Surcharge, Fee, Car Rental, Insurance
type_code	varchar	The tax codes, fee codes.. Eg. For Applied Fare, the type code will be Applied Fare itself. For Surcharge, it will be surcharge code like FUEL.
sub_type_code	varchar	If same fee code is applied based on some conditions and if a sub type code can be identified, using these combination, a unique row could be identified. For eg. For car rental, the car group is a sub type and based on this the fee amount is varying.
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.21 Status Codes

Table Name	ires_dim_status
Description	This table defines the status codes for all of the entities. Unique Id represent the various status codes
Primary Key	status_id
Indexes	airline_iata_code, status_type, status_code – Unique Key

Column Name	Data Type	Description
status_id	integer	
airline_iata_code	varchar	
status_type	varchar	This could be PNR_STATUS, FLIGHT_STATUS, PAYMENT_STATUS
status_code	varchar	the various possible status codes for each status types. Eg. CANCELLED, ACTIVE
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.22 Payment Codes

Table Name	ires_dim_payment_codes
Description	This table defines the payment codes and the fop codes used for the payment by the pnr / cnr / enr. Unique Id represent the various payment codes
Primary Key	payment_code_id
Indexes	airline_iata_code, payment_code, fop_code – Unique Key

Column Name	Data Type	Description

payment_code_id	integer	
airline_iata_code	varchar	
payment_code	varchar	The payment codes used to display in the iFly Res payment screens. For eg: for the fop CA, the payment code will be CASH
fop_code	varchar	the code used to identify each fop defined in the source system
last_modified_date	datetime	date in which the data was populated / updated in GMT

3.1.23 Service Initiator Details

Table Name	ires_dim_pym_service_initiator
Description	This table defines the payment initiator. i.e.whether the payment is initiated for a pnr or a cnr or an enr
Primary Key	service_initiator_id
Indexes	airline_iata_code, service_initiator – Unique Key

Column Name	Data Type	Description
service_initiator_id	integer	
airline_iata_code	varchar	
service_initiator	varchar	Identifies the source which inititated the payment transaction. For eg. PNR, ENR. CNR, GA

3.1.24 Car Rental Details

Table Name	ires_dim_car_rental
Description	This table contains the specific details of the rentals provided. This will include the pick up and drop off details. This also has the unique id representing the rentals in the system.
Primary Key	airline_iata_code, passenger_id, aux_id
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
passenger_id	varchar	Id representing the passenger who has rented the car. This id can be used to get the PNR and guest details
aux_id	integer	Unique id representing the car rental. This id can be used in the PNR sales or PNR payment facts to get the sales information using the element_id in the fact table. The data will be available for the element_id in the fact table for type_codes 'CAR'
vendor_code	varchar	Vendor code. Eg: SIXT
vendor_name	varchar	Vendor name. Eg: SIXT
car_group	varchar	Car Group. Eg: C
car_type	varchar	Car Type. Eg: Economy 5 porte - Citroen C3
Transmission	varchar	Transmission of the car. Eg: Manual, Automatic
pick_up_location	varchar	Pick up location code. Eg: GOA

pick_up_date	datetime	Pick up date. Eg: 2012-01-01
drop_off_location	varchar	Drop Off location code. Eg: GOA
drop_off_date	datetime	Drop Off date. Eg: 2012-01-10
no_of_days	integer	10
no_of_seats	varchar	5
last_modified_date	datetime	Last modified date in GMT

3.1.25 Ticket Details

Table Name	ires_dim_ticket_details
Description	This table contains the specific details of the tickets issued by both iFlyRes and external ticketing systems. For the internal tickets, the data will be updated directly from the iFlyRes database.
Primary Key	airline_iata_code, ticket_number
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
ticket_number	varchar	The ticket number issued for the PNR; either from ETM or from iFlyRes
pnr_number	varchar	PNR number associated with the ticket in iFlyRes. The PNR in the ETM will not be used as it will not be reflecting the actual PNR.
ticket_issued_system	varchar	The ticketing system – iFlyRes for internal tickets. For external tickets, it could be Worldspan.
agency_id	integer	The agency which issued the ticket. The agency id refers to the key in the dim_agency_profile. This will be identified based on the agency associated with the ticket in the Res system. The agency associated in the ticket will not be used as there could be errors in the ETM file.
conjunction_ticket_number	varchar	conjunction ticket number associated with the ticket. Identified from the ETM in case of external tickets.
primary_ticket_number	varchar	primary ticket number associated with the ticket. Identified from the ETM in case of external tickets.
check_digit	integer	Check digit calculated for this ticket number
oal_pnr_number	varchar	OAL PNR number associated with the ticket. Identified from the ETM in case of external tickets.
client_account_code	varchar	client account code identified from the ETM
plating_carrier_code	varchar	plating_carrier_code identified from the ETM for external tickets
first_name	varchar	First name of the passenger associated with the ticket
middle_name	varchar	Middle name of the passenger
last_name	varchar	Last name of the passenger
title	varchar	Title of the pax – MR/MRS
pax_type	varchar	pax type – ADULT / CHILD / INFANT
fare_ladder	varchar	fare details provided in the ETM for manual verification purpose.

exchanged_to	varchar	The ticket number to which this ticket is exchanged. In case of multiple documents, the numbers will be appended with a comma.
exchanged_from	varchar	The ticket number from which this ticket is exchanged. In case of multiple documents, the numbers will be appended with a comma.
ticket_status	varchar	Ticket status – Possible values are ISSUE, REFUND, VOID, EXCHANGED
payment_codes	varchar	FOPs used for issueing the ticket. In case of multiple FOPs, the payment codes will be appended using a comma.
additional_collection	decimal	Additional collection amount in the ticket at the time of issue.
adc_currency	varchar	Additional Collection Currency
booking_agent_id	varchar	user ID of creator of the PNR to which the ticket is associated
travel_agent_id	varchar	
travel_type	varchar	I – International / D - Domestic
ticket_creation_date	datetime	ticket creation date in GMT
ticket_creation_date_ltc	datetime	ticket creation date in default office timezone
last_modified_date	datetime	last modified date of the data in GMT

3.1.26 Ticket Coupon Details

Table Name	ires_dim_ticket_coupon_details
Description	This table contains the specific details of the ticket coupons issued by both iFlyRes and external ticketing systems. For the internal tickets, the data will be updated directly from the iFlyRes database.
Primary Key	airline_iata_code, ticket_number, coupon_number
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
ticket_number	varchar	The ticket number issued for the PNR; either from ETM or from iFlyRes
coupon_number	varchar	coupon_number
bd_airport_code	varchar	Board Airport Code of the segment
off_airport_code	varchar	Off Airport Code of the segment
flight_carrier	varchar	Flight Carrier of the segment
flight_number	int	Flight Number of the segment
flight_suffix	varchar	Flight Suffix
flight_date	date	Flight date
fareclass_code	varchar	Fare Class booked for the segment
fare_basis	varchar	Fare Basis Code of the segment
cabin_class	varchar	Cabin Class. Would be NULL for externally issued tickets
res_status	varchar	Segment Status in case of external tickets
not_valid_after	date	not_valid_after date of the ticket
not_valid_before	date	not_valid_before of the ticket

cpn_status_code	varchar	Coupon Status Code
baggage_limit	decimal	Would be null for external tickets
baggage_unit	varchar	Would be null for external tickets
operating_flt_carrier	varchar	Operating Carrier Code. Will be NULL for external tick-ets
operating_flt_number	int	operating_flt_number. Will be NULL for external tickets
operating_flt_suffix	varchar	operating_flt_suffix. Will be NULL for external tickets.
loyalty_number	varchar	Loyalty Number / Frequent Flier Number
last_modified_date	date	time at which the data is modified in the table.

3.1.27 MCO Coupon Details

Table Name	ires_dim_mco_details
Description	This table contains the specific details of the mco coupons
Primary Key	airline_iata_code, mco_number
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
mco_number	varchar	mco number issued
not_valid_after	varchar	not_valid_after date of the mco
not_valid_before	varchar	not_valid_before of the mco
cpn_status_code	varchar	The status of mco
operating_flt_carrier	varchar	Operating flt carrier details
operating_flt_number	date	Operating flt number
operating_flt_suffix	date	Operating flt suffix
last_modified_date	varchar	Last modified date
Amount	decimal	Total amount against the mco
pax_id	int	Booking pax id information

3.1.28 DCS Passenger Details

Table Name	ires_dim_chk_passenger
Description	This table contains the passenger details
Primary Key	passenger_id – surrogate key
Indexes	airline_iata_code, src_pax_id

Column Name	Data Type	Description
passenger_id	integer	Auto generated
airline_iata_code	varchar	Hosted airline code
src_pax_id	integer	A unique identifier for a passenger generated by the check-in system
pnr_number	varchar	The record locater generated by the reservation system (passenger name record)
pax_key	varchar	A unique number for a passenger generated by the reservation system

flight_id	Integer	Flight id referring to ires_dim_flight
bd_airport_id	integer	Airport Id of the board airport referring to ires_dim_airport
off_airport_id	Integer	Airport Id of the off airport referring to ires_dim_airport
origin	varchar	The origin airport of passenger
destination	varchar	The destination of passenger
pax_first_name	varchar	First name of the passenger
middle_name	varchar	Middle name of the passenger
family_name	varchar	Family name/last name of the passenger
pax_title	varchar	The title associated with the passenger
pax_type	varchar	The passenger type(adult, child etc)
pax_age	integer	The age of the passenger
num_in_party	integer	The number of passenger in the pnr
gender	varchar	Gender of the passenger
star_checkin_ind	varchar	Is the passenger is star checked in
er_ind	varchar	This is indicator is set if the flight in locked for emergency response situation
self_checkin_ind	varchar	This indicator indicates whether the passenger has checked in via aself service device
fare_class	varchar	The fare class
standbyrev_ind	varchar	Is the passenger revenue is stand by
standby_priority_code	varchar	The standby priority code attached with a passenger
standby_code	varchar	The standby code associated with the passenger
standby_type	varchar	To indicate whether it is a revenue or non-revenue passenger
standby_seg_id	integer	The segment id of standby passenger
res_status	varchar	Reservation status
checkin_status	varchar	The check in status of the passenger
measurement_unit	varchar	Unit of measuring baggage
travel_class	varchar	The cabin class in which the passenger is traveling
res_class	varchar	The cabin class in which the passenger is booked
group_id	integer	The unique id for a group
group_name	varchar	Name of a group in case of group booking
security_number	integer	Sequence number generated for a passenger on being checked in
offload_reason	varchar	The reason code defined to be attached to the passenger while offloading
waiver_reason	varchar	The reason for waiving the excess baggage fee.
checkedin_airport_code	varchar	The airport code of checked in airport
checkedin_by	varchar	The user who checked in the passenger
checkedin_time	datetime	Time of checking in
boarded_time	datetime	The time at which the passenger was boarded
uncheck_time	datetime	The time of unchecking
deboarded_time	datetime	The deboarded time
offloaded_time	datetime	The offloaded time

reported_time	datetime	The time at which the passenger was reported – for standby passengers
offload_remarks	varchar	Any remarks regarding offload
waiver_remarks	varchar	The remarks associated to a waiver reason code
remarks	varchar	Any remarks
mkt_flt_carrier	varchar	The marketing flight carrier in which the passenger booked
mkt_flt_number	integer	The marketing flight number in which the passenger booked
mkt_flt_suffix	varchar	The flight suffix of the marketing flight number
date_of_booking	datetime	The date at which the segment was added in the pnr
farelevel_code	varchar	The fare level code
offload_type	varchar	To distinguish whether the offload of the passenger had been voluntary or involuntary.
interline_booking_ind	varchar	The indicator to identify the booking as an interline booking.
standby_emp_hire_date	datetime	This column stores the date of hire of staff standby travellers
upgrade_ind	varchar	Indicator for an upgraded/downgraded pax,probable values being iv_up, iv_down, vl_up
standby_upgrade_ind	varchar	To indicate whether the pax is standby upgraded
farebasis_code	varchar	Fare basis code
pax_weight	integer	Stores the weight of the passenger
pax_paid_ind	varchar	To indicate whether the pax segment is paid or not (y for paid and n for not paid)
employee_id	varchar	This column stores the employee id of standby em-ployees
staff_guest_type	varchar	The staff guest type
standby_number	integer	Standby number
brd_gate_comments	varchar	This column is used to store the boarding gate com-ments.
local_family_name	varchar	This column will store the family name/last name of the passenger in local language
local_pax_first_name	varchar	This column will store the first name of the passenger in local language
bag_pool_owner_pax_id	integer	This column will store the pax id of the pax, with whom the pooled bags are associated.
bp_print_cnt	integer	Denotes number of times the boarding pass is printed
mkt_fare_class	varchar	The fare class of the marketing flight
last_modified_date	date	time at which the data is modified in the table.

3.1.29 DCS Passenger Seat Details

Table Name	ires_dim_chk_seatnumber
Description	This table contains the passenger seat details
Primary Key	passenger_id, airline_iata_code, child_bd_airport_code, child_off_airport_code, seat_number
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Iata code of the airline
src_pax_id	integer	A unique identifier for a passenger generated by the check-in system
child_bd_airport_code	varchar	The flight segment for which the seat is assigned
child_off_airport_code	varchar	The flight segment for which the seat is assigned
seat_number	varchar	Seat number of the passenger
last_modified_date	date	time at which the data is modified in the table.

3.1.30 DCS Passenger SSR Details

Table Name	ires_dim_chk_pax_ssr
Description	This table contains the passenger ssr details
Primary Key	passenger_id, airline_iata_code, dcs_ssr_id
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Iata code of the airline
src_pax_id	integer	A unique identifier for a passenger generated by the check-in system
dcs_ssr_id	integer	The ssr indicator at dcs
res_ssr_id	integer	Ssr id at reservation system
ssr_keyword	varchar	The ssr code used
ssr_status	varchar	The status of ssr
ssr_remark	varchar	Any remarks on ssr
ssr_iata_keyword	varchar	The iata keyword for an ssr
last_modified_date	date	time at which the data is modified in the table.

3.1.31 DCS Passenger Connection Info

Table Name	ires_dim_chk_pax_travelinfo
Description	This table contains the passenger travel details
Primary Key	passenger_id, airline_iata_code, travel_info_ind, station_order
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Iata code of the airline
src_pax_id	integer	A unique identifier for a passenger generated by the check-in system
travel_info_ind	varchar	Indicates whether Inbound (I) or outbound (O) segment.

station_order	integer	Order of station in case of connection flight
departure_index	varchar	The departure airport code
flight_carrier	varchar	Connection flight Carrier code
flight_number	integer	Connection flight_number
flight_suffix	varchar	Connection flight suffix
flight_date	datetime	Connection flight date
bd_airport_code	varchar	Airport code of the board point
off_airport_code	varchar	Airport code of the off point
travel_class	varchar	The cabin class in which the passenger is traveling
code_share_flight_carrier	varchar	Codeshare flight carrier
code_share_flight_number	integer	Codeshare flight number
code_share_flight_suffix	varchar	Codeshare flight suffix
fare_class	varchar	The fare class associated with the segment of the pnr for the pax.
arr_time_ltc	datetime	Sta of the oa
interline_type	varchar	Stores i for inbound interline and o for outbound interline
last_modified_date	date	time at which the data is modified in the table.

3.1.32 DCS Passenger Ticket Details

Table Name	ires_dim_chk_pax_tkt_details
Description	This table contains the passenger ticket details
Primary Key	passenger_id, airline_iata_code, ticket_number, coupon_number
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Hosted airline code
src_pax_id	integer	Pax id generated for the pax segment
ticket_number	varchar	Ticket number for the pax segment
coupon_number	integer	Coupon number corresponding to the pax segment
aires_generated_ind	varchar	Indicates whether the ticket is generated by aires or not
position_ind	varchar	Indicates the position of the ticket, when the ticket/coupon is attched to more than one segment
last_modified_date	date	time at which the data is modified in the table.

3.1.33 DCS Passenger Baggage Details

Table Name	ires_dim_chk_pax_bag_tag
Description	This table contains the passenger baggage details
Primary Key	passenger_id, airline_iata_code, pnr_number, bag_tag_number, flight_order, airline_number, bag_tag_issuer_code
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Hosted airline code
bag_tag_number	varchar	The bag tag number generated for a bag
flight_order	integer	The order of segments
flight_carrier	varchar	Carrier code
flight_number	integer	Flight number. unique for a particular date
flight_date	datetime	The date on which the flight operates.
flight_suffix	varchar	A unique identifier for a flight.
oversize_ind	varchar	To indicate, bag is over sized
bt_ind	varchar	Whether bag tag is printed or not
auto_ind	varchar	Is the bag tag automatic or manual
advanced_tag_ind	varchar	To indicate whether the bag was long tagged or not
bd_airport_code	varchar	Airport code of the board point
off_airport_code	varchar	Airport code of the off point
baggage_weight	integer	Total weight of baggage
baggage_status	varchar	The status of baggage
pieces_or_wt_ind	varchar	Indicates whether to pieces or weight
bag_tag_issuer_code	varchar	Bag tag issuer airline code
baggage_remarks	varchar	Baggage remarks.
last_modified_date	date	time at which the data is modified in the table.

3.1.34 DCS Check-in Fee Details

Table Name	ires_dim_chk_checkin_fee
Description	This table contains the check in fee details
Primary Key	passenger_id, airline_iata_code, ssr_keyword, fee_code, element_id
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Hosted airline code
fee_code	varchar	Ffee code
pnr_number	varchar	Pnr number
passenger_name	varchar	Name of the passenger
currency	varchar	Currency
applied_amount	integer	The actual applied fee amount.
status	varchar	Fee Status
remarks	varchar	Remarks
waiver_remarks	varchar	Remarks for fee waiver
paid_ind	varchar	Paid indicator

ssr_keyword	varchar	Ssr keyword
paid_amount	integer	To store the fee amount that has been paid by the pax.
addition_date	datetime	Date at which fee is added.
last_modified_date	date	time at which the data is modified in the table.

3.1.35 DCS Passenger Infant Details

Table Name	ires_dim_chk_pax_inf_details
Description	This table contains the passenger associated infant details.
Primary Key	passenger_id, airline_iata_code, dcs_infant_id
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Iata code of the airline
dcs_infant_id	integer	The infant id at dcs
res_infant_id	integer	The infant id at reservation system
first_name	varchar	The passengers" first name
last_name	varchar	Last name of the passenger
middle_name	varchar	Middle name of the infant
gender	varchar	Gender
date_of_birth	datetime	Date of birth
comment_text	varchar	Comments
first_name_local	varchar	The infant first name in local language
last_name_local	varchar	The infant last name in local language
title	varchar	The infants title is stored
last_modified_date	date	Time at which the data is modified in the table.

3.1.36 DCS Passenger OA Details

Table Name	ires_dim_chk_pax_oa_details
Description	This table contains the oa flight details.
Primary Key	passenger_id, airline_iata_code, station_order
Indexes	

Column Name	Data Type	Description
passenger_id	integer	The unique key to identify passenger referring to ires_dim_chk_passenger.
airline_iata_code	varchar	Hosted airline code.
station_order	integer	Unique identifier corresponding to the oa segment in travelinfo table.
pnr_number	varchar	Oa's pnr number.
boarding_time	datetime	Oa flight's boarding time.
boarding_gate	varchar	Oa's boarding gate.

terminal	varchar	Oa's terminal - nullable.
security_number	integer	Oa's sequence number.
seat_number	varchar	Oa segment's seat number(s).
loyalty_airline_code	varchar	Stores the airline code associated with loyalty number
loyalty_number	varchar	Fqtv number.
loyalty_tier	varchar	Frequent flyer level.
ticket_number	varchar	Ticket (coupon) number of the passenger.
checkin_status	varchar	Checkin status in oa segment.
last_modified_date	date	Time at which the data is modified in the table.

3.1.37 Group Quote General

Table Name	ires_dim_grp_quote
Description	This table contains the group quite general details.
Primary Key	airline_iata_code, quote_number, pax_type
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
grp_quote_id	int	Group quote auto increment id
quote_number	varchar	Group quote number
group_type	varchar	Group type information
group_name	varchar	Name of the group
pnr_number	varchar	Pnr number associated with the group, if no pnr associated , then it will be null
quote_option	varchar	The option selected for group quote
no_of_seat	int	Total number of seat in the group quote
offer_acceptance_tlt_date	datetime	Offer acceptance date
quote_status	varchar	Group quote status
promo_code	varchar	Promo code applied against the group quote
last_modified_by	varchar	Last modified user information
last_modified_duty_code	varchar	Last modified user duty code
last_modified_date	datetime	Last modified date
point_of_sale	varchar	POS information
creation_date	datetime	The group quote creation date
creator_user_id	varchar	Group quote creation user information
leader_first_name	varchar	Group leader first name
leader_middle_name	varchar	Group leader middle name
leader_last_name	varchar	Group leader last name
title	varchar	Group leader title
fare_quoted_currency	varchar	Quoted currency against the group
corporate_id	varchar	Corporate id, if it's a corporate booking

deposit_currency	varchar	Currency information
creator_channel_code	varchar	Creator channel code
creator_channel_type	varchar	Creator channel type
create_status_user	varchar	User who has approved the group quote by changing the status to "CREATED". For status, before group quote approval, this field will be blank.
create_status_date	datetime	Date on which group desk team has approved the group quote by changing the status to "CREATED". For status, before group quote approval, this field will be blank.
contact_type	varchar	The contact type
preferred_ind	int	The preferred contact active indicator
extension_no	varchar	Phone extension number
phone_countrycode	varchar	Phone country code
phone_no	varchar	Phone number
province	varchar	Province
city	varchar	City
country	varchar	Country
fax_no	varchar	Fax number
zipcode	varchar	Zipcode
email_id	varchar	Email id
mailing_address	varchar	Mailing address
alt_email_id	varchar	Alternate email id
address_one	varchar	Additional address 1
address_two	varchar	Addition address 2
cell_phone_countrycode	varchar	Cell phone country code
cell_phone_no	varchar	Cell phone number
pax_type	varchar	Passenger type
number_of_pax	Int	Number of passenger in that particular passenger type
exemption_reason	varchar	Exemption reason if any
exemption_codes	varchar	Exemption code if any
pos_currency	varchar	Pos currency

3.1.38 Group Quote Segment Details

Table Name	ires_dim_grp_quote_seg
Description	This table contains the group quote segment details.
Primary Key	quote_seg_id
Unique Key	airline_iata_code, quote_number, segment_id, flight_carrier, flight_number, flight_suffix, flight_date_ltc, bd_airport_code, off_airport_code
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
quote_seg_id	int	Group segment auto increment id

quote_number	varchar	Group quote number
segment_id	int	Segment id
segment_relation_id	int	Segment relation id
flight_carrier	varchar	Flight carrier
flight_number	int	Flight number
flight_suffix	varchar	Flight suffix
flight_date_ltc	datetime	Flight date in ltc
bd_airport_code	varchar	Airport code of the board point
off_airport_code	varchar	Airport code of the off point
dep_date_ltc	datetime	Departure date in ltc
dep_date_utc	datetime	Departure date in utc
arr_date_ltc	datetime	Arrival date in ltc
arr_date_utc	datetime	Arrival date in utc
fare_class	varchar	Fare class
fare_basis_code	varchar	Fare basis code
no_of_stops	int	Total number stops
journey_time	int	Journey time
cabin_class	varchar	Cabin class
flight_status	varchar	Flight status
flight_type	varchar	Flight type
remaining_seats	int	Remaining seats1
sold_seats	int	Sold seats in the segment
through_flt_ind	int	Indicator to identify whether the flight is through or not
origin	varchar	Airport code of the origin
destination	varchar	Airport code of the destination
added_time	timestamp	Segment added time
affected_flt_ind	int	Affected flights
pnr_segment_status	varchar	The pnr segment status. If any
last_modified_date	datetime	Last modified date

3.1.39 Group Quote Sales Details

Table Name	ires_dim_grp_quote_sales
Description	This table contains the group quote sales details.
Primary Key	airline_iata_code, grp_quote_id, quote_seg_id, flight_id, agency_id,, fare_details_id price_type_id, sector_id, pax_type
Unique Key	
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
grp_quote_id	int	Group quote id in the ires_dim_grp_quote
quote_seg_id	int	Group quote seq id in ires_dim_grp_quote_seg
flight_id	int	Flight id in the ires_dim_flight

agency_id	int	Agency id from ires_dim_agency_profile
fare_details_id	int	Fare details id from ires_dim_fare_details
price_type_id	int	Price type id from ires_dim_price_code
sector_id	int	Sector id from ires_dim_sector_details
amount	decimal	Total amount for the all passengers against a particular pax type.
pax_type	varchar	The pax type
fop	varchar	MCO # used for payment or refunds
last_modified_date	datetime	Last modified date
modified_date_utc_id	int	Modified date utc id
modified_date_ltc_id	int	Modified date ltc id

3.1.40 News Letter Subscription Details

Table Name	ires_dim_nl_subscription
Description	This table contains the newsletter subscription details.
Primary Key	airline_iata_code, email_id
Unique Key	
Indexes	

Column Name	Data Type	Description
subscription_id	int	Auto increment id
airline_iata_code	varchar	
email_id	varchar	Email id
phone_no	varchar	Phone number
pax_title	varchar	Pax title
pax_last_name	varchar	Pax last name
pax_middle_name	varchar	Pax middle name
pax_first_name	varchar	Pax first name
gender	varchar	Gender of the pax
date_of_birth	datetime	Date of birth of the pax
zipcode	varchar	Zzipcode
country	varchar	Country
language	varchar	Language
subscription_status	int	Subscription active status
last_modified_date	datetime	Last modified date
subscription_date	datetime	Subscription date

3.2 Fact Tables

3.2.1 PNR Booking Sales Details

Table Name	ires_fact_pnr_sales
Description	This fact table holds all the sales information for each transaction against the pnr. Data is available in various dimensions and the sales reports can be taken in any format from this table. This will have the

	sales recorded for all the modifications in the pnr pricing. This sales does not checks whether the particular price component is paid or not. The sale is meant by all the PNR price modifications in the system.
Primary Key	airline_iata_code, passenger_id, src_trans_id, data_level, element_id, flight_id, sector_id, type_code_id, currency
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
passenger_id	integer	passenger_id representing pax referencing pnr pax
src_trans_id	integer	pnr transaction id from the source system
data_level	varchar	indicated what the data in the row represents. Whether its the old value of the transaction or the new value of the transaction
element_id	integer	In case of fees, it will be the fee_id in the source system. In case of fare tax, surcharge and fare, it will be the oanddId in the source system
flight_id	integer	id representing flight referencing dim_flight. . If the price component could not be referenced to a particular flight, default -1 will be stored.
sector_id	integer	id representing sector referencing dim_sector. If the price component could not be referenced to a particular sector, default -1 will be stored.
agency_id	integer	id representing the agency referencing dim_agency_profile. If the pnr could not be referenced to a particular agency, default -1 will be stored.
channel_id	integer	id representing the channel referencing dim_channel. If the pnr could not be referenced to a particular agency, default -1 will be stored.
fare_details_id	integer	id representing the fare details associated with the pricing component referencing dim_fare_details. If the component could not be referenced to a particular fare details, default -1 will be stored. For eg. PER PNR fees
user_duty_code_id	integer	id representing the user who completed the transaction referencing dim_user_duty_code
type_code_id	integer	id representing the price type referencing the dim_price_types
amount	decimal	Amount associated with the transaction. For data_level OLD, the amount will be (–amount)
currency	varchar	currency code
modified_date_utc_id	integer	the date of the transaction in GMT
modified_time_utc_id	integer	the time of the transaction in GMT
modified_date_ltc_id	integer	the date of the transaction in def office time zone
modified_time_ltc_id	integer	the time of the transaction in def office time zone

3.2.2 PNR Ticket Details

Table Name	ires_fact_pnr_ticket_hist
Description	This fact table holds all the externally ticketed transactions which will come in the system as SSR TKNE, TKNA, TKNM. All the tickets issued / refund transactions will be stored in this table.

Primary Key	airline_iata_code, passenger_id, src_trans_id, element_id, data_level
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
pnr_number	varchar	
passenger_id	integer	passenger_id representing pax referencing pnr pax
src_trans_id	integer	pnr transaction id from the source system
element_id	Integer	For external tickets this will be the unique id to representing the ssr in the source system. For internally generated tickets, this will be the ticket number itself.
data_level	varchar	indicates what the data in the row represents. Whether its the old value of the transaction or the new value of the transaction. In case of ISSUE, the data level will be NEW and in case of REFUND the data level will be OLD.
flight_id	integer	id representing flight referencing dim_flight.
sector_id	integer	id representing sector referencing dim_sector.
fare_details_id	Integer	id representing the fare details associated with the pricing component referencing dim_fare_details. The fare class, fare basis codes can be identified using this id
channel_id	Integer	id representing the channel referencing dim_channel. The channel will be the owner channel code for all the transactions.
element_type	varchar	This will be the ssr keyword in case of externally ticketed PNRs. i.e. TKNE / TKNA. TKNM. In case of system generated PNRs, the keyword iResTKT will be used.
agency_id	integer	id representing the agency referencing dim_agency_profile. If the pnr could not be referenced to a particular agency, default -1 will be stored.
user_duty_code_id	integer	id representing the user who completed the transaction referencing dim_user_duty_code
ticket_number	varchar	Ticket number
coupon_number	Integer	The coupon number for the flight in the ticket
fare_amount	decimal	amount associated with the transaction. For data_level OLD, the amount will be (–amount). This amount will be identified using the fares published to the GDS which will be provided by BV. The fares provided will be available in the table ires_dim_fre_fare table. Using the market and the fare class of the PNR, the fare will be identified and will be used for population. Currently this information is not from the external ticket informations.
currency	varchar	currency code
modified_date_utc_id	integer	the date of the transaction in GMT
modified_time_utc_id	integer	the time of the transaction in GMT
modified_date_ltc_id	integer	the date of the transaction in def office time zone
modified_time_ltc_id	integer	the time of the transaction in def office time zone

3.2.3 Payment Details

Table Name	ires_fact_pym_process_payment
Description	This fact table holds all the payment transactions in the source system. And the payment information can be taken based on the fop code also from this table.
Primary Key	airline_iata_code, transaction_id
Indexes	

Column Name	Data Type	Description
airline_iata_code	varchar	
transaction_id	integer	id representing specific payment transaction in the source system.
payment_code_id	integer	id representing the payment code and the fop code referencing the dim_payment_codes
status_id	integer	id representing the payment transaction status referencing the dim_status.
service_initiator_id	integer	id representing service initiator referencing dim_service_initiator..
user_duty_code_id	integer	id representing the user who completed the transaction referencing dim_user_duty_code
tracking_number	varchar	in case of service inititator pnr, the tracking number will be the pnr number. For GA, it would be profile_id
amount	decimal	amount associated with the transaction. For data_level OLD, the amount will be (–amount)
currency	varchar	currency code
description	varchar	
exchange_rate	decimal	
modified_date_utc_id	integer	the date of the transaction in GMT
modified_time_utc_id	integer	the time of the transaction in GMT
modified_date_ltc_id	integer	the date of the transaction in def office time zone
modified_time_ltc_id	integer	the time of the transaction in def office time zone

3.2.4 Ticket Sales

Table Name	ires_fact_ticket_sales
Description	This fact table holds the ticket transactions which involves ticket or coupon status changes. This will have the information of both iFlyRes issued tickets as well as externally issued tickets.
Primary Key	airline_iata_code, ticket_number, coupon_number, ticket_status, coupon_status, type_code_id, flight_id, fare_details_id, sector_id
Indexes	ires_fact_tkt_sales_ticket_fk – airline_iata_code, ticket_number ires_fact_tkt_sales_price_type_fk – type_code_id ires_fact_tkt_sales_flight_fk – flight_id ires_fact_tkt_sales_sector_fk – sector_id ires_fact_tkt_sales_faredtls_fk – fare_details_id ires_fact_tkt_sales_pax_fk – passenger_id ires_fact_tkt_sales_agency_fk – agency_id ires_fact_tkt_sales_channel_fk – channel_id ires_fact_tkt_sales_date_fk – modified_date_ltc_id
Partition	Range Partition based on sale date year -> transaction_date_gmt

Column Name	Data Type	Description
airline_iata_code	varchar	
ticket_number	varchar	Ticket_number
coupon_number	varchar	Coupon number associated with the segment
ticket_status	varchar	ticket status. Possible values are N-ISSUE, REF-REFUND, V-VOID, RI-EXCHANGED. For external tickets, this will be identified from ETM.
coupon_status	varchar	Coupon status. Possible values are O-Open, E-Exchanged, R-Refund, V-Void, F-Flown, L-Lifted, Z-Closed, A-Airport Control, B-Reserved, C-Check in, I-Irregular Ops, S-Suspended, P-Printed, X-Print Exchange. For external tickets, this will be identified from ETM. This represent the coupon status at the time of ticket modification where the ticket status changes to N, V, RI, REF.
type_code_id	integer	Id representing the price type referencing the dim_price_types.
flight_id	integer	Id representing flight referencing dim_flight associated with the ticket coupon.
fare_details_id	integer	Id representing the fare details associated with the pricing component referencing dim_fare_details. The fare class, fare basis codes can be identified using this id
sector_id	integer	Id representing sector referencing dim_sector.
pnr_number	varchar	PNR number associated with the ticket in iFlyRes. The PNR in the ETM will not be used as it will not be reflecting the actual PNR.
ticket_issued_system	varchar	The ticketing system – iFlyRes for internal tickets. For external tickets, it could be Worldspan.
agency_id	integer	Id representing the agency referencing dim_agency_profile. If the pnr could not be referenced to a particular agency, default -1 will be stored.
channel_id	integer	Id representing the channel referencing dim_channel. The channel will be the owner channel code for all the transactions.
prorated_amount	decimal	Amount in the ticket. Will be positive if the ticket transaction is an ISSUE. Will be negative if the ticket transaction is either REFUND, EXCHANGE or VOID.
currency	varchar	currency
user_duty_code_id	integer	id representing the user who completed the transaction referencing dim_user_duty_code
modified_date_utc_id	integer	the date of the transaction in GMT
modified_time_utc_id	integer	the time of the transaction in GMT
modified_date_ltc_id	integer	the date of the transaction in default office time zone
modified_time_ltc_id	integer	the time of the transaction in default office time zone
transaction_date_gmt	date	modified_date. Partition key without time component.

3.2.5 Revenue Doc Sales

Table Name	ires_fact_rac_doc_sales
Description	Table to hold the transactions of revenue dcc sales. This will contain the sales

	information of the ticket and mco
Primary Key	rac_doc_id, transaction_date
Constraints	CK-airline_iata_code,doc_number,coupon_number,coupon_status ,price_type_id,flight_id,fare_details_id,sector_id,user_duty_code_id,agency_id,channel_id, element_code,trigger_action,transaction_date ires_dwh_doc_agency_profile_fk (agency_id) ires_dwh_doc_fare_details_fk (fare_details_id) ires_dwh_doc_channel_fk (channel_id) ires_dwh_doc_user_dutycode_fk (user_duty_code_id) ires_dwh_doc_flight_fk (flight_id) ires_dwh_doc_date_fk (modified_date_ltc_id) ires_dwh_doc_time_fk (modified_time_ltc_id) ires_dwh_doc_type_code_fk (price_type_id)
Partition	Range Partition based on sale date year -> transaction_date

Column Name	Data Type	Description
rac_doc_id	Integer	Auto increment id
airline_iata_code	varchar	airline iata code
document_number	varchar	Document number- Ticket/Mco number
ticket_number	varchar	Ticket number
service_initiator	varchar	The service initiator
tracking_number	Varchar	The tracking number of the ticket/mco
coupon_number	Integer	This will be the coupon number
document_type	Varchar	The document type – Ticket/mco
coupon_status	Varchar	Coupon status at the time of ticket status change
element_code	Varchar	Element code
src_pax_id	Integer	passenger_id representing pax referencing dim_pnr_pax
flight_id	Integer	Id representing flight referencing dim_flight associated with the ticket coupon.
sector_id	Integer	Id representing sector referencing dim_sector.
agency_id	Integer	id representing the agency referencing dim_agency_profile. If the pnr could not be referenced to a particular agency, default -1 will be stored.
channel_id	Integer	id representing the channel referencing dim_channel. If the pnr could not be referenced to a particular agency, default -1 will be stored.
fare_details_id	Integer	id representing the fare details associated with the pricing component referencing dim_fare_details. If the component could not be referenced to a particular fare details, default -1 will be stored. For eg. PER PNR fees
price_type_id	Integer	id representing the price type referencing the dim_price_types
user_duty_code_id	Integer	id representing the user who completed the transaction referencing dim_user_duty_code
amount	Integer	Amount associated with the transaction.

amount_in_def_currency	Integer	Amount associated with the transaction in airline default currency.
currency	Varchar	currency code
modified_date_utc_id	Integer	the date of the transaction in GMT
modified_time_utc_id	Integer	the time of the transaction in GMT
modified_date_ltc_id	Integer	the date of the transaction in def office time zone
modified_time_ltc_id	Integer	the time of the transaction in def office time zone
promocode	varchar	Certificate number/promocode
discount_amt	Integer	Discount amount associated with the transaction
discount_amt_in_def_currency	Integer	Discount amount in airline default office currency
def_currency_exchange_rate	Integer	Exchange rate
tour_operator_code	varchar	Tour operator code
loyalty_number	varchar	Loyalty number
company_name	varchar	Corporate Company name
corporate_id	varchar	Id of the corporate company
travel_type	varchar	Type of travel
fare_calc_area	varchar	Fare calc area
connected_type	varchar	Connected type
last_modified_userid	Integer	Last modified user id referencing dim_user_duty_code
last_modified_agencycode_id	Integer	Last modified agency id referencing dim_agency_profile
last_modified_channel_id	Integer	Last modified channel id referencing dim_channel.
trigger _action	varchar	The trigger action of the transaction
pnr_type	varchar	The type of pnr
segment_status	varchar	Segment status
fare_class	varchar	Fare class
fare_basis	varchar	Fare basis
interline_ind	int	Interline ind
transaction_date	Datetime	The transaction date and the same will be used for the partition

3.2.6 Agency credit record

Table Name	ires_fact_agency_cf_credit_record
Description	This fact table holds the agency credit record details
Primary Key	Type,ag_cf_seq
Indexes	ires_fact_agency_cf_credit_serv_initiator_fk (service_initiator_id), ires_fact_agency_cf_user_duty_code_fk (user_duty_code_id), ires_fact_agency_cf_user_details_fk (user_details_id), ires_fact_agency_cf_credit_channel_fk (channel_id), ires_fact_agency_cf_agency_profile_fk (agency_id), ires_fact_agency_cf_date_ltc_fk (modified_date_ltc_id),

	ires_fact_agency_cf_time_ltc_fk (modified_time_ltc_id), ires_fact_agency_cf_idx (tracking_number),
Partition	

Column Name	Data Type	Description
airline_iata_code	varchar	Airline iata code
credit_rec_num	varchar	Credit File number. This will be null when the transaction is corresponding to an agency credit transaction.
Type	varchar	AG/CF representing the type of transaction
tracking_number	varchar	Tracking_number
transaction_date	timestamp	Date of transaction
process_service_initiator	varchar	This is the service initiator if the CF is used for payment. Required for identifying the type of transaction in report. Null for agency
process_tracking_number	varchar	For CF alone. Need to identify the PNR number if CF is used for PNR payment
transaction_id	varchar	Transaction id
positive_trans_ind	char	For CF only. N for debit and Y for credit
process_transaction_id	decimal	For CF only. Required to identify the status in the report
credit_limit	decimal	Maximum credit available. For CF take from TRANSACTION_AMOUNT and for agency take from credit_limit
balance_amount	decimal	Balance amount in the credit.Take from available_credit for CF and balance_amount for AG
curr_tran_amount	varchar	Amount in the current transaction. For CF take from CURR_TRAN_AMOUNT and for AG TRANSACTION_AMOUNT
Action	varchar	Agency only. Required to identify the status in report
currency	varchar	currency
credit_file_type_code	varchar	CF only.
service_initiator	varchar	Service initiator
Status	varchar	CF only. ACTIVE or not
general_comments	timestamp	Comments added while creating CF. Only for CF
manual_pnr_refund_ind	integer	1/0. 1 when CF is used for manual refund.only for CF
last_modified_date	integer	Last modified date
channel_id	integer	Id representing the channel referencing dim_channel. The channel will be the modified channel code for all the transactions.
agency_id	integer	Id representing the agency referencing dim_agency_profile. If the pnr could not be referenced to a particular agency, default -1 will be stored.
service_initiator_id	integer	Id representing the service initiator referencing ires_dim_pym_service_initiator
user_duty_code_id	Integer	id representing the user who completed the transaction referencing dim_user_duty_code
user_details_id	integer	id representing the user who completed the transaction referencing dim_user_details
modified_date_utc_id	integer	the date of the transaction in GMT
modified_time_utc_id	integer	the time of the transaction in GMT

modified_date_ltc_id	integer	the date of the transaction in default office time zone
modified_time_ltc_id	integer	the time of the transaction in default office time zone