

```

%% THIS PROGRAM WILL SIMULATE CORRELATED STANDARD NORMAL FIELD USING K-L
%% EXPANSION METHOD (HOME ASSIGNMENT 1)
% SUBMITTED BY: Rudraprasad Bhattacharyya
%-----
clc; clear all; close all;
% Discretization of "t" domain
start_point=0;
end_point=1;
N_interval=20;           % No. of intervals
interval_size=(end_point-start_point)/N_interval;
N_points=N_interval+1;
t=linspace(start_point,end_point,N_points);
N_simulations=10000;      % Total number of experiments
%% Construction of target Auto-correlation matrix R
for i=1:1:N_points
    for j=1:1:N_points
        tau=(j-i)*interval_size;
        R(i,j)=exp(-abs(tau));
    end
end
R1=R(:,1);
%% Simulation of correlated random field
% EVALUATION OF EIGENVALUE AND EIGEN FUNCTIONS
[f,lambda]=eig(R);
for simulation=1:N_simulations

    for i=1:N_points
        g(:,i)=sqrt(lambda(i,i)).*f(:,i)*randn;
    end

    G_storage(:,simulation)=sum(g,2);
end
%% Check: Estimation of simulated data
% Calculation of correlation coefficient
G_storage=G_storage';
for i=1:N_points
    g_1=G_storage(:,i);
    for j=1:N_points
        g_2=G_storage(:,j);
        Expectation_g1g2=(g_1'*g_2)/N_simulations;
        Expectation_g1=mean(g_1);
        Expectation_g2=mean(g_2);
        std_dev_g1=std(g_1);
        std_dev_g2=std(g_2);
        computed_correlation=abs((Expectation_g1g2-(Expectation_g1)*(Expectation_g2))/
(std_dev_g1*std_dev_g2));
        computed_correlation_matrix(i,j)=computed_correlation;
    end
end
C1=computed_correlation_matrix(:,1);
% Plot the correlation
figure;
plot(t,R1,'k.-',t,C1,'r*-');xlabel('t');ylabel('R(\tau)');
legend('Target correlation','Simulated correlation');

```

