

# PAN-OS 7.0 FIREWALL ESSENTIALS LAB SERIES

Lab 7: File Blocking and WildFire

Document Version: 2016-04-19

Copyright © 2016 Network Development Group, Inc. www.netdevgroup.com

NETLAB Academy Edition, NETLAB Professional Edition, and NETLAB+ are registered trademarks of Network Development Group, Inc.

Palo Alto Networks and the Palo Alto Networks logo are trademarks or registered trademarks of Palo Alto Networks, Inc.




#### Lab 7: File Blocking and WildFire

# **Contents**

Intr	oduction	3
	ective	
_	I Topology	
	Settings	
	Configure the Initial Settings	
	Create a File Blocking Profile	
	Create a WildFire Analysis Profile	
	Assign the File Blocking and WildFire Profiles to the Profile Group	
	Test the File Blocking Profile	
	Test the WildFire Analysis Profile	



#### Introduction



Now that traffic is passing through the firewall, you decide to further protect the environment with some more security profiles. The additional security requirements for general Internet traffic are:

- Configure downloaded pdf files to be automatically blocked.
- Test file blocking by trying to download a pdf file.
- Configure WildFire and confirm that executable files are sent to WildFire for analysis.




# **Objective**

In this lab, you will be utilizing Palo Alto technology to perform the following tasks:

- 1. Configure security profiles for file blocking and WildFire analysis
- 2. Add these security profiles to the security profile groups associated with the security rule



# **Pod Topology**







# **Lab Settings**

The information in the table below will be needed in order to complete the lab. The task sections below provide details on the use of this information.

Virtual Machine	IP Address	Account (if needed)	Password (if needed)
Ubuntu Desktop 1	192.168.10.50	sysadmin	Train1ng\$
Ubuntu Server	192.168.10.10	sysadmin	Train1ng\$
Ubuntu Desktop 2	172.30.1.10	sysadmin	Train1ng\$
Palo Alto Firewall	192.168.10.1 172.30.1.1	admin	paloalto



## 1 Configure the Initial Settings

- 1. Click on the **Desktop 1** graphic found on the *topology page*.
- Login using sysadmin as the username and Training\$ as the password. Click Log In.
- 3. Double-click on the **Firefox Web Browser** icon located on the *Desktop*.



4. In the address field, type https://192.168.10.1 and press Enter.


If you experience the "Unable to connect" message while attempting to connect to the specified IP above, please wait an additional 3-5 minutes for the PA VM to fully initialize and refresh the page to continue.

5. Login with the *username* admin and *password* paloalto on the firewall web interface.







 Using the Palo Alto WebUI, navigate to Device > Setup > Operations and click on Load named configuration snapshot underneath the Configuration Management section.



7. In the *Load Named Configuration* window, select **Basic-App-Config** from the *Name* drop-down box. Click **OK**.




- 8. When prompted with the config loaded message, click on the **Close** button to continue.
- 9. Click on the **Commit** link located at the top-right of the *WebUI*.






10. In the Commit window, click Commit to proceed with committing the changes.



11. Once the operation successfully completes, click **Close** to continue.




12. Leave the WebUI opened to continue with the next task.



## 2 Create a File Blocking Profile

1. Using the WebUI, navigate to Objects > Security Profiles > File Blocking.



2. Click on **Add**, located near the bottom of the window, to create a file blocking profile.




3. In the *File Blocking Profile* window, use the information from the table below to fill out the form fields.

Field	Data/Selection
Name	Enter student-file-blocking
Rules list	Click Add and create a rule with these parameters:  • Rule Name: Enter BlockPDF  • Applications: any • File Types: pdf • Direction: both • Action: block
Rules list	<ul> <li>Rule Name: Enter BlockPDF</li> <li>Applications: any</li> <li>File Types: pdf</li> <li>Direction: both</li> </ul>



Lab 7: File Blocking and WildFire




- 4. Click **OK** to save changes.
- 5. Leave the WebUI opened to continue with the next task.



### 3 Create a WildFire Analysis Profile

1. Using the WebUI, navigate to Objects > Security Profiles > WildFire Analysis.



2. Click on **Add**, located near the bottom of the window, to create a new antispyware profile.




3. In the *WildFire Analysis Profile* window, use the information from the table below to fill out the form fields.

Field	Data/Selection
Name	Enter student-wildfire
Rules list	Click Add and create a rule with these parameters:  • Rule Name: Enter AnalyzeEXE • Applications: any • File Types: pe • Direction: both • Analysis: public-cloud



Lab 7: File Blocking and WildFire




- 4. Click **OK** to save the rule.
- 5. Leave the WebUI opened to continue with the next task.



## 4 Assign the File Blocking and WildFire Profiles to the Profile Group

1. Using the *WebUI*, navigate to **Objects > Security Profile Groups**.




2. Click on **Add**, located near the bottom of the window, to define a security profile group.




3. In the *Security Profile Group* window, use the information from the table below to fill out the form fields.

Field	Data/Selection
Name	Enter student-profile-group
File Blocking Profile	Select student-file-blocking
WildFire Analysis Profile	Select student-wildfire





- 4. Click **OK** to save changes.
- 5. Navigate to **Policies > Security**.




6. Click on the Basic-Allowed-Apps link in the list of policy names.




- 7. In the Security Policy Rule window, edit the policy by clicking on the Actions tab.
- 8. Select **Group** from the *Profile Type* drop-down menu.




9. Then, select **student-profile-group** from the *Group Profile* drop-down menu.



- 10. Click **OK** to save changes.
- 11. Click on the **Commit** link, located near the top-right of the *WebUI*.



12. In the *Commit* window, click the **Commit** button.



- 13. Once the commit process successfully completes, click the **Close** button to continue.
- 14. Leave the *Firefox* application opened to continue with the next task.



## 5 Test the File Blocking Profile

- 1. Using the *Firefox* application, open a **new tab**.
- 2. Type http://www.panedufiles.com into the address field and press Enter.
- Click on the Panorama\_AdminGuide70.pdf file link located near the top of the webpage.



#### 201 PAN Firewall Essentials I (7.0) Files

#### File-Blocking and WildFire Lab

Panorama\_AdminGuide70.pdf

4. Notice the file transfer was blocked.

#### File Transfer Blocked

Transfer of the file you were trying to download or upload has been blocked in accordance with company policy. Please contact your system administrator if you believe this is in error.

File name: Panorama\_AdminGuide70.pdf

- 5. Close the second tab.
- 6. Navigate back to the **first tab** with the WebUI.
- Using the WebUI, navigate to Monitor > Logs > Data Filtering to view the log entries.
- 8. Identify the log entry for the PDF file that has been blocked.

	Receive Time	File Name	Name	From Zone	To Zone
<b></b>	03/24 10:37:31	Panorama_Adm	Adobe Portable Document Format (PDF)	Untrust-L3	Trust-L3

9. Leave the *Firefox* web browser opened to continue with the next task.




## 6 Test the WildFire Analysis Profile

- 1. Using the *Firefox* application, open a **new tab**.
- 2. Type http://wildfire.paloaltonetworks.com/publicapi/test/pe into the address field and press **Enter**.

This site generates an attack file with a unique signature, which simulates a zero-day attack.

3. When prompted, click the **Save File** button.



- 4. Save the file in the **Downloads** directory and click **Save**.
- 5. Close the second **tab**.
- 6. To verify the file was uploaded to the *Public WildFire Cloud*, open a terminal window by clicking on the **LXTerminal** icon located on the bottom tool pane.



7. In the terminal window, type the command below followed by pressing the Enter key.

ssh admin@192.168.10.1

8. When prompted for a password, enter paloalto. Press **Enter**.




9. Once logged in via SSH, enter the debug command below to view the output showing "log: 0, filename: wildfire-test-pe-file-exe processed...". This verifies the file was uploaded to the WildFire Public Cloud.

```
debug wildfire upload-log show
```

```
Upload Log disk log rotation size: 2.000 MB.
Public Cloud upload logs:
    log: 0, filename: wildfire-test-pe-file.exe
    processed 60 seconds ago, action: upload success
    vsys_id: 1, session_id: 1102, transaction_id: 1
    file_len: 55296, flag: 0x801c, file type: pe
    threat id: 52020, user_id: 0, app_id: 109
    from 192.168.10.50/56369 to 52.20.176.145/80
    SHA256: 7dfd57fc5c882d7le02e31c968a3c39d16b3f890f3a3c16cd99882f528b307f9
Private Cloud upload logs:
```

Change focus back to the Firefox web browser and navigate to Monitor > Logs > WildFire Submissions.



11. Locate the entry for *wildfire-test-pe-file.exe* that has been submitted to WildFire and notice the file has been identified as *malicious* underneath its respective *Verdict* column.


If the *wildfire-test-pe-file.exe* does not automatically appear in the list, wait a couple of minutes for it to populate. The manual refresh button may be used if necessary.

12. Click on the **magnifying glass** icon next to the *wildfire-test-pe-file.exe* entry to see a detailed log view.





- 13. In the *Detailed Log View* window, make sure to view the **Log Info** tab and review the information within the *General*, *Details*, and *Destination* panels.
- 14. In the *Detailed Log View* window, click on the **Wildfire Analysis Report** tab and review the information provided. Click on the **Close** button when finished.



15. Close the **Desktop 1** PC viewer.