

Case 21: Wind-driven elliptical spread

ELMFIRE Verification and Validation Suite

September 2, 2026

1 Verification purpose

Case ID: CASE21_WDE. This case verifies the coupling of wind-adjusted surface spread to the Huygens and level-set propagation geometry. Uniform fuels and flat terrain isolate wind as the only directional forcing. The verification question is whether the simulated head rate is within 10 percent of 3.635 m min^{-1} and the unclipped arrival-time isochrone has length-to-width ratio within 10 percent of 1.24.

The scientific setup and historical expected response are reconstructed from Section 3.2 of the supplied *ELMFIRE Guide*. The Guide is used as reference provenance, not as an instruction or a substitute for evidence. Configuration statements below are checked against the generated GeoTIFFs and namelist; current results and decisions come only from case-local outputs and generated metrics. Where the generated experiment differs from the historical example, the report states that difference explicitly.

2 Mathematical formulation and numerical implementation

The normal-velocity construction combines the backing, flanking, and heading rates into an expanding ellipse. Its major axis aligns with the wind-driven heading direction, while the ratio L/W characterizes anisotropy independent of absolute size. ELMFIRE writes rate in metres per minute and arrival time on the same raster grid used to infer the ellipse.

For uncovered fuel of depth H ft, the Guide uses

$$WAF_u = \frac{1.83}{\ln[(20 + 0.36H)/(0.13H)]}, \quad U_{mf} = WAF_u U_{20}. \quad (1)$$

The resulting effective midflame wind determines the ellipse aspect ratio

$$\frac{L}{W} = \min(0.936e^{0.1147U_{mf,e}} + 0.461e^{-0.0692U_{mf,e}} - 0.397, 8). \quad (2)$$

The local head rate is $R_H = R_0(1 + \phi_w)$; the Huygens/level-set construction uses the ellipse to obtain normal speed away from the heading direction.

3 Derivation of expected behavior

Constant forcing produces self-similar elliptical isochrones: scaling time changes both axes proportionally and leaves L/W constant. The configured Fuel Model 5 response supplies the independent head-rate target 3.635 m min^{-1} , and the GUIDE construction supplies $L/W = 1.24$.

For the generated Fuel Model 5 state, the independent no-wind rate is $R_0 = 0.41042 \text{ m min}^{-1}$. The 6 mph 20-ft wind and 2-ft fuel-bed depth give a wind-adjustment factor $WAF = 0.418640$, hence $U_{mf} = 6(0.418640) = 2.51184 \text{ mph}$. With the calculated wind factor $\phi_w = 7.87958$,

$$R_h = R_0(1 + \phi_w) = 0.41042(1 + 7.87958) = 3.6444 \text{ m min}^{-1},$$

consistent with the Guide reference 3.635 m min^{-1} . The ellipse length-to-width reference uses

$$\frac{L}{W} = 0.936e^{0.2566U} + 0.461e^{-0.1548U} - 0.397,$$

where U is in m s^{-1} . Here $U = 2.51184 \text{ mph}(0.44704) = 1.12291 \text{ m s}^{-1}$, so substitution gives $L/W = 1.23898$, reported as 1.24. The report evaluates the relative substitutions $e_R = |R_h - 3.635|/3.635$ and $e_{LW} = |(L/W) - 1.24|/1.24$ against their tabulated limits.

4 Verification metrics and acceptance criteria

Maximum finite `vs` measures the heading response. The shape metric is $\sqrt{\lambda_{\max}/\lambda_{\min}}$, where the eigenvalues come from the covariance of burned-cell coordinates at the last isochrone that remains away from the boundary. This metric is rotation invariant and avoids a wind-axis assumption. Each component uses 10 percent relative tolerance, and both must pass.

5 Simulation configuration and predicted outcome

The 126×126 , 30 m domain uses uniform Fuel Model 5, 6 mph wind, flat terrain, and an upwind point ignition. The predicted arrival field is an ellipse elongated downwind, with head ROS 3.635 m min^{-1} and $L/W = 1.24$.

Parameter	Configured value	Units	Role in the experiment
Grid	126×126 at 30	m per cell	Resolves the whole spatial response on the generated north-up raster
Projection	EPSG:32635	—	Fixes the map-coordinate and row-orientation convention
Time control	$\Delta t = 1$, $t_{\text{stop}} = 259200$	s	Whole-second step; stop time is an exact timestep multiple
Meteorology interval	3600	s	Defines weather-band timing and stalled-final compatibility
Live moisture	herb 60; woody 90	percent	Holds live-fuel damping fixed while the named mechanism is isolated
Evidence	prepared inputs; final case outputs	—	Separates configuration provenance from acceptance evidence

Figure 1 is generated mechanically from the prepared case-local GeoTIFF inputs. It identifies the selected source artifact and representative variant; the left panel shows a fuel, terrain, moisture, wind, canopy, or other controlling field selected for this experiment, and the right panel shows the cells selected by the non-positive initial level-set field. No values in this figure are redrawn or inferred from the expected response.

Whole-domain input configuration — data; WS=6 mph, WD=0 deg




Figure 1: Prepared input conditions from case-local generated rasters. Coordinates are in metres; the colorbar identifies the displayed field and its physical units or category. The ignition panel is derived directly from $\phi \leq 0$.

6 Actual simulation results

The required evidence is generated only from case-local ELMFIRE outputs. The current postprocessing status is **PASS**; 2 of 2 required metric rows pass across 1 variant(s). A missing output is reported as NOT RUN or NOT EVALUABLE and is not interpreted as verification evidence.




Figure 2: Final whole-domain ELMFIRE time of arrival for the displayed variant, in seconds. The figure annotation records the selected case-local GeoTIFF path and coordinate reference system; the generated metrics table, not visual appearance, determines acceptance.

7 Calculated metrics and verification decision

Variant / metric	Expected	Calculated	Status
main / head ROS	3.635 m/min	3.64438 m/min	PASS
main / L/W ratio	1.24 -	1.24859 -	PASS

The displayed overall decision is **PASS**. When `outputs/metrics.json` exists, `scripts/postprocess.py` generates every table value and status; when it is absent, the standalone wrapper renders NOT EVALUABLE with no invented rows.

8 Technical interpretation

A rate-only discrepancy points toward wind adjustment or unit conversion; a shape-only discrepancy points toward wavelet geometry, arrival-time extraction, or boundary clipping. No scientific conclusion should be drawn when the status is NOT RUN or NOT EVALUABLE.

9 Scope and limitations

The test covers one steady wind speed and one fuel model. The covariance estimator is intentionally applied only before boundary contact. This case provides implementation verification evidence only.