

Case 01: Biomass Emission-Time Resolution Independence

1 Verification purpose

Case ID: CASE01_BET

This case verifies that biomass-emission duration is represented as a physical residence time rather than a grid-dependent number of solver steps. Changing cell size must preserve accumulated firebrand density for the same unit-width source and forcing.

The test exposes incorrect conversion between per-cell and unit-width generation rates, timestep-dependent source integration, and unintended cell-width scaling. Success requires overlapping down-wind profiles and mesh-independent far-field accumulation within tolerance.

2 Mathematical formulation and numerical implementation

A surface-fire cell emits firebrands while the flame front crosses that cell. For a square cell of size $\Delta x = \Delta y$ and surface-fire spread rate V_s , the emission duration is

$$t_{\text{emission}} = \frac{\Delta x}{V_s}.$$

Without this duration scaling, changing the resolution would change the time for which a burning cell acts as a firebrand source and would therefore change the accumulated deposition solely as a numerical artifact.

This case represents a one-dimensional firebrand-transport problem with a 1 m-wide strip perpendicular to the transport direction. The unit-width firebrand generation rate is

$$\text{GR}_{1\text{m}} = 33.3 \text{ pcs s}^{-1} \text{ MW}^{-1}.$$

ELMFIRE applies `EMBER_GR_PER_MW_VEGE` to the total fire power of a computational pixel. A pixel with fireline intensity I_B and cross-stream width Δy has fire power $I_B \Delta y$. Its firebrand generation rate is therefore

$$\dot{N}_{\text{pixel}} = I_B \Delta y \text{ GR}_{\text{ELMFIRE}}.$$

To keep the represented source equal to the 1 m-wide source at every grid resolution, preprocessing sets

$$\text{GR}_{\text{ELMFIRE}} = \frac{\text{GR}_{1\text{m}}}{\Delta y} = \frac{33.3}{\Delta x} \text{ [pcs s}^{-1} \text{ MW}^{-1}\text{]}.$$

The configured `EMBER_GR_PER_MW_VEGE` values are consequently 6.66, 3.33, and 1.11 pcs/s/MW for the 5, 10, and 30 m variants. In all three variants, $\text{GR}_{\text{ELMFIRE}} \Delta y = \text{GR}_{1\text{m}}$, so the unit-width source strength is independent of cell size.

2.1 Implementation path

The documented residence-time formulation requires a burning cell to emit only while the flame resides in that cell [1]. In the current implementation, `READ_SPOTTING` reads the PER-MW source parameters, `SPOTTING` calls `EMBER_TO_EMIT_PER_CELL` to convert fireline intensity and cell width to an ember rate, and `CALC_SPOTTING_DURATION` determines the source lifetime from the cell fire state. Accumulated deposition, fireline intensity, and spread-rate rasters are then written for postprocessing. The report checks both halves of the discretization: preprocessing keeps the represented one-metre source strength

intensive by scaling the configured rate with cross-stream cell size, and postprocessing derives the expected density from the simulated FLIN and VS at the same physical state. A source-duration or pixel-power scaling defect would therefore create a systematic resolution trend. This is a controlled code-verification test; it does not validate the empirical generation constant or the transport distribution against experiments.

3 Derivation of expected behavior

Combining the pixel generation rate with the emission duration gives the number emitted while the front crosses one cell. Dividing that number by the represented bin area eliminates Δx and gives the expected accumulated density:

$$N''_{\text{ref}} = \frac{I_B \Delta y \text{GR}_{\text{ELMFIRE}}(\Delta x/V_s)}{\Delta x(1 \text{ m})} = \text{GR}_{1\text{m}} \frac{I_B}{V_s} \quad [\text{pcs m}^{-2}].$$

Thus, the reference is calculated separately from the fire behavior actually produced by each simulation; it is not a fixed nominal number. The postprocessor finds the maximum positive fireline intensity in the usable interior of the latest `flin_*.tif` and reads the spread rate from the corresponding cell of `vs_*.tif`. ELMFIRE writes these fields in kW/m and ft/min for this configuration, so the implemented conversion is

$$N''_{\text{ref}} = 33.3 \frac{I_{B,\text{sim}}/1000}{V_{s,\text{sim}}(0.3048/60)} \quad [\text{pcs m}^{-2}].$$

For the current outputs, the mean values across the variants are $I_{B,\text{sim}} = 2.200042 \text{ MW/m}$ and $V_{s,\text{sim}} = 0.577015 \text{ m/s}$. These values give $N''_{\text{ref}} = 126.966 \text{ pcs/m}^2$. The per-variant values and selected raster cells are retained in `../outputs/metrics.json`.

The generated numerical substitutions make the cancellation visible. With $CFL_w = 0.5$ and $U = 6.71 \text{ m s}^{-1}$,

Δx (m)	5	10	30
$\Delta t_{\text{generated}}$ (s)	0.372578	0.745156	2.000000
$GR_{\text{ELM}} = 33.3/\Delta x$	6.66	3.33	1.11
$GR_{\text{ELM}}\Delta y$	33.3	33.3	33.3

in $\text{pcs s}^{-1} \text{ MW}^{-1}$ for the last two rows. The 5- and 10-m CFL steps divide the requested 500-s duration exactly. At 30 m, the nominal CFL step is 2.235469 s; preprocessing selects the conservative whole-second divisor 2 s, giving 250 steps and preserving the 500-s stop while keeping $CFL_w = 0.4473 < 0.5$. Thus the source-scaling reference is exactly 33.3 in all three variants, and its relative error is

$$e_{GR} = \max_i \frac{|GR_i \Delta y_i - 33.3|}{33.3}, \quad e_{GR,\text{ref}} = 0.$$

The run-derived FLIN and VS values enter only as controlled fire-behavior normalizers; the ember-flux field being tested does not determine them. With $0.3048/60 = 0.00508$,

$$N''_{\text{ref}} = 33.3 \frac{FLIN/1000}{VS(0.00508)} = 6.555118 \frac{FLIN [\text{kW m}^{-1}]}{VS [\text{ft min}^{-1}]} \quad \text{pcs m}^{-2}.$$

For each generated mesh the expected far-field error is therefore zero, and the substituted decision requires

$$\text{mean}_{150 < x \leq 200} |N'' - N''_{\text{ref}}|/N''_{\text{ref}} \leq 0.05.$$

4 Verification metrics and acceptance criteria

For each resolution, the centre-row accumulated count N_i is converted to an areal density for the represented one-metre strip,

$$n''_i = \frac{N_i}{\Delta x (1 \text{ m})}.$$

The independent reference uses the maximum-FLIN valid interior cell from the same run,

$$n''_{\text{ref}} = GR_{1m} \frac{FLIN/1000}{VS (0.3048/60)},$$

where FLIN is read in kW m^{-1} , VS in ft min^{-1} , and $GR_{1m} = 33.3 \text{ pcs s}^{-1} \text{ MW}^{-1}$. The comparison mask contains finite physical cells with $150 < x \leq 200 \text{ m}$; the two-cell halo is excluded.

4.1 Justification of metric quantification

The source-scaling check is an algebraic invariant rather than an empirical model tolerance. Preprocessing computes $G_{R,\Delta x} \Delta x$ from the same double-precision inputs used to write the namelist, so a relative allowance of 10^{-12} admits only floating-point roundoff and still detects any omitted or duplicated width factor. The 5% density-error limit is applied to a far-field mean because the derived expectation is a developed plateau, not a pointwise subcell solution. It permits the cell integration, discrete selection of the run-derived FLIN/VS reference cell, and finite-window averaging to differ slightly while remaining far below the order-one, resolution-proportional error caused by incorrect extensive/intensive scaling. Requiring the limit at every resolution makes the criterion a grid-consistency test rather than an agreement obtained by cancellation in one variant. Completeness and the conjunctive decision are logical requirements: without every source and reference raster, neither the normalization nor the claimed resolution independence is testable.

4.2 Predeclared acceptance contract

Table 1 summarizes the metrics fixed before inspection of the calculated results. Numerical values and component statuses are reported separately in Section 7.

Table 1: Predeclared verification metrics and acceptance criteria.

Metric	Output, region, and aggregation	Acceptance criterion
Output completeness	Final <code>ember_flux</code> , <code>flin</code> , and <code>vs</code> rasters for each manifest variant; shape, cell size, nodata, and halo are validated.	3 of 3 variants usable
Unit-width source scaling	Configured rate multiplied by cross-stream cell width, $G_{R,\Delta x} \Delta x$.	$33.3 \text{ pcs s}^{-1} \text{ MW}^{-1}$ to 10^{-12} relative tolerance
Far-field mean relative error	$E_r = \text{mean}_{150 < x \leq 200} n''_i - n''_{\text{ref}} / n''_{\text{ref}}$, evaluated separately for every resolution.	$E_r \leq 0.05$ for every variant
Overall decision	Conjunction of completeness, source scaling, and all per-resolution error decisions.	PASS only if every component passes

5 Simulation configuration and predicted outcome

Figure 1 records the prepared spatial inputs for dx10. The postprocessor reads these panels from the variant-local GeoTIFF files, removes the two-cell numerical buffer, and retains map coordinates in

metres. The left panel shows the most informative fuel or structure layout available for the case; the right panel shows the cells selected by the non-positive initial level-set field, making a localized ignition or firebrand-emission source explicit.




Figure 1: Whole-domain prepared input configuration for the representative variant. The physical domain is shown without the numerical halo; coordinates, configured wind values, fuel or structure layout, and initial ignition/source geometry are identified in the panels.

The preprocessor creates flat, uniform FBFM102 domains at $\Delta x = \Delta y = 5, 10$, and 30 m. The physical simulation domain is the same for every resolution. Each raster also includes a two-cell numerical buffer outside each side of that physical domain. The ignition is placed in the first usable column rather than in the buffer. Crosswind transport and secondary firebrand ignition are disabled so the accumulated deposition can be evaluated as a one-dimensional profile.

ELMFIRE writes the accumulated number of deposited firebrands in each target pixel. The area represented by a streamwise bin in the unit-width problem is $\Delta x \times 1$ m, so the postprocessor converts the pixel count N_i to density using

$$N''(x_i) = \frac{N_i}{\Delta x(1 \text{ m})} = \frac{N_i}{\Delta x} \quad [\text{pcs m}^{-2}].$$

The two buffer columns on each end are excluded from this profile.

For each completed variant, the mean accumulated density over $150 < x \leq 200$ m is compared with that variant's FLIN/VS-derived reference. The mean relative error must not exceed 5%. The case passes only when all three variants have valid outputs and pass independently. Agreement across the three resolutions demonstrates that both the emission duration and the unit-width generation-rate scaling are resolution independent.

6 Actual simulation results

Figure 2 shows the representative accumulated firebrand density from dx10. It is read from the actual ELMFIRE output named in the panel, masks nodata, and excludes the two-cell numerical buffer. Firebrand counts are normalized by the cell length and the represented 1-m cross-stream strip, giving units of pcs m^{-2} .




Figure 2: Whole-domain accumulated firebrand density from the representative completed ELMFIRE run. This domain-scale result supplements, rather than replaces, the higher-level verification profiles, convergence plots, ensemble statistics, and calculated acceptance metrics below.

Figure 3 first presents the physical observable in the same three-resolution arrangement used to define the test. All bars are calculated from final ELMFIRE ember-flux rasters, and each dashed line uses the FLIN and spread rate extracted from that same variant.




Figure 3: Accumulated firebrand density for the 5, 10, and 30 m grids. The dashed red line in each panel is the run-derived reference. The two-cell numerical halo is excluded from every profile.

7 Calculated metrics and verification decision

The overall decision is sourced from the generated metric macros and is **pass**.

Quantity	Value
Overall status	pass
Mean reference fireline intensity	2.200042 MW/m
Mean reference spread rate	0.577015 m/s
Calculated accumulation reference	126.966 pcs/m ²
Variants configured	3
Variants computed	3

Table 2: Biomass emission-time verification summary.

8 Technical interpretation

Agreement between the accumulated deposition density and the independently calculated FLIN/VS reference verifies the complete chain from biomass consumption through emission duration, per-unit-area source scaling, transport, and raster accumulation. Consistent agreement across the three grids further indicates that the implemented source normalization is not tied to cell area.

9 Scope and limitations

This case isolates a uniform, one-dimensional transport problem with crosswind dispersion, delayed ignition, and secondary spotting disabled. It verifies emission-time scaling and accumulated deposition, but does not by itself validate stochastic trajectories or ignition physics. The preprocessing parameters, variant manifest, calculated raster samples, and metric values are retained with the case so that the reported decision can be reproduced.

References

- [1] Y. Qin, *A Physics-Based Eulerian Framework for Modeling Firebrand Showering in Regional-Scale Wildland and Wildland–Urban Interface Fire Simulations*, Ph.D. dissertation, University of Maryland, College Park, 2025.