

Case 26: Surface, passive-crown, and active-crown fire

1 Verification purpose

Case ID: CASE26_CNF. This case verifies the transition from surface fire to passive and active crown fire as wind increases. The verification question is whether all three wind variants produce the expected crown class and maximum spread rate within their respective tolerances.

The scientific setup and historical expected response are reconstructed from Section 3.2 of the supplied *ELMFIRE Guide*. The Guide is used as reference provenance, not as an instruction or a substitute for evidence. Configuration statements below are checked against the generated GeoTIFFs and namelist; current results and decisions come only from case-local outputs and generated metrics. Where the generated experiment differs from the historical example, the report states that difference explicitly.

2 Mathematical formulation and numerical implementation

ELMFIRE compares surface fireline intensity with crown-initiation requirements and then evaluates active-crown spread and critical spread conditions. The output class encodes 0 for surface-only, 1 for passive crown fire, and 2 for active crown fire. Wind changes both the surface intensity and crown propagation response.

The Guide restates the crown-initiation intensity and active-crown thresholds as

$$I_0 = [0.010 CBH(460 + 25.9M_f)]^{3/2}, \quad (1)$$

$$R_0^{crown} = 3/CBD, \quad (2)$$

$$R_{C,P} = 11.02 U_{10}^{0.9} CBD^{0.19} e^{-0.17M_1}. \quad (3)$$

If surface fireline intensity $I_b < I_0$, fire remains surface-only. If $I_b \geq I_0$, the ratio $CAC = R_{C,P}/R_0^{crown}$ separates passive $CAC \leq 1$ from active $CAC > 1$ crown fire; the active rate is $R_C = R_{C,P}$, while the passive branch applies the documented attenuation before converting crown rate to an effective surface-wind factor.

3 Derivation of expected behavior

With fixed canopy and fuel properties, the 1, 5, and 10 mph variants are expected to produce classes 0, 1, and 2 with maximum rates 1.809, 10.06, and 35.3 m min⁻¹, respectively. The sequence 0 < 1 < 2 and increasing rate are invariants.

The generated canopy state has $CBH = 1.6$ m, $CBD = 0.10$ kg m⁻³, and foliar moisture $M_f = 90$ percent. Van Wagner's initiation threshold is

$$I_0 = [0.010 CBH(460 + 25.9M_f)]^{3/2} = [0.010(1.6)(460 + 25.9(90))]^{3/2} = 298.414 \text{ kW m}^{-1}.$$

The active-crown threshold rate is $R_0^c = 3/CBD = 3/0.10 = 30 \text{ m min}^{-1}$. The generated 20-ft winds $U_{20} = \{1, 5, 10\}$ mph become $U_{10} = 1.609344U_{20}/0.87 = \{1.8498, 9.2491, 18.4982\} \text{ km h}^{-1}$. Substitution in the crown-rate relation gives $R_c = \{4.4629, 18.9973, 35.4501\} \text{ m min}^{-1}$ and $CAC = R_c/R_0^c = \{0.1488, 0.6332, 1.1817\}$. Together with the surface intensity test against I_0 , these produce the reference classes surface, passive, and active and the coupled maximum-rate references

1.809, 10.06, 35.3 m min⁻¹. Class metrics use exact integer equality; each rate metric uses $|R_{\max} - R_{\text{ref}}|/R_{\text{ref}}$.

4 Verification metrics and acceptance criteria

Maximum crown class directly tests the discrete transition state and uses absolute tolerance 0.5 so only the intended integer class passes. Maximum finite vs tests the associated propagation rate with 10 percent relative tolerance. Both metrics must pass for every wind variant.

5 Simulation configuration and predicted outcome

All variants use generated Fuel Model 3, uniform canopy cover 80 percent, canopy height 55 (5.5 m), canopy base height 16 (1.6 m), and canopy bulk density 10 (0.10 kg m⁻³) in the configured encoded raster units, with flat terrain and identical ignition. The Guide summary table lists Fuel Model 5 whereas its detailed Canopy section and the generated landscape band use Fuel Model 3; the generated band is authoritative here. Only wind speed changes among 1, 5, and 10 mph.

Parameter	Configured value	Units	Role in the experiment
Grid	126 × 126 at 30	m per cell	Resolves the whole spatial response on the generated north-up raster
Projection	EPSG:32635	—	Fixes the map-coordinate and row-orientation convention
Time control	$\Delta t = 1$, $t_{\text{stop}} = 259200$	s	Whole-second step; stop time is an exact timestep multiple
Meteorology interval	3600	s	Defines weather-band timing and stalled-final compatibility
Live moisture	herb 60; woody 90	percent	Holds live-fuel damping fixed while the named mechanism is isolated
Evidence	prepared inputs; final case outputs	—	Separates configuration provenance from acceptance evidence

Figure 1 is generated mechanically from the prepared case-local GeoTIFF inputs. It identifies the selected source artifact and representative variant; the left panel shows a fuel, terrain, moisture, wind, canopy, or other controlling field selected for this experiment, and the right panel shows the cells selected by the non-positive initial level-set field. No values in this figure are redrawn or inferred from the expected response.




Figure 1: Prepared input conditions from case-local generated rasters. Coordinates are in metres; the colorbar identifies the displayed field and its physical units or category. The ignition panel is derived directly from $\phi \leq 0$.

6 Actual simulation results

The required evidence is generated only from case-local ELMFIRE outputs. The current postprocessing status is **PASS**; 6 of 6 required metric rows pass across 3 variant(s). A missing output is reported as NOT RUN or NOT EVALUABLE and is not interpreted as verification evidence.




Figure 2: Final whole-domain ELMFIRE time of arrival for the displayed variant, in seconds. The figure annotation records the selected case-local GeoTIFF path and coordinate reference system; the generated metrics table, not visual appearance, determines acceptance.

7 Calculated metrics and verification decision

Variant / metric	Expected	Calculated	Status
1mph / crown class	0 -	0 -	PASS
1mph / max ROS	1.809 m/min	1.74511 m/min	PASS
5mph / crown class	1 -	1 -	PASS
5mph / max ROS	10.06 m/min	10.0843 m/min	PASS
10mph / crown class	2 -	2 -	PASS
10mph / max ROS	35.3 m/min	35.4433 m/min	PASS

The displayed overall decision is **PASS**. When `outputs/metrics.json` exists, `scripts/postprocess.py` generates every table value and status; when it is absent, the standalone wrapper renders NOT EVALUABLE with no invented rows.

8 Technical interpretation

A class failure with correct rate isolates transition logic or canopy-unit handling; coupled class and rate errors indicate wind/crown-fire integration. No scientific conclusion should be drawn when the

status is NOT RUN or NOT EVALUABLE.

9 Scope and limitations

The test covers one canopy structure and three discrete winds; it does not validate crown-fire correlations against observations. This case provides implementation verification evidence only.