D405-120

• 405nm 120mW laser diode•

Features

- Device: 405nm laser diode
- Power: 120mW
- Package Type: 5.6mm TO
- PIN configuration Style B

▪ Absolute Maximum Rating (Tc=25°C)

Characteristics	Symbols	Rating	Unit
Optical power	Po	140	mW
Reverse Voltage (Laser)	V	5	V
Reverse Voltage (PIN)	V	20	V
Operating Temperature	Top	-10 to +70	°C
Storage Temperature	Tstg	-40 to +85	°C

▪ Electrical and Optical Characteristics (Tc=25°C)

Characteristics	Symbols	Min	Typ	Max.	Unit	Condition
Optical Power	Po	-	120	-	mW	-
Threshold Current	Ith	-	35	50	mA	Po=120mW
Operating Current	Iop	-	120	150	mA	Po=120mW
Operating Voltage	Vop	-	4.8	6.0	Volts	Po=120mW
Slope Efficiency	η	-	1.3	-	mW/mA	-
Lasing Wavelength	λ	395	405	415	nm	Po=120mW
Beam Divergence	$\theta_{\parallel}$	6.0	9.0	12	deg	Po=120mW
	$\theta_{\perp}$	16	20	25	deg	Po=120mW
Beam Angle Deviation	$\theta_{\parallel}$	-3		3	deg	Po=120mW
	$\theta_{\perp}$	-3		3	deg	Po=120mW
Monitor Current	Im	-	0.40	0.70	mA	Po=120mW
Emission Point Accuracy	ΔX	-80	-	80	μm	
	ΔY	-80	-	80	μm	
	ΔZ	-80	-	80	μm	
Astigmatism	As	-	-	15	μm	

US LASERS, INC. • 418 B Cloverleaf Drive, Baldwin Park, CA 91706
Tel: 626.968.7181 • Fax: 626.934.0161 • www.us-lasers.com