
DOI	doi.org/10.1016/j.engstruct.2017.08.066
Title	Operational modal analysis of an eleven-span concrete bridge subjected to weak ambient excitations
	Background
Why this paper? How'd you find it?	My research project involves modal identification of concrete bridges. I wanted an example study that is grounded in a well-established lineage of state space system identification methods. Found with Google Scholar and following references and relatively well-cited articles.
Study Objective	Assess modal analysis methods for ambient/low excitation/low SNR vibrations.
Intended gaps to fill	- Ambient vibration to forgo the need for excitation equipment - Bridges with stiff, short to moderate span lengths
Authors	Ge-Wei Chen, Piotr Omenzetter, Sherif Beskhyroun
Affiliations	Hunan University of Science and Tech, China, University of Aberdeen, UK, Auckland University of Technology, New Zealand
Funding Source	Lloyd's Register Foundation (LRF) Centre for Safety and Reliability Engineering, University of Aberdeen
Journal / Field	Engineering Structures / Civil, Reliability Engineering
Date	09/12/2017
Historical Context	1960s: Filtering/Control with state space dynamics, aerospace navigation (Kalman) 1980s: Modal identification with state space system identification, aerospace/EE (Juang/Pappa/Longman) 1990s: Stochastic system identification, optimal control/EE (van Overschee/de Moor) 2000: Modal identification with stochastic system identification, civil structures (Peeters/de Roeck) 2010s: Model updating for civil structures
Relationship to SEMM	Works with equation of dynamic equilibrium
	Methods
Given:	Ambient (assume zero-mean Gaussian white noise excitation) vibration measurements from densely-instrumented concrete bridge deck
Find:	Natural frequencies, mode shapes, and damping ratios for vertical and lateral modes of the deck
Experimental Design	46 low-cost tri-axial MEMS sensors at 186 locations along deck. For baseline of modes and to guide sensor placement, ANSYS finite element model with elastic beam elements, free rotation associated w/bending at hinge and abutments. Vibrations preprocessed and analyzed with Peak Picking (PP), Frequency Domain Decomposition (FDD), and Data-Driven Stochastic Subspace Identification (SSI) to obtain modal properties.
	Nelson St. off-ramp bridge in Auckland, New Zealand while closed to traffic. 11 short-medium spans, vertical and horizontal curvature, on 10 pile or footing piers, one pile-bent abutment with sliding bearings and one gravity abutment, one hinge with pot bearing between pier 4 and 5.
	Measurement nodes of different setups 3 49 17 17 102 194 102 104 105 107 108 108 109 109 109 109 109 109





Test Subjects	ABUTMENT 2	
Results		
Baseline for comparison	Compare among methods and against finite element model	
Metric for comparison	Frequencies and damping: % difference; Mode shapes: Modal Assurance Criterion (MAC)	
Difference from baseline	Frequencies: w/in 0.9% difference and 0.04Hz stdev, but FDD and SSI missed the fundamental lateral mode; Mode shapes (FDD and SSI only): most MAC > 0.9, and MAC decreased for higher order modes; Damping: (SSI only) stdev of 0.2-0.5%	
Conclusions		
Authors'	PP, FDD, and SSI can identify modal properties in this context but are pushed to their limits and must be used together.	
Yours	Same as authors; would also like to know if any parameters of FE model or modal analysis methods were adjusted for the two to match better.	
Applications	Structural health monitoring	