


CS 188: Artificial Intelligence

Reinforcement Learning II



Instructor: Stuart Russell and Dawn Song, University of California, Berkeley

Recap: Reinforcement Learning

- Still assume a Markov decision process (MDP):
 - A **set of states** $s \in S$
 - A **set of actions** (per state) A
 - A **model** $T(s,a,s')$
 - A **reward function** $R(s,a,s')$
- Still looking for a policy $\pi(s)$
- New twist: **don't know T or R**
 - I.e. we don't know which states are good or what the actions do
 - Must actually try actions and states out to learn




Recap: Reinforcement Learning

- Passive reinforcement learning:
 - A passive learning agent has a fixed policy that determines its behavior
- Model-based learning:
 - Learn an approximate MDP model based on experiences
- Model-free learning:
 - Do not learn an explicit MDP model

Recap: Temporal Difference Learning

- Big idea: learn from every experience!
 - Update $V(s)$ each time we experience a transition (s, a, s', r)
 - Likely outcomes s' will contribute updates more often
- Temporal difference learning of values
 - Policy still fixed, still doing evaluation!
 - Move values toward value of whatever successor occurs: running average



Sample of $V(s)$: $sample = R(s, \pi(s), s') + \gamma V^\pi(s')$

Update to $V(s)$: $V^\pi(s) \leftarrow (1 - \alpha)V^\pi(s) + (\alpha)sample$

Same update: $V^\pi(s) \leftarrow V^\pi(s) + \alpha(sample - V^\pi(s))$


Recap: Problems with TD Value Learning

- TD value learning is a model-free way to do policy evaluation, mimicking Bellman updates with running sample averages
- However, if we want to turn values into a (new) policy, we're sunk:

$$\pi(s) = \arg \max_a Q(s, a)$$

$$Q(s, a) = \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V(s')]$$

- Idea: learn Q-values, not values
- Makes action selection model-free too!



Detour: Q-Value Iteration

- Value iteration: find successive (depth-limited) values
 - Start with $V_0(s) = 0$, which we know is right
 - Given V_k , calculate the depth $k+1$ values for all states:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V_k(s')]$$

- But Q-values are more useful, so compute them instead
 - Start with $Q_0(s,a) = 0$
 - Given Q_k , calculate the depth $k+1$ q-values for all q-states:

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma \max_{a'} Q_k(s', a')]$$

Q-Learning

- Q-Learning: sample-based Q-value iteration

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') \left[R(s, a, s') + \gamma \max_{a'} Q_k(s', a') \right]$$


- Learn $Q(s,a)$ values as you go

- Receive a sample (s,a,s',r)
- Consider your old estimate $Q(s, a)$
- Consider your new sample estimate:

$$sample = R(s, a, s') + \gamma \max_{a'} Q(s', a') \quad \text{no longer policy evaluation!}$$

- Incorporate the new estimate into a running average

$$Q(s, a) \leftarrow (1 - \alpha)Q(s, a) + (\alpha) [sample]$$



Video of Demo Q-Learning -- Gridworld




Video of Demo Q-Learning -- Crawler



Active Reinforcement Learning


- Passive reinforcement learning:
 - A passive learning agent has a fixed policy that determines its behavior
- Active reinforcement learning:
 - An active learning agent gets to decide what actions to take



Q-Learning:

act according to current optimal (and also explore...)

- Full reinforcement learning: optimal policies (like value iteration)
 - You don't know the transitions $T(s,a,s')$
 - You don't know the rewards $R(s,a,s')$
 - You choose the actions now
 - **Goal: learn the optimal policy / values**
- In this case:
 - Learner makes choices!
 - Fundamental tradeoff: exploration vs. exploitation
 - This is NOT offline planning! You actually take actions in the world and find out what happens...





Q-Learning Properties

- Amazing result: Q-learning converges to optimal policy -- even if you're acting suboptimally!
- This is called **off-policy learning**
- Caveats:
 - You have to explore enough
 - You have to eventually make the learning rate small enough
 - ... but not decrease it too quickly
 - Basically, in the limit, it doesn't matter how you select actions (!)




Active Reinforcement Learning




Model-Free Learning

- act according to current optimal (based on Q-Values)
- but also explore...




Model-Based Learning

~~Input Policy π~~



act according to current optimal policy
also explore!

Exploration vs. Exploitation



Video of Demo Q-learning – Manual Exploration – Bridge Grid



How to Explore?

- Several schemes for forcing exploration
 - Simplest: random actions (ϵ -greedy)
 - Every time step, flip a coin
 - With (small) probability ϵ , act randomly
 - With (large) probability $1-\epsilon$, act on current policy
 - Problems with random actions?
 - You do eventually explore the space, but keep thrashing around once learning is done
 - One solution: lower ϵ over time
 - Another solution: exploration functions



Video of Demo Q-learning – Epsilon-Greedy – Crawler



Exploration Functions

- When to explore?
 - Random actions: explore a fixed amount
 - Better idea: explore areas whose badness is not (yet) established, eventually stop exploring
- Exploration function
 - Takes a value estimate u and a visit count n , and returns an optimistic utility, e.g. $f(u, n) = u + k/n$ is a predetermined constant



Regular Q-Update: $Q(s, a) \leftarrow_{\alpha} R(s, a, s') + \gamma \max_{a'} Q(s', a')$

Modified Q-Update: $Q(s, a) \leftarrow_{\alpha} R(s, a, s') + \gamma \max_{a'} f(Q(s', a'), N(s', a'))$

$N(s, a)$: number of times q-state (s, a) has been visited


- Note: this propagates the “bonus” back to states that lead to unknown states as well!

Video of Demo Q-learning – Exploration Function – Crawler




Regret

- Even if you learn the optimal policy, you still make mistakes along the way!
- Regret is a measure of your total mistake cost: the difference between your (expected) rewards, including youthful suboptimality, and optimal (expected) rewards
- Minimizing regret goes beyond learning to be optimal – it requires optimally learning to be optimal
- Example: random exploration and exploration functions both end up optimal, but random exploration has higher regret





Approximate Q-Learning




Generalizing Across States

- Basic Q-Learning keeps a table of all q-values
- In realistic situations, we cannot possibly learn about every single state!
 - Too many states to visit them all in training
 - Too many states to hold the q-tables in memory
- Instead, we want to generalize:
 - Learn about some small number of training states from experience
 - Generalize that experience to new, similar situations
 - This is a fundamental idea in machine learning, and we'll see it over and over again




Example: Pacman


Let's say we discover through experience that this state is bad:



In naïve q-learning, we know nothing about this state:



Or even this one!



Video of Demo Q-Learning Pacman – Tiny – Watch All



Video of Demo Q-Learning Pacman – Tiny – Silent Train



Video of Demo Q-Learning Pacman – Tricky – Watch All



Feature-Based Representations

- Solution: describe a state using a vector of features (properties)
 - Features are functions from states to real numbers (often 0/1) that capture important properties of the state
 - Example features:
 - Distance to closest ghost
 - Distance to closest dot
 - Number of ghosts
 - $1 / (\text{dist to dot})^2$
 - Is Pacman in a tunnel? (0/1)
 - etc.
 - Is it the exact state on this slide?
 - Can also describe a q-state (s, a) with features (e.g. action moves closer to food)



Linear Value Functions

- Using a feature representation, we can write a q function (or value function) for any state using a few weights:

$$V(s) = w_1 f_1(s) + w_2 f_2(s) + \dots + w_n f_n(s)$$

$$Q(s, a) = w_1 f_1(s, a) + w_2 f_2(s, a) + \dots + w_n f_n(s, a)$$

- Advantage: our experience is summed up in a few powerful numbers
- Disadvantage: states may share features but actually be very different in value!

Approximate Q-Learning

$$Q(s, a) = w_1 f_1(s, a) + w_2 f_2(s, a) + \dots + w_n f_n(s, a)$$

- Q-learning with linear Q-functions:

$$\text{transition} = (s, a, r, s')$$

$$\text{difference} = \left[r + \gamma \max_{a'} Q(s', a') \right] - Q(s, a)$$

$$Q(s, a) \leftarrow Q(s, a) + \alpha [\text{difference}]$$

$$w_i \leftarrow w_i + \alpha [\text{difference}] f_i(s, a)$$


Exact Q's

Approximate Q's

- Intuitive interpretation:


- Adjust weights of active features
- E.g., if something unexpectedly bad happens, blame the features that were on: disprefer all states with that state's features

- Formal justification: online least squares



Example: Q-Pacman

$$Q(s, a) = 4.0 f_{DOT}(s, a) - 1.0 f_{GST}(s, a)$$



$$f_{DOT}(s, \text{NORTH}) = 0.5$$

$$f_{GST}(s, \text{NORTH}) = 1.0$$

$$Q(s, \text{NORTH}) = +1$$

$$r + \gamma \max_{a'} Q(s', a') = -500 + 0$$

$$Q(s', \cdot) = 0$$

difference = -501



$$w_{DOT} \leftarrow 4.0 + \alpha [-501] 0.5$$


$$w_{GST} \leftarrow -1.0 + \alpha [-501] 1.0$$

$$Q(s, a) = 3.0 f_{DOT}(s, a) - 3.0 f_{GST}(s, a)$$


Video of Demo Approximate Q-Learning -- Pacman



Q-Learning and Least Squares




Linear Approximation: Regression



Prediction:

$$\hat{y} = w_0 + w_1 f_1(x)$$




Prediction:

$$\hat{y}_i = w_0 + w_1 f_1(x) + w_2 f_2(x)$$

Optimization: Least Squares


$$\text{total error} = \sum_i (y_i - \hat{y}_i)^2 = \sum_i \left(y_i - \sum_k w_k f_k(x_i) \right)^2$$



Minimizing Error

Imagine we had only one point x , with features $f(x)$, target value y , and weights w :

$$\begin{aligned}\text{error}(w) &= \frac{1}{2} \left(y - \sum_k w_k f_k(x) \right)^2 \\ \frac{\partial \text{error}(w)}{\partial w_m} &= - \left(y - \sum_k w_k f_k(x) \right) f_m(x) \\ w_m &\leftarrow w_m + \alpha \left(y - \sum_k w_k f_k(x) \right) f_m(x)\end{aligned}$$



Approximate q update explained:

$$w_m \leftarrow w_m + \alpha \left[\underset{\text{“target”}}{r + \gamma \max_a Q(s', a')} - \underset{\text{“prediction”}}{Q(s, a)} \right] f_m(s, a)$$

Summary: MDPs and RL

Known MDP: Offline Solution

Goal	Technique
Compute V^* , Q^* , π^*	Value / policy iteration
Evaluate a fixed policy π	Policy evaluation


Unknown MDP: Model-Based

Goal	<i>*use features to generalize</i> Technique
Compute V^* , Q^* , π^*	VI/PI on approx. MDP
Evaluate a fixed policy π	PE on approx. MDP



Unknown MDP: Model-Free

Goal	<i>*use features to generalize</i> Technique
Compute V^* , Q^* , π^*	Q-learning
Evaluate a fixed policy π	Value Learning



RL and dopamine



reward following
0% predictive cue




reward following
50% predictive cue




reward following
100% predictive cue

- Dopamine signal generated by parts of the striatum
- Encodes predictive error in value function (as in TD learning)



no reward following
100% predictive cue



Voorn et al 2004

(Fiorillo et al 2003)

Next Section: Advanced Topics

- Advanced topic I: Adversarial machine learning
- Advanced topic II: Fairness in machine learning
- Advanced topic III: CLIP
- Final lecture: AI safety (Stuart)