1 Controllability

We are given a discrete-time state space system, where \vec{x} is our state vector, A is the state space model, B is the input matrix, and \vec{u} is the control input.

$$\vec{x}[t+1] = A\vec{x}[t] + B\vec{u}[t]$$

We want to know if this system is "controllable"; if given set of inputs, we can reach any state in our state-space after a finite number time steps. This has an important physical meaning; if a system is controllable, we can travel anywhere in the system it is living in given enough control inputs.

Constructing the Controllability Matrix

To figure out if a system is controllable, we start by looking at a simplified problem. Suppose the initial state $\vec{x}[0] = \vec{0}$ and we would like to reach a certain state \vec{x}_0 . If a system were controllable, we can give a set of control inputs $\vec{u}[t]$ to reach this state \vec{x}_0 . Let's start by analyzing what happens after one time step.

$$\vec{x}[1] = A\vec{x}[0] + B\vec{u}[0] = A\vec{0} + B\vec{u}[0] = B\vec{u}[0] \tag{1}$$

This shows us that we can go anywhere spanned by *B* in the first time step. Now let us push the system another time step.

$$\vec{x}[2] = A\vec{x}[1] + B\vec{u}[1] = A(A\vec{x}[0] + B\vec{u}[0]) + B\vec{u}[1]$$
(2)

$$=AB\vec{u}[0]+B\vec{u}[1] \tag{3}$$

Similarly, at this time step, we can go anywhere spanned by $\begin{bmatrix} B & AB \end{bmatrix}$. Every time step adds another degree of freedom to the system.

To generalize this relation, after *n* time steps, we get the following:

$$\vec{x}[n] = A\vec{x}[n-1] + B\vec{u}[n-1] \tag{4}$$

$$= A^{n-1}B\vec{u}[0] + A^{n-2}B\vec{u}[1] + \dots + AB\vec{u}[n-2] + B\vec{u}[n-1]$$
(5)

This shows that after n time steps, we can go anywhere spanned by the columns of the matrix C defined below. This is called the "controllability" matrix.

$$C = \begin{bmatrix} B & AB & A^2B & \cdots & A^{n-2}B & A^{n-1}B \end{bmatrix}$$
 (6)

If this matrix is of rank n (the dimension of our state space), then our system is controllable. But what if these aren't enough steps and the system can be controlled only in n + 1 steps? What is the maximal number of steps we need to take to have a long sequence of control inputs that $\{B, AB, A^2B, \ldots\}$ spans the state space?

Cayley-Hamilton Theorem

These questions are answered by the Cayley-Hamilton theorem. The Cayley-Hamilton theorem says that higher order powers of A can be expressed as a linear combination of lower order matrix powers of A. Specifically if A is an $n \times n$, matrix, the highest order unique power of A is A^{n-1} . Thus, if we keep applying control inputs past n time steps, our control inputs will be a linear combination of the previous control inputs and cannot increase the rank of the controllability matrix.

Definition of Controllability

This also works for continuous time systems; instead of incrementing the time steps in our system by 1 every time, we increment by Δt , $2\Delta t$, etc. The math and our controllability test work out to be exactly the same! Putting all of this together, we get the following:

$$\dot{\vec{x}}(t) = A\vec{x}(t) + B\vec{u}(t)$$
 or $\vec{x}[t+1] = A\vec{x}[t] + B\vec{u}[t]$
 $C = \begin{bmatrix} B & AB & A^2B & \cdots & A^{n-2}B & A^{n-1}B \end{bmatrix}$

Given a continuous or discrete time system \vec{x} of dimension n, the system is controllable if its controllability matrix C is of rank n. If a system is controllable, then given any starting position $\vec{x}[0]$, it takes a maximum of n control inputs over n time steps for the system to reach any final state \vec{x}_0 .

2 Deadbeat Control

Consider the system

$$\vec{x}[t+1] = A\vec{x}[t] + Bu[t] = \begin{bmatrix} 1 & -1 \\ -1 & 1 \end{bmatrix} \vec{x}[t] + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u[t].$$

a) Is this system controllable?

b) For which initial states $\vec{x}[0]$ is there a control that will bring the state to zero in a single time step?

c) For which initial states $\vec{x}[0]$ is there a control that will bring the state to zero in two time steps?

d) Now let $\vec{x}[0] = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$ be the initial state. Give a set of control inputs u[0] and u[1] to bring to system to $\vec{y} = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$ in two time steps.

3 Discretization

Consider a cart of mass M, pushed with a force u(t) with position, x(t), and velocity, v(t). Hence, we have:

$$\frac{\mathrm{d}}{\mathrm{d}t} x(t) = v(t)$$
$$\frac{\mathrm{d}}{\mathrm{d}t} v(t) = \frac{u(t)}{M}$$

We will apply a constant input between any time $t \in [nT, nT + T)$. Here T is our time between samples.

a) Find a discretized system of equations for this system.

b) Is the discretized system controllable?