

CMPE321 Introduction to Database Systems
2016/2017-2

Berk Erol

Storage Manager Design

Berk Erol
2014400189

Table of Contents

Introduction	3
Assumptions and Constraints.....	4
System Catalog	4
System Catalog Page	4
Type	4
Page	5
Record.....	5
Data Structures	6
System Catalog	6
Type	6
Page	7
Record	7
Operations	8
DDL Operations	8
Create a Type.....	8
Delete a Type.....	8
List all Types	9
DML Operations.....	9
Create a Record	9
Delete a Record	10
Update a Record.....	10
Search for a Record	11
List all Records.....	11
Conclusion	12

Introduction

This project is about designing a storage manager. This document explains the assumptions and constraints required to manage the system & the data structures (with diagrams) and operations (with pseudocodes) required to store the data in the system. This DBMS enables users to run various DDL and DML operations as the followings

- DDL Operations
 1. Create a type
 2. Delete a type
 3. List all types
- DML Operations
 1. Create a record
 2. Delete a record
 3. Update a record
 4. Search for a record (by key field)
 - < views all records whose key fields are less than a specific value.
 - > views all records whose key fields are more than a specific value.
 - = views all records whose key fields are equal to a specific value.
 5. List all records of a type

Assumptions and Constraints

System Catalog

- There is only one system catalog.
- Creating or deleting system catalogs are not allowed.
- System Catalog file shall have the following format: SystemCatalog.txt
- System Catalog header
 - Name of the storage system (50 bytes)
 - # of pages (2 bytes)
- Storage system name
 - Storage system name shall be alphanumeric.
 - The length of storage system name shall be at most 50 bytes.
- Size of System Catalog shall be at most 101428 bytes.
- System Catalog shall have at most 99 pages. $(101428 - 50 - 2) / 1024$
- System Catalog shall have at most 3465 types. $(99 * 35)$

System Catalog Page

- Each page stores type names.
- Page header
 - Page number (2 bytes)
 - # of type names (2 bytes)
- Line endings $(35 + 1) * 2 = 72$ bytes.
- Unused space 3 bytes.
- Size of each page shall be 1024 bytes.
- Each page shall have at most 35 type names. $(1024 - 2 - 2 - 72 - 3) / 27$
- Pages are deleted physically because type names are deleted physically.

Type

- Each type is stored in a different file.
- Each file shall be able to store all pages for a type.
- File shall have the following format: <TypeName>.txt
- Type name
 - Each type name shall be unique.
 - Type names shall be alphanumeric.
 - The length of type names shall be at most 27 bytes.
- File header
 - Usage status (1 byte)
 - # of pages (2 bytes)
 - # of fields (2 bytes)
 - Field names (160 bytes)
- Field name
 - Each field name shall be unique.
 - Field names shall be alphanumeric.
 - The length of field names shall be at most 10 bytes.
- Size of each type shall be at most 101541 bytes.

- Each type shall have at most 99 pages. $(101541-1-2-2-160)/1024$
- Each type shall have at most 1485 records. $(99*15)$
- Each type shall have at most 23760 fields. $(1485*16)$
- Types cannot be deleted physically (only their status change).

Page

- Each page stores records.
- Page header
 - Page number (2 bytes)
 - # of active records (2 bytes)
 - # of deleted records (2 bytes)
- Line endings $(15+1) * 2 = 32$ bytes.
- Unused space 11 bytes.
- Size of each page shall be 1024 bytes.
- Each page shall have at most 15 records. $(1024-2-2-2-32-11)/65$
- Each page shall have at most 240 fields. $(15*16)$
- Pages do not need to be deleted physically because records are not deleted physically.

Record

- Each record stores fields.
- Record header
 - Usage status (1 byte)
- Key field
 - Each key field shall be unique.
 - There shall be one and only one key field in a record.
 - Key field shall always be the first field in its record.
- Size of each record shall be at most 65 bytes.
- Each record shall have at most 16 fields. $(65-1)/4$
- Records cannot be deleted physically (only their status change).
- Size of each field shall be at most 4 bytes.
- Each field stores data as integers.
- Fields can be deleted physically (except key field).

Data Structures

System Catalog

It is the main file of the storage system. It keeps all general information about the storage system and its files. Users first reach this file if they want to make an operation in the storage system. There is only one system catalog. Creating or deleting system catalogs are not allowed. Type names are stored in System Catalog pages. Each page shall have a fixed size of 1024 bytes the System Catalog can have multiple pages. There shall always be enough number of pages in System Catalog for all type names (Pages are created after the last page of the type when there is no empty type name slot in the last page and last page is deleted when there is no type name in the last page). Pages can have different number of type names but the maximum amount for this value is the same for all pages as specified in Assumptions and Constraints section. Pages that are not completely full are filled with blank spaces to reach 1024 bytes.

System Catalog		System Catalog Header		System Catalog Page	Page Header	
System Catalog Header				Page Header		
System Catalog Page 1		System name	# of pages	Type Name 1	Page number	# of types
System Catalog Page 2				Type Name 2		
System Catalog Page ...				Type Name ...		
System Catalog Page 99				Type Name 35		

Type

The storage system consists of several types. Each type is stored in a different file. Each file stores all pages for a type. Usage status specifies whether the type is deleted or not (1 for active, 0 for deleted). Types cannot be deleted physically (only their status change). This property speeds up the type deletion process. Types can have different number of pages, records, fields and different sizes but the maximum amount for these values are the same for all types as specified in Assumptions and Constraints section.

File		File Header				
File Header						
Page 1		Usage status	# of pages	# of fields	Field Name 1	Field Name ...
Page 2						
Page ...						
Page 99						
					Field Name 16	

Page

Each page stores records. Each page shall have a fixed size of 1024 bytes but a type (file) can have multiple pages. There shall always be enough number of pages in a file for all records of a type (Pages are created after the last page of the type when there is no empty record slot in the last page but pages do not need to be deleted physically because records are not deleted physically). This property speeds up the record creation and deletion processes. Pages can have different number of records and fields and different sizes but the maximum amount for these values are the same for all pages as specified in Assumptions and Constraints section. Pages that are not completely full are filled with blank spaces to reach 1024 bytes.

Page		Page Header		
Page Header				
Record 1 (Status 1)		Page number	# of active records	# of deleted records
Record ... (Status 1)				
Record 10 (Status 1)				
Record 1 (Status 0)				
Record ... (Status 0)				
Record 5 (Status 0)				

Record

Each record stores fields. Usage status specifies whether the record is deleted or not (1 for active, 0 for deleted). New records are created at the right position in the used records (to keep used records sorted according to key field). Records cannot be deleted physically (only their status change) and newly deleted records are moved to the end of the file. This way used records remain sorted and deleted records come after used records. These properties speed up the record searching and listing processes. Records can have different number of fields and different sizes but the maximum amount for these values are the same for all records as specified in Assumptions and Constraints section. Records that are not completely full (number of fields is less than maximum number of fields) are filled with zeroes to reach the maximum record size and keep page size and number of records in a page fixed. There is only one key field which is the first field. Each field stores data as integers. Fields can be deleted physically (except key field).

Record		Record Header	
Record Header		Usage status	
Field 1 (Key Field)			
Field 2			
Field ...			
Field 16			