

Instituto Superior Técnico

**Departamento de Engenharia Electrotécnica e de
Computadores**

Machine Learning

4th Lab Assignment

Shift_____ Group number_____

Number_____ Name_____

Number_____ Name_____

Support Vector Machines for Classification

1 Introduction

Simple linear classifiers, such as the one implemented by the Rosenblatt perceptron, are unable to correctly classify patterns, unless the classes under consideration are linearly separable. Neural networks that use hidden units with nonlinear activation functions are used in many classification problems, since they are able to perform nonlinear classification. However, several strong theoretical results, valid for the linearly separable case, are not applicable to nonlinear classifiers.

Support vector machines (SVMs) address the classification problem using linearly separable classes, not in the input space, but in the so-called *feature space*. Input patterns are mapped onto the higher-dimensional feature space, where the classification is performed using a hyperplane as classification border. Since the mapping from the input space to the feature space is usually nonlinear, these hyperplanes in feature space correspond to nonlinear borders in input space.

At first glance this might seem to be a double-edged sword, since it suggests that calculations have to be performed in the high-dimensional feature space. However, an interesting result proves that, since linear classification only requires inner product operations, all calculations can be performed in the lower-dimensional input space, if the nonlinear mapping is chosen in an appropriate way. This result is particularly strong when one takes into account that certain mappings yield infinite-dimensional feature spaces. This is the same as saying that linear classification in an infinite-dimensional feature space can be performed by means of operations in the lower-dimensional input space. Imagine all the power of infinite-dimensional hyperplanes, without the associated computational burden.

The purpose of this assignment is twofold: first, to work out, in detail, two simple classification problems in two-dimensional input space, one of them involving a mapping to a three-dimensional feature space; second, to provide some experience and some intuition on the capabilities of support vector machines.

2 Two simple examples

Consider the AND and XOR logic functions, defined in the following truth table:

x_1	x_2	d_{AND}	d_{XOR}
-1	-1	-1	-1
-1	1	-1	1
1	-1	-1	1
1	1	1	-1

Here, the input pattern is a vector $\mathbf{x} = (x_1, x_2)$, and d_{AND} and d_{XOR} are the desired values for the AND and XOR functions. Note that, in this assignment, we represent logical *true* by 1 and logical *false* by -1 . Similarly, in binary classification problems, we assign the desired value of 1 to the patterns of one of the classes, and the desired value of -1 to those of the other class.

2.1(T) For the AND function, find (by inspection) the maximum-margin separating straight line, the support vectors and the margin boundaries. Then compute the vector \mathbf{w} and the bias b that satisfy the equation

$$(\mathbf{w} \cdot \mathbf{x}^s - b) d^s = 1 \quad (1)$$

for all support vectors \mathbf{x}^s , where d^s is the desired value corresponding to \mathbf{x}^s .¹

R.

2.2(T) Since, for the XOR function, a linear classification cannot be performed in the input space – explain why – we will consider here a simple nonlinear mapping to a three-dimensional feature space:

$$\tilde{\mathbf{x}} = \varphi(\mathbf{x}) = (x_1, x_2, x_1 x_2)^T. \quad (4)$$

Find the kernel function that corresponds to this mapping.

¹It can be easily shown (but you're not asked to show) that, defining the border of the maximum-margin linear classifier by the equation

$$\tilde{\mathbf{w}} \cdot \tilde{\mathbf{x}} - b = 0, \quad (2)$$

then $\tilde{\mathbf{w}}$ and b obey the equation

$$(\tilde{\mathbf{w}} \cdot \tilde{\mathbf{x}}^s - b) d^s = C \quad (3)$$

for all support vectors $\tilde{\mathbf{x}}^s$, where C is a constant. Normally, we choose $C = 1$.

In our case of the AND function, vectors with and without tilde are equal, since the feature space (where the linear classification is performed) is the input space itself.

R.

2.3(T) Visualize the points in this 3D feature space. Find, by inspection, which are the support vectors. Compute $\tilde{\mathbf{w}}$ and b in this feature space, so that equation (1) is satisfied for all support vectors.

R.

2.4(T) Algebraically express, in the two-dimensional input space, the classification border and the margin boundaries corresponding to the classifier found above for the XOR problem. Then sketch them in a graph, together with the input patterns.

R.

2.5(T) Indicate the mathematical condition under which the classifier that you have just developed will produce an output of 1. The condition should be expressed in terms of the input space coordinates. It shouldn't use coordinates from the feature space.

R.

3 Classification using SVMs

A kernel commonly employed in pattern recognition problems is the polynomial one, defined by

$$K(\mathbf{x}, \mathbf{y}) = (\mathbf{x} \cdot \mathbf{y} + a)^p - a^p, \quad (5)$$

where $\mathbf{x}, \mathbf{y} \in \mathbb{R}^2$, $a \in \mathbb{R}^+$ and $p \in \mathbb{N}$.[†]

3.1(T) Indicate the mapping to feature space that this kernel corresponds to, and the dimensionality of the feature space.

R.

[†]This is one of the variants of the polynomial kernel. Another variant omits the term “ $-a^p$ ” in the defining equation.

3.2(T) Assume that $p = 2$. Explain how the kernel used in 2.2 maps to a subspace of the feature space of item 3.1, and find the vector $\tilde{\mathbf{w}}$ that represents, in this new feature space, the same classification border and margins as in 2.2.

R.

4 Experiments

The experimental part of this assignment uses the SVM toolbox developed by Steve Gunn (University of Southampton).³ From within Matlab, run the command `uiclass` to launch the graphical interface of the toolbox.⁴ The selection box at the upper left corner of the interface selects the kernel function to be employed: use **Linear** for a linear classifier (*i.e.*, the feature space is equal to the input space), **Polynomial** for the kernel (5), where **Degree**

³Depending on the *Matlab* version being used, you may need to recompile the optimizer code to use this toolbox. Check the Makefile in the Optimizer directory.

⁴In the graphical interface, you can use the buttons **Class A** and **Class B**, together with left mouse clicks, to enter your own input patterns, if you wish. Right-click to indicate that you have finished entering the patterns of a class.

stands for the parameter p , and **Gaussian RBF** (radial basis function) for the kernel

$$K(\mathbf{x}, \mathbf{y}) = e^{-\frac{\|\mathbf{x} - \mathbf{y}\|^2}{2\sigma^2}}, \quad (6)$$

where **Sigma** stands for σ . Among these kernels, Gaussian RBF is the one that is most frequently used, for several reasons (for instance, because it is shift-invariant and isotropic).

4.1(E) Use the **Load** button to load the file `spiral.mat`. This file contains the classical spiral example, with 50 patterns per class. Determine experimentally, using the polynomial kernel, the value of p for which you get the best classifier. (start with $p = 1$). Write down all experiments performed, together with the classification error percentages (the number of classification errors is printed in the Matlab window). Comment on the results you obtained.

R.

4.2(E) Using the same data file (`spiral.mat`), try now the Gaussian RBF kernel. Find the approximate value of σ for which you can get the best classifier. Comment on the results you obtained.

R.

4.3(E) Load the file `chess33.mat` from the interface. Using the Gaussian RBF kernel, find a value of σ that approximately minimizes the number of support vectors, while correctly classifying all patterns. Indicate the value of σ and the number of support vectors.

R.

4.4(E) The file `chess33n.mat` is similar to the one used in the previous question, except for the presence of a couple of outlier patterns. Run the classification algorithm with the same value of σ , and comment on the shape of the classification border, the margin size and the number of support vectors.

R.

4.5(E) Now deselect the **Separable** check box. Doing so changes the classifier to a so-called *soft margin* SVM. The **Bound** value specifies the relative weight of the margin violations in the objective function that is optimized in the training of the classifier. Try different values (suggestion: use powers of 10) and comment on the results.

R.