

# SQL - RIGHT JOINS

<http://www.tutorialspoint.com/sql/sql-right-joins.htm>

Copyright © tutorialspoint.com

The SQL **RIGHT JOIN** returns all rows from the right table, even if there are no matches in the left table. This means that if the ON clause matches 0 *zero* records in left table, the join will still return a row in the result, but with NULL in each column from left table.

This means that a right join returns all the values from the right table, plus matched values from the left table or NULL in case of no matching join predicate.

## Syntax:

The basic syntax of **RIGHT JOIN** is as follows:

```
SELECT table1.column1, table2.column2...
FROM table1
RIGHT JOIN table2
ON table1.common_field = table2.common_field;
```

## Example:

Consider the following two tables, a CUSTOMERS table is as follows:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

b Another table is ORDERS as follows:

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

Now, let us join these two tables using RIGHT JOIN as follows:

```
SQL> SELECT ID, NAME, AMOUNT, DATE
FROM CUSTOMERS
RIGHT JOIN ORDERS
ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

This would produce the following result:

ID	NAME	AMOUNT	DATE
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
2	Khilan	1560	2009-11-20 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00

