GLOBAL CONTEXT FOR AI AGENTS

The model knows the world, not your business.

5 steps to give an agent what the model cannot know.

THE GAP, IN A FICTIONAL EXAMPLE

Two sessions, no shared memory

```
# session 1, Tuesday
user:  Team plan goes up to $119
       next month.
agent: Got it.
saved: nothing

# session 2, Friday
context: no price, no map
search:  stripe, attio, db,
         drive, slack
found:   "Team plan: $99" (Slack)
output:  renewal email, $99
```

STEP 1

Split the information into domains

```
global-context/
   map.md
   sales/
      prices.md
      customers.md
   people/
      team.md
   product/
      roadmap.md
```

STEP 2

Write a map: one line for each domain

```
# map.md
sales/   Prices, discounts,
         plan changes, customers.
         Price list: prices.md
people/  Team, roles, who decides.
product/ Roadmap, release dates.
```

STEP 3

At session start, load only the map

```
# session start
load: map.md
rule: read the map before
      any tool call
```

The domains stay saved, not loaded.

STEP 4

For each question, load one domain

```
ask:    How much is the Team plan?
route: sales/
load:  sales/prices.md
skip:  people/, product/
```

Other domains are text that the model can confuse with the answer.

STEP 5

Save each change where it belongs

```
user: Team plan goes up to $119
      next month.
save: sales/prices.md
      Team: $99 → $119
```

RESULT, SAME FICTIONAL EXAMPLE

Same model. Next session: $119.

```
# session 2, Friday
load:   map.md
route:  sales/
load:   sales/prices.md
output: renewal email, $119
```

WHERE IT BREAKS

The two halves depend on each other.

The map only helps if what it points to is current.

A save only helps if the next session can find it.

Each domain must make sense alone. "Ask Sales" is useless to an agent.

THE FULL ARTICLE

Minimal to load, fast to find.

Why the adapter (MCP, files, or a database) matters least, and a test for your own agent.

samperalabs.com/posts/why-ai-agents-need-a-global-context