

13.1 FCL using AAPS Master and Automations

AAPS 3.0 was (Sep.2023) the first DIY system to launch Full Closed Looping as a fully described option to manage T1D, if a described set of pre-requisites apply.

Key pre-requisites were sketched in [section 1](#). For a complete description see <https://androidaps.readthedocs.io/en/latest/Usage/FullClosedLoop.html>

You may (not) have noticed: There was no big „marketing fuzz“ made around that FCL option. Seeing how many AAPS users struggle with even getting their basal, ISF and SMB settings right, it would be foolish to allure everybody to a supposedly very easy way of looping. True, it can be easy. But only after doing a personalized set-up project. Setting up is easier than what autoISF and the methods we get to in [section 13.3](#) demand, but still a project. It also requires a well mastered hybrid closed loop, to begin with.

With attention to the pre-requisites, and avoiding extreme high carb diets, many (mostly: adult) users achieve satisfactory %TIR after supplementing AAPS Master with personalized Automations that attempt to strongly elevate iob upon recognition of a meal-related bg rise.

See also Case Studies, and the randomized cross-over study involving AAPS FCL: PubMed [First Use of Open-Source Automated Insulin Delivery AndroidAPS in Full Closed-Loop Scenario: Pancreas4ALL Randomized Pilot Study](#);

This method is **highly recommended for an entry into FCL for those who do not have the interest, or lack the time, to deal with the very much more sophisticated and demanding other routes** towards FCL, like autoISF, or also like the methods briefly presented below in [section 13.3](#) .

13.2 FCL using dynamicISF with AAPS or iAPS (Master)

As opposed to

- autoISF, with it's bgAccel_ component , or to....
- AAPS Master, with Automations strengthening ISF at meal-related bg rises ...

dynamicISF was not designed to help boost SMBs asap after an omitted user bolus.

36 Rather (as the name also suggests) it was designed to be used in hybrid closed looping to make
37 ISF react more dynamic to suspected swings in insulin sensitivity (which shows in bg values, and
38 in TDD trends). It does a similar job like Autosens, but can be much more amplified (by the users
39 tuning their dynamicISF adjustment factor (%)).

40

41 When using a fast insulin (and when some other pre-requisites discussed in section 1 are in place,
42 too), the dynamicISF method can be applied also to Full Closed Looping. (See *Case Study 13.X; if
43 not available by time of publication, this is a call for a dynISF FCL user to provide a case study that
44 contains a 1 week 24h scatter plot as well as one analyzed meal where we can see when and how
45 dynISF helped build iob, after not having bolussed*).

46

47 It will have a principal timing-disadvantage because responses are more tied to high bg values
48 than to acceleration (in autoISF) or to delta (in the Automations route to FCL).

49

50 On the other hand, people who 1) do have strong sensitivity swings and 2) cannot pro-actively
51 deal with those (e.g. by making profile switches) might be satisfied with the automatic (although a
52 bit late) adjustments that dynamicISF automatically will provide.

53

54 dynamicISF therefore could be characterized, in the FCL context, as a potential solution to a rather
55 care-free approach for those who do not seek best-possible performance (or who take other
56 measures, like low carb diet, to still reach pretty acceptable performance in FCL mode).

57

58 *? mention, or even include ((here or in kid section 7.)) with a Case Study: T.....d code (fully auto bolus,no carbs)
59 uses last three days average TDD, and also last 3hr and 6 hrs to check if cannula had likely failed ...as his teenage
60 son never changes his cannula until it falls off.*

61

62 *⇒ A very different approach:*

63 *⇒ ~ „survival at half-way reasonable TIR despite negligent behaviour“ ?*

64 Contact (caution, both not focussed on FCL:)

65 AAPS / search term dynamicISF in: <https://discord.gg/DfvK5HnxXu>

66 iAPS / section dynamic-isf-cr: <https://discord.gg/gGKXW5uX3m>

67

68

69 13.3 Methods involving simple Meal Announcement that might be 70 stretched into a FCL

71

72 13.3.1 Boost

73 All of the additional code outside of the standard SMB calculation requires a daily time period
74 („Boost window“) to be specified within which it is active.

75 A variation of dynamicISF is used in which also predicted bg will be considered in varying degrees
76 (40...75%) to mimic the effects of higher insulin sensitivity at lower glucose levels.

77 When using Boost without carb inputs (permanent cob=0) a special **boosting of SMBs** is provided
78 when an **initial bg rise** is detected with a meal:

79 delta, short_avgDelta and long_avgDelta are used to trigger an early bolus (assuming IOB is below
80 a user defined amount).

81 This procedure goes in the direction of the bgAccel_ISF route discussed for autoISF
82 ([section 4.1](#)). If used with an excellent CGM, autoISF acceleration detection should be a bit
83 earlier, and boosting can be made much stronger in autoISF

84 For safety, the user sets a value of 2.5% (up to 5%) of TDD for the max. Boost Bolus (Boost Bolus
85 Cap).

86 For stronger boost, the default AAPS 50% SMB_delivery_rate can be overwritten with a higher in-
87 sulin percentage determined by the user. The SMB_delivery_ratio is called „Boost insulin required
88 percent“ here, and suggested not to go over 75%. The % can be defined variable with bg value
89 (like also in autoISF).

90 The Boost function automatically shuts off as soon as delta and the average deltas are aligned,
91 i.e. when the accelerated rise goes over into a constant rise (compare pp_ISF in autoISF).

92 However, the boost function is only „dormant“ if the boost window lasts longer for more meal-
93 related accelerations.

94 Additional functions are a step-count modified dynamic_ISF, inactivity detection etc

95 A couple of safety feature are integrated. The user can define an iob limit for boosts, here called
96 UAM Boost max IOB . In Preferences/Treatments There is also a user adjustable Low Glucose
97 Suspend threshold. This allows the user to set a value higher than the system would normally use,
98 such that when predictions drop below this level (65...100), a zero TBR is set.

99 **More info:** <https://discord.gg/nYC4T9PgCR> ; <https://github.com/tim2000s/no-bolus-dev>
100 : <https://github.com/tim2000s/Boost-master-v3/blob/master/README.md>

101 Contact: Tim Street @ diabettech.com

102

103 13.3.2 **AIMI**

104 AIMI has a single goal: to minimize the decisions necessary to maintain the target range, simplify
105 the composition of the profile for the user or doctor accompanying the patient, and allow the patient
106 to live normally without having to count carbohydrates or even without signifying physical activity
107 (especially for brisk walking).

108 A key component of AIMI concept is to give a **small pre-bolus before each meal** (“Meal
109 Announcement” that also provides some pos. iob).

110 • A **simplified profile** composition (neutral ISF around 100, DIA 9, target 90-90, a single value for
111 basal, a ratio that is not used in AIMI, so not important) For a first basal estimate, you can use the
112 TDD / weight ratio.

113 • Some variables in preferences that are important (AIMI_UAM which allows AIMI to make
114 decisions, Max SMB size which is the highest value for an SMB, B30_duration (which is the
115 duration during which the **basal will be forced after a manual bolus**), B30_upperBG and
116 B30_Upperdelta (these last two variables represent the conditions for replacing smb with a
117 consistent TBR depending on the delta)

118 • The basal profile is calculated by a polynomial equation.

119 • The ISF is calculated from the TDD (**dynamicISF**) and is adjusted based on the evolution of TIR
120 throughout the day and the **detection of physical activity**.

121 • The detection of glycemic rise (or the opposite situation) is also calculated by a polynomial
122 equation, which will influence the change of target but also the replacement of SMB by a TBR
123 between 100% and 500% or by an SMB of the same equivalence.

124 • SMB calculation is done in several ways specific to AIMI depending on the evolution of the delta
125 and IOB, with a distribution that can be done in three parts depending on the conditions.

126 Example scenario of execution, on almost all existing variants:

- 127 1. Make a "standard" manual bolus. I usually do 1.5U or 2U with luymjev
- 128 2. Just after this bolus, AIMI will force the 500% TBR for a duration defined by the user. The
129 observation made is that the absorption of insulin such as humalog for example is acceler-
130 ated and will strongly limit the first wave.
- 131 3. Depending on the options chosen, it is possible to receive an SMB of the initial manual bo-
132 lus size after the duration of the 500% TBR
- 133 4. Then the rest of the calculations will depend on the result of a polynomial equation and its
134 evolution.
- 135 5. A few hours later, if the patient decides to take a walk to go shopping, or other activities re-
136 quiring movement, the phone sensor will send information on the number **of steps taken**.
137 This will result in a reduction of the profile to about 60%. The return of the profile to normal
138 will be done in stages, in the first half hour following the activity, the profile will be restored
139 to about 80%.

140 The AIMI developer has been working on using machine learning (using tensorflow lite).

141 **More info** <https://discord.gg/7ehczAfZ>

142 The developer hasn't kept the code public. AIMI can only be obtained as an apk via joining their
143 WhatsApp group. Given the very high number of changes happening in this AAPS variant, it is
144 probably deemed important to keep it in a tight sub-community. But, caution: This can be seen as

145 violation of the Open Source principle

146 Contact: Mathieu Tellier @ AndroidAPS User; FB/Twitter: @MTR93600

147

148 13.3.3 EatingNow (EN)

149

150 This version of AAPS has evolved over time using elements from AIMI and Boost. It includes a
151 modified dynamicISF which moves ISF modulation in the direction as pioneered by autoISF, and
152 also uses Automations for FCL.

153

154 "Eating Now" (EN) allows user definable SMB's when deltas are sufficient and accelerating.

155 The intent of this plugin is the same, to deliver insulin earlier using mostly the AAPS predictions.

156

157 As all other variants for FCL, also EatingNow requires to set glucose TT occasionally, to nudge the
158 loop in certain direction, notably to announce and be prepared for activity.

159

160 Operating Modes provide 3 levels of „aggressiveness“ in 3 time windows:

161

- 162 • Master AAPS w/up to 120 min basal per SMB when EN is off (usually set for night-time).
- 163 • EN (usually set for daytime) is when the modified algorithm is capable of boosting ISF and
164 insulin delivery. At BG level rises within the EN Window, a „UAM maxBolus“ is given as a
165 first SMB. Recommended Setting: 1h current basal in units (max allowed: 2).
- 166 • ENW: A further boosted SMB will be issued in this ENW time window (e.g. for breakfast, or
167 generally for the first meal of a day, after fasting, with higher insulin need). Upon detection
168 of rising glucose, a SMB called Breakfast COB maxBolus is given by the loop. Recom-
169 mended Setting: 25% of average breakfast total units

170

171 EN uses the dynamicISF concept, modified to making ISF stronger as and eventualBG predictions.
172 Increase.

173

174 Specifically for the ENW (usually: breakfast window), an additional boost factor called Breakfast
175 ISF/CR Percentage (e.g. 125 or 150%) can be applied

176

177 A setting „TIRS“ provides a very simple version of autoISF (dura_ISF) and sharpens ISF
178 temporarily when bg „seems stuck“ above a certain value.

179

180 Autosens sensitivityRatio will be overridden by EN sensitivity options.

181

182 SMB delivery ratio for insulinReq. Is set to 65% for when EN is disabled (overnight, usually).

183 It is recommended to set maxSMBBasalMinutes and maxUAMSMBBasalMinutes to 30 minutes

max as these will be used when EN is OFF or in SLEEP mode. Falling back on OAPS SMB settings is considered as the safe mode should you experience any issues with sensitivity or EN settings in general

It is set 85% for an active ENW, or 75% when EN is on but ENW not active

Furthermore, SMB optionally can be disabled day/night below defined bg level/s (SMB Disabled)
More info <https://discord.gg/XqhnPRChEP> (method description in pinned post)

<https://github.com/dicko72/AAPS-EatingNow> scroll down to README.md

Contact: dicko via Discord channel

13.3.4 Tsunami

The Tsunami loop algorithm analyses blood glucose and insulin activity developments to estimate bolus requirements during meals, without the necessity of carb announcements.

Users must make a **meal announcement via a button** on AAPS main screen. It switches on the main Tsunami algorithm for a finite amount of time.

In between meals (when Tsunami is inactive), users are given the choice between running a weaker version of the Tsunami algorithm (called wave), or falling back to oref1.

A “historic” merit of this method was that it pioneered a BG smoothing algorithm that later became included as a plugin in AAPS.

The insulin models dynamically readjust DIA based on bolus size so that a user-set, fixed DIA value is no longer needed.

For best results, it is recommended to issue a **bolus** at the beginning of a meal to account for the disadvantageous kinetics of subcutaneously administered insulin in a UAM setting.

More info <https://discord.gg/veRKcgwVUT> GitHub repository: <https://github.com/piecycle/tsunami> official documentation: https://cdn.discordapp.com/attachments/969948954949189633/972852790739238992/tsunami_guide_3_2.pdf

Contact: nichii#1391 on discord / piecycle on GitHub

13.4 No-Bolus Looping with Carb Entries

Some oref(1) loopers attempting to go full closed loop reported that they do best when they (do not bolus but) give their loop precise carb (and absorption time) information. This:

- * announces a meal to follow (so it is not UAM, but might be called full closed looping if the insulin management is left 100% to the loop)
- * provides data on cob, and with the glucose and insulin activity info the loop has, it can always calculate how much more carbs are to become absorbed (to the extent the carb-related infos the user put in is correct)
- * will display realistic cob info to the user, including cob info looking forward (rather than only calculating carb deviations for the past minutes or hours, and making some coarse assumptions for the upcoming hour). It gives the user better feeling of safety if she/he can see cob info in addition to the available iob info, and insulin activity prediction.

With detailed carb (amounts + absorption times) inputs, the loop has best-possible info to provide „the best expert fit“ of insulin activity and carb absorption.

It still rarely can come close to physiological values, because the time-delays inherent in our „artificial pancreas“, notably the stretched out DIA, make it difficult still, compared to a real pancreas.

So, carb inputs could help. However,

- only to the extent amounts and time pattern for absorption („eCarbs“) are correct ((which, every day, is a mission impossible))
- the oref(1) loop still largely „waits for glucose to rise“, and there is no significant time advantage from inputting carb info

Only the **user**-bolussing for **expected** carb absorption in hybrid closed loop offers a convincing time advantage (but with associated risks).

- inputs require actually more attention to detail than it is good practice even in AndroidAPS hybrid closed loop, so in that respect a step back, not forward.

Entering **precise** carb information takes away a very large part of the attractivity of full closed looping.

And entering *imprecise* carb info could easy be inferior to not doing *any* carb inputs = to letting the *UAM mode* of oref(1) figure out further carbs that probably come to be absorbed in the next minutes, judging from the pattern of the calculated past *carb deviations* (see section 4.5 and

256 <https://openaps.readthedocs.io/en/latest/docs/While%20You%20Wait%20For%20Gear/Understand>
257 [-determine-basal.html#understanding-the-basic-logic-written-version](https://openaps.readthedocs.io/en/latest/docs/While%20You%20Wait%20For%20Gear/Understand)).

258 PS: Because that is so, also loopers who do carb inputs get the UAM predictions besides their
259 other predictions, and their algo makes a judgement (every 5 minutes) as to what the best
260 calculation might be for where glucose, underlying „real“ carb absorption, and estimated carb
261 deviation are headed.

262

263 13.5 Machine Learning

264

265 Involving machine learning (“artificial intelligence”) could help both in the learning/tuning phase, but
266 also in fine adjustments in daily utilization.

267 The study that was already referenced in [section 1](#) discusses *on page 80* the application of
268 machine learning in some predictions of postprandial glucose response (IEEE Control Systems
269 Magazine, ResearchGate: The Artificial Pancreas and Meal Control. A. El Fathi et al, IEEE Control
270 Systems Magazine Feb.2018 p.67-85.).

271 So there is already a body of data and evidence. To which extent it lends itself to UAM remains to
272 be researched. For this, a body of data would have to be captured from UAM loopers, and I fear
273 many more data would be required than what could easily be captured in Clarity® or even in the
274 OPEN project database.

275

276 In the DIY universe, a prototype solution was already developed for AIMI ([section 13.3.3](#)).

277

278 We might see industry come up with a 1st generation solution that will probably be geared to folks
279 with miserable HbA1c and poor carb counting/meal handling, to offer a safe gradual improvement.

280

281 A top performing entirely self-learning system might be impossible to design:

282 For instance, if today you do something entirely different from yesterday (don’t we all want this
283 freedom – even need it? Think about the fasting day following a feasting day...) there are
284 two problems:

- 285 • Such systems rely on information from the preceding day, or an average of several preced-
286 ing days
- 287 • The user does not know/learn much about how the system works, what it is calibrated for
288 today, how she/he might intelligently change something for the specific different situation
289 coming up. This seems like the opposite of the FCL solutions we discussed, for instance
290 self-defined Automations, combined with profile switches for to-be-expected temporary sen-
291 sitivity shifts. ([section 13.1](#).)

292

293

13.6 Dual Hormone Systems

Many see a dual hormone “double full loop” as the ultimate system.

The beauty of this concept would be that the second pump could influence the glucose curve via giving glucagon or an analogue, thus overcoming the strongest limitation our current systems have:

Taking basal away (zero-temping) is only a severely limited course of action against impending hypoglycemia, and therefore, to keep things safe at the back-end of each meal, fighting glucose highs is more limited than we would like to see.

In conclusion, the glucagon component not only helps stay out of hypos. It enables a more aggressive treatment for preventing, or reducing, high glucose values, as well.

While insulin and carbs have complex activity curves stretching over hours, glucagon has a window of physiological activity starting 5-10 minutes after administration, and lasting only 30-40 minutes. Compared to insulin and carbs, that makes it a better component for rapid corrections (without a lengthy “tail” of action).

As glucagon does not per se introduce more calories, but stimulates glucose release from the liver, there should at least be no concern about gaining body weight from eventual roller-coasters the dual loop might send us into. Actually there could be a nice side benefit of helping in body weight control. Also, activity/sports management could become as easy as the meal management became in the UAM step into full closed looping.

It will be interesting to see for which application(s) the dual loop will be developed and launched; as part of a full closed loop with top performance, or as part of even only a hybrid closed loop for problem patients?

It remains to be seen how well such systems work in day-to-day circumstances. And whether “real people” will be able to handle all the involved technology, and use it in ways that truly could justify the substantial extra cost.

The author currently is not really looking forward to become loaded with even more technology, and quite happy with an aggressively tuned full UAM closed loop (...and an occasional nice post-dinner or during- activity snack).

331 However, the dual hormone path holds enough promise to learn more about it, and to test it some
332 time in the near future.
333
334 This is an exciting time to be part of the open source T1D community. Anyone is welcome to
335 contribute ideas, help develop software or instructions how to use. Carefully weigh for yourself
336 what may be your entry point for eventually surmounting the initial hurdles, and **JUST EAT happily**
337 **ever after.**
338