InterSystems CACHÉ®

Caché Switches

Version 2009.1
30 June 2009

Caché Switches
Caché   Version 2009.1   30 June 2009
Copyright © 2009 InterSystems Corporation
All rights reserved.

This book was assembled and formatted in Adobe Page Description Format (PDF) using tools and information from the following sources: Sun Microsystems, RenderX, Inc., Adobe Systems, and the World Wide Web Consortium at www.w3c.org. The primary document development tools were special-purpose XML-processing applications built by InterSystems using Caché and Java.

InterSystems CACHÉ and **InterSystems ENSEMBLE**

Caché WEBLINK, Distributed Cache Protocol, M/SQL, M/NET, and M/PACT are registered trademarks of InterSystems Corporation.

INTERSYSTEMS, InterSystems HEALTHSHARE, InterSystems DEEPSEE and **InterSystems TRAKCARE**

InterSystems Jalapeño Technology, Enterprise Cache Protocol, ECP, and InterSystems Zen are trademarks of InterSystems Corporation.

All other brand or product names used herein are trademarks or registered trademarks of their respective companies or organizations.

For Support questions about any InterSystems products, contact:

InterSystems Worldwide Customer Support

Tel:	+1 617 621-0700
Fax:	+1 617 374-9391
Email:	support@InterSystems.com

Table of Contents

Caché Switches

Background

Switches in Caché have their genesis in the physical contacts once part of computer operator consoles or included in the front panel of microcomputers. By setting one of these switches, an operator could convey a single bit of information to the programs running on the machine at that time. Since Caché implements a "virtual machine", the concept of the switch for this machine has been similarly abstracted.

Today, switches in Caché are represented as individual bit settings in the shared, common memory of a Caché instance; they are visible to all Caché processes. While several have been set aside for users, most influence the operation of Caché itself.

1 Currently Defined Switches

All switches are identified by number. They are initialized to zero (off) when Caché starts. The following table gives the switch number(s) and their effect:

Switch	Meaning / Use
0 — 7	Reserved for use by applications programs.
8	Inhibits existing Caché daemons from responding to network requests.
9	Inhibits the creation of new daemons to process network logins.
10	Inhibit all global access except by the process that sets this switch. Also inhibit routine accesses that causes disk IO except for this process.
11	Inhibit all global access except for the system job that sets this switch. This overrides switch 10 and is reserved for use by the system. This switch is set, for example, by the backup process to quiesce system activity before copying.
12	Inhibits the ability to login to Caché. Users who attempting to login will receive a message: "Sign-on and JOB inhibited: Switch 12 is set".
13	Inhibits all global SETs, KILLs and ZSAVE commands; only read access is allowed to globals and routines.
14	Inhibits all access to all globals and all routines.

Switch	Meaning / Use
15	Allow network references from peers, even if switch 10,13, or 14 would normally prevent the access.
16	Used internally by Caché to coordinate shutdown activity.
17	Bypass wait for completion of journal flush on clusters.
18	Inhibits pausing added processes if the queue for a block gets too long.
19	Inhibit the start of new transactions.
20 — 31	Undefined and reserved for InterSystems use.

CAUTION: Unless specifically directed to do so by InterSystems personnel or its documented procedures, customers should confine any switch activity by their applications to the set reserved for their use, 0 — 7.

2 Manipulating Switches

The **^SWSET** routine is used to directly manipulate the values of the switches. In addition, other Caché facilities, such as those that work with journals on clustered systems and system backup, also set them on behalf of their callers.

SWSET

```
SWSET
```

Parameters

None.

Description

This provides an interactive way to set the value of the switches from, for example, a terminal session.

Remarks

When invoked as in the example below, the routine will prompt for the switch number and then prompt for the value to be set in the switch (0 or 1).

Examples

The following example demonstrates the use of **SWSET** . After executing

```
DO ^SWSET
```

the user will successively see the following:

```
Set/Clear switch #:
Set/Clear switch #: 2
Set/Clear switch #: 2 to value (0 or 1):
Set/Clear switch #: 2 to value (0 or 1): 1
Set/Clear switch #: 2 to value (0 or 1): 1...done
```

%swstat^SWSET

```
%swstat^SWSET(switch)
```

Parameters

switch	The number of the switch.

Description

This function returns the current setting for the switch.

Parameters

switch

The number of a valid switch.

Remarks

If the switch is a valid number, this function returns the value of the switch as one of the following:

- 0 — the switch is reset (off)
- 1 — the switch is set (on)

otherwise it returns a value of –1 indicating that an error has occurred.

Examples

The following example prints the value of switch number 1.

```
Write $$%swstat^SWSET(1)
```

%swset^SWSET

```
%swset^SWSET(switch, value)
```

Parameters

switch	The number of the switch.
value	The value it should have, 0 or 1.

Description

This function sets the switch to the specified value.

Parameters

switch

The number of a valid switch.

value

The value 0 or 1.

Remarks

If the switch is a valid number and value is either a 0 or 1, this function sets the switch to that value and returns:

- 0 — the switch is now reset (off)

- 1 — the switch is now set (on)

otherwise it returns a value of –1 indicating that an error has occurred.

Examples

The following example sets the value of switch number 1 to off.

```
Write $$%swset^SWSET(1, 0)
```

3 Other Considerations

3.1 Locality

As noted in the introduction, users should view the switches as being local to a Caché instance. Although Caché itself provides mechanisms to propagate the meaning of certain settings to other members of a cluster or ECP configuration, these are for InterSystems internal use only. The values of the user switches cannot be moved to other systems.

3.2 Failure Modes

A Caché process which sets one of the system-reserved switches and terminates without properly cleaning up its work can leave the system in a restricted operating mode. For example, a process that sets switch 12 and then suffers a catastrophic failure (or even merely HALTs) will leave Caché in a state where no further users can login. If this situation occurs, the administrator or operator is urged to call the InterSystems Worldwide Response Center.

Note: The only situation for which Caché implements an automatic recovery is for switch 10. If a process sets this switch and then HALTs, Caché will automatically reset the switch to zero.